

Package ‘spiderbar’

November 17, 2017

Type Package

Title Parse and Test Robots Exclusion Protocol Files and Rules

Version 0.2.1

Date 2017-11-17

Author Bob Rudis (bob@rud.is) [aut, cre], SEOmoz, Inc [aut]

Maintainer Bob Rudis <bob@rud.is>

Description The 'Robots Exclusion Protocol' <<http://www.robotstxt.org/orig.html>> documents a set of standards for allowing or excluding robot/spider crawling of different areas of site content. Tools are provided which wrap The 'rep-cpp' <<https://github.com/seomoz/rep-cpp>> C++ library for processing these 'robots.txt' files.

SystemRequirements C++11

NeedsCompilation yes

URL <https://github.com/hrbrmstr/spiderbar>

BugReports <https://github.com/hrbrmstr/spiderbar/issues>

License MIT + file LICENSE

Suggests testthat, covr, robotstxt

Depends R (>= 3.2.0)

Imports Rcpp

RoxygenNote 6.0.1

LinkingTo Rcpp

Repository CRAN

Date/Publication 2017-11-17 12:40:19 UTC

R topics documented:

can_fetch	2
crawl_delays	2
robxp	3
sitemaps	4
spiderbar	4

Index**5**

can_fetch	<i>Test URL paths against a robxp robots.txt object</i>
-----------	---

Description

Provide a character vector of URL paths plus optional user agent and this function will return a logical vector indicating whether you have permission to fetch the content at the respective path.

Usage

```
can_fetch(obj, path = "/", user_agent = "*")
```

Arguments

obj	robxp object
path	path to test
user_agent	user agent to test

Examples

```
gh <- paste0(readLines(system.file("extdata", "github-robots.txt",
  package="spiderbar")), collapse="\n")
gh_rt <- robxp(gh)

can_fetch(gh_rt, "/humans.txt", "*") # TRUE
can_fetch(gh_rt, "/login", "*") # FALSE
can_fetch(gh_rt, "/oembed", "CCBot") # FALSE

can_fetch(gh_rt, c("/humans.txt", "/login", "/oembed"))
```

crawl_delays	<i>Retrieve all agent crawl delay values in a robxp robots.txt object</i>
--------------	---

Description

Retrieve all agent crawl delay values in a robxp robots.txt object

Usage

```
crawl_delays(obj)
```

Arguments

obj	robxp object
-----	--------------

Value

data frame of agents and their crawl delays

Note

-1 will be returned for any listed agent *without* a crawl delay setting

Examples

```
gh <- paste0(readLines(system.file("extdata", "github-robots.txt",
                                package="spiderbar")), collapse="\n")
gh_rt <- robxp(gh)
crawl_delays(gh_rt)

imdb <- paste0(readLines(system.file("extdata", "imdb-robots.txt",
                                package="spiderbar")), collapse="\n")
imdb_rt <- robxp(imdb)
crawl_delays(imdb_rt)
```

robxp

Parse a 'robots.txt' file & create a 'robxp' object

Description

This function takes in a single element character vector and parses it into a 'robxp' object.

Usage

```
robxp(x)
```

Arguments

x either an atomic character vector containing a complete 'robots.txt' file *_or_* a length >1 character vector that will be concatenated into a single string *_or_* a 'connection' object that will be passed to [readLines()], the result of which will be concatenated into a single string and parsed and the connection will be closed.

Examples

```
imdb <- paste0(readLines(system.file("extdata", "imdb-robots.txt",
                                package="spiderbar")), collapse="\n")
rt <- robxp(imdb)
```

sitemaps

Retrieve a character vector of sitemaps from a parsed robots.txt object

Description

Retrieve a character vector of sitemaps from a parsed robots.txt object

Usage

```
sitemaps(xp)
```

Arguments

xp A robxp object

Value

character vector of all sitemaps found in the parsed robots.txt file

Examples

```
imdb <- paste0(readLines(system.file("extdata", "imdb-robots.txt",  
                                   package="rep")), collapse="\n")  
rt <- robxp(imdb)  
sitemaps(rt)
```

spiderbar*Parse and Test Robots Exclusion Protocol Files and Rules*

Description

The 'Robots Exclusion Protocol' (<http://www.robotstxt.org/orig.html>) documents a set of standards for allowing or excluding robot/spider crawling of different areas of site content. Tools are provided which wrap The rep-cpp <https://github.com/seomoz/rep-cpp> C++ library for processing these 'robots.txt' files.

Author(s)

Bob Rudis (bob@rud.is)

Index

[can_fetch](#), 2

[crawl_delays](#), 2

[robxp](#), 3

[sitemaps](#), 4

[spiderbar](#), 4

[spiderbar-package \(spiderbar\)](#), 4