

Package ‘diffdf’

January 9, 2019

Type Package

Title Dataframe Difference Tool

Version 1.0.2

Description Functions for comparing two data.frames against each other. The core functionality is to provide a detailed breakdown of any differences between two data.frames as well as providing utility functions to help narrow down the source of problems and differences.

Encoding UTF-8

LazyData true

Depends R (>= 3.1.2)

Imports tibble

Suggests testthat, lubridate, knitr, rmarkdown, purrr, dplyr, stringi, stringr, devtools, covr

RoxygenNote 6.1.1

VignetteBuilder knitr

License MIT + file LICENSE

URL <https://github.com/gowerc/diffdf>

BugReports <https://github.com/gowerc/diffdf/issues>

NeedsCompilation no

Author Craig Gower [cre, aut],
Kieran Martin [aut]

Maintainer Craig Gower <craig.gower@roche.com>

Repository CRAN

Date/Publication 2019-01-09 09:40:02 UTC

R topics documented:

as_ascii_table	3
as_cropped_char	3

cast_variables	4
class_merge	4
compare_vectors	5
compare_vectors.default	5
compare_vectors.factor	6
compare_vectors.numeric	6
construct_issue	7
convert_to_issue	7
diffdf	8
diffdf_has_issues	9
diffdf_issuerows	10
factor_to_character	11
find_difference	11
generate_keyname	12
get_casted_dataset	12
get_casted_vector	13
get_issue_dataset	13
get_issue_message	14
get_print_message	14
get_print_message.default	15
get_print_message.issue	15
get_table	16
has_unique_rows	16
identify_att_differences	17
identify_class_differences	17
identify_differences	18
identify_extra_cols	18
identify_extra_rows	19
identify_matching_cols	19
identify_mode_differences	20
identify_properties	20
identify_unsupported_cols	21
invert	21
is_variable_different	21
print.diffdf	22
recursive_reduce	23
sort_then_join	23
string_pad	24

as_ascii_table	<i>as_ascii_table</i>
----------------	-----------------------

Description

This function takes a data.frame and attempts to convert it into a simple ascii format suitable for printing to the screen. It is assumed all variable values have a as.character() method in order to cast them to character.

Usage

```
as_ascii_table(dat, line_prefix = " ")
```

Arguments

dat	Input dataset to convert into a ascii table
line_prefix	Symbols to prefix in front of every line of the table

as_cropped_char	<i>as_cropped_char</i>
-----------------	------------------------

Description

Makes any character string above x chars. Reduce down to a x char string with ...

Usage

```
as_cropped_char(inval, crop_at = 30)
```

Arguments

inval	a single element value
crop_at	character limit

cast_variables *cast_variables*

Description

Function to cast datasets columns if they have differing types Restricted to specific cases, currently integer and double, and character and factor

Usage

```
cast_variables(BASE, COMPARE, ignore_vars = NULL,  
              cast_integers = FALSE, cast_factors = FALSE)
```

Arguments

BASE	base dataset
COMPARE	comparison dataset
ignore_vars	Variables not to be considered for casting
cast_integers	Logical - Whether integers should be cased to double when compared to doubles
cast_factors	Logical - Whether characters should be cased to characters when compared to characters

class_merge *class_merge*

Description

Convenience function to put all classes an object has into one string

Usage

```
class_merge(x)
```

Arguments

x	an object
---	-----------

compare_vectors	<i>compare_vectors</i>
-----------------	------------------------

Description

Compare two vectors looking for differences

Usage

```
compare_vectors(target, current, ...)
```

Arguments

target	the base vector
current	a vector to compare target to
...	Additional arguments which might be passed through (numerical accuracy)

compare_vectors.default	<i>compare_vectors.default</i>
-------------------------	--------------------------------

Description

Default method, if the vector is not numeric or factor. Basic comparison

Usage

```
## Default S3 method:  
compare_vectors(target, current, ...)
```

Arguments

target	the base vector
current	a vector to compare target to
...	Additional arguments which might be passed through (numerical accuracy)

```
compare_vectors.factor
```

```
compare_vectors.factor
```

Description

Compares factors. Sets them as character and then compares

Usage

```
## S3 method for class 'factor'
compare_vectors(target, current, ...)
```

Arguments

target	the base vector
current	a vector to compare target to
...	Additional arguments which might be passed through (numerical accuracy)

```
compare_vectors.numeric
```

```
compare_vectors.numeric
```

Description

This is a modified version of the all.equal function which returns a vector rather than a message

Usage

```
## S3 method for class 'numeric'
compare_vectors(target, current,
  tolerance = sqrt(.Machine$double.eps), scale = NULL)
```

Arguments

target	the base vector
current	a vector to compare target to
tolerance	Level of tolerance for differences between two variables
scale	Scale that tolerance should be set on. If NULL assume absolute

construct_issue	<i>construct_issue</i>
-----------------	------------------------

Description

Make an s3 object with class issue and possible additional class, and assign other arguments to attributes

Usage

```
construct_issue(value, message, add_class = NULL)
```

Arguments

value	the value of the object
message	the value of the message attribute
add_class	additional class to add

convert_to_issue	<i>convert_to_issue</i>
------------------	-------------------------

Description

converts the count value into the correct issue format

Usage

```
convert_to_issue(datin)
```

Arguments

datin	data inputted
-------	---------------

diffdf	<i>diffdf</i>
--------	---------------

Description

Compares 2 dataframes and outputs any differences.

Usage

```
diffdf(base, compare, keys = NULL, suppress_warnings = FALSE,
       strict_numeric = TRUE, strict_factor = TRUE, file = NULL,
       tolerance = sqrt(.Machine$double.eps), scale = NULL)
```

Arguments

base	input dataframe
compare	comparison dataframe
keys	vector of variables (as strings) that defines a unique row in the base and compare dataframes
suppress_warnings	Do you want to suppress warnings? (logical)
strict_numeric	Flag for strict numeric to numeric comparisons (default = TRUE). If False diffdf will cast integer to double where required for comparisons. Note that variables specified in the keys will never be casted.
strict_factor	Flag for strict factor to character comparisons (default = TRUE). If False diffdf will cast factors to characters where required for comparisons. Note that variables specified in the keys will never be casted.
file	Location and name of a text file to output the results to. Setting to NULL will cause no file to be produced.
tolerance	Set tolerance for numeric comparisons. Note that comparisons fail if $(x-y)/scale > tolerance$.
scale	Set scale for numeric comparisons. Note that comparisons fail if $(x-y)/scale > tolerance$. Setting as NULL is a slightly more efficient version of $scale = 1$.

Examples

```
x <- subset( iris, ~Species)
x[1,2] <- 5
COMPARE <- diffdf( iris, x)
print( COMPARE )
print( COMPARE , "Sepal.Length" )

#### Sample data frames

DF1 <- data.frame(
  id = c(1,2,3,4,5,6),
```



```

    v1 = letters[1:6],
    v2 = c(NA , NA , 1 , 2 , 3 , NA)
  )

DF2 <- data.frame(
  id = c(1,2,3,4,5,7),
  v1 = letters[1:6],
  v2 = c(NA , NA , 1 , 2 , NA , NA),
  v3 = c(NA , NA , 1 , 2 , NA , 4)
)

diffdf(DF1 , DF1 , keys = "id")

# We can control matching with scale/location for example:

DF1 <- data.frame(
  id = c(1,2,3,4,5,6),
  v1 = letters[1:6],
  v2 = c(1,2,3,4,5,6)
)
DF2 <- data.frame(
  id = c(1,2,3,4,5,6),
  v1 = letters[1:6],
  v2 = c(1.1,2,3,4,5,6)
)

diffdf(DF1 , DF2 , keys = "id")
diffdf(DF1 , DF2 , keys = "id", tolerance = 0.2)
diffdf(DF1 , DF2 , keys = "id", scale = 10, tolerance = 0.2)

# We can use strict_factor to compare factors with characters for example:

DF1 <- data.frame(
  id = c(1,2,3,4,5,6),
  v1 = letters[1:6],
  v2 = c(NA , NA , 1 , 2 , 3 , NA),
  stringsAsFactors = FALSE
)
DF2 <- data.frame(
  id = c(1,2,3,4,5,6),
  v1 = letters[1:6],
  v2 = c(NA , NA , 1 , 2 , 3 , NA)
)

diffdf(DF1 , DF2 , keys = "id", strict_factor = TRUE)
diffdf(DF1 , DF2 , keys = "id", strict_factor = FALSE)

```

Description

Utility function which returns TRUE if an diffdf object has issues or FALSE if an diffdf object does not have issues

Usage

```
diffdf_has_issues(x)
```

Arguments

x diffdf object

Examples

```
# Example with no issues
x <- diffdf( iris, iris )
diffdf_has_issues(x)

# Example with issues
iris2 <- iris
iris2[2,2] <- NA
x <- diffdf( iris , iris2 , suppress_warnings = TRUE)
diffdf_has_issues(x)
```

diffdf_issuerows *diffdf_issuerows*

Description

This function takes a diffdf object and a dataframe and subsets the dataframe for problem rows as identified in the comparison object. If vars has been specified only issue rows associated with those variable(s) will be returned.

Usage

```
diffdf_issuerows(df, diff, vars = NULL)
```

Arguments

df dataframe to be subsetted

diff diffdf object

vars (optional) character vector containing names of issue variables to subset dataframe on. A value of NULL (default) will be taken to mean available issue variables.

Details

Note that `diffdf_issuerows` can be used to subset against any dataframe. The only requirement is that the original variables specified in the `keys` argument to `diffdf` are present on the dataframe you are subsetting against. However please note that if no keys were specified in `diffdf` then the row number is used. This means using `diffdf_issuerows` without a `keys` against an arbitrary dataset can easily result in nonsense rows being returned. It is always recommended to supply keys to `diffdf`.

Examples

```
iris2 <- iris
for ( i in 1:3) iris2[i,i] <- 99
x <- diffdf( iris , iris2, suppress_warnings = TRUE)
diffdf_issuerows( iris , x)
diffdf_issuerows( iris2 , x)
diffdf_issuerows( iris2 , x , vars = "Sepal.Length")
diffdf_issuerows( iris2 , x , vars = c("Sepal.Length" , "Sepal.Width"))
```

factor_to_character *factor_to_character*

Description

Takes a dataframe and converts any factor variables to character

Usage

```
factor_to_character(dsin, vars = NULL)
```

Arguments

<code>dsin</code>	input dataframe
<code>vars</code>	variables to consider for conversion. Default NULL will consider every variable within the dataset

find_difference *find_difference*

Description

This determines if two vectors are different. It expects vectors of the same length and type, and is intended to be used after checks have already been done Initially picks out any nas (matching nas count as a match) Then compares remaining vector

Usage

```
find_difference(target, current, ...)
```

Arguments

target	the base vector
current	a vector to compare target to
...	Additional arguments which might be passed through (numerical accuracy)

generate_keyname	<i>generate_keyname</i>
------------------	-------------------------

Description

Function to generate a name for the keys if not provided

Usage

```
generate_keyname(BASE, COMP, replace_names = c("..ROWNUMBER..", "..RN..",
"..ROWN..", "..N.."))
```

Arguments

BASE	base dataset
COMP	comparison dataset
replace_names	a vector of replacement names. Used for recursion, should be edited in function for clarity

get_casted_dataset	<i>get_casted_dataset</i>
--------------------	---------------------------

Description

Internal utility function to loop across a dataset casting all target variables

Usage

```
get_casted_dataset(df, columns, whichdat)
```

Arguments

df	dataset to be casted
columns	columns to be casted
whichdat	whether base or compare is being casted (used for messages)

get_casted_vector *get_casted_vector*

Description

casts a vector depending on its type and input

Usage

```
get_casted_vector(colin, colname, whichdat)
```

Arguments

colin	column to cast
colname	name of vector
whichdat	whether base or compare is being casted (used for messages)

get_issue_dataset *get_issue_dataset*

Description

Internal function used by `diffdf_issuerows` to extract the dataframe from each a target issue. In particular it also strips off any non-key variables

Usage

```
get_issue_dataset(issue, diff)
```

Arguments

issue	name of issue to extract the dataset from diff
diff	diffdf object which contains issues

`get_issue_message` *get_issue_message*

Description

Simple function to grab the issue message

Usage

`get_issue_message(object, ...)`

Arguments

`object` inputted object of class issue
`...` other arguments

`get_print_message` *get_print_message*

Description

Get the required text depending on type of issue

Usage

`get_print_message(object, ...)`

Arguments

`object` inputted object of class issue
`...` other arguments

```
get_print_message.default  
    get_print_message.default
```

Description

Errors, as this should only ever be given an issue

Usage

```
## Default S3 method:  
get_print_message(object)
```

Arguments

object issue

```
get_print_message.issue  
    get_print_message.issue
```

Description

Get text from a basic issue, based on the class of the value of the issue

Usage

```
## S3 method for class 'issue'  
get_print_message(object)
```

Arguments

object an object of class issue_basic

<code>get_table</code>	<i>get_table</i>
------------------------	------------------

Description

Generate nice looking table from a data frame

Usage

```
get_table(dsin, row_limit = 10)
```

Arguments

<code>dsin</code>	dataset
<code>row_limit</code>	Maximum number of rows displayed in dataset

<code>has_unique_rows</code>	<i>has_unique_rows</i>
------------------------------	------------------------

Description

Check if a data sets rows are unique

Usage

```
has_unique_rows(DAT, KEYS)
```

Arguments

<code>DAT</code>	input data set (data frame)
<code>KEYS</code>	Set of keys which should be unique

```
identify_att_differences  
    identify_att_differences
```

Description

Identifies any attribute differences between two data frames

Usage

```
identify_att_differences(BASE, COMP, exclude_cols = "")
```

Arguments

BASE	Base dataset for comparison (data.frame)
COMP	Comparator dataset to compare base against (data.frame)
exclude_cols	Columns to exclude from comparison

```
identify_class_differences  
    identify_class_differences
```

Description

Identifies any class differences between two data frames

Usage

```
identify_class_differences(BASE, COMP)
```

Arguments

BASE	Base dataset for comparison (data.frame)
COMP	Comparator dataset to compare base against (data.frame)

identify_differences *identify_differences*

Description

Compares each column within 2 datasets to identify any values which they mismatch on.

Usage

```
identify_differences(BASE, COMP, KEYS, exclude_cols,
  tolerance = sqrt(.Machine$double.eps), scale = NULL)
```

Arguments

BASE	Base dataset for comparison (data.frame)
COMP	Comparator dataset to compare base against (data.frame)
KEYS	List of variables that define a unique row within the datasets (strings)
exclude_cols	Columns to exclude from comparison
tolerance	Level of tolerance for numeric differences between two variables
scale	Scale that tolerance should be set on. If NULL assume absolute

identify_extra_cols *identify_extra_cols*

Description

Identifies columns that are in a baseline dataset but not in a comparator dataset

Usage

```
identify_extra_cols(DS1, DS2)
```

Arguments

DS1	Baseline dataset (data frame)
DS2	Comparator dataset (data frame)

identify_extra_rows *identify_extra_rows*

Description

Identifies rows that are in a baseline dataset but not in a comparator dataset

Usage

```
identify_extra_rows(DS1, DS2, KEYS)
```

Arguments

DS1	Baseline dataset (data frame)
DS2	Comparator dataset (data frame)
KEYS	List of variables that define a unique row within the datasets (strings)

identify_matching_cols
identify_matching_cols

Description

Identifies columns with the same name in two data frames

Usage

```
identify_matching_cols(DS1, DS2, EXCLUDE = "")
```

Arguments

DS1	Input dataset 1 (data frame)
DS2	Input dataset 2 (data frame)
EXCLUDE	Columns to ignore

identify_mode_differences
identify_mode_differences

Description

Identifies any mode differences between two data frames

Usage

```
identify_mode_differences(BASE, COMP)
```

Arguments

BASE	Base dataset for comparison (data.frame)
COMP	Comparator dataset to compare base against (data.frame)

identify_properties *identify_properties*

Description

Returns a dataframe of metadata for a given dataset. Returned values include variable names , class , mode , type & attributes

Usage

```
identify_properties(dsin)
```

Arguments

dsin	input dataframe that you want to get the metadata from
------	--

```
identify_unsupported_cols  
  identify_unsupported_cols
```

Description

Identifies any columns for which the package is not setup to handle

Usage

```
identify_unsupported_cols(dsin)
```

Arguments

dsin	input dataset
------	---------------

invert	<i>invert</i>
--------	---------------

Description

Utility function used to replicated purrr::transpose. Turns a list inside out.

Usage

```
invert(x)
```

Arguments

x	list
---	------

```
is_variable_different  is_variable_different
```

Description

This subsets the data set on the variable name, picks out differences and returns a tibble of differences for the given variable

Usage

```
is_variable_different(variablename, keynames, datain, ...)
```

Arguments

variablename	name of variable being compared
keynames	name of keys
datain	Inputted dataset with base and compare vectors
...	Additional arguments which might be passed through (numerical accuracy)

Value

A boolean vector which is T if target and current are different

print.diffdf	<i>Print diffdf objects</i>
--------------	-----------------------------

Description

Print nicely formatted version of an diffdf object

Usage

```
## S3 method for class 'diffdf'
print(x, ..., as_string = FALSE)
```

Arguments

x	comparison object created by diffdf().
...	Additional arguments (not used)
as_string	Return printed message as an R character vector?

Examples

```
x <- subset( iris , -Species )
x[1,2] <- 5
COMPARE <- diffdf( iris, x)
print( COMPARE )
print( COMPARE , "Sepal.Length" )
```

recursive_reduce	<i>recursive_reduce</i> Utility function used to replicated <code>purrr::reduce</code> . Recursively applies a function to a list of elements until only 1 element remains
------------------	--

Description

recursive_reduce

Utility function used to replicated `purrr::reduce`. Recursively applies a function to a list of elements until only 1 element remains

Usage

```
recursive_reduce(.l, .f)
```

Arguments

<code>.l</code>	list of values to apply a function to
<code>.f</code>	function to apply to each element of the list in turn i.e. <code>.[[1]] <- .f(.[[1]], .[[2]])</code> ; <code>.[[1]] <- .f(.[[1]], .[[3]])</code>

sort_then_join	<i>sort_then_join</i>
----------------	-----------------------

Description

Convenience function to sort two strings and paste them together

Usage

```
sort_then_join(string1, string2)
```

Arguments

<code>string1</code>	first string
<code>string2</code>	second string

string_pad	<i>string_pad</i> Utility function used to replicate <i>str_pad</i> . Adds white space to either end of a string to get it to equal the desired length
------------	--

Description

string_pad

Utility function used to replicate *str_pad*. Adds white space to either end of a string to get it to equal the desired length

Usage

```
string_pad(x, width)
```

Arguments

x	string
width	desired length

Index

as_ascii_table, 3
as_cropped_char, 3

cast_variables, 4
class_merge, 4
compare_vectors, 5
compare_vectors.default, 5
compare_vectors.factor, 6
compare_vectors.numeric, 6
construct_issue, 7
convert_to_issue, 7

diffdf, 8
diffdf_has_issues, 9
diffdf_issuerows, 10

factor_to_character, 11
find_difference, 11

generate_keyname, 12
get_casted_dataset, 12
get_casted_vector, 13
get_issue_dataset, 13
get_issue_message, 14
get_print_message, 14
get_print_message.default, 15
get_print_message.issue, 15
get_table, 16

has_unique_rows, 16

identify_att_differences, 17
identify_class_differences, 17
identify_differences, 18
identify_extra_cols, 18
identify_extra_rows, 19
identify_matching_cols, 19
identify_mode_differences, 20
identify_properties, 20
identify_unsupported_cols, 21
invert, 21

is_variable_different, 21

print.diffdf, 22

recursive_reduce, 23

sort_then_join, 23
string_pad, 24