

# Package ‘dynprog’

March 27, 2018

**Version** 0.1.0

**Title** Dynamic Programming Domain-Specific Language

**Description** A domain-specific language for specifying translating recursions into dynamic-programming algorithms. See [https://en.wikipedia.org/wiki/Dynamic\\_programming](https://en.wikipedia.org/wiki/Dynamic_programming) for a description of dynamic programming.

**License** GPL-3

**Encoding** UTF-8

**LazyData** true

**ByteCompile** true

**Imports** rlang (>= 0.1.2)

**Suggests** covr, testthat

**RoxygenNote** 6.0.1

**URL** <https://github.com/mailund/dynprog>

**BugReports** <https://github.com/mailund/dynprog/issues>

**NeedsCompilation** no

**Author** Thomas Mailund [aut, cre]

**Maintainer** Thomas Mailund <mailund@birc.au.dk>

**Repository** CRAN

**Date/Publication** 2018-03-27 19:15:50 UTC

## R topics documented:

eval_recursion . . . . .	2
get_table_name . . . . .	2
make_condition_checks . . . . .	3
make_pattern_match . . . . .	3
make_pattern_tests . . . . .	4
make_recursion_case . . . . .	4
make_update_expr . . . . .	5

parse_ranges . . . . .	5
parse_recursion . . . . .	6
%where% . . . . .	6

<b>Index</b>	<b>8</b>
--------------	----------

---

eval_recursion	<i>Evaluate an entire dynprog recursion.</i>
----------------	--

---

### Description

This function takes the ranges and recursions of a specification and evaluate the dynprog expression, returning a filled out dynamic programming table.

### Usage

```
eval_recursion(ranges, recursions)
```

### Arguments

ranges	The ranges specification
recursions	The recursions specification

### Value

The filled out dynamic programming table

---

get_table_name	<i>Extract the table name from a pattern.</i>
----------------	---

---

### Description

We generally assume that patterns are on the form table[exprs] where table is the name of the dynamic programming table. This function extract that name.

### Usage

```
get_table_name(patterns)
```

### Arguments

patterns	The patterns used in the recursion.
----------	-------------------------------------

### Value

The table part of the pattern.

---

make\_condition\_checks *Translate condition expressions into calls that test them.*

---

**Description**

Takes the full dynprog expression and construct a list of condition tests for each component of the recursion.

**Usage**

```
make_condition_checks(ranges, patterns, conditions, recursions)
```

**Arguments**

ranges	The ranges specifications
patterns	The patterns specifications
conditions	The conditions specifications
recursions	The recursions specification

**Value**

A list of calls, one per recursion, for testing conditions.

---

make\_pattern\_match *Translate a pattern into a predicate that checks the pattern.*

---

**Description**

Takes a pattern from the DSL and make a comparison of the pattern specification against range variables.

**Usage**

```
make_pattern_match(pattern, range_vars)
```

**Arguments**

pattern	An expression on the form table[index-list]
range_vars	A list of the variables used in the ranges.

**Value**

An expression that tests pattern against range\_vars.

---

make\_pattern\_tests     *Make pattern tests for all patterns.*

---

### Description

This function calls `make_pattern_match()` for each pattern in `patterns` and return a list of all the pattern test expressions.

### Usage

```
make_pattern_tests(patterns, range_vars)
```

### Arguments

`patterns`             A list of the patterns used in a recursion.  
`range_vars`            The variables used in the ranges.

### Value

A list of pattern check expressions.

---

make\_recursion\_case     *Construct a test for a case in the recursion*

---

### Description

This function creates an if-statement for testing if a case can be applied.

### Usage

```
make_recursion_case(test_expr, value_expr, continue)
```

### Arguments

`test_expr`             The expression that must be true for the case to be applied  
`value_expr`            The value to compute if the test is true  
`continue`             The next case to check if this one isn't true

### Value

An if-statement for checking and potentially evaluating one case.

---

make_update_expr	<i>String together the case if-statements of a recursion.</i>
------------------	---

---

**Description**

String together the case if-statements of a recursion.

**Usage**

```
make_update_expr(ranges, patterns, conditions, recursions)
```

**Arguments**

ranges	The ranges specification
patterns	The patterns specification
conditions	The conditions specifications
recursions	The recursions specification

**Value**

A series of if-else-statements for evaluating a recursion.

---

parse_ranges	<i>Parser for the ranges part of a specification.</i>
--------------	---

---

**Description**

Parses the ranges and return a list of index variables and the values they should iterate over. The ranges are returned as a list with the range variables as its names and the range values as the list components.

**Usage**

```
parse_ranges(ranges)
```

**Arguments**

ranges	The quosure wrapping the input to the specification.
--------	--

**Value**

A parsed specification for ranges.

---

parse_recursion	<i>Parser for the recursion part of a specification.</i>
-----------------	--

---

### Description

Parse the recursion part of an expressions.

### Usage

```
parse_recursion(recursion)
```

### Arguments

recursion	The quosure wrapping the recursion of the specification.
-----------	--

### Details

The parser return a list with the following components:

- **recursion\_env:** The environment in which expressions should be evaluated.
- **patterns:** A list of patterns, one per recursion case.
- **conditions:** A list of conditions, one per recursion case.
- **recursions:** A list of expressions, one per recursion case.

### Value

A parsed specification for recursions.

---

%where%	<i>Connects a recursion with sequences it should recurse over.</i>
---------	--

---

### Description

This function parses a dynamic programming recursion expression and evaluates it, returning the table that the recursions specify.

### Usage

```
recursion %where% ranges
```

### Arguments

recursion	Specification of the dynamic programming recursion.
ranges	Specification of the index-ranges the recursion should compute values over.

## Value

A filled out dynamic programming table.

## Examples

```
# Fibonacci numbers
fib <- {
  F[n] <- 1 ? n <= 2
  F[n] <- F[n-1] + F[n-2]
} %where% {
  n <- 1:10
}
fib

# Edit distance
x <- c("a", "b", "c")
y <- c("a", "b", "b", "c")
edit <- {
  E[1,j] <- j - 1
  E[i,1] <- i - 1
  E[i,j] <- min(
    E[i - 1,j] + 1,
    E[i,j - 1] + 1,
    E[i - 1,j - 1] + (x[i - 1] != y[j - 1])
  )
} %where% {
  i <- 1:(length(x) + 1)
  j <- 1:(length(y) + 1)
}
edit
```

# Index

`%where%`, [6](#)

`eval_recursion`, [2](#)

`get_table_name`, [2](#)

`make_condition_checks`, [3](#)

`make_pattern_match`, [3](#)

`make_pattern_match()`, [4](#)

`make_pattern_tests`, [4](#)

`make_recursion_case`, [4](#)

`make_update_expr`, [5](#)

`parse_ranges`, [5](#)

`parse_recursion`, [6](#)