

# Package ‘argon2’

June 12, 2017

**Type** Package

**Title** Secure Password Hashing

**Version** 0.2-0

**Description** Utilities for secure password hashing via the argon2 algorithm. It is a relatively new hashing algorithm and is believed to be very secure. The ‘argon2’ implementation included in the package is the reference implementation. The package also includes some utilities that should be useful for digest authentication, including a wrapper of ‘blake2b’. For similar R packages, see sodium and ‘bcrypt’. See <https://en.wikipedia.org/wiki/Argon2> or <https://eprint.iacr.org/2015/430.pdf> for more information.

**License** BSD 2-clause License + file LICENSE

**Copyright** See inst/COPYRIGHTS for files in src/argon2.

**Depends** R (>= 3.0.0)

**NeedsCompilation** yes

**ByteCompile** yes

**URL** <https://github.com/wrathematics/argon2>

**BugReports** <https://github.com/wrathematics/argon2/issues>

**Maintainer** Drew Schmidt <[wrathematics@gmail.com](mailto:wrathematics@gmail.com)>

**RoxygenNote** 6.0.1

**Author** Drew Schmidt [aut, cre]

**Repository** CRAN

**Date/Publication** 2017-06-12 16:00:50 UTC

## R topics documented:

argon2-package . . . . .	2
blake2b . . . . .	2
gen_nonce . . . . .	3
hashing . . . . .	3
raw_as_char . . . . .	4

**Index****6**


---

argon2-package	<i>argon2</i>
----------------	---------------

---

**Description**

Utilities for secure password hashing via the argon2 algorithm. It is a relatively new hashing algorithm and is believed to be very secure. The argon2 implementation included in the package is the reference implementation. The package also includes some utilities that should be useful for digest authentication, including a wrapper of blake2b. For similar R packages, see sodium and bcrypt.

**Author(s)**

Drew Schmidt

**References**

Project URL: <https://github.com/wrathematics/argon2>

---

blake2b	<i>blake2b</i>
---------	----------------

---

**Description**

A 512-bit blake2b hash implementation.

**Usage**

```
blake2b(x, key = NULL)
```

**Arguments**

x	Input to be hashed. Can be a single string or a raw vector.
key	An optional key. Should be NULL (for no key), a single string, or a raw vector.

**Value**

The hash of the string as a raw vector.

**References**

Aumasson, J.P., Neves, S., Wilcox-O’Hearn, Z. and Winnerlein, C., 2013, June. BLAKE2: simpler, smaller, fast as MD5. In International Conference on Applied Cryptography and Network Security (pp. 119-135). Springer Berlin Heidelberg.

**Examples**

```
## Not run:
library(argon2)
blake2b("some string")
blake2b("another")

## End(Not run)
```

---

gen\_nonce

*Generate a nonce*


---

**Description**

Generates a random raw (unsigned char\*) vector.

**Usage**

```
gen_nonce(length = 64)
```

**Arguments**

length            The number of elements to return.

**Value**

A random raw vector.

---

hashing

*Password Hashing*


---

**Description**

Basic password hashing. Use pw\_hash() to hash and pw\_check() to compare a possible password with the hashed password.

**Usage**

```
pw_hash(pass, type = "i")
```

```
pw_check(hash, pass)
```

**Arguments**

pass            The (plaintext) password.

type            Choice of algorithm; choices are "i" and "d".

hash            The hashed password; this is the output of pw\_hash().

## Details

For more hashing options, see the sodium and bcrypt.

This uses the argon2 (i or d variety) hash algorithm. See references for details and implementation source code (also bundled with this package).

Our binding uses a 512 bit salt with data generated from MT, a "time cost" (number of passes) of 16, "memory cost" of 8192 MiB, and 1 thread.

## Value

pw\_hash() returns a hash to be used as an input to pw\_check().

pw\_check() returns TRUE or FALSE, whether or not the plaintext password matches its hash.

## References

Biryukov, A., Dinu, D. and Khovratovich, D., 2015. Fast and Tradeoff-Resilient Memory-Hard Functions for Cryptocurrencies and Password Hashing. IACR Cryptology ePrint Archive, 2015, p.430.

Reference implementation <https://github.com/P-H-C/phc-winner-argon2>

## Examples

```
## Not run:
library(argon2)

pass <- "myPassw0rd!"
hash <- pw_hash(pass)
hash # store this

pw_check(hash, pass)
pw_check(hash, "password")
pw_check(hash, "1234")

## End(Not run)
```

---

raw\_as\_char

*raw\_as\_char*

---

## Description

Convert the literal bytes of a raw (unsigned char\*) to a string representation. This is different from R's rawToChar(). See examples for details.

## Usage

```
raw_as_char(raw, upper = TRUE, spaces = FALSE)
```

**Arguments**

<code>raw</code>	A raw vector.
<code>upper</code>	Should hex digits A-F be given in uppercase?
<code>spaces</code>	Should the str use spaces?

**Value**

A character string.

**Examples**

```
## Not run:  
library(argon2)  
str <- "some text"  
raw <- charToRaw(str)  
raw  
  
rawToChar(raw)  
raw_as_char(raw)  
  
## End(Not run)
```

# Index

\*Topic **package**

argon2-package, [2](#)

argon2-package, [2](#)

blake2b, [2](#)

gen\_nonce, [3](#)

hashing, [3](#)

pw\_check (hashing), [3](#)

pw\_hash (hashing), [3](#)

raw\_as\_char, [4](#)