

Package ‘clustermq’

February 22, 2019

Title Evaluate Function Calls on HPC Schedulers (LSF, SGE, SLURM, PBS/Torque)

Version 0.8.6

Author Michael Schubert <mschu.dev@gmail.com>

Maintainer Michael Schubert <mschu.dev@gmail.com>

Description Evaluate arbitrary function calls using workers on HPC schedulers in single line of code. All processing is done on the network without accessing the file system. Remote schedulers are supported via SSH.

URL <https://github.com/mschubert/clustermq>

BugReports <https://github.com/mschubert/clustermq/issues>

Depends R (>= 3.0.2)

Imports infuser (>= 0.2.8), narray, progress, purrr, R6, rzmq (>= 0.9.4), utils

License Apache License (== 2.0) | file LICENSE

LazyData true

Encoding UTF-8

Suggests dplyr, foreach, iterators, knitr, parallel, roxygen2 (>= 5.0.0), testthat, tools

VignetteBuilder knitr

RoxygenNote 6.1.1

NeedsCompilation no

Repository CRAN

Date/Publication 2019-02-22 14:30:22 UTC

R topics documented:

clustermq	2
Q	2
Q_rows	4
register_dopar_cmq	5
workers	5

 clustermq

Evaluate Function Calls on HPC Schedulers (LSF, SGE, SLURM)

Description

Provides the Q function to send arbitrary function calls to workers on HPC schedulers without relying on network-mounted storage. Allows using remote schedulers via SSH.

Details

Under the hood, this will submit a cluster job that connects to the master via TCP the master will then send the function and argument chunks to the worker and the worker will return the results to the master until everything is done and you get back your result

Computations are done entirely on the network and without any temporary files on network-mounted storage, so there is no strain on the file system apart from starting up R once per job. This removes the biggest bottleneck in distributed computing.

Using this approach, we can easily do load-balancing, i.e. workers that get their jobs done faster will also receive more function calls to work on. This is especially useful if not all calls return after the same time, or one worker has a high load.

For more detailed usage instructions, see the documentation of the Q function.

 Q

Queue function calls on the cluster

Description

Queue function calls on the cluster

Usage

```
Q(fun, ..., const = list(), export = list(), seed = 128965,
  memory = NULL, template = list(), n_jobs = NULL, job_size = NULL,
  split_array_by = -1, retype = "list", fail_on_error = TRUE,
  workers = NULL, log_worker = FALSE, chunk_size = NA,
  timeout = Inf)
```

Arguments

fun	A function to call
...	Objects to be iterated in each function call
const	A list of constant arguments passed to each function call
export	List of objects to be exported to the worker
seed	A seed to set for each function call
memory	Short for template=list(memory=value)
template	A named list of values to fill in template
n_jobs	The number of LSF jobs to submit; upper limit of jobs if job_size is given as well
job_size	The number of function calls per job
split_array_by	The dimension number to split any arrays in '...'; default: last
rettype	Return type of function call (vector type or 'list')
fail_on_error	If an error occurs on the workers, continue or fail?
workers	Optional instance of QSys representing a worker pool
log_worker	Write a log file for each worker
chunk_size	Number of function calls to chunk together defaults to 100 chunks per worker or max. 10 kb per chunk
timeout	Maximum time in seconds to wait for worker (default: Inf)

Value

A list of whatever 'fun' returned

Examples

```
## Not run:
# Run a simple multiplication for numbers 1 to 3 on a worker node
fx = function(x) x * 2
Q(fx, x=1:3, n_jobs=1)
# list(2,4,6)

# Run a mutate() call in dplyr on a worker node
iris %>%
  mutate(area = Q(`*`, e1=Sepal.Length, e2=Sepal.Width, n_jobs=1))
# iris with an additional column 'area'

## End(Not run)
```

 Q_rows

Queue function calls defined by rows in a data.frame

Description

Queue function calls defined by rows in a data.frame

Usage

```
Q_rows(df, fun, const = list(), export = list(), seed = 128965,
       memory = NULL, template = list(), n_jobs = NULL, job_size = NULL,
       rettype = "list", fail_on_error = TRUE, workers = NULL,
       log_worker = FALSE, chunk_size = NA, timeout = Inf)
```

Arguments

df	data.frame with iterated arguments
fun	A function to call
const	A list of constant arguments passed to each function call
export	List of objects to be exported to the worker
seed	A seed to set for each function call
memory	Short for template=list(memory=value)
template	A named list of values to fill in template
n_jobs	The number of LSF jobs to submit; upper limit of jobs if job_size is given as well
job_size	The number of function calls per job
rettype	Return type of function call (vector type or 'list')
fail_on_error	If an error occurs on the workers, continue or fail?
workers	Optional instance of QSys representing a worker pool
log_worker	Write a log file for each worker
chunk_size	Number of function calls to chunk together defaults to 100 chunks per worker or max. 10 kb per chunk
timeout	Maximum time in seconds to wait for worker (default: Inf)

Examples

```
## Not run:
# Run a simple multiplication for data frame columns x and y on a worker node
fx = function(x, y) x * y
df = data.frame(x = 5, y = 10)
Q_rows(df, fx, job_size = 1)
# [1] 50
```

```
# Q_rows also matches the names of a data frame with the function arguments
fx = function (x, y) x - y
df = data.frame(y = 5, x = 10)
Q_rows(df, fx, job_size = 1)
# [1] 5

## End(Not run)
```

register_dopar_cmq *Register clustermq as 'foreach' parallel handler*

Description

Register clustermq as 'foreach' parallel handler

Usage

```
register_dopar_cmq(...)
```

Arguments

... List of arguments passed to the 'Q' function, e.g. n_jobs

workers *Creates a pool of workers*

Description

Creates a pool of workers

Usage

```
workers(n_jobs, data = NULL, reuse = TRUE, template = list(),
        log_worker = FALSE, qsys_id = getOption("clustermq.scheduler",
        qsys_default))
```

Arguments

n_jobs	Number of jobs to submit (0 implies local processing)
data	Set common data (function, constant args, seed)
reuse	Whether workers are reusable or get shut down after call
template	A named list of values to fill in template
log_worker	Write a log file for each worker
qsys_id	Character string of QSys class to use

Value

An instance of the QSys class

Index

clustermq, [2](#)
clustermq-package (clustermq), [2](#)

Q, [2](#)
Q_rows, [4](#)

register_dopar_cmq, [5](#)

workers, [5](#)