

# Package ‘popReconstruct’

May 19, 2018

**Type** Package

**Title** Reconstruct Human Populations of the Recent Past

**Version** 1.0-5

**Date** 2018-05-18

**Author** Mark C. Wheldon

**Maintainer** “Mark C. Wheldon” <biostatmark@gmail.com>

**Description** Implements the Bayesian hierarchical model described by Wheldon, Raftery, Clark and Gerland (see: <doi:10.1080/01621459.2012.737729>) for simultaneously estimating age-specific population counts, fertility rates, mortality rates and net international migration flows, at the national level.

**License** GPL-3

**Depends** coda

**Suggests** ggplot2, reshape, gdata

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2018-05-19 07:08:07 UTC

## R topics documented:

popReconstruct-package . . . . .	2
burkina_faso_females.RData . . . . .	3
life.expectancy.stationary . . . . .	4
make.leslie.matrix . . . . .	5
net.number.migrants . . . . .	6
popRecon.ccmp.female . . . . .	8
popRecon.sampler . . . . .	9

<b>Index</b>	<b>13</b>
--------------	-----------

---

popReconstruct-package

*Reconstruct Human Populations of the Recent Past*

---

## Description

**popReconstruct** is a package for reconstructing populations of the recent past. It simultaneously estimates age-specific population counts, fertility rates, mortality rates and net international migration flows from fragmentary data, and incorporates measurement error. Informative priors are required for vital rates, migration rates, population counts at baseline, and their respective measurement error variances. Inference is based on the joint posterior probability distribution which yields fully probabilistic interval estimates. A sample from this distribution is drawn using a Markov chain Monte Carlo algorithm.

## Details

The DESCRIPTION file:

```
Package:      popReconstruct
Type:         Package
Title:        Reconstruct Human Populations of the Recent Past
Version:      1.0-5
Date:         2018-05-18
Author:       Mark C. Wheldon
Maintainer:   "Mark C. Wheldon" <biostatmark@gmail.com>
Description:  Implements the Bayesian hierarchical model described by Wheldon, Raftery, Clark and Gerland (see: <doi:10.1111/rssc.12187>)
License:      GPL-3
Depends:     coda
Suggests:    ggplot2, reshape, gdata
```

Index of help topics:

```
burkina_faso_females    Data for the Vignette burkina-faso-females
life.expectancy.stationary
                        Life Expectancy At Birth in a Stationary
                        Population
make.leslie.matrix      Make Leslie Matrix
net.number.migrants      Calculate Net Number of Migrants
popRecon.ccmp.female     Female Dominant Cohort Component Projection
popRecon.sampler        MCMC Sampler for the popReconstruct Package
popReconstruct-package   Reconstruct Human Populations of the Recent
                        Past
```

Further information is available in the following vignettes:

burkina-faso-females Burkina Faso Females Reconstruction (source, pdf)

See the vignette **burkina-faso-females** for a detailed illustration.

### Vignettes

burkina-faso-females

### Author(s)

Mark C. Wheldon

Maintainer: "Mark C. Wheldon" <biostatmark@gmail.com>

### References

Wheldon, M. C., Raftery, A. E., Clark, S. J. and Gerland, P. (2013). Reconstructing Past Populations With Uncertainty From Fragmentary Data. *Journal of the American Statistical Association*, 108:501, 96-110. doi: [10.1080/01621459.2012.737729](https://doi.org/10.1080/01621459.2012.737729).

---

burkina\_faso\_females.RData

*Data for the Vignette burkina-faso-females*

---

### Description

Contains initial estimates of fertility, mortality, migration and population counts for the reconstruction of the female population of Burkina Faso from 1960–2000. See the vignette **burkina-faso-females** for an illustration of its use.

### Usage

```
data(burkina_faso_females)
```

### Format

The format is: chr "burkina-faso-females.RData"

**Details**

The dataset contains two lists.

burkina.faso.females has components:

**fertility.rates** Matrix of initial estimates of average annual single-year age-specific fertility rates.

**survival.proportions** Matrix of initial estimates of age-specific survival proportions.

**migration.proportions** Matrix of initial estimates of age-specific average annual net migration as a proportion of the size of the same age-group in the receiving population.

**baseline.pop.counts** Single column matrix of age-specific population counts in the baseline year (1960).

**census.pop.counts** Matrix of age-specific census counts in years after the baseline year (1975, 1985, 1995, 2005).

burkina.faso.prop.vars has components fert.rate, surv.prop, mig.prop, population.count which contain variances for the Gaussian densities used as proposals in the random walk Metropolis-Hastings algorithm used to sample from the joint posterior.

**Vignettes**

**burkina-faso-females**

**References**

Wheldon, M. C., Raftery, A. E., Clark, S. J. and Gerland, P. (2011) *Estimating Demographic Parameters with Uncertainty*. Working Paper No. 108, Center for Statistics and the Social Sciences, University of Washington, Seattle. <http://www.csss.washington.edu/Papers/wp108.pdf>.

**Examples**

```
data(burkina_faso_females.RData)
```

---

```
life.expectancy.stationary
```

*Life Expectancy At Birth in a Stationary Population*

---

**Description**

Calculates life expectancy at birth from age-specific survival proportions in a stationary population. See the vignette burkina-faso-females for an illustration of its use.

**Usage**

```
life.expectancy.stationary(z)
```

**Arguments**

**z** Vector of age specific survival proportions for age groups of width five years.

**Details**

This function calculates the life expectancy at birth in a stationary population subject to the survival proportions supplied.

**Value**

Life expectancy at birth.

**Vignettes**

burkina-faso-females

**Author(s)**

Mark C. Wheldon

**Examples**

```
## Can take a few minutes

## Not run: data(burkina_faso_females)
life.expectancy.stationary(burkina.faso.females$survival.proportions[,1])

## End(Not run)
```

---

make.leslie.matrix      *Make Leslie Matrix*

---

**Description**

Constructs the Leslie Matrix needed for cohort component projection.

**Usage**

```
make.leslie.matrix(pop, surv, fert, srb = 1.05, age.int = 5, label.dims = FALSE)
```

**Arguments**

pop	Population count at baseline.
surv	Survivorship probabilities: the probability of reaching the age at the start of the interval. The first row should be $nL_0/(n*10)$ . The last row is survival for age.int years in the open interval.
fert	Matrix of age specific fertility rates NOT yet multiplied by age.int.
srb	Sex ratio at birth (matrix or scalar).
age.int	Width of the age intervals; needed for correct interpretation of survival probabilities and fertility rates.
label.dims	Should row and column names be set? Aesthetic.

**Details**

This function is used in the calculation of the average annual net number of migrants. See the vignette `burkina-faso-females` for an example of its use.

**Value**

A Leslie matrix as a matrix object.

**Vignettes**

`burkina-faso-females`

**Author(s)**

Mark C. Wheldon

**References**

Preston, S. H., Heuveline, P. and Guillot, M. (2001) *Demography*, chapter 6. Malden, MA: Blackwell.

**See Also**

[popRecon.ccmp.female](#), [net.number.migrants](#)

**Examples**

```
example(popRecon.ccmp.female)

(Lk <- make.leslie.matrix(pop = pop.input.mat[,1]
  ,surv = burkina.faso.females$survival.proportions[,1]
  ,fert = burkina.faso.females$fertility.rates[,1]
  ,srb = 1.05
  ,age.int = 5))
```

---

`net.number.migrants`     *Calculate Net Number of Migrants*

---

**Description**

Calculates the net number of migrants from two population vectors and the Leslie matrix describing the amount of change attributable to fertility and mortality.

**Usage**

```
net.number.migrants(n1, n2, L)
```

### Arguments

n1	Population vector at time $t$ .
n2	Population vectors at time $t + \delta$ .
L	The Leslie matrix (see <a href="#">make.leslie.matrix</a> ).

### Details

This function is used in the calculation of the average annual net number of migrants. See the vignette **burkina-faso-females** for an example of its use.

### Value

Vector of net number of migrants in each age group to the population between times  $t$  and  $t + \delta$ .

### Vignettes

[burkina-faso-females](#)

### Author(s)

Mark C. Wheldon

### See Also

[popRecon.ccmp.female](#), [make.leslie.matrix](#)

### Examples

```
## Can take several minutes to run

## Not run:
example(popRecon.ccmp.female)

example(make.leslie.matrix)

net.number.migrants(n1 = pop.input.mat[,k]
                    ,n2 = pop.input.mat[,k+1]
                    ,L = Lk)

## End(Not run)
```

---

popRecon.ccmp.female *Female Dominant Cohort Component Projection*

---

## Description

Implements the deterministic female dominant cohort component method of population projection.

## Usage

```
popRecon.ccmp.female(pop, surv, fert, srb = 1.05,
  mig, proj.steps, age.int = 5, label.dims = FALSE, base.year = "1960")
```

## Arguments

pop	Population count at baseline.
surv	Survivorship probabilities: the probability of reaching the age at the start of the interval.
fert	Matrix of average annual, single-year age-specific fertility rates (see Details).
srb	Sex ratio at birth matrix
mig	Net number of migrants as a <i>proportion</i> of prev time period's population.
proj.steps	Number of time periods to project forward. If missing, set to ncol(fert).
age.int	Width of the age intervals; needed for correct interpretation of survival probabilities and fertility rates.
label.dims	Should row and column names be set? Aesthetic.
base.year	Baseline year for population projections (aesthetic).

## Details

The first row of `surv` should be  ${}_nL_0/(nl_0)$ , where  ${}_nL_0$  and  $l_0$  are the usual life table parameters. The last row is survival for `age.int` years in the open interval.

The elements of the `fert` argument should not be multiplied by `age.int`. In other words, the average annual total fertility rates (TFRs) corresponding to the columns of `fert` are `age.int * colSums(fert)`.

The elements of `mig` give the average annual net number of migrants, as proportion of the size of the same age-group in the receiving population. Thus, the total net number of migrants to the population over the period

## Value

A matrix of projected population counts, age groups as rows, time periods as columns.

## Vignettes

burkina-faso-females



**Author(s)**

Mark C. Wheldon

**References**

Preston, S. H., Heuveline, P. and Guillot, M. (2001) *Demography*, chapter 6. Malden, MA: Blackwell.

**See Also**

[make.leslie.matrix](#), [net.number.migrants](#)

**Examples**

```
data(burkina_faso_females)

(pop.input.mat <-
  popRecon.ccmp.female(pop=burkina.faso.females$baseline.pop.counts
    ,surv=burkina.faso.females$survival.proportions
    ,fert=burkina.faso.females$fertility.rates
    ,mig=burkina.faso.females$migration.proportions
  ))
```

---

popRecon.sampler

*MCMC Sampler for the popReconstruct Package*

---

**Description**

Draws an MCMC sample from the joint posterior distribution of age-specific fertility rates, survival and migration proportions and baseline population counts.

**Usage**

```
popRecon.sampler(n.iter, burn.in = 0, thin.by = 1, al.f = 1, be.f = 0.0109,
  al.s = 1, be.s = 0.0109, al.g = 1, be.g = 0.0436, al.n = 1, be.n = 0.0109,
  mean.f, mean.s, mean.g, mean.b, start.f = mean.f, start.s = mean.s,
  start.g = mean.g, start.b = mean.b, start.sigmasq.f = 5, start.sigmasq.s = 5,
  start.sigmasq.g = 5, start.sigmasq.n = 5, pop.data, prop.vars,
  ccmp.function = popRecon.ccmp.female, proj.periods = ncol(mean.f),
  age.size = 5, verb = FALSE, s.tol = 10^(-10))
```

**Arguments**

n.iter	Number of iterations to save.
burn.in	Number of burn-in iterations; not saved.
thin.by	Thinning parameter; save every 'thin'th iteration.

al.f	Shape parameter of the distribution of the variance of the age-specific fertility rate initial estimates.
be.f	Scale parameter of the distribution of the variance of the age-specific fertility rate initial estimates.
al.s	Shape parameter of the distribution of the variance of the age-specific survival proportion initial estimates.
be.s	Scale parameter of the distribution of the variance of the age-specific survival proportion initial estimates.
al.g	Shape parameter of the distribution of the variance of the age-specific migration proportion initial estimates.
be.g	Scale parameter of the distribution of the variance of the age-specific migration proportion initial estimates.
al.n	Shape parameter of the distribution of the variance of the age-specific population count initial estimates and census counts.
be.n	Scale parameter of the distribution of the variance of the age-specific population count initial estimates and census counts.
mean.f	Matrix of initial estimates of age-specific fertility rates with age groups as rows, time periods as columns.
mean.s	Matrix of initial estimates of age-specific survival proportions with age groups as rows, time periods as columns.
mean.g	Matrix of initial estimates of age-specific migration proportions with age groups as rows, time periods as columns.
mean.b	Matrix of initial estimates of age-specific baseline population counts with age groups as rows, time periods as columns.
start.f	Matrix of MCMC start values of age-specific fertility rates with age groups as rows, time periods as columns.
start.s	Matrix of MCMC start values of age-specific survival proportions with age groups as rows, time periods as columns.
start.g	Matrix of MCMC start values of age-specific migration proportions with age groups as rows, time periods as columns.
start.b	Matrix of MCMC start values of age-specific baseline population counts with age groups as rows, time periods as columns.
start.sigmasq.f	MCMC start value for variance of the age-specific fertility rate initial estimates.
start.sigmasq.s	MCMC start value for variance of the age-specific survival proportions initial estimates.
start.sigmasq.g	MCMC start value for variance of the age-specific migration proportions initial estimates.
start.sigmasq.n	MCMC start value for variance of the age-specific baseline count initial estimates.

pop.data	Matrix fo census counts, with age groups as rows, time periods as columns.
prop.vars	List of matrices of variances for Gaussian Metropolis random walk proposals. Components are
ccmp.function	Function to do cohort component projection.
proj.periods	Number of age.size-year periods to over which to do the reconstruction, beginning at the baseline year.
age.size	Width of the age groups and time periods in years.
verb	Logical; should progress messages be printed.
s.tol	A tolerance parameter to stop over-/under-flow when taking logits of survival proportions.

## Details

This is the main function of the **popReconstruct** package. It takes initial estimates of age-specific vital rates, migration proportions and population counts in the baseline year and draws an MCMC sample from the joint posterior distribution defined in Wheldon et al. (2011). See the vignette **burkina-faso-females** for an extended illustration of its use.

## Value

A list with components;

fert.rate.mcmc	mcmc object containing MCMC chains for age-specific fertility rates.
surv.prop.mcmc	mcmc object containing MCMC chains for age-specific survival proportions.
mig.prop.mcmc	mcmc object containing MCMC chains for age-specific migration proportions.
baseline.count.mcmc	mcmc object containing MCMC chains for age-specific baseline counts.
lx.mcmc	mcmc object containing MCMC chains for age-specific population counts at years subsequent to baseline.
variances.mcmc	mcmc object containing MCMC chains for the vital rate variance parameters.
alg.stats	“algorithm statistics”; a list with components <code>acceptance.proportions</code> giving Metropolis acceptance proportions for each vital rate parameter, <code>pop.went.negative</code> giving the number of times Metropolis proposals resulted in negative population counts, <code>run.time</code> giving the time taken to run the sampler and some other, as yet undocumented, components.
fixed.params	A list containing the initial estimates and hyperparameters of the variance distributions.
start.vals	A list containing Metropolis start values for the vital rates, migration proportions, baseline counts and variance parameters.
alg.params	“algorithm parameters”; a list returning some of the arguments supplied for this run, saved for later reference. For example, Metropolis proposal variances ( <code>prop.vars</code> ) and the number of iterations ( <code>iters</code> ) are stored here.

## Vignettes

burkina-faso-females

**Author(s)**

Mark C. Wheldon

**References**

Wheldon, M. C., Raftery, A. E., Clark, S. J. and Gerland, P. (2011) *Estimating Demographic Parameters with Uncertainty*. Working Paper No. 108, Center for Statistics and the Social Sciences, University of Washington, Seattle. <http://www.csss.washington.edu/Papers/wp108.pdf>.

# Index

## \*Topic **datasets**

- burkina\_faso\_females.RData, [3](#)
  
- burkina.faso.females
  - (burkina\_faso\_females.RData), [3](#)
- burkina.faso.prop.vars
  - (burkina\_faso\_females.RData), [3](#)
- burkina\_faso\_females
  - (burkina\_faso\_females.RData), [3](#)
- burkina\_faso\_females.RData, [3](#)
  
- life.expectancy.stationary, [4](#)
  
- make.leslie.matrix, [5](#), [7](#), [9](#)
  
- net.number.migrants, [6](#), [6](#), [9](#)
  
- popRecon.ccmp.female, [6](#), [7](#), [8](#)
- popRecon.sampler, [9](#)
- popReconstruct
  - (popReconstruct-package), [2](#)
- popReconstruct-package, [2](#)