

Package ‘quadmesh’

January 16, 2019

Type Package

Title Quadrangle Mesh

Version 0.3.0

Description Create surface forms from matrix or 'raster' data for flexible plotting and conversion to other mesh types. The functions 'quadmesh' or 'triangmesh' produce a continuous surface as a 'mesh3d' object as used by the 'rgl' package. This is used for plotting raster data in 3D (optionally with texture), and allows the application of a map projection without data loss. There are discrete forms of these continuous surfaces available with 'dquadmesh' and 'dtriangmesh' functions.

License GPL-3

LazyData TRUE

RoxygenNote 6.1.1

Depends R (>= 2.10)

Encoding UTF-8

Imports raster, gridBase, viridis, png, sp, geometry, reproj (>= 0.2.0)

Suggests datasets, knitr, rmarkdown, palr, rgl, testthat, ncdf4, covr, vdiff, proj4

URL <https://github.com/hypertidy/quadmesh>

BugReports <https://github.com/hypertidy/quadmesh/issues>

VignetteBuilder knitr

ByteCompile true

NeedsCompilation no

Author Michael D. Sumner [aut, cre]

Maintainer Michael D. Sumner <mdsumner@gmail.com>

Repository CRAN

Date/Publication 2019-01-16 06:20:14 UTC

R topics documented:

bary_index	2
etopo	3
llh2xyz	3
mesh_plot	4
qm_as_raster	5
qsc	6
quadmesh	6
reproj	8
triangmesh	8
triangulate_quads	10
worldll	11
xymap	11
Index	12

bary_index	<i>Barycentric triangle index for interpolation</i>
------------	---

Description

This function returns the barycentric weight for a grid of coordinates from a geographic raster.

Usage

```
bary_index(x, coords = NULL, grid = NULL, ...)
```

Arguments

x	a 'RasterLayer' source
coords	optional input coordinates
grid	target 'RasterLayer', a target regular grid
...	ignored

Details

It's not as fast as [raster::projectRaster()] (e.g. 'projectRaster(x, grid)') but it also accepts a 'coords' argument and so can be used for non-regular raster reprojection.

'coords' may be 'NULL' or longitude, latitude in a 2-layer raster brick or stack as with 'mesh_plot'.

Value

RasterLayer

Examples

```

library(raster)
p_srs <- "+proj=stere +lat_0=-90 +lat_ts=-71 +datum=WGS84"
polar <- raster(extent(-5e6, 5e6, -5e6, 5e6), crs = p_srs, res = 25000)
etopo <- aggregate(etopo, fact = 4)
index <- bary_index(etopo, grid = polar)
ok <- !is.na(index$idx)
r <- setValues(polar, NA_integer_)
r[ok] <- colSums(matrix(values(etopo)[index$stri[, index$idx[ok]]], nrow = 3) * t(index$p)[, ok])
plot(r)

```

etopo	<i>World topography map</i>
-------	-----------------------------

Description

A simplified version of 'Etopo2'. The Etopo2 data set was reduced 20X to create this raster layer of global relief. See code in 'data-raw/topo.R'.

1lh2xyz	<i>Angular coordinates to X, Y, Z.</i>
---------	--

Description

Angular coordinates to X, Y, Z.

Usage

```
1lh2xyz(lonlatheight, rad = 6378137, exag = 1)
```

Arguments

lonlatheight	matrix or data.frame of lon,lat,height values
rad	radius of sphere
exag	exaggeration to apply to height values (added to radius)

Value

matrix

 mesh_plot

Plot as a mesh

Description

Convert to a quadmesh and plot in efficient vectorized form using 'grid'.

Usage

```
mesh_plot(x, crs = NULL, colfun = NULL, add = FALSE, ...,
          coords = NULL)
```

```
## S3 method for class 'BasicRaster'
mesh_plot(x, crs = NULL, colfun = NULL,
          add = FALSE, ..., coords = NULL)
```

```
## S3 method for class 'RasterLayer'
mesh_plot(x, crs = NULL, colfun = NULL,
          add = FALSE, ..., coords = NULL)
```

```
## S3 method for class 'TRI'
mesh_plot(x, crs = NULL, colfun = NULL, add = FALSE,
          ..., coords = NULL)
```

```
## S3 method for class 'quadmesh'
mesh_plot(x, crs = NULL, colfun = NULL,
          add = FALSE, ..., coords = NULL)
```

Arguments

x	object to convert to mesh and plot
crs	target map projection
colfun	colour function to use, 'viridis' is the default
add	add to existing plot or start a new one
...	ignored
coords	optional input raster of coordinates of each cell, see details

Details

The mesh may be reprojected prior to plotting using the 'crs' argument to define the target map projection in 'PROJ string' format. (There is no "reproject" function for quadmesh, this is performed directly on the x-y coordinates of the 'quadmesh' output). The 'colfun' argument is used to generate colours which are mapped to the input object data as in 'image'.

If 'coords' is supplied, it is currently assumed to be a 2-layer 'RasterBrick' with longitude and latitude as the *cell values*. These are used to geographically locate the resulting mesh, and

will be transformed to the 'crs' if that is supplied. This is modelled on the approach to curvilinear grid data used in the 'angstroms' package. There the function [angstroms::romsmap()] and [angstroms::romscoords()] are used to separate the complicated grid geometry from the grid data itself. A small fudge is applied to extend the coordinates by 1 cell to avoid losing any data due to the half cell outer margin (get in touch if this causes problems!).

Value

nothing, used for the side-effect of creating or adding to a plot

Examples

```
##mesh_plot(world11)
## crop otherwise out of bounds from PROJ
rr <- raster::crop(world11, raster::extent(-179, 179, -89, 89))
mesh_plot(rr, crs = "+proj=laea +datum=WGS84")
mesh_plot(world11, crs = "+proj=moll +datum=WGS84")
prj <- "+proj=lcc +datum=WGS84 +lon_0=147 +lat_0=-40 +lat_1=-55 +lat_2=-20"
mesh_plot(etopo, crs = prj, add = FALSE, colfun = function(n = 20) grey(seq(0, 1, length = n)))
mesh_plot(world11, crs = prj, add = TRUE)
```

qm_as_raster

Quadmesh to raster

Description

Approximate re-creation of a raster from a quadmesh.

Usage

```
qm_as_raster(x, index = NULL)
```

Arguments

x	'mesh3d' object
index	optional index to specify which z coordinate to use as raster values

Details

The raster is populated with the mean of the values at each corner, which is closest to the interpretation use to create mesh3d from rasters. This can be over ridden by setting 'index' to 1, 2, 3, or 4.

Value

RasterLayer

Examples

```
qm_as_raster(quadmesh(etopo))
```

qsc

Quadrilateralized Spherical Cube (QSC)

Description

The QSC is a set of six equal area projections for each side of the cube. Here a raw rendition of the cube is returned as six quad primitives in a 'mesh3d' object.

Usage

```
qsc()
```

Details

It's not clear if this is useful.

Value

```
mesh3d
```

References

<https://github.com/OSGeo/proj.4/wiki/Qsc>

Examples

```
library(rgl); #rgl.clear()
wire3d(qsc())
if ( rgl::rgl.useNULL() ) rglwidget()
```

quadmesh*Create a quad-type mesh for use in rgl.*

Description

Convert an object to a 'mesh3d' ([rgl::qmesh3d()]) quadrangle mesh, with methods for [raster::raster()] and 'matrix'.

Usage

```
dquadmesh(x, z = x, na.rm = FALSE, ..., texture = NULL,
          texture_filename = NULL)

## Default S3 method:
dquadmesh(x, z = x, na.rm = FALSE, ...,
          texture = NULL, texture_filename = NULL)

quadmesh(x, z = x, na.rm = FALSE, ..., texture = NULL,
         texture_filename = NULL)

## S3 method for class 'BasicRaster'
quadmesh(x, z = x, na.rm = FALSE, ...,
         texture = NULL, texture_filename = NULL)

## S3 method for class 'matrix'
quadmesh(x, z = x, na.rm = FALSE, ...,
         texture = NULL, texture_filename = NULL)
```

Arguments

x	raster object for mesh structure
z	raster object for height values
na.rm	remove quads where missing values?
...	ignored
texture	optional input RGB raster, 3-layers
texture_filename	optional input file path for PNG texture

Details

'quadmesh()' generates the cell-based interpretation of a raster (AREA) but applies a continuous interpretation of the values of the cells to each quad corner. 'dquadmesh' splits the mesh and applies a discrete interpretation directly. Loosely, the quadmesh is a continuous surface and the dquadmesh is free-floating cells, but it's a little more complicated and depends on the options applied. (The interpolation) applied in the quadmesh case is not entirely consistent.

The output is described as a mesh because it is a dense representation of a continuous shape, in this case plane-filling quadrilaterals defined by index of four of the available vertices.

The 'z' argument defaults to the input 'x' argument, though may be set to 'NULL', a constant numeric value, or another raster. If the coordinate system of 'z' and 'x' don't match the z values are queried by reprojection.

Any raster RGB object (3-layers, ranging in 0-255) may be used as a `_texture_` on the resulting mesh3d object. It is not possible to provide rgl with an object of data for texture, it must be a PNG file and so the in-memory 'texture' argument is written out to PNG file (with a message). The location of the file may be set explicitly with 'texture_filename'. Currently it's not possible to not use the 'texture' object in-memory.

Value

mesh3d

Examples

```
library(raster)
data(volcano)
r <- setExtent(raster(volcano), extent(0, 100, 0, 200))
qm <- quadmesh(r)
```

reproj	<i>Reprojection methods</i>
--------	-----------------------------

Description

A ‘quadmesh’ method for [reproj::reproj()].

Usage

```
## S3 method for class 'quadmesh'
reproj(x, target, ..., source = NULL)
```

Arguments

x	coordinates
target	target specification (PROJ.4 string or epsg code)
...	arguments passed to [proj4::ptransform()]
source	source specification (PROJ.4 string or epsg code)

triangmesh	<i>Create a triangle-type mesh for use in rgl.</i>
------------	--

Description

Convert an object to a ‘mesh3d’ ([rgl::tmesh3d()]) triangle mesh, with methods for [raster::raster()] and ‘matrix’.

Usage

```

triangmesh(x, z = x, na.rm = FALSE, ..., texture = NULL,
           texture_filename = NULL)

## S3 method for class 'matrix'
triangmesh(x, z = x, na.rm = FALSE, ...,
           texture = NULL, texture_filename = NULL)

## S3 method for class 'BasicRaster'
triangmesh(x, z = x, na.rm = FALSE, ...,
           texture = NULL, texture_filename = NULL)

dtriangmesh(x, z = x, na.rm = FALSE, ..., texture = NULL,
            texture_filename = NULL)

## Default S3 method:
dtriangmesh(x, z = x, na.rm = FALSE, ...,
            texture = NULL, texture_filename = NULL)

```

Arguments

x	raster object for mesh structure
z	raster object for height values
na.rm	remove quads where missing values?
...	ignored
texture	optional input RGB raster, 3-layers
texture_filename	optional input file path for PNG texture

Details

‘triangmesh()’ generates the point-based interpretation of a raster (POINT) with the obvious continuous interpretation. ‘dtriangmesh’ splits the mesh so that each primitive is independent. This is more coherent than the analogous distinction for quadmesh, though both will appear the same on creation.

The output is described as a mesh because it is a dense representation of a continuous shape, in this case plane-filling triangles defined by index of three of the available vertices.

The ‘z’ argument defaults to the input ‘x’ argument, though may be set to ‘NULL’, a constant numeric value, or another raster. If the coordinate system of ‘z’ and ‘x’ don’t match the z values are queried by reprojection.

Any raster RGB object (3-layers, ranging in 0-255) may be used as a `_texture_` on the resulting mesh3d object. It is not possible to provide rgl with an object of data for texture, it must be a PNG file and so the in-memory ‘texture’ argument is written out to PNG file (with a message). The location of the file may be set explicitly with ‘texture_filename’. Currently it’s not possible to not use the ‘texture’ object in-memory.

Value

mesh3d (primitivetype triangle)

Examples

```
library(raster)
r <- setExtent(raster(volcano), extent(0, nrow(volcano), 0, ncol(volcano)))
tm <- triangmesh(r)
#rgl::shade3d(tm)

## jitter the mesh just enough to show that they are distinct in the discrete case
a <- dtriangmesh(r)
a$vb[3L, ] <- jitter(a$vb[3L, ], factor = 10)
##rgl.clear(); rgl::shade3d(a, col = "grey"); aspect3d(1, 1, 0.2); rglwidget()
```

triangulate_quads	<i>Triangles from quads</i>
-------------------	-----------------------------

Description

Convert quad index to triangles, this converts the 'rgl mesh3d (ib)' quad index to the complementary triangle index '(it)'.

Usage

```
triangulate_quads(quad_index, clockwise = FALSE)
```

Arguments

quad_index	the 'ib' index of quads from 'quadmesh'
clockwise	if true triangles are wound clockwise, if false anticlockwise. This affects which faces rendering engines consider to be the 'front' and 'back' of the triangle. If your mesh appears 'inside out', try the alternative setting.

Details

Triangle pairs from each quad are interleaved in the result, so that neighbour triangles from a single quad are together.

Value

matrix of triangle indices

Examples

```

triangulate_quads(cbind(c(1, 2, 4, 3), c(3, 4, 6, 5)))

qm <- quadmesh(raster::crop(etopo, raster::extent(140, 160, -50, -30)))
tri <- triangulate_quads(qm$ib)
plot(t(qm$vb))
tri_avg <- colMeans(matrix(qm$vb[3, tri], nrow = 3), na.rm = TRUE)
scl <- function(x) (x - min(x))/diff(range(x))
tri_col <- grey(seq(0, 1, length = 100))[scl(tri_avg) * 99 + 1]
## tri is qm$ib converted to triangles for the same vertex set
polygon(t(qm$vb)[rbind(tri, NA), ])
polygon(t(qm$vb)[rbind(tri, NA), ], col = tri_col)

```

worldll	<i>World raster map</i>
---------	-------------------------

Description

A rasterized version of 'wrlld_simpl', created by burning the country polygon ID number into a one-degree world raster. (This is a very out of date polygon data set used for example only). See code in 'data-raw/worldll.R'.

xymap	<i>World map</i>
-------	------------------

Description

The world coastline coordinates. A simple matrix of lon, lat, separated by NA.

Details

From the maps package, see 'data-raw/xymap.R'.

Index

[bary_index](#), 2

[dquadmesh](#) ([quadmesh](#)), 6

[dtriangmesh](#) ([triangmesh](#)), 8

[etopo](#), 3

[llh2xyz](#), 3

[mesh_plot](#), 4

[qm_as_raster](#), 5

[qsc](#), 6

[quadmesh](#), 6

[reproj](#), 8

[triangmesh](#), 8

[triangulate_quads](#), 10

[worldll](#), 11

[xymap](#), 11