

Package ‘mirtjml’

December 21, 2018

Type Package

Title Joint Maximum Likelihood Estimation for High-Dimensional Item Factor Analysis

Version 1.2

Date 2018-12-11

Author Siliang Zhang [aut, cre],
Yunxiao Chen [aut],
Xiaoou Li [aut]

Maintainer Siliang Zhang <zhangsiliang123@gmail.com>

Description Provides constrained joint maximum likelihood estimation algorithms for item factor analysis (IFA) based on multidimensional item response theory models. So far, we provide functions for exploratory and confirmatory IFA based on the multidimensional two parameter logistic (M2PL) model for binary response data. Comparing with traditional estimation methods for IFA, the methods implemented in this package scale better to data with large numbers of respondents, items, and latent factors. The computation is facilitated by multiprocessing 'OpenMP' API. For more information, please refer to:
1. Chen, Y., Li, X., & Zhang, S. (2018). Joint Maximum Likelihood Estimation for High-Dimensional Exploratory Item Factor Analysis. *Psychometrika*, 1-23. <doi:10.1007/s11336-018-9646-5>;
2. Chen, Y., Li, X., & Zhang, S. (2017). Structured Latent Factor Analysis for Large-scale Data: Identifiability, Estimability, and Their Implications. arXiv preprint <arXiv:1712.08966>.

License GPL-3

URL <https://github.com/slzhang-fd/mirtjml>

BugReports <https://github.com/slzhang-fd/mirtjml/issues>

LazyData true

Depends R (>= 3.1)

Imports Rcpp (>= 0.12.17), stats, GPArotation

LinkingTo Rcpp, RcppArmadillo

RoxygenNote 6.1.0

Encoding UTF-8

NeedsCompilation yes

Repository CRAN

Date/Publication 2018-12-21 13:50:06 UTC

R topics documented:

data_sim	2
mirtjml_conf	2
mirtjml_expr	4

Index	6
--------------	----------

data_sim	<i>Simulated dataset for item factor analysis on the multidimensional two parameter logistic model.</i>
----------	---

Description

The dataset contains the simulation setting and the response data.

Usage

```
data_sim
```

Format

An object of class list of length 9.

mirtjml_conf	<i>Constrained joint maximum likelihood estimation for confirmatory item factor analysis on the multidimensional two parameter logistic model.</i>
--------------	--

Description

Constrained joint maximum likelihood estimation for confirmatory item factor analysis on the multidimensional two parameter logistic model.

Usage

```
mirtjml_conf(response, Q, theta0, A0, d0, cc = NULL, tol = 1e-04,
  print_proc = TRUE, parallel = FALSE)
```

Arguments

response	N by J matrix containing 0/1/NA responses, where N is the number of respondents, J is the number of items, and NA indicates a missing response.
Q	J by K matrix containing 0/1 entries, where J is the number of items and K is the number of latent traits. Each entry indicates whether an item measures a certain latent trait.
theta0	N by K matrix, the initial value of latent factor scores for each respondent.
A0	J by K matrix, the initial value of loading matrix, satisfying the constraints given by Q.
d0	Length J vector, the initial value of intercept parameters.
cc	A constant constraining the magnitude of the norms of person and item parameter vectors.
tol	The tolerance for convergence with a default value 1e-4.
print_proc	Print the precision during the estimation procedure with a default value TRUE.
parallel	Whether or not enable the parallel computing with a default value FALSE.

Value

The function returns a list with the following components:

theta_hat The estimated person parameter matrix.

A_hat The estimated loading parameter matrix

d_hat The estimated intercept parameters.

References

Chen, Y., Li, X., & Zhang, S. (2017). Structured Latent Factor Analysis for Large-scale Data: Identifiability, Estimability, and Their Implications. *arXiv preprint* <arXiv:1712.08966>.

Examples

```
# load a simulated dataset
attach(data_sim)

# generate starting values for the algorithm
A0 <- Q
d0 <- rep(0, J)
theta0 <- matrix(rnorm(N*K, 0, 1),N)

# run the confirmatory analysis
res_conf <- mirtjml_conf(response, Q, theta0, A0, d0)
```

mirtjml_expr	<i>Constrained joint maximum likelihood estimation for exploratory item factor analysis on the multidimensional two parameter logistic model.</i>
--------------	---

Description

Constrained joint maximum likelihood estimation for exploratory item factor analysis on the multidimensional two parameter logistic model.

Usage

```
mirtjml_expr(response, K, theta0 = NULL, A0 = NULL, d0 = NULL,
             cc = NULL, tol = 1e-04, print_proc = TRUE, parallel = FALSE)
```

Arguments

response	N by J matrix containing 0/1/NA responses, where N is the number of respondents, J is the number of items, and NA indicates a missing response.
K	The number of factors in exploratory item factor analysis.
theta0	N by K matrix, the initial value of latent factor scores for each respondent.
A0	J by K matrix, the initial value of loading matrix.
d0	Length J vector, the initial value of intercept parameters.
cc	A constant constraining the magnitude of the norms of person and item parameter vectors.
tol	The tolerance for convergence with a default value 1e-4.
print_proc	Print the precision during the estimation procedure with a default value TRUE.
parallel	Whether or not enable the parallel computing with a default value FALSE.

Value

The function returns a list with the following components:

theta_hat The estimated person parameter matrix.

A_hat The estimated loading parameter matrix

d_hat The estimated intercept parameters.

References

Chen, Y., Li, X., & Zhang, S. (2018). Joint Maximum Likelihood Estimation for High-Dimensional Exploratory Item Factor Analysis. *Psychometrika*, 1-23. <doi:10.1007/s11336-018-9646-5>;

Examples

```
# load a simulated dataset
attach(data_sim)

# run the exploratory analysis
res <- mirtjml_expr(response, K)
```

Index

*Topic **datasets**

data_sim, [2](#)

data_sim, [2](#)

mirtjml_conf, [2](#)

mirtjml_expr, [4](#)