

Package ‘broom’

April 7, 2019

Type Package

Title Convert Statistical Analysis Objects into Tidy Tibbles

Version 0.5.2

Description Summarizes key information about statistical objects in tidy tibbles. This makes it easy to report results, create plots and consistently work with large numbers of models at once. Broom provides three verbs that each provide different types of information about a model. `tidy()` summarizes information about model components such as coefficients of a regression. `glance()` reports information about an entire model, such as goodness of fit measures like AIC and BIC. `augment()` adds information about individual observations to a dataset, such as fitted values or influence measures.

License MIT + file LICENSE

URL <http://github.com/tidyverse/broom>

BugReports <http://github.com/tidyverse/broom/issues>

Depends R (>= 3.1)

Imports backports, dplyr, generics (>= 0.0.2), methods, nlme, purrr, reshape2, stringr, tibble, tidyr

Suggests AER, akima, AUC, bbmle, betareg, biglm, binGroup, boot, brms, btergm, car, caret, coda, covr, e1071, emmeans, ergm, gam (>= 1.15), gamlss, gamlss.data, gamlss.dist, geepack, ggplot2, glmnet, gmm, Hmisc, irlba, joineRML, Kendall, knitr, ks, Lahman, lavaan, lfe, lme4, lmodel2, lmtest, lsmeans, maps, mapprotools, MASS, Matrix, mclust, mgcv, muhaz, multcomp, network, nnet, orcutt (>= 2.2), ordinal, plm, plyr, polCA, psych, quantreg, rgeos, rmarkdown, robust, rsample, rstan, rstanarm, sp, speedglm, statnet.common, survey, survival, testthat, tseries, xergm, zoo

VignetteBuilder knitr

LazyData true

RoxygenNote 6.1.1

NeedsCompilation no

Author David Robinson [aut],
 Alex Hayes [aut, cre] (<<https://orcid.org/0000-0002-4985-5160>>),
 Matthieu Gomez [ctb],
 Boris Demeshev [ctb],
 Dieter Menne [ctb],
 Benjamin Nutter [ctb],
 Luke Johnston [ctb],
 Ben Bolker [ctb],
 Francois Briatte [ctb],
 Jeffrey Arnold [ctb],
 Jonah Gabry [ctb],
 Luciano Selzer [ctb],
 Gavin Simpson [ctb],
 Jens Preussner [ctb],
 Jay Hesselberth [ctb],
 Hadley Wickham [ctb],
 Matthew Lincoln [ctb],
 Alessandro Gasparini [ctb],
 Lukasz Komsta [ctb],
 Frederick Novometsky [ctb],
 Wilson Freitas [ctb],
 Michelle Evans [ctb],
 Jason Cory Brunson [ctb],
 Simon Jackson [ctb],
 Ben Whalley [ctb],
 Michael Kuehn [ctb],
 Jorge Cimentada [ctb],
 Erle Holgersen [ctb],
 Karl Dunkle Werner [ctb]

Maintainer Alex Hayes <alexphayes@gmail.com>

Repository CRAN

Date/Publication 2019-04-07 19:52:53 UTC

R topics documented:

argument_glossary	6
augment.betareg	7
augment.coxph	8
augment.decomposed.ts	10
augment.factanal	12
augment.felm	14
augment.glm	15
augment.glmRob	17
augment.htest	18
augment.ivreg	20

augment.kmeans	22
augment.lm	23
augment.lmRob	25
augment.loess	27
augment.Mclust	28
augment.mjoint	30
augment.nlrq	31
augment.nls	32
augment.plm	34
augment.poLCA	35
augment.prcomp	36
augment.rlm	38
augment.rq	39
augment.rqs	41
augment.smooth.spline	43
augment.speedlm	45
augment.stl	46
augment.survreg	47
augment_columns	49
bootstrap	50
brms_tidiers	51
broom	52
column_glossary	53
confint_tidy	53
data.frame_tidiers	54
durbinWatsonTest_tidiers	56
emmeans_tidiers	57
finish_glance	59
fix_data_frame	60
glance.aareg	60
glance.Arima	61
glance.betareg	62
glance.biglm	64
glance.binDesign	65
glance.cch	66
glance.coxph	67
glance.cv.glmnet	68
glance.ergm	69
glance.factanal	70
glance.felm	71
glance.ftdistr	73
glance.Gam	74
glance.gam	75
glance.garch	76
glance.glm	77
glance.glmnet	78
glance.glmRob	79
glance.gmm	80

glance.ivreg	81
glance.kmeans	82
glance.lavaan	84
glance.lm	85
glance.lmodel2	87
glance.lmRob	88
glance.Mclust	89
glance.mjoint	90
glance.muhaaz	91
glance.multinom	92
glance.nlrq	93
glance.nls	94
glance.orcutt	95
glance.plm	96
glance.poLCA	97
glance.pyears	98
glance.ridgelm	99
glance.rlm	100
glance.rq	102
glance.smooth.spline	103
glance.speedlm	104
glance.survdiff	105
glance.survexp	106
glance.survfit	107
glance.survreg	108
glance_optim	109
insert_NAs	110
list_tidiers	111
lme4_tidiers	111
matrix_tidiers	114
mcmc_tidiers	115
nlme_tidiers	117
null_tidiers	119
rowwise_df_tidiers	120
rstanarm_tidiers	122
sparse_tidiers	124
sp_tidiers	125
summary_tidiers	126
tidy.aareg	127
tidy.acf	128
tidy.anova	129
tidy.aov	131
tidy.aovlist	132
tidy.Arima	133
tidy.betareg	134
tidy.biglm	136
tidy.binDesign	138
tidy.binWidth	139

tidy.boot	140
tidy.btergm	142
tidy.cch	143
tidy.cld	145
tidy.coefest	146
tidy.confint.glht	147
tidy.confusionMatrix	148
tidy.coxph	149
tidy.cv.glmnet	151
tidy.density	153
tidy.dist	154
tidy.ergm	155
tidy.factanal	157
tidy.felm	158
tidy.fitdistr	160
tidy.ftable	161
tidy.Gam	162
tidy.gam	163
tidy.gamlss	164
tidy.garch	165
tidy.geeglm	166
tidy.glht	168
tidy.glm	169
tidy.glmnet	170
tidy.glmRob	172
tidy.gmm	174
tidy.htest	176
tidy.ivreg	178
tidy.kappa	180
tidy.kde	181
tidy.Kendall	182
tidy.kmeans	184
tidy.lavaan	185
tidy.lm	186
tidy.lmodel2	188
tidy.lmRob	190
tidy.manova	192
tidy.map	193
tidy.Mclust	194
tidy.mjoint	196
tidy.mle2	198
tidy.muhaz	199
tidy.multinom	200
tidy.nlrq	201
tidy.nls	203
tidy.numeric	204
tidy.orcutt	205
tidy.pairwise.htest	206

tidy.plm	208
tidy.poLCA	209
tidy.polr	211
tidy.power.htest	214
tidy.pcomp	215
tidy.pyears	217
tidy.rcorr	218
tidy.ridgelm	220
tidy.rlm	221
tidy.roc	223
tidy.rq	224
tidy.rqs	225
tidy.spec	227
tidy.speedlm	228
tidy.summary.glht	229
tidy.survdiff	230
tidy.survexp	231
tidy.survfit	232
tidy.survreg	234
tidy.table	235
tidy.ts	236
tidy.TukeyHSD	237
tidy.zoo	239
tidy_irlba	240
tidy_optim	242
tidy_svd	243
tidy_xyz	245

Index	247
--------------	------------

argument_glossary	<i>Allowed argument names in tidiers</i>
-------------------	--

Description

Allowed argument names in tidiers

Usage

```
argument_glossary
```

Format

A tibble with 3 variables:

method One of "glance", "augment" or "tidy".

argument Character name of allowed argument name.

description Character description of argument use.

Examples

```
argument_glossary
```

augment.betareg	<i>Augment data with information from a(n) betareg object</i>
-----------------	---

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to augment via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that all columns used to fit the model are present.

Augment will often behavior different depending on whether `data` or `newdata` is specified. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many augment methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases augment tries to reconstruct the original data based on the model object, with some varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'betareg'
augment(x, data = stats::model.frame(x),
        newdata = NULL, type.predict, type.residuals, ...)
```

Arguments

<code>x</code>	A betareg object produced by a call to <code>betareg::betareg()</code> .
<code>data</code>	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.

newdata	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create <code>x</code> . Defaults to <code>NULL</code> , indicating that nothing has been passed to <code>newdata</code> . If <code>newdata</code> is specified, the <code>data</code> argument will be ignored.
type.predict	Character indicating type of prediction to use. Passed to the <code>type</code> argument of the <code>stats::predict()</code> generic. Allowed arguments vary with model class, so be sure to read the <code>predict.my_class</code> documentation.
type.residuals	Character indicating type of residuals to use. Passed to the <code>type</code> argument of <code>stats::residuals()</code> generic. Allowed arguments vary with model class, so be sure to read the <code>residuals.my_class</code> documentation.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Value

`augment` returns the original data, along with new columns describing each observation:

<code>.fitted</code>	Fitted values of model
<code>.resid</code>	Residuals
<code>.cooks</code>	Cooks distance, <code>cooks.distance()</code>

See Also

`augment()`, `betareg::betareg()`

<code>augment.coxph</code>	<i>Augment data with information from a(n) coxph object</i>
----------------------------	---

Description

`Augment` accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that all columns used to fit the model are present.

`Augment` will often behavior different depending on whether `data` or `newdata` is specified. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many augment methods provide default data arguments, so that `augment(fit)` will return the augmented training data. In these cases `augment` tries to reconstruct the original data based on the model object, with some varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'coxph'
augment(x, data = NULL, newdata = NULL,
        type.predict = "lp", type.residuals = "martingale", ...)
```

Arguments

<code>x</code>	A <code>coxph</code> object returned from <code>survival::coxph()</code> .
<code>data</code>	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. <code>augment</code> will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
<code>newdata</code>	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create <code>x</code> . Defaults to <code>NULL</code> , indicating that nothing has been passed to <code>newdata</code> . If <code>newdata</code> is specified, the <code>data</code> argument will be ignored.
<code>type.predict</code>	Character indicating type of prediction to use. Passed to the <code>type</code> argument of the <code>stats::predict()</code> generic. Allowed arguments vary with model class, so be sure to read the <code>predict.my_class</code> documentation.
<code>type.residuals</code>	Character indicating type of residuals to use. Passed to the <code>type</code> argument of <code>stats::residuals()</code> generic. Allowed arguments vary with model class, so be sure to read the <code>residuals.my_class</code> documentation.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Details

When the modeling was performed with `na.action = "na.omit"` (as is the typical default), rows with NA in the initial data are omitted entirely from the augmented data frame. When the

modeling was performed with `na.action = "na.exclude"`, one should provide the original data as a second argument, at which point the augmented data will contain those rows (typically with NAs in place of the new columns). If the original data is not provided to `augment()` and `na.action = "na.exclude"`, a warning is raised and the incomplete rows are dropped.

Value

A `tibble::tibble` with the passed data and additional columns:

<code>.fitted</code>	Fitted values of model
<code>.se.fit</code>	Standard errors of fitted values
<code>.resid</code>	Residuals (not present if <code>newdata</code> specified.)

See Also

[na.action](#)

[augment\(\)](#), [survival::coxph\(\)](#)

Other `coxph` tidiers: [glance.coxph](#), [tidy.coxph](#)

Other survival tidiers: [augment.survreg](#), [glance.aareg](#), [glance.cch](#), [glance.coxph](#), [glance.pyears](#), [glance.survdiff](#), [glance.survexp](#), [glance.survfit](#), [glance.survreg](#), [tidy.aareg](#), [tidy.cch](#), [tidy.coxph](#), [tidy.pyears](#), [tidy.survdiff](#), [tidy.survexp](#), [tidy.survfit](#), [tidy.survreg](#)

`augment.decomposed.ts` *Augment data with information from a(n) decomposed.ts object*

Description

`Augment` accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that all columns used to fit the model are present.

`Augment` will often behavior different depending on whether `data` or `newdata` is specified. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases `augment` tries to reconstruct the original data based on the model object, with some varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model

formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'decomposed.ts'
augment(x, ...)
```

Arguments

<code>x</code>	A <code>decomposed.ts</code> object returned from <code>stats::decompose()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A `tibble::tibble` with one row for each observation in the original times series:

<code>.seasonal</code>	The seasonal component of the decomposition.
<code>.trend</code>	The trend component of the decomposition.
<code>.remainder</code>	The remainder, or "random" component of the decomposition.
<code>.weight</code>	The final robust weights (stl only).
<code>.seasadj</code>	The seasonally adjusted (or "deseasonalised") series.

See Also

`augment()`, `stats::decompose()`

Other decompose tidiers: `augment.stl`

Examples

```
# Time series of temperatures in Nottingham, 1920-1939:
nottem

# Perform seasonal decomposition on the data with both decompose
# and stl:
d1 <- stats::decompose(nottem)
d2 <- stats::stl(nottem, s.window = "periodic", robust = TRUE)
```

```

# Compare the original series to its decompositions.

cbind(broom::tidy(nottem), broom::augment(d1),
      broom::augment(d2))

# Visually compare seasonal decompositions in tidy data frames.

library(tibble)
library(dplyr)
library(tidyr)
library(ggplot2)

decomps <- tibble(
  # Turn the ts objects into data frames.
  series = list(as.data.frame(nottem), as.data.frame(nottem)),
  # Add the models in, one for each row.
  decomp = c("decompose", "stl"),
  model = list(d1, d2)
) %>%
  rowwise() %>%
  # Pull out the fitted data using broom::augment.
  mutate(augment = list(broom::augment(model))) %>%
  ungroup() %>%
  # Unnest the data frames into a tidy arrangement of
  # the series next to its seasonal decomposition, grouped
  # by the method (stl or decompose).
  group_by(decomp) %>%
  unnest(series, augment) %>%
  mutate(index = 1:n()) %>%
  ungroup() %>%
  select(decomp, index, x, adjusted = .seasadj)

ggplot(decomps) +
  geom_line(aes(x = index, y = x), colour = "black") +
  geom_line(aes(x = index, y = adjusted, colour = decomp,
               group = decomp))

```

augment.factanal

Augment data with information from a(n) factanal object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to augment via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object.

Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that all columns used to fit the model are present.

Augment will often behavior different depending on whether `data` or `newdata` is specified. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many augment methods provide default data arguments, so that `augment(fit)` will return the augmented training data. In these cases augment tries to reconstruct the original data based on the model object, with some varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'factanal'
augment(x, data, ...)
```

Arguments

<code>x</code>	A <code>factanal</code> object created by <code>stats::factanal()</code> .
<code>data</code>	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Value

When `data` is not supplied `augment.factanal` returns one row for each observation, with a factor score column added for each factor `X`, (`.fsX`). This is because `factanal()`, unlike other stats methods like `lm()`, does not retain the original data.

When `data` is supplied, `augment.factanal` returns one row for each observation, with a factor score column added for each factor `X`, (`.fsX`).

See Also

[augment\(\)](#), [stats::factanal\(\)](#)

Other factanal tidiers: [glance.factanal](#), [tidy.factanal](#)

augment.felm

Augment data with information from a(n) felm object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that all columns used to fit the model are present.

Augment will often behavior different depending on whether `data` or `newdata` is specified. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases `augment` tries to reconstruct the original data based on the model object, with some varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'felm'
augment(x, data = NULL, ...)
```

Arguments

<code>x</code>	A <code>felm</code> object returned from <code>lfe::felm()</code> .
<code>data</code>	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

A `tibble::tibble()` containing the data passed to `augment`, and **additional** columns:

<code>.fitted</code>	The predicted response for that observation.
<code>.resid</code>	The residual for a particular point. Present only when data has been passed to <code>augment</code> via the <code>data</code> argument.

See Also

`augment()`, `lfe::felm()`

Other `felm` tidiers: `tidy.felm`

<code>augment.glm</code>	<i>Augment a(n) glm object</i>
--------------------------	--------------------------------

Description

This `augment` method wraps `augment.lm()`.

Usage

```
## S3 method for class 'glm'
augment(x, ...)
```

Arguments

<code>x</code>	A <code>glm</code> object returned from <code>stats::glm()</code> .
...	Arguments passed on to <code>augment.lm</code>
data	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. <code>Augment</code> will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
newdata	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create <code>x</code> . Defaults to <code>NULL</code> , indicating that nothing has been passed to <code>newdata</code> . If <code>newdata</code> is specified, the <code>data</code> argument will be ignored.

type.predict Type of predictions to use when `x` is a `glm` object. Passed to `stats::predict.glm()`.

type.residuals Type of residuals to use when `x` is a `glm` object. Passed to `stats::residuals.glm()`.

x An `lm` object created by `stats::lm()`.

Value

When `newdata` is not supplied `augment.lm` returns one row for each observation, with seven columns added to the original data:

<code>.hat</code>	Diagonal of the hat matrix
<code>.sigma</code>	Estimate of residual standard deviation when corresponding observation is dropped from model
<code>.cooks</code>	Cooks distance, <code>cooks.distance()</code>
<code>.fitted</code>	Fitted values of model
<code>.se.fit</code>	Standard errors of fitted values
<code>.resid</code>	Residuals
<code>.std.resid</code>	Standardised residuals

Some unusual `lm` objects, such as `r1m` from MASS, may omit `.cooks` and `.std.resid`. `gam` from `mgcv` omits `.sigma`.

When `newdata` is supplied, returns one row for each observation, with three columns added to the new data:

<code>.fitted</code>	Fitted values of model
<code>.se.fit</code>	Standard errors of fitted values
<code>.resid</code>	Residuals of fitted values on the new data

See Also

`augment()`, `augment.lm()`

`stats::glm()`

Other `lm` tidiers: `augment.lm`, `glance.glm`, `glance.lm`, `tidy.glm`, `tidy.lm`

augment.glmRob	<i>Augment a(n) glmRob object</i>
----------------	-----------------------------------

Description

This augment method wraps `augment.lm()`.

Usage

```
## S3 method for class 'glmRob'
augment(x, ...)
```

Arguments

<code>x</code>	A <code>glmRob</code> object returned from <code>robust::glmRob()</code> .
<code>...</code>	Arguments passed on to <code>augment.lm</code>
data	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
newdata	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create <code>x</code> . Defaults to <code>NULL</code> , indicating that nothing has been passed to <code>newdata</code> . If <code>newdata</code> is specified, the <code>data</code> argument will be ignored.
type.predict	Type of predictions to use when <code>x</code> is a <code>glm</code> object. Passed to <code>stats::predict.glm()</code> .
type.residuals	Type of residuals to use when <code>x</code> is a <code>glm</code> object. Passed to <code>stats::residuals.glm()</code> .
x	An <code>lm</code> object created by <code>stats::lm()</code> .

Details

For tidiers for robust models from the **MASS** package see `tidy.rlm()`.

Value

When `newdata` is not supplied `augment.lm` returns one row for each observation, with seven columns added to the original data:

<code>.hat</code>	Diagonal of the hat matrix
<code>.sigma</code>	Estimate of residual standard deviation when corresponding observation is dropped from model
<code>.cooks</code>	Cooks distance, <code>cooks.distance()</code>

<code>.fitted</code>	Fitted values of model
<code>.se.fit</code>	Standard errors of fitted values
<code>.resid</code>	Residuals
<code>.std.resid</code>	Standardised residuals

Some unusual `lm` objects, such as `rlm` from MASS, may omit `.cooks` and `.std.resid`. `gam` from `mgcv` omits `.sigma`.

When `newdata` is supplied, returns one row for each observation, with three columns added to the new data:

<code>.fitted</code>	Fitted values of model
<code>.se.fit</code>	Standard errors of fitted values
<code>.resid</code>	Residuals of fitted values on the new data

See Also

[augment\(\)](#), [augment.lm\(\)](#)

[robust::glmRob\(\)](#)

Other robust tidiers: [augment.lmRob](#), [glance.glmRob](#), [glance.lmRob](#), [tidy.glmRob](#), [tidy.lmRob](#)

`augment.htest`

Augment data with information from a(n) htest object

Description

`augment` accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that all columns used to fit the model are present.

`augment` will often behavior different depending on whether `data` or `newdata` is specified. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases `augment` tries to reconstruct the original data based on the model object, with some varying degrees of success.

The augmented dataset is always returned as a [tibble::tibble](#) with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that [splines::ns\(\)](#), [stats::poly\(\)](#) and

`survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'htest'
augment(x, ...)
```

Arguments

`x` An `htest` objected, such as those created by `stats::cor.test()`, `stats::t.test()`, `stats::wilcox.test()`, `stats::chisq.test()`, etc.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the data argument.

Details

See `stats::chisq.test()` for more details on how residuals are computed.

Value

Errors unless `x` is a chi-squared test. If `x` is a chi-squared test, for each cell of the tested table returns columns:

<code>.observed</code>	Observed count
<code>.prop</code>	Proportion of the total
<code>.row.prop</code>	Row proportion (2 dimensions table only)
<code>.col.prop</code>	Column proportion (2 dimensions table only)
<code>.expected</code>	Expected count under the null hypothesis
<code>.residuals</code>	Pearson residual
<code>.stdres</code>	Standardized residual

See Also

`augment()`, `stats::chisq.test()`

Other `htest` tidiers: `tidy.htest`, `tidy.pairwise.htest`, `tidy.power.htest`

augment.ivreg

Augment data with information from a(n) ivreg object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to augment via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that all columns used to fit the model are present.

Augment will often behavior different depending on whether `data` or `newdata` is specified. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many augment methods provide default data arguments, so that `augment(fit)` will return the augmented training data. In these cases augment tries to reconstruct the original data based on the model object, with some varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'ivreg'
augment(x, data = model.frame(x), newdata, ...)
```

Arguments

<code>x</code>	An ivreg object created by a call to <code>AER::ivreg()</code> .
<code>data</code>	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
<code>newdata</code>	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create <code>x</code> . Defaults to <code>NULL</code> , indicating that nothing has been passed to <code>newdata</code> . If <code>newdata</code> is specified, the <code>data</code> argument will be ignored.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

A `tibble::tibble()` containing the data passed to `augment`, and **additional** columns:

<code>.fitted</code>	The predicted response for that observation.
<code>.resid</code>	The residual for a particular point. Present only when data has been passed to <code>augment</code> via the <code>data</code> argument.

See Also

`augment()`, `AER::ivreg()`

Other ivreg tidiers: `glance.ivreg`, `tidy.ivreg`

Examples

```
library(AER)

data("CigarettesSW", package = "AER")
ivr <- ivreg(
  log(packs) ~ income | population,
  data = CigarettesSW,
  subset = year == "1995"
)

summary(ivr)

tidy(ivr)
tidy(ivr, conf.int = TRUE)
tidy(ivr, conf.int = TRUE, exponentiate = TRUE)

augment(ivr)

glance(ivr)
```

augment.kmeans

Augment data with information from a(n) kmeans object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to augment via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that all columns used to fit the model are present.

Augment will often behavior different depending on whether `data` or `newdata` is specified. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many augment methods provide default data arguments, so that `augment(fit)` will return the augmented training data. In these cases augment tries to reconstruct the original data based on the model object, with some varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'kmeans'
augment(x, data, ...)
```

Arguments

<code>x</code>	A kmeans object created by <code>stats::kmeans()</code> .
<code>data</code>	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be

used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

The original data as a `tibble::tibble` with one extra column:

`.cluster` The cluster assigned by the k-means algorithm

See Also

`augment()`, `stats::kmeans()`

Other kmeans tidiers: `glance.kmeans`, `tidy.kmeans`

`augment.lm`

Augment data with information from a(n) lm object

Description

`Augment` accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that all columns used to fit the model are present.

`Augment` will often behavior different depending on whether `data` or `newdata` is specified. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases `augment` tries to reconstruct the original data based on the model object, with some varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'lm'
augment(x, data = stats::model.frame(x), newdata,
        type.predict, type.residuals, ...)
```

Arguments

x	An lm object created by <code>stats::lm()</code> .
data	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object x. Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the data argument. Augment will report information such as influence and cooks distance for data passed to the data argument. These measures are only defined for the original training data.
newdata	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create x. Defaults to NULL, indicating that nothing has been passed to newdata. If newdata is specified, the data argument will be ignored.
type.predict	Type of predictions to use when x is a glm object. Passed to <code>stats::predict.glm()</code> .
type.residuals	Type of residuals to use when x is a glm object. Passed to <code>stats::residuals.glm()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a newdata argument, it will use the default value for the data argument.

Details

When the modeling was performed with `na.action = "na.omit"` (as is the typical default), rows with NA in the initial data are omitted entirely from the augmented data frame. When the modeling was performed with `na.action = "na.exclude"`, one should provide the original data as a second argument, at which point the augmented data will contain those rows (typically with NAs in place of the new columns). If the original data is not provided to `augment()` and `na.action = "na.exclude"`, a warning is raised and the incomplete rows are dropped.

Value

When newdata is not supplied `augment.lm` returns one row for each observation, with seven columns added to the original data:

<code>.hat</code>	Diagonal of the hat matrix
<code>.sigma</code>	Estimate of residual standard deviation when corresponding observation is dropped from model
<code>.cooks</code>	Cooks distance, <code>cooks.distance()</code>
<code>.fitted</code>	Fitted values of model

.se.fit	Standard errors of fitted values
.resid	Residuals
.std.resid	Standardised residuals

Some unusual `lm` objects, such as `rlm` from MASS, may omit `.cooks` and `.std.resid`. `gam` from `mgcv` omits `.sigma`.

When `newdata` is supplied, returns one row for each observation, with three columns added to the new data:

.fitted	Fitted values of model
.se.fit	Standard errors of fitted values
.resid	Residuals of fitted values on the new data

See Also

[na.action](#)

[augment\(\)](#), [stats::predict.lm\(\)](#)

Other `lm` tidiers: [augment.glm](#), [glance.glm](#), [glance.lm](#), [tidy.glm](#), [tidy.lm](#)

<code>augment.lmRob</code>	<i>Augment a(n) lmRob object</i>
----------------------------	----------------------------------

Description

This `augment` method wraps [augment.lm\(\)](#).

Usage

```
## S3 method for class 'lmRob'
augment(x, ...)
```

Arguments

<code>x</code>	A <code>lmRob</code> object returned from robust::lmRob() .
<code>...</code>	Arguments passed on to <code>augment.lm</code>
data	A data.frame() or tibble::tibble() containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
newdata	A data.frame() or tibble::tibble() containing all the original predictors used to create <code>x</code> . Defaults to <code>NULL</code> , indicating that nothing has been passed to <code>newdata</code> . If <code>newdata</code> is specified, the <code>data</code> argument will be ignored.

type.predict Type of predictions to use when `x` is a `glm` object. Passed to `stats::predict.glm()`.

type.residuals Type of residuals to use when `x` is a `glm` object. Passed to `stats::residuals.glm()`.

x An `lm` object created by `stats::lm()`.

Details

For tidiers for robust models from the **MASS** package see `tidy.rlm()`.

Value

When `newdata` is not supplied `augment.lm` returns one row for each observation, with seven columns added to the original data:

<code>.hat</code>	Diagonal of the hat matrix
<code>.sigma</code>	Estimate of residual standard deviation when corresponding observation is dropped from model
<code>.cooks</code>	Cooks distance, <code>cooks.distance()</code>
<code>.fitted</code>	Fitted values of model
<code>.se.fit</code>	Standard errors of fitted values
<code>.resid</code>	Residuals
<code>.std.resid</code>	Standardised residuals

Some unusual `lm` objects, such as `rlm` from **MASS**, may omit `.cooks` and `.std.resid`. `gam` from **mgcv** omits `.sigma`.

When `newdata` is supplied, returns one row for each observation, with three columns added to the new data:

<code>.fitted</code>	Fitted values of model
<code>.se.fit</code>	Standard errors of fitted values
<code>.resid</code>	Residuals of fitted values on the new data

See Also

`augment()`, `augment.lm()`

`robust::lmRob()`

Other robust tidiers: `augment.glmRob`, `glance.glmRob`, `glance.lmRob`, `tidy.glmRob`, `tidy.lmRob`

augment.loess	<i>Tidy a(n) loess object</i>
---------------	-------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'loess'
augment(x, data = stats::model.frame(x), newdata, ...)
```

Arguments

x	A loess objects returned by <code>stats::loess()</code> .
data	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object x. Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the data argument. Augment will report information such as influence and cooks distance for data passed to the data argument. These measures are only defined for the original training data.
newdata	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create x. Defaults to NULL, indicating that nothing has been passed to newdata. If newdata is specified, the data argument will be ignored.
...	Arguments passed on to <code>stats::predict.loess</code>

object an object fitted by loess.

newdata an optional data frame in which to look for variables with which to predict, or a matrix or vector containing exactly the variables needs for prediction. If missing, the original data points are used.

se should standard errors be computed?

na.action function determining what should be done with missing values in data frame newdata. The default is to predict NA.

Details

When the modeling was performed with `na.action = "na.omit"` (as is the typical default), rows with NA in the initial data are omitted entirely from the augmented data frame. When the modeling was performed with `na.action = "na.exclude"`, one should provide the original data as a second argument, at which point the augmented data will contain those rows (typically with NAs in place of the new columns). If the original data is not provided to `augment()` and `na.action = "na.exclude"`, a warning is raised and the incomplete rows are dropped.

Value

When `newdata` is not supplied `augment.loess` returns one row for each observation with three columns added to the original data:

<code>.fitted</code>	Fitted values of model
<code>.se.fit</code>	Standard errors of the fitted values
<code>.resid</code>	Residuals of the fitted values

When `newdata` is supplied `augment.loess` returns one row for each observation with one additional column:

<code>.fitted</code>	Fitted values of model
<code>.se.fit</code>	Standard errors of the fitted values

See Also

[na.action](#)
[augment\(\)](#), [stats::loess\(\)](#), [stats::predict.loess\(\)](#)

Examples

```
lo <- loess(mpg ~ wt, mtcars)
augment(lo)

# with all columns of original data
augment(lo, mtcars)

# with a new dataset
augment(lo, newdata = head(mtcars))
```

augment.Mclust

Augment data with information from a(n) Mclust object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that all columns used to fit the model are present.

Augment will often behavior different depending on whether data or newdata is specified. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many augment methods provide default data arguments, so that `augment(fit)` will return the augmented training data. In these cases augment tries to reconstruct the original data based on the model object, with some varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'Mclust'
augment(x, data, ...)
```

Arguments

<code>x</code>	An Mclust object return from <code>mclust::Mclust()</code> .
<code>data</code>	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Value

A `tibble::tibble` of the original data with two extra columns:

<code>.class</code>	The class assigned by the Mclust algorithm
<code>.uncertainty</code>	The uncertainty associated with the classification. If a point has a probability of 0.9 of being in its assigned class under the model, then the uncertainty is 0.1.

See Also

`augment()`, `mclust::Mclust()`

Other mclust tidiers: `tidy.Mclust`

augment.mjoint *Augment data with information from a(n) mjoint object*

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that all columns used to fit the model are present.

Augment will often behavior different depending on whether `data` or `newdata` is specified. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases `augment` tries to reconstruct the original data based on the model object, with some varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'mjoint'
augment(x, data = x$data, ...)
```

Arguments

`x` An `mjoint` object returned from `joineRML::mjoint()`.

`data` A `data.frame()` or `tibble::tibble()` containing the original data that was used to produce the object `x`. Defaults to `stats::model.frame(x)` so that `augment(my_fit)` returns the augmented original data. **Do not** pass new data to the `data` argument. Augment will report information such as influence and cooks distance for data passed to the `data` argument. These measures are only defined for the original training data.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Details

See `joineRML::fitted.mjoint()` and `joineRML::residuals.mjoint()` for more information on the difference between population-level and individual-level fitted values and residuals.

If fitting a joint model with a single longitudinal process, make sure you are using a named list to define the formula for the fixed and random effects of the longitudinal submodel.

Value

A `tibble::tibble()` with one row for each original observation with addition columns:

<code>.fitted_j_0</code>	population-level fitted values for the j-th longitudinal process
<code>.fitted_j_1</code>	individuals-level fitted values for the j-th longitudinal process
<code>.resid_j_0</code>	population-level residuals for the j-th longitudinal process
<code>.resid_j_1</code>	individual-level residuals for the j-th longitudinal process

<code>augment.nlrq</code>	<i>Tidy a(n) nlrq object</i>
---------------------------	------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'nlrq'
augment(x, ...)
```

Arguments

<code>x</code>	A <code>nlrq</code> object returned from <code>quantreg::nlrq()</code> .
...	Arguments passed on to <code>augment.nls</code>

- data** A `data.frame()` or `tibble::tibble()` containing the original data that was used to produce the object `x`. Defaults to `stats::model.frame(x)` so that `augment(my_fit)` returns the augmented original data. **Do not** pass new data to the `data` argument. Augment will report information such as influence and cooks distance for data passed to the `data` argument. These measures are only defined for the original training data.
- newdata** A `data.frame()` or `tibble::tibble()` containing all the original predictors used to create `x`. Defaults to `NULL`, indicating that nothing has been passed to `newdata`. If `newdata` is specified, the `data` argument will be ignored.
- x** An `nls` object returned from `stats::nls()`.

Value

A `tibble::tibble()` containing the data passed to `augment`, and **additional** columns:

<code>.fitted</code>	The predicted response for that observation.
<code>.resid</code>	The residual for a particular point. Present only when data has been passed to <code>augment</code> via the <code>data</code> argument.

See Also

`augment()`, `quantreg::nlrq()`

Other `quantreg` tidiers: `augment.rqs`, `augment.rq`, `glance.nlrq`, `glance.rq`, `tidy.nlrq`, `tidy.rqs`, `tidy.rq`

augment.nls

Augment data with information from a(n) nls object

Description

`Augment` accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that all columns used to fit the model are present.

`Augment` will often behavior different depending on whether `data` or `newdata` is specified. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases `augment` tries to reconstruct the original data based on the model object, with some varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'nls'
augment(x, data = NULL, newdata = NULL, ...)
```

Arguments

<code>x</code>	An <code>nls</code> object returned from <code>stats::nls()</code> .
<code>data</code>	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
<code>newdata</code>	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create <code>x</code> . Defaults to <code>NULL</code> , indicating that nothing has been passed to <code>newdata</code> . If <code>newdata</code> is specified, the <code>data</code> argument will be ignored.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Value

A `tibble::tibble()` containing the data passed to `augment`, and **additional** columns:

<code>.fitted</code>	The predicted response for that observation.
<code>.resid</code>	The residual for a particular point. Present only when data has been passed to <code>augment</code> via the <code>data</code> argument.

See Also

`tidy`, `stats::nls()`, `stats::predict.nls()`

Other `nls` tidiers: `glance.nls`, `tidy.nls`

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to augment via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that all columns used to fit the model are present.

Augment will often behavior different depending on whether `data` or `newdata` is specified. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many augment methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases augment tries to reconstruct the original data based on the model object, with some varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'plm'
augment(x, data = model.frame(x), ...)
```

Arguments

<code>x</code>	A <code>plm</code> object returned by <code>plm::plm()</code> .
<code>data</code>	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be

used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

A `tibble::tibble()` containing the data passed to `augment`, and **additional** columns:

<code>.fitted</code>	The predicted response for that observation.
<code>.resid</code>	The residual for a particular point. Present only when data has been passed to <code>augment</code> via the <code>data</code> argument.

See Also

`augment()`, `plm::plm()`

Other plm tidiers: `glance.plm`, `tidy.plm`

augment.poLCA

Augment data with information from a(n) poLCA object

Description

`Augment` accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that all columns used to fit the model are present.

`Augment` will often behavior different depending on whether `data` or `newdata` is specified. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases `augment` tries to reconstruct the original data based on the model object, with some varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'poLCA'
augment(x, data = NULL, ...)
```

Arguments

`x` A poLCA object returned from `poLCA::poLCA()`.

`data` The original dataset used to fit the latent class model, as a tibble or data. If not given, uses manifest variables in `x$y` and, if applicable, covariates in `x$x`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

A `tibble::tibble` with one row for each original observation, with additional columns:

<code>.class</code>	Predicted class, using modal assignment
<code>.probability</code>	Posterior probability of predicted class

If the `data` argument is given, those columns are included in the output (only rows for which predictions could be made). Otherwise, the `y` element of the poLCA object, which contains the manifest variables used to fit the model, are used, along with any covariates, if present, in `x`.

Note that while the probability of all the classes (not just the predicted modal class) can be found in the posterior element, these are not included in the augmented output.

See Also

`augment()`, `poLCA::poLCA()`

Other poLCA tidiers: `glance.poLCA`, `tidy.poLCA`

`augment.prcomp`

Augment data with information from a(n) prcomp object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object.

Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that all columns used to fit the model are present.

Augment will often behavior different depending on whether `data` or `newdata` is specified. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many augment methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases `augment` tries to reconstruct the original data based on the model object, with some varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'prcomp'
augment(x, data = NULL, newdata, ...)
```

Arguments

<code>x</code>	A <code>prcomp</code> object returned by <code>stats::prcomp()</code> .
<code>data</code>	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
<code>newdata</code>	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create <code>x</code> . Defaults to <code>NULL</code> , indicating that nothing has been passed to <code>newdata</code> . If <code>newdata</code> is specified, the <code>data</code> argument will be ignored.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Value

A `tibble::tibble` containing the original data along with additional columns containing each observation's projection into PCA space.

See Also

[stats::prcomp\(\)](#), [svd_tidiers](#)

Other svd tidiers: [tidy.prcomp](#), [tidy_irlba](#), [tidy_svd](#)

augment.rlm

Augment a(n) rlm object

Description

This augment method wraps [augment.lm\(\)](#).

Usage

```
## S3 method for class 'rlm'
augment(x, ...)
```

Arguments

x An rlm object returned by [MASS::rlm\(\)](#).

... Arguments passed on to [augment.lm](#)

data A [data.frame\(\)](#) or [tibble::tibble\(\)](#) containing the original data that was used to produce the object x. Defaults to [stats::model.frame\(x\)](#) so that [augment\(my_fit\)](#) returns the augmented original data. **Do not** pass new data to the data argument. Augment will report information such as influence and cooks distance for data passed to the data argument. These measures are only defined for the original training data.

newdata A [data.frame\(\)](#) or [tibble::tibble\(\)](#) containing all the original predictors used to create x. Defaults to NULL, indicating that nothing has been passed to newdata. If newdata is specified, the data argument will be ignored.

type.predict Type of predictions to use when x is a glm object. Passed to [stats::predict.glm\(\)](#).

type.residuals Type of residuals to use when x is a glm object. Passed to [stats::residuals.glm\(\)](#).

x An lm object created by [stats::lm\(\)](#).

Details

For tidiers for models from the **robust** package see [tidy.lmRob\(\)](#) and [tidy.glmRob\(\)](#).

Value

When `newdata` is not supplied `augment.lm` returns one row for each observation, with seven columns added to the original data:

<code>.hat</code>	Diagonal of the hat matrix
<code>.sigma</code>	Estimate of residual standard deviation when corresponding observation is dropped from model
<code>.cooks</code>	Cooks distance, <code>cooks.distance()</code>
<code>.fitted</code>	Fitted values of model
<code>.se.fit</code>	Standard errors of fitted values
<code>.resid</code>	Residuals
<code>.std.resid</code>	Standardised residuals

Some unusual `lm` objects, such as `rlm` from MASS, may omit `.cooks` and `.std.resid`. `gam` from `mgcv` omits `.sigma`.

When `newdata` is supplied, returns one row for each observation, with three columns added to the new data:

<code>.fitted</code>	Fitted values of model
<code>.se.fit</code>	Standard errors of fitted values
<code>.resid</code>	Residuals of fitted values on the new data

See Also

[augment\(\)](#), [augment.lm\(\)](#)

[MASS::rlm\(\)](#)

Other `rlm` tidiers: [glance.rlm](#), [tidy.rlm](#)

`augment.rq`

Augment data with information from a(n) rq object

Description

`Augment` accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that all columns used to fit the model are present.

`Augment` will often behavior different depending on whether `data` or `newdata` is specified. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many augment methods provide default data arguments, so that `augment(fit)` will return the augmented training data. In these cases `augment` tries to reconstruct the original data based on the model object, with some varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'rq'
augment(x, data = model.frame(x), newdata = NULL, ...)
```

Arguments

<code>x</code>	An <code>rq</code> object returned from <code>quantreg::rq()</code> .
<code>data</code>	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
<code>newdata</code>	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create <code>x</code> . Defaults to <code>NULL</code> , indicating that nothing has been passed to <code>newdata</code> . If <code>newdata</code> is specified, the <code>data</code> argument will be ignored.
<code>...</code>	Arguments passed on to <code>quantreg::predict.rq</code>

object object of class `rq` or `rqs` or `rq.process` produced by `rq`

newdata An optional data frame in which to look for variables with which to predict. If omitted, the fitted values are used.

interval type of interval desired: default is 'none', when set to 'confidence' the function returns a matrix predictions with point predictions for each of the 'newdata' points as well as lower and upper confidence limits.

level coverage probability for the 'confidence' intervals.

type For `predict.rq`, the method for 'confidence' intervals, if desired. If 'percentile' then one of the bootstrap methods is used to generate percentile intervals for each prediction, if 'direct' then a version of the Portnoy and Zhou (1998) method is used, and otherwise an estimated covariance matrix for the parameter estimates is used. Further arguments to determine the choice of bootstrap method or covariance matrix estimate can be passed via the `...` argument. For `predict.rqs` and `predict.rq.process` when `stepfun = TRUE`, `type` is "Qhat", "Fhat" or "fhat" depending on whether the user would like to have estimates of the conditional quantile, distribution or density functions respectively. As noted below the two former

estimates can be monotized with the function `rearrange`. When the "fhat" option is invoked, a list of conditional density functions is returned based on Silverman's adaptive kernel method as implemented in `akj` and `approxfun`.

na.action function determining what should be done with missing values in 'newdata'. The default is to predict 'NA'.

Value

A `tibble::tibble` with one row per obseration and columns:

<code>.resid</code>	Residuals
<code>.fitted</code>	Fitted quantiles of the model
<code>.tau</code>	Quantile estimated

Depending on the arguments passed on to `predict.rq` via `...`, a confidence interval is also calculated on the fitted values resulting in columns:

<code>.conf.low</code>	Lower confidence interval value
<code>.conf.high</code>	Upper confidence interval value

`predict.rq` does not provide confidence intervals when `newdata` is provided.

See Also

`augment`, `quantreg::rq()`, `quantreg::predict.rq()`

Other `quantreg` tidiers: `augment.nlrq`, `augment.rqs`, `glance.nlrq`, `glance.rq`, `tidy.nlrq`, `tidy.rqs`, `tidy.rq`

`augment.rqs`

Augment data with information from a(n) rqs object

Description

`Augment` accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that all columns used to fit the model are present.

`Augment` will often behavior different depending on whether `data` or `newdata` is specified. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many augment methods provide default data arguments, so that `augment(fit)` will return the augmented training data. In these cases `augment` tries to reconstruct the original data based on the model object, with some varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'rqs'
augment(x, data = model.frame(x), newdata, ...)
```

Arguments

<code>x</code>	An <code>rqs</code> object returned from <code>quantreg::rq()</code> .
<code>data</code>	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. <code>augment</code> will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.
<code>newdata</code>	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create <code>x</code> . Defaults to <code>NULL</code> , indicating that nothing has been passed to <code>newdata</code> . If <code>newdata</code> is specified, the <code>data</code> argument will be ignored.
<code>...</code>	Arguments passed on to <code>quantreg::predict.rqs</code> object object of class <code>rq</code> or <code>rqs</code> or <code>rq.process</code> produced by <code>rq</code> newdata An optional data frame in which to look for variables with which to predict. If omitted, the fitted values are used. type For <code>predict.rq</code> , the method for 'confidence' intervals, if desired. If 'percentile' then one of the bootstrap methods is used to generate percentile intervals for each prediction, if 'direct' then a version of the Portnoy and Zhou (1998) method is used, and otherwise an estimated covariance matrix for the parameter estimates is used. Further arguments to determine the choice of bootstrap method or covariance matrix estimate can be passed via the <code>...</code> argument. For <code>predict.rqs</code> and <code>predict.rq.process</code> when <code>stepfun = TRUE</code> , <code>type</code> is "Qhat", "Fhat" or "fhat" depending on whether the user would like to have estimates of the conditional quantile, distribution or density functions respectively. As noted below the two former estimates can be monotonized with the function <code>rearrange</code> . When the "fhat" option is invoked, a list of conditional density functions is returned based on Silverman's adaptive kernel method as implemented in <code>akj</code> and <code>approxfun</code> .

stepfun If 'TRUE' return stepfunctions otherwise return matrix of predictions. these functions can be estimates of either the conditional quantile or distribution functions depending upon the type argument. When stepfun = FALSE a matrix of point estimates of the conditional quantile function at the points specified by the newdata argument.

na.action function determining what should be done with missing values in 'newdata'. The default is to predict 'NA'.

Value

A `tibble::tibble` with one row per obseration and columns:

<code>.resid</code>	Residuals
<code>.fitted</code>	Fitted quantiles of the model
<code>.tau</code>	Quantile estimated

Depending on the arguments passed on to `predict.rqs` via `...`, a confidence interval is also calculated on the fitted values resulting in columns:

<code>.conf.low</code>	Lower confidence interval value
<code>.conf.high</code>	Upper confidence interval value

`predict.rqs` does not provide confidence intervals when `newdata` is provided.

See Also

[augment](#), [quantreg::rq\(\)](#), [quantreg::predict.rqs\(\)](#)

Other `quantreg` tidiers: [augment.nlrq](#), [augment.rq](#), [glance.nlrq](#), [glance.rq](#), [tidy.nlrq](#), [tidy.rqs](#), [tidy.rq](#)

`augment.smooth.spline` *Tidy a(n) smooth.spline object*

Description

`Tidy` summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what `tidy` considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'smooth.spline'
augment(x, data = x$data, ...)
```

Arguments

x	A <code>smooth.spline</code> object returned from <code>stats::smooth.spline()</code> .
data	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object x. Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the data argument. Augment will report information such as influence and cooks distance for data passed to the data argument. These measures are only defined for the original training data.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A `tibble::tibble()` containing the data passed to `augment`, and **additional** columns:

<code>.fitted</code>	The predicted response for that observation.
<code>.resid</code>	The residual for a particular point. Present only when data has been passed to <code>augment</code> via the data argument.

See Also

`augment()`, `stats::smooth.spline()`, `stats::predict.smooth.spline()`

Other smoothing spline tidiers: `glance.smooth.spline`

Examples

```
spl <- smooth.spline(mtcars$wt, mtcars$mpg, df = 4)
augment(spl, mtcars)
augment(spl) # calls original columns x and y

library(ggplot2)
ggplot(augment(spl, mtcars), aes(wt, mpg)) +
  geom_point() + geom_line(aes(y = .fitted))
```

augment.speedlm

Augment data with information from a(n) speedlm object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to augment via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that all columns used to fit the model are present.

Augment will often behavior different depending on whether `data` or `newdata` is specified. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many augment methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases augment tries to reconstruct the original data based on the model object, with some varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'speedlm'
augment(x, data = model.frame(x), newdata = data,
  ...)
```

Arguments

<code>x</code>	A <code>speedlm</code> object returned from <code>speedglm::speedlm()</code> .
<code>data</code>	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object <code>x</code> . Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the <code>data</code> argument. Augment will report information such as influence and cooks distance for data passed to the <code>data</code> argument. These measures are only defined for the original training data.

`newdata` A `data.frame()` or `tibble::tibble()` containing all the original predictors used to create `x`. Defaults to `NULL`, indicating that nothing has been passed to `newdata`. If `newdata` is specified, the `data` argument will be ignored.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

A `tibble::tibble` containing the original data and one additional column `.fitted`.

See Also

`speedglm::speedlm()`

Other `speedlm` tidiers: `glance.speedlm`, `tidy.speedlm`

`augment.stl`

Augment data with information from a(n) stl object

Description

`Augment` accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to `augment` data that was not used during model fitting. This still requires that all columns used to fit the model are present.

`Augment` will often behavior different depending on whether `data` or `newdata` is specified. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases `augment` tries to reconstruct the original data based on the model object, with some varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a `tibble`. At this time, `tibbles` do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a `tibble`, or fitting the original model on data in a `tibble`.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'stl'
augment(x, weights = TRUE, ...)
```

Arguments

`x` An `stl` object returned from `stats::stl()`.

`weights` Logical indicating whether or not to include the robust weights in the output.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

A `tibble::tibble` with one row for each observation in the original times series:

<code>.seasonal</code>	The seasonal component of the decomposition.
<code>.trend</code>	The trend component of the decomposition.
<code>.remainder</code>	The remainder, or "random" component of the decomposition.
<code>.weight</code>	The final robust weights, if requested.
<code>.seasadj</code>	The seasonally adjusted (or "deseasonalised") series.

See Also

`augment()`, `stats::stl()`

Other decompose tidiers: `augment.decomposed.ts`

`augment.survreg`

Augment data with information from a(n) survreg object

Description

Augment accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that all columns used to fit the model are present.

Augment will often behavior different depending on whether data or newdata is specified. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many augment methods provide default data arguments, so that `augment(fit)` will return the augmented training data. In these cases augment tries to reconstruct the original data based on the model object, with some varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'survreg'
augment(x, data = NULL, newdata = NULL,
        type.predict = "response", type.residuals = "response", ...)
```

Arguments

x	An survreg object returned from <code>survival::survreg()</code> .
data	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing the original data that was used to produce the object x. Defaults to <code>stats::model.frame(x)</code> so that <code>augment(my_fit)</code> returns the augmented original data. Do not pass new data to the data argument. Augment will report information such as influence and cooks distance for data passed to the data argument. These measures are only defined for the original training data.
newdata	A <code>data.frame()</code> or <code>tibble::tibble()</code> containing all the original predictors used to create x. Defaults to NULL, indicating that nothing has been passed to newdata. If newdata is specified, the data argument will be ignored.
type.predict	Character indicating type of prediction to use. Passed to the type argument of the <code>stats::predict()</code> generic. Allowed arguments vary with model class, so be sure to read the <code>predict.my_class</code> documentation.
type.residuals	Character indicating type of residuals to use. Passed to the type argument of <code>stats::residuals()</code> generic. Allowed arguments vary with model class, so be sure to read the <code>residuals.my_class</code> documentation.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a newdata argument, it will use the default value for the data argument.

Details

When the modeling was performed with `na.action = "na.omit"` (as is the typical default), rows with NA in the initial data are omitted entirely from the augmented data frame. When the modeling was performed with `na.action = "na.exclude"`, one should provide the original data as a second argument, at which point the augmented data will contain those rows (typically with NAs in place of the new columns). If the original data is not provided to `augment()` and `na.action = "na.exclude"`, a warning is raised and the incomplete rows are dropped.

Value

A `tibble::tibble` with the passed data and additional columns:

<code>.fitted</code>	Fitted values of model
<code>.se.fit</code>	Standard errors of fitted values
<code>.resid</code>	Residuals

See Also

[na.action](#)

[augment\(\)](#), [survival::survreg\(\)](#)

Other survreg tidiers: [glance.survreg](#), [tidy.survreg](#)

Other survival tidiers: [augment.coxph](#), [glance.aareg](#), [glance.cch](#), [glance.coxph](#), [glance.pyears](#), [glance.survdiff](#), [glance.survexp](#), [glance.survfit](#), [glance.survreg](#), [tidy.aareg](#), [tidy.cch](#), [tidy.coxph](#), [tidy.pyears](#), [tidy.survdiff](#), [tidy.survexp](#), [tidy.survfit](#), [tidy.survreg](#)

<code>augment_columns</code>	<i>add fitted values, residuals, and other common outputs to an augment call</i>
------------------------------	--

Description

Add fitted values, residuals, and other common outputs to the value returned from `augment`.

Usage

```
augment_columns(x, data, newdata, type, type.predict = type,
  type.residuals = type, se.fit = TRUE, ...)
```

Arguments

<code>x</code>	a model
<code>data</code>	original data onto which columns should be added
<code>newdata</code>	new data to predict on, optional
<code>type</code>	Type of prediction and residuals to compute
<code>type.predict</code>	Type of prediction to compute; by default same as <code>type</code>

`type.residuals` Type of residuals to compute; by default same as `type`
`se.fit` Value to pass to `predict`'s `se.fit`, or `NULL` for no value
`...` extra arguments (not used)

Details

In the case that a residuals or influence generic is not implemented for the model, fail quietly.

`bootstrap` *Set up bootstrap replicates of a dplyr operation*

Description

The `bootstrap()` function is deprecated and will be removed from an upcoming release of broom. For tidy resampling, please use the `rsample` package instead.

Usage

```
bootstrap(df, m, by_group = FALSE)
```

Arguments

`df` a data frame
`m` number of bootstrap replicates to perform
`by_group` If `TRUE`, then bootstrap within each group if `df` is a grouped `tbl`.

Details

This code originates from Hadley Wickham (with a few small corrections) here:
<https://github.com/hadley/dplyr/issues/269>

Examples

```

## Not run:
library(dplyr)
mtcars %>% bootstrap(10) %>% do(tidy(lm(mpg ~ wt, .)))

## End(Not run)

```

brms_tidiers

*Tidying methods for a brms model***Description**

brms tidiers will soon be deprecated in broom and there is no ongoing development of these functions at this time. brms tidiers are being developed in the broom.mixed package, which is not yet on CRAN.

Usage

```
## S3 method for class 'brmsfit'
tidy(x, parameters = NA, par_type = c("all",
  "non-varying", "varying", "hierarchical"), robust = FALSE,
  intervals = TRUE, prob = 0.9, ...)
```

Arguments

x	Fitted model object from the brms package. See <code>brms::brmsfit-class()</code> .
parameters	Names of parameters for which a summary should be returned, as given by a character vector or regular expressions. If NA (the default) summarized parameters are specified by the par_type argument.
par_type	One of "all", "non-varying", "varying", or "hierarchical" (can be abbreviated). See the Value section for details.
robust	Whether to use median and median absolute deviation rather than mean and standard deviation.
intervals	If TRUE columns for the lower and upper bounds of posterior uncertainty intervals are included.
prob	Defines the range of the posterior uncertainty intervals, such that $100 * \text{prob}\%$ of the parameter's posterior distribution lies within the corresponding interval. Only used if intervals = TRUE.
...	Extra arguments, not used

Details

These methods tidy the estimates from `brms::brmsfit()` (fitted model objects from the **brms** package) into a summary.

Value

All tidying methods return a data.frame without rownames. The structure depends on the method chosen.

When parameters = NA, the par_type argument is used to determine which parameters to summarize.

Generally, tidy.brmsfit returns one row for each coefficient, with at least three columns:

term	The name of the model parameter.
estimate	A point estimate of the coefficient (mean or median).
std.error	A standard error for the point estimate (sd or mad).

When `par_type = "non-varying"`, only population-level effects are returned.

When `par_type = "varying"`, only group-level effects are returned. In this case, two additional columns are added:

group	The name of the grouping factor.
level	The name of the level of the grouping factor.

Specifying `par_type = "hierarchical"` selects the standard deviations and correlations of the group-level parameters.

If `intervals = TRUE`, columns for the lower and upper bounds of the posterior intervals computed.

See Also

[brms::brms\(\)](#), [brms::brmsfit\(\)](#)

Examples

```
## Not run:
library(brms)
fit <- brm(mpg ~ wt + (1|cyl) + (1+wt|gear), data = mtcars,
          iter = 500, chains = 2)
tidy(fit)
tidy(fit, parameters = "^sd_", intervals = FALSE)
tidy(fit, par_type = "non-varying")
tidy(fit, par_type = "varying")
tidy(fit, par_type = "hierarchical", robust = TRUE)

## End(Not run)
```

broom

Convert Statistical Objects into Tidy Tibbles

Description

Convert statistical analysis objects from R into tidy tibbles, so that they can more easily be combined, reshaped and otherwise processed with tools like `dplyr`, `tidyr` and `ggplot2`. The package provides three S3 generics: `tidy`, which summarizes a model's statistical findings such as coefficients of a regression; `augment`, which adds columns to the original data such as predictions, residuals and cluster assignments; and `glance`, which provides a one-row summary of model-level statistics.

column_glossary	<i>Allowed column names in tidied tibbles</i>
-----------------	---

Description

Allowed column names in tidied tibbles

Usage

```
column_glossary
```

Format

A tibble with 4 variables:

method One of "glance", "augment" or "tidy".

column Character name of allowed output column.

description Character description of expected column contents.

used_by A list of character vectors detailing the *classes* that use the column when tidied. For example `c("Arima", "betareg")`.

Examples

```
column_glossary
```

confint_tidy	<i>Calculate confidence interval as a tidy data frame</i>
--------------	---

Description

Return a confidence interval as a tidy data frame. This directly wraps the `confint()` function, but ensures it follows broom conventions: column names of `conf.low` and `conf.high`, and no row names.

Usage

```
confint_tidy(x, conf.level = 0.95, func = stats::confint, ...)
```

Arguments

<code>x</code>	a model object for which <code>confint()</code> can be calculated
<code>conf.level</code>	confidence level
<code>func</code>	A function to compute a confidence interval for <code>x</code> . Calling <code>func(x, level = conf.level, ...)</code> must return an object coercable to a tibble. This dataframe like object should have to columns corresponding the lower and upper bounds on the confidence interval.
<code>...</code>	extra arguments passed on to <code>confint</code>

Details

confint_tidy

Value

A tibble with two columns: `conf.low` and `conf.high`.

See Also

[confint](#)

data.frame_tidiers *Tidiers for data.frame objects*

Description

Data frame tidiers are deprecated and will be removed from an upcoming release of broom.

Usage

```
## S3 method for class 'data.frame'
tidy(x, ..., na.rm = TRUE, trim = 0.1)
```

```
## S3 method for class 'data.frame'
glance(x, ...)
```

Arguments

<code>x</code>	A data.frame
<code>...</code>	Additional arguments for other methods.
<code>na.rm</code>	a logical value indicating whether NA values should be stripped before the computation proceeds.
<code>trim</code>	the fraction (0 to 0.5) of observations to be trimmed from each end of <code>x</code> before the mean is computed. Passed to the <code>trim</code> argument of <code>mean()</code>
<code>data</code>	data, not used

Details

These perform tidy summaries of data.frame objects. `tidy` produces summary statistics about each column, while `glance` simply reports the number of rows and columns. Note that `augment.data.frame` will throw an error.

Value

`tidy.data.frame` produces a data frame with one row per original column, containing summary statistics of each:

<code>column</code>	name of original column
<code>n</code>	Number of valid (non-NA) values
<code>mean</code>	mean
<code>sd</code>	standard deviation
<code>median</code>	median
<code>trimmed</code>	trimmed mean, with trim defaulting to .1
<code>mad</code>	median absolute deviation (from the median)
<code>min</code>	minimum value
<code>max</code>	maximum value
<code>range</code>	range
<code>skew</code>	skew
<code>kurtosis</code>	kurtosis
<code>se</code>	standard error

`glance` returns a one-row data.frame with

<code>nrow</code>	number of rows
<code>ncol</code>	number of columns
<code>complete.obs</code>	number of rows that have no missing values
<code>na.fraction</code>	fraction of values across all rows and columns that are missing

Author(s)

David Robinson, Benjamin Nutter

Source

Skew and Kurtosis functions are adapted from implementations in the `moments` package: Lukasz Komsta and Frederick Novomestky (2015). `moments`: Moments, cumulants, skewness, kurtosis and related tests. R package version 0.14.
<https://CRAN.R-project.org/package=moments>

Examples

```
## Not run:
td <- tidy(mtcars)
td

glance(mtcars)

library(ggplot2)
```

```
# compare mean and standard deviation
ggplot(td, aes(mean, sd)) + geom_point() +
  geom_text(aes(label = column), hjust = 1, vjust = 1) +
  scale_x_log10() + scale_y_log10() + geom_abline()

## End(Not run)
```

durbinWatsonTest_tidiers

Tidy/glance a(n) durbinWatsonTest object

Description

For models that have only a single component, the `tidy()` and `glance()` methods are identical. Please see the documentation for both of those methods.

Usage

```
## S3 method for class 'durbinWatsonTest'
tidy(x, ...)

## S3 method for class 'durbinWatsonTest'
glance(x, ...)
```

Arguments

<code>x</code>	An object of class <code>durbinWatsonTest</code> created by a call to <code>car::durbinWatsonTest()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A one-row `tibble::tibble` with columns:

<code>statistic</code>	Test statistic for Durbin-Watson test.
<code>p.value</code>	P-value of test statistic.
<code>autocorrelation</code>	Residual autocorrelations.
<code>method</code>	Always "Durbin-Watson Test".
<code>alternative</code>	Alternative hypothesis (character).

See Also

[tidy\(\)](#), [glance\(\)](#), [car::durbinWatsonTest\(\)](#)

Examples

```
dw <- car::durbinWatsonTest(lm(mpg ~ wt, data = mtcars))
tidy(dw)
glance(dw) # same output for all durbinWatsonTests
```

emmeans_tidiers	<i>Tidy estimated marginal means (least-squares means) objects from the emmeans and lsmeans packages</i>
-----------------	--

Description

Tidiers for estimated marginal means objects, which report the predicted means for factors or factor combinations in a linear model. This covers three classes: `emmGrid`, `lsmobj`, and `ref.grid`. (The first class is from the `emmeans` package, and is the successor to the latter two classes, which have slightly different purposes within the `lsmeans` package but have similar output).

Usage

```
## S3 method for class 'lsmobj'
tidy(x, conf.level = 0.95, ...)

## S3 method for class 'ref.grid'
tidy(x, ...)

## S3 method for class 'emmGrid'
tidy(x, ...)
```

Arguments

<code>x</code>	"emmGrid", "lsmobj", or "ref.grid" object
<code>conf.level</code>	Level of confidence interval, used only for <code>emmGrid</code> and <code>lsmobj</code> objects
<code>...</code>	Additional arguments passed to emmeans::summary.emmGrid() or lsmeans::summary.ref.grid() . Cautionary note: misspecified arguments may be silently ignored!

Details

There are a large number of arguments that can be passed on to [emmeans::summary.emmGrid\(\)](#) or [lsmeans::summary.ref.grid\(\)](#). By broom convention, we use `conf.level` to pass the `level` argument.

Value

A data frame with one observation for each estimated mean, and one column for each combination of factors, along with the following variables:

estimate	Estimated least-squares mean
std.error	Standard error of estimate
df	Degrees of freedom
conf.low	Lower bound of confidence interval
conf.high	Upper bound of confidence interval

When the input is a contrast, each row will contain one estimated contrast, along with some of the following columns:

level1	One level of the factor being contrasted
level2	Second level
contrast	In cases where the contrast is not made up of two levels, describes each
statistic	T-ratio statistic
p.value	P-value

Examples

```
if (require("emmeans", quietly = TRUE)) {
  # linear model for sales of oranges per day
  oranges_lm1 <- lm(sales1 ~ price1 + price2 + day + store, data = oranges)

  # reference grid; see vignette("basics", package = "emmeans")
  oranges_rg1 <- ref_grid(oranges_lm1)
  td <- tidy(oranges_rg1)
  td

  # marginal averages
  marginal <- emmeans(oranges_rg1, "day")
  tidy(marginal)

  # contrasts
  tidy(contrast(marginal))
  tidy(contrast(marginal, method = "pairwise"))

  # plot confidence intervals
  library(ggplot2)
  ggplot(tidy(marginal), aes(day, estimate)) +
    geom_point() +
    geom_errorbar(aes(ymin = conf.low, ymax = conf.high))

  # by multiple prices
  by_price <- emmeans(oranges_lm1, "day", by = "price2",
    at = list(price1 = 50, price2 = c(40, 60, 80),
    day = c("2", "3", "4")) )
}
```

```

by_price
tidy(by_price)

ggplot(tidy(by_price), aes(price2, estimate, color = day)) +
  geom_line() +
  geom_errorbar(aes(ymin = conf.low, ymax = conf.high))
}

```

finish_glance	<i>Add logLik, AIC, BIC, and other common measurements to a glance of a prediction</i>
---------------	--

Description

A helper function for several functions in the glance generic. Methods such as logLik, AIC, and BIC are defined for many prediction objects, such as lm, glm, and nls. This is a helper function that adds them to a glance data.frame can be performed. If any of them cannot be computed, it fails quietly.

Usage

```
finish_glance(ret, x)
```

Arguments

ret	a one-row data frame (a partially complete glance)
x	the prediction model

Details

In one special case, deviance for objects of the lmerMod class from lme4 is computed with deviance(x, REML=FALSE).

Value

a one-row data frame with additional columns added, such as

logLik	log likelihoods
AIC	Akaike Information Criterion
BIC	Bayesian Information Criterion
deviance	deviance
df.residual	residual degrees of freedom

Each of these are produced by the corresponding generics

fix_data_frame	<i>Ensure an object is a data frame, with rownames moved into a column</i>
----------------	--

Description

Ensure an object is a data frame, with rownames moved into a column

Usage

```
fix_data_frame(x, newnames = NULL, newcol = "term")
```

Arguments

x	a data.frame or matrix
newnames	new column names, not including the rownames
newcol	the name of the new rownames column

Value

a data.frame, with rownames moved into a column and new column names assigned

glance.aareg	<i>Glance at a(n) aareg object</i>
--------------	------------------------------------

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'aareg'
glance(x, ...)
```

Arguments

`x` An aareg object returned from `survival::aareg()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the data argument.

Value

A one-row `tibble::tibble` with columns:

<code>statistic</code>	chi-squared statistic
<code>p.value</code>	p-value based on chi-squared statistic
<code>df</code>	degrees of freedom used by coefficients

See Also

`glance()`, `survival::aareg()`

Other aareg tidiers: `tidy.aareg`

Other survival tidiers: `augment.coxph`, `augment.survreg`, `glance.cch`, `glance.coxph`, `glance.pyears`, `glance.survdiff`, `glance.survexp`, `glance.survfit`, `glance.survreg`, `tidy.aareg`, `tidy.cch`, `tidy.coxph`, `tidy.pyears`, `tidy.survdiff`, `tidy.survexp`, `tidy.survfit`, `tidy.survreg`

`glance.Arima`

Glance at a(n) Arima object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'Arima'
glance(x, ...)
```

Arguments

`x` An object of class `Arima` created by `stats::arima()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

A one-row `tibble::tibble` with columns:

<code>sigma</code>	the square root of the estimated residual variance
<code>logLik</code>	the data's log-likelihood under the model
<code>AIC</code>	the Akaike Information Criterion
<code>BIC</code>	the Bayesian Information Criterion

See Also

`stats::arima()`

Other Arima tidiers: `tidy.Arima`

<code>glance.betareg</code>	<i>Glance at a(n) betareg object</i>
-----------------------------	--------------------------------------

Description

`Glance` accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

`Glance` never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

`Glance` does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'betareg'
glance(x, ...)
```

Arguments

`x` A betareg object produced by a call to `betareg::betareg()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

`glance` returns a one-row tibble with columns:

<code>pseudo.r.squared</code>	the deviance of the null model
<code>logLik</code>	the data's log-likelihood under the model
<code>AIC</code>	the Akaike Information Criterion
<code>BIC</code>	the Bayesian Information Criterion
<code>df.residual</code>	residual degrees of freedom
<code>df.null</code>	degrees of freedom under the null

See Also

`glance()`, `betareg::betareg()`

Examples

```
library(betareg)

data("GasolineYield", package = "betareg")

mod <- betareg(yield ~ batch + temp, data = GasolineYield)

mod
tidy(mod)
tidy(mod, conf.int = TRUE)
tidy(mod, conf.int = TRUE, conf.level = .99)

augment(mod)

glance(mod)
```

glance.biglm	<i>Glance at a(n) biglm object</i>
--------------	------------------------------------

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'biglm'
glance(x, ...)
```

Arguments

x	A biglm object created by a call to <code>biglm::biglm()</code> or <code>biglm::bigglm()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Value

`glance.biglm` returns a one-row data frame, with columns

<code>r.squared</code>	The percent of variance explained by the model
<code>AIC</code>	the Akaike Information Criterion
<code>deviance</code>	deviance
<code>df.residual</code>	residual degrees of freedom

See Also

`glance()`, `biglm::biglm()`, `biglm::bigglm()`

Other biglm tidiers: `tidy.biglm`

glance.binDesign	<i>Glance at a(n) binDesign object</i>
------------------	--

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'binDesign'
glance(x, ...)
```

Arguments

x	A <code>binGroup::binDesign</code> object.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A one-row `tibble::tibble` with columns:

power	Power achieved by the analysis.
n	Sample size used to achieve this power.
power.reached	Whether the desired power was reached.
maxit	Number of iterations performed.

See Also

`glance()`, `binGroup::binDesign()`

Other bingroup tidiers: `tidy.binDesign`, `tidy.binWidth`

Examples

```
if (require("binGroup", quietly = TRUE)) {
  des <- binDesign(nmax = 300, delta = 0.06,
                  p.hyp = 0.1, power = .8)

  glance(des)
  tidy(des)

  # the ggplot2 equivalent of plot(des)
  library(ggplot2)
  ggplot(tidy(des), aes(n, power)) +
    geom_line()
}
```

glance.cch

Glance at a(n) cch object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'cch'
glance(x, ...)
```

Arguments

`x` An cch object returned from `survival::cch()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the data argument.

Value

A one-row `tibble::tibble` with columns:

score	score
rscore	rscore
p.value	p-value from Wald test
iter	number of iterations
n	number of predictions
nevent	number of events

See Also

`glance()`, `survival::cch()`

Other cch tidiers: `glance.survfit`, `tidy.cch`

Other survival tidiers: `augment.coxph`, `augment.survreg`, `glance.aareg`, `glance.coxph`, `glance.pyyears`, `glance.survdiff`, `glance.survexp`, `glance.survfit`, `glance.survreg`, `tidy.aareg`, `tidy.cch`, `tidy.coxph`, `tidy.pyyears`, `tidy.survdiff`, `tidy.survexp`, `tidy.survfit`, `tidy.survreg`

<code>glance.coxph</code>	<i>Glance at a(n) coxph object</i>
---------------------------	------------------------------------

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'coxph'
glance(x, ...)
```

Arguments

`x` A coxph object returned from `survival::coxph()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

A one-row `tibble::tibble` with columns: TODO.

See Also

`glance()`, `survival::coxph()`

Other coxph tidiers: `augment.coxph`, `tidy.coxph`

Other survival tidiers: `augment.coxph`, `augment.survreg`, `glance.aareg`, `glance.cch`, `glance.pyears`, `glance.survdiff`, `glance.survexp`, `glance.survfit`, `glance.survreg`, `tidy.aareg`, `tidy.cch`, `tidy.coxph`, `tidy.pyears`, `tidy.survdiff`, `tidy.survexp`, `tidy.survfit`, `tidy.survreg`

`glance.cv.glmnet`

Glance at a(n) cv.glmnet object

Description

`Glance` accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

`Glance` never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

`Glance` does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'cv.glmnet'
glance(x, ...)
```

Arguments

`x` A `cv.glmnet` object returned from `glmnet::cv.glmnet()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

A `tibble::tibble` with one-row with columns:

`lambda.min` The value of the penalization parameter `lambda` that achieved minimum loss as estimated by cross validation.

`lambda.1se` The value of the penalization parameter `lambda` that results in the sparsest model while remaining within one standard error of the minimum loss.

See Also

`glance()`, `glmnet::cv.glmnet()`

Other `glmnet` tidiers: `glance.glmnet`, `tidy.cv.glmnet`, `tidy.glmnet`

`glance.ergm`

Glance at a(n) ergm object

Description

`Glance` accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

`Glance` never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

`Glance` does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'ergm'
glance(x, deviance = FALSE, mcmc = FALSE, ...)
```

Arguments

x	An ergm object returned from a call to <code>ergm::ergm()</code> .
deviance	Logical indicating whether or not to report null and residual deviance for the model, as well as degrees of freedom. Defaults to FALSE.
mcmc	Logical indicating whether or not to report MCMC interval, burn-in and sample size used to estimate the model. Defaults to FALSE.
...	Additional arguments to pass to <code>ergm::summary()</code> . Cautionary note: Mispecified arguments may be silently ignored.

Value

`glance.ergm` returns a one-row data.frame with the columns

independence	Whether the model assumed dyadic independence
iterations	The number of MCMLE iterations performed before convergence
logLik	If applicable, the log-likelihood associated with the model
AIC	The Akaike Information Criterion
BIC	The Bayesian Information Criterion

If `deviance = TRUE`, and if the model supports it, the data frame will also contain the columns

null.deviance	The null deviance of the model
df.null	The degrees of freedom of the null deviance
residual.deviance	The residual deviance of the model
df.residual	The degrees of freedom of the residual deviance

See Also

`glance()`, `ergm::ergm()`, `ergm::summary.ergm()`

Other ergm tidiers: `tidy.ergm`

`glance.factanal` *Glance at a(n) factanal object*

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'factanal'
glance(x, ...)
```

Arguments

`x` A factanal object created by `stats::factanal()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

A one-row `tibble::tibble` with columns:

<code>n.factors</code>	The number of fitted factors
<code>total.variance</code>	Total cumulative proportion of variance accounted for by all factors
<code>statistic</code>	Significance-test statistic
<code>p.value</code>	p-value from the significance test, describing whether the covariance matrix estimated from the factors is significantly different from the observed covariance matrix
<code>df</code>	Degrees of freedom used by the factor analysis
<code>n</code>	Sample size used in the analysis
<code>method</code>	The estimation method; always Maximum Likelihood, "mle"
<code>converged</code>	Whether the factor analysis converged

See Also

`glance()`, `stats::factanal()`

Other factanal tidiers: `augment.factanal`, `tidy.factanal`

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'felm'
glance(x, ...)
```

Arguments

`x` A `felm` object returned from `lfe::felm()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the data argument.

Value

A one-row `tibble::tibble` with columns:

<code>r.squared</code>	The percent of variance explained by the model
<code>adj.r.squared</code>	<code>r.squared</code> adjusted based on the degrees of freedom
<code>sigma</code>	The square root of the estimated residual variance
<code>statistic</code>	F-statistic
<code>p.value</code>	p-value from the F test
<code>df</code>	Degrees of freedom used by the coefficients
<code>df.residual</code>	residual degrees of freedom

glance.fitdistr	<i>Glance at a(n) fitdistr object</i>
-----------------	---------------------------------------

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'fitdistr'
glance(x, ...)
```

Arguments

x	A fitdistr object returned by <code>MASS::fitdistr()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Value

A one-row `tibble::tibble` with columns:

n	Number of observations used in estimation
logLik	log-likelihood of estimated data
AIC	Akaike Information Criterion
BIC	Bayesian Information Criterion

See Also

`tidy()`, `MASS::fitdistr()`

Other fitdistr tidiers: `tidy.fitdistr`

glance.Gam

Glance at a(n) Gam object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'Gam'
glance(x, ...)
```

Arguments

`x` A Gam object returned from a call to `gam::gam()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the data argument.

Details

Glance at gam objects created by calls to `mgcv::gam()` with `glance.gam()`.

Value

A one-row `tibble::tibble` with columns:

<code>logLik</code>	Log-likelihood of the model.
<code>AIC</code>	Akaike's Information Criterion for the model.
<code>BIC</code>	Bayesian Information Criterion for the model.
<code>deviance</code>	Deviance of the model.
<code>df.residual</code>	Residual degrees of freedom for the model.

See Also

[glance\(\)](#), [gam::gam\(\)](#)

Other gam tidiers: [tidy.Gam](#)

glance.gam

Glance at a(n) gam object

Description

Glance accepts a model object and returns a [tibble::tibble\(\)](#) with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'gam'
glance(x, ...)
```

Arguments

x	A gam object returned from a call to mgcv::gam() .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an augment() method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Details

To glance Gam objects created by calls to [gam::gam\(\)](#), see [glance.Gam\(\)](#).

Value

A one-row [tibble::tibble](#) with columns:

logLik	Log-likelihood of the model.
AIC	Akaike's Information Criterion for the model.
BIC	Bayesian Information Criterion for the model.
deviance	Deviance of the model.
df.residual	Residual degrees of freedom for the model.

See Also

[glance\(\)](#), [mgcv::gam\(\)](#), [glance.Gam\(\)](#)

Other mgcv tidiers: [tidy.gam](#)

glance.garch	<i>Tidy a(n) garch object</i>
--------------	-------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'garch'
glance(x, test = c("box-ljung-test", "jarque-bera-test"),
  ...)
```

Arguments

x	A garch object returned by tseries::garch() .
test	Character specification of which hypothesis test to use. The garch function reports 2 hypothesis tests: Jarque-Bera to residuals and Box-Ljung to squared residuals.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an augment() method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A one-row [tibble::tibble](#) with columns:

statistic	Test statistic used to compute the p-value
p.value	P-value
parameter	Parameter field in the htest, typically degrees of freedom
method	Method used to compute the statistic as a string
logLik	the data's log-likelihood under the model
AIC	the Akaike Information Criterion
BIC	the Bayesian Information Criterion

See Also

[glance\(\)](#), [tseries::garch\(\)](#), []
 Other garch tidiers: [tidy.garch](#)

glance.glm

*Glance at a(n) glm object***Description**

Glance accepts a model object and returns a [tibble::tibble\(\)](#) with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'glm'
glance(x, ...)
```

Arguments

`x` A glm object returned from [stats::glm\(\)](#).
`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an [augment\(\)](#) method that does not accept a `newdata` argument, it will use the default value for the data argument.

Value

A one-row [tibble::tibble](#) with columns:

<code>null.deviance</code>	the deviance of the null model
<code>df.null</code>	the residual degrees of freedom for the null model
<code>logLik</code>	the data's log-likelihood under the model
<code>AIC</code>	the Akaike Information Criterion
<code>BIC</code>	the Bayesian Information Criterion
<code>deviance</code>	deviance
<code>df.residual</code>	residual degrees of freedom

See Also

`stats::glm()`

Other lm tidiers: `augment.glm`, `augment.lm`, `glance.lm`, `tidy.glm`, `tidy.lm`

Examples

```
g <- glm(am ~ mpg, mtcars, family = "binomial")
glance(g)
```

glance.glmnet

Glance at a(n) glmnet object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'glmnet'
glance(x, ...)
```

Arguments

`x` A `glmnet` object returned from `glmnet::glmnet()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the data argument.

Value

A one-row `tibble::tibble` with columns:

<code>nulldev</code>	null deviance
<code>npasses</code>	total passes over the data across all lambda values

See Also

[glance\(\)](#), [glmnet::glmnet\(\)](#)

Other glmnet tidiers: [glance.cv.glmnet](#), [tidy.cv.glmnet](#), [tidy.glmnet](#)

`glance.glmRob`

Glance at a(n) glmRob object

Description

Glance accepts a model object and returns a [tibble::tibble\(\)](#) with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'glmRob'
glance(x, ...)
```

Arguments

`x` A `glmRob` object returned from [robust::glmRob\(\)](#).

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an [augment\(\)](#) method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

A one-row [tibble::tibble](#) with columns:

<code>deviance</code>	Robust deviance
<code>null.deviance</code>	Deviance under the null model
<code>df.residual</code>	Number of residual degrees of freedom

See Also

[robust::glmRob\(\)](#)

Other robust tidiers: [augment.glmRob](#), [augment.lmRob](#), [glance.lmRob](#), [tidy.glmRob](#), [tidy.lmRob](#)

glance.gmm

Glance at a(n) gmm object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'gmm'
glance(x, ...)
```

Arguments

`x` A gmm object returned from `gmm::gmm()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

A one-row `tibble::tibble` with columns:

<code>df</code>	Degrees of freedom
<code>statistic</code>	Statistic from J-test for $E(g)=0$
<code>p.value</code>	P-value from J-test
<code>df.residual</code>	Residual degrees of freedom, if included in <code>x</code> .

See Also

`glance()`, `gmm::gmm()`

Other gmm tidiers: `tidy.gmm`

glance.ivreg	<i>Glance at a(n) ivreg object</i>
--------------	------------------------------------

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'ivreg'
glance(x, diagnostics = FALSE, ...)
```

Arguments

x	An ivreg object created by a call to <code>AER::ivreg()</code> .
diagnostics	Logical indicating whether to include statistics and p-values for Sargan, Wu-Hausman and weak instrument tests. Defaults to FALSE.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A one-row tibble with columns

r.squared	The percent of variance explained by the model
adj.r.squared	r.squared adjusted based on the degrees of freedom
sigma	The square root of the estimated residual variance
statistic	Wald test statistic
p.value	p-value from the Wald test
df	Degrees of freedom used by the coefficients
df.residual	residual degrees of freedom

If `diagnostics = TRUE`, will also return the following columns:

```
statistic.Sargan      Statistic for Sargan test
p.value.Sargan       P-value for Sargan test
statistic.Wu.Hausman  Statistic for Wu-Hausman test
p.value.Wu.Hausman   P-value for Wu-Hausman test
statistic.weakinst   Statistic for Wu-Hausman test
p.value.weakinst     P-value for weak instruments test
```

See Also

[glance\(\)](#), [AER::ivreg\(\)](#)

Other ivreg tidiers: [augment.ivreg](#), [tidy.ivreg](#)

Examples

```
library(AER)

data("CigarettesSW", package = "AER")
ivr <- ivreg(
  log(packs) ~ income | population,
  data = CigarettesSW,
  subset = year == "1995"
)

summary(ivr)

tidy(ivr)
tidy(ivr, conf.int = TRUE)
tidy(ivr, conf.int = TRUE, exponentiate = TRUE)

augment(ivr)

glance(ivr)
```

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'kmeans'
glance(x, ...)
```

Arguments

<code>x</code>	A kmeans object created by <code>stats::kmeans()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A one-row `tibble::tibble` with columns:

<code>totss</code>	The total sum of squares
<code>tot.withinss</code>	The total within-cluster sum of squares
<code>betweenss</code>	The total between-cluster sum of squares
<code>iter</code>	The number of (outer) iterations

See Also

`glance()`, `stats::kmeans()`

Other kmeans tidiers: `augment.kmeans`, `tidy.kmeans`

glance.lavaan *Glance at a(n) lavaan object*

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'lavaan'
glance(x, ...)
```

Arguments

`x` A lavaan object, such as those return from `lavaan::cfa()`, and `lavaan::sem()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the data argument.

Value

A one-row `tibble::tibble` with columns:

<code>chisq</code>	Model chi squared
<code>npar</code>	Number of parameters in the model
<code>rmsea</code>	Root mean square error of approximation
<code>rmsea.conf.high</code>	95 percent upper bound on RMSEA
<code>srmr</code>	Standardised root mean residual
<code>agfi</code>	Adjusted goodness of fit
<code>cfi</code>	Comparative fit index
<code>tli</code>	Tucker Lewis index
<code>aic</code>	Akaike information criterion

bic	Bayesian information criterion
ngroups	Number of groups in model
nobs	Number of observations included
norig	Number of observation in the original dataset
nexcluded	Number of excluded observations
converged	Logical - Did the model converge
estimator	Estimator used
missing_method	Method for eliminating missing data

For further recommendations on reporting SEM and CFA models see Schreiber, J. B. (2017). Update to core reporting practices in structural equation modeling. *Research in Social and Administrative Pharmacy*, 13(3), 634-643. <https://doi.org/10.1016/j.sapharm.2016.06.006>

See Also

[glance\(\)](#), [lavaan::cfa\(\)](#), [lavaan::sem\(\)](#), [lavaan::fitmeasures\(\)](#)

Other lavaan tidiers: [tidy.lavaan](#)

Examples

```
if (require("lavaan", quietly = TRUE)) {
  library(lavaan)

  cfa.fit <- cfa(
    'F =~ x1 + x2 + x3 + x4 + x5',
    data = HolzingerSwineford1939, group = "school"
  )
  glance(cfa.fit)
}
```

glance.lm

Glance at a(n) lm object

Description

Glance accepts a model object and returns a [tibble::tibble\(\)](#) with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'lm'
glance(x, ...)

## S3 method for class 'summary.lm'
glance(x, ...)
```

Arguments

`x` An `lm` object created by `stats::lm()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

A one-row `tibble::tibble` with columns:

<code>r.squared</code>	The percent of variance explained by the model
<code>adj.r.squared</code>	<code>r.squared</code> adjusted based on the degrees of freedom
<code>sigma</code>	The square root of the estimated residual variance
<code>statistic</code>	F-statistic
<code>p.value</code>	p-value from the F test, describing whether the full regression is significant
<code>df</code>	Degrees of freedom used by the coefficients
<code>logLik</code>	the data's log-likelihood under the model
<code>AIC</code>	the Akaike Information Criterion
<code>BIC</code>	the Bayesian Information Criterion
<code>deviance</code>	deviance
<code>df.residual</code>	residual degrees of freedom

See Also

[glance\(\)](#)

Other `lm` tidiers: [augment.glm](#), [augment.lm](#), [glance.glm](#), [tidy.glm](#), [tidy.lm](#)

glance.lmodel2	<i>Glance at a(n) lmodel2 object</i>
----------------	--------------------------------------

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'lmodel2'
glance(x, ...)
```

Arguments

x	A lmodel2 object returned by <code>lmodel2::lmodel2()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Value

A one-row `tibble::tibble` with columns:

r.squared	OLS R-squared
p.value	OLS parametric p-value
theta	Angle between OLS lines $lm(y \sim x)$ and $lm(x \sim y)$
H	H statistic for computing confidence interval of major axis slope

See Also

`glance()`, `lmodel2::lmodel2()`

Other lmodel2 tidiers: `tidy.lmodel2`

glance.lmRob

Glance at a(n) lmRob object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'lmRob'
glance(x, ...)
```

Arguments

<code>x</code>	A <code>lmRob</code> object returned from <code>robust::lmRob()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Value

A one-row `tibble::tibble` with columns:

<code>r.squared</code>	R-squared
<code>deviance</code>	Robust deviance
<code>sigma</code>	Residual scale estimate
<code>df.residual</code>	Number of residual degrees of freedom

See Also

`robust::lmRob()`

Other robust tidiers: `augment.glmRob`, `augment.lmRob`, `glance.glmRob`, `tidy.glmRob`, `tidy.lmRob`

glance.Mclust	<i>Glance at a(n) Mclust object</i>
---------------	-------------------------------------

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'Mclust'
glance(x, ...)
```

Arguments

x	An Mclust object return from <code>mclust::Mclust()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A one-row `tibble::tibble` with columns:

model	A character string denoting the model at which the optimal BIC occurs
n	The number of observations in the data
G	The optimal number of mixture components
BIC	The optimal BIC value
logLik	The log-likelihood corresponding to the optimal BIC
df	The number of estimated parameters
hypvol	If the other model contains a noise component, the value of the hypervolume parameter. Otherwise NA.

glance.mjoint

Glance at a(n) mjoint object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'mjoint'
glance(x, ...)
```

Arguments

`x` An `mjoint` object returned from `joineRML::mjoint()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

A one-row `tibble::tibble` with columns:

<code>sigma2_j</code>	the square root of the estimated residual variance for the <code>j</code> -th longitudinal process
<code>AIC</code>	the Akaike Information Criterion
<code>BIC</code>	the Bayesian Information Criterion
<code>logLik</code>	the data's log-likelihood under the model

See Also

`glance()`, `joineRML::mjoint()`

Other `mjoint` tidiers: `tidy.mjoint`

glance.muhaz

*Glance at a(n) muhaz object***Description**

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'muhaz'
glance(x, ...)
```

Arguments

`x` A muhaz object returned by `muhaz::muhaz()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the data argument.

Value

A one-row `tibble::tibble` with columns:

<code>nobs</code>	Number of observations used for estimation
<code>min.time</code>	The minimum observed event or censoring time
<code>max.time</code>	The maximum observed event or censoring time
<code>min.hazard</code>	Minimal estimated hazard
<code>max.hazard</code>	Maximal estimated hazard

See Also

`glance()`, `muhaz::muhaz()`

Other muhaz tidiers: `tidy.muhaz`

glance.multinom *Glance at a(n) multinom object*

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'multinom'
glance(x, ...)
```

Arguments

<code>x</code>	A <code>multinom</code> object returned from <code>nnet::multinom()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A one-row `tibble::tibble` with columns:

<code>edf</code>	The effective degrees of freedom
<code>deviance</code>	deviance
<code>AIC</code>	the Akaike Information Criterion

See Also

`glance()`, `nnet::multinom()`

Other `multinom` tidiers: `tidy.multinom`

glance.nlrq

*Glance at a(n) nlrq object***Description**

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'nlrq'
glance(x, ...)
```

Arguments

<code>x</code>	A <code>nlrq</code> object returned from <code>quantreg::nlrq()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Value

A one-row `tibble::tibble()` with columns:

<code>tau</code>	quantile
<code>logLik</code>	the data's log-likelihood under the model
<code>AIC</code>	the Akaike Information Criterion
<code>BIC</code>	the Bayesian Information Criterion
<code>df.residual</code>	residual degrees of freedom

See Also

`glance()`, `quantreg::nlrq()`

Other `quantreg` tidiers: `augment.nlrq`, `augment.rqs`, `augment.rq`, `glance.rq`, `tidy.nlrq`, `tidy.rqs`, `tidy.rq`

glance.nls

*Glance at a(n) nls object***Description**

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'nls'
glance(x, ...)
```

Arguments

<code>x</code>	An nls object returned from <code>stats::nls()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A one-row `tibble::tibble` with columns:

<code>sigma</code>	the square root of the estimated residual variance
<code>isConv</code>	whether the fit successfully converged
<code>finTol</code>	the achieved convergence tolerance
<code>logLik</code>	the data's log-likelihood under the model
<code>AIC</code>	the Akaike Information Criterion
<code>BIC</code>	the Bayesian Information Criterion
<code>deviance</code>	deviance
<code>df.residual</code>	residual degrees of freedom

See Also

[tidy](#), [stats::nls\(\)](#)

Other nls tidiers: [augment.nls](#), [tidy.nls](#)

glance.orcutt

Glance at a(n) orcutt object

Description

Glance accepts a model object and returns a [tibble::tibble\(\)](#) with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'orcutt'
glance(x, ...)
```

Arguments

x	An orcutt object returned from orcutt::cochrane.orcutt() .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an augment() method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A one-row [tibble::tibble](#) with columns:

r.squared	R-squared
adj.r.squared	Adjusted R-squared
rho	Spearman's rho autocorrelation
number.interaction	Number of interactions
dw.original	Durbin-Watson statistic of original fit

```

p.value.original      P-value of original Durbin-Watson statistic
dw.transformed       Durbin-Watson statistic of transformed fit
p.value.transformed  P-value of autocorrelation after transformation

```

See Also

[glance\(\)](#), [orcutt::cochrane.orcutt\(\)](#)

Other orcutt tidiers: [tidy.orcutt](#)

glance.plm

Glance at a(n) plm object

Description

Glance accepts a model object and returns a [tibble::tibble\(\)](#) with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```

## S3 method for class 'plm'
glance(x, ...)

```

Arguments

```

x          A plm object returned by plm::plm\(\).
...       Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass conf.level = 0.9, all computation will proceed using conf.level = 0.95. Additionally, if you pass newdata = my_tibble to an augment\(\) method that does not accept a newdata argument, it will use the default value for the data argument.

```


Value

A one-row `tibble::tibble` with columns:

<code>r.squared</code>	The percent of variance explained by the model
<code>adj.r.squared</code>	<code>r.squared</code> adjusted based on the degrees of freedom
<code>statistic</code>	F-statistic
<code>p.value</code>	p-value from the F test, describing whether the full regression is significant
<code>deviance</code>	deviance
<code>df.residual</code>	residual degrees of freedom

See Also

`glance()`, `plm::plm()`

Other plm tidiers: `augment.plm`, `tidy.plm`

`glance.poLCA`

Augment data with information from a(n) poLCA object

Description

`Augment` accepts a model object and a dataset and adds information about each observation in the dataset. Most commonly, this includes predicted values in the `.fitted` column, residuals in the `.resid` column, and standard errors for the fitted values in a `.se.fit` column. New columns always begin with a `.` prefix to avoid overwriting columns in the original dataset.

Users may pass data to `augment` via either the `data` argument or the `newdata` argument. If the user passes data to the `data` argument, it **must** be exactly the data that was used to fit the model object. Pass datasets to `newdata` to augment data that was not used during model fitting. This still requires that all columns used to fit the model are present.

`Augment` will often behavior different depending on whether `data` or `newdata` is specified. This is because there is often information associated with training observations (such as influences or related) measures that is not meaningfully defined for new observations.

For convenience, many `augment` methods provide default `data` arguments, so that `augment(fit)` will return the augmented training data. In these cases `augment` tries to reconstruct the original data based on the model object, with some varying degrees of success.

The augmented dataset is always returned as a `tibble::tibble` with the **same number of rows** as the passed dataset. This means that the passed data must be coercible to a tibble. At this time, tibbles do not support matrix-columns. This means you should not specify a matrix of covariates in a model formula during the original model fitting process, and that `splines::ns()`, `stats::poly()` and `survival::Surv()` objects are not supported in input data. If you encounter errors, try explicitly passing a tibble, or fitting the original model on data in a tibble.

We are in the process of defining behaviors for models fit with various `na.action` arguments, but make no guarantees about behavior when data is missing at this time.

Usage

```
## S3 method for class 'poLCA'
glance(x, ...)
```

Arguments

`x` A poLCA object returned from `poLCA: :poLCA()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the data argument.

Value

A one-row `tibble::tibble` with columns:

<code>logLik</code>	the data's log-likelihood under the model
<code>AIC</code>	the Akaike Information Criterion
<code>BIC</code>	the Bayesian Information Criterion
<code>g.squared</code>	The likelihood ratio/deviance statistic
<code>chi.squared</code>	The Pearson Chi-Square goodness of fit statistic for multiway tables
<code>df</code>	Number of parameters estimated, and therefore degrees of freedom used
<code>df.residual</code>	Number of residual degrees of freedom left

See Also

`glance()`, `poLCA: :poLCA()`

Other poLCA tidiers: `augment.poLCA`, `tidy.poLCA`

`glance.pyyears`

Glance at a(n) pyyears object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'pyears'
glance(x, ...)
```

Arguments

`x` A pyears object returned from `survival::pyears()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

A one-row `tibble::tibble` with columns:

<code>total</code>	total number of person-years tabulated
<code>offtable</code>	total number of person-years off table

See Also

`glance()`, `survival::pyears()`

Other pyears tidiers: `tidy.pyears`

Other survival tidiers: `augment.coxph`, `augment.survreg`, `glance.aareg`, `glance.cch`, `glance.coxph`, `glance.survdiff`, `glance.survexp`, `glance.survfit`, `glance.survreg`, `tidy.aareg`, `tidy.cch`, `tidy.coxph`, `tidy.pyears`, `tidy.survdiff`, `tidy.survexp`, `tidy.survfit`, `tidy.survreg`

`glance.ridgelm`

Glance at a(n) ridgelm object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'ridgelm'
glance(x, ...)
```

Arguments

`x` A `ridgelm` object returned from `MASS::lm.ridge()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Details

This is similar to the output of `select.ridgelm`, but it is returned rather than printed.

Value

A one-row `tibble::tibble` with columns:

<code>kHKB</code>	modified HKB estimate of the ridge constant
<code>kLW</code>	modified L-W estimate of the ridge constant
<code>lambdaGCV</code>	choice of lambda that minimizes GCV

See Also

`glance()`, `MASS::select.ridgelm()`, `MASS::lm.ridge()`

Other `ridgelm` tidiers: `tidy.ridgelm`

`glance.rlm`

Glance at a(n) rlm object

Description

`Glance` accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

`Glance` never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

`Glance` does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'rlm'
glance(x, ...)
```

Arguments

x	An rlm object returned by <code>MASS::rlm()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Details

For tidiers for models from the **robust** package see `tidy.lmRob()` and `tidy.glmRob()`.

Value

A one-row `tibble::tibble` with columns:

sigma	The square root of the estimated residual variance
converged	whether the IWLS converged
logLik	the data's log-likelihood under the model
AIC	the Akaike Information Criterion
BIC	the Bayesian Information Criterion
deviance	deviance

See Also

`glance()`, `MASS::rlm()`

Other rlm tidiers: `augment.rlm`, `tidy.rlm`

Examples

```
library(MASS)

r <- rlm(stack.loss ~ ., stackloss)
tidy(r)
augment(r)
glance(r)
```

glance.rq

Glance at a(n) rq object

Description

Glance accepts a model object and returns a `tibble::tibble()` with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'rq'
glance(x, ...)
```

Arguments

`x` An rq object returned from `quantreg::rq()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the data argument.

Details

Only models with a single tau value may be passed. For multiple values, please use a `purrr::map()` workflow instead, e.g.

```
taus %>%
  map(function(tau_val) rq(y ~ x, tau = tau_val)) %>%
  map_dfr(glance)
```

Value

A one-row `tibble::tibble` with columns:

<code>tau</code>	quantile estimated
<code>logLik</code>	the data's log-likelihood under the model
<code>AIC</code>	the Akaike Information Criterion

BIC	the Bayesian Information Criterion
df.residual	residual degrees of freedom

See Also

[glance\(\)](#), [quantreg::rq\(\)](#)

Other quantreg tidiers: [augment.nlrq](#), [augment.rqs](#), [augment.rq](#), [glance.nlrq](#), [tidy.nlrq](#), [tidy.rqs](#), [tidy.rq](#)

`glance.smooth.spline` *Tidy a(n) smooth.spline object*

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'smooth.spline'
glance(x, ...)
```

Arguments

<code>x</code>	A <code>smooth.spline</code> object returned from stats::smooth.spline() .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an augment() method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Value

A one-row [tibble::tibble](#) with columns:

<code>spar</code>	smoothing parameter
<code>lambda</code>	choice of lambda corresponding to <code>spar</code>
<code>df</code>	equivalent degrees of freedom
<code>crit</code>	minimized criterion
<code>pen.crit</code>	penalized criterion
<code>cv.crit</code>	cross-validation score

See Also

[augment\(\)](#), [stats::smooth.spline\(\)](#)

Other smoothing spline tidiers: [augment.smooth.spline](#)

glance.speedlm

*Glance at a(n) speedlm object***Description**

Glance accepts a model object and returns a [tibble::tibble\(\)](#) with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'speedlm'
glance(x, ...)
```

Arguments

x	A speedlm object returned from speedglm::speedlm() .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an augment() method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A one-row [tibble::tibble](#) with columns:

r.squared	The percent of variance explained by the model
adj.r.squared	r.squared adjusted based on the degrees of freedom
statistic	F-statistic
p.value	p-value from the F test, describing whether the full regression is significant
df	Degrees of freedom used by the coefficients
logLik	the data's log-likelihood under the model

AIC	the Akaike Information Criterion
BIC	the Bayesian Information Criterion
deviance	deviance
df.residual	residual degrees of freedom

See Also

[speedglm::speedlm\(\)](#)

Other speedlm tidiers: [augment.speedlm](#), [tidy.speedlm](#)

glance.survdiff	<i>Glance at a(n) survdiff object</i>
-----------------	---------------------------------------

Description

Glance accepts a model object and returns a [tibble::tibble\(\)](#) with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'survdiff'
glance(x, ...)
```

Arguments

x	An survdiff object returned from survival::survdiff() .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an augment() method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A one-row [tibble::tibble](#) with columns:

statistic	value of the test statistic
df	degrees of freedom
p.value	p-value

See Also

[glance\(\)](#), [survival::survdiff\(\)](#)

Other survdiff tidiers: [tidy.survdiff](#)

Other survival tidiers: [augment.coxph](#), [augment.survreg](#), [glance.aareg](#), [glance.cch](#), [glance.coxph](#), [glance.pyears](#), [glance.survexp](#), [glance.survfit](#), [glance.survreg](#), [tidy.aareg](#), [tidy.cch](#), [tidy.coxph](#), [tidy.pyears](#), [tidy.survdiff](#), [tidy.survexp](#), [tidy.survfit](#), [tidy.survreg](#)

glance.survexp

Glance at a(n) survexp object

Description

Glance accepts a model object and returns a [tibble::tibble\(\)](#) with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'survexp'
glance(x, ...)
```

Arguments

`x` An survexp object returned from [survival::survexp\(\)](#).

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an [augment\(\)](#) method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

A one-row [tibble::tibble](#) with columns:

<code>n.max</code>	maximum number of subjects at risk
<code>n.start</code>	starting number of subjects at risk
<code>timepoints</code>	number of timepoints

See Also

[glance\(\)](#), [survival::survexp\(\)](#)

Other survexp tidiers: [tidy.survexp](#)

Other survival tidiers: [augment.coxph](#), [augment.survreg](#), [glance.aareg](#), [glance.cch](#), [glance.coxph](#), [glance.pyears](#), [glance.survdiff](#), [glance.survfit](#), [glance.survreg](#), [tidy.aareg](#), [tidy.cch](#), [tidy.coxph](#), [tidy.pyears](#), [tidy.survdiff](#), [tidy.survexp](#), [tidy.survfit](#), [tidy.survreg](#)

glance.survfit

Glance at a(n) survfit object

Description

Glance accepts a model object and returns a [tibble::tibble\(\)](#) with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'survfit'
glance(x, ...)
```

Arguments

`x` An survfit object returned from [survival::survfit\(\)](#).

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an [augment\(\)](#) method that does not accept a `newdata` argument, it will use the default value for the data argument.

Value

A one-row [tibble::tibble](#) with columns:

<code>records</code>	number of observations
<code>n.max</code>	<code>n.max</code>
<code>n.start</code>	<code>n.start</code>

events	number of events
rmean	Restricted mean (see survival::print.survfit())
rmean.std.error	Restricted mean standard error
median	median survival
conf.low	lower end of confidence interval on median
conf.high	upper end of confidence interval on median

See Also

[glance\(\)](#), [survival::survfit\(\)](#)

Other cch tidiers: [glance.cch](#), [tidy.cch](#)

Other survival tidiers: [augment.coxph](#), [augment.survreg](#), [glance.aareg](#), [glance.cch](#), [glance.coxph](#), [glance.pyears](#), [glance.survdiff](#), [glance.survexp](#), [glance.survreg](#), [tidy.aareg](#), [tidy.cch](#), [tidy.coxph](#), [tidy.pyears](#), [tidy.survdiff](#), [tidy.survexp](#), [tidy.survfit](#), [tidy.survreg](#)

<code>glance.survreg</code>	<i>Glance at a(n) survreg object</i>
-----------------------------	--------------------------------------

Description

Glance accepts a model object and returns a [tibble::tibble\(\)](#) with exactly one row of model summaries. The summaries are typically goodness of fit measures, p-values for hypothesis tests on residuals, or model convergence information.

Glance never returns information from the original call to the modelling function. This includes the name of the modelling function or any arguments passed to the modelling function.

Glance does not calculate summary measures. Rather, it farms out these computations to appropriate methods and gathers the results together. Sometimes a goodness of fit measure will be undefined. In these cases the measure will be reported as NA.

Usage

```
## S3 method for class 'survreg'
glance(x, ...)
```

Arguments

x	An survreg object returned from survival::survreg() .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an augment() method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A one-row `tibble::tibble` with columns:

<code>iter</code>	number of iterations
<code>df</code>	degrees of freedom
<code>statistic</code>	chi-squared statistic
<code>p.value</code>	p-value from chi-squared test
<code>logLik</code>	log likelihood
<code>AIC</code>	Akaike information criterion
<code>BIC</code>	Bayesian information criterion
<code>df.residual</code>	residual degrees of freedom

See Also

`glance()`, `survival::survreg()`

Other survreg tidiers: `augment.survreg`, `tidy.survreg`

Other survival tidiers: `augment.coxph`, `augment.survreg`, `glance.aareg`, `glance.cch`, `glance.coxph`, `glance.pyyears`, `glance.survdiff`, `glance.survexp`, `glance.survfit`, `tidy.aareg`, `tidy.cch`, `tidy.coxph`, `tidy.pyyears`, `tidy.survdiff`, `tidy.survexp`, `tidy.survfit`, `tidy.survreg`

`glance_optim`

Tidy a(n) optim object masquerading as list

Description

Broom tidies a number of lists that are effectively S3 objects without a class attribute. For example, `stats::optim()`, `svd()` and `akima::interp()` produce consistent output, but because they do not have a class attribute, they cannot be handled by S3 dispatch.

These functions look at the elements of a list and determine if there is an appropriate tidying method to apply to the list. Those tidiers are themselves implemented as functions of the form `tidy_<function>` or `glance_<function>` and are not exported (but they are documented!).

If no appropriate tidying method is found, throws an error.

Usage

```
glance_optim(x, ...)
```

Arguments

`x` A list returned from `stats::optim()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

A one-row `tibble::tibble` with columns:

`value` minimized or maximized output value

`function.count` number of calls to `fn`

`gradient.count` number of calls to `gr`

`convergence` convergence code representing the error state

See Also

`glance()`, `optim()`

Other list tidiers: `list_tidiers`, `tidy_irlba`, `tidy_optim`, `tidy_svd`, `tidy_xyz`

<code>insert_NAs</code>	<i>insert a row of NAs into a data frame wherever another data frame has NAs</i>
-------------------------	--

Description

insert a row of NAs into a data frame wherever another data frame has NAs

Usage

```
insert_NAs(x, original)
```

Arguments

`x` data frame that has one row for each non-NA row in `original`

`original` data frame with NAs

list_tidiers	<i>Tidying methods for lists / returned values that are not S3 objects</i>
--------------	--

Description

Broom tidies a number of lists that are effectively S3 objects without a class attribute. For example, `stats::optim()`, `svd()` and `akima::interp()` produce consistent output, but because they do not have a class attribute, they cannot be handled by S3 dispatch.

Usage

```
## S3 method for class 'list'
tidy(x, ...)

## S3 method for class 'list'
glance(x, ...)
```

Arguments

`x` A list, potentially representing an object that can be tidied.
`...` Additionally arguments passed to the tidying function.

Details

These functions look at the elements of a list and determine if there is an appropriate tidying method to apply to the list. Those tidiers are themselves implemented as functions of the form `tidy_<function>` or `glance_<function>` and are not exported (but they are documented!).

If no appropriate tidying method is found, throws an error.

See Also

Other list tidiers: [glance_optim](#), [tidy_irlba](#), [tidy_optim](#), [tidy_svd](#), [tidy_xyz](#)

lme4_tidiers	<i>Tidying methods for mixed effects models</i>
--------------	---

Description

lme4 tidiers will soon be deprecated in broom and there is no ongoing development of these functions at this time. lme4 tidiers are being developed in the `broom.mixed` package, which is not yet on CRAN.

Usage

```
## S3 method for class 'merMod'
tidy(x, effects = c("ran_pars", "fixed"),
     scales = NULL, ran_prefix = NULL, conf.int = FALSE,
     conf.level = 0.95, conf.method = "Wald", ...)

## S3 method for class 'merMod'
augment(x, data = stats::model.frame(x), newdata, ...)

## S3 method for class 'merMod'
glance(x, ...)
```

Arguments

<code>x</code>	An object of class <code>merMod</code> , such as those from <code>lmer</code> , <code>glmer</code> , or <code>nlmer</code>
<code>effects</code>	A character vector including one or more of "fixed" (fixed-effect parameters), "ran_pars" (variances and covariances or standard deviations and correlations of random effect terms) or "ran_modes" (conditional modes/BLUPs/latent variable estimates)
<code>scales</code>	scales on which to report the variables: for random effects, the choices are "sd-cor" (standard deviations and correlations: the default if <code>scales</code> is <code>NULL</code>) or "vcov" (variances and covariances). <code>NA</code> means no transformation, appropriate e.g. for fixed effects; inverse-link transformations (exponentiation or logistic) are not yet implemented, but may be in the future.
<code>ran_prefix</code>	a length-2 character vector specifying the strings to use as prefixes for self- (variance/standard deviation) and cross- (covariance/correlation) random effects terms
<code>conf.int</code>	whether to include a confidence interval
<code>conf.level</code>	confidence level for CI
<code>conf.method</code>	method for computing confidence intervals (see <code>lme4::confint.merMod</code>)
<code>...</code>	extra arguments (not used)
<code>data</code>	original data this was fitted on; if not given this will attempt to be reconstructed
<code>newdata</code>	new data to be used for prediction; optional

Details

These methods tidy the coefficients of mixed effects models, particularly responses of the `merMod` class

When the modeling was performed with `na.action = "na.omit"` (as is the typical default), rows with `NA` in the initial data are omitted entirely from the augmented data frame. When the modeling was performed with `na.action = "na.exclude"`, one should provide the original data as a second argument, at which point the augmented data will contain those rows (typically with `NA`s in place of the new columns). If the original data is not provided to `augment()` and `na.action = "na.exclude"`, a warning is raised and the incomplete rows are dropped.

Value

All tidying methods return a `data.frame` without rownames. The structure depends on the method chosen.

`tidy` returns one row for each estimated effect, either with groups depending on the effects parameter. It contains the columns

<code>group</code>	the group within which the random effect is being estimated: "fixed" for fixed effects
<code>level</code>	level within group (NA except for modes)
<code>term</code>	term being estimated
<code>estimate</code>	estimated coefficient
<code>std.error</code>	standard error
<code>statistic</code>	t- or Z-statistic (NA for modes)
<code>p.value</code>	P-value computed from t-statistic (may be missing/NA)

`augment` returns one row for each original observation, with columns (each prepended by a `.`) added. Included are the columns

<code>.fitted</code>	predicted values
<code>.resid</code>	residuals
<code>.fixed</code>	predicted values with no random effects

Also added for "merMod" objects, but not for "mer" objects, are values from the response object within the model (of type `lmResp`, `glmResp`, `nlsResp`, etc). These include `".mu"`, `".offset"`, `".sqrtXwt"`, `".sqrttrwt"`,

`glance` returns one row with the columns

<code>sigma</code>	the square root of the estimated residual variance
<code>logLik</code>	the data's log-likelihood under the model
<code>AIC</code>	the Akaike Information Criterion
<code>BIC</code>	the Bayesian Information Criterion
<code>deviance</code>	deviance

See Also

[na.action](#)

Examples

```
## Not run:
if (require("lme4")) {
  # example regressions are from lme4 documentation
  lmm1 <- lmer(Reaction ~ Days + (Days | Subject), sleepstudy)
  tidy(lmm1)
  tidy(lmm1, effects = "fixed")
  tidy(lmm1, effects = "fixed", conf.int=TRUE)
  tidy(lmm1, effects = "fixed", conf.int=TRUE, conf.method="profile")
}
```

```

tidy(lmm1, effects = "ran_modes", conf.int=TRUE)
head(augment(lmm1, sleepstudy))
glance(lmm1)

glmm1 <- glmer(cbind(incidence, size - incidence) ~ period + (1 | herd),
              data = cbpp, family = binomial)
tidy(glmm1)
tidy(glmm1, effects = "fixed")
head(augment(glmm1, cbpp))
glance(glmm1)

startvec <- c(Asym = 200, xmid = 725, scal = 350)
nm1 <- nlmmer(circumference ~ SSlogis(age, Asym, xmid, scal) ~ Asym|Tree,
             Orange, start = startvec)
tidy(nm1)
tidy(nm1, effects = "fixed")
head(augment(nm1, Orange))
glance(nm1)
}

## End(Not run)

```

matrix_tidiers

Tidiers for matrix objects

Description

Matrix tidiers are deprecated and will be removed from an upcoming release of broom.

Usage

```

## S3 method for class 'matrix'
tidy(x, ...)

## S3 method for class 'matrix'
glance(x, ...)

```

Arguments

x	A matrix
...	extra arguments, not used

Details

These perform tidying operations on matrix objects. `tidy` turns the matrix into a `data.frame` while bringing rownames, if they exist, in as a column called `.rownames` (since results of tidying operations never contain rownames). `glance` simply reports the number of rows and columns. Note that no `augment` method exists for matrices.

Value

`tidy.matrix` returns the original matrix converted into a `data.frame`, except that it incorporates rownames (if they exist) into a column called `.rownames`.

`glance` returns a one-row `data.frame` with

<code>nrow</code>	number of rows
<code>ncol</code>	number of columns
<code>complete.obs</code>	number of rows that have no missing values
<code>na.fraction</code>	fraction of values across all rows and columns that are missing

Examples

```
## Not run:
mat <- as.matrix(mtcars)
tidy(mat)
glance(mat)

## End(Not run)
```

mcmc_tidiers

Tidying methods for MCMC (Stan, JAGS, etc.) fits

Description

MCMC tidiers will soon be deprecated in broom and there is no ongoing development of these functions at this time. MCMC tidiers are being developed in the broom.mixed package, which is not yet on CRAN.

Usage

```
tidyMCMC(x, pars, estimate.method = "mean", conf.int = FALSE,
  conf.level = 0.95, conf.method = "quantile", droppars = "lp__",
  rhat = FALSE, ess = FALSE, ...)

## S3 method for class 'rjags'
tidy(x, pars, estimate.method = "mean",
  conf.int = FALSE, conf.level = 0.95, conf.method = "quantile", ...)

## S3 method for class 'stanfit'
tidy(x, pars, estimate.method = "mean",
  conf.int = FALSE, conf.level = 0.95, conf.method = "quantile",
  droppars = "lp__", rhat = FALSE, ess = FALSE, ...)
```

Arguments

<code>x</code>	an object of class "stanfit"
<code>pars</code>	(character) specification of which parameters to include
<code>estimate.method</code>	method for computing point estimate ("mean" or "median")
<code>conf.int</code>	(logical) include confidence interval?
<code>conf.level</code>	probability level for CI
<code>conf.method</code>	method for computing confidence intervals ("quantile" or "HPDinterval")
<code>droppars</code>	Parameters not to include in the output (such as log-probability information)
<code>rhat, ess</code>	(logical) include Rhat and/or effective sample size estimates?
<code>...</code>	unused

Examples

```
## Not run:

# Using example from "RStan Getting Started"
# https://github.com/stan-dev/rstan/wiki/RStan-Getting-Started

model_file <- system.file("extdata", "8schools.stan", package = "broom")

schools_dat <- list(J = 8,
                   y = c(28, 8, -3, 7, -1, 1, 18, 12),
                   sigma = c(15, 10, 16, 11, 9, 11, 10, 18))

if (requireNamespace("rstan", quietly = TRUE)) {
  set.seed(2015)
  rstan_example <- stan(file = model_file, data = schools_dat,
                       iter = 100, chains = 2)
}

## End(Not run)

if (requireNamespace("rstan", quietly = TRUE)) {
  # the object from the above code was saved as rstan_example.rda
  infile <- system.file("extdata", "rstan_example.rda", package = "broom")
  load(infile)

  tidy(rstan_example)
  tidy(rstan_example, conf.int = TRUE, pars = "theta")

  td_mean <- tidy(rstan_example, conf.int = TRUE)
  td_median <- tidy(rstan_example, conf.int = TRUE, estimate.method = "median")

  library(dplyr)
  library(ggplot2)
  tds <- rbind(mutate(td_mean, method = "mean"),
```

```

mutate(td_median, method = "median"))

ggplot(tds, aes(estimate, term)) +
  geom_errorbarh(aes(xmin = conf.low, xmax = conf.high)) +
  geom_point(aes(color = method))
}

```

nlme_tidiers

Tidying methods for mixed effects models

Description

nlme tidiers will soon be deprecated in broom and there is no ongoing development of these functions at this time. nlme tidiers are being developed in the broom.mixed package, which is not yet on CRAN.

Usage

```

## S3 method for class 'lme'
tidy(x, effects = "random", ...)

## S3 method for class 'lme'
augment(x, data = x$data, newdata, ...)

## S3 method for class 'lme'
glance(x, ...)

```

Arguments

x	An object of class lme, such as those from lme or nlme
effects	Either "random" (default) or "fixed"
...	extra arguments (not used)
data	original data this was fitted on; if not given this will attempt to be reconstructed
newdata	new data to be used for prediction; optional

Details

These methods tidy the coefficients of mixed effects models of the lme class from functions of the nlme package.

When the modeling was performed with `na.action = "na.omit"` (as is the typical default), rows with NA in the initial data are omitted entirely from the augmented data frame. When the modeling was performed with `na.action = "na.exclude"`, one should provide the original data as a second argument, at which point the augmented data will contain those rows (typically with NAs in place of the new columns). If the original data is not provided to `augment()` and `na.action = "na.exclude"`, a warning is raised and the incomplete rows are dropped.

Value

All tidying methods return a `data.frame` without rownames. The structure depends on the method chosen.

`tidy` returns one row for each estimated effect, either random or fixed depending on the `effects` parameter. If `effects = "random"`, it contains the columns

<code>group</code>	the group within which the random effect is being estimated
<code>level</code>	level within group
<code>term</code>	term being estimated
<code>estimate</code>	estimated coefficient

If `effects="fixed"`, `tidy` returns the columns

<code>term</code>	fixed term being estimated
<code>estimate</code>	estimate of fixed effect
<code>std.error</code>	standard error
<code>statistic</code>	t-statistic
<code>p.value</code>	P-value computed from t-statistic

`augment` returns one row for each original observation, with columns (each prepended by a `.`) added. Included are the columns

<code>.fitted</code>	predicted values
<code>.resid</code>	residuals
<code>.fixed</code>	predicted values with no random effects

`glance` returns one row with the columns

<code>sigma</code>	the square root of the estimated residual variance
<code>logLik</code>	the data's log-likelihood under the model
<code>AIC</code>	the Akaike Information Criterion
<code>BIC</code>	the Bayesian Information Criterion
<code>deviance</code>	returned as NA. To quote Brian Ripley on R-help: McCullagh & Nelder (1989) would be the authoritative reference, but the 1982 first edition manages to use 'deviance' in three separate senses on one page.

See Also

[na.action](#)

Examples

```
## Not run:
if (require("nlme") & require("lme4")) {
  # example regressions are from lme4 documentation, but used for nlme
  lmm1 <- lme(Reaction ~ Days, random=~ Days|Subject, sleepstudy)
  tidy(lmm1)
  tidy(lmm1, effects = "fixed")
  head(augment(lmm1, sleepstudy))
  glance(lmm1)

  startvec <- c(Asym = 200, xmid = 725, scal = 350)
  nm1 <- nlme(circumference ~ SSlogis(age, Asym, xmid, scal),
             data = Orange,
             fixed = Asym + xmid + scal ~1,
             random = Asym ~1,
             start = startvec)

  tidy(nm1)
  tidy(nm1, effects = "fixed")
  head(augment(nm1, Orange))
  glance(nm1)
}

## End(Not run)
```

null_tidiers

Tidiers for NULL inputs

Description

`tidy(NULL)`, `glance(NULL)` and `augment(NULL)` all return an empty [tibble::tibble](#). This empty tibble can be treated a tibble with zero rows, making it convenient to combine with other tibbles using functions like `purrr::map_df()` on lists of potentially NULL objects.

Usage

```
## S3 method for class 'NULL'
tidy(x, ...)

## S3 method for class 'NULL'
glance(x, ...)

## S3 method for class 'NULL'
augment(x, ...)
```

Arguments

x The value NULL.
 ... Additional arguments (not used).

Value

An empty `tibble::tibble`.

See Also

[tibble::tibble](#)

rowwise_df_tidiers	<i>Tidying methods for rowwise_dfs from dplyr, for tidying each row and recombining the results</i>
--------------------	---

Description

Rowwise tidiers are deprecated and will be removed from an upcoming version of broom. We strongly recommend moving to a nest-map-unnest workflow over a rowwise-do workflow. See the vignettes for examples.

Usage

```
## S3 method for class 'rowwise_df'
tidy(x, object, ...)

## S3 method for class 'rowwise_df'
tidy_(x, object, ...)

## S3 method for class 'rowwise_df'
augment(x, object, ...)

## S3 method for class 'rowwise_df'
augment_(x, object, ...)

## S3 method for class 'rowwise_df'
glance(x, object, ...)

## S3 method for class 'rowwise_df'
glance_(x, object, ...)

## S3 method for class 'tbl_df'
tidy(x, ...)

## S3 method for class 'tbl_df'
```



```
augment(x, ...)

## S3 method for class 'tbl_df'
glance(x, ...)
```

Arguments

x	a rowwise_df
object	the column name of the column containing the models to be tidied. For tidy, augment, and glance it should be the bare name; for _ methods it should be quoted.
...	additional arguments to pass on to the respective tidying method

Details

These tidy, augment and glance methods are for performing tidying on each row of a rowwise data frame created by dplyr's group_by and do operations. They first group a rowwise data frame based on all columns that are not lists, then perform the tidying operation on the specified column. This greatly shortens a common idiom of extracting tidy/augment/glance outputs after a do statement.

Note that this functionality is not currently implemented for data.tables, since the result of the do operation is difficult to distinguish from a regular data.table.

Value

A "grouped_df", where the non-list columns of the original are used as grouping columns alongside the tidied outputs.

Examples

```
library(dplyr)
regressions <- mtcars %>%
  group_by(cyl) %>%
  do(mod = lm(mpg ~ wt, .))

regressions

regressions %>% tidy(mod)
regressions %>% augment(mod)
regressions %>% glance(mod)

# we can provide additional arguments to the tidying function
regressions %>% tidy(mod, conf.int = TRUE)

# we can also include the original dataset as a "data" argument
# to augment:
regressions <- mtcars %>%
  group_by(cyl) %>%
  do(mod = lm(mpg ~ wt, .), original = (..))
```

```
# this allows all the original columns to be included:
regressions %>% augment(mod) # doesn't include all original
regressions %>% augment(mod, data = original) # includes all original
```

rstanarm_tidiers *Tidying methods for an rstanarm model*

Description

rstanarm tidiers will soon be deprecated in broom and there is no ongoing development of these functions at this time.

Usage

```
## S3 method for class 'stanreg'
tidy(x, parameters = "non-varying",
     intervals = FALSE, prob = 0.9, ...)
```

```
## S3 method for class 'stanreg'
glance(x, looic = FALSE, ...)
```

Arguments

x	Fitted model object from the rstanarm package. See rstanarm::stanreg-objects() .
parameters	One or more of "non-varying", "varying", "hierarchical", "auxiliary" (can be abbreviated). See the Value section for details.
intervals	If TRUE columns for the lower and upper bounds of the 100*prob% posterior uncertainty intervals are included. See rstanarm::posterior_interval() for details.
prob	See rstanarm::posterior_interval() .
...	For glance, if looic=TRUE, optional arguments to rstanarm::loo.stanreg() .
looic	Should the LOO Information Criterion (and related info) be included? See rstanarm::loo.stanreg() for details. Note: for models fit to very large datasets this can be a slow computation.

Details

These methods tidy the estimates from [rstanarm::stanreg-objects\(\)](#) (fitted model objects from the **rstanarm** package) into a summary.

Value

All tidying methods return a `data.frame` without rownames. The structure depends on the method chosen.

When `parameters="non-varying"` (the default), `tidy.stanreg` returns one row for each coefficient, with three columns:

<code>term</code>	The name of the corresponding term in the model.
<code>estimate</code>	A point estimate of the coefficient (posterior median).
<code>std.error</code>	A standard error for the point estimate based on <code>stats::mad()</code> . See the <i>Uncertainty estimates</i> section in <code>rstanarm::print.stanreg()</code> for more details.

For models with group-specific parameters (e.g., models fit with `rstanarm::stan_glmer()`), setting `parameters="varying"` selects the group-level parameters instead of the non-varying regression coefficients. Additional columns are added indicating the level and group. Specifying `parameters="hierarchical"` selects the standard deviations and (for certain models) correlations of the group-level parameters.

Setting `parameters="auxiliary"` will select parameters other than those included by the other options. The particular parameters depend on which **rstanarm** modeling function was used to fit the model. For example, for models fit using `rstanarm::stan_glm.nb()` the overdispersion parameter is included if `parameters="aux"`, for `rstanarm::stan_lm()` the auxiliary parameters include the residual SD, R^2 , and $\log(\text{fit_ratio})$, etc.

If `intervals=TRUE`, columns for the lower and upper values of the posterior intervals computed with `rstanarm::posterior_interval()` are also included.

`glance` returns one row with the columns

<code>algorithm</code>	The algorithm used to fit the model.
<code>pss</code>	The posterior sample size (except for models fit using optimization).
<code>nobs</code>	The number of observations used to fit the model.
<code>sigma</code>	The square root of the estimated residual variance, if applicable. If not applicable (e.g., for binomial GLMs), <code>sigma</code> will be given the value 1 in the returned object.

If `looic=TRUE`, then the following additional columns are also included:

<code>looic</code>	The LOO Information Criterion.
<code>elpd_loo</code>	The expected log predictive density ($\text{elpd_loo} = -2 * \text{looic}$).
<code>p_loo</code>	The effective number of parameters.

See Also

[rstanarm::summary.stanreg\(\)](#)

Examples

```
## Not run:
fit <- stan_glmmer(mpg ~ wt + (1|cyl) + (1+wt|gear), data = mtcars,
                  iter = 300, chains = 2)
# non-varying ("population") parameters
tidy(fit, intervals = TRUE, prob = 0.5)

# hierarchical sd & correlation parameters
tidy(fit, parameters = "hierarchical")

# group-specific deviations from "population" parameters
tidy(fit, parameters = "varying")

# glance method
glance(fit)
glance(fit, looic = TRUE, cores = 1)

## End(Not run)
```

sparse_tidiers

Tidy a sparseMatrix object from the Matrix package

Description

sparseMatrix tidiers are deprecated and will be removed from an upcoming version of broom.

Usage

```
## S3 method for class 'dgTMatrix'
tidy(x, ...)

## S3 method for class 'dgCMatrix'
tidy(x, ...)

## S3 method for class 'sparseMatrix'
tidy(x, ...)
```

Arguments

x	A Matrix object
...	Extra arguments, not used

Details

Tidy a sparseMatrix object from the Matrix package into a three-column data frame, row, column, and value (with zeros missing). If there are row names or column names, use those, otherwise use indices

`sp_tidiers`*Tidy a(n) SpatialPolygonsDataFrame object*

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Note that the `sf` package now defines tidy spatial objects and is the recommend approach to spatial data. `sp tidiers` are likely to be deprecated in the near future in favor of `sf::st_as_sf()`. Development of `sp tidiers` has halted in broom.

Usage

```
## S3 method for class 'SpatialPolygonsDataFrame'  
tidy(x, region = NULL, ...)
```

```
## S3 method for class 'SpatialPolygons'  
tidy(x, ...)
```

```
## S3 method for class 'Polygons'  
tidy(x, ...)
```

```
## S3 method for class 'Polygon'  
tidy(x, ...)
```

```
## S3 method for class 'SpatialLinesDataFrame'  
tidy(x, ...)
```

```
## S3 method for class 'Lines'  
tidy(x, ...)
```

```
## S3 method for class 'Line'  
tidy(x, ...)
```

Arguments

<code>x</code>	A <code>SpatialPolygonsDataFrame</code> , <code>SpatialPolygons</code> , <code>Polygons</code> , <code>Polygon</code> , <code>SpatialLinesDataFrame</code> , <code>Lines</code> or <code>Line</code> object.
<code>region</code>	name of variable used to split up regions
<code>...</code>	not used by this method

summary_tidiers	<i>Tidy/glance a(n) summaryDefault object</i>
-----------------	---

Description

For models that have only a single component, the `tidy()` and `glance()` methods are identical. Please see the documentation for both of those methods.

Usage

```
## S3 method for class 'summaryDefault'
tidy(x, ...)

## S3 method for class 'summaryDefault'
glance(x, ...)
```

Arguments

<code>x</code>	A <code>summaryDefault</code> object, created by calling <code>summary()</code> on a vector.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Value

A one-row `tibble::tibble` with columns:

<code>minimum</code>	Minimum value in original vector.
<code>q1</code>	First quartile of original vector.
<code>median</code>	Median of original vector.
<code>mean</code>	Mean of original vector.
<code>q3</code>	Third quartile of original vector.
<code>maximum</code>	Maximum value in original vector.
<code>na</code>	Number of NA values in original vector. Column present only when original vector had at least one NA entry.

See Also

`tidy()`, `summary()`

Examples

```
v <- rnorm(1000)
s <- summary(v)
s

tidy(s)
glance(s)

v2 <- c(v, NA)
tidy(summary(v2))
```

tidy.aareg

Tidy a(n) aareg object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'aareg'
tidy(x, ...)
```

Arguments

x	An aareg object returned from <code>survival::aareg()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Value

A `tibble::tibble` with one row for each coefficient and columns:

term	name of coefficient
estimate	estimate of the slope
statistic	test statistic for coefficient
std.error	standard error of statistic

robust.se	robust version of standard error estimate (only when x was called with dfbeta = TRUE)
z	z score
p.value	p-value

See Also

[tidy\(\)](#), [survival::aareg\(\)](#)

Other aareg tidiers: [glance.aareg](#)

Other survival tidiers: [augment.coxph](#), [augment.survreg](#), [glance.aareg](#), [glance.cch](#), [glance.coxph](#), [glance.pyyears](#), [glance.survdiff](#), [glance.survexp](#), [glance.survfit](#), [glance.survreg](#), [tidy.cch](#), [tidy.coxph](#), [tidy.pyyears](#), [tidy.survdiff](#), [tidy.survexp](#), [tidy.survfit](#), [tidy.survreg](#)

Examples

```
library(survival)

afit <- aareg(
  Surv(time, status) ~ age + sex + ph.ecog,
  data = lung,
  dfbeta = TRUE
)

tidy(afit)
```

tidy.acf

Tidy a(n) acf object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'acf'
tidy(x, ...)
```

Arguments

x An acf object created by [stats::acf\(\)](#), [stats::pacf\(\)](#) or [stats::ccf\(\)](#).

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

A `tibble::tibble` with columns:

lag	lag values
acf	calculated correlation

See Also

`tidy()`, `stats::acf()`, `stats::pacf()`, `stats::ccf()`

Other time series tidiers: `tidy.spec`, `tidy.ts`, `tidy.zoo`

Examples

```
tidy(acf(lh, plot = FALSE))
tidy(ccf(mdeaths, fdeaths, plot = FALSE))
tidy(pacf(lh, plot = FALSE))
```

tidy.anova

Tidy a(n) anova object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'anova'
tidy(x, ...)
```

Arguments

`x` An anova objects, such as those created by `stats::anova()` or `car::Anova()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the data argument.

Details

The term column of an ANOVA table can come with leading or trailing whitespace, which this tidying method trims.

Value

A `tibble::tibble` with columns

<code>term</code>	Term within the model, or "Residuals"
<code>df</code>	Degrees of freedom used by this term in the model
<code>sumsq</code>	Sum of squares explained by this term
<code>meansq</code>	Mean of sum of squares among degrees of freedom
<code>statistic</code>	F statistic
<code>p.value</code>	P-value from F test

See Also

`tidy()`, `stats::anova()`, `car::Anova()`

Other anova tidiers: `tidy.TukeyHSD`, `tidy.aovlist`, `tidy.aov`, `tidy.manova`

Examples

```
a <- a <- aov(mpg ~ wt + qsec + disp, mtcars)
tidy(a)
```

tidy.aov	<i>Tidy a(n) aov object</i>
----------	-----------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'aov'
tidy(x, ...)
```

Arguments

x	An aov objects, such as those created by <code>stats::aov()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Details

The term column of an ANOVA table can come with leading or trailing whitespace, which this tidying method trims.

Value

A `tibble::tibble` with columns

term	Term within the model, or "Residuals"
df	Degrees of freedom used by this term in the model
sumsq	Sum of squares explained by this term
meansq	Mean of sum of squares among degrees of freedom
statistic	F statistic
p.value	P-value from F test

See Also

`tidy()`, `stats::aov()`

Other anova tidiers: `tidy.TukeyHSD`, `tidy.anova`, `tidy.aovlist`, `tidy.manova`

Examples

```
a <- aov(mpg ~ wt + qsec + disp, mtcars)
tidy(a)
```

tidy.aovlist	<i>Tidy a(n) aovlist object</i>
--------------	---------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'aovlist'
tidy(x, ...)
```

Arguments

x	An aovlist objects, such as those created by <code>stats::aov()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Details

The term column of an ANOVA table can come with leading or trailing whitespace, which this tidying method trims.

Value

A `tibble::tibble` with columns

term	Term within the model, or "Residuals"
df	Degrees of freedom used by this term in the model
sumsq	Sum of squares explained by this term
meansq	Mean of sum of squares among degrees of freedom
statistic	F statistic
p.value	P-value from F test
stratum	The error stratum

See Also

`tidy()`, `stats::aov()`

Other anova tidiers: `tidy.TukeyHSD`, `tidy.anova`, `tidy.aov`, `tidy.manova`

Examples

```
a <- aov(mpg ~ wt + qsec + Error(displ / am), mtcars)
tidy(a)
```

tidy.Arima

Tidy a(n) Arima object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'Arima'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

<code>x</code>	An object of class <code>Arima</code> created by <code>stats::arima()</code> .
<code>conf.int</code>	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to <code>FALSE</code> .
<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A `tibble::tibble` with one row for each coefficient and columns:

<code>term</code>	The term in the nonlinear model being estimated and tested
<code>estimate</code>	The estimated coefficient
<code>std.error</code>	The standard error from the linear model

If `conf.int = TRUE`, also returns

<code>conf.low</code>	low end of confidence interval
<code>conf.high</code>	high end of confidence interval

See Also

`stats::arima()`

Other Arima tidiers: `glance.Arima`

Examples

```
fit <- arima(lh, order = c(1, 0, 0))
tidy(fit)
glance(fit)
```

`tidy.betareg`

Tidy a(n) betareg object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'betareg'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

<code>x</code>	A betareg object produced by a call to <code>betareg::betareg()</code> .
<code>conf.int</code>	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A `tibble::tibble()` with one row for each term in the regression. The tibble has columns:

<code>term</code>	The name of the regression term.
<code>estimate</code>	The estimated value of the regression term.
<code>std.error</code>	The standard error of the regression term.
<code>statistic</code>	The value of a statistic, almost always a T-statistic, to use in a hypothesis that the regression term is non-zero.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>conf.low</code>	The low end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .
<code>conf.high</code>	The high end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .

In addition to the standard columns, the returned tibble has an additional column `component`. `component` indicates whether a particular term was used to model either the "mean" or "precision". Here the precision is the inverse of the variance, often referred to as ϕ . At least one term will have been used to model ϕ .

See Also

[tidy\(\)](#), [betareg::betareg\(\)](#)

Examples

```
library(betareg)

data("GasolineYield", package = "betareg")

mod <- betareg(yield ~ batch + temp, data = GasolineYield)
```

```

mod
tidy(mod)
tidy(mod, conf.int = TRUE)
tidy(mod, conf.int = TRUE, conf.level = .99)

augment(mod)

glance(mod)

```

tidy.biglm

Tidy a(n) biglm object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'biglm'
tidy(x, conf.int = FALSE, conf.level = 0.95,
     exponentiate = FALSE, quick = FALSE, ...)

```

Arguments

x	A biglm object created by a call to <code>biglm::biglm()</code> or <code>biglm::bigglm()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
exponentiate	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to FALSE.
quick	Logical indicating if the only the term and estimate columns should be returned. Often useful to avoid time consuming covariance and standard error calculations. Defaults to FALSE.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A `tibble::tibble()` with one row for each term in the regression. The tibble has columns:

<code>term</code>	The name of the regression term.
<code>estimate</code>	The estimated value of the regression term.
<code>std.error</code>	The standard error of the regression term.
<code>statistic</code>	The value of a statistic, almost always a T-statistic, to use in a hypothesis that the regression term is non-zero.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>conf.low</code>	The low end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .
<code>conf.high</code>	The high end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .

See Also

`tidy()`, `biglm::biglm()`, `biglm::bigglm()`

Other biglm tidiers: `glance.biglm`

Examples

```
if (require("biglm", quietly = TRUE)) {
  bfit <- biglm(mpg ~ wt + disp, mtcars)
  tidy(bfit)
  tidy(bfit, conf.int = TRUE)
  tidy(bfit, conf.int = TRUE, conf.level = .9)

  glance(bfit)

  # bigglm: logistic regression
  bgfit <- bigglm(am ~ mpg, mtcars, family = binomial())
  tidy(bgfit)
  tidy(bgfit, exponentiate = TRUE)
  tidy(bgfit, conf.int = TRUE)
  tidy(bgfit, conf.int = TRUE, conf.level = .9)
  tidy(bgfit, conf.int = TRUE, conf.level = .9, exponentiate = TRUE)

  glance(bgfit)
}
```

tidy.binDesign	<i>Tidy a(n) binDesign object</i>
----------------	-----------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'binDesign'
tidy(x, ...)
```

Arguments

x	A <code>binGroup::binDesign()</code> object.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A one-row `tibble::tibble` with columns:

n	Number of trials in given iteration.
power	Power achieved for given value of n.

See Also

`tidy()`, `binGroup::binDesign()`

Other bingroup tidiers: `glance.binDesign`, `tidy.binWidth`

Examples

```
if (require("binGroup", quietly = TRUE)) {
  des <- binDesign(nmax = 300, delta = 0.06,
                  p.hyp = 0.1, power = .8)

  glance(des)
  tidy(des)
}
```

```

# the ggplot2 equivalent of plot(des)
library(ggplot2)
ggplot(tidy(des), aes(n, power)) +
  geom_line()
}

```

tidy.binWidth

Tidy a(n) binWidth object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'binWidth'
tidy(x, ...)

```

Arguments

x	A <code>binGroup::binWidth()</code> object.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A one-row `tibble::tibble` with columns:

ci.width	Expected width of confidence interval.
alternative	Alternative hypothesis.
p	True proportion.
n	Total sample size.

See Also

`tidy()`, `binGroup::binWidth()`

Other bingroup tidiers: `glance.binDesign`, `tidy.binDesign`

Examples

```

if (require("binGroup", quietly = TRUE)) {
  bw <- binWidth(100, .1)
  bw
  tidy(bw)

  library(dplyr)
  d <- expand.grid(n = seq(100, 800, 100),
                  p = .5,
                  method = c("CP", "Blaker", "Score", "Wald"),
                  stringsAsFactors = FALSE) %>%
    group_by(n, p, method) %>%
    do(tidy(binWidth(.$n, .$p, method = .$method)))

  library(ggplot2)
  ggplot(d, aes(n, ci.width, color = method)) +
    geom_line() +
    xlab("Total Observations") +
    ylab("Expected CI Width")
}

```

tidy.boot

Tidy a(n) boot object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'boot'
tidy(x, conf.int = FALSE, conf.level = 0.95,
     conf.method = "perc", ...)

```

Arguments

x	A <code>boot::boot()</code> object.
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
conf.method	Passed to the type argument of <code>boot::boot.ci()</code> . Defaults to "perc".

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

A `tibble::tibble` with one row per bootstrapped statistic and columns:

<code>term</code>	Name of the computed statistic, if present.
<code>statistic</code>	Original value of the statistic.
<code>bias</code>	Bias of the statistic.
<code>std.error</code>	Standard error of the statistic.

If weights were provided to the `boot` function, an `estimate` column is included showing the weighted bootstrap estimate, and the standard error is of that estimate.

If there are no original statistics in the "boot" object, such as with a call to `tsboot` with `orig.t = FALSE`, the `original` and `statistic` columns are omitted, and only `estimate` and `std.error` columns shown.

See Also

[tidy\(\)](#), [boot::boot\(\)](#), [boot::tsboot\(\)](#), [boot::boot.ci\(\)](#), [rsample::bootstraps\(\)](#)

Examples

```
if (require("boot")) {
  clotting <- data.frame(
    u = c(5,10,15,20,30,40,60,80,100),
    lot1 = c(118,58,42,35,27,25,21,19,18),
    lot2 = c(69,35,26,21,18,16,13,12,12))

  g1 <- glm(lot2 ~ log(u), data = clotting, family = Gamma)

  bootfun <- function(d, i) {
    coef(update(g1, data= d[i,]))
  }
  bootres <- boot(clotting, bootfun, R = 999)
  tidy(g1, conf.int=TRUE)
  tidy(bootres, conf.int=TRUE)
}
```

tidy.btergm

*Tidy a(n) btergm object***Description**

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

This method tidies the coefficients of a bootstrapped temporal exponential random graph model estimated with the **xergm**. It simply returns the coefficients and their confidence intervals.

Usage

```
## S3 method for class 'btergm'
tidy(x, conf.level = 0.95, exponentiate = FALSE,
     quick = FALSE, ...)
```

Arguments

x	A <code>btergm:btergm()</code> object.
conf.level	Confidence level for confidence intervals. Defaults to 0.95.
exponentiate	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to FALSE.
quick	Logical indicating if the only the term and estimate columns should be returned. Often useful to avoid time consuming covariance and standard error calculations. Defaults to FALSE.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A `tibble::tibble` with one row per term in the random graph model and columns:

term	The term in the model being estimated and tested.
estimate	The estimated value of the coefficient.
conf.low	The lower bound of the confidence interval.
conf.high	The lower bound of the confidence interval.

See Also

[tidy\(\)](#), [btergm::btergm\(\)](#)

Examples

```
if (require("xergm")) {
  set.seed(1)
  # Using the same simulated example as the xergm package
  # Create 10 random networks with 10 actors
  networks <- list()
  for(i in 1:10){
    mat <- matrix(rbinom(100, 1, .25), nrow = 10, ncol = 10)
    diag(mat) <- 0
    nw <- network::network(mat)
    networks[[i]] <- nw
  }
  # Create 10 matrices as covariates
  covariates <- list()
  for (i in 1:10) {
    mat <- matrix(rnorm(100), nrow = 10, ncol = 10)
    covariates[[i]] <- mat
  }
  # Fit a model where the propensity to form ties depends
  # on the edge covariates, controlling for the number of
  # in-stars
  suppressWarnings(btfit <- btergm(networks ~ edges + istar(2) +
    edgescov(covariates), R = 100))

  # Show terms, coefficient estimates and errors
  tidy(btfit)

  # Show coefficients as odds ratios with a 99% CI
  tidy(btfit, exponentiate = TRUE, conf.level = 0.99)
}
```

tidy.cch

Tidy a(n) cch object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'cch'
tidy(x, conf.level = 0.95, ...)
```

Arguments

x	An cch object returned from <code>survival::cch()</code> .
conf.level	confidence level for CI
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.lvel = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Value

A `tibble::tibble()` with one row for each term in the regression. The tibble has columns:

term	The name of the regression term.
estimate	The estimated value of the regression term.
std.error	The standard error of the regression term.
statistic	The value of a statistic, almost always a T-statistic, to use in a hypothesis that the regression term is non-zero.
p.value	The two-sided p-value associated with the observed statistic.
conf.low	The low end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .
conf.high	The high end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .

See Also

`tidy()`, `survival::cch()`

Other cch tidiers: `glance.cch`, `glance.survfit`

Other survival tidiers: `augment.coxph`, `augment.survreg`, `glance.aareg`, `glance.cch`, `glance.coxph`, `glance.pyears`, `glance.survdiff`, `glance.survexp`, `glance.survfit`, `glance.survreg`, `tidy.aareg`, `tidy.coxph`, `tidy.pyears`, `tidy.survdiff`, `tidy.survexp`, `tidy.survfit`, `tidy.survreg`

Examples

```
library(survival)

# examples come from cch documentation
subcoh <- nwtco$in.subcohort
```



```

selccoh <- with(nwtco, rel==1|subcoh==1)
ccoh.data <- nwtco[selccoh,]
ccoh.data$subcohort <- subcoh[selccoh]
## central-lab histology
ccoh.data$histol <- factor(ccoh.data$histol, labels=c("FH", "UH"))
## tumour stage
ccoh.data$stage <- factor(ccoh.data$stage, labels=c("I", "II", "III", "IV"))
ccoh.data$age <- ccoh.data$age/12 # Age in years

fit.ccP <- cch(Surv(edrel, rel) ~ stage + histol + age, data = ccoh.data,
              subcoh = ~subcohort, id= ~seqno, cohort.size = 4028)

tidy(fit.ccP)

# coefficient plot
library(ggplot2)
ggplot(tidy(fit.ccP), aes(x = estimate, y = term)) +
  geom_point() +
  geom_errorbarh(aes(xmin = conf.low, xmax = conf.high), height = 0) +
  geom_vline(xintercept = 0)

```

tidy.cld

Tidy a(n) cld object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'cld'
tidy(x, ...)
```

Arguments

x A cld object created by calling `multcomp::cld()` on a `glht`, `confint.glht()` or `summary.glht()` object.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the data argument.

See Also

[tidy\(\)](#), [multcomp::cld\(\)](#), [multcomp::summary.glht\(\)](#), [multcomp::confint.glht\(\)](#), [multcomp::glht\(\)](#)
 Other multcomp tidiers: [tidy.confint.glht](#), [tidy.glht](#), [tidy.summary.glht](#)

tidy.coefstest	<i>Tidy a(n) coefstest object</i>
----------------	-----------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'coefstest'
tidy(x, ...)
```

Arguments

x	A coefstest object returned from lmtest::coefstest() .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an augment() method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Value

A [tibble::tibble](#) with one row for each coefficient and columns:

term	The term in the linear model being estimated and tested
estimate	The estimated coefficient
std.error	The standard error
statistic	test statistic
p.value	p-value

See Also

[tidy\(\)](#), [lmtest::coefstest\(\)](#)

Examples

```
if (require("lmtest", quietly = TRUE)) {
  data(Mandible)
  fm <- lm(length ~ age, data=Mandible, subset=(age <= 28))

  lmtest::coefstest(fm)
  tidy(coefstest(fm))
}
```

tidy.confint.glm *Tidy a(n) confint.glm object*

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'confint.glm'
tidy(x, ...)
```

Arguments

x A confint.glm object created by calling `multcomp::confint.glm()` on a glm object created with `multcomp::glm()`.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

See Also

`tidy()`, `multcomp::confint.glm()`, `multcomp::glm()`

Other multcomp tidiers: `tidy.cld`, `tidy.glm`, `tidy.summary.glm`

tidy.confusionMatrix *Tidy a(n) confusionMatrix object*

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'confusionMatrix'
tidy(x, by_class = TRUE, ...)
```

Arguments

x	An object of class confusionMatrix created by a call to <code>caret::confusionMatrix()</code> .
by_class	Logical indicating whether or not to show performance measures broken down by class. Defaults to TRUE. When <code>by_class = FALSE</code> only returns a tibble with accuracy and kappa statistics.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A `tibble::tibble` with one or more of the following columns:

term	The name of a statistic from the confusion matrix
class	Which class the term is a measurement of
estimate	The value of the statistic
conf.low	Low end of 95 percent CI only applicable to accuracy
conf.high	High end of 95 percent CI only applicable to accuracy
p.value	P-value for accuracy and kappa statistics

See Also

`tidy()`, `caret::confusionMatrix()`

Examples

```

if (requireNamespace("caret", quietly = TRUE)) {

  set.seed(27)

  two_class_sample1 <- as.factor(sample(letters[1:2], 100, TRUE))
  two_class_sample2 <- as.factor(sample(letters[1:2], 100, TRUE))

  two_class_cm <- caret::confusionMatrix(
    two_class_sample1,
    two_class_sample2
  )

  tidy(two_class_cm)
  tidy(two_class_cm, by_class = FALSE)

  # multiclass example

  six_class_sample1 <- as.factor(sample(letters[1:6], 100, TRUE))
  six_class_sample2 <- as.factor(sample(letters[1:6], 100, TRUE))

  six_class_cm <- caret::confusionMatrix(
    six_class_sample1,
    six_class_sample2
  )

  tidy(six_class_cm)
  tidy(six_class_cm, by_class = FALSE)
}

```

tidy.coxph

Tidy a(n) coxph object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'coxph'
tidy(x, exponentiate = FALSE, conf.int = TRUE,
     conf.level = 0.95, ...)

```

Arguments

<code>x</code>	A coxph object returned from <code>survival::coxph()</code> .
<code>exponentiate</code>	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to FALSE.
<code>conf.int</code>	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A `tibble::tibble` with one row for each term and columns:

<code>estimate</code>	estimate of slope
<code>std.error</code>	standard error of estimate
<code>statistic</code>	test statistic
<code>p.value</code>	p-value

See Also

`tidy()`, `survival::coxph()`

Other coxph tidiers: `augment.coxph`, `glance.coxph`

Other survival tidiers: `augment.coxph`, `augment.survreg`, `glance.aareg`, `glance.cch`, `glance.coxph`, `glance.pyears`, `glance.survdiff`, `glance.survexp`, `glance.survfit`, `glance.survreg`, `tidy.aareg`, `tidy.cch`, `tidy.pyears`, `tidy.survdiff`, `tidy.survexp`, `tidy.survfit`, `tidy.survreg`

Examples

```
library(survival)

cf1t <- coxph(Surv(time, status) ~ age + sex, lung)

tidy(cf1t)
tidy(cf1t, exponentiate = TRUE)

lp <- augment(cf1t, lung)
risks <- augment(cf1t, lung, type.predict = "risk")
```

```
expected <- augment(cfit, lung, type.predict = "expected")

glance(cfit)

# also works on clogit models
resp <- levels(logan$occupation)
n <- nrow(logan)
indx <- rep(1:n, length(resp))
logan2 <- data.frame(
  logan[indx,],
  id = indx,
  tocc = factor(rep(resp, each=n))
)

logan2$case <- (logan2$occupation == logan2$tocc)

c1 <- clogit(case ~ tocc + tocc:education + strata(id), logan2)
tidy(c1)
glance(c1)

library(ggplot2)

ggplot(lp, aes(age, .fitted, color = sex)) +
  geom_point()

ggplot(risks, aes(age, .fitted, color = sex)) +
  geom_point()

ggplot(expected, aes(time, .fitted, color = sex)) +
  geom_point()
```

tidy.cv.glmnet

Tidy a(n) cv.glmnet object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'cv.glmnet'
tidy(x, ...)
```

Arguments

`x` A `cv.glmnet` object returned from `glmnet::cv.glmnet()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the data argument.

Value

A `tibble::tibble` with one-row for each value of the penalization parameter `lambda` in `x` and columns:

<code>lambda</code>	Value of the penalty parameter <code>lambda</code> .
<code>estimate</code>	Median loss across all cross-validation folds for a given <code>lambda</code> .
<code>std.error</code>	Standard error of the cross-validation estimated loss.
<code>conf.low</code>	lower bound on confidence interval for cross-validation estimated loss.
<code>conf.high</code>	Upper bound on confidence interval for cross-validation estimated loss.
<code>nzero</code>	Number of coefficients that are exactly zero for given <code>lambda</code>
<code>.</code>	

See Also

`tidy()`, `glmnet::cv.glmnet()`

Other `glmnet` tidiers: `glance.cv.glmnet`, `glance.glmnet`, `tidy.glmnet`

Examples

```
if (requireNamespace("glmnet", quietly = TRUE)) {
  library(glmnet)
  set.seed(27)

  nobs <- 100
  nvar <- 50
  real <- 5

  x <- matrix(rnorm(nobs * nvar), nobs, nvar)
  beta <- c(rnorm(real, 0, 1), rep(0, nvar - real))
  y <- c(t(beta) %*% t(x)) + rnorm(nvar, sd = 3)

  cvfit1 <- cv.glmnet(x,y)

  tidy(cvfit1)
  glance(cvfit1)
}
```



```

library(ggplot2)
tidied_cv <- tidy(cvfit1)
glance_cv <- glance(cvfit1)

# plot of MSE as a function of lambda
g <- ggplot(tidied_cv, aes(lambda, estimate)) + geom_line() + scale_x_log10()
g

# plot of MSE as a function of lambda with confidence ribbon
g <- g + geom_ribbon(aes(ymin = conf.low, ymax = conf.high), alpha = .25)
g

# plot of MSE as a function of lambda with confidence ribbon and choices
# of minimum lambda marked
g <- g + geom_vline(xintercept = glance_cv$lambda.min) +
  geom_vline(xintercept = glance_cv$lambda.1se, lty = 2)
g

# plot of number of zeros for each choice of lambda
ggplot(tidied_cv, aes(lambda, nzero)) + geom_line() + scale_x_log10()

# coefficient plot with min lambda shown
tidied <- tidy(cvfit1$glmnet.fit)
ggplot(tidied, aes(lambda, estimate, group = term)) + scale_x_log10() +
  geom_line() +
  geom_vline(xintercept = glance_cv$lambda.min) +
  geom_vline(xintercept = glance_cv$lambda.1se, lty = 2)
}

```

tidy.density

Tidy a(n) density object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'density'
tidy(x, ...)
```

Arguments

x A density object returned from `stats::density()`.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

A `tibble::tibble` with two columns: points `x` where the density is estimated, and estimated density `y`.

See Also

`tidy()`, `stats::density()`

Other stats tidiers: `tidy.dist`, `tidy.ftable`

`tidy.dist`

Tidy a(n) dist object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'dist'
tidy(x, diagonal = attr(x, "Diag"), upper = attr(x,
  "Upper"), ...)
```

Arguments

`x` A `dist` object returned from `stats::dist()`.

`diagonal` Logical indicating whether or not to tidy the diagonal elements of the distance matrix. Defaults to whatever was based to the `diag` argument of `stats::dist()`.

`upper` Logical indicating whether or not to tidy the upper half of the distance matrix. Defaults to whatever was based to the `upper` argument of `stats::dist()`.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Details

If the distance matrix does not include an upper triangle and/or diagonal, the tidied version will not either.

Value

A `tibble::tibble` with one row for each pair of items in the distance matrix, with columns:

<code>item1</code>	First item
<code>item2</code>	Second item
<code>distance</code>	Distance between items

See Also

`tidy()`, `stats::dist()`

Other stats tidiers: `tidy.density`, `tidy.ftable`

Examples

```
iris_dist <- dist(t(iris[, 1:4]))
iris_dist

tidy(iris_dist)
tidy(iris_dist, upper = TRUE)
tidy(iris_dist, diagonal = TRUE)
```

tidy.ergm

Tidy a(n) ergm object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

The methods should work with any model that conforms to the `ergm` class, such as those produced from weighted networks by the `ergm.count` package.

Usage

```
## S3 method for class 'ergm'
tidy(x, conf.int = FALSE, conf.level = 0.95,
     exponentiate = FALSE, ...)
```

Arguments

x	An ergm object returned from a call to <code>ergm::ergm()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
exponentiate	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to FALSE.
...	Additional arguments to pass to <code>ergm::summary()</code> . Cautionary note: Misppecified arguments may be silently ignored.

Value

A `tibble::tibble` with one row for each coefficient in the exponential random graph model, with columns:

term	The term in the model being estimated and tested
estimate	The estimated coefficient
std.error	The standard error
mcmc.error	The MCMC error
p.value	The two-sided p-value

References

Hunter DR, Handcock MS, Butts CT, Goodreau SM, Morris M (2008b). **ergm**: A Package to Fit, Simulate and Diagnose Exponential-Family Models for Networks. *Journal of Statistical Software*, 24(3). <http://www.jstatsoft.org/v24/i03/>.

See Also

`tidy()`, `ergm::ergm()`, `ergm::control.ergm()`, `ergm::summary()`

Other ergm tidiers: `glance.ergm`

Examples

```
library(ergm)
# Using the same example as the ergm package
# Load the Florentine marriage network data
data(florentine)

# Fit a model where the propensity to form ties between
# families depends on the absolute difference in wealth
gest <- ergm(flo marriage ~ edges + absdiff("wealth"))
```

```
# Show terms, coefficient estimates and errors
tidy(gest)

# Show coefficients as odds ratios with a 99% CI
tidy(gest, exponentiate = TRUE, conf.int = TRUE, conf.level = 0.99)

# Take a look at likelihood measures and other
# control parameters used during MCMC estimation
glance(gest)
glance(gest, deviance = TRUE)
glance(gest, mcmc = TRUE)
```

tidy.factanal	<i>Tidy a(n) factanal object</i>
---------------	----------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'factanal'
tidy(x, ...)
```

Arguments

x	A factanal object created by <code>stats::factanal()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Value

A `tibble::tibble` with one row for each variable used in the analysis and columns:

variable	The variable being estimated in the factor analysis
uniqueness	Proportion of residual, or unexplained variance
flX	Factor loading of term on factor X. There will be as many columns of this format as there were factors fitted.

See Also

[tidy\(\)](#), [stats::factanal\(\)](#)

Other factanal tidiers: [augment.factanal](#), [glance.factanal](#)

Examples

```
mod <- factanal(mtcars, 3, scores = "regression")

glance(mod)
tidy(mod)
augment(mod)
augment(mod, mtcars)
```

tidy.felm

Tidy a(n) felm object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'felm'
tidy(x, conf.int = FALSE, conf.level = 0.95,
     fe = FALSE, ...)
```

Arguments

x	A <code>felm</code> object returned from <code>lfe::felm()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
fe	Logical indicating whether or not to include estimates of fixed effects. Defaults to FALSE.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A `tibble::tibble()` with one row for each term in the regression. The tibble has columns:

<code>term</code>	The name of the regression term.
<code>estimate</code>	The estimated value of the regression term.
<code>std.error</code>	The standard error of the regression term.
<code>statistic</code>	The value of a statistic, almost always a T-statistic, to use in a hypothesis that the regression term is non-zero.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>conf.low</code>	The low end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .
<code>conf.high</code>	The high end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .

If `fe = TRUE`, also includes rows for fixed effects estimates.

See Also

`tidy()`, `lfe::felm()`

Other felm tidiers: `augment.felm`

Examples

```
if (require("lfe", quietly = TRUE)) {
  library(lfe)

  N=1e2
  DT <- data.frame(
    id = sample(5, N, TRUE),
    v1 = sample(5, N, TRUE),
    v2 = sample(1e6, N, TRUE),
    v3 = sample(round(runif(100,max=100),4), N, TRUE),
    v4 = sample(round(runif(100,max=100),4), N, TRUE)
  )

  result_felm <- felm(v2~v3, DT)
  tidy(result_felm)
  augment(result_felm)
  result_felm <- felm(v2~v3|id+v1, DT)
  tidy(result_felm, fe = TRUE)
  augment(result_felm)
  v1<-DT$v1
  v2 <- DT$v2
  v3 <- DT$v3
  id <- DT$id
  result_felm <- felm(v2~v3|id+v1)
  tidy(result_felm)
}
```

```

    augment(result_felm)
    glance(result_felm)
  }

```

tidy.fitdistr

Tidy a(n) fitdistr object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'fitdistr'
tidy(x, ...)

```

Arguments

x	A fitdistr object returned by <code>MASS::fitdistr()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A `tibble::tibble` with one row for estimated parameter, with columns:

term	The term that was estimated
estimate	Estimated value
std.error	Standard error of estimate

See Also

[tidy\(\)](#), [MASS::fitdistr\(\)](#)

Other fitdistr tidiers: [glance.fitdistr](#)

Examples

```
set.seed(2015)
x <- rnorm(100, 5, 2)

library(MASS)
fit <- fitdistr(x, dnorm, list(mean = 3, sd = 1))

tidy(fit)
glance(fit)
```

tidy.ftable	<i>Tidy a(n) ftable object</i>
-------------	--------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'ftable'
tidy(x, ...)
```

Arguments

x An ftable object returned from `stats::ftable()`.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

An ftable contains a "flat" contingency table. This melts it into a `tibble:tibble` with one column for each variable, then a `Freq` column.

See Also

`tidy()`, `stats::ftable()`

Other stats tidiers: `tidy.density`, `tidy.dist`

Examples

```
tidy(ftable(Titanic, row.vars = 1:3))
```

tidy.Gam	<i>Tidy a(n) Gam object</i>
----------	-----------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'Gam'
tidy(x, ...)
```

Arguments

x	A Gam object returned from a call to <code>gam::gam()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Details

Tidy gam objects created by calls to `mgcv::gam()` with `tidy.gam()`.

Value

The tidied output of the parametric ANOVA for the GAM model as a `tibble::tibble` with one row for each term in the model.

See Also

`tidy()`, `gam::gam()`, `tidy.anova()`, `tidy.gam()`

Other gam tidiers: `glance.Gam`

Examples

```
library(gam)
g <- gam(mpg ~ s(hp, 4) + am + qsec, data = mtcars)

tidy(g)
glance(g)
```

tidy.gam

Tidy a(n) gam object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'gam'
tidy(x, parametric = FALSE, ...)
```

Arguments

x	A gam object returned from a call to <code>mgcv::gam()</code> .
parametric	Logical indicating if parametric or smooth terms should be tidied. Defaults to FALSE, meaning that smooth terms are tidied by default.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Details

To tidy Gam objects created by calls to `gam::gam()`, see `tidy.Gam()`.

See Also

`tidy()`, `mgcv::gam()`, `tidy.Gam()`

Other mgcv tidiers: `glance.gam`

Examples

```
g <- mgcv::gam(mpg ~ s(hp) + am + qsec, data = mtcars)

tidy(g)
tidy(g, parametric = TRUE)
glance(g)
```

tidy.gamlss	<i>Tidy a(n) gamlss object</i>
-------------	--------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'gamlss'
tidy(x, quick = FALSE, ...)
```

Arguments

x	A gamlss object returned from <code>gamlss::gamlss()</code> .
quick	Logical indicating if the only the term and estimate columns should be returned. Often useful to avoid time consuming covariance and standard error calculations. Defaults to FALSE.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A `tibble::tibble` with one row for each coefficient, containing columns

parameter	Type of coefficient being estimated: mu, sigma, nu, or tau.
term	Name of term in the model.
estimate	Estimate coefficient of given term.

std.error	Standard error of given term.
statistic	T-statistic used to test hypothesis that coefficient equals zero.
p.value	Two sided p-value based on null hypothesis of coefficient equaling zero.

Examples

```
library(gamlss)

g <- gamlss(
  y ~ pb(x),
  sigma.fo = ~ pb(x),
  family = BCT,
  data = abdom,
  method = mixed(1, 20)
)

tidy(g)
```

tidy.garch	<i>Tidy a(n) garch object</i>
------------	-------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'garch'
tidy(x, ...)
```

Arguments

x	A garch object returned by <code>tseries::garch()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A `tibble::tibble` with one row for each coefficient and columns:

term	The term in the linear model being estimated and tested
estimate	The estimated coefficient
std.error	The standard error
statistic	test statistic
p.value	p-value

See Also

`tidy()`, `tseries::garch()`

Other garch tidiers: `glance.garch`

Examples

```
library(tseries)

data(EuStockMarkets)
dax <- diff(log(EuStockMarkets))[, "DAX"]
dax.garch <- garch(dax)
dax.garch

tidy(dax.garch)
glance(dax.garch)
```

tidy.geeglm

Tidy a(n) geeglm object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'geeglm'
tidy(x, conf.int = FALSE, conf.level = 0.95,
     exponentiate = FALSE, quick = FALSE, ...)
```

Arguments

<code>x</code>	A <code>geeglm</code> object returned from a call to <code>geepack::geeglm()</code> .
<code>conf.int</code>	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to <code>FALSE</code> .
<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>exponentiate</code>	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to <code>FALSE</code> .
<code>quick</code>	Logical indicating if the only the <code>term</code> and <code>estimate</code> columns should be returned. Often useful to avoid time consuming covariance and standard error calculations. Defaults to <code>FALSE</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Details

If `conf.int = TRUE`, the confidence interval is computed with the an internal `confint.geeglm()` function.

If you have missing values in your model data, you may need to refit the model with `na.action = na.exclude` or deal with the missingness in the data beforehand.

Value

A `tibble::tibble` with one row for each coefficient, with five columns:

<code>term</code>	The term in the linear model being estimated and tested
<code>estimate</code>	The estimated coefficient
<code>std.error</code>	The standard error from the GEE model
<code>statistic</code>	Wald statistic
<code>p.value</code>	two-sided p-value

If `conf.int = TRUE`, includes includes columns `conf.low` and `conf.high`, which are computed internally.

See Also

`tidy()`, `geepack::geeglm()`

Examples

```

if (requireNamespace("geepack", quietly = TRUE)) {
  library(geepack)
  data(state)

  ds <- data.frame(state.region, state.x77)

  geefit <- geeglm(Income ~ Frost + Murder, id = state.region,
                  data = ds, family = gaussian,
                  corstr = "exchangeable")

  tidy(geefit)
  tidy(geefit, quick = TRUE)
  tidy(geefit, conf.int = TRUE)
}

```

tidy.glht

Tidy a(n) glht object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'glht'
tidy(x, ...)

```

Arguments

x	A glht object returned by <code>multcomp::glht()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautious note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

See Also

`tidy()`, `multcomp::glht()`

Other multcomp tidiers: `tidy.cld`, `tidy.confint.glht`, `tidy.summary.glht`

Examples

```

if (require("multcomp") && require("ggplot2")) {

  library(multcomp)
  library(ggplot2)

  amod <- aov(breaks ~ wool + tension, data = warpbreaks)
  wht <- glht(amod, linfct = mcp(tension = "Tukey"))

  tidy(wht)
  ggplot(wht, aes(lhs, estimate)) + geom_point()

  CI <- confint(wht)
  tidy(CI)
  ggplot(CI, aes(lhs, estimate, ymin = lwr, ymax = upr)) +
    geom_pointrange()

  tidy(summary(wht))
  ggplot(mapping = aes(lhs, estimate)) +
    geom_linerange(aes(ymin = lwr, ymax = upr), data = CI) +
    geom_point(aes(size = p), data = summary(wht)) +
    scale_size(trans = "reverse")

  cld <- cld(wht)
  tidy(cld)
}

```

`tidy.glm`*Tidy a(n) glm object*

Description

This method wraps `tidy.lm()`.

Usage

```

## S3 method for class 'glm'
tidy(x, ...)

```

Arguments

`x` A `glm` object returned from `stats::glm()`.

`...` Arguments passed on to `tidy.lm`

`x` An `lm` object created by `stats::lm()`.

conf.int Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to `FALSE`.

- conf.level** The confidence level to use for the confidence interval if `conf.int = TRUE`. Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
- quick** Logical indicating if the only the `term` and `estimate` columns should be returned. Often useful to avoid time consuming covariance and standard error calculations. Defaults to `FALSE`.
- exponentiate** Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to `FALSE`.

Value

A `tibble::tibble()` with one row for each term in the regression. The tibble has columns:

<code>term</code>	The name of the regression term.
<code>estimate</code>	The estimated value of the regression term.
<code>std.error</code>	The standard error of the regression term.
<code>statistic</code>	The value of a statistic, almost always a T-statistic, to use in a hypothesis that the regression term is non-zero.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>conf.low</code>	The low end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .
<code>conf.high</code>	The high end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .

If the linear model is an `mlm` object (multiple linear model), there is an additional column:

<code>response</code>	Which response column the coefficients correspond to (typically Y1, Y2, etc)
-----------------------	--

See Also

`tidy()`, `tidy.lm()`

`stats::glm()`

Other lm tidiers: `augment.glm`, `augment.lm`, `glance.glm`, `glance.lm`, `tidy.lm`

`tidy.glmnet`

Tidy a(n) glmnet object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'glmnet'
tidy(x, return_zeros = FALSE, ...)
```

Arguments

x	A glmnet object returned from <code>glmnet::glmnet()</code> .
return_zeros	Logical indicating whether coefficients with value zero should be included in the results. Defaults to FALSE.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Details

Note that while this representation of GLMs is much easier to plot and combine than the default structure, it is also much more memory-intensive. Do not use for large, sparse matrices.

No `augment` method is yet provided even though the model produces predictions, because the input data is not tidy (it is a matrix that may be very wide) and therefore combining predictions with it is not logical. Furthermore, predictions make sense only with a specific choice of `lambda`.

Value

A `tibble::tibble` with columns:

term	coefficient name (V1...VN by default, along with "(Intercept)")
step	which step of lambda choices was used
estimate	estimate of coefficient
lambda	value of penalty parameter lambda
dev.ratio	fraction of null deviance explained at each value of lambda

See Also

`tidy()`, `glmnet::glmnet()`

Other glmnet tidiers: `glance.cv.glmnet`, `glance.glmnet`, `tidy.cv.glmnet`

Examples

```
if (requireNamespace("glmnet", quietly = TRUE)) {
  library(glmnet)
```

```

set.seed(2014)
x <- matrix(rnorm(100*20),100,20)
y <- rnorm(100)
fit1 <- glmnet(x,y)

tidy(fit1)
glance(fit1)

library(dplyr)
library(ggplot2)

tidied <- tidy(fit1) %>% filter(term != "(Intercept)")

ggplot(tidied, aes(step, estimate, group = term)) + geom_line()
ggplot(tidied, aes(lambda, estimate, group = term)) +
  geom_line() + scale_x_log10()

ggplot(tidied, aes(lambda, dev.ratio)) + geom_line()

# works for other types of regressions as well, such as logistic
g2 <- sample(1:2, 100, replace=TRUE)
fit2 <- glmnet(x, g2, family="binomial")
tidy(fit2)
}

```

tidy.glmRob

Tidy a(n) glmRob object

Description

This method wraps [tidy.lm\(\)](#).

Usage

```
## S3 method for class 'glmRob'
tidy(x, ...)
```

Arguments

x A glmRob object returned from [robust::glmRob\(\)](#).

... Arguments passed on to [tidy.lm](#)

x An lm object created by [stats::lm\(\)](#).

conf.int Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.

conf.level The confidence level to use for the confidence interval if `conf.int = TRUE`. Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.

quick Logical indicating if the only the term and estimate columns should be returned. Often useful to avoid time consuming covariance and standard error calculations. Defaults to FALSE.

exponentiate Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to FALSE.

Details

For tidiers for robust models from the **MASS** package see [tidy.rlm\(\)](#).

Value

A `tibble::tibble()` with one row for each term in the regression. The tibble has columns:

term	The name of the regression term.
estimate	The estimated value of the regression term.
std.error	The standard error of the regression term.
statistic	The value of a statistic, almost always a T-statistic, to use in a hypothesis that the regression term is non-zero.
p.value	The two-sided p-value associated with the observed statistic.
conf.low	The low end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .
conf.high	The high end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .

If the linear model is an `mlm` object (multiple linear model), there is an additional column:

response	Which response column the coefficients correspond to (typically Y1, Y2, etc)
----------	--

See Also

[tidy\(\)](#), [tidy.lm\(\)](#)

[robust::glmRob\(\)](#)

Other robust tidiers: [augment.glmRob](#), [augment.lmRob](#), [glance.glmRob](#), [glance.lmRob](#), [tidy.lmRob](#)

Examples

```
library(robust)
m <- lmRob(mpg ~ wt, data = mtcars)

tidy(m)
augment(m)
glance(m)

gm <- glmRob(am ~ wt, data = mtcars, family = "binomial")
glance(gm)
```

tidy.gmm	<i>Tidy a(n) gmm object</i>
----------	-----------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'gmm'
tidy(x, conf.int = FALSE, conf.level = 0.95,
     exponentiate = FALSE, quick = FALSE, ...)
```

Arguments

x	A gmm object returned from <code>gmm::gmm()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
exponentiate	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to FALSE.
quick	Logical indicating if the only the term and estimate columns should be returned. Often useful to avoid time consuming covariance and standard error calculations. Defaults to FALSE.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A `tibble::tibble()` with one row for each term in the regression. The tibble has columns:

term	The name of the regression term.
estimate	The estimated value of the regression term.
std.error	The standard error of the regression term.

statistic	The value of a statistic, almost always a T-statistic, to use in a hypothesis that the regression term is non-zero.
p.value	The two-sided p-value associated with the observed statistic.
conf.low	The low end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .
conf.high	The high end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .

See Also

[tidy\(\)](#), [gmm::gmm\(\)](#)

Other gmm tidiers: [glance.gmm](#)

Examples

```
if (requireNamespace("gmm", quietly = TRUE)) {
  library(gmm)

  # examples come from the "gmm" package
  ## CAPM test with GMM
  data(Finance)
  r <- Finance[1:300, 1:10]
  rm <- Finance[1:300, "rm"]
  rf <- Finance[1:300, "rf"]

  z <- as.matrix(r-rf)
  t <- nrow(z)
  zm <- rm-rf
  h <- matrix(zm, t, 1)
  res <- gmm(z ~ zm, x = h)

  # tidy result
  tidy(res)
  tidy(res, conf.int = TRUE)
  tidy(res, conf.int = TRUE, conf.level = .99)

  # coefficient plot
  library(ggplot2)
  library(dplyr)
  tidy(res, conf.int = TRUE) %>%
    mutate(variable = reorder(variable, estimate)) %>%
    ggplot(aes(estimate, variable)) +
    geom_point() +
    geom_errorbarh(aes(xmin = conf.low, xmax = conf.high)) +
    facet_wrap(~ term) +
    geom_vline(xintercept = 0, color = "red", lty = 2)

  # from a function instead of a matrix
  g <- function(theta, x) {
```

```

e <- x[,2:11] - theta[1] - (x[,1] - theta[1]) %*% matrix(theta[2:11], 1, 10)
gmat <- cbind(e, e*c(x[,1]))
return(gmat) }

x <- as.matrix(cbind(rm, r))
res_black <- gmm(g, x = x, t0 = rep(0, 11))

tidy(res_black)
tidy(res_black, conf.int = TRUE)

## APT test with Fama-French factors and GMM

f1 <- zm
f2 <- Finance[1:300, "hml"] - rf
f3 <- Finance[1:300, "smb"] - rf
h <- cbind(f1, f2, f3)
res2 <- gmm(z ~ f1 + f2 + f3, x = h)

td2 <- tidy(res2, conf.int = TRUE)
td2

# coefficient plot
td2 %>%
  mutate(variable = reorder(variable, estimate)) %>%
  ggplot(aes(estimate, variable)) +
  geom_point() +
  geom_errorbarh(aes(xmin = conf.low, xmax = conf.high)) +
  facet_wrap(~ term) +
  geom_vline(xintercept = 0, color = "red", lty = 2)
}

```

tidy.htest

Tidy/glance a(n) htest object

Description

For models that have only a single component, the `tidy()` and `glance()` methods are identical. Please see the documentation for both of those methods.

Usage

```

## S3 method for class 'htest'
tidy(x, ...)

## S3 method for class 'htest'
glance(x, ...)

```


Arguments

<code>x</code>	An <code>htest</code> objected, such as those created by <code>stats::cor.test()</code> , <code>stats::t.test()</code> , <code>stats::wilcox.test()</code> , <code>stats::chisq.test()</code> , etc.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Value

A one-row `tibble::tibble` with one or more of the following columns, depending on which hypothesis test was used.

<code>estimate</code>	Estimate of the effect size
<code>statistic</code>	Test statistic used to compute the p-value
<code>p.value</code>	P-value
<code>parameter</code>	Parameter field in the <code>htest</code> , typically degrees of freedom
<code>conf.low</code>	Lower bound on a confidence interval
<code>conf.high</code>	Upper bound on a confidence interval
<code>estimate1</code>	Sometimes two estimates are computed, such as in a two-sample t-test
<code>estimate2</code>	Sometimes two estimates are computed, such as in a two-sample t-test
<code>method</code>	Method used to compute the statistic as a string
<code>alternative</code>	Alternative hypothesis as a string

See Also

`tidy()`, `stats::cor.test()`, `stats::t.test()`, `stats::wilcox.test()`, `stats::chisq.test()`
 Other `htest` tidiers: `augment.htest`, `tidy.pairwise.htest`, `tidy.power.htest`

Examples

```
tt <- t.test(rnorm(10))
tidy(tt)
glance(tt) # same output for all htests

tt <- t.test(mpg ~ am, data = mtcars)
tidy(tt)

wt <- wilcox.test(mpg ~ am, data = mtcars, conf.int = TRUE, exact = FALSE)
tidy(wt)

ct <- cor.test(mtcars$wt, mtcars$mpg)
```

```
tidy(ct)

chit <- chisq.test(xtabs(Freq ~ Sex + Class, data = as.data.frame(Titanic)))
tidy(chit)
augment(chit)
```

tidy.ivreg

Tidy a(n) ivreg object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'ivreg'
tidy(x, conf.int = FALSE, conf.level = 0.95,
     exponentiate = FALSE, ...)
```

Arguments

x	An ivreg object created by a call to <code>AER::ivreg()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
exponentiate	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to FALSE.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A `tibble::tibble()` with one row for each term in the regression. The tibble has columns:

<code>term</code>	The name of the regression term.
<code>estimate</code>	The estimated value of the regression term.
<code>std.error</code>	The standard error of the regression term.
<code>statistic</code>	The value of a statistic, almost always a T-statistic, to use in a hypothesis that the regression term is non-zero.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>conf.low</code>	The low end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .
<code>conf.high</code>	The high end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .

See Also

`tidy()`, `AER::ivreg()`

Other ivreg tidiers: `augment.ivreg`, `glance.ivreg`

Examples

```
library(AER)

data("CigarettesSW", package = "AER")
ivr <- ivreg(
  log(packs) ~ income | population,
  data = CigarettesSW,
  subset = year == "1995"
)

summary(ivr)

tidy(ivr)
tidy(ivr, conf.int = TRUE)
tidy(ivr, conf.int = TRUE, exponentiate = TRUE)

augment(ivr)

glance(ivr)
```

tidy.kappa

Tidy a(n) kappa object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'kappa'
tidy(x, ...)
```

Arguments

`x` A kappa object returned from `psych::cohen.kappa()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the data argument.

Details

Note that confidence level (alpha) for the confidence interval cannot be set in tidy. Instead you must set the alpha argument to `psych::cohen.kappa()` when creating the kappa object.

Value

A `tibble::tibble` with columns:

<code>type</code>	Either "weighted" or "unweighted"
<code>estimate</code>	The estimated value of kappa with this method
<code>conf.low</code>	Lower bound of confidence interval
<code>conf.high</code>	Upper bound of confidence interval

See Also

`tidy()`, `psych::cohen.kappa()`

Examples

```
library(psych)

rater1 = 1:9
rater2 = c(1, 3, 1, 6, 1, 5, 5, 6, 7)
ck <- cohen.kappa(cbind(rater1, rater2))

tidy(ck)

# graph the confidence intervals
library(ggplot2)
ggplot(tidy(ck), aes(estimate, type)) +
  geom_point() +
  geom_errorbarh(aes(xmin = conf.low, xmax = conf.high))
```

tidy.kde

Tidy a(n) kde object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'kde'
tidy(x, ...)
```

Arguments

x	A kde object returned from <code>ks::kde()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A `tibble::tibble` with one row for each point in the estimated grid. The result contains one column (named `x1`, `x2`, etc) for each dimension, and an `estimate` column containing the estimated density.

See Also

[tidy\(\)](#), [ks::kde\(\)](#)

Examples

```
if (requireNamespace("ks", quietly = TRUE)) {  
  
  library(ks)  
  
  dat <- replicate(2, rnorm(100))  
  k <- kde(dat)  
  
  td <- tidy(k)  
  td  
  
  library(ggplot2)  
  ggplot(td, aes(x1, x2, fill = estimate)) +  
    geom_tile() +  
    theme_void()  
  
  # also works with 3 dimensions  
  dat3 <- replicate(3, rnorm(100))  
  k3 <- kde(dat3)  
  
  td3 <- tidy(k3)  
  td3  
}
```

tidy.Kendall

Tidy a(n) Kendall object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'Kendall'  
tidy(x, ...)
```

Arguments

`x` A Kendall object returned from a call to `Kendall::Kendall()`, `Kendall::MannKendall()`, or `Kendall::SeasonalMannKendall()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

A `tibble::tibble` with one row and columns:

<code>statistic</code>	Kendall's tau statistic.
<code>p.value</code>	two-sided p-value.
<code>kendall_score</code>	Kendall score.
<code>denominator</code>	The denominator, which is $\tau = \text{kendall_score} / \text{denominator}$.
<code>var_kendall_score</code>	Variance of the <code>kendall_score</code> .

See Also

`tidy()`, `Kendall::Kendall()`, `Kendall::MannKendall()`, `Kendall::SeasonalMannKendall()`

Examples

```
library(Kendall)

A <- c(2.5, 2.5, 2.5, 2.5, 5, 6.5, 6.5, 10, 10, 10, 10, 10, 14, 14, 14, 16, 17)
B <- c(1, 1, 1, 1, 2, 1, 1, 2, 1, 1, 1, 1, 1, 1, 2, 2, 2)

f_res <- Kendall(A, B)
tidy(f_res)

s_res <- MannKendall(B)
tidy(s_res)

t_res <- SeasonalMannKendall(ts(A))
tidy(t_res)
```

tidy.kmeans

*Tidy a(n) kmeans object***Description**

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'kmeans'
tidy(x, col.names = paste0("x", 1:ncol(x$centers)), ...)
```

Arguments

x	A kmeans object created by <code>stats::kmeans()</code> .
col.names	Dimension names. Defaults to x1, x2, ...
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Details

For examples, see the `kmeans` vignette.

Value

A `tibble::tibble` with one row per cluster, and columns:

size	Number of points in cluster
withinss	The within-cluster sum of squares
cluster	A factor describing the cluster from 1:k

See Also

`tidy()`, `stats::kmeans()`

Other kmeans tidiers: `augment.kmeans`, `glance.kmeans`

tidy.lavaan	<i>Tidy a(n) lavaan object</i>
-------------	--------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'lavaan'
tidy(x, conf.int = TRUE, conf.level = 0.95, ...)
```

Arguments

x	A lavaan object, such as those return from <code>lavaan::cfa()</code> , and <code>lavaan::sem()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
...	Additional arguments passed to <code>lavaan::parameterEstimates()</code> . Cautionary note: Misspecified arguments may be silently ignored.

Value

A `tibble::tibble` with one row for each estimated parameter and columns:

term	The result of <code>paste(lhs, op, rhs)</code>
op	The operator in the model syntax (e.g. <code>~~</code> for covariances, or <code>~</code> for regression parameters)
group	The group (if specified) in the lavaan model
estimate	The parameter estimate (may be standardized)
std.error	
statistic	The z value returned by <code>lavaan::parameterEstimates()</code>
p.value	
conf.low	
conf.high	
std.lv	Standardized estimates based on the variances of the (continuous) latent variables only
std.all	Standardized estimates based on both the variances of both (continuous) observed and latent variables.
std.nox	Standardized estimates based on both the variances of both (continuous) observed and latent variables, but not the variances of exogenous covariates.

See Also

[tidy\(\)](#), [lavaan::cfa\(\)](#), [lavaan::sem\(\)](#), [lavaan::parameterEstimates\(\)](#)

Other lavaan tidiers: [glance.lavaan](#)

Examples

```
if (require("lavaan")) {
  library(lavaan)

  cfa.fit <- cfa('F =~ x1 + x2 + x3 + x4 + x5 + x6 + x7 + x8 + x9',
               data = HolzingerSwineford1939, group = "school")
  tidy(cfa.fit)
}
```

tidy.lm

Tidy a(n) lm object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'lm'
tidy(x, conf.int = FALSE, conf.level = 0.95,
     exponentiate = FALSE, quick = FALSE, ...)
```

```
## S3 method for class 'summary.lm'
tidy(x, ...)
```

Arguments

<code>x</code>	An <code>lm</code> object created by stats::lm() .
<code>conf.int</code>	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to <code>FALSE</code> .
<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>exponentiate</code>	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to <code>FALSE</code> .

<code>quick</code>	Logical indicating if the only the term and estimate columns should be returned. Often useful to avoid time consuming covariance and standard error calculations. Defaults to FALSE.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Details

If you have missing values in your model data, you may need to refit the model with `na.action = na.exclude`.

Value

A `tibble::tibble()` with one row for each term in the regression. The tibble has columns:

<code>term</code>	The name of the regression term.
<code>estimate</code>	The estimated value of the regression term.
<code>std.error</code>	The standard error of the regression term.
<code>statistic</code>	The value of a statistic, almost always a T-statistic, to use in a hypothesis that the regression term is non-zero.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>conf.low</code>	The low end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .
<code>conf.high</code>	The high end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .

If the linear model is an `mlm` object (multiple linear model), there is an additional column:

<code>response</code>	Which response column the coefficients correspond to (typically Y1, Y2, etc)
-----------------------	--

See Also

[tidy\(\)](#), [stats::summary.lm\(\)](#)

Other lm tidiers: [augment.glm](#), [augment.lm](#), [glance.glm](#), [glance.lm](#), [tidy.glm](#)

Examples

```
library(ggplot2)
library(dplyr)

mod <- lm(mpg ~ wt + qsec, data = mtcars)

tidy(mod)
```

```

glance(mod)

# coefficient plot
d <- tidy(mod) %>%
  mutate(
    low = estimate - std.error,
    high = estimate + std.error
  )

ggplot(d, aes(estimate, term, xmin = low, xmax = high, height = 0)) +
  geom_point() +
  geom_vline(xintercept = 0) +
  geom_errorbarh()

augment(mod)
augment(mod, mtcars)

# predict on new data
newdata <- mtcars %>% head(6) %>% mutate(wt = wt + 1)
augment(mod, newdata = newdata)

au <- augment(mod, data = mtcars)

ggplot(au, aes(.hat, .std.resid)) +
  geom_vline(size = 2, colour = "white", xintercept = 0) +
  geom_hline(size = 2, colour = "white", yintercept = 0) +
  geom_point() + geom_smooth(se = FALSE)

plot(mod, which = 6)
ggplot(au, aes(.hat, .cooks)) +
  geom_vline(xintercept = 0, colour = NA) +
  geom_abline(slope = seq(0, 3, by = 0.5), colour = "white") +
  geom_smooth(se = FALSE) +
  geom_point()

# column-wise models
a <- matrix(rnorm(20), nrow = 10)
b <- a + rnorm(length(a))
result <- lm(b ~ a)
tidy(result)

```

tidy.lmodel2

Tidy a(n) lmodel2 object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'lmodel2'
tidy(x, ...)
```

Arguments

`x` A `lmodel2` object returned by `lmodel2::lmodel2()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Details

There are always only two terms in an `lmodel2`: "Intercept" and "Slope". These are computed by four methods: OLS (ordinary least squares), MA (major axis), SMA (standard major axis), and RMA (ranged major axis).

Value

A `tibble::tibble` within eight rows (one for each term estimated with each method) and columns:

<code>method</code>	Either OLS/MA/SMA/RMA
<code>term</code>	Either "Intercept" or "Slope"
<code>estimate</code>	Estimated coefficient
<code>conf.low</code>	Lower bound of 95% confidence interval
<code>conf.high</code>	Upper bound of 95% confidence interval

See Also

`tidy()`, `lmodel2::lmodel2()`

Other `lmodel2` tidiers: `glance.lmodel2`

Examples

```
if (require("lmodel2", quietly = TRUE)) {
  library(lmodel2)

  data(mod2ex2)
  Ex2.res <- lmodel2(Prey ~ Predators, data=mod2ex2, "relative", "relative", 99)
  Ex2.res

  tidy(Ex2.res)
```

```

glance(Ex2.res)

# this allows coefficient plots with ggplot2
library(ggplot2)
ggplot(tidy(Ex2.res), aes(estimate, term, color = method)) +
  geom_point() +
  geom_errorbarh(aes(xmin = conf.low, xmax = conf.high)) +
  geom_errorbarh(aes(xmin = conf.low, xmax = conf.high))
}

```

tidy.lmRob

Tidy a(n) lmRob object

Description

This method wraps `tidy.lm()`.

Usage

```

## S3 method for class 'lmRob'
tidy(x, ...)

```

Arguments

x A `lmRob` object returned from `robust::lmRob()`.

... Arguments passed on to `tidy.lm`

x An `lm` object created by `stats::lm()`.

conf.int Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to `FALSE`.

conf.level The confidence level to use for the confidence interval if `conf.int = TRUE`. Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.

quick Logical indicating if the only the term and estimate columns should be returned. Often useful to avoid time consuming covariance and standard error calculations. Defaults to `FALSE`.

exponentiate Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to `FALSE`.

Details

For tidiers for robust models from the **MASS** package see `tidy.rlm()`.

Value

A `tibble::tibble()` with one row for each term in the regression. The tibble has columns:

<code>term</code>	The name of the regression term.
<code>estimate</code>	The estimated value of the regression term.
<code>std.error</code>	The standard error of the regression term.
<code>statistic</code>	The value of a statistic, almost always a T-statistic, to use in a hypothesis that the regression term is non-zero.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>conf.low</code>	The low end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .
<code>conf.high</code>	The high end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .

If the linear model is an `mlm` object (multiple linear model), there is an additional column:

<code>response</code>	Which response column the coefficients correspond to (typically Y1, Y2, etc)
-----------------------	--

See Also

[tidy\(\)](#), [tidy.lm\(\)](#)

[robust::lmRob\(\)](#)

Other robust tidiers: [augment.glmRob](#), [augment.lmRob](#), [glance.glmRob](#), [glance.lmRob](#), [tidy.glmRob](#)

Examples

```
library(robust)
m <- lmRob(mpg ~ wt, data = mtcars)

tidy(m)
augment(m)
glance(m)

gm <- glmRob(am ~ wt, data = mtcars, family = "binomial")
glance(gm)
```

tidy.manova

*Tidy a(n) manova object***Description**

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'manova'
tidy(x, test = "Pillai", ...)
```

Arguments

x	A manova object return from <code>stats::manova()</code> .
test	One of "Pillai" (Pillai's trace), "Wilks" (Wilk's lambda), "Hotelling-Lawley" (Hotelling-Lawley trace) or "Roy" (Roy's greatest root) indicating which test statistic should be used. Defaults to "Pillai".
...	Arguments passed on to <code>stats::summary.manova</code>

object An object of class "manova" or an aov object with multiple responses.
test The name of the test statistic to be used. Partial matching is used so the name can be abbreviated.
intercept logical. If TRUE, the intercept term is included in the table.
tol tolerance to be used in deciding if the residuals are rank-deficient: see [qr](#).

Value

A `tibble::tibble` with columns:

```
\item{term}{Term in design}
\item{statistic}{Approximate F statistic}
\item{num.df}{Degrees of freedom}
\item{p.value}{P-value}
```

Depending on which test statistic is specified, one of the following columns is also included:

```
\item{pillai}{Pillai's trace}
\item{wilks}{Wilk's lambda}
\item{hl}{Hotelling-Lawley trace}
\item{roy}{Roy's greatest root}
```


See Also

[tidy\(\)](#), [stats::summary.manova\(\)](#)

Other anova tidiers: [tidy.TukeyHSD](#), [tidy.anova](#), [tidy.aovlist](#), [tidy.aov](#)

Examples

```
npk2 <- within(npk, foo <- rnorm(24))
m <- manova(cbind(yield, foo) ~ block + N * P * K, npk2)
tidy(m)
```

tidy.map

Tidy a(n) map object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'map'
tidy(x, ...)
```

Arguments

x A map object returned from [maps::map\(\)](#).

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in **...**, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an [augment\(\)](#) method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

See Also

[tidy\(\)](#), [maps::map\(\)](#)

Examples

```
if (require("maps") && require("ggplot2")) {
  library(maps)
  library(ggplot2)

  ca <- map("county", "ca", plot = FALSE, fill = TRUE)
  tidy(ca)
  qplot(long, lat, data = ca, geom = "polygon", group = group)

  tx <- map("county", "texas", plot = FALSE, fill = TRUE)
  tidy(tx)
  qplot(long, lat, data = tx, geom = "polygon", group = group,
        colour = I("white"))
}
```

tidy.Mclust

Tidy a(n) Mclust object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'Mclust'
tidy(x, ...)
```

Arguments

x	An Mclust object return from <code>mclust::Mclust()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A `tibble::tibble` with one row per component:

component	Cluster id as a factor. For a model k clusters, these will be as <code>.factor(1:k)</code> , or as <code>.factor(0:k)</code> if there's a noise term.
size	Number of observations assigned to component
proportion	The mixing proportion of each component
variance	In case of one-dimensional and spherical models, the variance for each component, omitted otherwise. NA for noise component
mean	The mean for each component. In case of 2+ dimensional models, a column with the mean is added for each dimension. NA for noise component

See Also

`tidy()`, `mclust::Mclust()`

Other mclust tidiers: `augment.Mclust`

Examples

```
library(dplyr)
library(mclust)
set.seed(27)

centers <- tibble::tibble(
  cluster = factor(1:3),
  num_points = c(100, 150, 50), # number points in each cluster
  x1 = c(5, 0, -3), # x1 coordinate of cluster center
  x2 = c(-1, 1, -2) # x2 coordinate of cluster center
)

points <- centers %>%
  mutate(
    x1 = purrr::map2(num_points, x1, rnorm),
    x2 = purrr::map2(num_points, x2, rnorm)
  ) %>%
  select(-num_points, -cluster) %>%
  tidyr::unnest(x1, x2)

m <- mclust::Mclust(points)

tidy(m)
augment(m, points)
glance(m)
```

tidy.mjoint

*Tidy a(n) mjoint object***Description**

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'mjoint'
tidy(x, component = "survival", conf.int = FALSE,
     conf.level = 0.95, boot_se = NULL, ...)
```

Arguments

x	An mjoint object returned from <code>joineRML::mjoint()</code> .
component	Character specifying whether to tidy the survival or the longitudinal component of the model. Must be either "survival" or "longitudinal". Defaults to "survival".
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
boot_se	Optionally a bootSE object from <code>joineRML::bootSE()</code> . If specified, calculates confidence intervals via the bootstrap. Defaults to NULL, in which case standard errors are calculated from the empirical information matrix.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Value

A `tibble::tibble()` with one row for each term in the regression. The tibble has columns:

term	The name of the regression term.
estimate	The estimated value of the regression term.
std.error	The standard error of the regression term.

statistic	The value of a statistic, almost always a T-statistic, to use in a hypothesis that the regression term is non-zero.
p.value	The two-sided p-value associated with the observed statistic.
conf.low	The low end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .
conf.high	The high end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .

See Also

[tidy\(\)](#), [joineRML::mjoint\(\)](#), [joineRML::bootSE\(\)](#)

Other mjoint tidiers: [glance.mjoint](#)

Examples

```
## Not run:
# Fit a joint model with bivariate longitudinal outcomes
library(joineRML)
data(heart.valve)
hvd <- heart.valve[!is.na(heart.valve$log.grad) &
                  !is.na(heart.valve$log.lvmi) &
                  heart.valve$num <= 50, ]

fit <- mjoint(
  formLongFixed = list(
    "grad" = log.grad ~ time + sex + hs,
    "lvmi" = log.lvmi ~ time + sex
  ),
  formLongRandom = list(
    "grad" = ~ 1 | num,
    "lvmi" = ~ time | num
  ),
  formSurv = Surv(fuyrs, status) ~ age,
  data = hvd,
  inits = list("gamma" = c(0.11, 1.51, 0.80)),
  timeVar = "time"
)

# Extract the survival fixed effects
tidy(fit)

# Extract the longitudinal fixed effects
tidy(fit, component = "longitudinal")

# Extract the survival fixed effects with confidence intervals
tidy(fit, ci = TRUE)

# Extract the survival fixed effects with confidence intervals based
# on bootstrapped standard errors
bSE <- bootSE(fit, nboot = 5, safe.boot = TRUE)
tidy(fit, boot_se = bSE, ci = TRUE)
```

```
# Augment original data with fitted longitudinal values and residuals
hvd2 <- augment(fit)

# Extract model statistics
glance(fit)

## End(Not run)
```

tidy.mle2	<i>Tidy a(n) mle2 object</i>
-----------	------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'mle2'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

x	An mle2 object created by a call to <code>bbmle::mle2()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

See Also

[tidy\(\)](#), [bbmle::mle2\(\)](#), [tidy_optim\(\)](#)

Examples

```
if (require("bbmle", quietly = TRUE)) {
  x <- 0:10
  y <- c(26, 17, 13, 12, 20, 5, 9, 8, 5, 4, 8)
  d <- data.frame(x,y)

  fit <- mle2(y ~ dpois(lambda = ymean),
             start = list(ymean = mean(y)), data = d)

  tidy(fit)
}
```

tidy.muhaz

Tidy a(n) muhaz object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'muhaz'
tidy(x, ...)
```

Arguments

x A muhaz object returned by `muhaz::muhaz()`.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

A `tibble::tibble` with two columns:

<code>time</code>	The time at which the hazard rate was estimated.
<code>estimate</code>	The estimated hazard rate.

See Also

[tidy\(\)](#), [muhaz::muhaz\(\)](#)

Other muhaz tidiers: [glance.muhaz](#)

Examples

```
if (require("muhaz", quietly = TRUE)) {
  data(ovarian, package="survival")
  x <- muhaz::muhaz(ovarian$futime, ovarian$fustat)
  tidy(x)
  glance(x)
}
```

tidy.multinom

Tidying methods for multinomial logistic regression models

Description

These methods tidy the coefficients of multinomial logistic regression models generated by `multinom` of the `nnet` package.

Usage

```
## S3 method for class 'multinom'
tidy(x, conf.int = FALSE, conf.level = 0.95,
     exponentiate = TRUE, ...)
```

Arguments

<code>x</code>	A <code>multinom</code> object returned from <code>nnet::multinom()</code> .
<code>conf.int</code>	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to <code>FALSE</code> .
<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>exponentiate</code>	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to <code>FALSE</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

`tidy.multinom` returns one row for each coefficient at each level of the response variable, with six columns:

<code>y.value</code>	The response level
<code>term</code>	The term in the model being estimated and tested
<code>estimate</code>	The estimated coefficient
<code>std.error</code>	The standard error from the linear model
<code>statistic</code>	Wald z-statistic
<code>p.value</code>	two-sided p-value

If `conf.int = TRUE`, also includes columns for `conf.low` and `conf.high`.

See Also

[tidy\(\)](#), [nnet::multinom\(\)](#)

Other multinom tidiers: [glance.multinom](#)

Examples

```
if (require(nnet) & require(MASS)){
  library(nnet)
  library(MASS)

  example(birthwt)
  bwt.mu <- multinom(low ~ ., bwt)
  tidy(bwt.mu)
  glance(bwt.mu)

  /* This model is a truly terrible model
  /* but it should show you what the output looks
  /* like in a multinomial logistic regression

  fit.gear <- multinom(gear ~ mpg + factor(am), data = mtcars)
  tidy(fit.gear)
  glance(fit.gear)
}
```

tidy.nlrq

Tidy a(n) nlrq object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'nlrq'
tidy(x, conf.int = FALSE, conf.level = 0.95, ...)
```

Arguments

x	A <code>nlrq</code> object returned from <code>quantreg::nlrq()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to <code>FALSE</code> .
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A `tibble::tibble()` with one row for each term in the regression. The tibble has columns:

term	The name of the regression term.
estimate	The estimated value of the regression term.
std.error	The standard error of the regression term.
statistic	The value of a statistic, almost always a T-statistic, to use in a hypothesis that the regression term is non-zero.
p.value	The two-sided p-value associated with the observed statistic.
conf.low	The low end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .
conf.high	The high end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .

See Also

`tidy()`, `quantreg::nlrq()`

Other `quantreg` tidiers: `augment.nlrq`, `augment.rqs`, `augment.rq`, `glance.nlrq`, `glance.rq`, `tidy.rqs`, `tidy.rq`

tidy.nls

*Tidy a(n) nls object***Description**

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'nls'
tidy(x, conf.int = FALSE, conf.level = 0.95,
     quick = FALSE, ...)
```

Arguments

x	An nls object returned from <code>stats::nls()</code> .
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
quick	Logical indicating if the only the term and estimate columns should be returned. Often useful to avoid time consuming covariance and standard error calculations. Defaults to FALSE.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A `tibble::tibble()` with one row for each term in the regression. The tibble has columns:

term	The name of the regression term.
estimate	The estimated value of the regression term.
std.error	The standard error of the regression term.
statistic	The value of a statistic, almost always a T-statistic, to use in a hypothesis that the regression term is non-zero.
p.value	The two-sided p-value associated with the observed statistic.

conf.low	The low end of a confidence interval for the regression term. Included only if conf.int = TRUE.
conf.high	The high end of a confidence interval for the regression term. Included only if conf.int = TRUE.

See Also

[tidy](#), [stats::nls\(\)](#), [stats::summary.nls\(\)](#)

Other nls tidiers: [augment.nls](#), [glance.nls](#)

Examples

```
n <- nls(mpg ~ k * e ^ wt, data = mtcars, start = list(k = 1, e = 2))

tidy(n)
augment(n)
glance(n)

library(ggplot2)
ggplot(augment(n), aes(wt, mpg)) +
  geom_point() +
  geom_line(aes(y = .fitted))

newdata <- head(mtcars)
newdata$wt <- newdata$wt + 1
augment(n, newdata = newdata)
```

tidy.numeric

Tidy atomic vectors

Description

Vector tidiers are deprecated and will be removed from an upcoming release of broom.

Usage

```
## S3 method for class 'numeric'
tidy(x, ...)

## S3 method for class 'character'
tidy(x, ...)

## S3 method for class 'logical'
tidy(x, ...)
```

Arguments

`x` An object of class "numeric", "integer", "character", or "logical". Most likely a named vector

`...` Extra arguments (not used)

Details

Turn atomic vectors into data frames, where the names of the vector (if they exist) are a column and the values of the vector are a column.

Examples

```
## Not run:
x <- 1:5
names(x) <- letters[1:5]
tidy(x)

## End(Not run)
```

tidy.orcutt

Tidy a(n) orcutt object

Description

This method wraps `tidy.lm()`.

Usage

```
## S3 method for class 'orcutt'
tidy(x, ...)
```

Arguments

`x` An orcutt object returned from `orcutt::cochrane.orcutt()`.

`...` Arguments passed on to `tidy.lm`

`x` An `lm` object created by `stats::lm()`.

conf.int Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.

conf.level The confidence level to use for the confidence interval if `conf.int = TRUE`. Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.

quick Logical indicating if the only the term and estimate columns should be returned. Often useful to avoid time consuming covariance and standard error calculations. Defaults to FALSE.

exponentiate Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to FALSE.

Value

tidy returns the same information as `tidy.lm()`, though without confidence interval options.

See Also

`tidy()`, `tidy.lm()`

`orcutt::cochrane.orcutt()`

Other orcutt tidiers: `glance.orcutt`

Examples

```
reg <- lm(mpg ~ wt + qsec + disp, mtcars)
tidy(reg)

if (require("orcutt", quietly = TRUE)) {
  co <- cochrane.orcutt(reg)
  co

  tidy(co)
  glance(co)
}
```

`tidy.pairwise.htest` *Tidy a(n) pairwise.htest object*

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'pairwise.htest'
tidy(x, ...)
```

Arguments

`x` A `pairwise.htest` object such as those returned from `stats::pairwise.t.test()` or `stats::pairwise.wilcox.test()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Details

Note that in one-sided tests, the alternative hypothesis of each test can be stated as "group1 is greater/less than group2".

Note also that the columns of `group1` and `group2` will always be a factor, even if the original input is (e.g.) numeric.

Value

A `tibble::tibble` with one row per group/group comparison and columns:

<code>group1</code>	First group being compared
<code>group2</code>	Second group being compared
<code>p.value</code>	(Adjusted) p-value of comparison

See Also

`stats::pairwise.t.test()`, `stats::pairwise.wilcox.test()`, `tidy()`

Other `htest` tidiers: `augment.htest`, `tidy.htest`, `tidy.power.htest`

Examples

```
attach(airquality)
Month <- factor(Month, labels = month.abb[5:9])
ptt <- pairwise.t.test(Ozone, Month)
tidy(ptt)

attach(iris)
ptt2 <- pairwise.t.test(Petal.Length, Species)
tidy(ptt2)

tidy(pairwise.t.test(Petal.Length, Species, alternative = "greater"))
tidy(pairwise.t.test(Petal.Length, Species, alternative = "less"))

tidy(pairwise.wilcox.test(Petal.Length, Species))
```

tidy.plm

*Tidy a(n) plm object***Description**

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'plm'
tidy(x, conf.int = FALSE, conf.level = 0.95,
     exponentiate = FALSE, ...)
```

Arguments

<code>x</code>	A plm object returned by <code>plm::plm()</code> .
<code>conf.int</code>	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>exponentiate</code>	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to FALSE.
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A `tibble::tibble()` with one row for each term in the regression. The tibble has columns:

<code>term</code>	The name of the regression term.
<code>estimate</code>	The estimated value of the regression term.
<code>std.error</code>	The standard error of the regression term.
<code>statistic</code>	The value of a statistic, almost always a T-statistic, to use in a hypothesis that the regression term is non-zero.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.

conf.low	The low end of a confidence interval for the regression term. Included only if conf.int = TRUE.
conf.high	The high end of a confidence interval for the regression term. Included only if conf.int = TRUE.

See Also

[tidy\(\)](#), [plm::plm\(\)](#), [tidy.lm\(\)](#)

Other plm tidiers: [augment.plm](#), [glance.plm](#)

Examples

```
library(plm)

data("Produc", package = "plm")
zz <- plm(log(gsp) ~ log(pcap) + log(pc) + log(emp) + unemp,
          data = Produc, index = c("state", "year"))

summary(zz)

tidy(zz)
tidy(zz, conf.int = TRUE)
tidy(zz, conf.int = TRUE, conf.level = .9)

augment(zz)
glance(zz)
```

tidy.poLCA

Tidy a(n) poLCA object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'poLCA'
tidy(x, ...)
```

Arguments

`x` A poLCA object returned from `poLCA: :poLCA()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the data argument.

Value

A `tibble::tibble` with one row per variable-class-outcome combination, with columns:

<code>variable</code>	Manifest variable
<code>class</code>	Latent class ID, an integer
<code>outcome</code>	Outcome of manifest variable
<code>estimate</code>	Estimated class-conditional response probability
<code>std.error</code>	Standard error of estimated probability

See Also

`tidy()`, `poLCA: :poLCA()`

Other poLCA tidiers: `augment.poLCA`, `glance.poLCA`

Examples

```
if (require("poLCA", quietly = TRUE)) {
  library(poLCA)
  library(dplyr)

  data(values)
  f <- cbind(A, B, C, D)~1
  M1 <- poLCA(f, values, nclass = 2, verbose = FALSE)

  M1
  tidy(M1)
  augment(M1)
  glance(M1)

  library(ggplot2)

  ggplot(tidy(M1), aes(factor(class), estimate, fill = factor(outcome))) +
    geom_bar(stat = "identity", width = 1) +
    facet_wrap(~ variable)

  set.seed(2016)
  # compare multiple
```

```

mods <- tibble(nclass = 1:3) %>%
  group_by(nclass) %>%
  do(mod = polCA(f, values, nclass = .$nclass, verbose = FALSE))

# compare log-likelihood and/or AIC, BIC
mods %>%
  glance(mod)

## Three-class model with a single covariate.

data(election)
f2a <- cbind(MORALG,CARESG,KNOWG,LEADG,DISHONG,INTELG,
            MORALB,CARESB,KNOWB,LEADB,DISHONB,INTELB)~PARTY
nes2a <- polCA(f2a, election, nclass = 3, nrep = 5, verbose = FALSE)

td <- tidy(nes2a)
td

# show

ggplot(td, aes(outcome, estimate, color = factor(class), group = class)) +
  geom_line() +
  facet_wrap(~ variable, nrow = 2) +
  theme(axis.text.x = element_text(angle = 90, hjust = 1))

au <- augment(nes2a)
au
au %>%
  count(.class)

# if the original data is provided, it leads to NAs in new columns
# for rows that weren't predicted
au2 <- augment(nes2a, data = election)
au2
dim(au2)
}

```

Description

These methods tidy the coefficients of ordinal logistic regression models generated by `ordinal::clm()` or `ordinal::clmm()` of the `ordinal` package, `MASS::polr()` of the `MASS` package, or `survey::svyolr()` of the `survey` package.

Usage

```
## S3 method for class 'polr'
```

```

tidy(x, conf.int = FALSE, conf.level = 0.95,
     exponentiate = FALSE, quick = FALSE, ...)

## S3 method for class 'polr'
glance(x, ...)

## S3 method for class 'polr'
augment(x, data = stats::model.frame(x), newdata,
        type.predict = c("probs", "class"), ...)

## S3 method for class 'clm'
tidy(x, conf.int = FALSE, conf.level = 0.95,
     exponentiate = FALSE, quick = FALSE, conf.type = c("profile",
     "Wald"), ...)

## S3 method for class 'clmm'
tidy(x, conf.int = FALSE, conf.level = 0.95,
     exponentiate = FALSE, quick = FALSE, conf.type = c("profile",
     "Wald"), ...)

## S3 method for class 'clm'
glance(x, ...)

## S3 method for class 'clmm'
glance(x, ...)

## S3 method for class 'clm'
augment(x, data = stats::model.frame(x), newdata,
        type.predict = c("prob", "class"), ...)

## S3 method for class 'svyolr'
tidy(x, conf.int = FALSE, conf.level = 0.95,
     exponentiate = FALSE, quick = FALSE, ...)

## S3 method for class 'svyolr'
glance(x, ...)

```

Arguments

<code>x</code>	a model of class <code>clm</code> , <code>clmm</code> , <code>polr</code> or <code>svyolr</code>
<code>conf.int</code>	whether to include a confidence interval
<code>conf.level</code>	confidence level of the interval, used only if <code>conf.int=TRUE</code>
<code>exponentiate</code>	whether to exponentiate the coefficient estimates and confidence intervals (typical for ordinal logistic regression)
<code>quick</code>	whether to compute a smaller and faster version, containing only the term, estimate and <code>coefficient_type</code> columns
<code>...</code>	extra arguments

data	original data, defaults to the extracting it from the model
newdata	if provided, performs predictions on the new data
type.predict	type of prediction to compute for a CLM; passed on to <code>ordinal::predict.clm()</code> or <code>predict.polr</code>
conf.type	the type of confidence interval (see <code>ordinal::confint.clm()</code>)

Value

`tidy.clm`, `tidy.clmm`, `tidy.polr` and `tidy.svyolr` return one row for each coefficient at each level of the response variable, with six columns:

term	term in the model
estimate	estimated coefficient
std.error	standard error
statistic	z-statistic
p.value	two-sided p-value
coefficient_type	type of coefficient, see <code>ordinal::clm()</code>

If `conf.int=TRUE`, it also includes columns for `conf.low` and

`glance.clm`, `glance.clmm`, `glance.polr` and `glance.svyolr` return a one-row data.frame with the columns:

edf	the effective degrees of freedom
logLik	the data's log-likelihood under the model
AIC	the Akaike Information Criterion
BIC	the Bayesian Information Criterion
df.residual	residual degrees of freedom

`augment.clm` and `augment.polr` returns one row for each observation, with additional columns added to the original data:

.fitted	fitted values of model
.se.fit	standard errors of fitted values

`augment` is not supported for `ordinal::clmm()` and `survey::svyolr()` models.

All tidying methods return a data.frame without rownames. The structure depends on the method chosen.

Examples

```
if (require(ordinal)){
  clm_mod <- clm(rating ~ temp * contact, data = wine)
  tidy(clm_mod)
  tidy(clm_mod, conf.int = TRUE)
  tidy(clm_mod, conf.int = TRUE, conf.type = "Wald", exponentiate = TRUE)
  glance(clm_mod)
```

```

augment(clm_mod)

clm_mod2 <- clm(rating ~ temp, nominal = ~ contact, data = wine)
tidy(clm_mod2)

clmm_mod <- clmm(rating ~ temp + contact + (1 | judge), data = wine)
tidy(clmm_mod)
glance(clmm_mod)
}
if (require(MASS)) {
  polr_mod <- polr(Sat ~ Infl + Type + Cont, weights = Freq, data = housing)
  tidy(polr_mod, exponentiate = TRUE, conf.int = TRUE)
  glance(polr_mod)
  augment(polr_mod, type.predict = "class")
}

```

tidy.power.htest *Tidy a(n) power.htest object*

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'power.htest'
tidy(x, ...)

```

Arguments

`x` A `power.htest` object such as those returned from `stats::power.t.test()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the data argument.

Value

A data frame with one row per parameter passed in, with columns `n`, `delta`, `sd`, `sig.level`, and `power`.

See Also

[stats::power.t.test\(\)](#)

Other htest tidiers: [augment.htest](#), [tidy.htest](#), [tidy.pairwise.htest](#)

Examples

```
ptt <- power.t.test(n = 2:30, delta = 1)
tidy(ptt)

library(ggplot2)

ggplot(tidy(ptt), aes(n, power)) +
  geom_line()
```

tidy.prcomp

Tidy a(n) prcomp object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'prcomp'
tidy(x, matrix = "u", ...)
```

Arguments

x	A prcomp object returned by stats::prcomp() .
matrix	Character specifying which component of the PCA should be tidied. <ul style="list-style-type: none"> • "u", "samples", or "x": returns information about the map from the original space into principle components space. • "v", "rotation", or "variables": returns information about the map from principle components space back into the original space. • "d" or "pcs": returns information about the eigenvalues will return information about
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an augment() method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Details

See <https://stats.stackexchange.com/questions/134282/relationship-between-svd-and-pca-how-to-use-svd-to-perform-pca> for information on how to interpret the various tidied matrices. Note that SVD is only equivalent to PCA on centered data.

Value

A `tibble::tibble` with columns depending on the component of PCA being tidied.

If `matrix` is "u", "samples", or "x" each row in the tidied output corresponds to the original data in PCA space. The columns are:

row	ID of the original observation (i.e. rowname from original data).
PC	Integer indicating a principle component.
value	The score of the observation for that particular principle component. That is, the location of the observation in PCA space.

If `matrix` is "v", "rotation", or "variables", each row in the tidied output corresponds to information about the principle components in the original space. The columns are:

row	The variable labels (colnames) of the data set on which PCA was performed
PC	An integer vector indicating the principal component
value	The value of the eigenvector (axis score) on the indicated principal component

If `matrix` is "d" or "pcs", the columns are:

PC	An integer vector indicating the principal component
std.dev	Standard deviation explained by this PC
percent	Percentage of variation explained
cumulative	Cumulative percentage of variation explained

See Also

[stats::prcomp\(\)](#), [svd_tidiers](#)

Other svd tidiers: [augment.prcomp](#), [tidy_irlba](#), [tidy_svd](#)

Examples

```
pc <- prcomp(USArrests, scale = TRUE)

# information about rotation
tidy(pc)

# information about samples (states)
tidy(pc, "samples")

# information about PCs
tidy(pc, "pcs")
```



```

# state map
library(dplyr)
library(ggplot2)

pc %>%
  tidy(matrix = "samples") %>%
  mutate(region = tolower(row)) %>%
  inner_join(map_data("state"), by = "region") %>%
  ggplot(aes(long, lat, group = group, fill = value)) +
  geom_polygon() +
  facet_wrap(~ PC) +
  theme_void() +
  ggtitle("Principal components of arrest data")

au <- augment(pc, data = USArrests)
au

ggplot(au, aes(.fittedPC1, .fittedPC2)) +
  geom_point() +
  geom_text(aes(label = .rownames), vjust = 1, hjust = 1)

```

tidy.pyears

*Tidy a(n) pyears object***Description**

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'pyears'
tidy(x, ...)

```

Arguments

x A pyears object returned from `survival::pyears()`.

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the data argument.

Value

A `tibble::tibble` with one row for each time point and columns:

<code>pyears</code>	person-years of exposure
<code>n</code>	number of subjects contributing time
<code>event</code>	observed number of events
<code>expected</code>	expected number of events (present only if a <code>ratetable</code> term is present)

If the `data.frame = TRUE` argument is supplied to `pyears`, this is simply the contents of `x$data`.

See Also

`tidy()`, `survival::pyears()`

Other `pyears` tidiers: `glance.pyears`

Other survival tidiers: `augment.coxph`, `augment.survreg`, `glance.aareg`, `glance.cch`, `glance.coxph`, `glance.pyears`, `glance.survdiff`, `glance.survexp`, `glance.survfit`, `glance.survreg`, `tidy.aareg`, `tidy.cch`, `tidy.coxph`, `tidy.survdiff`, `tidy.survexp`, `tidy.survfit`, `tidy.survreg`

Examples

```
library(survival)

temp.yr <- tcut(mgus$dxyr, 55:92, labels=as.character(55:91))
temp.age <- tcut(mgus$age, 34:101, labels=as.character(34:100))
ptime <- ifelse(is.na(mgus$pctime), mgus$futime, mgus$pctime)
pstat <- ifelse(is.na(mgus$pctime), 0, 1)
pfit <- pyears(Surv(ptime/365.25, pstat) ~ temp.yr + temp.age + sex, mgus,
              data.frame=TRUE)

tidy(pfit)
glance(pfit)

# if data.frame argument is not given, different information is present in
# output
pfit2 <- pyears(Surv(ptime/365.25, pstat) ~ temp.yr + temp.age + sex, mgus)
tidy(pfit2)
glance(pfit2)
```

`tidy.rcorr`

Tidy a(n) rcorr object

Description

`Tidy` summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what `tidy` considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'rcorr'
tidy(x, diagonal = FALSE, ...)
```

Arguments

x	An rcorr object returned from <code>Hmisc::rcorr()</code> .
diagonal	Logical indicating whether or not to include diagonal elements of the correlation matrix, or the correlation of a column with itself. For the elements, estimate is always 1 and p.value is always NA. Defaults to FALSE.
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Details

Suppose the original data has columns A and B. In the correlation matrix from `rcorr` there may be entries for both the `cor(A, B)` and `cor(B, A)`. Only one of these pairs will ever be present in the tidy output.

Value

A `tibble::tibble` with one row for each unique pair of columns in the correlation matrix and columns:

column1	Name or index of the first column being described
column2	Name or index of the second column being described
estimate	Estimate of Pearson's r or Spearman's rho
n	Number of observations used to compute the correlation
p.value	P-value of correlation

See Also

`tidy()`, `Hmisc::rcorr()`

Examples

```
if (requireNamespace("Hmisc", quietly = TRUE)) {
  library(Hmisc)

  mat <- replicate(52, rnorm(100))
  # add some NAs
  mat[sample(length(mat), 2000)] <- NA
}
```

```

# also column names
colnames(mat) <- c(LETTERS, letters)

rc <- rcorr(mat)

td <- tidy(rc)
td

library(ggplot2)
ggplot(td, aes(p.value)) +
  geom_histogram(binwidth = .1)

ggplot(td, aes(estimate, p.value)) +
  geom_point() +
  scale_y_log10()
}

```

tidy.ridgelm

Tidy a(n) ridgelm object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'ridgelm'
tidy(x, ...)

```

Arguments

x	A <code>ridgelm</code> object returned from <code>MASS::lm.ridge()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A `tibble::tibble` with one row for each combination of lambda and a term in the formula, with columns:

lambda	choice of lambda
GCV	generalized cross validation value for this lambda
term	the term in the ridge regression model being estimated
estimate	estimate of scaled coefficient using this lambda
scale	Scaling factor of estimated coefficient

See Also

[tidy\(\)](#), [MASS::lm.ridge\(\)](#)

Other `ridgelm` tidiers: [glance.ridgelm](#)

Examples

```
names(longley)[1] <- "y"
fit1 <- MASS::lm.ridge(y ~ ., longley)
tidy(fit1)

fit2 <- MASS::lm.ridge(y ~ ., longley, lambda = seq(0.001, .05, .001))
td2 <- tidy(fit2)
g2 <- glance(fit2)

# coefficient plot
library(ggplot2)
ggplot(td2, aes(lambda, estimate, color = term)) +
  geom_line()

# GCV plot
ggplot(td2, aes(lambda, GCV)) +
  geom_line()

# add line for the GCV minimizing estimate
ggplot(td2, aes(lambda, GCV)) +
  geom_line() +
  geom_vline(xintercept = g2$lambdaGCV, col = "red", lty = 2)
```

tidy.rlm

Tidy a(n) rlm object

Description

This method wraps [tidy.lm\(\)](#).

Usage

```
## S3 method for class 'rlm'
tidy(x, ...)
```

Arguments

- `x` An `rlm` object returned by `MASS::rlm()`.
- `...` Arguments passed on to `tidy.lm`
- `x` An `lm` object created by `stats::lm()`.
- conf.int** Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to `FALSE`.
- conf.level** The confidence level to use for the confidence interval if `conf.int = TRUE`. Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
- quick** Logical indicating if the only the `term` and `estimate` columns should be returned. Often useful to avoid time consuming covariance and standard error calculations. Defaults to `FALSE`.
- exponentiate** Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to `FALSE`.

Details

For tidiers for models from the **robust** package see `tidy.lmRob()` and `tidy.glmRob()`.

Value

A `tibble::tibble()` with one row for each term in the regression. The tibble has columns:

<code>term</code>	The name of the regression term.
<code>estimate</code>	The estimated value of the regression term.
<code>std.error</code>	The standard error of the regression term.
<code>statistic</code>	The value of a statistic, almost always a T-statistic, to use in a hypothesis that the regression term is non-zero.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>conf.low</code>	The low end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .
<code>conf.high</code>	The high end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .

If the linear model is an `mlm` object (multiple linear model), there is an additional column:

<code>response</code>	Which response column the coefficients correspond to (typically Y1, Y2, etc)
-----------------------	--

See Also

`tidy()`, `tidy.lm()`

`MASS::rlm()`

Other `rlm` tidiers: `augment.rlm`, `glance.rlm`

tidy.roc

Tidy a(n) roc object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'roc'
tidy(x, ...)
```

Arguments

x	An roc object returned from a call to <code>AUC::roc()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Value

A `tibble::tibble()` with three columns:

cutoff	The cutoff used for classification. Observations with predicted probabilities above this value were assigned class 1, and observations with predicted probabilities below this value were assigned class 0.
tpr	The true positive rate at the given cutoff.
fpr	The false positive rate at the given cutoff.

See Also

`tidy()`, `AUC::roc()`

Examples

```
if (require("AUC", quietly = TRUE)) {
  data(churn)
  r <- roc(churn$predictions, churn$labels)
```

```

td <- tidy(r)
td

library(ggplot2)

ggplot(td, aes(fpr, tpr)) +
  geom_line()

# compare the ROC curves for two prediction algorithms

library(dplyr)
library(tidyr)

rocs <- churn %>%
  gather(algorithm, value, -labels) %>%
  nest(-algorithm) %>%
  mutate(tidy_roc = purrr::map(data, ~tidy(roc(.x$value, .x$labels)))) %>%
  unnest(tidy_roc)

ggplot(rocs, aes(fpr, tpr, color = algorithm)) +
  geom_line()
}

```

tidy.rq

Tidy a(n) rq object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'rq'
tidy(x, se.type = "rank", conf.int = TRUE,
     conf.level = 0.95, ...)

```

Arguments

x	An rq object returned from <code>quantreg::rq()</code> .
se.type	Character specifying the method to use to calculate standard errors. Passed to <code>quantreg::summary.rq()</code> se argument. Defaults to "rank".
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.

`conf.level` The confidence level to use for the confidence interval if `conf.int = TRUE`. Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.

... Additional arguments passed to `quantreg::summary.rq()`.

Details

If `se.type = "rank"` confidence intervals are calculated by `summary.rq`. When only a single predictor is included in the model, no confidence intervals are calculated and the confidence limits are set to NA.

Value

A `tibble::tibble()` with one row for each term in the regression. The tibble has columns:

<code>term</code>	The name of the regression term.
<code>estimate</code>	The estimated value of the regression term.
<code>std.error</code>	The standard error of the regression term.
<code>statistic</code>	The value of a statistic, almost always a T-statistic, to use in a hypothesis that the regression term is non-zero.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>conf.low</code>	The low end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .
<code>conf.high</code>	The high end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .

See Also

`tidy()`, `quantreg::rq()`

Other `quantreg` tidiers: `augment.nlrq`, `augment.rqs`, `augment.rq`, `glance.nlrq`, `glance.rq`, `tidy.nlrq`, `tidy.rqs`

`tidy.rqs`

Tidy a(n) rqs object

Description

`Tidy` summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what `tidy` considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'rqs'
tidy(x, se.type = "rank", conf.int = TRUE,
     conf.level = 0.95, ...)
```

Arguments

<code>x</code>	An rqs object returned from <code>quantreg::rq()</code> .
<code>se.type</code>	Character specifying the method to use to calculate standard errors. Passed to <code>quantreg::summary.rq()</code> <code>se</code> argument. Defaults to "rank".
<code>conf.int</code>	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
<code>conf.level</code>	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>...</code>	Additional arguments passed to <code>quantreg::summary.rqs()</code>

Details

If `se.type = "rank"` confidence intervals are calculated by `summary.rq`. When only a single predictor is included in the model, no confidence intervals are calculated and the confidence limits are set to NA.

Value

A `tibble::tibble()` with one row for each term in the regression. The tibble has columns:

<code>term</code>	The name of the regression term.
<code>estimate</code>	The estimated value of the regression term.
<code>std.error</code>	The standard error of the regression term.
<code>statistic</code>	The value of a statistic, almost always a T-statistic, to use in a hypothesis that the regression term is non-zero.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>conf.low</code>	The low end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .
<code>conf.high</code>	The high end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .

An additional quantile column indicating with quantile the coefficient corresponds to.

See Also

`tidy()`, `quantreg::rq()`

Other `quantreg` tidiers: `augment.nlrq`, `augment.rqs`, `augment.rq`, `glance.nlrq`, `glance.rq`, `tidy.nlrq`, `tidy.rq`

`tidy.spec`*Tidy a(n) spec object*

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'spec'  
tidy(x, ...)
```

Arguments

<code>x</code>	A spec object created by <code>stats::spectrum()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A `tibble::tibble` with two columns: `freq` and `spec`.

See Also

`tidy()`, `stats::spectrum()`

Other time series tidiers: `tidy.acf`, `tidy.ts`, `tidy.zoo`

Examples

```
spc <- spectrum(lh)  
tidy(spc)  
  
library(ggplot2)  
ggplot(tidy(spc), aes(freq, spec)) +  
  geom_line()
```

tidy.speedlm	<i>Tidy a(n) speedlm object</i>
--------------	---------------------------------

Description

This method wraps `tidy.lm()`.

Usage

```
## S3 method for class 'speedlm'
tidy(x, ...)
```

Arguments

`x` A speedlm object returned from `speedglm::speedlm()`.

`...` Arguments passed on to `tidy.lm`

`x` An lm object created by `stats::lm()`.

conf.int Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.

conf.level The confidence level to use for the confidence interval if `conf.int = TRUE`. Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.

quick Logical indicating if the only the term and estimate columns should be returned. Often useful to avoid time consuming covariance and standard error calculations. Defaults to FALSE.

exponentiate Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to FALSE.

Value

A `tibble::tibble()` with one row for each term in the regression. The tibble has columns:

<code>term</code>	The name of the regression term.
<code>estimate</code>	The estimated value of the regression term.
<code>std.error</code>	The standard error of the regression term.
<code>statistic</code>	The value of a statistic, almost always a T-statistic, to use in a hypothesis that the regression term is non-zero.
<code>p.value</code>	The two-sided p-value associated with the observed statistic.
<code>conf.low</code>	The low end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .
<code>conf.high</code>	The high end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .

If the linear model is an `mlm` object (multiple linear model), there is an additional column:

<code>response</code>	Which response column the coefficients correspond to (typically Y1, Y2, etc)
-----------------------	--

See Also[tidy\(\)](#), [tidy.lm\(\)](#)[speedglm::speedlm\(\)](#)Other speedlm tidiers: [augment.speedlm](#), [glance.speedlm](#)**Examples**

```
mod <- speedglm::speedlm(mpg ~ wt + qsec, data = mtcars)

tidy(mod)
glance(mod)
augment(mod)
```

tidy.summary.glht	<i>Tidy a(n) summary.glht object</i>
-------------------	--------------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'summary.glht'
tidy(x, ...)
```

Arguments

x	A <code>summary.glht</code> object created by calling <code>multcomp::summary.glht()</code> on a <code>glht</code> object created with <code>multcomp::glht()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

See Also[tidy\(\)](#), [multcomp::summary.glht\(\)](#), [multcomp::glht\(\)](#)Other multcomp tidiers: [tidy.cld](#), [tidy.confint.glht](#), [tidy.glht](#)

tidy.survdiff	<i>Tidy a(n) survdiff object</i>
---------------	----------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'survdiff'
tidy(x, ...)
```

Arguments

x	An survdiff object returned from <code>survival::survdiff()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Value

A `tibble::tibble` with one row for each time point and columns:

...	The initial columns correspond to the grouping factors on the right hand side of the model formula.
obs	weighted observed number of events in each group
exp	weighted expected number of events in each group
N	number of subjects in each group

See Also

`tidy()`, `survival::survdiff()`

Other survdiff tidiers: `glance.survdiff`

Other survival tidiers: `augment.coxph`, `augment.survreg`, `glance.aareg`, `glance.cch`, `glance.coxph`, `glance.pyyears`, `glance.survdiff`, `glance.survexp`, `glance.survfit`, `glance.survreg`, `tidy.aareg`, `tidy.cch`, `tidy.coxph`, `tidy.pyyears`, `tidy.survexp`, `tidy.survfit`, `tidy.survreg`

Examples

```
library(survival)

s <- survdiff(
  Surv(time, status) ~ pat.karno + strata(inst),
  data = lung
)

tidy(s)
glance(s)
```

tidy.survexp	<i>Tidy a(n) survexp object</i>
--------------	---------------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'survexp'
tidy(x, ...)
```

Arguments

x	An survexp object returned from <code>survival::survexp()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Value

A `tibble::tibble` with one row for each time point and columns:

time	time point
estimate	estimated survival
n.risk	number of individuals at risk

See Also

[tidy\(\)](#), [survival::survexp\(\)](#)

Other survexp tidiers: [glance.survexp](#)

Other survival tidiers: [augment.coxph](#), [augment.survreg](#), [glance.aareg](#), [glance.cch](#), [glance.coxph](#), [glance.pyears](#), [glance.survdiff](#), [glance.survexp](#), [glance.survfit](#), [glance.survreg](#), [tidy.aareg](#), [tidy.cch](#), [tidy.coxph](#), [tidy.pyears](#), [tidy.survdiff](#), [tidy.survfit](#), [tidy.survreg](#)

Examples

```
library(survival)
sexpfit <- survexp(
  futime ~ 1,
  rmap = list(
    sex = "male",
    year = accept.dt,
    age = (accept.dt - birth.dt)
  ),
  method = 'conditional',
  data = jasa
)

tidy(sexpfit)
glance(sexpfit)
```

tidy.survfit

Tidy a(n) survfit object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'survfit'
tidy(x, ...)
```

Arguments

x An survfit object returned from [survival::survfit\(\)](#).

... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

A `tibble::tibble` with one row for each time point and columns:

<code>time</code>	timepoint
<code>n.risk</code>	number of subjects at risk at time t0
<code>n.event</code>	number of events at time t
<code>n.censor</code>	number of censored events
<code>estimate</code>	estimate of survival or cumulative incidence rate when multistate
<code>std.error</code>	standard error of estimate
<code>conf.high</code>	upper end of confidence interval
<code>conf.low</code>	lower end of confidence interval
<code>state</code>	state if multistate survfit object inputted
<code>strata</code>	strata if stratified survfit object inputted

See Also

[tidy\(\)](#), [survival::survfit\(\)](#)

Other survival tidiers: [augment.coxph](#), [augment.survreg](#), [glance.aareg](#), [glance.cch](#), [glance.coxph](#), [glance.pyears](#), [glance.survdiff](#), [glance.survexp](#), [glance.survfit](#), [glance.survreg](#), [tidy.aareg](#), [tidy.cch](#), [tidy.coxph](#), [tidy.pyears](#), [tidy.survdiff](#), [tidy.survexp](#), [tidy.survreg](#)

Examples

```
library(survival)
cfits <- coxph(Surv(time, status) ~ age + sex, lung)
sfit <- survfit(cfits)

tidy(sfit)
glance(sfit)

library(ggplot2)
ggplot(tidy(sfit), aes(time, estimate)) + geom_line() +
  geom_ribbon(aes(ymin=conf.low, ymax=conf.high), alpha=.25)

# multi-state
fitCI <- survfit(Surv(stop, status * as.numeric(event), type = "mstate") ~ 1,
  data = mgus1, subset = (start == 0))
td_multi <- tidy(fitCI)
```

```

td_multi

ggplot(td_multi, aes(time, estimate, group = state)) +
  geom_line(aes(color = state)) +
  geom_ribbon(aes(ymin = conf.low, ymax = conf.high), alpha = .25)

```

tidy.survreg

*Tidy a(n) survreg object***Description**

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```

## S3 method for class 'survreg'
tidy(x, conf.level = 0.95, ...)

```

Arguments

x	An survreg object returned from <code>survival::survreg()</code> .
conf.level	confidence level for CI
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Value

A `tibble::tibble()` with one row for each term in the regression. The tibble has columns:

term	The name of the regression term.
estimate	The estimated value of the regression term.
std.error	The standard error of the regression term.
statistic	The value of a statistic, almost always a T-statistic, to use in a hypothesis that the regression term is non-zero.
p.value	The two-sided p-value associated with the observed statistic.
conf.low	The low end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .
conf.high	The high end of a confidence interval for the regression term. Included only if <code>conf.int = TRUE</code> .

See Also

`tidy()`, `survival::survreg()`

Other survreg tidiers: `augment.survreg`, `glance.survreg`

Other survival tidiers: `augment.coxph`, `augment.survreg`, `glance.aareg`, `glance.cch`, `glance.coxph`, `glance.pyears`, `glance.survdiff`, `glance.survexp`, `glance.survfit`, `glance.survreg`, `tidy.aareg`, `tidy.cch`, `tidy.coxph`, `tidy.pyears`, `tidy.survdiff`, `tidy.survexp`, `tidy.survfit`

Examples

```
library(survival)

sr <- survreg(
  Surv(futime, fustat) ~ ecog.ps + rx,
  ovarian,
  dist = "exponential"
)

td <- tidy(sr)
augment(sr, ovarian)
glance(sr)

# coefficient plot
library(ggplot2)
ggplot(td, aes(estimate, term)) +
  geom_point() +
  geom_errorbarh(aes(xmin = conf.low, xmax = conf.high), height = 0) +
  geom_vline(xintercept = 0)
```

tidy.table

Tidy a(n) table object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'table'
tidy(x, ...)
```

Arguments

`x` A `table` object.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Details

Directly calls `tibble::as_tibble()` on a `table` object, which does the same things as `as.data.frame.table()` but also gives the returned object `tibble::tibble` class.

Value

A `tibble::tibble` in long-form containing frequency information for the table in a `Freq` column. The result is much like what you get from `tidyr::gather()`.

See Also

`as_tibble.table()`

Examples

```
tab <- with(airquality, table(Temp = cut(Temp, quantile(Temp)), Month))
tidy(tab)
```

tidy.ts

Tidy a(n) ts object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'ts'
tidy(x, ...)
```

Arguments

`x` A univariate or multivariate `ts` times series object.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

A `tibble::tibble` with one row for each observation and columns:

<code>index</code>	Index (i.e. date or time) for the "ts" object.
<code>series</code>	Name of the series (multivariate "ts" objects only).
<code>value</code>	Value of the observation.

See Also

`tidy()`, `stats::ts()`

Other time series tidiers: `tidy.acf`, `tidy.spec`, `tidy.zoo`

Examples

```
set.seed(678)

tidy(ts(1:10, frequency = 4, start = c(1959, 2)))

z <- ts(matrix(rnorm(300), 100, 3), start = c(1961, 1), frequency = 12)
colnames(z) <- c("Aa", "Bb", "Cc")
tidy(z)
```

`tidy.TukeyHSD`

Tidy a(n) TukeyHSD object

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'TukeyHSD'
tidy(x, ...)
```

Arguments

`x` A TukeyHSD object return from `stats::TukeyHSD()`.

`...` Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in `...`, where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the data argument.

Value

A `tibble::tibble` with one row per comparison and columns:

<code>term</code>	Term for which levels are being compared
<code>comparison</code>	Levels being compared, separated by -
<code>estimate</code>	Estimate of difference
<code>conf.low</code>	Low end of confidence interval of difference
<code>conf.high</code>	High end of confidence interval of difference
<code>adj.p.value</code>	P-value adjusted for multiple comparisons

See Also

[tidy\(\)](#), [stats::TukeyHSD\(\)](#)

Other anova tidiers: [tidy.anova](#), [tidy.aovlist](#), [tidy.aov](#), [tidy.manova](#)

Examples

```
fm1 <- aov(breaks ~ wool + tension, data = warpbreaks)
thsd <- TukeyHSD(fm1, "tension", ordered = TRUE)
tidy(thsd)

# may include comparisons on multiple terms
fm2 <- aov(mpg ~ as.factor(gear) * as.factor(cyl), data = mtcars)
tidy(TukeyHSD(fm2))
```

tidy.zoo	<i>Tidy a(n) zoo object</i>
----------	-----------------------------

Description

Tidy summarizes information about the components of a model. A model component might be a single term in a regression, a single hypothesis, a cluster, or a class. Exactly what tidy considers to be a model component varies cross models but is usually self-evident. If a model has several distinct types of components, you will need to specify which components to return.

Usage

```
## S3 method for class 'zoo'
tidy(x, ...)
```

Arguments

x	A zoo object such as those created by <code>zoo::zoo()</code> .
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Value

A `tibble::tibble` with one row for each observation in the zoo time series and columns:

index	Index (usually date) for the zoo object
series	Name of the series
value	Value of the observation

See Also

`tidy()`, `zoo::zoo()`

Other time series tidiers: `tidy.acf`, `tidy.spec`, `tidy.ts`

Examples

```
library(zoo)
library(ggplot2)

set.seed(1071)
```

```
# data generated as shown in the zoo vignette
Z.index <- as.Date(sample(12450:12500, 10))
Z.data <- matrix(rnorm(30), ncol = 3)
colnames(Z.data) <- c("Aa", "Bb", "Cc")
Z <- zoo(Z.data, Z.index)

tidy(Z)

ggplot(tidy(Z), aes(index, value, color = series)) +
  geom_line()

ggplot(tidy(Z), aes(index, value)) +
  geom_line() +
  facet_wrap(~ series, ncol = 1)

Zrolled <- rollmean(Z, 5)
ggplot(tidy(Zrolled), aes(index, value, color = series)) +
  geom_line()
```

tidy_irlba

Tidy a(n) irlba object masquerading as list

Description

Broom tidies a number of lists that are effectively S3 objects without a class attribute. For example, `stats::optim()`, `svd()` and `akima::interp()` produce consistent output, but because they do not have a class attribute, they cannot be handled by S3 dispatch.

These functions look at the elements of a list and determine if there is an appropriate tidying method to apply to the list. Those tidiers are themselves implemented as functions of the form `tidy_<function>` or `glance_<function>` and are not exported (but they are documented!).

If no appropriate tidying method is found, throws an error.

Usage

```
tidy_irlba(x, ...)
```

Arguments

`x` A list returned from `irlba::irlba()`.

`...` Arguments passed on to `tidy_svd`

x A list with components `u`, `d`, `v` returned by `svd()`.

matrix Character specifying which component of the PCA should be tidied.

- `"u"`, `"samples"`, or `"x"`: returns information about the map from the original space into principle components space.
- `"v"`, `"rotation"`, or `"variables"`: returns information about the map from principle components space back into the original space.
- `"d"` or `"pcs"`: returns information about the eigenvalues will return information about

Details

A very thin wrapper around [tidy_svd\(\)](#).

Value

A `tibble::tibble` with columns depending on the component of PCA being tidied.

If `matrix` is "u", "samples", or "x" each row in the tidied output corresponds to the original data in PCA space. The columns are:

row	ID of the original observation (i.e. rowname from original data).
PC	Integer indicating a principle component.
value	The score of the observation for that particular principle component. That is, the location of the observation in PCA space.

If `matrix` is "v", "rotation", or "variables", each row in the tidied output corresponds to information about the principle components in the original space. The columns are:

row	The variable labels (colnames) of the data set on which PCA was performed
PC	An integer vector indicating the principal component
value	The value of the eigenvector (axis score) on the indicated principal component

If `matrix` is "d" or "pcs", the columns are:

PC	An integer vector indicating the principal component
std.dev	Standard deviation explained by this PC
percent	Percentage of variation explained
cumulative	Cumulative percentage of variation explained

See Also

[tidy\(\)](#), [irlba::irlba\(\)](#)

Other list tidiers: [glance_optim](#), [list_tidiers](#), [tidy_optim](#), [tidy_svd](#), [tidy_xyz](#)

Other svd tidiers: [augment.prcomp](#), [tidy.prcomp](#), [tidy_svd](#)

tidy_optim

Tidy a(n) optim object masquerading as list

Description

Broom tidies a number of lists that are effectively S3 objects without a class attribute. For example, `stats::optim()`, `svd()` and `akima::interp()` produce consistent output, but because they do not have a class attribute, they cannot be handled by S3 dispatch.

These functions look at the elements of a list and determine if there is an appropriate tidying method to apply to the list. Those tidiers are themselves implemented as functions of the form `tidy_<function>` or `glance_<function>` and are not exported (but they are documented!).

If no appropriate tidying method is found, throws an error.

Usage

```
tidy_optim(x, ...)
```

Arguments

<code>x</code>	A list returned from <code>stats::optim()</code> .
<code>...</code>	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in <code>...</code> , where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the <code>data</code> argument.

Value

A `tibble::tibble` with one row per parameter estimated by `optim` and columns:

<code>parameter</code>	name of the parameter, or <code>parameter1</code> , <code>parameter2</code> ... if the input vector is not named
<code>value</code>	parameter value that minimizes or maximizes the output

See Also

`tidy()`, `stats::optim()`

Other list tidiers: `glance_optim`, `list_tidiers`, `tidy_irlba`, `tidy_svd`, `tidy_xyz`

Examples

```
func <- function(x) {
  (x[1] - 2)^2 + (x[2] - 3)^2 + (x[3] - 8)^2
}

o <- optim(c(1, 1, 1), func)

tidy(o)
glance(o)
```

tidy_svd

Tidy a(n) svd object masquerading as list

Description

Broom tidies a number of lists that are effectively S3 objects without a class attribute. For example, `stats::optim()`, `svd()` and `akima::interp()` produce consistent output, but because they do not have a class attribute, they cannot be handled by S3 dispatch.

These functions look at the elements of a list and determine if there is an appropriate tidying method to apply to the list. Those tidiers are themselves implemented as functions of the form `tidy_<function>` or `glance_<function>` and are not exported (but they are documented!).

If no appropriate tidying method is found, throws an error.

Usage

```
tidy_svd(x, matrix = "u", ...)
```

Arguments

x	A list with components u, d, v returned by <code>svd()</code> .
matrix	Character specifying which component of the PCA should be tidied. <ul style="list-style-type: none"> • "u", "samples", or "x": returns information about the map from the original space into principle components space. • "v", "rotation", or "variables": returns information about the map from principle components space back into the original space. • "d" or "pcs": returns information about the eigenvalues will return information about
...	Additional arguments. Not used. Needed to match generic signature only. Cautionary note: Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be used. For example, if you pass <code>conf.level = 0.9</code> , all computation will proceed using <code>conf.level = 0.95</code> . Additionally, if you pass <code>newdata = my_tibble</code> to an <code>augment()</code> method that does not accept a <code>newdata</code> argument, it will use the default value for the data argument.

Details

See <https://stats.stackexchange.com/questions/134282/relationship-between-svd-and-pca-how-to-use-svd-to-perform-pca> for information on how to interpret the various tidied matrices. Note that SVD is only equivalent to PCA on centered data.

Value

A `tibble::tibble` with columns depending on the component of PCA being tidied.

If `matrix` is "u", "samples", or "x" each row in the tidied output corresponds to the original data in PCA space. The columns are:

row	ID of the original observation (i.e. rowname from original data).
PC	Integer indicating a principle component.
value	The score of the observation for that particular principle component. That is, the location of the observation in PCA space.

If `matrix` is "v", "rotation", or "variables", each row in the tidied output corresponds to information about the principle components in the original space. The columns are:

row	The variable labels (colnames) of the data set on which PCA was performed
PC	An integer vector indicating the principal component
value	The value of the eigenvector (axis score) on the indicated principal component

If `matrix` is "d" or "pcs", the columns are:

PC	An integer vector indicating the principal component
std.dev	Standard deviation explained by this PC
percent	Percentage of variation explained
cumulative	Cumulative percentage of variation explained

See Also

[svd\(\)](#)

Other svd tidiers: [augment.prcomp](#), [tidy.prcomp](#), [tidy_irlba](#)

Other list tidiers: [glance_optim](#), [list_tidiers](#), [tidy_irlba](#), [tidy_optim](#), [tidy_xyz](#)

Examples

```
mat <- scale(as.matrix(iris[, 1:4]))
s <- svd(mat)

tidy_u <- tidy(s, matrix = "u")
tidy_u

tidy_d <- tidy(s, matrix = "d")
tidy_d
```

```

tidy_v <- tidy(s, matrix = "v")
tidy_v

library(ggplot2)
library(dplyr)

ggplot(tidy_d, aes(PC, percent)) +
  geom_point() +
  ylab("% of variance explained")

tidy_u %>%
  mutate(Species = iris$Species[row]) %>%
  ggplot(aes(Species, value)) +
  geom_boxplot() +
  facet_wrap(~ PC, scale = "free_y")

```

tidy_xyz

Tidy a(n) xyz object masquerading as list

Description

Broom tidies a number of lists that are effectively S3 objects without a class attribute. For example, `stats::optim()`, `svd()` and `akima::interp()` produce consistent output, but because they do not have a class attribute, they cannot be handled by S3 dispatch.

These functions look at the elements of a list and determine if there is an appropriate tidying method to apply to the list. Those tidiers are themselves implemented as functions of the form `tidy_<function>` or `glance_<function>` and are not exported (but they are documented!).

If no appropriate tidying method is found, throws an error.

xyz lists (lists where x and y are vector of coordinates and z is a matrix of values) are typically used by functions such as `graphics::persp()` or `graphics::image()` and returned by interpolation functions such as `akima::interp()`.

Usage

```
tidy_xyz(x, ...)
```

Arguments

- x A list with component x, y and z, where x and y are vectors and z is a matrix. The length of x must equal the number of rows in z and the length of y must equal the number of columns in z.
- ... Additional arguments. Not used. Needed to match generic signature only. **Cautionary note:** Misspelled arguments will be absorbed in ..., where they will be ignored. If the misspelled argument has a default value, the default value will be

used. For example, if you pass `conf.level = 0.9`, all computation will proceed using `conf.level = 0.95`. Additionally, if you pass `newdata = my_tibble` to an `augment()` method that does not accept a `newdata` argument, it will use the default value for the `data` argument.

Value

A `tibble::tibble` with vector columns `x`, `y` and `z`.

See Also

`tidy()`, `graphics::persp()`, `graphics::image()`, `akima::interp()`

Other list tidiers: `glance_optim`, `list_tidiers`, `tidy_irlba`, `tidy_optim`, `tidy_svd`

Examples

```
A <- list(x = 1:5, y = 1:3, z = matrix(runif(5 * 3), nrow = 5))
image(A)
tidy(A)
```

Index

*Topic **datasets**

- argument_glossary, 6
- column_glossary, 53

- aareg_tidiers (tidy.aareg), 127
- AER::ivreg(), 20, 21, 81, 82, 178, 179
- aer_tidiers (tidy.ivreg), 178
- akima::interp(), 109, 111, 240, 242, 243, 245, 246
- argument_glossary, 6
- Arima_tidiers (tidy.Arima), 133
- as.data.frame.table(), 236
- as_tibble.table(), 236
- AUC::roc(), 223
- auc_tidiers (tidy.roc), 223
- augment, 41, 43
- augment(), 8–11, 13–16, 18, 19, 21, 23–33, 35–37, 39, 44, 46–49, 56, 61–66, 68, 69, 71–81, 83, 84, 86–96, 98–108, 110, 112, 117, 126, 127, 129–133, 135, 136, 138, 139, 141, 142, 144–148, 150, 152, 154, 157, 158, 160–165, 167, 168, 171, 174, 177, 178, 180, 181, 183, 184, 187, 189, 193, 194, 196, 198–200, 202, 203, 207, 208, 210, 214, 215, 217, 219, 220, 223, 227, 229–231, 233, 234, 236–239, 242, 243, 246
- augment.betareg, 7
- augment.clm (tidy.polr), 211
- augment.coxph, 8, 49, 61, 67, 68, 99, 106–109, 128, 144, 150, 218, 230, 232, 233, 235
- augment.decomposed.ts, 10, 47
- augment.factanal, 12, 71, 158
- augment.felm, 14, 159
- augment.glm, 15, 25, 78, 86, 170, 187
- augment.glmRob, 17, 26, 79, 88, 173, 191
- augment.htest, 18, 177, 207, 215
- augment.ivreg, 20, 82, 179
- augment.kmeans, 22, 83, 184
- augment.lm, 16, 23, 78, 86, 170, 187
- augment.lm(), 15–18, 25, 26, 38, 39
- augment.lme (nlme_tidiers), 117
- augment.lmRob, 18, 25, 79, 88, 173, 191
- augment.loess, 27
- augment.Mclust, 28, 195
- augment.merMod (lme4_tidiers), 111
- augment.mjoint, 30
- augment.nlrq, 31, 41, 43, 93, 103, 202, 225, 226
- augment.nls, 32, 95, 204
- augment.NULL (null_tidiers), 119
- augment.plm, 34, 97, 209
- augment.poLCA, 35, 98, 210
- augment.polr (tidy.polr), 211
- augment.prcomp, 36, 216, 241, 244
- augment.rlm, 38, 101, 222
- augment.rowwise_df (rowwise_df_tidiers), 120
- augment.rq, 32, 39, 43, 93, 103, 202, 225, 226
- augment.rqs, 32, 41, 41, 93, 103, 202, 225, 226
- augment.smooth.spline, 43, 104
- augment.speedlm, 45, 105, 229
- augment.stl, 11, 46
- augment.survreg, 10, 47, 61, 67, 68, 99, 106–109, 128, 144, 150, 218, 230, 232, 233, 235
- augment.tbl_df (rowwise_df_tidiers), 120
- augment_.rowwise_df (rowwise_df_tidiers), 120
- augment_columns, 49

- bbmle::mle2(), 198
- bbmle_tidiers (tidy.mle2), 198
- betareg::betareg(), 7, 8, 63, 135
- betareg_tidiers (tidy.betareg), 134
- biglm::bigglm(), 64, 136, 137
- biglm::biglm(), 64, 136, 137

- bindesign_tidiers (tidy.binDesign), 138
- binGroup:binDesign, 65
- binGroup:binDesign(), 65, 138
- binGroup:binWidth(), 139
- binwidth_tidiers (tidy.binWidth), 139
- boot:boot(), 140, 141
- boot:boot.ci(), 140, 141
- boot:tsboot(), 141
- boot_tidiers (tidy.boot), 140
- bootstrap, 50
- brms:brms(), 52
- brms:brmsfit(), 51, 52
- brms_tidiers, 51
- broom, 52
- broom-package (broom), 52
- btergm:btergm(), 142, 143
- btergm_tidiers (tidy.btergm), 142

- car::Anova(), 130
- car::durbinWatsonTest(), 56, 57
- caret::confusionMatrix(), 148
- caret_tidiers (tidy.confusionMatrix), 148
- cch_tidiers (tidy.cch), 143
- cfa_tidiers (tidy.lavaan), 185
- coefstest_tidiers (tidy.coefstest), 146
- column_glossary, 53
- confint, 54
- confint(), 53
- confint_tidy, 53
- confusionMatrix_tidiers (tidy.confusionMatrix), 148
- cooks.distance(), 8, 16, 17, 24, 26, 39
- coxph_tidiers (tidy.coxph), 149

- data.frame(), 7–9, 13–15, 17, 20, 22, 24, 25, 27, 29, 30, 32–34, 37, 38, 40, 42, 44–46, 48
- data.frame_tidiers, 54
- decompose_tidiers (augment.decomposed.ts), 10
- durbinWatsonTest_tidiers, 56

- emmeans::summary.emmGrid(), 57
- emmeans_tidiers, 57
- ergm:control.ergm(), 156
- ergm:ergm(), 70, 156
- ergm:summary(), 70, 156
- ergm:summary.ergm(), 70

- ergm_tidiers (tidy.ergm), 155

- factanal(), 13
- factanal_tidiers (tidy.factanal), 157
- felm_tidiers (tidy.felm), 158
- finish_glance, 59
- fitdistr_tidiers (tidy.fitdistr), 160
- fix_data_frame, 60

- gam::gam(), 74, 75, 162, 163
- Gam_tidiers (tidy.Gam), 162
- gam_tidiers (tidy.gam), 163
- gamlss:gamlss(), 164
- garch_tidiers (tidy.garch), 165
- geeglm_tidiers (tidy.geeglm), 166
- geepack::geeglm(), 167
- geepack_tidiers (tidy.geeglm), 166
- glance(), 56, 57, 61, 63–65, 67–71, 75–77, 79, 80, 82, 83, 85–87, 90–93, 96–101, 103, 106–110, 126, 176
- glance.aareg, 10, 49, 60, 67, 68, 99, 106–109, 128, 144, 150, 218, 230, 232, 233, 235
- glance.Arima, 61, 134
- glance.betareg, 62
- glance.biglm, 64, 137
- glance.binDesign, 65, 138, 139
- glance.cch, 10, 49, 61, 66, 68, 99, 106–109, 128, 144, 150, 218, 230, 232, 233, 235
- glance.clm (tidy.polr), 211
- glance.clmm (tidy.polr), 211
- glance.coxph, 10, 49, 61, 67, 67, 99, 106–109, 128, 144, 150, 218, 230, 232, 233, 235
- glance.cv.glmnet, 68, 79, 152, 171
- glance.data.frame (data.frame_tidiers), 54
- glance.durbinWatsonTest (durbinWatsonTest_tidiers), 56
- glance.ergm, 69, 156
- glance.factanal, 14, 70, 158
- glance.felm, 71
- glance.fitdistr, 73, 160
- glance.Gam, 74, 162
- glance.gam, 75, 163
- glance.Gam(), 75, 76
- glance.gam(), 74
- glance.garch, 76, 166

- glance.glm, [16](#), [25](#), [77](#), [86](#), [170](#), [187](#)
 glance.glmnet, [69](#), [78](#), [152](#), [171](#)
 glance.glmRob, [18](#), [26](#), [79](#), [88](#), [173](#), [191](#)
 glance.gmm, [80](#), [175](#)
 glance.htest (tidy.htest), [176](#)
 glance.ivreg, [21](#), [81](#), [179](#)
 glance.kmeans, [23](#), [82](#), [184](#)
 glance.lavaan, [84](#), [186](#)
 glance.list (list_tidiers), [111](#)
 glance.lm, [16](#), [25](#), [78](#), [85](#), [170](#), [187](#)
 glance.lme (nlme_tidiers), [117](#)
 glance.lmodel2, [87](#), [189](#)
 glance.lmRob, [18](#), [26](#), [79](#), [88](#), [173](#), [191](#)
 glance.matrix (matrix_tidiers), [114](#)
 glance.Mclust, [89](#)
 glance.merMod (lme4_tidiers), [111](#)
 glance.mjoint, [90](#), [197](#)
 glance.muhaaz, [91](#), [200](#)
 glance.multinom, [92](#), [201](#)
 glance.nlrq, [32](#), [41](#), [43](#), [93](#), [103](#), [202](#), [225](#),
 [226](#)
 glance.nls, [33](#), [94](#), [204](#)
 glance.NULL (null_tidiers), [119](#)
 glance.optim (glance_optim), [109](#)
 glance.orcutt, [95](#), [206](#)
 glance.plm, [35](#), [96](#), [209](#)
 glance.poLCA, [36](#), [97](#), [210](#)
 glance.polr (tidy.polr), [211](#)
 glance.pyears, [10](#), [49](#), [61](#), [67](#), [68](#), [98](#),
 [106–109](#), [128](#), [144](#), [150](#), [218](#), [230](#),
 [232](#), [233](#), [235](#)
 glance.ridgeIm, [99](#), [221](#)
 glance.rlm, [39](#), [100](#), [222](#)
 glance.rowwise_df (rowwise_df_tidiers),
 [120](#)
 glance.rq, [32](#), [41](#), [43](#), [93](#), [102](#), [202](#), [225](#), [226](#)
 glance.smooth.spline, [44](#), [103](#)
 glance.speedIm, [46](#), [104](#), [229](#)
 glance.stanreg (rstanarm_tidiers), [122](#)
 glance.summary.lm (glance.lm), [85](#)
 glance.summaryDefault
 (summary_tidiers), [126](#)
 glance.survdiff, [10](#), [49](#), [61](#), [67](#), [68](#), [99](#), [105](#),
 [107–109](#), [128](#), [144](#), [150](#), [218](#), [230](#),
 [232](#), [233](#), [235](#)
 glance.survexp, [10](#), [49](#), [61](#), [67](#), [68](#), [99](#), [106](#),
 [106](#), [108](#), [109](#), [128](#), [144](#), [150](#), [218](#),
 [230](#), [232](#), [233](#), [235](#)
 glance.survfit, [10](#), [49](#), [61](#), [67](#), [68](#), [99](#), [106](#),
 [107](#), [107](#), [109](#), [128](#), [144](#), [150](#), [218](#),
 [230](#), [232](#), [233](#), [235](#)
 glance.survreg, [10](#), [49](#), [61](#), [67](#), [68](#), [99](#),
 [106–108](#), [108](#), [128](#), [144](#), [150](#), [218](#),
 [230](#), [232](#), [233](#), [235](#)
 glance.svyolr (tidy.polr), [211](#)
 glance.tbl_df (rowwise_df_tidiers), [120](#)
 glance_.rowwise_df
 (rowwise_df_tidiers), [120](#)
 glance_optim, [109](#), [111](#), [241](#), [242](#), [244](#), [246](#)
 glmnet::cv.glmnet(), [69](#), [152](#)
 glmnet::glmnet(), [78](#), [79](#), [171](#)
 glmnet_tidiers (tidy.glmnet), [170](#)
 gmm::gmm(), [80](#), [174](#), [175](#)
 gmm_tidiers (tidy.gmm), [174](#)
 graphics::image(), [245](#), [246](#)
 graphics::persp(), [245](#), [246](#)
 Hmisc::rcorr(), [219](#)
 Hmisc_tidiers (tidy.rcorr), [218](#)
 htest_tidiers (tidy.htest), [176](#)
 insert_NAs, [110](#)
 irlba::irlba(), [240](#), [241](#)
 irlba_tidiers (tidy_irlba), [240](#)
 ivreg_tidiers (tidy.ivreg), [178](#)
 joinerML::bootSE(), [196](#), [197](#)
 joinerML::fitted.mjoint(), [31](#)
 joinerML::mjoint(), [30](#), [90](#), [196](#), [197](#)
 joinerML::residuals.mjoint(), [31](#)
 joinerml_tidiers (tidy.mjoint), [196](#)
 kappa_tidiers (tidy.kappa), [180](#)
 kde_tidiers (tidy.kde), [181](#)
 Kendall::Kendall(), [183](#)
 Kendall::MannKendall(), [183](#)
 Kendall::SeasonalMannKendall(), [183](#)
 Kendall_tidiers (tidy.Kendall), [182](#)
 kendall_tidiers (tidy.Kendall), [182](#)
 kmeans_tidiers (tidy.kmeans), [184](#)
 ks::kde(), [181](#), [182](#)
 ks_tidiers (tidy.kde), [181](#)
 lavaan::cfa(), [84](#), [85](#), [185](#), [186](#)
 lavaan::fitmeasures(), [85](#)
 lavaan::parameterEstimates(), [185](#), [186](#)
 lavaan::sem(), [84](#), [85](#), [185](#), [186](#)

- lavaan_tidiers (tidy.lavaan), 185
 lfe::felm(), 14, 15, 72, 158, 159
 lfe_tidiers (tidy.felm), 158
 list_tidiers, 110, 111, 241, 242, 244, 246
 lm(), 13
 lm_tidiers (tidy.lm), 186
 lme4_tidiers, 111
 lmodel2::lmodel2(), 87, 189
 lmodel2_tidiers (tidy.lmodel2), 188
 lmtest::coefstest(), 146
 lmtest_tidiers (tidy.coefstest), 146
 loess_tidiers (augment.loess), 27
 lsmeans::summary.ref.grid(), 57
- maps::map(), 193
 maps_tidiers (tidy.map), 193
 MASS::fitdistr(), 73, 160
 MASS::lm.ridge(), 100, 220, 221
 MASS::polr(), 211
 MASS::rlm(), 38, 39, 101, 222
 MASS::select.ridgelm(), 100
 matrix_tidiers, 114
 mclust::Mclust(), 29, 30, 89, 194, 195
 mclust_tidiers (tidy.Mclust), 194
 mcmc_tidiers, 115
 mean(), 54
 mgcv::gam(), 74–76, 162, 163
 mgcv_tidiers (tidy.gam), 163
 mjoint_tidiers (tidy.mjoint), 196
 mle2_tidiers (tidy.mle2), 198
 muhaz::muhaz(), 91, 199, 200
 muhaz_tidiers (tidy.muhaz), 199
 multcomp::cld(), 145, 146
 multcomp::confint.glh(), 146, 147
 multcomp::glht(), 146, 147, 168, 229
 multcomp::summary.glh(), 146, 229
 multcomp_tidiers (tidy.glh), 168
 multinom_tidiers (tidy.multinom), 200
- na.action, 7, 9–11, 13, 14, 19, 20, 22, 23, 25,
 28–30, 33–35, 37, 40, 42, 45, 46, 48,
 49, 97, 113, 118
 nlme_tidiers, 117
 nlrq_tidiers (tidy.nlrq), 201
 nls_tidiers (tidy.nls), 203
 nnet::multinom(), 92, 200, 201
 nnet_tidiers (tidy.multinom), 200
 null_tidiers, 119
- optim(), 110
 optim_tidiers (tidy.optim), 242
 orcutt::cochrane.orcutt(), 95, 96, 205,
 206
 orcutt_tidiers (tidy.orcutt), 205
 ordinal::clm(), 211, 213
 ordinal::clmm(), 211, 213
 ordinal::confint.clm(), 213
 ordinal::predict.clm(), 213
 ordinal_tidiers (tidy.polr), 211
- plm::plm(), 34, 35, 96, 97, 208, 209
 plm_tidiers (tidy.plm), 208
 polCA::polCA(), 36, 98, 210
 polCA_tidiers (tidy.polCA), 209
 prcomp_tidiers (tidy.prcomp), 215
 psych::cohen.kappa(), 180
 psych_tidiers (tidy.kappa), 180
 purrr::map(), 102
 purrr::map_df(), 119
 pyyears_tidiers (tidy.pyyears), 217
- qr, 192
 quantreg::nlrq(), 31, 32, 93, 202
 quantreg::predict.rq(), 41
 quantreg::predict.rqs(), 43
 quantreg::rq(), 40–43, 102, 103, 224–226
 quantreg::summary.rq(), 224–226
 quantreg::summary.rqs(), 226
 quantreg_tidiers (tidy.rq), 224
- rcorr_tidiers (tidy.rcorr), 218
 ridgelm_tidiers (tidy.ridgelm), 220
 rlm_tidiers (glance.rlm), 100
 robust::glmRob(), 17, 18, 79, 172, 173
 robust::lmRob(), 25, 26, 88, 190, 191
 robust_tidiers (tidy.lmRob), 190
 roc_tidiers (tidy.roc), 223
 rowwise_df_tidiers, 120
 rq_tidiers (tidy.rq), 224
 rqs_tidiers (tidy.rqs), 225
 rsample::bootstraps(), 141
 rstanarm::loo.stanreg(), 122
 rstanarm::posterior_interval(), 122,
 123
 rstanarm::print.stanreg(), 123
 rstanarm::stan_glm.nb(), 123
 rstanarm::stan_glmer(), 123
 rstanarm::stan_lm(), 123

- rstanarm::summary.stanreg(), 123
- rstanarm_tidiers, 122
- sem_tidiers (tidy.lavaan), 185
- sexpfit_tidiers (tidy.survexp), 231
- smooth.spline_tidiers
 - (augment.smooth.spline), 43
- sp_tidiers, 125
- sparse_tidiers, 124
- speedglm::speedlm(), 45, 46, 104, 105, 228, 229
- speedglm_tidiers (tidy.speedlm), 228
- speedlm_tidiers (tidy.speedlm), 228
- splines::ns(), 7, 9, 11, 13, 14, 18, 20, 22, 23, 29, 30, 33–35, 37, 40, 42, 45, 46, 48, 97
- stats::acf(), 128, 129
- stats::anova(), 130
- stats::aov(), 131–133
- stats::arima(), 62, 133, 134
- stats::ccf(), 128, 129
- stats::chisq.test(), 19, 177
- stats::cor.test(), 19, 177
- stats::decompose(), 11
- stats::density(), 153, 154
- stats::dist(), 154, 155
- stats::factanal(), 13, 14, 71, 157, 158
- stats::ftable(), 161
- stats::glm(), 15, 16, 77, 78, 169, 170
- stats::kmeans(), 22, 23, 83, 184
- stats::lm(), 16, 17, 24, 26, 38, 86, 169, 172, 186, 190, 205, 222, 228
- stats::loess(), 27, 28
- stats::mad(), 123
- stats::manova(), 192
- stats::nls(), 32, 33, 94, 95, 203, 204
- stats::optim(), 109–111, 240, 242, 243, 245
- stats::pacf(), 128, 129
- stats::pairwise.t.test(), 207
- stats::pairwise.wilcox.test(), 207
- stats::poly(), 7, 9, 11, 13, 14, 18, 20, 22, 23, 29, 30, 33–35, 37, 40, 42, 45, 46, 48, 97
- stats::power.t.test(), 214, 215
- stats::prcomp(), 37, 38, 215, 216
- stats::predict(), 8, 9, 48
- stats::predict.glm(), 16, 17, 24, 26, 38
- stats::predict.lm(), 25
- stats::predict.loess(), 28
- stats::predict.nls(), 33
- stats::predict.smooth.spline(), 44
- stats::residuals(), 8, 9, 48
- stats::residuals.glm(), 16, 17, 24, 26, 38
- stats::smooth.spline(), 44, 103, 104
- stats::spectrum(), 227
- stats::stl(), 47
- stats::summary.lm(), 187
- stats::summary.manova(), 193
- stats::summary.nls(), 204
- stats::t.test(), 19, 177
- stats::ts(), 237
- stats::TukeyHSD(), 238
- stats::wilcox.test(), 19, 177
- summary(), 126
- summary_tidiers, 126
- survdifftidiers (tidy.survdifft), 230
- survexp_tidiers (tidy.survexp), 231
- survey::svyolr(), 211, 213
- survfit_tidiers (tidy.survfit), 232
- survival::aareg(), 61, 127, 128
- survival::cch(), 66, 67, 144
- survival::coxph(), 9, 10, 68, 150
- survival::print.survfit(), 108
- survival::pyears(), 99, 217, 218
- survival::Surv(), 7, 9, 11, 13, 14, 19, 20, 22, 23, 29, 30, 33–35, 37, 40, 42, 45, 46, 48, 97
- survival::survdifft(), 105, 106, 230
- survival::survexp(), 106, 107, 231, 232
- survival::survfit(), 107, 108, 232, 233
- survival::survreg(), 48, 49, 108, 109, 234, 235
- survreg_tidiers (tidy.survreg), 234
- svd(), 109, 111, 240, 242–245
- svd_tidiers, 38, 216
- svd_tidiers (tidy_svd), 243
- table, 236
- tibble::as_tibble(), 236
- tibble::tibble, 7, 9–11, 13, 14, 18, 20, 22, 23, 29, 30, 33–37, 40–43, 45–49, 56, 61, 62, 65, 67–69, 71–80, 83, 84, 86–92, 94, 95, 97–107, 109, 110, 119, 120, 126, 127, 129–132, 134, 138, 139, 141, 142, 146, 148, 150, 152, 154–157, 160–162, 164, 166, 167, 171, 177, 180, 181, 183–185,

- 189, 192, 195, 199, 207, 210, 216,
218–220, 227, 230, 231, 233,
236–239, 241, 242, 244, 246
- `tibble::tibble()`, 7–9, 13–15, 17, 20–22,
24, 25, 27, 29–35, 37, 38, 40, 42,
44–46, 48, 60–62, 64–70, 72–75,
77–81, 83–85, 87–96, 98–100, 102,
104–108, 135, 137, 144, 159, 170,
173, 174, 179, 187, 191, 196, 202,
203, 208, 222, 223, 225, 226, 228,
234
- `tidy`, 33, 95, 204
- `tidy()`, 56, 57, 73, 126, 128–131, 133, 135,
137–139, 141, 143, 144, 146–148,
150, 152, 154–156, 158–163,
166–168, 170, 171, 173, 175–177,
179, 180, 182–184, 186, 187, 189,
191, 193, 195, 197, 198, 200–202,
206, 207, 209, 210, 218, 219,
221–223, 225–227, 229, 230, 232,
233, 235, 237–239, 241, 242, 246
- `tidy.aareg`, 10, 49, 61, 67, 68, 99, 106–109,
127, 144, 150, 218, 230, 232, 233,
235
- `tidy.acf`, 128, 227, 237, 239
- `tidy.anova`, 129, 131, 133, 193, 238
- `tidy.anova()`, 162
- `tidy.aov`, 130, 131, 133, 193, 238
- `tidy.aovlist`, 130, 131, 132, 193, 238
- `tidy.Arima`, 62, 133
- `tidy.betareg`, 134
- `tidy.biglm`, 64, 136
- `tidy.binDesign`, 65, 138, 139
- `tidy.binWidth`, 65, 138, 139
- `tidy.boot`, 140
- `tidy.brmsfit` (`brms_tidiers`), 51
- `tidy.btergm`, 142
- `tidy.cch`, 10, 49, 61, 67, 68, 99, 106–109,
128, 143, 150, 218, 230, 232, 233,
235
- `tidy.character` (`tidy.numeric`), 204
- `tidy.cld`, 145, 147, 168, 229
- `tidy.clm` (`tidy.polr`), 211
- `tidy.clmm` (`tidy.polr`), 211
- `tidy.coefTest`, 146
- `tidy.confint.glm`, 146, 147, 168, 229
- `tidy.confusionMatrix`, 148
- `tidy.coxph`, 10, 49, 61, 67, 68, 99, 106–109,
128, 144, 149, 218, 230, 232, 233,
235
- `tidy.cv.glmnet`, 69, 79, 151, 171
- `tidy.data.frame` (`data.frame_tidiers`), 54
- `tidy.density`, 153, 155, 161
- `tidy.dgCMatrix` (`sparse_tidiers`), 124
- `tidy.dgTMatrix` (`sparse_tidiers`), 124
- `tidy.dist`, 154, 154, 161
- `tidy.durbinWatsonTest`
(`durbinWatsonTest_tidiers`), 56
- `tidy.emmGrid` (`emmeans_tidiers`), 57
- `tidy.ergm`, 70, 155
- `tidy.factanal`, 14, 71, 157
- `tidy.felm`, 15, 158
- `tidy.fitdistr`, 73, 160
- `tidy.ftable`, 154, 155, 161
- `tidy.Gam`, 75, 162
- `tidy.gam`, 76, 163
- `tidy.Gam()`, 163
- `tidy.gam()`, 162
- `tidy.gamlss`, 164
- `tidy.garch`, 77, 165
- `tidy.geeglm`, 166
- `tidy.glm`, 16, 25, 78, 86, 169, 187
- `tidy.glmnet`, 69, 79, 152, 170
- `tidy.glmRob`, 18, 26, 79, 88, 172, 191
- `tidy.glmRob()`, 38, 101, 222
- `tidy.gmm`, 80, 174
- `tidy.htest`, 19, 176, 207, 215
- `tidy.irlba` (`tidy_irlba`), 240
- `tidy.ivreg`, 21, 82, 178
- `tidy.kappa`, 180
- `tidy.kde`, 181
- `tidy.Kendall`, 182
- `tidy.kmeans`, 23, 83, 184
- `tidy.lavaan`, 85, 185
- `tidy.Line` (`sp_tidiers`), 125
- `tidy.Lines` (`sp_tidiers`), 125
- `tidy.list` (`list_tidiers`), 111
- `tidy.lm`, 16, 25, 78, 86, 170, 186
- `tidy.lm()`, 169, 170, 172, 173, 190, 191, 205,
206, 209, 221, 222, 228, 229
- `tidy.lme` (`nlme_tidiers`), 117
- `tidy.lmodel2`, 87, 188
- `tidy.lmRob`, 18, 26, 79, 88, 173, 190
- `tidy.lmRob()`, 38, 101, 222
- `tidy.logical` (`tidy.numeric`), 204

- tidy.lsmobj (emmeans_tidiers), 57
- tidy.manova, 130, 131, 133, 192, 238
- tidy.map, 193
- tidy.matrix (matrix_tidiers), 114
- tidy.Mclust, 30, 194
- tidy.merMod (lme4_tidiers), 111
- tidy.mjoint, 90, 196
- tidy.mle2, 198
- tidy.muhaaz, 91, 199
- tidy.multinom, 92, 200
- tidy.nlrq, 32, 41, 43, 93, 103, 201, 225, 226
- tidy.nls, 33, 95, 203
- tidy.NULL (null_tidiers), 119
- tidy.numeric, 204
- tidy.optim (tidy_optim), 242
- tidy.orcutt, 96, 205
- tidy.pairwise.htest, 19, 177, 206, 215
- tidy.plm, 35, 97, 208
- tidy.poLCA, 36, 98, 209
- tidy.polr, 211
- tidy.Polygon (sp_tidiers), 125
- tidy.Polygons (sp_tidiers), 125
- tidy.power.htest, 19, 177, 207, 214
- tidy.pcomp, 38, 215, 241, 244
- tidy.pyears, 10, 49, 61, 67, 68, 99, 106–109, 128, 144, 150, 217, 230, 232, 233, 235
- tidy.rcorr, 218
- tidy.ref.grid (emmeans_tidiers), 57
- tidy.ridgeIm, 100, 220
- tidy.rjags (mcmc_tidiers), 115
- tidy.rlm, 39, 101, 221
- tidy.rlm(), 17, 26, 173, 190
- tidy.roc, 223
- tidy.rowwise_df (rowwise_df_tidiers), 120
- tidy.rq, 32, 41, 43, 93, 103, 202, 224, 226
- tidy.rqs, 32, 41, 43, 93, 103, 202, 225, 225
- tidy.sparseMatrix (sparse_tidiers), 124
- tidy.SpatialLinesDataFrame (sp_tidiers), 125
- tidy.SpatialPolygons (sp_tidiers), 125
- tidy.SpatialPolygonsDataFrame (sp_tidiers), 125
- tidy.spec, 129, 227, 237, 239
- tidy.speedIm, 46, 105, 228
- tidy.stanfit (mcmc_tidiers), 115
- tidy.stanreg (rstanarm_tidiers), 122
- tidy.summary.glm, 146, 147, 168, 229
- tidy.summary.lm (tidy.lm), 186
- tidy.summaryDefault (summary_tidiers), 126
- tidy.survdiff, 10, 49, 61, 67, 68, 99, 106–109, 128, 144, 150, 218, 230, 232, 233, 235
- tidy.survexp, 10, 49, 61, 67, 68, 99, 106–109, 128, 144, 150, 218, 230, 231, 233, 235
- tidy.survfit, 10, 49, 61, 67, 68, 99, 106–109, 128, 144, 150, 218, 230, 232, 232, 235
- tidy.survreg, 10, 49, 61, 67, 68, 99, 106–109, 128, 144, 150, 218, 230, 232, 233, 234
- tidy.svyolr (tidy.polr), 211
- tidy.table, 235
- tidy.tbl_df (rowwise_df_tidiers), 120
- tidy.ts, 129, 227, 236, 239
- tidy.TukeyHSD, 130, 131, 133, 193, 237
- tidy.zoo, 129, 227, 237, 239
- tidy_.rowwise_df (rowwise_df_tidiers), 120
- tidy_irlba, 38, 110, 111, 216, 240, 242, 244, 246
- tidy_optim, 110, 111, 241, 242, 244, 246
- tidy_optim(), 198
- tidy_svd, 38, 110, 111, 216, 241, 242, 243, 246
- tidy_svd(), 241
- tidy_xyz, 110, 111, 241, 242, 244, 245
- tidyMCMC (mcmc_tidiers), 115
- tidyr::gather(), 236
- tseries::garch(), 76, 77, 165, 166
- xyz_tidiers (tidy_xyz), 245
- zoo::zoo(), 239
- zoo_tidiers (tidy.zoo), 239