

Package ‘emoa’

February 19, 2015

Title Evolutionary Multiobjective Optimization Algorithms

Description Collection of building blocks for the design and analysis of evolutionary multiobjective optimization algorithms.

Author Olaf Mersmann <olafm@statistik.tu-dortmund.de>

Maintainer Olaf Mersmann <olafm@statistik.tu-dortmund.de>

License GPL-2

URL <http://www.statistik.tu-dortmund.de/~olafm/software/emoa/>

LazyData yes

Version 0.5-0

Suggests RUnit

Collate 'cec2009.r' 'control.R' 'crowding_distance.r' 'dominance.r' 'emoa.r' 'front_edge.R' 'hypervolume.r' 'indicators.r' 'logger.R' 'poly_mutation.r' 'sb_crossover.r' 'selection.r' 'sympart.r' 'utilities.r'

Date

Repository CRAN

Date/Publication 2012-09-25 11:35:13

NeedsCompilation yes

R topics documented:

emoa-package	2
cec2007	3
coalesce	4
crowding_distance	4
dominated_hypervolume	5
emoa_console_logger	6
emoa_control	6
emoa_logger	7
emoa_null_logger	8
hypervolume_indicator	8

inbounds	9
is_dominated	10
nds_hv_selection	10
nds_rank	11
nondominated_points	12
normalize_points	12
pm_control	13
pm_operator	13
sbx_control	14
sbx_operator	15
steady_state_emoa_control	15
sympart	16
UF1	17
unary_r2_indicator	18
which_points_on_edge	18

Index	20
--------------	-----------

emoa-package	<i>The EMOA package</i>
--------------	-------------------------

Description

This package provides functions to construct evolutionary multiobjective optimization algorithms (EMOA). The long term goal is to also provide standard implementations of the most common EMOA in use today.

Details

Without the hard work of many researchers who have published their source code under a liberal license, this package would not have been possible. In alphabetical order they are

- Michael H. Buselli
- Wessel Dankers
- Carlos Fonseca
- Joshua Knowles
- Huang Ling
- Wudong Liu
- Manuel Lopez-Ibanez
- Luis Paquete
- Ponnuthurai Nagarathnam Suganthany
- Santosh Tiwar
- Qingfu Zhang
- Aimin Zhou
- Shizheng Zhaoy

Author(s)

Olaf Mersmann <olafm@statistik.tu-dortmund.de>

cec2007

CEC 2007 multiobjective optimization competition results

Description

This data set contains the hypervolume and R2 indicator results of the 8 different algorithms that took part in the CEC 2007 multiobjective optimization benchmark.

Usage

```
data(cec2007)
```

Format

A data frame with 456 observations of the following 9 variables.

`algo` Abbreviated name of algorithm

`fun` Name of benchmark function

`d` Dimension of objective space

`n` Number of function evaluations

`metric` Name of quality metric

`pdef` Unique id for each combination of `fun`, `d`, `n` and `metric`

`best` Largest value of metric

`median` Median value of metric

`worst` Smallest value of metric

`mean` Average value of metric

`std` Standard deviation of metric

Source

<http://web.mysites.ntu.edu.sg/epnsugan/PublicSite/Shared%20Documents/CEC2007-final-pdfs.zip>

Examples

```
## Not run:
data(cec2007)
require(lattice)
print(dotplot(algo ~ median | fun + metric, cec2007, groups=cec2007$n))

## End(Not run)
```

coalesce	<i>Return first non null argument.</i>
----------	--

Description

This function is useful when processing complex arguments with multiple possible defaults based on other arguments that may or may not have been provided.

Usage

```
coalesce(...)
```

Arguments

... List of values.

Value

First non null element in

Author(s)

Olaf Mersmann <olafm@statistik.tu-dortmund.de>

crowding_distance	<i>Crowding Distance</i>
-------------------	--------------------------

Description

Calculate crowding distances.

Usage

```
crowding_distance(front)
```

Arguments

front matrix of function values.

Value

crowding distance for each function value.

Author(s)

Olaf Mersmann <olafm@statistik.tu-dortmund.de>

dominated_hypervolume *Dominated Hypervolume calculation*

Description

dominated_hypervolume calculates the dominated hypervolume of the points in points.

Usage

```
dominated_hypervolume(points, ref)
```

```
hypervolume_contribution(points, ref)
```

Arguments

points	Matrix containing the points one per column.
ref	Optional reference point. If not provided the maximum in each dimension is used.

Details

hypervolume_contribution calculates the hypervolume contribution of each point.

If no reference point ref is given, one is automatically calculated by determining the maximum in each coordinate.

Currently only one general algorithm is implemented due to Fonseca et.al. but work is underway to include others such as the Beume & Rudolph approach as well as the approach by Bradstreet et.al.

The 1D and 2D cases are handled separately by efficient algorithms. Calculates the exact dominated hypervolume of the points given in x subject to the reference point ref.

Value

For dominated_hypervolume the dominated hypervolume by the points in points with respect to the reference point ref. For hypervolume_contribution a vector giving the hypervolume solely dominated by that point.

Author(s)

Olaf Mersmann <olafm@statistik.tu-dortmund.de>

References

This code uses version 1.3 of the hypervolume code available from <http://iridia.ulb.ac.be/~manuel/hypervolume>. For a description of the algorithm see

Carlos M. Fonseca, Luis Paquete, and Manuel Lopez-Ibanez. *An improved dimension-sweep algorithm for the hypervolume indicator*. In IEEE Congress on Evolutionary Computation, pages 1157-1163, Vancouver, Canada, July 2006.

See Also

[nondominated_points](#) to extract the pareto front approximation from a given set of points and [nds_hv_selection](#) for a selection strategy based on the hypervolume contribution of each point.

emoa_console_logger *console logger*

Description

Logger object that outputs log messages to the console

Usage

```
emoa_console_logger(...)
```

Arguments

... passed to [emoa_logger](#).

Details

This is a wrapper that calls `emoa_logger(output=output, ...)` internally and returns that logger.

Value

An `emoa_logger` object.

emoa_control *Basic EMOA control parameters.*

Description

The following control parameters are recognized by `emoa_control`:

logger `emoa_logger` object used to log events.

n Number of parameters, defaults to the length of the longer of upper or lower.

d Number of dimensions.

Usage

```
emoa_control(f, upper, lower, ..., control, default)
```

Arguments

f	Multiobjective optimization function.
upper	Upper bounds of parameter space.
lower	Lower bounds of parameter space.
...	Further arguments passed to f.
control	List of control parameters.
default	List of default control parameters.

Value

The control list with suitably adjusted arguments. Missing control parameters are taken from default or, if not present there, from an internal default.

Author(s)

Olaf Mersmann <olafm@statistik.tu-dortmund.de>

emoa_logger

generic logger factory

Description

Basic logger object with a flexible output routine.

Usage

```
emoa_logger(output, every = 10L)
```

Arguments

output	function used to display logging messages.
every	number of steps of the emoa between evaluations.
...	passed to the parent logger factory.

Value

An emoa_logger object.

See Also

[emoa_console_logger](#) and [emoa_null_logger](#) for convenience wrappers around emoa_logger providing useful defaults.

emoa_null_logger *null logger*

Description

Logger object that discards all log events.

Usage

```
emoa_null_logger(...)
```

Arguments

... ignored.

Value

An emoa_logger object.

hypervolume_indicator *Binary quality indicators*

Description

Calculates the quality indicator value of the set of points given in *x* with respect to the set given in *o*. As with all functions in emoa that deal with sets of objective values these are stored by column.

Usage

```
hypervolume_indicator(points, o, ref)
```

```
epsilon_indicator(points, o)
```

```
r1_indicator(points, o, ideal, nadir, lambda,
utility = "Tchebycheff")
```

```
r2_indicator(points, o, ideal, nadir, lambda,
utility = "Tchebycheff")
```

```
r3_indicator(points, o, ideal, nadir, lambda,
utility = "Tchebycheff")
```


Arguments

points	Matrix of points for which to calculate the indicator value stored one per column.
o	Matrix of points of the reference set.
ref	Reference point, if omitted, the nadir of the point sets is used.
ideal	Ideal point of true Pareto front. If omitted the ideal of both point sets is used.
nadir	Nadir of the true Pareto front. If omitted the nadir of both point sets is used.
lambda	Number of weight vectors to use in estimating the utility.
utility	Name of utility function.

Value

Value of the quality indicator.

Author(s)

Olaf Mersmann <olafm@statistik.tu-dortmund.de>

References

Zitzler, E., Thiele, L., Laumanns, M., Fonseca, C., and Grunert da Fonseca, V (2003): Performance Assessment of Multiobjective Optimizers: An Analysis and Review. IEEE Transactions on Evolutionary Computation, 7(2), 117-132.

inbounds	<i>Clip value to a given range</i>
----------	------------------------------------

Description

Clip x to the interval $[l, u]$. This is useful to enforce box constraints.

Usage

```
inbounds(x, l, u)
```

Arguments

x	Value to clip.
l	Lower limit.
u	Upper limit.

Value

l if $x < l$, u if $x > u$ else x .

Author(s)

Olaf Mersmann <olafm@statistik.tu-dortmund.de>

is_dominated	<i>Pareto dominance checks.</i>
--------------	---------------------------------

Description

is_dominated returns which points from a set are dominated by another point in the set. %dominates% returns true if x Pareto dominates y and is_maximally_dominated returns TRUE for those points which do not dominate any other points.

Usage

```
is_dominated(points)
```

```
is_maximally_dominated(points)
```

Arguments

points	Matrix containing points one per column.
--------	--

Value

For is_dominated and is_maximally_dominated a boolean vector and for %dominates% a single boolean.

Author(s)

Olaf Mersmann <olafm@statistik.tu-dortmund.de>

nds_hv_selection	<i>Selection strategies</i>
------------------	-----------------------------

Description

Selection strategies for EMOA.

Usage

```
nds_hv_selection(values, n = 1, ...)
```

```
nds_cd_selection(values, n = 1, ...)
```

Arguments

values	Matrix of function values.
n	Number of individuals to select for replacement.
...	Optional parameters passed to hypervolume_contribution .

Details

The currently implemented strategies are nondominated sorting followed by either hypervolume contribution or crowding distance based ranking. Both of these implementations are currently limited to selecting a single individual for replacement.

Author(s)

Olaf Mersmann <olafm@statistik.tu-dortmund.de>

nds_rank	<i>Nondominated sorting ranks</i>
----------	-----------------------------------

Description

Perform (partial) nondominated sort of the points in `points` and return the rank of each point.

Usage

```
nds_rank(points, partial)
nondominated_ordering(points, partial)
```

Arguments

<code>points</code>	Matrix containing points one per column.
<code>partial</code>	Optional integer specifying the number of points for which the rank should be calculated. Defaults to all points.

Value

Vector containing the ranks of the first `partial` individuals or all individuals.

Author(s)

Olaf Mersmann <olafm@statistik.tu-dortmund.de>

nondominated_points *Nondominated points*

Description

Return those points which are not dominated by another point in points. This is the Pareto front approximation of the point set.

Usage

```
nondominated_points(points)
```

Arguments

points Matrix of points, one per column.

Value

Those points in points which are not dominated by another point.

Author(s)

Olaf Mersmann <olafm@statistik.tu-dortmund.de>

normalize_points *Scale point cloud*

Description

Rescale all points to lie in the box bounded by minval and maxval.

Usage

```
normalize_points(points, minval, maxval)
```

Arguments

points Matrix containing points, one per column.
minval Optional lower limits for the new bounding box.
maxval Optional upper limits for the new bounding box.

Value

Scaled points.

Author(s)

Olaf Mersmann <olafm@statistik.tu-dortmund.de>

pm_control *Polynomial mutation (PM) control parameters*

Description

Control parameters:

pm.n Nu parameter of PM.

pm.p p parameter of PM.

Usage

```
pm_control(f, upper, lower, ..., control,
           default = list())
```

Arguments

f	Multiobjective optimization function.
upper	Upper bounds of parameter space.
lower	Lower bounds of parameter space.
...	Further arguments passed to f.
control	List of control parameters.
default	List of default control parameters.

Value

The control list with suitably adjusted arguments. Missing control parameters are taken from default or, if not present there, from an internal default.

Author(s)

Olaf Mersmann <olafm@statistik.tu-dortmund.de>

pm_operator *Polynomial mutation operator*

Description

Returns a polynomial mutation operator with the given parameters.

Usage

```
pm_operator(n, p, lower, upper)
```

Arguments

n	Distance parameter mutation distribution (η).
p	Probability of one point mutation.
lower	Lower bounds of parameter space.
upper	Upper bounds of parameter space.

Value

Function which implements the specified mutation operator.

Author(s)

Olaf Mersmann <olafm@statistik.tu-dortmund.de>

sbx_control	<i>Simulated binary crossover (SBX) control parameters</i>
-------------	--

Description

sbx_control interprets the following parameters used to control the behaviour of the simulated binary crossover operator (see [sbx_operator](#)):

sbx.n Nu parameter of SBX.

sbx.p \$p\$ parameter of SBX.

Usage

```
sbx_control(f, upper, lower, ..., control,
           default = list())
```

Arguments

f	Multiobjective optimization function.
upper	Upper bounds of parameter space.
lower	Lower bounds of parameter space.
...	Further arguments passed to f.
control	List of control parameters.
default	List of default control parameters.

Value

The control list with suitably adjusted arguments. Missing control parameters are taken from default or, if not present there, from an internal default.

Author(s)

Olaf Mersmann <olafm@statistik.tu-dortmund.de>

sbx_operator	<i>Simulated binary crossover operator</i>
--------------	--

Description

Returns a simulated binary crossover operator with the given parameters.

Usage

```
sbx_operator(n, p, lower, upper)
```

Arguments

n	Distance parameter of crossover distribution (η).
p	Probability of one point crossover.
lower	Lower bounds of parameter space.
upper	Upper bounds of parameter space.

Value

Function with one parameter x which takes a matrix containing two sets of parameters and returns a matrix of two sets of parameters which resulted from the crossover operation. As with all emoa functions, the parameter sets are stored in the columns of x . x should therefore always have two columns and a warning will be given if it has more than two columns.

Author(s)

Olaf Mersmann <olafm@statistik.tu-dortmund.de>

See Also

[pm_operator](#)

steady_state_emoa_control	<i>Steady state EMOA parameters</i>
---------------------------	-------------------------------------

Description

steady_state_emoa_control interprets the following control parameters:

mu Population size.

maxeval Maximum number of function evaluations to use.

Usage

```
steady_state_emoa_control(f, upper, lower, ..., control,  
                          default = list())
```

Arguments

f	Multiobjective optimization function.
upper	Upper bounds of parameter space.
lower	Lower bounds of parameter space.
...	Further arguments passed to f.
control	List of control parameters.
default	List of default control parameters.

Value

The control list with suitably adjusted arguments. Missing control parameters are taken from default or, if not present there, from an internal default.

Author(s)

Olaf Mersmann <olafm@statistik.tu-dortmund.de>

sympart

Functions from the CEC 2007 EMOA competition.

Description

Functions from the CEC 2007 EMOA competition.

Usage

```
sympart(x)
```

Arguments

x	Parameter vector.
---	-------------------

Value

Function value.

Author(s)

Olaf Mersmann <olafm@statistik.tu-dortmund.de>

UF1

Functions from the CEC 2009 EMOA competition.

Description

Functions from the CEC 2009 EMOA competition.

Usage

UF1(x)

UF2(x)

UF3(x)

UF4(x)

UF5(x)

UF6(x)

UF7(x)

UF8(x)

UF9(x)

UF10(x)

Arguments

x Parmater vector.

Value

Function value.

Author(s)

Olaf Mersmann <olafm@statistik.tu-dortmund.de>

unary_r2_indicator *Unary R2 indicator*

Description

Unary R2 indicator

Usage

```
unary_r2_indicator(points, weights, ideal)
```

Arguments

points	Matrix of points for which to calculate the indicator value stored one per column.
weights	Matrix of weight vectors stored one per column.
ideal	Ideal point of true Pareto front. If omitted the ideal of points is used.

Value

Value of unary R2 indicator.

Author(s)

Olaf Mersmann <olafm@p-value.net>

which_points_on_edge *Determine which points are on the edge of a Pareto-front approximation.*

Description

Determine which points are on the edge of a Pareto-front approximation.

Usage

```
which_points_on_edge(front)
```

Arguments

front	Pareto-front approximation.
-------	-----------------------------

Value

An integer vector containing the indices of the points (columns) of front which are on the edge of the Pareto-front approximation.

Author(s)

Olaf Mersmann <olafm@statistik.tu-dortmund.de>

Index

- *Topic **datasets**
 - cec2007, 3
- *Topic **nonlinear**
 - nds_hv_selection, 10
- *Topic **optimize**
 - dominated_hypervolume, 5
 - is_dominated, 10
 - nds_hv_selection, 10
 - nds_rank, 11
 - nondominated_points, 12
 - sympart, 16
 - UF1, 17
- *Topic **package**
 - emoa-package, 2

cec2007, 3

coalesce, 4

crowding_distance, 4

dominated_hypervolume, 5

emoa-package, 2

emoa_console_logger, 6, 7

emoa_control, 6

emoa_logger, 6, 7

emoa_null_logger, 7, 8

epsilon_indicator

- (hypervolume_indicator), 8

hypervolume_contribution, 10

hypervolume_contribution

- (dominated_hypervolume), 5

hypervolume_indicator, 8

inbounds, 9

is_dominated, 10

is_maximally_dominated (is_dominated), 10

nds_cd_selection (nds_hv_selection), 10

nds_hv_selection, 6, 10

nds_rank, 11

nondominated_ordering (nds_rank), 11

nondominated_points, 6, 12

normalize_points, 12

pm_control, 13

pm_operator, 13, 15

r1_indicator (hypervolume_indicator), 8

r2_indicator (hypervolume_indicator), 8

r3_indicator (hypervolume_indicator), 8

sbx_control, 14

sbx_operator, 14, 15

steady_state_emoa_control, 15

sympart, 16

UF1, 17

UF10 (UF1), 17

UF2 (UF1), 17

UF3 (UF1), 17

UF4 (UF1), 17

UF5 (UF1), 17

UF6 (UF1), 17

UF7 (UF1), 17

UF8 (UF1), 17

UF9 (UF1), 17

unary_r2_indicator, 18

which_points_on_edge, 18