

Package ‘radiant.design’

March 6, 2019

Type Package

Title Design Menu for Radiant: Business Analytics using R and Shiny

Version 0.9.9

Date 2019-3-4

Description The Radiant Design menu includes interfaces for design of experiments, sampling, and sample size calculation. The application extends the functionality in radiant.data.

Depends R (>= 3.4.0), radiant.data (>= 0.9.7), mvtnorm

Imports dplyr (>= 0.8.0), shiny (>= 1.2.0), AlgDesign (>= 1.1.7.3), import (>= 1.1.0), pwr (>= 1.1.2), polycor

Suggests testthat (>= 2.0.0), pkgdown (>= 1.1.0)

URL <https://github.com/radiant-rstats/radiant.design>,
<https://radiant-rstats.github.io/radiant.design>,
<https://radiant-rstats.github.io/docs>

BugReports <https://github.com/radiant-rstats/radiant.design/issues>

License AGPL-3 | file LICENSE

LazyData true

Encoding UTF-8

RoxygenNote 6.1.1

NeedsCompilation no

Author Vincent Nijs [aut, cre]

Maintainer Vincent Nijs <radiant@rady.ucsd.edu>

Repository CRAN

Date/Publication 2019-03-06 15:20:21 UTC

R topics documented:

doe	2
plot.sample_size_comp	3
radiant.design	4
radiant.design_viewer	4
radiant.design_window	5
rndnames	6
sample_size	6
sample_size_comp	7
sampling	8
summary.doe	9
summary.sample_size	10
summary.sample_size_comp	10
summary.sampling	11

Index	13
--------------	-----------

doe	<i>Create (partial) factorial design</i>
-----	--

Description

Create (partial) factorial design

Usage

```
doe(factors, int = "", trials = NA, seed = NA)
```

Arguments

factors	Categorical variables used as input for design
int	Vector of interaction terms to consider when generating design
trials	Number of trials to create. If NA then all feasible designs will be considered until a design with perfect D-efficiency is found
seed	Random seed to use as the starting point

Details

See <https://radiant-rstats.github.io/docs/design/doe.html> for an example in Radiant

Value

A list with all variables defined in the function as an object of class doe

See Also

[summary.doe](#) to summarize results

Examples

```
doe(c("price; $10; $13; $16", "food; popcorn; gourmet; no food"))
doe(
  c("price; $10; $13; $16", "food; popcorn; gourmet; no food"),
  int = "price:food", trials = 9, seed = 1234
)
```

plot.sample_size_comp *Plot method for the sample_size_comp function*

Description

Plot method for the sample_size_comp function

Usage

```
## S3 method for class 'sample_size_comp'
plot(x, ...)
```

Arguments

x	Return value from sample_size_comp
...	further arguments passed to or from other methods

Details

See https://radiant-rstats.github.io/docs/design/sample_size_comp.html for an example in Radiant

See Also

[sample_size_comp](#) to generate the results

Examples

```
sample_size_comp(
  type = "proportion", p1 = 0.1, p2 = 0.15,
  conf_lev = 0.95, power = 0.8
) %>% plot()
```

<code>radiant.design</code>	<i>radiant.design</i>
-----------------------------	-----------------------

Description

`radiant.design`
Launch `radiant.design` in the default browser

Usage

```
radiant.design(state, ...)
```

Arguments

<code>state</code>	Path to state file to load
<code>...</code>	additional arguments to pass to <code>shiny::runApp</code> (e.g, port = 8080)

Details

See <https://radiant-rstats.github.io/docs> for documentation and tutorials

Examples

```
## Not run:  
radiant.design()  
  
## End(Not run)
```

<code>radiant.design_viewer</code>	<i>Launch radiant.design in the Rstudio viewer</i>
------------------------------------	--

Description

Launch `radiant.design` in the Rstudio viewer

Usage

```
radiant.design_viewer(state, ...)
```

Arguments

<code>state</code>	Path to state file to load
<code>...</code>	additional arguments to pass to <code>shiny::runApp</code> (e.g, port = 8080)

Details

See <https://radiant-rstats.github.io/docs> for documentation and tutorials

Examples

```
## Not run:  
radiant.design_viewer()  
  
## End(Not run)
```

`radiant.design_window` *Launch radiant.design in an Rstudio window*

Description

Launch `radiant.design` in an Rstudio window

Usage

```
radiant.design_window(state, ...)
```

Arguments

<code>state</code>	Path to state file to load
<code>...</code>	additional arguments to pass to <code>shiny::runApp</code> (e.g, port = 8080)

Details

See <https://radiant-rstats.github.io/docs> for documentation and tutorials

Examples

```
## Not run:  
radiant.design_window()  
  
## End(Not run)
```

rndnames	<i>100 random names</i>
----------	-------------------------

Description

100 random names

Usage

```
data(rndnames)
```

Format

A data frame with 100 rows and 2 variables

Details

A list of 100 random names generated by listofrandomnames.com. Description provided in `attr(rndnames,"description")`

sample_size	<i>Sample size calculation</i>
-------------	--------------------------------

Description

Sample size calculation

Usage

```
sample_size(type, err_mean = 2, sd_mean = 10, err_prop = 0.1,
  p_prop = 0.5, conf_lev = 0.95, incidence = 1, response = 1,
  pop_correction = "no", pop_size = 1e+06)
```

Arguments

type	Choose "mean" or "proportion"
err_mean	Acceptable Error for Mean
sd_mean	Standard deviation for Mean
err_prop	Acceptable Error for Proportion
p_prop	Initial proportion estimate for Proportion
conf_lev	Confidence level
incidence	Incidence rate (i.e., fraction of valid respondents)
response	Response rate
pop_correction	Apply correction for population size ("yes","no")
pop_size	Population size

Details

See https://radiant-rstats.github.io/docs/design/sample_size.html for an example in Radiant

Value

A list of variables defined in `sample_size` as an object of class `sample_size`

See Also

`summary.sample_size` to summarize results

Examples

```
sample_size(type = "mean", err_mean = 2, sd_mean = 10)
```

sample_size_comp	<i>Sample size calculation for comparisons</i>
------------------	--

Description

Sample size calculation for comparisons

Usage

```
sample_size_comp(type, n1 = NULL, n2 = NULL, p1 = NULL, p2 = NULL,  
  delta = NULL, sd = NULL, conf_lev = NULL, power = NULL,  
  ratio = 1, alternative = "two.sided")
```

Arguments

type	Choose "mean" or "proportion"
n1	Sample size for group 1
n2	Sample size for group 2
p1	Proportion 1 (only used when "proportion" is selected)
p2	Proportion 2 (only used when "proportion" is selected)
delta	Difference in means between two groups (only used when "mean" is selected)
sd	Standard deviation (only used when "mean" is selected)
conf_lev	Confidence level
power	Power
ratio	Sampling ratio (n1 / n2)
alternative	Two or one sided test

Details

See https://radiant-rstats.github.io/docs/design/sample_size_comp.html for an example in Radiant

Value

A list of variables defined in `sample_size_comp` as an object of class `sample_size_comp`

See Also

[summary.sample_size_comp](#) to summarize results

Examples

```
sample_size_comp(
  type = "proportion", p1 = 0.1, p2 = 0.15,
  conf_lev = 0.95, power = 0.8
)
```

sampling

Simple random sampling

Description

Simple random sampling

Usage

```
sampling(dataset, var, sample_size, seed = NA, data_filter = "")
```

Arguments

<code>dataset</code>	Dataset to sample from
<code>var</code>	The variable to sample
<code>sample_size</code>	Number of units to select
<code>seed</code>	Random seed to use as the starting point
<code>data_filter</code>	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See <https://radiant-rstats.github.io/docs/design/sampling.html> for an example in Radiant

Value

A list of variables defined in `sampling` as an object of class `sampling`

See Also

[summary.sampling](#) to summarize results

Examples

```
sampling(rndnames, "Names", 10)
```

summary.doe

Summary method for doe function

Description

Summary method for doe function

Usage

```
## S3 method for class 'doe'
summary(object, eff = TRUE, part = TRUE, full = TRUE,
        dec = 3, ...)
```

Arguments

<code>object</code>	Return value from doe
<code>eff</code>	If TRUE print efficiency output
<code>part</code>	If TRUE print partial factorial
<code>full</code>	If TRUE print full factorial
<code>dec</code>	Number of decimals to show
<code>...</code>	further arguments passed to or from other methods.

Details

See <https://radiant-rstats.github.io/docs/design/doe.html> for an example in Radiant

See Also

[doe](#) to calculate results

Examples

```
c("price; $10; $13; $16", "food; popcorn; gourmet; no food") %>%
  doe() %>%
  summary()
```

summary.sample_size *Summary method for the sample_size function*

Description

Summary method for the sample_size function

Usage

```
## S3 method for class 'sample_size'  
summary(object, ...)
```

Arguments

object	Return value from sample_size
...	further arguments passed to or from other methods

Details

See https://radiant-rstats.github.io/docs/design/sample_size.html for an example in Radiant

See Also

[sample_size](#) to generate the results

Examples

```
sample_size(type = "mean", err_mean = 2, sd_mean = 10) %>%  
summary()
```

summary.sample_size_comp
Summary method for the sample_size_comp function

Description

Summary method for the sample_size_comp function

Usage

```
## S3 method for class 'sample_size_comp'  
summary(object, ...)
```

Arguments

object Return value from [sample_size_comp](#)
 ... further arguments passed to or from other methods

Details

See https://radiant-rstats.github.io/docs/design/sample_size_comp.html for an example in Radiant

See Also

[sample_size_comp](#) to generate the results

Examples

```
sample_size_comp(
  type = "proportion", p1 = 0.1, p2 = 0.15,
  conf_lev = 0.95, power = 0.8
) %>% summary()
```

summary.sampling *Summary method for the sampling function*

Description

Summary method for the sampling function

Usage

```
## S3 method for class 'sampling'
summary(object, prn = FALSE, dec = 3, ...)
```

Arguments

object Return value from [sampling](#)
 prn Print full sampling frame. Default is FALSE
 dec Number of decimals to show
 ... further arguments passed to or from other methods

Details

See <https://radiant-rstats.github.io/docs/design/sampling.html> for an example in Radiant

See Also

[sampling](#) to generate the results

Examples

```
set.seed(1234)
sampling(rndnames, "Names", 10) %>% summary()
```

Index

*Topic **datasets**

- [rndnames](#), [6](#)
- [doe](#), [2](#), [9](#)
- [plot.sample_size_comp](#), [3](#)
- [radiant.design](#), [4](#)
- [radiant.design-package](#)
 - [\(radiant.design\)](#), [4](#)
- [radiant.design_viewer](#), [4](#)
- [radiant.design_window](#), [5](#)
- [rndnames](#), [6](#)
- [sample_size](#), [6](#), [10](#)
- [sample_size_comp](#), [3](#), [7](#), [11](#)
- [sampling](#), [8](#), [11](#), [12](#)
- [summary.doe](#), [2](#), [9](#)
- [summary.sample_size](#), [7](#), [10](#)
- [summary.sample_size_comp](#), [8](#), [10](#)
- [summary.sampling](#), [9](#), [11](#)