

Package ‘rdbnomics’

March 19, 2019

Type Package

Title Download DBnomics Data

Version 0.4.7

Description R access to hundreds of millions data series from DBnomics API
(<<https://db.nomics.world/>>).

Depends R (>= 3.1.0)

License AGPL-3

URL <https://github.com/dbnomics/rdbnomics>

BugReports <https://github.com/dbnomics/rdbnomics/issues>

Encoding UTF-8

LazyData true

Imports curl, jsonlite, data.table

RoxygenNote 6.1.1

Suggests knitr, rmarkdown, dplyr, magrittr, ggplot2, DT, testthat

VignetteBuilder knitr

NeedsCompilation no

Author Thomas Brand [aut],
Sebastien Galais [cre, ctb]

Maintainer Sebastien Galais <s915.stem@gmail.com>

Repository CRAN

Date/Publication 2019-03-19 11:00:03 UTC

R topics documented:

rdb	2
rdbnomics	4
rdb_by_api_link	4
rdb_last_updates	6
rdb_providers	8

Index	9
--------------	----------

rdb *Download DBnomics data.*

Description

rdb downloads data series from **DBnomics** using shortcuts like `ids`, `dimensions` or `mask`.

Usage

```
rdb(provider_code = NULL, dataset_code = NULL, ids = NULL,
     dimensions = NULL, mask = NULL,
     verbose = getOption("rdbnomics.verbose_warning"), ...)
```

Arguments

<code>provider_code</code>	Character string (default NULL). DBnomics code of the provider.
<code>dataset_code</code>	Character string (default NULL). DBnomics code of the dataset.
<code>ids</code>	Character string (default NULL). DBnomics code of one or several series.
<code>dimensions</code>	List or character string (single quoted) (default NULL). DBnomics code of one or several dimensions in the specified provider and dataset. If it is a named list, then the function <code>toJSON</code> (from the package jsonlite) is applied to generate the json object.
<code>mask</code>	Character string (default NULL). DBnomics code of one or several masks in the specified provider and dataset.
<code>verbose</code>	Logical (default TRUE). Show warnings of the function.
<code>...</code>	Arguments to be passed to <code>rdb_by_api_link</code> . These arguments concern connection configuration. See <code>rdb_by_api_link</code> for details.

Details

This function gives you access to hundreds of millions data series from **DBnomics API** (documentation about the API can be found [here](#)). The code of each series is given on the **DBnomics website**.

In the event that only the argument `ids` is provided (and those in the ellipsis `...`), the argument name can be dropped. The character string vector is directly passed to `ids`.

In the same way, if only `provider_code`, `dataset_code` and `mask` are provided then the arguments names can be dropped. The last character string is automatically passed to `mask`.

Value

A `data.frame` or a `data.table`.

See Also

[rdb_by_api_link](#)

Examples

```

## Not run:
## By ids
# Fetch one series from dataset 'Unemployment rate' (ZUTN) of AMECO provider :
df1 <- rdb(ids = 'AMECO/ZUTN/EA19.1.0.0.0.ZUTN')
# or when no argument names are given (provider_code -> ids)
df1 <- rdb('AMECO/ZUTN/EA19.1.0.0.0.ZUTN')

# Fetch two series from dataset 'Unemployment rate' (ZUTN) of AMECO provider :
df2 <- rdb(ids = c('AMECO/ZUTN/EA19.1.0.0.0.ZUTN', 'AMECO/ZUTN/DNK.1.0.0.0.ZUTN'))

# Fetch two series from different datasets of different providers :
df3 <- rdb(ids = c('AMECO/ZUTN/EA19.1.0.0.0.ZUTN', 'IMF/CPI/A.AT.PCPIT_IX'))

## By dimensions
# Fetch one value of one dimension from dataset 'Unemployment rate' (ZUTN) of AMECO provider :
df1 <- rdb('AMECO', 'ZUTN', dimensions = list(geo = "ea12"))
# or
df1 <- rdb('AMECO', 'ZUTN', dimensions = '{"geo": ["ea12"]}')
```

```

# Fetch two values of one dimension from dataset 'Unemployment rate' (ZUTN) of AMECO provider :
df2 <- rdb('AMECO', 'ZUTN', dimensions = list(geo = c("ea12", "dnk")))
# or
df2 <- rdb('AMECO', 'ZUTN', dimensions = '{"geo": ["ea12", "dnk"]}')
```

```

# Fetch several values of several dimensions from dataset 'Doing business' (DB) of World Bank :
dim <- list(
  country = c("DZ", "PE"),
  indicator = c("ENF.CONT.COEN.COST.ZS", "IC.REG.COST.PC.FE.ZS")
)
df3 <- rdb('WB', 'DB', dimensions = dim)
# or
dim <- paste0(
  '{"country": ["DZ", "PE"],',
  '"indicator": ["ENF.CONT.COEN.COST.ZS", "IC.REG.COST.PC.FE.ZS"]}'
)
df3 <- rdb('WB', 'DB', dimensions = dim)
```

```

## By mask
# Fetch one series from dataset 'Consumer Price Index' (CPI) of IMF :
df1 <- rdb('IMF', 'CPI', mask = 'M.DE.PCPIEC_WT')
# or when no argument names are given except provider_code and dataset_code (ids -> mask)
df1 <- rdb('IMF', 'CPI', 'M.DE.PCPIEC_WT')
```

```

# Fetch two series from dataset 'Consumer Price Index' (CPI) of IMF :
df2 <- rdb('IMF', 'CPI', mask = 'M.DE+FR.PCPIEC_WT')
```

```

# Fetch all series along one dimension from dataset 'Consumer Price Index' (CPI) of IMF :
df3 <- rdb('IMF', 'CPI', mask = 'M..PCPIEC_WT')
```

```

# Fetch series along multiple dimensions from dataset 'Consumer Price Index' (CPI) of IMF :
df4 <- rdb('IMF', 'CPI', mask = 'M..PCPIEC_IX+PCPIA_IX')

## Use a specific proxy to fetch the data
# Fetch one series from dataset 'Unemployment rate' (ZUTN) of AMECO provider :
h <- curl::new_handle(
  proxy = "<proxy>",
  proxyport = <port>,
  proxyusername = "<username>",
  proxypassword = "<password>"
)
options(rdbnomics.curl_config = h)
df1 <- rdb(ids = 'AMECO/ZUTN/EA19.1.0.0.0.ZUTN')
# or to use once
df1 <- rdb(ids = 'AMECO/ZUTN/EA19.1.0.0.0.ZUTN', curl_config = h)

## Use R default connection to avoid a proxy failure (in some cases)
# Fetch one series from dataset 'Unemployment rate' (ZUTN) of AMECO provider :
options(rdbnomics.use_readLines = TRUE)
df1 <- rdb(ids = 'AMECO/ZUTN/EA19.1.0.0.0.ZUTN')
# or to use once
df1 <- rdb(ids = 'AMECO/ZUTN/EA19.1.0.0.0.ZUTN', use_readLines = TRUE)

## End(Not run)

```

rdbnomics

Package rdbnomics

Description

DBnomics R client.

rdb_by_api_link

Download DBnomics data using API link.

Description

rdb_by_api_link downloads data series from **DBnomics**.

Usage

```

rdb_by_api_link(api_link,
  use_readLines = getOption("rdbnomics.use_readLines"),
  curl_config = getOption("rdbnomics.curl_config"))

```

Arguments

api_link	Character string. DBnomics API link of the search.
use_readLines	Logical (default FALSE). If TRUE, then the data are requested and read with the base function readLines i.e. through the default R internet connection. This can be used to get round the error Could not resolve host: api.db.nomics.world.
curl_config	Curl_handle or list (default NULL). If not NULL, it is used to configure a proxy connection. This configuration is passed to the function curl_fetch_memory of the package curl . If it is a curl_handle object then it is considered to be the argument handle of curl_fetch_memory. In the case of a list, the names of the object are the arguments names of curl_fetch_memory (except url of course). It means that curl_config = h is equivalent to curl_config = list(handle = h). For curl_fetch_memory arguments see curl_fetch . For available curl options see curl_options , names(curl_options()) and libcurl .

Details

This function gives you access to hundreds of millions data series from **DBnomics API** (documentation about the API can be found [here](#)). The API link is given on the [DBnomics website](#).

Value

A data.frame or a data.table.

See Also

[rdb](#)

Examples

```
## Not run:
# Fetch two series from different datasets of different providers :
df1 <- rdb_by_api_link(
  paste0(
    'https://api.db.nomics.world/v22/',
    'series?observations=1&series_ids=AMECO/ZUTN/EA19.1.0.0.0.ZUTN,IMF/CPI/A.AT.PCPIT_IX'
  )
)

# Fetch one series from the dataset 'Doing Business' of WB provider :
df2 <- rdb_by_api_link(
  paste0(
    'https://api.db.nomics.world/v22/series/WB/DB?dimensions=%7B%22',
    'indicator%22%3A%5B%22IC.REG.PROC.FE.NO%22%5D%7D&q=Doing%20Business',
    '&observations=1&format=json&align_periods=1&offset=0&facets=0'
  )
)

## Use a specific proxy to fetch the data
# Fetch one series from the dataset 'Doing Business' of WB provider :
```

```

h <- curl::new_handle(
  proxy = "<proxy>",
  proxyport = <port>,
  proxyusername = "<username>",
  proxypassword = "<password>"
)
options(rdbnomics.curl_config = h)
df2 <- rdb_by_api_link(
  paste0(
    'https://api.db.nomics.world/v22/series/WB/DB?dimensions=%7B%22',
    'indicator%22%3A%5B%22IC.REG.PROC.FE.NO%22%5D%7D&q=Doing%20Business',
    '&observations=1&format=json&align_periods=1&offset=0&facets=0'
  )
)
# or to use once
df2 <- rdb_by_api_link(
  paste0(
    'https://api.db.nomics.world/v22/series/WB/DB?dimensions=%7B%22',
    'indicator%22%3A%5B%22IC.REG.PROC.FE.NO%22%5D%7D&q=Doing%20Business',
    '&observations=1&format=json&align_periods=1&offset=0&facets=0'
  ),
  curl_config = h
)

## Use R default connection to avoid a proxy failure (in some cases)
# Fetch one series from the dataset 'Doing Business' of WB provider :
options(rdbnomics.use_readLines = TRUE)
df2 <- rdb_by_api_link(
  paste0(
    'https://api.db.nomics.world/v22/series/WB/DB?dimensions=%7B%22',
    'indicator%22%3A%5B%22IC.REG.PROC.FE.NO%22%5D%7D&q=Doing%20Business',
    '&observations=1&format=json&align_periods=1&offset=0&facets=0'
  )
)
# or to use once
df2 <- rdb_by_api_link(
  paste0(
    'https://api.db.nomics.world/v22/series/WB/DB?dimensions=%7B%22',
    'indicator%22%3A%5B%22IC.REG.PROC.FE.NO%22%5D%7D&q=Doing%20Business',
    '&observations=1&format=json&align_periods=1&offset=0&facets=0'
  ),
  use_readLines = TRUE
)

## End(Not run)

```

Description

rdb_last_updates downloads informations about the last updates from [DBnomics](#).

Usage

```
rdb_last_updates(all = FALSE,  
  use_readLines = getOption("rdbnomics.use_readLines"),  
  curl_config = getOption("rdbnomics.curl_config"))
```

Arguments

all	Logical (default FALSE). If TRUE, then the full dataset of the last updates is retrieved.
use_readLines	Logical (default FALSE). If TRUE, then the data are requested and read with the base function readLines i.e. through the default R internet connection. This can be used to get round the error Could not resolve host: api.db.nomics.world.
curl_config	Curl_handle or list (default NULL). If not NULL, it is used to configure a proxy connection. This configuration is passed to the function curl_fetch_memory of the package curl . If it is a curl_handle object then it is considered to be the argument handle of curl_fetch_memory. In the case of a list, the names of the object are the arguments names of curl_fetch_memory (except url of course). It means that curl_config = h is equivalent to curl_config = list(handle = h). For curl_fetch_memory arguments see curl_fetch . For available curl options see curl_options , names(curl_options()) and libcurl .

Details

By default, the function returns a data.frame (or a data.table) containing the last 100 updates from [DBnomics](#) with additional informations.

Value

A data.frame or a data.table.

See Also

[rdb_providers](#)

Examples

```
## Not run:  
rdb_last_updates()  
  
rdb_last_updates(all = TRUE)  
  
## End(Not run)
```

rdb_providers	<i>Download list of DBnomics providers.</i>
---------------	---

Description

rdb_providers downloads the list of providers from **DBnomics**.

Usage

```
rdb_providers(code = FALSE,
              use_readLines = getOption("rdbnomics.use_readLines"),
              curl_config = getOption("rdbnomics.curl_config"))
```

Arguments

code	Logical (default FALSE). If TRUE, then only the providers are returned in a vector.
use_readLines	Logical (default FALSE). If TRUE, then the data are requested and read with the base function readLines i.e. through the default R internet connection. This can be used to get round the error Could not resolve host: api.db.nomics.world.
curl_config	Curl_handle or list (default NULL). If not NULL, it is used to configure a proxy connection. This configuration is passed to the function curl_fetch_memory of the package curl . If it is a curl_handle object then it is considered to be the argument handle of curl_fetch_memory. In the case of a list, the names of the object are the arguments names of curl_fetch_memory (except url of course). It means that curl_config = h is equivalent to curl_config = list(handle = h). For curl_fetch_memory arguments see curl_fetch . For available curl options see curl_options , names(curl_options()) and libcurl .

Details

By default, the function returns a data.frame (or a data.table) containing the list of providers from **DBnomics** with additional informations such as the region, the website, etc.

Value

A data.frame, a data.table or a vector.

See Also

[rdb_last_updates](#)

Examples

```
## Not run:
rdb_providers()

rdb_providers(code = TRUE)

## End(Not run)
```


Index

`curl_fetch`, [5](#), [7](#), [8](#)
`curl_options`, [5](#), [7](#), [8](#)

`rdb`, [2](#), [5](#)
`rdb_by_api_link`, [2](#), [4](#)
`rdb_last_updates`, [6](#), [8](#)
`rdb_providers`, [7](#), [8](#)
`rdbnomics`, [4](#)
`rdbnomics-package (rdbnomics)`, [4](#)