

Package ‘stream’

June 2, 2018

Version 1.3-0

Date 2018-05-31

Title Infrastructure for Data Stream Mining

Description A framework for data stream modeling and associated data mining tasks such as clustering and classification. The development of this package was supported in part by NSF IIS-0948893 and NIH R21HG005912.

Depends R (>= 2.13.0), methods, proxy (>= 0.4-7)

Imports animation, clue, cluster, clusterGeneration, dbscan (>= 1.0-0), fpc, graphics, grDevices, MASS, mlbench, Rcpp (>= 0.11.4), stats, utils

Suggests DBI, rJava, RSQLite, testthat

URL <http://lyle.smu.edu/IDA/TRACDS/>

BugReports <https://github.com/mhahsler/stream>

LinkingTo Rcpp, BH

License GPL-3

RoxygenNote 6.0.1

NeedsCompilation yes

Author Michael Hahsler [aut, cre, cph],
Matthew Bolanos [aut, cph],
John Forrest [aut, cph],
Matthias Carnein [ctb],
Dennis Assenmacher [ctb]

Maintainer Michael Hahsler <mhahsler@lyle.smu.edu>

Repository CRAN

Date/Publication 2018-06-02 05:07:55 UTC

R topics documented:

animation	3
DSC	4

DSCclassify	5
DSC_BICO	5
DSC_BIRCH	6
DSC_DBSCAN	7
DSC_DBSTREAM	9
DSC_DStream	11
DSC_Hierarchical	14
DSC_Kmeans	16
DSC_Marco	17
DSC_Mirco	18
DSC_Reachability	18
DSC_Sample	20
DSC_Static	21
DSC_TwoStage	23
DSC_Window	24
DSD	25
DSD_BarsAndGaussians	26
DSD_Benchmark	27
DSD_Cubes	28
DSD_Gaussians	29
DSD_Memory	30
DSD_MG	32
DSD_mlbenchData	34
DSD_mlbenchGenerator	35
DSD_ReadCSV	36
DSD_ReadDB	38
DSD_ScaleStream	39
DSD_Target	40
DSD_UniformNoise	41
DSFP	42
DSO	42
DSO_Sample	43
DSO_Window	44
DST	45
evaluate	46
get_assignment	50
get_centers	51
get_copy	52
get_points	53
get_weights	54
MGC	55
microToMacro	58
nclusters	59
plot	60
prune_clusters	61
recluster	62
reset_stream	63
save	64

update	65
write_stream	66

Index	68
--------------	-----------

animation	<i>Animates the plotting of a DSD and the clustering process</i>
-----------	--

Description

Generates an animation of a data stream or a data stream clustering.

Usage

```
animate_data(dsd, horizon = 100, n = 1000, wait = .1, plot.args = NULL, ...)
animate_cluster(dsc, dsd, measure = NULL, horizon = 100, n = 1000,
  type=c("auto", "micro", "macro"), assign="micro",
  assignmentMethod=c("auto", "model", "nn"),
  noise = c("class", "exclude"),
  wait=.1, plot.args = NULL, ...)
```

Arguments

dsd	a DSD object
dsc	a DSC object
horizon	the number of points displayed at once/used for evaluation.
n	the number of points to be plotted
measure	the evaluation measure that should be graphed below the animation
type	evaluate "micro" or "macro"-clusters? "auto" chooses micro if dsc is of class DSC_micro and no macro is given. Otherwise macro is used.
assign	assign new points to the closest "micro" or "macro"-cluster to calculate the evaluation measure.
assignmentMethod	how to assign data points to micro-clusters. Options are "model" and "nn" (nearest neighbor). "auto" uses model if available and nn otherwise.
noise	how to handle noise for calculating the evaluation measure (as a separate class or excluded).
wait	the time interval between each frame
plot.args	a list with plotting parameters for the clusters.
...	extra arguments are added to plot.args.

Details

Animations are recorded using the library animation and can be replayed (which gives a smoother experience since there is no more computation done) and saved in various formats (see Examples section below).

Author(s)

Michael Hahsler

See Also

[evaluate_cluster](#) for stream evaluation without animation. See [ani.replay](#) for replaying and saving animations.

Examples

```
## Not run:
stream <- DSD_Benchmark(1)
animate_data(stream, horizon=100, n=5000, xlim=c(0,1), ylim=c(0,1))

### animations can be replayed with the animation package
library(animation)
animation::ani.options(interval=.1) ## change speed
ani.replay()

### animations can also be saved as HTML, animated gifs, etc.
saveHTML(ani.replay())

### animate the clustering process with evaluation
### Note: we choose to exclude noise points from the evaluation
###       measure calculation, even if the algorithm would assign
###       them to a cluster.
reset_stream(stream)
dbstream <- DSC_DBSTREAM(r=.04, lambda=.1, gaptime=100, Cm=3,
  shared_density=TRUE, alpha=.2)

animate_cluster(dbstream, stream, horizon=100, n=5000,
  measure="crand", type="macro", assign="micro", noise = "exclude",
  plot.args = list(xlim=c(0,1), ylim=c(0,1), shared = TRUE))

## End(Not run)
```

DSC

Data Stream Clusterer Base Classes

Description

Abstract base classes for all DSC (Data Stream Clusterer) and DSC_R classes.

Details

The DSC and DSC_R classes cannot be instantiated (calling `DSC()` or `DSC_R()` produces errors), but they serve as a base class from which other DSC classes inherit.

Class DSC provides several generic functions that can operate on all DSC subclasses: `print()`, `plot()`, `nclusters()` to get the current number of clusters, `get_centers()` to get the cluster

centers, and `get_weights()` to get the cluster weights (if implemented). `get_centers()` and `get_weights()` are typically overwritten by subclasses of DSC. DSC_R provides these functions for R-based DSC implementations.

Since DSC objects often contain external pointers, regular saving and reading operations will fail. Use `saveDSC()` and `readDSC()` which will serialize the objects first appropriately.

Author(s)

Michael Hahsler

See Also

[animate_cluster](#), [cluster](#), [evaluate](#), [get_assignment](#), [get_centers](#), [get_weights](#), [get_copy](#), [microToMacro](#), [nclusters](#), [plot](#), [prune_clusters](#), [recluster](#), [readDSC](#), [saveDSC](#)

DSClassify

Abstract Class for Data Stream Classifiers

Description

Abstract class for data stream classifiers. Currently, **stream** does not implement classification algorithms.

Author(s)

Michael Hahsler

See Also

[DST](#)

DSC_BICO

BICO - Fast computation of k-means coresets in a data stream

Description

BICO maintains a tree which is inspired by the clustering tree of BIRCH, a SIGMOD Test of Time award-winning clustering algorithm. Each node in the tree represents a subset of these points. Instead of storing all points as individual objects, only the number of points, the sum and the squared sum of the subset's points are stored as key features of each subset. Points are inserted into exactly one node.

Usage

```
DSC_BICO(k = 5, space = 10, p = 10, iterations = 10)
```

Arguments

k	number of centres
space	coreset size
p	number of random projections used for nearest neighbour search in first level
iterations	number of repetitions for the kmeans++ procedure in the offline component

Details

In this implementation, the nearest neighbour search on the first level of the tree is sped up by projecting all points to random 1-d subspaces. The first estimation of the optimal clustering cost is computed in a buffer phase at the beginning of the algorithm.

This implementation interfaces the original C++ implementation available here: <http://ls2-www.cs.tu-dortmund.de/grav/de/bico>. For micro-clustering, the algorithm computes the coreset of the stream. Reclustering is performed by using the kmeans++ algorithm on the coreset.

Author(s)

R-Interface: Matthias Carnein (<Matthias.Carnein@uni-muenster.de>), Dennis Assenmacher.

C-Implementation: Hendrik Fichtenberger, Marc Gille, Melanie Schmidt, Chris Schwiegelshohn, Christian Sohler.

References

Hendrik Fichtenberger, Marc Gille, Melanie Schmidt, Chris Schwiegelshohn, Christian Sohler: BICO: BIRCH Meets Coresets for k-Means Clustering. *ESA 2013*: 481-492.

Examples

```
stream <- DSD_Gaussians(k = 3, d = 2)

BICO <- DSC_BICO(k = 3, p = 10, space = 100, iterations = 10)
update(BICO, stream, n = 500)

plot(BICO, stream, type = "both")
```

DSC_BIRCH

Balanced Iterative Reducing Clustering using Hierarchies

Description

BIRCH builds a balanced-tree of Clustering Features (CFs) to summarize the stream. A CF is a tuple (n, LS, SS) which represents a cluster by storing the number of elements (n), their linear sum (LS) and their squared sum (SS). Each new observation descends the tree by following its closest CF until a leaf node is reached. It is either merged into its closest leaf-CF or inserted as a new one. All leaf-CFs form the micro-clusters. Rebuilding the tree is realized by inserting all leaf-CF nodes into a new tree structure with an increased threshold.

Usage

```
DSC_BIRCH(treshold, branching, maxLeaf, maxMem = 0, outlierThreshold = 0.25)
```

Arguments

treshold	treshold used to check whether a new datapoint can be absorbed or not
branching	branching factor (maximum amount of child nodes for a nonleaf node) of the CF-Tree.
maxLeaf	maximum number of entries within a leaf node
outlierThreshold	threshold for identifying outliers when rebuilding the CF-Tree
maxMem	memory limitation for the whole CFTree in bytes. Default is 0, indicating no memory restriction.

Author(s)

Dennis Assenmacher (<Dennis.Assenmacher@uni-muenster.de>), Matthias Carnein (<Matthias.Carnein@uni-muenster.de>)

References

Zhang T, Ramakrishnan R and Livny M (1996), "BIRCH: An Efficient Data Clustering Method for Very Large Databases", *In Proceedings of the 1996 ACM SIGMOD International Conference on Management of Data*. Montreal, Quebec, Canada , pp. 103-114. ACM.

Zhang T, Ramakrishnan R and Livny M (1997), "BIRCH: A new data clustering algorithm and its applications", *Data Mining and Knowledge Discovery*. Vol. 1(2), pp. 141-182.

Examples

```
stream <- DSD_Gaussians(k = 3, d = 2)

BIRCH <- DSC_BIRCH(treshold = .1, branching = 8, maxLeaf = 20)
update(BIRCH, stream, n = 500)

plot(BIRCH, stream)
```

DSC_DBSCAN

DBSCAN Macro-clusterer

Description

Implements the DBSCAN algorithm for reclustering micro-clusterings.

Usage

```
DSC_DBSCAN(eps, MinPts = 5, weighted = TRUE, description=NULL)
```

Arguments

eps	radius of the eps-neighborhood.
MinPts	minimum number of points required in the eps-neighborhood.
weighted	logical indicating if a weighted version of DBSCAN should be used.
description	optional character string to describe the clustering method.

Details

DBSCAN is a weighted extended version of the implementation in **fpc** where each micro-cluster center considered a pseudo point. For weighting we use in the MinPts comparison the sum of weights of the micro-cluster instead of the number.

DBSCAN first finds core points based on the number of other points in its eps-neighborhood. Then core points are joined into clusters using reachability (overlapping eps-neighborhoods).

Note that this clustering cannot be updated iteratively and every time it is used for (re)clustering, the old clustering is deleted.

Value

An object of class DSC_DBSCAN (a subclass of DSC, DSC_R, DSC_Macro).

Author(s)

Michael Hahsler

References

Martin Ester, Hans-Peter Kriegel, Joerg Sander, Xiaowei Xu (1996). A density-based algorithm for discovering clusters in large spatial databases with noise. In Evangelos Simoudis, Jiawei Han, Usama M. Fayyad. *Proceedings of the Second International Conference on Knowledge Discovery and Data Mining (KDD-96)*. AAAI Press. pp. 226-231.

See Also

[DSC](#), [DSC_Macro](#)

Examples

```
# 3 clusters with 5% noise
stream <- DSD_Gaussians(k=3, d=2, noise=0.05)

# Use DBSCAN to recluster micro clusters (a sample)
sample <- DSC_Sample(k=100)
update(sample, stream, 500)

dbscan <- DSC_DBSCAN(eps = .05)
recluster(dbscan, sample)
plot(dbscan, stream, type="both")

# For comparison we can cluster some data with DBSCAN directly
```



```
# Note: DBSCAN is not suitable for data streams since it passes over the data
# several times.
dbscan <- DSC_DBSCAN(eps = .05)
update(dbscan, stream, 500)
plot(dbscan, stream)
```

DSC_DBSTREAM

DBSTREAM clustering algorithm

Description

Implements a simple density-based stream clustering algorithm that assigns data points to micro-clusters with a given radius and implements shared-density-based reclustering.

Usage

```
DSC_DBSTREAM(r, lambda = 0.001, gaptime = 1000L,
  Cm = 3, metric = "Euclidean", shared_density = FALSE,
  alpha=0.1, k=0, minweight = 0)
get_shared_density(x, use_alpha = TRUE)
change_alpha(x, alpha)
get_cluster_assignments(x)
```

Arguments

<code>r</code>	The radius of micro-clusters.
<code>lambda</code>	The lambda used in the fading function.
<code>gaptime</code>	weak micro-clusters (and weak shared density entries) are removed every <code>gaptime</code> points.
<code>Cm</code>	minimum weight for a micro-cluster.
<code>metric</code>	metric used to calculate distances.
<code>shared_density</code>	Record shared density information. If set to TRUE then shared density is used for reclustering, otherwise reachability is used (overlapping clusters with less than $r * (1 - \alpha)$ distance are clustered together).
<code>k</code>	The number of macro clusters to be returned if macro is true.
<code>alpha</code>	For shared density: The minimum proportion of shared points between to clusters to warrant combining them (a suitable value for 2D data is .3). For reachability clustering it is a distance factor.
<code>minweight</code>	The proportion of the total weight a macro-cluster needs to have not to be noise (between 0 and 1).
<code>x</code>	A DSC_DBSTREAM object to get the shared density information from.
<code>use_alpha</code>	only return shared density if it exceeds alpha.

Details

The DBSTREAM algorithm checks for each new data point in the incoming stream, if it is below the threshold value of dissimilarity value of any existing micro-clusters, and if so, merges the point with the micro-cluster. Otherwise, a new micro-cluster is created to accommodate the new data point.

Although DSC_DBSTREAM is a micro clustering algorithm, macro clusters and weights are available.

`get_cluster_assignments()` can be used to extract the MC assignment for each data point clustered during the last update operation (note: update needs to be called with `assignments = TRUE` and the block size needs to be large enough). The function returns the MC index (in the current set of MCs obtained with, e.g., `get_centers()`) and as an attribute the permanent MC ids.

`plot()` for DSC_DBSTREAM has two extra logical parameters called `assignment` and `shared_density` which show the assignment area and the shared density graph, respectively.

Value

An object of class DSC_DBSTREAM (subclass of DSC, DSC_R, DSC_Micro).

Author(s)

Michael Hahsler and Matthew Bolanos

References

Michael Hahsler and Matthew Bolanos. Clustering data streams based on shared density between micro-clusters. *IEEE Transactions on Knowledge and Data Engineering*, 28(6):1449–1461, June 2016

See Also

[DSC](#), [DSC_Micro](#)

Examples

```
set.seed(0)
stream <- DSD_Gaussians(k = 3, noise = 0.05)

# create clusterer with r = 0.05
dbstream <- DSC_DBSTREAM(r = .05)
update(dbstream, stream, 1000)
dbstream

# check micro-clusters
nclusters(dbstream)
head(get_centers(dbstream))
plot(dbstream, stream)

# plot macro-clusters
plot(dbstream, stream, type = "both")
```

```

# plot micro-clusters with assignment area
plot(dbstream, stream, type = "both", assignment = TRUE)

# DBSTREAM with shared density
dbstream <- DSC_DBSTREAM(r = .05, shared_density = TRUE, Cm=5)
update(dbstream, stream, 1000)
dbstream
plot(dbstream, stream, type = "both")
# plot the shared density graph (several options)
plot(dbstream, stream, type = "both", shared_density = TRUE)
plot(dbstream, stream, type = "micro", shared_density = TRUE)
plot(dbstream, stream, type = "micro", shared_density = TRUE, assignment = TRUE)
plot(dbstream, stream, type = "none", shared_density = TRUE, assignment = TRUE)

# see how micro and macro-clusters relate
# each microcluster has an entry with the macro-cluster id
# Note: unassigned micro-clusters (noise) have an NA
microToMacro(dbstream)

# do some evaluation
evaluate(dbstream, stream, measure="purity")
evaluate(dbstream, stream, measure="cRand", type="macro")

# use DBSTREAM for conventional clustering (with assignments = TRUE so we can
# later retrieve the cluster assignments for each point)
data("iris")
dbstream <- DSC_DBSTREAM(r = 1)
update(dbstream, iris[,-5], assignments = TRUE)
dbstream

cl <- get_cluster_assignments(dbstream)
cl

# micro-clusters
plot(iris[,-5], col = cl, pch = cl)

# macro-clusters
plot(iris[,-5], col = microToMacro(dbstream, cl))

```

Description

Implements the D-Stream data stream clustering algorithm.

Usage

```
DSC_DStream(gridsize, lambda = 1e-3, gaptime=1000L,
            Cm=3, Cl=.8, attraction=FALSE, epsilon=.3, Cm2=Cm, k=NULL, N = 0)
get_attraction(x, relative=FALSE, grid_type = "dense", dist=FALSE)
```

Arguments

gridsize	Size of grid cells.
lambda	Fading constant used function to calculate the decay factor $2^{-lambda}$. (Note: in the paper the authors use lambda to denote the decay factor and not the fading constant!)
gaptime	sporadic grids are removed every gaptime number of points.
Cm	density threshold used to detect dense grids as a proportion of the average expected density ($Cm > 1$). The average density is given by the total weight of the clustering over N , the number of grid cells.
Cl	density threshold to detect sporadic grids ($0 > Cl > Cm$). Transitional grids have a density between Cl and Cm.
attraction	compute and store information about the attraction between adjacent grids. If TRUE then attraction is used to create macro-clusters, otherwise macro-clusters are created by merging adjacent dense grids.
epsilon	overlap parameter for attraction as a proportion of gridsize.
Cm2	threshold on attraction to join two dense grid cells (as a proportion on the average expected attraction). In the original algorithm Cm2 is equal to Cm.
k	alternative to Cm2 (not in the original algorithm). Create k clusters based on attraction. In case of more than k unconnected components, closer groups of MCs are joined.
N	Fix the number of grid cells used for the calculation of the density thresholds with Cl and Cm. If N is not given (0) then the algorithm tries to determine N from the data. Note that this means that N potentially increases over time and outliers might produce an extremely large value which will lead to a sudden creation of too many dense micro-clusters. The original paper assumed that N is known a priori.
x	DSC_DStream object to get attraction values from.
relative	calculates relative attraction (normalized by the cluster weight).
grid_type	the attraction between what grid types should be returned?
dist	make attraction symmetric and transform into a distance.

Details

D-Stream creates an equally spaced grid and estimates the density in each grid cell using the count of points falling in the cells. Grid cells are classified based on density into dense, transitional and sporadic cells. The density is faded after every new point by a factor of $2^{-lambda}$. Every gaptime number of points sporadic grid cells are removed.

For reclustering D-Stream (2007 version) merges adjacent dense grids to form macro-clusters and then assigns adjacent transitional grids to macro-clusters. This behavior is implemented as `attraction=FALSE`.

The 2009 version of the algorithm adds the concept of attraction between grids cells. If attraction=TRUE is used then the algorithm produces macro-clusters based on attraction between dense adjacent grids (uses Cm2 which in the original algorithm is equal to Cm).

For many functions (e.g., get_centers(), plot()), D-Stream adds a parameter grid_type with possible values of "dense", "transitional", "sparse", "all" and "used". This only returns the selected type of grid cells. "used" includes dense and adjacent transitional cells which are used in D-Stream for reclustering.

For plot D-Stream also provides extra parameters "grid" and "grid_type" to show micro-clusters as grid cells (density represented by gray values).

Note that DSC_DStream can at this point not be saved to disk using save() or saveRDS(). This functionality will be added later!

Value

An object of class DSC_DStream (subclass of DSC, DSC_R, DSC_Micro).

Author(s)

Michael Hahsler

References

Yixin Chen and Li Tu. 2007. Density-based clustering for real-time stream data. In *Proceedings of the 13th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD '07)*. ACM, New York, NY, USA, 133-142.

Li Tu and Yixin Chen. 2009. Stream data clustering based on grid density and attraction. *ACM Transactions on Knowledge Discovery from Data*, 3(3), Article 12 (July 2009), 27 pages.

See Also

[DSC](#), [DSC_Micro](#)

Examples

```
stream <- DSD_BarsAndGaussians(noise=.05)
plot(stream)

# we set Cm=.8 to pick up the lower density clusters
dstream1 <- DSC_DStream(gridsize=1, Cm=1.5)
update(dstream1, stream, 1000)
dstream1

# micro-clusters (these are "used" grid cells)
nclusters(dstream1)
head(get_centers(dstream1))

# plot (DStream provides additional grid visualization)
plot(dstream1, stream)
plot(dstream1, stream, grid=TRUE)
```

```

# look only at dense grids
nclusters(dstream1, grid_type="dense")
plot(dstream1, stream, grid=TRUE, grid_type="dense")

# look at transitional and sparse cells
plot(dstream1, stream, grid=TRUE, grid_type="transitional")
plot(dstream1, stream, grid=TRUE, grid_type="sparse")

### Macro-clusters
# standard D-Stream uses reachability
nclusters(dstream1, type="macro")
get_centers(dstream1, type="macro")
plot(dstream1, stream, type="both", grid=TRUE)
evaluate(dstream1, stream, measure="crand", type="macro")

# use attraction for reclustering
dstream2 <- DSC_DStream(gridsize=1, attraction=TRUE, Cm=1.5)
update(dstream2, stream, 1000)
dstream2

plot(dstream2, stream, type="both", grid=TRUE)
evaluate(dstream2, stream, measure="crand", type="macro")

```

DSC_Hierarchical

Hierarchical Micro-Cluster Reclusterer

Description

Implementation of hierarchical clustering to recluster a set of micro-clusters.

Usage

```
DSC_Hierarchical(k=NULL, h=NULL, method = "complete", min_weight=NULL,
description=NULL)
```

Arguments

k	The number of desired clusters.
h	Height where to cut the dendrogram.
method	the agglomeration method to be used. This should be (an unambiguous abbreviation of) one of "ward", "single", "complete", "average", "mcquitty", "median" or "centroid".
min_weight	micro-clusters with a weight less than this will be ignored for reclustering.
description	optional character string to describe the clustering method.

Details

Please refer to `hclust` for more details on the behavior of the algorithm.

Note that this clustering cannot be updated iteratively and every time it is used for (re)clustering, the old clustering is deleted.

Value

A list of class `DSC`, `DSC_R`, `DSC_Macro`, and `DSC_Hierarchical`. The list contains the following items:

<code>description</code>	The name of the algorithm in the DSC object.
<code>Robj</code>	The underlying R object.

Author(s)

Michael Hahsler

See Also

[DSC](#), [DSC_Macro](#)

Examples

```
# Cassini dataset
stream <- DSD_mlbenchGenerator("cassini")

# Use hierarchical clustering to recluster micro-clusters
dbstream <- DSC_DBSTREAM(r=.05)
update(dbstream, stream, 500)

# reclustering using single-link and specifying k
hc <- DSC_Hierarchical(k=3, method="single")
recluster(hc, dbstream)
hc
plot(hc, stream, type="both")

# reclustering by specifying height
hc <- DSC_Hierarchical(h=.2, method="single")
recluster(hc, dbstream)
hc
plot(hc, stream, type="both")

# For comparison we use hierarchical clustering directly on the data
# Note: hierarchical clustering is not a data stream clustering algorithm!
hc <- DSC_Hierarchical(k=3, method="single")
update(hc, stream, 500)
plot(hc, stream)
```

DSC_Kmeans

Kmeans Macro-clusterer

Description

Class implements the k-means algorithm for reclustering a set of micro-clusters.

Usage

```
DSC_Kmeans(k, weighted = TRUE, iter.max = 10, nstart = 1,  
algorithm = c("Hartigan-Wong", "Lloyd", "Forgy", "MacQueen"),  
min_weight = NULL, description=NULL)
```

Arguments

k	either the number of clusters, say k, or a set of initial (distinct) cluster centers. If a number, a random set of (distinct) rows in x is chosen as the initial centers.
weighted	use a weighted k-means (algorithm is ignored).
iter.max	the maximum number of iterations allowed.
nstart	if centers is a number, how many random sets should be chosen?
algorithm	character: may be abbreviated.
min_weight	micro-clusters with a weight less than this will be ignored for reclustering.
description	optional character string to describe the clustering method.

Details

Please refer to function `kmeans` in **stats** for more details on the algorithm.

Note that this clustering cannot be updated iteratively and every time it is used for (re)clustering, the old clustering is deleted.

Value

An object of class `DSC_Kmeans` (subclass of `DSC`, `DSC_R`, `DSC_Macro`)

Author(s)

Michael Hahsler

See Also

[DSC](#), [DSC_Macro](#)

Examples

```
stream <- DSD_Gaussians(k=3, noise=0)

# create micro-clusters via sampling
sample <- DSC_Sample(k=20)
update(sample, stream, 500)
sample

# recluster micro-clusters
kmeans <- DSC_Kmeans(k=3)
recluster(kmeans, sample)
plot(kmeans, stream, type="both")

# For comparison we use k-means directly to cluster data
# Note: k-means is not a data stream clustering algorithm
kmeans <- DSC_Kmeans(k=3)
update(kmeans, stream, 500)
plot(kmeans, stream)
```

DSC_Marco

Abstract Class for Macro Clusterers

Description

Abstract class for all DSC Macro Clusterers.

Details

DSC_Macro cannot be instantiated. Calling DSC_Macro() results in an error.

Author(s)

Michael Hahsler

See Also

[DSC](#)

DSC_Mirco

Abstract Class for Micro Clusterers

Description

Abstract class for all DSC Micro Clusterers.

Details

DSC_Mirco cannot be instantiated. Calling DSC_Mirco() results in an error.

Author(s)

Michael Hahsler

See Also

[DSC](#)

DSC_Reachability

Reachability Micro-Cluster Reclusterer

Description

Implementation of reachability clustering (based on DBSCAN's concept of reachability) to recluster a set of micro-clusters. Two micro-clusters are directly reachable if they are within each other's epsilon-neighborhood (i.e., the distance between the centers is less than epsilon). Two micro-clusters are reachable if they are connected by a chain of pairwise directly reachable micro-clusters. All mutually reachable micro-clusters are put in the same cluster.

Usage

```
DSC_Reachability(epsilon, min_weight=NULL, description=NULL)
```

Arguments

epsilon	radius of the epsilon-neighborhood.
min_weight	micro-clusters with a weight less than this will be ignored for reclusterer.
description	optional character string to describe the clustering method.

Details

Reachability uses internally DSC_Hierarchical with single link.

Note that this clustering cannot be updated iteratively and every time it is used for (re)clustering, the old clustering is deleted.

Value

An object of class DSC_Reachability. The object contains the following items:

description	The name of the algorithm in the DSC object.
RObj	The underlying R object.

Author(s)

Michael Hahsler

References

Martin Ester, Hans-Peter Kriegel, Joerg Sander, Xiaowei Xu (1996). A density-based algorithm for discovering clusters in large spatial databases with noise. In Evangelos Simoudis, Jiawei Han, Usama M. Fayyad. *Proceedings of the Second International Conference on Knowledge Discovery and Data Mining (KDD-96)*. AAAI Press. pp. 226-231.

See Also

[DSC](#), [DSC_Macro](#)

Examples

```
stream <- DSD_mlbenchGenerator("cassini")

# Recluster micro-clusters from DSC_Sample with reachability
sample <- DSC_Sample(k = 200)
update(sample, stream, 1000)

reach <- DSC_Reachability(epsilon=0.3)
recluster(reach, sample)

plot(reach, stream, type="both")

# For comparison we using reachability clustering directly on data points
# Note: reachability is not a data stream clustering algorithm taking O(n^2)
# time and space.
reach <- DSC_Reachability(epsilon=0.2)
update(reach, stream, 500)
reach
plot(reach, stream)
```

`DSC_Sample`*Extract a Fixed-size Sample from a Data Stream*

Description

Extracts a sample from a data stream using Reservoir Sampling. The sample is stored as a set of micro-clusters to be compatible with other data DSC stream clustering algorithms.

Usage

```
DSC_Sample(k = 100, biased = FALSE)
```

Arguments

<code>k</code>	the number of points to be sampled from the stream.
<code>biased</code>	if FALSE then a regular (unbiased) reservoir sampling is used. If true then the sample is biased towards keeping more recent data points (see Details section).

Details

If `biased=FALSE` then the reservoir sampling algorithm by McLeod and Bellhouse (1983) is used. This sampling makes sure that each data point has the same chance to be sampled. All sampled points will have a weight of 1. Note that this might not be ideal for an evolving stream since very old data points have the same chance to be in the sample as newer points.

If `bias=TRUE` then sampling prefers newer points using the modified reservoir sampling algorithm 2.1 by Aggarwal (2006). New points are always added. They replace a random point in the reservoir with a probability of reservoir size over k . This is an exponential bias function of $2^{-\lambda}$ with $\lambda = 1/k$.

Value

An object of class `DSC_Sample` (subclass of `DSC`, `DSC_R`, `DSC_Micro`).

Author(s)

Michael Hahsler

References

- Vitter, J. S. (1985): Random sampling with a reservoir. *ACM Transactions on Mathematical Software*, 11(1), 37-57.
- McLeod, A.I., Bellhouse, D.R. (1983): A Convenient Algorithm for Drawing a Simple Random Sample. *Applied Statistics*, 32(2), 182-184.
- Aggarwal C. (2006) On Biased Reservoir Sampling in the Presence of Stream Evolution. *International Conference on Very Large Databases (VLDB'06)*. 607-618.

See Also

[DSC](#), [DSC_Micro](#)

Examples

```
stream <- DSD_Gaussians(k=3, noise=0.05)

sample <- DSC_Sample(k=20)
update(sample, stream, 500)
sample

# plot micro-clusters
plot(sample, stream)

# reclustering
kmeans <- DSC_Kmeans(3)
recluster(kmeans, sample)
plot(kmeans, stream, type="both")

# sample from an evolving stream
stream <- DSD_Benchmark(1)
sample <- DSC_Sample(k=20)
update(sample, stream, 1000)
plot(sample, stream)
# Note: the clusters move from left to right and the sample keeps many
# outdated points

# use a biased sample to keep more recent data points
stream <- DSD_Benchmark(1)
sample <- DSC_Sample(k=20, biased=TRUE)
update(sample, stream, 1000)
plot(sample, stream)
```

DSC_Static

Create as Static Copy of a Clustering

Description

This representation cannot perform clustering anymore, but it also does not need the supporting data structures. It only stores the cluster centers and weights.

Usage

```
DSC_Static(x, type=c("auto", "micro", "macro"), k_largest=NULL, min_weight=NULL)
```

Arguments

x	The clustering (a DSD object) to copy.
type	which clustering to copy.
k_largest	only copy the k largest (highest weight) clusters.
min_weight	only copy clusters with a weight larger or equal to min_weight.

Value

An object of class DSC_Static (sub class of DSC, DSC_R). The list also contains either DSC_Micro or DSC_Macro depending on what type of clustering was copied.

Author(s)

Michael Hahsler

See Also

[DSC](#), [DSC_Micro](#), [DSC_Macro](#)

Examples

```
stream <- DSD_Gaussians(k=3, noise=0.05)

dstream <- DSC_DStream(gridsize=0.05)
update(dstream, stream, 500)
dstream
plot(dstream, stream)

# create a static copy of the clustering
static <- DSC_Static(dstream)
static
plot(static, stream)

# copy only the 5 largest clusters
static2 <- DSC_Static(dstream, k_largest=5)
static2
plot(static2, stream)

# copy all clusters with a weight of at least .3
static3 <- DSC_Static(dstream, min_weight=.3)
static3
plot(static3, stream)
```

DSC_TwoStage	<i>TwoStage Clustering Process</i>
--------------	------------------------------------

Description

Combines a micro and a macro clustering algorithm into a single process.

Usage

```
DSC_TwoStage(micro, macro)
```

Arguments

micro	Clustering algorithm for online stage (DSC_micro)
macro	Clustering algorithm for offline stage (DSC_macro)

Details

update() runs the micro-clustering stage and if centers/weights are requested the reclustering is automatically performed.

Value

An object of class DSC_TwoStage (subclass of DSC, DSC_Macro).

Author(s)

Michael Hahsler

See Also

[DSC](#), [DSC_Macro](#)

Examples

```
stream <- DSD_Gaussians(k=3)

# Create a clustering process that uses a window for the online stage and
# k-means for the offline stage (reclustering)
win_km <- DSC_TwoStage(
  micro=DSC_Window(horizon=100),
  macro=DSC_Kmeans(k=3)
)
win_km

update(win_km, stream, 200)
win_km
plot(win_km, stream, type="both")
evaluate(win_km, stream, assign="macro")
```

DSC_Window

A sliding window from a Data Stream

Description

Implements a sliding window which keeps a fixed amount (window length) of the most recent data points of the stream.

Usage

```
DSC_Window(horizon = 100, lambda=0)
```

Arguments

horizon the window length.
lambda decay factor damped window model. lambda=0 means no dampening.

Details

If lambda is greater than 0 then the weight uses a damped window model (Zhu and Shasha, 2002). The weight for points in the window follows $2^{-\lambda * t}$ where t is the age of the point.

Value

An object of class DSC_Window (subclass of DSC, DSC_R, DSC_Micro).

Author(s)

Michael Hahsler

References

Zhu, Y. and Shasha, D. (2002). StatStream: Statistical Monitoring of Thousands of Data Streams in Real Time, *International Conference of Very Large Data Bases (VLDB'02)*.

See Also

[DSC](#), [DSC_Micro](#)

Examples

```
stream <- DSD_Gaussians(k=3, d=2, noise=0.05)

window <- DSC_Window(horizon=100)
window

update(window, stream, 200)
window
```



```
# plot micro-clusters
plot(window, stream)

# animation for a window using a damped window model. The weight decays
# with a half-life of 25
## Not run:
window <- DSC_Window(horizon=25, lambda=1/25)
animate_cluster(window, stream, horizon=1, n=100, xlim=c(0,1), ylim=c(0,1))

## End(Not run)
```

DSD

Data Stream Data Generator Base Classes

Description

Abstract base classes for DSD (Data Stream Data Generator).

Details

The DSD class cannot be instantiated, but it serves as a abstract base class from which all DSD objects inherit.

DSD_R inherits from DSD and is the abstract parent class for DSD implemented in R. To create a new R-based implementation there are only two function that needs to be implemented for a new DSD subclass: A creator function (the name should start with DSD_) and a method `get_points()` for that class.

DSD provides common functionality like `print()`, `plot()`, etc.

Note that calling `DSD()` or `DSD_R()` results in an error since both are abstract classes.

Author(s)

Michael Hahsler

See Also

[animate_data](#), [animate_cluster](#), [cluster](#), [evaluate](#), [get_points](#), [plot](#), [recluster](#), [write_stream](#)

Examples

```
# create data stream with three clusters in 3-dimensional space
stream <- DSD_Gaussians(k=3, d=3)

# get points from stream
get_points(stream, n=5)

# get points with true cluster assignment
p <- get_points(stream, n=5, cluster=TRUE)
attr(p, "cluster")
```

```
# plotting the data (scatter plot matrix, first and third dimension, and first
# two principal components)
plot(stream)
plot(stream, dim=c(1,3))
plot(stream, method="pc")
```

DSD_BarsAndGaussians *Data Stream Generator for Bars and Gaussians*

Description

A data stream generator which creates the shape of two bars and two Gaussians clusters with different density.

Usage

```
DSD_BarsAndGaussians(angle= NULL, noise = 0)
```

Arguments

angle	rotation in degrees. NULL will produce a random rotation.
noise	The amount of noise that should be added to the output.

Value

Returns a DSD_BarsAndGaussians object.

Author(s)

Michael Hahsler

See Also

[DSD](#)

Examples

```
# create data stream with three clusters in 2D
stream <- DSD_BarsAndGaussians(noise=0.1)

# plotting the data
plot(stream)
```

Description

A data stream generator that generates several dynamic streams intended to be benchmarks to compare data stream clustering algorithms.

Usage

```
DSD_Benchmark(i=1)
```

Arguments

`i` number of the benchmark.

Details

Currently available benchmarks are 1 and 2.

Value

Returns a DSD object.

Author(s)

Michael Hahsler

See Also

[DSD](#)

Examples

```
stream <- DSD_Benchmark(i=1)
## Not run:
animate_data(stream, n=10000, horizon=100, xlim=c(0,1), ylim=c(0,1))

## End(Not run)
```

DSD_Cubes

Static Cubes Data Stream Generator

Description

A data stream generator that produces a data stream with static (hyper) cubes filled uniformly with data points.

Usage

```
DSD_Cubes(k=2, d=2, center, size, p, noise = 0, noise_range)
```

Arguments

k	Determines the number of clusters.
d	Determines the number of dimensions.
center	A matrix of means for each dimension of each cluster.
size	A k times d matrix with the cube dimensions.
p	A vector of probabilities that determines the likelihood of generated a data point from a particular cluster.
noise	Noise probability between 0 and 1. Noise is uniformly distributed within noise range (see below).
noise_range	A matrix with d rows and 2 columns. The first column contains the minimum values and the second column contains the maximum values for noise.

Value

Returns a DSD_Cubes object (subclass of DSD_R, DSD).

Author(s)

Michael Hahsler

See Also

[DSD](#)

Examples

```
# create data stream with three clusters in 3D
stream <- DSD_Cubes(k=3, d=3)

# plotting the data
plot(stream)
```

DSD_Gaussians

*Mixture of Gaussians Data Stream Generator***Description**

A data stream generator that produces a data stream with a mixture of static Gaussians.

Usage

```
DSD_Gaussians(k=2, d=2, mu, sigma, p, separation=0.2, noise=0, noise_range)
```

Arguments

k	Determines the number of clusters.
d	Determines the number of dimensions.
mu	A matrix of means for each dimension of each cluster.
sigma	A list of length k of covariance matrices.
p	A vector of probabilities that determines the likelihood of generated a data point from a particular cluster.
separation	Minimum distance between cluster centers to reduce overlap between clusters (0-.8).
noise	Noise probability between 0 and 1. Noise is uniformly distributed within noise range (see below).
noise_range	A matrix with d rows and 2 columns. The first column contains the minimum values and the second column contains the maximum values for noise.

Details

DSD_Gaussians creates a mixture of k d-dimensional static Gaussians in approximately unit space. The centers mu and the covariance matrices sigma can be supplied or will be randomly generated. The probability vector p defines for each cluster the probability that the next data point will be chosen from it (defaults to equal probability).

The generation method is similar to the one suggested by Jain and Dubes (1988).

Value

Returns a DSD_Gaussians object (subclass of DSD_R, DSD) which is a list of the defined params. The params are either passed in from the function or created internally. They include:

description	A brief description of the DSD object.
k	The number of clusters.
d	The number of dimensions.
mu	The matrix of means of the dimensions in each cluster.
sigma	The covariance matrix.
p	The probability vector for the clusters.
noise	A flag that determines if or if not noise is generated.

Author(s)

Michael Hahsler

References

Jain and Dubes(1988) Algorithms for clustering data, Prentice-Hall, Inc., Upper Saddle River, NJ, USA.

See Also

[DSD](#)

Examples

```
# create data stream with three clusters in 3-dimensional data space
stream1 <- DSD_Gaussians(k=3, d=3)

plot(stream1)

# create data stream with specified clusterpositions,
# 20% noise in a given bounding box and
# with different densities (1 to 9 between the two clusters)
stream2 <- DSD_Gaussians(k=2, d=2,
  mu=rbind(c(-.5,-.5), c(.5,.5)),
  noise=0.2, noise_range=rbind(c(-1,1),c(-1,1)),
  p=c(.1,.9))
plot(stream2)
```

DSD_Memory

A Data Stream Interface for Data Stored in Memory

Description

This class provides a data stream interface for data stored in memory as matrix-like objects (including data frames). All or a portion of the stored data can be replayed several times.

Usage

```
DSD_Memory(x, n, k=NA, loop=FALSE,
  class = NULL, description=NULL)
```

Arguments

x	A matrix-like object containing the data. If x is a DSD object then a data frame for n data points from this DSD is created.
n	Number of points used if x is a DSD object. If x is a matrix-like object then n is ignored.

k	Optional: The known number of clusters in the data
loop	Should the stream start over when it reaches the end?
class	Vector with the class/cluster label (only used if x is not a DSD object).
description	character string with a description.

Details

In addition to regular data.frames other matrix-like objects that provide subsetting with the bracket operator can be used. This includes `ffdf` (large data.frames stored on disk) from package **ff** and `big.matrix` from **bigmemory**.

Value

Returns a DSD_Memory object (subclass of DSD_R, DSD).

Author(s)

Michael Hahsler

See Also

[DSD](#), [reset_stream](#)

Examples

```
# store 1000 points from a stream
stream <- DSD_Gaussians(k=3, d=2)
replayer <- DSD_Memory(stream, k=3, n=1000)
replayer
plot(replayer)

# creating 2 clusterers of different algorithms
dsc1 <- DSC_DBSTREAM(r=0.1)
dsc2 <- DSC_DStream(gridsize=0.1, Cm=1.5)

# clustering the same data in 2 DSC objects
reset_stream(replayer) # resetting the replayer to the first position
update(dsc1, replayer, 500)
reset_stream(replayer)
update(dsc2, replayer, 500)

# plot the resulting clusterings
reset_stream(replayer)
plot(dsc1, replayer, main="DBSTREAM")
reset_stream(replayer)
plot(dsc2, replayer, main="D-Stream")

### use a data.frame to create a stream (3rd col. contains the assignment)
df <- data.frame(x=runif(100), y=runif(100),
  class=sample(1:3, 100, replace=TRUE))
head(df)
```

```
stream <- DSD_Memory(df[,c("x", "y")], class=df[, "class"])
stream
```

DSD_MG

DSD Moving Generator

Description

Creates an evolving DSD that consists of several MGCs.

Usage

```
DSD_MG(dimension = 2, ..., labels=NULL, description=NULL)

add_cluster(x, c, label=NULL)
get_clusters(x)
remove_cluster(x, i)
```

Arguments

dimension	the dimension of the DSD object
...	initial set of MGCs
x	A DSD_MG object.
c	The cluster that should be added to the DSD_MG object.
i	The index of the cluster that should be removed from the DSD_MG object.
label, labels	integer representing the cluster label. NA represents noise. If labels are not specified, then each new cluster gets a new label.
description	An optional string used by print to describe the data generator.

Details

This DSD is able to generate complex datasets that are able to evolve over a period of time. Its behavior is determined by the MGCs it is composed of.

Author(s)

Matthew Bolanos

See Also

[MGC_Function](#), [MGC_Linear](#), [MGC_Noise](#), [MGC_Random](#) for details on the different MGC objects.

Examples

```

### create an empty DSD_MG
stream <- DSD_MG(dim = 2)
stream

### add two clusters
c1 <- MGC_Random(density=50, center=c(50,50), parameter=1, randomness = )
add_cluster(stream, c1)
stream

c2 <- MGC_Noise(density=1, range=rbind(c(-20,120), c(-20,120)))
add_cluster(stream, c2)
stream

get_clusters(stream)
plot(stream, xlim=c(-20,120), ylim=c(-20,120))

## Not run:
animate_data(stream, n=5000, xlim=c(-20,120), ylim=c(-20,120))

## End(Not run)

### remove cluster 1
remove_cluster(stream,1)

get_clusters(stream)
plot(stream, xlim=c(-20,120), ylim=c(-20,120))

### create a more complicated cluster structure (using 2 clusters with the same
### label to form an L shape)
stream <- DSD_MG(dim=2,
  MGC_Static(density=10, center=c(.5,.2), par=c(.4,.2), shape=MGC_Shape_Block),
  MGC_Static(density=10, center=c(.6,.5), par=c(.2,.4), shape=MGC_Shape_Block),
  MGC_Static(density=5, center=c(.39,.53), par=c(.16,.35), shape=MGC_Shape_Block),
  MGC_Noise(density=1, range=rbind(c(0,1), c(0,1))),
  labels= c(1, 1, 2, NA)
)

plot(stream, xlim=c(0,1), ylim=c(0,1))

### simulate the clustering of a splitting cluster
c1 <- MGC_Linear(dim = 2, keyframelist = list(
  keyframe(time = 1, dens = 20, center = c(0,0), param = 10),
  keyframe(time = 50, dens = 10, center = c(50,50), param = 10),
  keyframe(time = 100,dens = 10, center = c(50,100),param = 10)
))

### Note: Second cluster appear at time=50
c2 <- MGC_Linear(dim = 2, keyframelist = list(
  keyframe(time = 50, dens = 10, center = c(50,50), param = 10),
  keyframe(time = 100,dens = 10, center = c(100,50),param = 10)
))

```

```
))

stream <- DSD_MG(dim = 2, c1, c2)
stream

dbstream <- DSC_DBSTREAM(r=10, lambda=0.1)

## Not run:
purity <- animate_cluster(dbstream, stream, n=2500, type="both",
  xlim=c(-10,120), ylim=c(-10,120), evaluationMeasure="purity", horizon=100)

## End(Not run)
```

DSD_mlbenchData

Stream Interface for Data Sets From mlbench

Description

Provides a convenient stream interface for data sets from the mlbench package.

Usage

```
DSD_mlbenchData(data=NULL, loop = FALSE, random = FALSE, scale = FALSE)
```

Arguments

data	The name of the dataset from mlbench. If missing then a list of all available data sets is shown and returned.
loop	A flag that tells the stream to loop or not to loop over the data frame.
random	A flag that determines if the data should be in a random order.
scale	A flag that determines if the data should be scaled.

Details

The DSD_mlbenchData class is designed to be a wrapper class for data that is held in memory in either a data frame or matrix form. It is a subclass of DSD_Memory.

Call DSD_mlbenchData with a missing value for data to get a list of all available data sets.

Value

Returns a DSD_mlbenchData object which is also of class DSD_Memory.

Author(s)

Michael Hahsler and Matthew Bolanos

See Also

[DSD](#), [DSD_Memory](#), [reset_stream](#)

Examples

```
stream <- DSD_mlbenchData("Shuttle")
stream

plot(stream, n=100)
```

DSD_mlbenchGenerator *mlbench Data Stream Generator*

Description

A data stream generator class that interfaces data generators found in mlbench.

Usage

```
DSD_mlbenchGenerator(method, ...)
```

Arguments

method	The name of the mlbench data generator.
...	Parameters for the mlbench data generator.

Details

The DSD_mlbenchGenerator class is designed to be a wrapper class for data created by data generators in the mlbench library.

Call DSD_mlbenchGenerator with missing method to get a list of available methods.

Value

Returns a DSD_mlbenchGenerator object (subclass of DSD_R, DSD) which is a list of the defined parameters. The parameters are either passed in from the function or created internally. They include:

description	The name of the class of the DSD object.
method	The name of the mlbench data generator.
variables	The variables for the mlbench data generator.

Author(s)

John Forrest

See Also[DSD](#)**Examples**

```
stream <- DSD_mlbenchGenerator(method="cassini")
plot(stream, n=500)
```

DSD_ReadCSV

*Read a Data Stream from File***Description**

A DSD class that reads a data stream from a file or any R connection.

Usage

```
DSD_ReadCSV(file, k=NA, take=NULL, class=NULL, loop=FALSE,
  sep=",", header=FALSE, skip=0, colClasses = NA, ...)
close_stream(dsd)
```

Arguments

file	A file/URL or an open connection.
k	Number of true clusters, if known.
take	indices of columns to extract from the file.
class	column index for the class attribute/cluster label. If take is specified then it needs to also include the class/label column.
loop	If enabled, the object will loop through the stream when the end has been reached. If disabled, the object will warn the user upon reaching the end.
sep	The character string that separates dimensions in data points in the stream.
header	Does the first line contain variable names?
skip	the number of lines of the data file to skip before beginning to read data.
colClasses	A vector of classes to be assumed for the columns passed on to read.table.
...	Further arguments are passed on to read.table. This can for example be used for encoding, quotes, etc.
dsd	A object of class DSD_ReadCSV.

Details

DSD_ReadCSV uses `read.table()` to read in data from an R connection. The connection is responsible for maintaining where the stream is currently being read from. In general, the connections will consist of files stored on disk but have many other possibilities (see [connection](#)).

The implementation tries to gracefully deal with slightly corrupted data by dropping points with inconsistent reading and producing a warning. However, this might not always be possible resulting in an error instead.

The position in the file can be reset to the beginning using `reset_stream()`. The connection can be closed using `close_stream()`.

Value

An object of class DSD_ReadCSV (subclass of DSD_R, DSD).

Author(s)

Michael Hahsler

See Also

[DSD](#), [reset_stream](#), [read.table](#).

Examples

```
# creating data and writing it to disk
stream <- DSD_Gaussians(k=3, d=5)
write_stream(stream, "data.txt", n=10, header = TRUE, sep=",")

# reading the same data back (as a loop)
stream2 <- DSD_ReadCSV("data.txt", sep=",", header = TRUE, loop=TRUE)
stream2

# get points (first a single point and then 20 using loop)
get_points(stream2)
get_points(stream2, n=20)

# clean up
close_stream(stream2)
file.remove("data.txt")

# example with a part of the kddcup1999 data (take only cont. variables)
file <- system.file("examples", "kddcup10000.data.gz", package="stream")
stream <- DSD_ReadCSV(gzfile(file),
  take=c(1, 5, 6, 8:11, 13:20, 23:42), class=42, k=7)
stream

get_points(stream, 5, class = TRUE)

# plot 100 points (projected on the first two principal components)
```

```
plot(stream, n=100, method="pc")  
close_stream(stream)
```

DSD_ReadDB

Read a Data Stream from an open DB Query

Description

A DSD class that reads a data stream from an open DB result set from a relational database with using R's data base interface (DBI).

Usage

```
DSD_ReadDB(result, k=NA, class=NULL, description=NULL)
```

Arguments

result	An open DBI result set.
k	Number of true clusters, if known.
class	column index for the class/cluster assignment.
description	a character string describing the data.

Details

This class provides a streaming interface for result sets from a data base with via **DBI**. You need to connect to the data base and submit a SQL query using `dbGetQuery()` to obtain a result set. Make sure that your query only includes the columns that should be included in the stream. Do not forget to close the result set and the data base connection.

Value

An object of class `DSD_ReadDB` (subclass of `DSD_R`, `DSD`).

Author(s)

Michael Hahsler

See Also

[DSD](#), [dbGetQuery](#)

Examples

```

### create a data base with a table with 3 Gaussians
library("RSQLite")
con <- dbConnect(RSQLite::SQLite(), ":memory:")

points <- get_points(DSD_Gaussians(k=3, d=2), 600, class = TRUE)
head(points)

dbWriteTable(con, "gaussians", points)

### prepare a query result set
res <- dbSendQuery(con, "SELECT X1, X2, class FROM gaussians")
res

### create a stream interface to the result set
stream <- DSD_ReadDB(res, k=3, class = 3)

### get points
get_points(stream, 5, class = TRUE)
plot(stream)

### clean up
dbClearResult(res)
dbDisconnect(con)

```

DSD_ScaleStream	<i>Scale a Stream from a DSD</i>
-----------------	----------------------------------

Description

Make an unscaled data stream into a scaled data stream.

Usage

```
DSD_ScaleStream(dsd, center=TRUE, scale=TRUE, n=1000, reset=FALSE)
```

Arguments

dsd	A object of class DSD that will be scaled.
center, scale	logical or a numeric vector of length equal to the number of columns used for centering/scaling (see function <code>scale</code>).
n	The number of points used to creating the centering/scaling
reset	Try to reset the stream to its beginning after taking n points for scaling.

Details

`scale_stream()` estimates the values for centering and scaling (see `scale` in **base**) using n points from the stream.

Value

An object of class `DSD_ScaleStream` (subclass of `DSD_R`, `DSD`).

Author(s)

Michael Hahsler

See Also

[DSD](#), [reset_stream](#), [scale](#) in **base**,

Examples

```
stream <- DSD_Gaussians(k=3, d=3)
plot(stream)

# scale stream using 100 points
stream_scaled <- DSD_ScaleStream(stream, n=100)
plot(stream_scaled)
```

DSD_Target

Target Data Stream Generator

Description

A data stream generator that generates a data stream in the shape of a target. It has a single Gaussian cluster in the center and a ring that surrounds it.

Usage

```
DSD_Target(center_sd = 0.05, center_weight = 0.5, ring_r = 0.2,
           ring_sd = 0.02, noise = 0)
```

Arguments

<code>center_sd</code>	standard deviation of center
<code>center_weight</code>	proportion of points in center
<code>ring_r</code>	average ring radius
<code>ring_sd</code>	standard deviation of ring radius
<code>noise</code>	proportion of noise

Details

`DSD_Target` is a DSD generator for stream data. It has been implemented entirely in R, so there is no computational overhead with communicating to the Java Runtime Interface (JRI) or native C code. This DSD will produce a singular Gaussian cluster in the center with a ring around it.

Value

Returns a DSD_Target object which is a list of the defined params. The params are either passed in from the function or created internally. They include:

description	A brief description of the DSD object.
k	The number of clusters.
d	The number of dimensions.

Author(s)

Michael Hahsler

See Also

[DSD](#)

Examples

```
# create data stream with three clusters in 2D
stream <- DSD_Target()
# plotting the data
plot(stream)
```

DSD_UniformNoise	<i>Uniform Noise Data Stream Generator</i>
------------------	--

Description

This generator produces uniform noise in a d-dimensional unit (hyper) cube.

Usage

```
DSD_UniformNoise(d=2, range=NULL)
```

Arguments

d	Determines the number of dimensions.
range	A matrix with two columns and d rows giving the minimum and maximum for each dimension. Defaults to the range of [0, 1].

Value

Returns a DSD_UniformNoise object.(subclass of DSD_R, DSD).

Author(s)

Michael Hahsler

See Also[DSD](#)**Examples**

```
# create data stream with three clusters in 2D
stream <- DSD_UniformNoise(d=2)
plot(stream, n=100)

# specify a different range for each dimension
stream <- DSD_UniformNoise(d=3, range=rbind(c(0,1), c(0,10), c(0,5)))
plot(stream, n=100)
```

DSDP*Abstract Class for Frequent Pattern Mining Algorithms for Data Streams*

Description

Abstract class for frequent pattern mining algorithms for data streams. Currently, **stream** does not implement frequent pattern mining algorithms.

Author(s)

Michael Hahsler

See Also[DST](#)

DSO*Data Stream Operator Base Classes*

Description

Abstract base classes for all DSO (Data Stream Operator) classes.

Details

The DSO class cannot be instantiated (calling DSO() produces errors), but it serve as a base class from which other DSO classes inherit.

Data stream operators use update() to process new data from the stream. The result of the operator can be obtained via get_points() and get_weights().

Author(s)

Michael Hahsler

See Also

[update](#), [get_points](#), [get_weights](#), [DSO_Window](#), [DSO_Sample](#)

DSO_Sample

Sampling from a Data Stream (Data Stream Operator)

Description

Extracts a sample form a data stream using Reservoir Sampling.

Usage

```
DSO_Sample(k = 100, biased = FALSE)
```

Arguments

k	the number of points to be sampled from the stream.
biased	if FALSE then a regular (unbiased) reservoir sampling is used. If true then the sample is biased towards keeping more recent data points (see Details section).

Details

If `biased=FALSE` then the reservoir sampling algorithm by McLeod and Bellhouse (1983) is used. This sampling makes sure that each data point has the same chance to be sampled. All sampled points will have a weight of 1. Note that this might not be ideal for an evolving stream since very old data points have the same chance to be in the sample as newer points.

If `bias=TRUE` then sampling prefers newer points using the modified reservoir sampling algorithm 2.1 by Aggarwal (2006). New points are always added. They replace a random point in the reservoir with a probability of reservoir size over k. This an exponential bias function of $2^{-lambda}$ with $lambda = 1/k$.

Value

An object of class `DSO_Sample` (subclass of `DSO`).

Author(s)

Michael Hahsler

References

- Vitter, J. S. (1985): Random sampling with a reservoir. ACM Transactions on Mathematical Software, 11(1), 37-57.
- McLeod, A.I., Bellhouse, D.R. (1983): A Convenient Algorithm for Drawing a Simple Random Sample. Applied Statistics, 32(2), 182-184.
- Aggarwal C. (2006) On Biased Reservoir Sampling in the Presence of Stream Evolution. International Conference on Very Large Databases (VLDB'06). 607-618.

See Also

[DSO](#)

Examples

```
stream <- DSD_Gaussians(k=3, noise=0.05)

sample <- DSO_Sample(k=20)

update(sample, stream, 500)
sample

# plot points in sample
plot(get_points(sample))
```

DSO_Window

Sliding Window (Data Stream Operator)

Description

Implements a sliding window data stream operator which keeps a fixed amount (window length) of the most recent data points of the stream.

Usage

```
DSO_Window(horizon = 100, lambda=0)
```

Arguments

horizon the window length.

lambda decay factor damped window model. lambda=0 means no dampening.

Details

If lambda is greater than 0 then the weight uses a damped window model (Zhu and Shasha, 2002). The weight for points in the window follows $2^{-\lambda * t}$ where t is the age of the point.

Value

An object of class `DSO_Window` (subclass of `DSO`).

Author(s)

Michael Hahsler

References

Zhu, Y. and Shasha, D. (2002). StatStream: Statistical Monitoring of Thousands of Data Streams in Real Time, Intl. Conference of Very Large Data Bases (VLDB'02).

See Also

[DSO](#)

Examples

```
stream <- DSD_Gaussians(k=3, d=2, noise=0.05)

window <- DSO_Window(horizon=100)
window

update(window, stream, 200)
window

# plot points in window
plot(get_points(window))
```

DST

Abstract Base Class for All Data Stream Mining Tasks

Description

Abstract base class for all data stream mining tasks. Current tasks are data stream clustering `DSC`, classification on data streams `DSClassify` and frequent pattern mining on data streams `DSFP`.

Author(s)

Michael Hahsler

See Also

[DSC](#), [DSClassify](#), [DSFP](#)

 evaluate

Evaluate Clusterings

Description

Gets evaluation measures for micro or macro-clusters from a DSC object given the original DSD object.

Usage

```
evaluate(dsc, dsd, measure, n = 100, type=c("auto", "micro", "macro"),
  assign="micro", assignmentMethod=c("auto", "model", "nn"),
  noise = c("class", "exclude"), ...)
evaluate_cluster(dsc, dsd, measure, n = 1000,
  type=c("auto", "micro", "macro"),
  assign="micro", assignmentMethod=c("auto", "model", "nn"),
  horizon=100, verbose=FALSE, noise = c("class", "exclude"), ...)
```

Arguments

dsc	The DSC object that the evaluation measure is being requested from.
dsd	The DSD object that holds the initial training data for the DSC.
measure	Evaluation measure(s) to use. If missing then all available measures are returned.
n	The number of data points being requested.
type	Use micro- or macro-clusters for evaluation. Auto used the class of dsc to decide.
assign	Assign points to micro or macro-clusters?
assignmentMethod	How are points assigned to clusters for evaluation (see <code>get_assignment</code>)?
horizon	Evaluation is done using horizon many previous points (see detail section).
verbose	report progress?
noise	how to handle noise points in the data. Options are to treat as a separate class (default) or to exclude them from evaluation.
...	Unused arguments are ignored.

Details

For evaluation each data points are assigned to its nearest cluster using Euclidean distance to the cluster centers. Then for each cluster the majority class is determined. Based on the majority class several evaluation measures can be computed.

For `evaluate_cluster` the most commonly used method of prequential error estimation (see Gama, Sebastiao and Rodrigues; 2013). The data points in the horizon are first used to calculate the evaluation measure and then they are used for updating the cluster model. Many evaluation

measures are calculated with code from the packages **cluster**, **clue** and **fpc**. Detailed documentation can be found in these packages (see Section See Also.)

The following information items are available:

- "numMicroClusters" number of micro-clusters
- "numMacroClusters" number of macro-clusters
- "numClasses" number of classes

The following noise-related items are available:

- "noisePredicted" Number data points predicted as noise
- "noiseActual" Number of data points which are actually noise
- "noisePrecision" Precision of the predicting noise (i.e., number of correctly predicted noise points over the total number of points predicted as noise)

The following internal evaluation measures are available:

- "SSQ" within cluster sum of squares. Assigns each non-noise point to its nearest center from the clustering and calculates the sum of squares
- "silhouette" average silhouette width (actual noise points which stay unassigned by the clustering algorithm are removed; regular points that are unassigned by the clustering algorithm will form their own noise cluster) (**cluster**)
- "average.between" average distance between clusters (**fpc**)
- "average.within" average distance within clusters (**fpc**)
- "max.diameter" maximum cluster diameter (**fpc**)
- "min.separation" minimum cluster separation (**fpc**)
- "ave.within.cluster.ss" a generalization of the within clusters sum of squares (half the sum of the within cluster squared dissimilarities divided by the cluster size) (**fpc**)
- "g2" Goodman and Kruskal's Gamma coefficient (**fpc**)
- "pearsongamma" correlation between distances and a 0-1-vector where 0 means same cluster, 1 means different clusters (**fpc**)
- "dunn" Dunn index (minimum separation / maximum diameter) (**fpc**)
- "dunn2" minimum average dissimilarity between two cluster / maximum average within cluster dissimilarity (**fpc**)
- "entropy" entropy of the distribution of cluster memberships (**fpc**)
- "wb.ratio" average.within/average.between (**fpc**)

The following external evaluation measures are available:

- "precision", "recall", "F1" F1. A true positive (TP) decision assigns two points in the same true cluster also to the same cluster, a true negative (TN) decision assigns two points from two different true clusters to two different clusters. A false positive (FP) decision assigns two points from the same true cluster to two different clusters. A false negative (FN) decision assigns two points from the same true cluster to different clusters.

$$\text{precision} = \text{TP}/(\text{TP}+\text{FP})$$

$$\text{recall} = \text{TP}/(\text{TP}+\text{FN})$$

The F1 measure is the harmonic mean of precision and recall.

- "purity" Average purity of clusters. The purity of each cluster is the proportion of the points of the majority true group assigned to it (see Cao et al. (2006))
- "Euclidean" Euclidean dissimilarity of the memberships (see Dimitriadou, Weingessel and Hornik (2002)) (**clue**)
- "Manhattan" Manhattan dissimilarity of the memberships (**clue**)
- "Rand" Rand index (see Rand (1971)) (**clue**)
- "cRand" Adjusted Rand index (see Hubert and Arabie (1985)) (**clue**)
- "NMI" Normalized Mutual Information (see Strehl and Ghosh (2002)) (**clue**)
- "KP" Katz-Powell index (see Katz and Powell (1953)) (**clue**)
- "angle" maximal cosine of the angle between the agreements (**clue**)
- "diag" maximal co-classification rate (**clue**)
- "FM" Fowlkes and Mallows's index (see Fowlkes and Mallows (1983)) (**clue**)
- "Jaccard" Jaccard index (**clue**)
- "PS" Prediction Strength (see Tibshirani and Walter (2005)) (**clue**)
- "vi" variation of information (VI) index (**fpc**)

Many measures are the average over all clusters. For example, purity is the average purity over all clusters.

For DSC_Micro objects, data points are assigned to micro-clusters and then each micro-cluster is evaluated. For DSC_Macro objects, data points by default (`assign="micro"`) also assigned to micro-clusters, but these assignments are translated to macro-clusters. The evaluation is here done for macro-clusters. This is important when macro-clustering is done with algorithms which do not create spherical clusters (e.g. hierarchical clustering with single-linkage or DBSCAN) and this assignment to the macro-clusters directly (i.e., their center) does not make sense.

Using `type` and `assign`, the user can select how to assign data points and at what level (micro or macro) to evaluate.

Many of the above measures are implemented package **clue** in function `cl_agreement()`.

`evaluate_cluster()` is used to evaluate an evolving data stream using the method described by Wan et al. (2009). Of the n data points horizon many points are clustered and then the evaluation measure is calculated on the same data points. The idea is to find out if the clustering algorithm was able to adapt to the changing stream.

Value

`evaluate` returns an object of class `stream_eval` which is a numeric vector of the values of the requested measures and two attributes, `"type"` and `"assign"`, to see at what level the evaluation was done.

Author(s)

Michael Hahsler, Matthew Bolanos and John Forrest

References

- Joao Gama, Raquel Sebastiao, Pedro Pereira Rodrigues (2013). On evaluating stream learning algorithms. *Machine Learning*, March 2013, Volume 90, Issue 3, pp 317-346.
- F. Cao, M. Ester, W. Qian, A. Zhou (2006). Density-Based Clustering over an Evolving Data Stream with Noise. *Proceeding of the 2006 SIAM Conference on Data Mining*, 326-337.
- E. Dimitriadou, A. Weingessel and K. Hornik (2002). A combination scheme for fuzzy clustering. *International Journal of Pattern Recognition and Artificial Intelligence*, 16, 901-912.
- E. B. Fowlkes and C. L. Mallows (1983). A method for comparing two hierarchical clusterings. *Journal of the American Statistical Association*, 78, 553-569.
- L. Hubert and P. Arabie (1985). Comparing partitions. *Journal of Classification*, 2, 193-218.
- W. M. Rand (1971). Objective criteria for the evaluation of clustering methods. *Journal of the American Statistical Association*, 66, 846-850.
- L. Katz and J. H. Powell (1953). A proposed index of the conformity of one sociometric measurement to another. *Psychometrika*, 18, 249-256.
- A. Strehl and J. Ghosh (2002). Cluster ensembles - A knowledge reuse framework for combining multiple partitions. *Journal of Machine Learning Research*, 3, 583-617.
- R. Tibshirani and G. Walter (2005). Cluster validation by Prediction Strength. *Journal of Computational and Graphical Statistics*, 14/3, 511-528.
- L Wan, W.K. Ng, X.H. Dang, P.S. Yu and K. Zhang (2009). Density-Based Clustering of Data Streams at Multiple Resolutions, *ACM Transactions on Knowledge Discovery from Data*, 3(3).

See Also

[animate_cluster](#), [cl_agreement](#) in **clue**, [cluster.stats](#) in **fpc**, [silhouette](#) in **cluster**.

Examples

```
stream <- DSD_Gaussians(k=3, d=2)

dstream <- DSC_DStream(gridsize=0.05, Cm=1.5)
update(dstream, stream, 500)
plot(dstream, stream)
# Evaluate micro-clusters
# Note: we use here only n=500 points for evaluation to speed up execution
evaluate(dstream, stream, measure=c("numMicro","numMacro","purity","crand", "SSQ"),
  n=100)

# DStream also provides macro clusters. Evaluate macro clusters with type="macro"
plot(dstream, stream, type="macro")
evaluate(dstream, stream, type="macro",
  measure=c("numMicro","numMacro","purity","crand", "SSQ"), n=100)

# Points are by default assigned to the closest micro clusters for evaluation.
# However, points can also be assigned to the closest macro-cluster using
# assign="macro".
evaluate(dstream, stream, type="macro", assign="macro",
  measure=c("numMicro","numMacro","purity","crand", "SSQ"), n=100)
```

```

# Evaluate an evolving data stream
stream <- DSD_Benchmark(1)
dstream <- DSC_DStream(gridsize=0.05, lambda=0.1)
evaluate_cluster(dstream, stream, type="macro", assign="micro",
  measure=c("numMicro", "numMacro", "purity", "crand"),
  n=600, horizon=100)

## Not run:
# animate the clustering process
reset_stream(stream)
dstream <- DSC_DStream(gridsize=0.05, lambda=0.1)
animate_cluster(dstream, stream, horizon=100, n=5000,
  measure=c("crand"), type="macro", assign="micro",
  plot.args = list(type="both", xlim=c(0,1), ylim=c(0,1)))

## End(Not run)

```

get_assignment

Assignment Data Points to Clusters

Description

Get the assignment of data points to clusters in a DSC (nearest-neighbor).

Usage

```
get_assignment(dsc, points, type=c("auto", "micro", "macro"),
  method="auto", ...)
```

Arguments

dsc	The DSC object with the clusters for assignment.
points	The points to be assigned as a data.frame.
type	Use micro- or macro-clusters in DSC for assignment. Auto used the class of dsc to decide.
method	assignment method "model" uses the assignment model of the underlying algorithm (unassigned points return NA). "nn" performs nearest neighbor assignment using Euclidean distance. "auto" uses model if it is available and defaults to nn otherwise.
...	Additional arguments are passed on.

Details

Each data point is assigned either using the original model's assignment rule or Euclidean nearest neighbor assignment.

Value

A vector containing the assignment of each point. NA means that a data point was not assigned to a cluster.

Author(s)

Michael Hahsler

See Also

[DSC](#)

Examples

```
stream <- DSD_Gaussians(k=3, d=2, noise=.05)

dbstream <- DSC_DBSTREAM(r=.1)
update(dbstream, stream, n=100)

# find the assignment for the next 100 points to
# micro-clusters in dsc. This uses the model's assignemnt function
points <- get_points(stream, n=100)
a <- get_assignment(dbstream, points)
a

# show the MC assignment areas. Assigned points as blue circles and
# the unassigned points as red dots
plot(dbstream, stream, assignment= TRUE, type="none")
points(points[!is.na(a),], col="blue")
points(points[is.na(a),], col="red", pch=20)

# use nearest neighbor assignment instead
get_assignment(dbstream, points, method="nn")
```

get_centers

Get Cluster Centers from a DSC

Description

Gets the cluster centers (micro- or macro-clusters) from a DSC object.

Usage

```
get_centers(x, type=c("auto", "micro", "macro"), ...)
```

Arguments

x	The DSC object the centers are being requested from.
type	get centers for micro- or macro-clusters. Auto used the class of dsc to decide.
...	Additional parameters.

Value

A data.frame with the micro- or macro-cluster centers as rows.

Author(s)

Michael Hahsler

See Also

[DSC](#)

Examples

```
stream <- DSD_Gaussians(k=3, d=2)
dstream <- DSC_DStream(gridsize=.1)
update(dstream, stream, 500)
dstream

# getting the micro-cluster centers
get_centers(dstream)

# D-Stream also has macro-clusters
get_centers(dstream, type="macro")
```

get_copy

Create a Deep Copy of a DSC Object

Description

DSC objects contain reference classes or Java data structures (for MOA). Therefore, we provide a mechanism to create deep copies.

Usage

```
get_copy(x)
```

Arguments

x The DSC object being copied.

Value

A deep copy of the original DSC.

Author(s)

Michael Hahsler

See Also[DSC](#)

`get_points`*Get Points from a Data Stream Generator*

Description

Gets points from a DSD object.

Usage

```
get_points(x, n=1, outofpoints=c("stop", "warn", "ignore"), ...)
```

Arguments

<code>x</code>	The DSD object.
<code>n</code>	Request up to n points from the stream.
<code>outofpoints</code>	Action taken if less than n data points are available. The default is to stop with an error. For warn and ignore all available (possibly zero) points are returned.
<code>...</code>	Additional parameters to pass to <code>get_points()</code> implementations.

Details

Each DSD object has a unique way for returning data points, but they all are called through the generic function, `get_points()`. This is done by using the S3 class system. See the man page for the specific DSD class on the semantics for each implementation of `get_points()`.

Value

Returns a matrix of $x \times d$ columns and n rows.

Author(s)

Michael Hahsler

See Also[DSD](#)**Examples**

```
stream <- DSD_Gaussians()
get_points(stream, 100)
```

`get_weights`*Get Cluster Weights*

Description

Get the weights of the clusters in the DSC

Usage

```
get_weights(x, type=c("auto", "micro", "macro"), scale=NULL, ...)
```

Arguments

<code>x</code>	The DSC object the weights are being requested from.
<code>type</code>	Return wrights of micro- or macro-clusters in <code>x</code> . Auto uses the class of <code>x</code> to decide.
<code>scale</code>	a range (from, to) to scale the weights. Returns by default the raw weights.
<code>...</code>	Additional arguments are passed on.

Details

The cluster weights are typically a function of how many points were assigned to each cluster.

Value

A vector containing the weight of each micro-cluster or macro-cluster. Internally the call is delegated to the appropriate `get_microweights()` or `get_macroweights()` method.

Author(s)

Michael Hahsler

See Also

[DSC](#)

Examples

```
stream <- DSD_Gaussians(k=3, d=2)
dstream <- DSC_DStream(gridsize=.1)
update(dstream, stream, 500)
dstream

# getting the micro-cluster weights
get_weights(dstream)

# D-Stream also has macro-clusters
get_weights(dstream, type="macro")
```

Description

Creates an evolving cluster for a DSD_MG.

Usage

```
MGC_Static(density, center, parameter, shape = NULL)
MGC_Function(density, center, parameter, shape = NULL)
MGC_Random(density, center, parameter, randomness = 1, shape = NULL)
MGC_Noise(density, range)

MGC_Linear(dimension = 2, keyframelist = NULL, shape = NULL)
keyframe(time, density, center, parameter, reset = FALSE)
add_keyframe(x, time, density, center, parameter, reset = FALSE)
get_keyframes(x)
remove_keyframe(x, time)
```

Arguments

center	A list that defines the center of the cluster. The list should have a length equal to the dimensionality. For MGC_Function, this list consists of functions that define the movement of the cluster. For MGC_Random, this attribute defines the beginning location for the MGC before it begins moving.
density	The density of the cluster. For MGC_Function, this attribute is a function and defines the density of a cluster at a given timestamp.
dimension	Dimensionality of the data stream.
keyframelist	a list of keyframes to initialize the MGC_Linear object with.
parameter	Parameters for the shape. For the default shape MGC_Shape_Gaussian the parameter is the standard deviation, one per dimension. If a single value is specified then it is recycled for all dimensions.
randomness	The maximum amount the cluster will move during one time step.
range	The area in which the noise should appear.
reset	Should the cluster reset to the first keyframe (time 0) after this keyframe is finished?
shape	A function creating the shape of the cluster. It gets passed on the parameters argument from above. Available functions are MGC_Shape_Gaussian (the parameters are a vector containing standard deviations) and MGC_Shape_Block (parameters are the dimensions of the uniform block).
time	The time stamp the keyframe should be located or which keyframe should be removed.
x	An object of class MGC_Linear.

Details

An MGC describes a single cluster for use within an DSD_MG. There are currently four different MGCs that allow a user to express many different behaviors within a single data stream.

An MGC_Linear creates an evolving Gaussian cluster for a DSD_MG who's behavior is determined by several keyframes. Keyframes can be added and removed.

An MGC_Function allows for a creation of a DSD_MG that is defined by functions of time.

An MGC_Random allows for a creation of a DSD_MG that moves randomly.

An MGC_Noise allows for a creation of noise within a DSD_MG.

Author(s)

Matthew Bolanos

See Also

[DSD_MG](#) for details on how to use an MGC within a DSD

Examples

```
### Two static clusters
stream <- DSD_MG(dim=2,
  MGC_Static(den = 1, center=c(1, 0), par=.1),
  MGC_Static(den = 1, center=c(2, 0), par=.4, shape=MGC_Shape_Block)
)

plot(stream)

### Example of several MGC_Randoms
stream <- DSD_MG(dimension=2,
  MGC_Random(den = 100, center=c(1, 0), par=.1, rand=.1),
  MGC_Random(den = 100, center=c(2, 0), par=.4, shape=MGC_Shape_Block, rand=.1)
)

## Not run:
  animate_data(stream, 2500, xlim=c(0,3), ylim=c(-2,2), horizon=100)

## End(Not run)

### Example of several MGC_Functions
stream <- DSD_MG(dim = 2)

### block-shaped cluster moving from bottom-left to top-right increasing size
c1 <- MGC_Function(
  density = function(t){100},
  parameter = function(t){1*t},
  center = function(t) c(t,t),
  shape = MGC_Shape_Block
)
add_cluster(stream,c1)
```



```

### cluster moving in a circle (default shape is Gaussian)
c2 <- MGC_Function(
  density = function(t){25},
  parameter = function(t){5},
  center= function(t) c(sin(t/10)*50+50, cos(t/10)*50+50)
)
add_cluster(stream,c2)

## Not run:
animate_data(stream,10000,xlim=c(-20,120),ylim=c(-20,120), horizon=100)

## End(Not run)

### Example of several MGC_Linears: A single cluster splits at time 50 into two.
### Note that c2 starts at time=50!
stream <- DSD_MG(dim = 2)
c1 <- MGC_Linear(dim = 2)
add_keyframe(c1, time=1, dens=50, par=5, center=c(0,0))
add_keyframe(c1, time=50, dens=50, par=5, center=c(50,50))
add_keyframe(c1, time=100,dens=50, par=5, center=c(50,100))
add_cluster(stream,c1)

c2 <- MGC_Linear(dim = 2, shape=MGC_Shape_Block)
add_keyframe(c2, time=50, dens=25, par=c(10,10), center=c(50,50))
add_keyframe(c2, time=100,dens=25, par=c(30,30), center=c(100,50))
add_cluster(stream,c2)

## Not run:
animate_data(stream,5000,xlim=c(0,100),ylim=c(0,100), horiz=100)

## End(Not run)

### two fixed and a moving cluster
stream <- DSD_MG(dim = 2,
  MGC_Static(dens=1, par=.1, center=c(0,0)),
  MGC_Static(dens=1, par=.1, center=c(1,1)),
  MGC_Linear(dim=2,list(
    keyframe(time = 0, dens=1, par=.1, center=c(0,0)),
    keyframe(time = 1000, dens=1, par=.1, center=c(1,1)),
    keyframe(time = 2000, dens=1, par=.1, center=c(0,0), reset=TRUE)
  )))

noise <- MGC_Noise(dens=.1, range=rbind(c(-.2,1.2),c(-.2,1.2)))
add_cluster(stream, noise)

## Not run:
animate_data(stream, n=2000*3.1, xlim=c(-.2,1.2), ylim=c(-.2,1.2), horiz=200)

## End(Not run)

```

microToMacro	<i>Translate Micro-cluster IDs to Macro-cluster IDs</i>
--------------	---

Description

Translates micro-cluster ids into macro-cluster ids for a DSC_Macro object.

Usage

```
microToMacro(x, micro=NULL)
```

Arguments

x	a DSC_Macro object that also contains information about micro-clusters.
micro	A vector with micro-cluster ids. If NULL then the assignments for all micro-clusters in x are returned.

Value

A vector of the same length as micro with the macro-cluster ids.

Author(s)

Michael Hahsler

See Also

[DSC_Macro](#)

Examples

```
stream <- DSD_Gaussians(k=3, d=2, noise=0.05, p=c(.2,.4,.6))

# recluster a micro-clusters
micro <- DSC_DStream(gridsize=0.05)
update(micro, stream, 500)

macro <- DSC_Kmeans(k=3)
recluster(macro, micro)

# translate all micro-cluster ids
microToMacro(macro)

# plot some data points in gray
plot(stream, col="gray", cex=.5, xlim=c(0,1), ylim=c(0,1))
# add micro-clusters and use the macro-cluster ids as color and weights as size
points(get_centers(macro, type="micro"),
       col=microToMacro(macro),
       cex=get_weights(macro, type="micro", scale=c(.5,3)))
```

```
# add macro-cluster centers (size is weight)
points(get_centers(macro, type="macro"),
       cex = get_weights(macro, type="macro", scale=c(2,5)),
       pch=3,lwd=3, col=1:3)
```

nclusters

nclusters

Description

Returns the number of micro-clusters from the DSC object.

Usage

```
nclusters(x, type=c("auto", "micro", "macro"), ...)
```

Arguments

x	A DSC object.
type	Return the number of micro- or macro-clusters in DSC. Auto used the class of dsc to decide.
...	Additional arguments are passed on.

Value

An integer; the number of micro- or macro-clusters in the clustering.

Author(s)

Michael Hahsler

See Also

[DSC](#)

Examples

```
# setting up the objects
stream <- DSD_Gaussians(k=3)
dstream <- DSC_DStream(gridsize=0.1)
update(dstream, stream, 500)

# retrieving the results
get_centers(dstream)
nclusters(dstream)
```

plot

*Plotting Data Stream Data and Clusterings***Description**

Methods to plot data stream data and clusterings.

Usage

```
## S3 method for class 'DSD'
plot(x, n = 500, col= NULL,
     pch= NULL, ..., method="pairs", dim = NULL, alpha = 0.6)
## S3 method for class 'DSC'
plot(x, dsd = NULL, n = 500,
     col_points=NULL, col_clusters=c("red", "blue"),
     weights=TRUE, scale=c(1,5), cex=1, pch=NULL, method="pairs",
     dim = NULL, type = c("auto", "micro", "macro", "both"),
     assignment=FALSE, ...)
```

Arguments

x	the DSD or DSC object to be plotted.
dsd	a DSD object to plot the data in the background.
n	number of plots taken from the dsd to plot.
col, col_points, col_clusters	colors used for plotting.
weights	the size of the symbols for micro- and macro-clusters represents its weight.
scale	range for the symbol sizes used.
cex	size factor for symbols.
pch	symbol type.
method	method used for plotting: "pairs" (pairs plot), "scatter" (scatter plot) or "pc" (plot first 2 principal components).
dim	an integer vector with the dimensions to plot. If NULL then for methods "pairs" and "pc" all dimensions are used and for "scatter" the first two dimensions are plotted.
alpha	alpha shading used to plot the points.
type	Plot micro- or macro-clusters. Auto used the class of dsc to decide.
assignment	logical; show assignment area of micro-clusters.
...	further arguments are passed on to plot or pairs in graphics .

Author(s)

Michael Hahsler

See Also[DSC, DSD](#)**Examples**

```
stream <- DSD_Gaussians(k=3, d=3)

## plot data
plot(stream, n=500)
plot(stream, method="pc", n=500)
plot(stream, method="scatter", dim=c(1,3), n=500)

## create and plot micro-clusters
dstream <- DSC_DStream(gridsize=0.1)
update(dstream, stream, 500)
plot(dstream)

## plot with data, projected on the first two principal components
## and dimensions 2 and 3
plot(dstream, stream)
plot(dstream, stream, method="pc")
plot(dstream, stream, dim=c(2,3))

## plot micro and macro-clusters
plot(dstream, stream, type="both")
```

prune_clusters

Prune Clusters from a Clustering

Description

Creates a (static) copy of a clustering where a fraction of the weight or the number of clusters with the lowest weights were pruned.

Usage

```
prune_clusters(dsc, threshold= 0.05, weight = TRUE)
```

Arguments

dsc	The DSC object to be pruned.
threshold	The numeric vector of probabilities for the quantile.
weight	should a fraction of the total weight in the clustering be pruned? Otherwise a fraction of clusters is pruned.

Value

Returns an object of class `DSC_Static`.

Author(s)

Michael Hahsler

See Also

[DSC_Static](#)

Examples

```
# 3 clusters with 10% noise
stream <- DSD_Gaussians(k=3, noise=0.1)

dbstream <- DSC_DBSTREAM(r=0.1)
update(dbstream, stream, 500)
dbstream
plot(dbstream, stream)

# prune lightest micro-clusters for 20% of the weight of the clustering
static <- prune_clusters(dbstream, threshold=0.2)
static
plot(static, stream)
```

recluster

Re-clustering micro-clusters

Description

Use a macro clustering algorithm to recluster micro-clusters into a final clustering.

Usage

```
recluster(macro, micro, type="auto", ...)
```

Arguments

macro	a macro clustering algorithm (class "DSC_Macro")
micro	a DSC object containing micro-clusters.
type	controls which clustering is used from dsc (typically micro-clusters).
...	additional arguments passed on.

Details

Takes centers and weights of the micro-clusters and applies the macro clustering algorithm.

Value

The object macro is altered and contains the clustering.

Author(s)

Michael Hahsler

Examples

```
set.seed(0)
### create a data stream and a micro-clustering
stream <- DSD_Gaussians(k=3, d=3)

sample <- DSC_Sample(k=50)
update(sample, stream, 500)
sample

### recluster using k-means
kmeans <- DSC_Kmeans(k=3)
recluster(kmeans, sample)

### plot clustering
plot(kmeans, stream, main="Macro-clusters (Sampling + k-means)")
```

reset_stream

Reset a Data Stream to its Beginning

Description

Resets the counter in a DSD object to the beginning or any other position in the stream.

Usage

```
reset_stream(dsd, pos = 1)
```

Arguments

dsd An object of class a subclass of DSD which implements a reset function.
pos Position in the stream (the beginning of the stream is position 1).

Details

Resets the counter of the stream object. For example, for `DSD_Memory`, the counter stored in the environment variable is moved back to 1. For `DSD_ReadCSV` objects, this is done by calling `seek()` on the underlying connection.

Author(s)

Michael Hahsler

See Also

[DSD_ReadCSV](#), [DSD_MG](#), [DSD_ScaleStream](#), [DSD_Memory](#)

Examples

```
# initializing the objects
stream <- DSD_Gaussians(k=3, d=2)
replayer <- DSD_Memory(stream, 100)
replayer

p <- get_points(replayer, 50)
replayer

# reset replayer to the beginning of the stream
reset_stream(replayer)
replayer

# set replayer to position 21
reset_stream(replayer, pos=21)
replayer
```

save

Save and Read DSC Objects

Description

Save and Read DSC objects savely (serializes the underlying data structure). This also works for **streamMOA** DSC objects.

Usage

```
saveDSC(object, file, ...)
readDSC(file)
```

Arguments

object	a DSC object.
file	filename.
...	further arguments.

Author(s)

Michael Hahsler

See Also

[saveRDS](#) and [readRDS](#).

Examples

```

stream <- DSD_Gaussians(k = 3, noise = 0.05)

# create clusterer with r = 0.05
dbstream1 <- DSC_DBSTREAM(r = .05)
update(dbstream1, stream, 1000)
dbstream1

saveDSC(dbstream1, file="dbstream.Rds")

dbstream2 <- readDSC("dbstream.Rds")
dbstream2

## cleanup
unlink("dbstream.Rds")

```

update

*Update a Data Stream Clustering Model***Description**

Update a clustering model by clustering a number of input points from a data stream into a clustering object.

Usage

```

## S3 method for class 'DSC_R'
update(object, dsd, n = 1, verbose = FALSE, block=10000L, ...)
## S3 method for class 'DSC_TwoStage'
update(object, dsd, n = 1, verbose = FALSE,
       block=10000L, ...)
## S3 method for class 'DSO_Sample'
update(object, dsd, n = 1, verbose = FALSE, ...)
## S3 method for class 'DSO_Window'
update(object, dsd, n = 1, verbose = FALSE, ...)

```

Arguments

object	an object of a subclass of DST (data stream mining task).
dsd	a DSD object (data stream).
n	number of points to cluster.
verbose	report progress.
block	maximal number of data points passed on at once to the algorithm. This only is used since R loops are very slow.
...	extra arguments for clusterer.

Details

update takes n times a single data points out of the DSD updates the model in object. Note that update directly modifies the object (which is a reference class) and thus the result does not need to be reassigned to the object name.

Value

The updated model is returned invisibly for reassignment (however, this is not necessary).

To obtain the updated model for a DSC (data stream clustering model), call `get_centers()` on the DSC object.

Author(s)

Michael Hahsler

See Also

[DSC](#), [DSD](#), and [animation](#) for producing an animation of the clustering process.

Examples

```
stream <- DSD_Gaussians(k=3)
dstream <- DSC_DStream(gridsize=.05)

update(dstream, stream, 500)
plot(dstream, stream)
```

write_stream

Write a Data Stream to a File

Description

Writes points from a data stream DSD object to a file or a connection.

Usage

```
write_stream(dsd, file, n=100, block=100000L,
class=FALSE, append = FALSE, sep=",", header=FALSE, row.names=FALSE, ...)
```

Arguments

dsd	The DSD object that will generate the data points for output.
file	A file name or a R connection to be written to.
n	The number of data points to be written.
block	Write stream in blocks to improve file I/O speed.
class	Save the class/cluster labels of the points as the last column.

sep	The character that will separate attributes in a data point.
append	Append the data to an existing file.
header	A flag that determines if column names will be output (equivalent to col.names in write.table()).
row.names	A flag that determines if row names will be output.
...	Additional parameters that are passed to write.table().

Value

There is no value returned from this operation.

Author(s)

Michael Hahsler

See Also

[write.table](#), [DSD](#)

Examples

```
# creating data and writing it to disk
stream <- DSD_Gaussians(k=3, d=5)
write_stream(stream, file="data.txt", n=10, class=TRUE)

#file.show("data.txt")

# clean up
file.remove("data.txt")
```

Index

`add_cluster` (DSD_MG), 32
`add_keyframe` (MGC), 55
`ani.replay`, 4
`animate` (animation), 3
`animate_cluster`, 5, 25, 49
`animate_cluster` (animation), 3
`animate_data`, 25
`animate_data` (animation), 3
`animation`, 3, 66

`BICO` (DSC_BICO), 5
`bico` (DSC_BICO), 5
`BIRCH` (DSC_BIRCH), 6
`birch` (DSC_BIRCH), 6

`change_alpha` (DSC_DBSTREAM), 9
`cl_agreement`, 49
`close_stream` (DSD_ReadCSV), 36
`cluster`, 5, 25
`cluster.stats`, 49
`connection`, 37

`D-Stream` (DSC_DStream), 11
`d-stream` (DSC_DStream), 11
`dbGetQuery`, 38
`DBSTREAM` (DSC_DBSTREAM), 9
`dbstream` (DSC_DBSTREAM), 9
`description` (DSD), 25
`DSC`, 4, 8, 10, 13, 15–19, 21–24, 45, 51–54, 59, 61, 66
`DSC_BICO`, 5
`DSC_BIRCH`, 6
`DSC_DBSCAN`, 7
`DSC_DBSTREAM`, 9
`DSC_DStream`, 11
`DSC_Hierarchical`, 14
`DSC_Kmeans`, 16
`DSC_Macro`, 8, 15, 16, 19, 22, 23, 58
`DSC_Macro` (DSC_Marco), 17
`DSC_Marco`, 17
`DSC_Micro`, 10, 13, 21, 22, 24
`DSC_Micro` (DSC_Mirco), 18
`DSC_Mirco`, 18
`DSC_R` (DSC), 4
`DSC_Reachability`, 18
`DSC_Sample`, 20
`DSC_Static`, 21, 62
`DSC_TwoStage`, 23
`DSC_Window`, 24
`DSCClassify`, 5, 45
`DSD`, 25, 26–28, 30, 31, 35–38, 40–42, 53, 61, 66, 67
`DSD_BarsAndGaussians`, 26
`DSD_Benchmark`, 27
`DSD_Cubes`, 28
`DSD_Gaussians`, 29
`DSD_Memory`, 30, 35, 63
`DSD_MG`, 32, 56, 63
`DSD_mlbenchData`, 34
`DSD_mlbenchGenerator`, 35
`DSD_MovingGenerator` (DSD_MG), 32
`DSD_R` (DSD), 25
`DSD_ReadCSV`, 36, 63
`DSD_ReadDB`, 38
`DSD_ScaleStream`, 39, 63
`DSD_Target`, 40
`DSD_UniformNoise`, 41
`DSFP`, 42, 45
`DSO`, 42, 44, 45
`DSO_Sample`, 43, 43
`DSO_Window`, 43, 44
`DST`, 5, 42, 45
`dstream` (DSC_DStream), 11

`evaluate`, 5, 25, 46
`evaluate_cluster`, 4
`evaluate_cluster` (evaluate), 46
`get_assignment`, 5, 50
`get_attraction` (DSC_DStream), 11

get_centers, [5](#), [51](#)
get_cluster_assignments (DSC_DBSTREAM),
[9](#)
get_clusters (DSD_MG), [32](#)
get_copy, [5](#), [52](#)
get_keyframes (MGC), [55](#)
get_macroclusters (DSC), [4](#)
get_macroweights (DSC), [4](#)
get_microclusters (DSC), [4](#)
get_microweights (DSC), [4](#)
get_points, [25](#), [43](#), [53](#)
get_shared_density (DSC_DBSTREAM), [9](#)
get_weights, [5](#), [43](#), [54](#)

keyframe (MGC), [55](#)

MGC, [55](#)
MGC_Function, [32](#)
MGC_Function (MGC), [55](#)
MGC_Linear, [32](#)
MGC_Linear (MGC), [55](#)
MGC_Noise, [32](#)
MGC_Noise (MGC), [55](#)
MGC_Random, [32](#)
MGC_Random (MGC), [55](#)
MGC_Shape_Block (MGC), [55](#)
MGC_Shape_Gaussian (MGC), [55](#)
MGC_Static (MGC), [55](#)
microToMacro, [5](#), [58](#)
MovingGenerator (DSD_MG), [32](#)

nclusters, [5](#), [59](#)

plot, [5](#), [25](#), [60](#)
print.stream_eval (evaluate), [46](#)
prune_clusters, [5](#), [61](#)

read.table, [37](#)
readDSC, [5](#)
readDSC (save), [64](#)
readRDS, [64](#)
recluster, [5](#), [25](#), [62](#)
remove_cluster (DSD_MG), [32](#)
remove_keyframe (MGC), [55](#)
reset_stream, [31](#), [35](#), [37](#), [40](#), [63](#)

save, [64](#)
saveDSC, [5](#)
saveDSC (save), [64](#)
saveRDS, [64](#)

scale, [40](#)
scale_stream (DSD_ReadCSV), [36](#)
silhouette, [49](#)

update, [43](#), [65](#)

write.table, [67](#)
write_stream, [25](#), [66](#)