

Package ‘taxotools’

April 17, 2019

Type Package

Title Tools to Handle Taxonomic Lists

Version 0.0.23

Date 2019-04-17

Maintainer Vijay Barve <vijay.barve@gmail.com>

Description Some tools to work with taxonomic name lists.

License CC0

Imports taxize, wikitaxa, plyr, sqldf

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

BugReports <https://github.com/vijaybarve/taxotools/issues>

NeedsCompilation no

Author Vijay Barve [aut, cre] (<<https://orcid.org/0000-0002-4852-2567>>)

Repository CRAN

Date/Publication 2019-04-17 19:00:03 UTC

R topics documented:

BuildCSList	2
cast_cs_field	3
CheckScientificName	4
check_scientific	5
ExpandSyn	5
expand_name	6
GetITISyn	7
GetWikiSyn	7
get_itis_syn	8
GuessTaxoLevel	9
guess_taxo_level	10

ListITISyn	10
list_higher_taxo	11
list_itis_syn	12
list_wiki_syn	13
MakeCanonical	13
make_canonical	14
MatchLists	15
match_lists	16
melt_cs_field	16
taxotools	17

Index	19
--------------	-----------

BuildCSList	<i>Build a comma separated List</i>
-------------	-------------------------------------

Description

This function is depreciated. Please use [cast_cs_field](#)

Usage

```
BuildCSList(data, pri, sec, duplicate = FALSE, sepchar = ",")
```

Arguments

data	data frame containing primary and secondary data columns
pri	Primary field name (repeating values)
sec	Secondary field (values would be added to same record, comma separated)
duplicate	If true, duplicate entries are allowed in secondary field
sepchar	Character separator between the data items. Default is comma

Details

Builds a comma separated list given a data frame with two fiends, primary repeating values and secondary values to be summarized with comma separated in the same field

Value

a data frame with two fields Primary and secondary (comma separated list)

See Also

Other Discontinued functions: [CheckScientificName](#), [ExpandSyn](#), [GetWikiSyn](#), [GuessTaxoLevel](#), [MakeCanonical](#), [MatchLists](#)

Examples

```
## Not run:
scnames <- c("Abrothrix longipilis", "Abrothrix jelskii")
SynList <- GetITISyn(scnames)
BuildCSList(SynList,"Name","Syn")

## End(Not run)
```

cast_cs_field	<i>Build a character (comma) separated List within field</i>
---------------	--

Description

Builds a character (comma) separated list within a field given a data frame with primary field repeating values and secondary field with values to be character separated in the same field (secondary)

Usage

```
cast_cs_field(data, pri, sec, duplicate = FALSE, sepchar = ",")
```

Arguments

data	data frame containing primary and secondary data columns
pri	Primary field name (repeating values)
sec	Secondary field (values would be added to same record, comma separated)
duplicate	If true, duplicate entries are allowed in secondary field
sepchar	Character separator between the data items. Default is comma

Value

a data frame with two fields Primary and secondary (comma separated list)

See Also

Other List functions: [melt_cs_field](#)

Examples

```
## Not run:
scnames <- c("Abrothrix longipilis", "Abrothrix jelskii")
SynList <- list_itis_syn(scnames)
cast_cs_field(SynList,"Name","Syn")

## End(Not run)
```

CheckScientificName *Parse and resolve a scientific name string*

Description

This function is deprecated. Please use [check_scientific](#)

Usage

```
CheckScientificName(name)
```

Arguments

name	scientific name string to be checked
------	--------------------------------------

Details

Parse the names using GBIF parse API to make sure the name passed is an scientific name

Value

Resolved Canonical name and NULL is not matched

See Also

Other Discontinued functions: [BuildCSList](#), [ExpandSyn](#), [GetWikiSyn](#), [GuessTaxoLevel](#), [MakeCanonical](#), [MatchLists](#)

Examples

```
## Not run:  
CheckScientificName("Akodon longipilis (Waterhouse, 1837)")  
CheckScientificName("Mus longipilis Waterhouse, 1837")  
CheckScientificName("Akodon hershkovitzi Patterson, Gallardo, and Freas, 1984")  
  
## End(Not run)
```

check_scientific	<i>Parse and resolve a scientific name string</i>
------------------	---

Description

Parse the name using GNR and GBIF parse API to make sure the name is scientific name

Usage

```
check_scientific(name)
```

Arguments

name	scientific name string to be checked
------	--------------------------------------

Value

Resolved canonical name (NULL if not matched)

See Also

Other Name functions: [expand_name](#), [guess_taxo_level](#), [list_higher_taxo](#)

Examples

```
check_scientific("Akodon longipilis (Waterhouse, 1837)")
check_scientific("Mus longipilis Waterhouse, 1837")
check_scientific("Akodon hershkovitzi Patterson, Gallardo, and Freas, 1984")
```

ExpandSyn	<i>Expands Scientific name is the genus is used with ''</i>
-----------	---

Description

This function is depreciated. Please use [expand_name](#)

Usage

```
ExpandSyn(name, syn)
```

Arguments

name	scientific name
syn	synonym with short form genus name to expand the Genus

Value

Synonym with Genus expanded using either name or previous names in the syn list

See Also

Other Discontinued functions: [BuildCSList](#), [CheckScientificName](#), [GetWikiSyn](#), [GuessTaxoLevel](#), [MakeCanonical](#), [MatchLists](#)

Examples

```
## Not run:
ExpandSyn("Addax gibbosa", "A. mytilopes")
ExpandSyn("Oryx addax", "O. nasomaculatus")

## End(Not run)
```

expand_name	<i>Expands Scientific name</i>
-------------	--------------------------------

Description

At times the genus is specified with first character and '.' rather than repeating genus names every time. These are either synonyms or species of the same genus listed one below another. To convert these names to canonical names, we need to expand the genus name (typically) using previous entry in the list.

Usage

```
expand_name(fullname, shortname)
```

Arguments

fullname	full scientific name
shortname	scientific name with short form genus name to expand the Genus

Value

scientific name with Genus expanded using reference name provided as parameter

See Also

Other Name functions: [check_scientific](#), [guess_taxo_level](#), [list_higher_taxo](#)

Examples

```
expand_name("Addax gibbosa", "A. mytilopes")
expand_name("Oryx addax", "O. nasomaculatus")
```

GetITISSyn	<i>Get ITIS Synonyms for list of names</i>
------------	--

Description

This function is deprecated. Please use [list_itis_syn](#)

Usage

```
GetITISSyn(namelist)
```

Arguments

namelist list of scientific names

Details

Fetch Synonyms from ITIS

Value

a data frame containing names (passed) and synonyms

See Also

Other ITIS functions: [ListITISSyn](#), [get_itis_syn](#), [list_itis_syn](#)

Examples

```
#GetITISSyn("Abrothrix longipilis")
#GetITISSyn(c("Abditomys latidens", "Abeomelomys sevia", "Abrothrix jelskii" ))
```

GetWikiSyn	<i>Get Wikipedia Synonyms for list of names</i>
------------	---

Description

This function is deprecated. Please use [list_wiki_syn](#)

Usage

```
GetWikiSyn(namelist)
```

Arguments

namelist list of scientific names

Details

Fetch Synonyms from Wikipedia and clean them for use

Value

a data frame containing names, synonyms and Canonical synonyms matched with GBIF backbone taxonomy

- Name : Scientific name
- OrigSyn : Original synonym returned by Wikipedia
- Syn : Synonym in canonical form, matched with GBIF

See Also

Other Discontinued functions: [BuildCSList](#), [CheckScientificName](#), [ExpandSyn](#), [GuessTaxoLevel](#), [MakeCanonical](#), [MatchLists](#)

Examples

```
#GetWikiSyn("Abrothrix illutea")  
#GetWikiSyn(c("Abditomys latidens", "Abeomelomys sevia", "Abrocoma schistacea"))
```

get_itis_syn

Get ITIS Synonyms for a Scientific Name

Description

Fetch Synonyms using ITIS web service

Usage

```
get_itis_syn(scname)
```

Arguments

scname Scientific Name

Value

a list containing synonyms

See Also

Other ITIS functions: [GetITISSyn](#), [ListITISSyn](#), [list_itis_syn](#)

Examples

```
get_itis_syn("Abrothrix longipilis")
get_itis_syn("Abditomys latidens")
```

GuessTaxoLevel	<i>Guess the level of Scientific Name</i>
----------------	---

Description

#' This function is deprecated. Please use [match_lists](#)

Usage

```
GuessTaxoLevel(name)
```

Arguments

name scientific name string to be checked

Value

Guess on level of Taxon name and NULL if not sure

See Also

Other Discontinued functions: [BuildCSList](#), [CheckScientificName](#), [ExpandSyn](#), [GetWikiSyn](#), [MakeCanonical](#), [MatchLists](#)

Examples

```
## Not run:
GuessTaxoLevel("Akodon longipilis")
GuessTaxoLevel("Akodon")
GuessTaxoLevel("Abrocoma cinerea shistacea")

## End(Not run)
```

guess_taxo_level *Guess the taxonomic level of Scientific Name*

Description

Guesses the taxonomic level i.e. Genus, Species or Subspecies based on number of words

Usage

```
guess_taxo_level(name)
```

Arguments

name scientific name string to be checked

See Also

Other Name functions: [check_scientific](#), [expand_name](#), [list_higher_taxo](#)

Examples

```
guess_taxo_level("Akodon longipilis")
guess_taxo_level("Akodon")
guess_taxo_level("Abrocoma cinerea shistacea")
```

ListITISSyn *Get list ITIS Synonyms for a Scientific Name*

Description

This function is depreciated. Please use [get_itis_syn](#)

Usage

```
ListITISSyn(scname)
```

Arguments

scname Scientific Name

Details

Fetch Synonyms using ITIS web service

Value

a list containing synonyms

See Also

Other ITIS functions: [GetITISSyn](#), [get_itis_syn](#), [list_itis_syn](#)

Examples

```
#ListITISSyn("Abrothrix longipilis")
#ListITISSyn("Abditomys latidens")
```

list_higher_taxo	<i>Get higher taxonomy data for list of names</i>
------------------	---

Description

Retrieve higher taxonomy information (like Family and Order) for each record from the "Encyclopedia of Life" web API.

Usage

```
list_higher_taxo(indf, canonical, genus = FALSE, verbose = FALSE,
  progress = TRUE)
```

Arguments

indf	input data frame containing taxonomic list
canonical	field name containing scientific names
genus	If TRUE, use only genus level data to get taxonomy
verbose	If TRUE, displays each name string for which the higher taxonomy is sought
progress	If TRUE prints progress bar and messages on the console.

Details

This function makes use of certain functions in the [taxize](#) package. It scans and retrieves the taxonomic hierarchy for each scientific name (or just genus name) in the data set. When new data are retrieved, they are stored in a local sqlite database, `taxo.db`, for faster further access.

Value

data frame with added / updated columns

- "Kingdom" Kingdom of the Scientific name
- "Phylum" Phylum of the Scientific name
- "Order_" Order of the Scientific name
- "Family" Family of the Scientific name
- "Genus" Genus of the Scientific name

and also saves a local copy of taxonomy downloaded for future use in 'taxo.db' sqlite file

See Also

Other Name functions: [check_scientific](#), [expand_name](#), [guess_taxo_level](#)

Examples

```
## Not run:
inat <- list_higher_taxo(inat)

## End(Not run)
```

list_itis_syn

Get ITIS Synonyms for list of names

Description

Fetch Synonyms from ITIS

Usage

```
list_itis_syn(namelist)
```

Arguments

namelist list of scientific names

Value

a data frame containing names (passed) and synonyms

See Also

Other ITIS functions: [GetITISSyn](#), [ListITISSyn](#), [get_itis_syn](#)

Examples

```
list_itis_syn("Abrothrix longipilis")
#list_itis_syn(c("Abditomys latidens", "Abeomelomys sevia", "Abrothrix jelskii" ))
```

list_wiki_syn	<i>Get Wikipedia Synonyms for list of names</i>
---------------	---

Description

Fetch Synonyms from Wikipedia and clean them for use

Usage

```
list_wiki_syn(namelist)
```

Arguments

namelist list of scientific names

Value

a data frame containing names, synonyms and Canonical synonyms matched with GBIF backbone taxonomy

- Name : Scientific name
- OrigSyn : Original synonym returned by Wikipedia
- Syn : Synonym in canonical form, matched with GBIF

Examples

```
list_wiki_syn("Abrothrix illutea")
#list_wiki_syn(c("Abditomys latidens", "Abeomelomys sevia", "Abrocoma schistacea"))
```

MakeCanonical	<i>Construct canonical names</i>
---------------	----------------------------------

Description

This function is depreciated. Please use [make_canonical](#)

Usage

```
MakeCanonical(dat, genus = "", species = "", subspecies = "")
```

Arguments

dat data frame containing taxonomic list
genus field name for Genus field
species field name for Species field
subspecies field name for Subspecies field

Details

Canonical names using Genus, Species and Subspecies friends

Value

a data frame containing Canonical names field added or repopulated using filed names for Genus, Species and Subspecies specified in parameters

See Also

Other Discontinued functions: [BuildCSList](#), [CheckScientificName](#), [ExpandSyn](#), [GetWikiSyn](#), [GuessTaxoLevel](#), [MatchLists](#)

Examples

```
## Not run:
MakeCanonical(mylist,"genus","species","subspecies")

## End(Not run)
```

make_canonical	<i>Construct canonical names</i>
----------------	----------------------------------

Description

Construct canonical names using Genus, Species and Subspecies fields. At times due to spaces or NAs in the data fields, it makes it tricky to generate canonical names.

Usage

```
make_canonical(dat, genus = "", species = "", subspecies = "")
```

Arguments

dat	data frame containing taxonomic list
genus	field name for Genus field
species	field name for Species field
subspecies	field name for Subspecies field

Value

a data frame containing Canonical names field added or repopulated using filed names for Genus, Species and Subspecies specified in parameters

Examples

```
## Not run:
make_canonical(mylist,"genus","species","subspecies")

## End(Not run)
```

MatchLists	<i>match two taxonomic lists</i>
------------	----------------------------------

Description

This function is deprecated. Please use [match_lists](#)

Usage

```
MatchLists(master, lst, masterfld, lstfld)
```

Arguments

master	master taxonomic list
lst	match taxonomic list
masterfld	field name for canonical name in master list
lstfld	field name for canonical name in match list

Details

match two taxonomic lists using canonical names

Value

a list with two data frames containing matched and non-matched names from the master list

See Also

Other Discontinued functions: [BuildCSList](#), [CheckScientificName](#), [ExpandSyn](#), [GetWikiSyn](#), [GuessTaxoLevel](#), [MakeCanonical](#)

Examples

```
## Not run:
MatchLists(master,lst,"canonical", "canonical")

## End(Not run)
```

match_lists	<i>match two taxonomic lists</i>
-------------	----------------------------------

Description

match two taxonomic lists using canonical names

Usage

```
match_lists(master, checklist, masterfld, checklistfld)
```

Arguments

master	master taxonomic list
checklist	match taxonomic list
masterfld	field name for canonical name in master list
checklistfld	field name for canonical name in match list

Value

a list with two data frames containing matched and non-matched names from the master list

Examples

```
## Not run:
match_lists(master, checklist, "canonical", "canonical")

## End(Not run)
```

melt_cs_field	<i>Build a list separating character (comma) separated field into separate records</i>
---------------	--

Description

Builds a list separating character (comma) separated field given a data frame with a field with repeating values

Usage

```
melt_cs_field(data, pri, sepchar = ",")
```


Arguments

<code>data</code>	data frame containing a data columns with character(comma) separated values
<code>pri</code>	Primary field name with character(comma) separated values
<code>sepchar</code>	Character separator between the data items. Default is comma

Value

a data frame with separate records for each value in primary field specified

See Also

Other List functions: [cast_cs_field](#)

Examples

```
## Not run:
scnames <- c("Abrothrix longipilis", "Abrothrix jelskii")
syn_list <- list_itis_syn(scnames)
cs_syn_list <- cast_cs_field(syn_list, "Name", "Syn")
syn_list_new <- melt_cs_field(cs_syn_list, "Syn")

## End(Not run)
```

taxotools

taxotools: Tools to handle taxonomic data

Description

Some tools to work with lists taxonomic names.

List functions

- [cast_cs_field](#)
- [melt_cs_field](#)
- [match_lists](#)

Name functions

- [expand_name](#)
- [check_scientific](#)
- [guess_taxo_level](#)
- [make_canonical](#)
- [list_higher_taxo](#)

ITIS functions

- [get_itis_syn #'](#)
- [list_itis_syn](#)

Wiki functions

- [list_wiki_syn](#)

Discontinued functions

- [MatchLists](#)
- [BuildCSList](#)
- [ExpandSyn](#)
- [CheckScientificName](#)
- [GuessTaxoLevel](#)
- [MakeCanonical](#)
- [GetWikiSyn](#)
- [GetITISyn](#)
- [ListITISyn](#)

Citation

- Barve, V., (2019). taxotools: Tools to handle taxonomic data (R package V 0.0.20). Retrieved from <https://cran.r-project.org/web/packages/taxotools/index.html>

Index

BuildCSList, [2](#), [4](#), [6](#), [8](#), [9](#), [14](#), [15](#), [18](#)

cast_cs_field, [2](#), [3](#), [17](#)

check_scientific, [4](#), [5](#), [6](#), [10](#), [12](#), [17](#)

CheckScientificName, [2](#), [4](#), [6](#), [8](#), [9](#), [14](#), [15](#), [18](#)

expand_name, [5](#), [6](#), [10](#), [12](#), [17](#)

ExpandSyn, [2](#), [4](#), [5](#), [8](#), [9](#), [14](#), [15](#), [18](#)

get_itis_syn, [7](#), [8](#), [10–12](#), [18](#)

GetITISSyn, [7](#), [8](#), [11](#), [12](#), [18](#)

GetWikiSyn, [2](#), [4](#), [6](#), [7](#), [9](#), [14](#), [15](#), [18](#)

guess_taxo_level, [5](#), [6](#), [10](#), [12](#), [17](#)

GuessTaxoLevel, [2](#), [4](#), [6](#), [8](#), [9](#), [14](#), [15](#), [18](#)

list_higher_taxo, [5](#), [6](#), [10](#), [11](#), [17](#)

list_itis_syn, [7](#), [8](#), [11](#), [12](#), [18](#)

list_wiki_syn, [7](#), [13](#), [18](#)

ListITISSyn, [7](#), [8](#), [10](#), [12](#), [18](#)

make_canonical, [13](#), [14](#), [17](#)

MakeCanonical, [2](#), [4](#), [6](#), [8](#), [9](#), [13](#), [15](#), [18](#)

match_lists, [9](#), [15](#), [16](#), [17](#)

MatchLists, [2](#), [4](#), [6](#), [8](#), [9](#), [14](#), [15](#), [18](#)

melt_cs_field, [3](#), [16](#), [17](#)

taxize, [11](#)

taxotools, [17](#)

taxotools-package (taxotools), [17](#)