

Package ‘tsdb’

April 2, 2019

Type Package

Title Terribly-Simple Data Base for Time Series

Version 0.6-2

Date 2019-03-31

Maintainer Enrico Schumann <es@enricoschumann.net>

Description A terribly-simple data base for numeric time series, written purely in R, so no external database-software is needed. Series are stored in plain-text files (the most-portable and enduring file type) in CSV format. Timestamps are encoded using R's native numeric representation for 'Date'/'POSIXct', which makes them fast to parse, but keeps them accessible with other software. The package provides tools for saving and updating series in this standardised format, for retrieving and joining data, for summarising files and directories, and for coercing series from and to other data types (such as 'zoo' series).

License GPL-3

Imports datetimeutils, fastmatch, utils, zoo

Suggests DBI, MonetDBLite, data.table

URL <http://enricoschumann.net/R/packages/tsdb>,
<https://github.com/enricoschumann/tsdb>,
<https://gitlab.com/enricoschumann/tsdb>

NeedsCompilation no

Author Enrico Schumann [aut, cre] (<<https://orcid.org/0000-0001-7601-6576>>)

Repository CRAN

Date/Publication 2019-04-02 15:40:02 UTC

R topics documented:

tsdb-package	2
as.ts_table	3
file_info	4
read_ts_tables	5
ts_table	6
ttime	8
write_ts_table	9

Index	11
--------------	-----------

tsdb-package	<i>Terribly-Simple Database for Time Series</i>
--------------	---

Description

A terribly-simple data base for numeric time series, written purely in R, so no external database-software is needed. Series are stored in plain-text files (the most-portable and enduring file type) in CSV format; timestamps are encoded using R's native numeric representation for `Date/POSIXct`, which makes them fast to parse, but keeps them accessible with other software. The package provides tools for saving and updating series in this standardised format, for retrieving and joining data, for summarising files and directories, and for coercing series from and to other data types (such as 'zoo' series).

Details

See the functions `ts_table` and `as.ts_table` for creating a `ts_table`.

See `write_ts_table` and `read_ts_tables` for storing and loading a `ts_table` (or several).

See the tutorial at <https://gitlab.com/enricoschumann/tsdb/blob/master/README.org> or <https://github.com/enricoschumann/tsdb/blob/master/README.org>.

Author(s)

Enrico Schumann

See Also

`ts_table` and `as.ts_table` for creating a `ts_table`

`write_ts_table` and `read_ts_tables` for storing and loading a `ts_table`

as.ts_table	<i>Coerce to ts_table</i>
-------------	---------------------------

Description

Coerce objects to `ts_table`

Usage

```
as.ts_table(x, ...)
```

```
## S3 method for class 'zoo'  
as.ts_table(x, columns, ...)
```

Arguments

<code>x</code>	object to be coerced to <code>ts_table</code>
<code>columns</code>	character
<code>...</code>	arguments to be passed to other methods

Details

A generic function for coercing objects to class `ts_table`.

Value

a `ts_table`

Author(s)

Enrico Schumann

See Also

[read_ts_tables](#)

Examples

```
library("zoo")  
as.ts_table(zoo(1:5, Sys.Date()-5:1), ## note that the "columns"  
            columns = "value")      ## must be specified
```

`file_info`*Information about Data File*

Description

Provides information about data stored in file: columns, number of observations, range of timestamps.

Usage

```
file_info(dir, file)
```

Arguments

<code>dir</code>	character
<code>file</code>	character

Details

Provide information, such as number of entries, of specified files.

It is recommended that code that uses the returned information to alter or write tables, should explicitly check whether a table exists (column exists in the returned `data.frame`). For instance, a value of `NA` for `min.timestamp` would occur for a non-existing file, but also if the file could not be read for some reason.

Value

An object of type `file_info`, which is a `data.frame` with information such as whether a file exists, minimum and maximum timestamp, and more.

Author(s)

Enrico Schumann

See Also

[ts_table](#)

Examples

```
ts <- ts_table(1:3, as.Date("2018-12-3") + 1:3, columns = "A")
d <- tempdir()
write_ts_table(ts, file = "temp", dir = d)
file_info(d, "temp")
```

read_ts_tables *Read Time-Series Data from Files*

Description

Read time-series data from files and merge them.

Usage

```
read_ts_tables(file, dir, t.type = "guess",
               start, end, columns,
               return.class = NULL,
               drop.weekends = TRUE,
               column.names = "%dir%/%file%::%column%",
               backend = "csv",
               read.fn = NULL,
               frequency = "1 sec")
```

Arguments

file	character
dir	character
t.type	character: guess, Date or POSIXct
start	character
end	character
columns	character.
return.class	NULL (default) or character: if NULL, a list is returned. Also supported are zoo , data.frame and ts_table .
drop.weekends	logical
column.names	character: a format string for column names; may contain %dir%, %file%, and %column%
backend	character: currently, only 'csv' is fully supported
read.fn	NULL or character: use 'fread' to use fread from package data.table
frequency	character: only used when t.type is POSIXct (or guessed to be POSIXct)

Details

Read time-series data from CSV files.

Value

When return.class is NULL, a list:

data	a numeric matrix
timestamp	Date or POSIXct
columns	character
file.path	character

Author(s)

Enrico Schumann

See Also

[write_ts_table](#)

Examples

```
t1 <- ts_table(1:3, as.Date("2018-12-3") + 1:3, columns = "A")
t2 <- ts_table(4:5, as.Date("2018-12-3") + 1:2, columns = "A")

d <- tempdir() ## this is just an example.
               ## Actual (valuable) data should never
               ## be stored in a tempdir!

write_ts_table(t1, dir = d, file = "t1")
write_ts_table(t2, dir = d, file = "t2")

read_ts_tables(c("t1", "t2"),
              dir = d, columns = "A",
              return.class = "zoo",
              column.names = "%file%.%column%")
```

ts_table

Create ts_table

Description

Create a ts_table.

Usage

```
ts_table(data, timestamp, columns)
```

Arguments

data	numeric
timestamp	Date or POSIXct
columns	column names

Details

Create a time-series table (`ts_table`). A `ts_table` is a numeric matrix, so there is always a `dim` attribute. For a `ts_table` `x`, you get the number of observations with `dim(x)[1L]`.

Attached to this matrix are several attributes:

timestamp a vector: the numeric representation of the timestamp

t.type character: the class of the original timestamp, either `Date` or `POSIXct`

columns a character vector that provides the columns names

There may be other attributes as well, but these three are always present.

Timestamps must be of class `Date` or `POSIXct` (`POSIXlt` is converted). A `tzone` attribute is dropped.

A `ts_table` is not meant as a time-series class. For most computations (plotting, calculation of statistics, etc.), the `ts_table` must first be coerced to `zoo`, `xts`, a `data.frame` or a similar data structure. Methods that perform such coercions are responsible for converting the numeric timestamp vector to an actual timestamp. For this, they may use the function `ttime` ('translate time').

Value

a `ts_table`

Author(s)

Enrico Schumann

See Also

[as.ts_table](#)

Examples

```
ts_table(1:5, Sys.Date() - 5:1, columns = "value")
```

ttime *Translate Timestamps*

Description

Translate a vector of timestamps.

Usage

```
ttime(x, from = "datetime", to = "numeric", tz = "",
      strip.attr = TRUE, format = "%Y-%m-%d")
```

Arguments

x	numeric
from	character
to	character
tz	character
strip.attr	logical: strip attributes; in particular, timezone information
format	character

Details

ttime ('translate time') converts timestamps between formats.

Author(s)

Enrico Schumann

See Also

[ts_table](#)

Examples

```
ttime(Sys.Date())
ttime(17397, from = "numeric", to = "Date")
```

write_ts_table	<i>Write Time-Series Data to File</i>
----------------	---------------------------------------

Description

Write time-series data to files.

Usage

```
write_ts_table(ts, dir, file, add = FALSE, overwrite = FALSE,  
              replace.file = FALSE, backend = "csv")
```

Arguments

ts	a ts_table
dir	character
file	character
add	logical: if TRUE, add data with timestamps that are not in a file.
overwrite	logical: overwrite existing file when data differs. overwrite implies add.
replace.file	logical: if TRUE, an existing file is deleted and replaced by a new file (i.e. containing ts)
backend	character: currently, csv and monetdb are supported

Details

The function takes a ts_table and writes it to a file.

If the file already exists and both add and overwrite are FALSE (the default), nothing is written.

When add is TRUE, the function checks if ts contains timestamps not yet in the file and, if there are any, writes only those data.

When overwrite is TRUE, the function merges all observations in the file with those in ts and writes the result back to the file. If ts contains timestamps that were already in the file, the data in the file are overwritten. Note that no data will be removed from the file: timestamps not in ts remain unchanged in the file.

Value

Invisibly, the number of data rows written to a file.

Author(s)

Enrico Schumann

See Also

[read_ts_tables](#)

Examples

```
t1 <- ts_table(1:3, as.Date("2018-12-3") + 1:3, columns = "A")
t2 <- ts_table(4:5, as.Date("2018-12-3") + 1:2, columns = "A")

d <- tempdir() ## this is just an example.
               ## Actual (valuable) data should never
               ## be stored in a tempdir!

write_ts_table(t1, dir = d, file = "t1")
write_ts_table(t2, dir = d, file = "t2")

read_ts_tables(c("t1", "t2"),
               dir = d, columns = "A",
               return.class = "zoo",
               column.names = "%file%.%column%")
```

Index

`as.ts_table`, [2](#), [3](#), [7](#)

`data.frame`, [4](#), [5](#), [7](#)

`Date`, [2](#), [7](#)

`file_info`, [4](#)

`fread`, [5](#)

`NA`, [4](#)

`POSIXct`, [2](#), [7](#)

`POSIXlt`, [7](#)

`read_ts_tables`, [2](#), [3](#), [5](#), [9](#)

`ts_table`, [2–5](#), [6](#), [8](#)

`tsdb` (`tsdb`-package), [2](#)

`tsdb`-package, [2](#)

`ttime`, [7](#), [8](#)

`write_ts_table`, [2](#), [6](#), [9](#)