

Package ‘PBSddesolve’

March 12, 2019

Version 1.12.4

Date 2019-03-11

Title Solver for Delay Differential Equations

Author Alex Couture-Beil [aut],
Jon T. Schnute [aut],
Rowan Haigh [aut, cre],
Simon N. Wood [aut],
Benjamin J. Cairns [aut],
Nicholas Boers [ctb]

Maintainer Rowan Haigh <rowan.haigh@dfo-mpo.gc.ca>

Copyright 2007-2019, Fisheries and Oceans Canada

Depends R (>= 3.5.0)

Suggests PBSmodelling

NeedsCompilation yes

Description Routines for solving systems of delay differential equations by interfacing numerical routines written by Simon N. Wood , with contributions by Benjamin J. Cairns. These numerical routines first appeared in Simon Wood's 'solv95' program. This package includes a vignette and a complete user's guide. 'PBSddesolve' originally appeared on CRAN under the name 'ddesolve'. That version is no longer supported. The current name emphasizes a close association with other PBS packages, particularly 'PBSmodelling'.

License GPL (>= 2)

URL <https://github.com/pbs-software/pbs-ddesolve>

Repository CRAN

Date/Publication 2019-03-12 17:36:09 UTC

R topics documented:

dde	2
pastvalue	4
PBSddesolve	5

Index	6
--------------	----------

Description

A solver for systems of delay differential equations based on numerical routines from [Simon Wood's solv95](#) program. This solver is also capable of solving systems of ordinary differential equations.

Please see the included demos for examples of how to use dde.

To view available demos run `demo(package="PBSddesolve")`.

The supplied demos require that the R package **PBSmodelling** be installed.

Usage

```
dde(y, times, func, parms=NULL, switchfunc=NULL, mapfunc=NULL,
    tol=1e-08, dt=0.1, hbsize=10000)
```

Arguments

y	Vector of initial values of the DDE system. The size of the supplied vector determines the number of variables in the system.
times	Numeric vector of specific times to solve.
func	A user supplied function that computes the gradients in the DDE system at time <i>t</i> . The function must be defined using the arguments: (<i>t</i> , <i>y</i>) or (<i>t</i> , <i>y</i> , <i>parms</i>), where <i>t</i> is the current time in the integration, <i>y</i> is a vector of the current estimated variables of the DDE system, and <i>parms</i> is any R object representing additional parameters (optional). The argument <i>func</i> must return one of the two following return types: 1) a vector containing the calculated gradients for each variable; or 2) a list with two elements - the first a vector of calculated gradients, the second a vector (possibly named) of values for a variable specified by the user at each point in the integration.
parms	Any constant parameters to pass to <i>func</i> , <i>switchfunc</i> , and <i>mapfunc</i> .
switchfunc	An optional function that is used to manipulate state values at given times. The switch function takes the arguments (<i>t</i> , <i>y</i>) or (<i>t</i> , <i>y</i> , <i>parms</i>) and must return a numeric vector. The size of the vector determines the number of switches used by the model. As values of <i>switchfunc</i> pass through zero (from positive to negative), a corresponding call to <i>mapfunc</i> is made, which can then modify any state value.
mapfunc	If <i>switchfunc</i> is defined, then a map function must also be supplied with arguments (<i>t</i> , <i>y</i> , <i>switch_id</i>) or (<i>t</i> , <i>y</i> , <i>switch_id</i> , <i>parms</i>), where <i>t</i> is the time, <i>y</i> are the current state values, <i>switch_id</i> is the index of the triggered switch, and <i>parms</i> are additional constant parameters.
tol	Maximum error tolerated at each time step (as a proportion of the state variable concerned).

dt	Maximum initial time step.
hbsize	History buffer size required for solving DDEs.

Details

The user supplied function `func` can access past values (lags) of `y` by calling the `pastvalue` function. Past gradients are accessible by the `pastgradient` function. These functions can only be called from `func` and can only be passed values of `t` greater or equal to the start time, but less than the current time of the integration point. For example, calling `pastvalue(t)` is not allowed, since these values are the current values which are passed in as `y`.

Value

A data frame with one column for `t`, a column for every variable in the system, and a column for every additional value that may (or may not) have been returned by `func` in the second element of the list.

If the initial `y` values parameter was named, then the solved values column will use the same names. Otherwise `y1`, `y2`, ... will be used.

If `func` returned a list, with a named vector as the second element, then those names will be used as the column names. If the vector was not named, then `extra1`, `extra2`, ... will be used.

Author(s)

Alex Couture-Beil <alex@mofoc.ca>

Maintainer: **Rowan Haigh**, Program Head – Offshore Rockfish
 Pacific Biological Station (PBS), Fisheries & Oceans Canada (DFO), Nanaimo BC
locus opus: Institute of Ocean Sciences (IOS), Sidney BC
 Last modified Rd: 2019-03-07

See Also

[pastvalue](#)

Examples

```
#####
# This is just a single example of using dde.
# For more examples see demo(package="PBSdresolve")
# the demos require the package PBSmodelling
#####

require(PBSdresolve)
local(env=.PBSddeEnv, expr={
  #create a func to return dde gradient
  yprime <- function(t,y,parms) {
    if (t < parms$tau)
      lag <- parms$initial
    else
      lag <- pastvalue(t - parms$tau)
    y1 <- parms$a * y[1] - (y[1]^3/3) + parms$m * (lag[1] - y[1])
  }
})
```

```

    y2 <- y[1] - y[2]
    return(c(y1,y2))
  }

  #define initial values and parameters
  yinit <- c(1,1)
  parms <- list(tau=3, a=2, m=-10, initial=yinit)

  # solve the dde system
  yout <- dde(y=yinit,times=seq(0,30,0.1),func=yprime,parms=parms)

  # and display the results
  plot(yout$time, yout$y1, type="l", col="red", xlab="t", ylab="y",
       ylim=c(min(yout$y1, yout$y2), max(yout$y1, yout$y2)))
  lines(yout$time, yout$y2, col="blue")
  legend("topleft", legend = c("y1", "y2"),lwd=2, lty = 1,
        xjust = 1, yjust = 1, col = c("red","blue"))
})

```

pastvalue

Retrieve Past Values (lags) During Gradient Calculation

Description

These routines provides access to variable history at lagged times. The lagged time t must not be less than t_0 , nor should it be greater than the current time of gradient calculation. The routine cannot be directly called by a user, and will only work during the integration process as triggered by the dde routine.

Usage

```

pastvalue(t)
pastgradient(t)

```

Arguments

t Access history at time t .

Value

Vector of variable history at time t .

Author(s)

Alex Couture-Beil <alex@mofa.ca>

Maintainer: **Rowan Haigh**, Program Head – Offshore Rockfish
 Pacific Biological Station (PBS), Fisheries & Oceans Canada (DFO), Nanaimo BC
locus opus: Institute of Ocean Sciences (IOS), Sidney BC
 Last modified Rd: 2019-03-07

See Also[dde](#)

`PBSddesolve`*Package: Solver for Delay Differential Equations*

Description

A solver for systems of delay differential equations based on numerical routines from **Simon Wood**'s `solv95` program. This solver is also capable of solving systems of ordinary differential equations.

Details

Please see the user guide `PBSddesolve-UG.pdf`, located in R's library directory `./library/PBSddesolve/doc`, for a comprehensive overview.

Author(s)

Alex Couture-Beil <alex@mofoc.ca>

Jon T. Schnute <schnutej-dfo@shaw.ca>

Rowan Haigh <rowan.haigh@dfo-mpo.gc.ca>

Maintainer: **Rowan Haigh**, Program Head – Offshore Rockfish

Pacific Biological Station (PBS), Fisheries & Oceans Canada (DFO), Nanaimo BC

locus opus: Institute of Ocean Sciences (IOS), Sidney BC

Last modified Rd: 2019-03-07

References

Wood, S.N. (1999) `Solv95`: a numerical solver for systems of delay differential equations with switches. Saint Andrews, UK. 10 pp.

See Also[dde](#)

Index

*Topic **math**

dde, [2](#)

pastvalue, [4](#)

*Topic **package**

PBSddesolve, [5](#)

dde, [2](#), [5](#)

pastgradient, [3](#)

pastgradient (pastvalue), [4](#)

pastvalue, [3](#), [4](#)

PBSddesolve, [5](#)

PBSddesolve-package (PBSddesolve), [5](#)