

Package ‘behaviorchange’

January 17, 2019

Type Package

Title Tools for Behavior Change Researchers and Professionals

Version 0.1.0

Date 2019-01-16

Maintainer Gjalt-Jorn Peters <gjalt-jorn@a-bc.eu>

License GPL (>= 3)

Description Contains specialised analyses and visualisation tools for behavior change science. These facilitate conducting determinant studies (for example, using confidence interval-based estimation of relevance, CIBER, or CIBERlite plots), systematically developing, reporting, and analysing interventions (for example, using acyclic behavior change diagrams or ABCDs), and reporting about intervention effectiveness (for example, using the Numbers Needed for Change). This package is especially useful for researchers in the field of behavior change or health psychology and to behavior change professionals such as intervention developers and prevention workers.

URL <https://a-bc.eu/R/behaviorchange>

BugReports <https://github.com/academy-of-behavior-change/behaviorchange/issues>

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

Depends R (>= 3.0.0)

Imports BiasedUrn (>= 1.07), data.tree (>= 0.7.5), DiagrammeR (>= 1.0.0), ggplot2 (>= 2.2.1), googlesheets (>= 0.3.0), gridExtra (>= 2.3), gtable (>= 0.2.0), magrittr (>= 0.1.5), methods (>= 3.0.0), ufs (>= 0.1.0), userfriendlyscience (>= 0.7.1), viridis (>= 0.5.1)

Suggests knitr, rmarkdown

VignetteBuilder knitr

NeedsCompilation no

Author Gjalt-Jorn Peters [aut, cre, ctb]

Repository CRAN

Date/Publication 2019-01-17 14:10:08 UTC

R topics documented:

abcd	2
abcd_specs_examples	5
apply_graph_theme	6
CIBER	7
convert.threshold.to.er	10
determinantStructure	13
detStructAddVarLabels	15
nnc	18

Index	21
--------------	-----------

abcd	<i>Acyclic Behavior Change Diagram</i>
------	--

Description

This function generates an acyclic behavior change diagram (ABCD) from a specification in a google sheet or .csv file. An ABCD is a logic model that illustrates the assumptions underlying a behavior change intervention. Specifically, the ABCD shows the assumed causal and structural assumptions, thereby showing what is assumed to cause what (e.g. which elements of the intervention are assumed to influence which aspects of the target population's psychology?) and what is assumed to consist of what (e.g. which determinants are assumed to contain which specific aspects of the target population's psychology?).

Usage

```
abcd(specs, specCols = c("bcps", "cnds", "apps", "sdts", "dets", "pobs",
  "behs"), omitColOrder = c("cnds", "behs", "bcps", "apps"),
  localBackup = NULL, title = "Acyclic Behavior Change Diagram\n\n",
  outputFile = NULL, outputWidth = 3000, outputHeight = 1500,
  includeColNames = TRUE, maxLabelLength = 30, silent = FALSE,
  returnGraphOnly = FALSE,
  regExReplacements = list(c("\\\\'", "'"), c("\\'", "'"), c("\\\\", "/")))

## S3 method for class 'abcdiagram'
print(x, width = x$input$width,
  height = x$input$height,
  title = DiagrammeR::get_graph_name(x$output$graph), ...)
```

Arguments

specs	The specifications: either a google sheets URL, the path to a local file, a character vector with both, or a matrix or data frame
specCols	The order of the columns. This character vector specified the order of the elements of an ABCD. In the default order, from left to right, these are (see below for definitions and more details): <ul style="list-style-type: none"> • bcps = Behavior Change Principles (BCPs); • cnds = Conditions for effectiveness; • apps = Applications; • sdts = Sub-determinants; • dets = Determinants; • pobs = Performance Objectives; • behs = Behaviors;
omitColOrder	If not all seven columns are available in the specifications, this character vector specifies which columns are assumed to be omitted.
localBackup	Whether to write the specifications to a local backup
title	The title of the diagram
outputFile	If specified, the ABCD is written to this file using DiagrammeR::export_graph .
outputWidth, outputHeight	If an outputFile is specified, these determine its width and height (in pixels)
includeColNames	Whether to include the column names as titles/legend for the entities in each 'column' of the ABCD.
maxLabelLength	At which width to word wrap the labels.
silent	Whether to suppress (TRUE) or show (FALSE) more detailed information.
returnGraphOnly	Whether to return the full results object or only the DiagrammeR::DiagrammeR graph.
regExReplacements	A list of pairs of regular expressions that will be applied to the specifications before generating the ABCD. This can be used to sanitize problematic characters (e.g. ', " and).
x	The ABCD object to print (as generated by a call to abcd).
width, height	Width and height to use when printing the ABCD.
...	Any additional arguments are passed on to DiagrammeR::render_graph() .

Details

Specifically, a full ABCD is a model that shows the following elements:

- **Behavior Change Principles (BCPs)**: The specific psychological principles engaged to influence the relevant sub-determinants, usually selected using the determinants to which the sub-determinants 'belong'. These are also known as methods of behavior change in the Intervention Mapping framework, or behavior change techniques, BCTs, in the Behavior Change Wheel approach. For a list of 99 BCPs, see Kok et al. (2016).

- **Conditions for effectiveness:** The conditions that need to be met for a Behavior Change Principle (BCP) to be effective. These conditions depend on the specific underlying Evolutionary Learning Processes (ELPs) that the BCP engages (Crutzen & Peters, 2018). If the conditions for effectiveness (called *parameters* for effectiveness in the Intervention Mapping framework) are not met, the method will likely not be effective, or at least, not achieve its maximum effectiveness.
- **Applications:** Since BCP's describe aspects of human psychology in general, they are necessarily formulated on a generic level. Therefore, using them in an intervention requires translating them to the specific target population, culture, available means, and context. The result of this translation is the application of the BCP. Multiple BCPs can be combined into one application; and one BCP can be applied in multiple applications (see Kok, 2014).
- **Sub-determinants:** Behavior change interventions engage specific aspects of the human psychology (ideally, they specifically, target those aspects found most important in predicting the target behavior, as can be established with CIBER plots. These aspects are called sub-determinants (the Intervention Mapping framework references *Change Objectives*, which are sub-determinants formulated according to specific guidelines). In some theoretical traditions, sub-determinants are called *beliefs*.
- **Determinants:** The overarching psychological constructs that are defined as clusters of specific aspects of the human psychology that explain humans' behavior (and are targeted by behavior change interventions). Psychological theories contain specific definitions of such determinants, and make statements about how they relate to each other and to human behavior. There are also theories (and exists empirical evidence) on how these determinants can be changed (i.e. BCPs), so although the sub-determinants are what is targeted in an intervention, the selection of feasible BCPs requires knowing to which determinants those sub-determinants belong.
- **Performance objectives:** The specific sub-behaviors that often underlie (or make up) the ultimate target behavior. These are distinguished from the overarching target behavior because the relevant determinants of these sub-behaviors can be different: for example, the reasons why people do or do not *buy* condoms can be very different from the reasons why they do or do not *carry* condoms or why they do or do not *negotiate* condom use with a sexual partner.
- **Behavior:** The ultimate target behavior of the intervention, usually an umbrella that implicitly contains multiple performance objectives.

For details, see Peters et al. (2019).

Value

A list consisting of an input, intermediate, and output list, where the ABCD is stored in the output list as a [DiagrammeR::DiagrammeR](#) called graph.

Author(s)

Gjalt-Jorn Peters, <gjalt-jorn@bc.eu>, with contributions from Matti Heino and Sander Eggers.

References

Crutzen, R., & Peters, G.-J. Y. (2018). Evolutionary learning processes as the foundation for behaviour change. *Health Psychology Review*, 12(1), 43–57. <https://doi.org/10.1080/17437199.2017.1362569>

Kok, G. (2014). A practical guide to effective behavior change: How to apply theory- and evidence-based behavior change methods in an intervention. *European Health Psychologist*, 16(5), 156–170. <https://doi.org/10.31234/osf.io/r78wh>

Kok, G., Gottlieb, N. H., Peters, G.-J. Y., Mullen, P. D., Parcel, G. S., Ruiters, R. A. C., ... Bartholomew, L. K. (2016). A taxonomy of behavior change methods: an Intervention Mapping approach. *Health Psychology Review*, 10(3), 297–312. <https://doi.org/10.1080/17437199.2015.1077155>

Peters, G.-J. Y., et al. (2019) The core of behavior change: introducing the Acyclic Behavior Change Diagram to report and analyze interventions.

Examples

```
### Using 'print' to prevent pkgdown() from choking
### Partial acyclic behavior change diagram of only
### one performance objective (sub-behavior)
### (using the 'abcd_specs_single_po_without_conditions'
### dataset in this package)
print(behaviorchange::abcd(behaviorchange::abcd_specs_single_po_without_conditions));

### Acyclic behavior change diagram including multiple
### sub-behaviors (performance objectives)
### (using the 'abcd_specs_complete' dataset in this
### package)
print(behaviorchange::abcd(behaviorchange::abcd_specs_complete));
```

abcd_specs_examples *Simple example datasets for ABCD's*

Description

This are three (nested) datasets illustrating the logic model of change for a simple condom use intervention in a way that can be visualised using the `abcd` function. The full dataset is `abcd_specs_full`, a subset that does not explicitly include the conditions for effectiveness (instead showing letters that can then be explained in, for example, the manuscript text) is called `abcd_specs_without_conditions`, and a version that only contains the information about one sub-behavior (performance objective) is available as `abcd_specs_single_po_without_conditions`. The variables in the full dataset are:

Usage

```
data(abcd_specs_complete)
```

Format

For `abcd_specs_complete`, a data frame with 7 variables and 7 rows; for `abcd_specs_without_conditions`, a data frame with 6 variables and 7 rows; for `abcd_specs_single_po_without_conditions`, a data frame with 5 variables and 4 rows;

Details

- Behavior Change Principles: The behavior change principles (BCPs), also known as methods for behavior change or 'behavior change techniques' (BCTs), that describe the psychological principles that are assumed to realise the change in the (sub-)determinants.
- Conditions for effectiveness (e.g. parameters for use): The conditions for effectiveness that describe the constraints and considerations taken into account in the translation of the BCPs to practical applications for the relevant target population, context, culture, etc.
- Applications: The applications of these BCPs. Where the BCPs describe theoretical principles, the applications are more or less tangible intervention elements.
- Sub-determinants (e.g. beliefs; can be formulated as Change Objectives): The specific aspects of the target population's psychology that are targeted by the BCPs (e.g. beliefs, or in Intervention Mapping vocabulary, Change Objectives).
- Determinants: The determinants, psychological constructs, that the targeted sub-determinants are a part of, and that together predict the Performance Objectives (sub-behaviors).
- Performance Objectives: Explicitly defined sub-behaviors at a level of specificity that distinguishes them from other sub-behaviors, and that together form the target behavior.
- Target Behavior: The ultimate target behavior, usually defined at a relatively general level.

In addition to these three datasets, a Dutch example specification is included named `abcd_specs_dutch_xtc`.

`apply_graph_theme`

Apply multiple DiagrammeR global graph attributes

Description

Apply multiple DiagrammeR global graph attributes

Usage

```
apply_graph_theme(graph, ...)
```

Arguments

<code>graph</code>	The <code>DiagrammeR::DiagrammeR</code> graph to apply the attributes to.
<code>...</code>	One or more character vectors of length three, where the first element is the attribute, the second the value, and the third, the attribute type (graph, node, or edge).

Value

The `DiagrammeR::DiagrammeR` graph.

Examples

```
abcd_complete <- behaviorchange::abcd(behaviorchange::abcd_specs_complete)$output$graph;
abcd_complete <- apply_graph_theme(abcd_complete,
                                   c("penwidth", 5, "node"),
                                   c("penwidth", 15, "edge"));
```

CIBER

*Confidence Interval-Based Estimation of Relevance (CIBER)***Description**

This function generates a high-level plot consisting of several diamond plots. This function is useful for estimating the relative relevance of a set of determinants of, for example, behavior. The plot in the left hand panel shows each determinant's distribution with a diamond representing the confidence interval. The right hand plot shows the determinants' associations to one or more 'target' variables, such as behavior or determinants of behavior.

Usage

```
CIBER(data, determinants, targets, conf.level = list(means = 0.9999,
  associations = 0.95), subQuestions = NULL, leftAnchors = rep("Lo",
  length(determinants)), rightAnchors = rep("Hi", length(determinants)),
  orderBy = NULL, decreasing = NULL, numberSubQuestions = FALSE,
  generateColors = list(means = c("red", "blue", "green"), associations =
  c("red", "grey", "green")),
  strokeColors = viridis::viridis(length(targets)),
  titlePrefix = "Means and associations with", titleVarLabels = NULL,
  titleSuffix = "", fullColorRange = NULL, associationsAlpha = 0.5,
  returnPlotOnly = TRUE, drawPlot = TRUE, baseSize = 0.8,
  dotSize = 2.5 * baseSize, baseFontSize = 10 * baseSize,
  theme = ggplot2::theme_bw(base_size = baseFontSize), xbreaks = NULL,
  ...)
```

```
detStructCIBER(determinantStructure, data, conf.level = list(means =
  0.9999, associations = 0.95), subQuestions = NULL,
  leftAnchors = rep("Lo", length(determinants)),
  rightAnchors = rep("Hi", length(determinants)), orderBy = 1,
  decreasing = NULL, generateColors = list(means = c("red", "blue",
  "green"), associations = c("red", "grey", "green")),
  strokeColors = NULL, titlePrefix = "Means and associations with",
  titleVarLabels = NULL, titleSuffix = "", fullColorRange = NULL,
  associationsAlpha = 0.5, baseSize = 0.8, dotSize = 2.5 * baseSize,
  baseFontSize = 10 * baseSize, theme = ggplot2::theme_bw(base_size =
  baseFontSize), ...)
```

Arguments

<code>data</code>	The dataframe containing the variables.
<code>determinants</code>	The 'determinants': the predictors (or 'covariates') of the target variables(s) (or 'criteria').
<code>targets</code>	The 'targets' or 'criteria' variables: the variables predicted by the determinants.
<code>conf.level</code>	The confidence levels for the confidence intervals: has to be a named list with two elements: means and associations, specifying the desired confidence levels for the means and associations, respectively. The confidence level for the associations is also used for the intervals for the proportions of explained variance.
<code>subQuestions</code>	The subquestions used to measure each determinants. This can also be used to provide pretty names for the variables if the determinants were not measured by one question each. Must have the same length as determinants.
<code>leftAnchors</code>	The anchors to display on the left side of the left hand panel. If the determinants were measured with one variable each, this can be used to show the anchors that were used for the respective scales. Must have the same length as determinants.
<code>rightAnchors</code>	The anchors to display on the left side of the left hand panel. If the determinants were measured with one variable each, this can be used to show the anchors that were used for the respective scales. Must have the same length as determinants.
<code>orderBy</code>	Whether to sort the determinants. Set to NULL to not sort at all; specify the name or index of one of the targets to sort by the point estimates of the associations with that target variable. Use <code>decreasing</code> to determine whether to sort in ascending or descending order. For convenience, if <code>orderBy</code> is not NULL, but <code>decreasing</code> is, the determinants are sorted in descending (decreasing) order.
<code>decreasing</code>	Whether to sort the determinants. Specify NULL to not sort at all, TRUE to sort in descending order, and FALSE to sort in ascending order. If <code>decreasing</code> is not NULL, but <code>orderBy</code> is NULL, the determinants are sorted by their means. For convenience, if <code>orderBy</code> is not NULL, but <code>decreasing</code> is, the determinants are sorted in descending (decreasing) order.
<code>numberSubQuestions</code>	Whether or not to number the subquestions. If they are numbered, they are numbered from the top to the bottom.
<code>generateColors</code>	The colors to use to generate the gradients for coloring the diamonds representing the confidence intervals. Has to be a named list with two elements: means and associations, specifying the desired colors for the means and associations, respectively.
<code>strokeColors</code>	The palette to use to color the stroke of the confidence intervals for the associations between the determinants and the targets. Successive colors from this palette are used for the targets.
<code>titlePrefix</code>	Text to add before the list of target names and the proportions of explained variance for each target. This plot title also serves as legend to indicate which target 'gets' which each color.

<code>titleVarLabels</code>	Optionally, variable labels to use in the plot title. Has to be the exact same length as targets.
<code>titleSuffix</code>	Text to add after the list of target names and the proportions of explained variance for each target.
<code>fullColorRange</code>	If colors are specified, this can be used to specify which values, for the determinant confidence intervals in the left hand panel, are the minimum and maximum. This is useful if those scores are not actually in the data (e.g. for extremely skewed distributions). If NULL, the range of all individual scores on the determinants is used. For the associations, <code>c(-1, 1)</code> is always used as <code>fullColorRange</code> .
<code>associationsAlpha</code>	The alpha level (transparency) of the confidence interval diamonds in the right hand plot. Value between 0 and 1, where 0 signifies complete transparency (i.e. invisibility) and 1 signifies complete 'opaqueness'.
<code>returnPlotOnly</code>	Whether to return the entire object that is generated (including all intermediate objects) or only the plot.
<code>drawPlot</code>	Whether to draw the plot, or only return it.
<code>baseSize</code>	This can be used to efficiently change the size of most plot elements.
<code>dotSize</code>	This is the size of the points used to show the individual data points in the left hand plot.
<code>baseFontSize</code>	This can be used to set the font size separately from the <code>baseSize</code> .
<code>theme</code>	This is the theme that is used for the plots.
<code>xbreaks</code>	Which breaks to use on the X axis (can be useful to override <code>ggplot2</code> 's defaults).
<code>...</code>	These arguments are passed on to <code>biAxisDiamondPlot</code> (for the left panel) and <code>diamondPlot</code> (for the right panel). Note that all argument are passed to both those functions.
<code>determinantStructure</code>	When using <code>detStructCIBER</code> , the determinant structure as generated by <code>determinantStructure</code> is included here. <code>determinants</code> , <code>targets</code> , <code>subQuestions</code> , <code>leftAnchors</code> , and <code>rightAnchors</code> are then read from the <code>determinantStructure</code> object. In other words: once a <code>determinantStructure</code> has been generated, only <code>dat</code> and <code>determinantStructure</code> have to be provided as argument to generate a CIBER diamond plot.

Details

Details are explained in Crutzen & Peters (2017).

Value

Depending on the value of `returnPlotOnly`, either the plot only (a `gtable` object) or an object containing most objects created along the way (in which case the plot is stored in `$output$plot`).

The plot has width and height attributes which can be used when saving the plot.

References

Crutzen, R., Peters, G.-J. Y., & Noijen, J. (2017). How to Select Relevant Social-Cognitive Determinants and Use them in the Development of Behaviour Change Interventions? Confidence Interval-Based Estimation of Relevance. <http://dx.doi.org/>

See Also

[determinantStructure](#)

Examples

```
## Not run:
CIBER(data=mtcars,
      determinants=c('drat', 'wt', 'am',
                    'gear', 'vs', 'carb'),
      targets=c('mpg', 'cyl'));

## End(Not run)
```

convert.threshold.to.er

Visualising Numbers Needed for Change

Description

These functions can be used to visualise Numbers Needed for Change (or Numbers Needed to Treat). `erDataSeq` is a helper function to generate an Event Rate Data Sequence, and it uses `convert.threshold.to.er` and `convert.er.to.threshold` to convert thresholds to event rates and vice versa.

Usage

```
convert.threshold.to.er(threshold, mean, sd, eventIfHigher = TRUE,
  pdist = stats::pnorm)

convert.er.to.threshold(er, mean, sd, eventIfHigher = TRUE,
  qdist = stats::qnorm)

erDataSeq(er = NULL, threshold = NULL, mean = NULL, sd = NULL,
  eventIfHigher = TRUE, pRange = c(1e-06, 0.99999), xStep = 0.01)

ggNNC(cerDataSeq, d = NULL, eventDesirable = TRUE, r = 1,
  xlab = "Continuous outcome",
  plotTitle = c("Numbers Needed for Change = ", ""),
  theme = ggplot2::theme_bw(), lineSize = 1, cerColor = "#EBF2F8",
  eerColor = "#172F47", cerLineColor = "#888888",
  eerLineColor = "#000000", dArrowColor = "#000000", cerAlpha = 0.66,
```

```

eerAlpha = 0.66, xLim = NULL, xLimAutoDensityTolerance = 0.001,
showLegend = TRUE, verticalLineColor = "#172F47",
desirableColor = "#00FF00", desirableAlpha = 0.2,
undesirableColor = "#FF0000", undesirableAlpha = 0.2,
desirableTextColor = "#009900", undesirableTextColor = "#990000",
dArrowDistance = 0.04 * max(cerDataSeq$density),
dLabelDistance = 0.08 * max(cerDataSeq$density))

```

Arguments

threshold	If the event rate is not available, a threshold value can be specified instead, which is then used in conjunction with the mean (mean) and standard deviation (sd) and assuming a normal distribution to compute the event rate.
mean	The mean of the control group distribution.
sd	The standard deviation (of the control distribution, but assumed to be the same for both distributions).
eventIfHigher	Whether scores above or below the threshold are considered 'an event'.
pdist, qdist	Distributions to use when converting thresholds to event rates and vice versa; defaults to the normal distribution.
er	Event rate to visualise (or convert).
pRange	The range of probabilities for which to so the distribution.
xStep	Precision of the drawn distribution; higher values mean lower precision/granularity/resolution.
cerDataSeq	The cerDataSeq object.
d	The value of Cohen's <i>d</i> .
eventDesirable	Whether an event is desirable or undesirable.
r	The correlation between the determinant and behavior (for mediated NNC's).
xlab	The label to display for the X axis.
plotTitle	The title of the plot; either one character value, this value if used; if two, they are considered a prefix and suffix to be pre/appended to the NNC value.
theme	The theme to use for the plot.
lineSize	The thickness of the lines in the plot.
cerColor	The color to use for the event rate portion of the control group distribution.
eerColor	The color to use for the event rate portion of the experimental group distribution.
cerLineColor	The line color to use for the control group distribution.
eerLineColor	The line color to use for the experimental group distribution.
dArrowColor	The color of the arrow to show the effect size.
cerAlpha	The alpha value (transparency) to use for the control group distribution.
eerAlpha	The alpha value (transparency) to use for the control group distribution.
xLim	This can be used to manually specify the limits for the X axis; if NULL, sensible limits will be derived using xLimAutoDensityTolerance.

xLimAutoDensityTolerance	If xLim is NULL, the limits will be set where the density falls below this proportion of its maximum value.
showLegend	Whether to show the legend (only if showing two distributions).
verticalLineColor	The color of the vertical line used to indicate the threshold.
desirableColor	The color for the desirable portion of the X axis.
desirableAlpha	The alpha for the desirable portion of the X axis.
undesirableColor	The color for the undesirable portion of the X axis.
undesirableAlpha	The color for the undesirable portion of the X axis.
desirableTextColor	The color for the text to indicate the desirable portion of the X axis.
undesirableTextColor	The color for the text to indicate the undesirable portion of the X axis.
dArrowDistance	The distance of the effect size arrow from the top of the distributions.
dLabelDistance	The distance of the effect size label from the top of the distributions.

Details

These functions are used by `nnc()` to show the distributions, and event rates. They probably won't be used much on their own.

Value

`erDataSeq` returns a data sequence; `ggNnc` a `ggplot2::ggplot()`.

Author(s)

Gjalt-Jorn Peters & Stefan Gruijters

Maintainer: Gjalt-Jorn Peters gjalt-jorn@userfriendlyscience.com

References

Gruijters, S. L., & Peters, G. Y. (2019). Gauging the impact of behavior change interventions: A tutorial on the Numbers Needed to Treat. *PsyArXiv*. doi:[10.31234/osf.io/2bau7](https://doi.org/10.31234/osf.io/2bau7)

See Also

[nnc\(\)](#)

Examples

```

### Show distribution for an event rate value of 125
behaviorchange::ggNNC(behaviorchange::erDataSeq(threshold=125, mean=90, sd=30));

### If the event occurs under the threshold instead of
### above it
behaviorchange::ggNNC(behaviorchange::erDataSeq(threshold=125,
                                                mean=90, sd=30,
                                                eventIfHigher = FALSE));

### ... And for undesirable events (note how
### desirability is an argument for ggNNC, whereas
### whether an event occurs 'above' or 'below' the
### threshold is an argument for erDataSeq):
behaviorchange::ggNNC(behaviorchange::erDataSeq(threshold=125,
                                                mean=90, sd=30,
                                                eventIfHigher = FALSE),
                    eventDesirable = FALSE);

### Show event rate for both experimental and
### control conditions, and show the numbers
### needed for change
behaviorchange::ggNNC(behaviorchange::erDataSeq(threshold=125,
                                                mean=90, sd=30),
                    d=.5);

### Illustration of how even with very large effect
### sizes, if the control event rate is very high,
### you'll still need a high number of NNC
behaviorchange::ggNNC(behaviorchange::erDataSeq(er=.9),
                    d=1);

```

determinantStructure *Determinant Structure specification*

Description

These functions can be used to specify a determinant structure: a hierarchical structure of determinants that can then be conveniently plotted and analysed, for example using [detStructCIBER](#). These functions are made to be used together; see the example and the forthcoming article for more information.

Usage

```
determinantStructure(name, selection = NULL, ...)
```

```
determinantVar(name, selection = NULL, ...)
```

```

subdeterminants(name, selection = NULL, ...)

subdeterminantProducts(name, selection = NULL, ...)

## S3 method for class 'determinantStructure'
plot(x, useDiagrammeR = FALSE, ...)

## S3 method for class 'determinantStructure'
print(x, ...)

```

Arguments

name	The name of the variable that is specified.
selection	A regular expression to use to select the variables in a dataframe that are considered items that together form this variable. For determinantStructure, a list can be provided that also contains a named regular expression with the name 'behaviorRegEx', which specifies the name of the behavior to which this determinant structure pertains.
...	Any additional arguments are other determinant structure building functions. These are used to construct the determinant structure 'tree'.
x	The determinantStructure object to print or plot.
useDiagrammeR	Whether to simply use print(plot(x)) (if FALSE) or whether to use data.tree::ToDiagrammeRGraph , tweak it a bit, by setting global graph attributes, and then using DiagrammeR::render_graph (if TRUE).

Details

This family of functions will be explained more in detail in a forthcoming paper.

plot and print methods plot and print a determinantStructure object.

Value

A determinantStructure object, which is a [data.tree](#) object.

Author(s)

Gjalt-Jorn Peters, <gjalt-jorn@bc.eu>

See Also

[detStructAddVarLabels](#), [detStructAddVarNames](#), [detStructComputeProducts](#), [detStructComputeScales](#), [detStructCIBER](#)

Examples

```

determinantStructure('using R',
  list('using R',
    behaviorRegEx = 'some RegEx'),
  determinantVar("Intention",
    "another RegEx",
    determinantVar("Attitude",
      "third RegEX",
      subdeterminants("Likelihood",
        "4th RegEx"),
      subdeterminants("Evaluation",
        "5th RegEx"),
      subdeterminantProducts("attProduct",
        c("4th RegEx",
          "5th RegEx"))),
    determinantVar("perceivedNorm",
      "6th RegEx",
      subdeterminants("Approval",
        "7th RegEx"),
      subdeterminants("Motivation to comply",
        "8th RegEx"),
      subdeterminantProducts("normProduct",
        c("7th RegEx",
          "8th RegEx"))),
    determinantVar("pbc",
      "9th RegEx",
      subdeterminants("Control beliefs",
        "10th RegEx"))));

```

detStructAddVarLabels *Functions to preprocess determinant structures*

Description

These functions are used in conjunction with the [determinantStructure](#) family of funtions to conveniently work with determinant structures.

Usage

```

detStructAddVarLabels(determinantStructure, varLabelDf,
  varNameCol = "varNames.cln", leftAnchorCol = "leftAnchors",
  rightAnchorCol = "rightAnchors", subQuestionCol = "subQuestions",
  questionTextCol = "questionText")

```

```

detStructAddVarNames(determinantStructure, names)

```

```

detStructComputeProducts(determinantStructure, data, append = TRUE)

```

```
detStructComputeScales(determinantStructure, data, append = TRUE,
  separator = "_")
```

Arguments

determinantStructure	The <code>determinantStructure</code> object.
varLabelDf	The variable label dataframe as generated by <code>processLSvarLabels</code> . It is also possible to specify 'homemade' dataframe, in which case the column names have to be specified (see the next arguments).
varNameCol	The name of the column of the <code>varLabelDf</code> that contains the variable name. Only needs to be changed from the default value if <code>varLabelDf</code> is not a dataframe as produced by <code>processLSvarLabels</code> .
leftAnchorCol	The name of the column of the <code>varLabelDf</code> that contains the left anchor. Only needs to be changed from the default value if <code>varLabelDf</code> is not a dataframe as produced by <code>processLSvarLabels</code> .
rightAnchorCol	The name of the column of the <code>varLabelDf</code> that contains the right anchor. Only needs to be changed from the default value if <code>varLabelDf</code> is not a dataframe as produced by <code>processLSvarLabels</code> .
subQuestionCol	The name of the column of the <code>varLabelDf</code> that contains the subquestion. Only needs to be changed from the default value if <code>varLabelDf</code> is not a dataframe as produced by <code>processLSvarLabels</code> .
questionTextCol	The name of the column of the <code>varLabelDf</code> that contains the question text. Only needs to be changed from the default value if <code>varLabelDf</code> is not a dataframe as produced by <code>processLSvarLabels</code> .
names	A character vector with the variable names. These are matched against the regular expressions as specified in the <code>determinantStructure</code> object, and any matches will be stored in the <code>determinantStructure</code> object.
data	The dataframe containing the data; the variables names specified in <code>names</code> (when calling <code>detStructAddVarNames</code>) must be present in this dataframe.
append	Whether to only return the products or scales, or whether to append these to the dataframe and return the entire dataframe.
separator	The separator to use when constructing the scale variables names.

Details

This family of functions will be explained more in detail in a forthcoming paper.

Value

`detStructAddVarLabels` and `detStructAddVarNames` just change the `determinantStructure` object; `detStructComputeProducts` and `detStructComputeScales` return either the dataframe with the new variables appended (if `append = TRUE`) or just a dataframe with the new variables (if `append = FALSE`).


```
### Show its presence
names(detStudyPlus);
mean(detStudyPlus$rUse_Determinant);
```

nnc *Numbers Needed for Change*

Description

This function computes the Numbers Needed for Change, and shows a visualisation to illustrate them. Numbers Needed for Change is the name for a Numbers Needed to Treat estimate that was computed for a continuous outcome as is common in behavior change research.

Usage

```
nnc(d = NULL, cer = NULL, r = 1, n = NULL, threshold = NULL,
    mean = 0, sd = 1, poweredFor = NULL, thresholdSensitivity = NULL,
    eventDesirable = TRUE, eventIfHigher = TRUE, conf.level = 0.95,
    dReliability = 1, d.ci = NULL, cer.ci = NULL, r.ci = NULL,
    d.n = NULL, cer.n = NULL, r.n = NULL, plot = TRUE,
    returnPlot = TRUE, silent = FALSE)
```

```
## S3 method for class 'nnc'
print(x, digits = 2, ...)
```

Arguments

d	The value of Cohen's <i>d</i> .
cer	The Control Event Rate.
r	The correlation between the determinant and behavior (for mediated Numbers Needed for Change).
n	The sample size.
threshold	If the event rate is not available, a threshold value can be specified instead, which is then used in conjunction with the mean (mean) and standard deviation (sd) and assuming a normal distribution to compute the event rate.
mean	The mean value, used to draw the plot, or, if no CER is provided but instead the threshold value, to compute the CER.
sd	The standard deviation, used to draw the plot (and to compute the CER if a threshold value is supplied instead of the CER).
poweredFor	The Cohen's <i>d</i> value for which the study was powered. This expected Cohen's <i>d</i> value can be used to compute the threshold, which then in turn is used to compute the CER. To use this approach, also specify the mean and the standard deviation.

<code>thresholdSensitivity</code>	This argument can be used to provide a vector of potential threshold values, each of which is used to compute an NNC. This enables easy inspection of whether the value chosen as threshold matters much for the NNC.
<code>eventDesirable</code>	Whether an event is desirable or undesirable.
<code>eventIfHigher</code>	Whether scores above or below the threshold are considered 'an event'.
<code>conf.level</code>	The confidence level of the confidence interval.
<code>dReliability</code>	If Cohen's d was not measured with perfect reliability, <code>nnc</code> can disattenuate it to correct for the resulting attenuation using <code>ufs::disattenuate.d()</code> before computing the Experimental Event Rate. Use this argument to specify the reliability of the outcome measure. By default, the setting of 1 means that no disattenuation is applied.
<code>d.ci</code>	Instead of providing a point estimate for Cohen's d , a confidence interval can be provided.
<code>cer.ci</code>	Instead of providing a point estimate for the Control Event Rate, a confidence interval can be provided.
<code>r.ci</code>	Instead of providing a point estimate for the correlation, a confidence interval can be provided.
<code>d.n</code>	In addition to providing a point estimate for Cohen's d , a sample size can be provided; if it is, the confidence interval is computed.
<code>cer.n</code>	In addition to providing a point estimate for the Control Event Rate, a sample size can be provided; if it is, the confidence interval is computed.
<code>r.n</code>	In addition to providing a point estimate for the correlation, a sample size can be provided; if it is, the confidence interval is computed.
<code>plot</code>	Whether to generate and show the plot.
<code>returnPlot</code>	Whether to return the plot (as an attribute), or to only display it.
<code>silent</code>	Whether to suppress notifications.
<code>x</code>	The <code>nnc</code> object to print.
<code>digits</code>	The number of digits to round to.
<code>...</code>	Any additional arguments are passed to the <code>print</code> function.

Details

Numbers Needed to Treat is a common and very useful effect size measure in use in the medical sciences. It is computed based on the Control Event Rate (CER) and the Experimental Event Rate (EER), and expresses how many people would need to receive a treatment to yield a beneficial result for one person. In behavior change research, a similar measure would be useful, but the outcome is normally not dichotomous as is common in the medical literature (i.e. whether a participant survives or is cured), but continuous. Numbers Needed for Change fills this lacuna: it is simply the Numbers Needed to Treat, but converted from a Cohen's d value. `nnt` is an alias for `nnc`. For more details, see Gruijters & Peters (2019) for details.

Value

The Numbers Needed for Change (NNC), potentially with a plot visualising the NNC in an attribute.

Author(s)

Gjalt-Jorn Peters & Stefan Gruijters

Maintainer: Gjalt-Jorn Peters gjalt-jorn@userfriendlyscience.com

References

Gruijters, S. L., & Peters, G. Y. (2019). Gauging the impact of behavior change interventions: A tutorial on the Numbers Needed to Treat. *PsyArXiv*. doi:[10.31234/osf.io/2bau7](https://doi.org/10.31234/osf.io/2bau7)

Examples

```
### Simple example
```

```
behaviorchange::nnc(d=.4, cer=.3);
```

```
### Or for a scenario where events are undesirable, and the
```

```
### intervention effective (therefore having a negative value for d):
```

```
behaviorchange::nnc(d=-.4, cer=.3, eventDesirable=FALSE);
```

Index

- *Topic **data**
 - abcd_specs_examples, 5
- *Topic **hplot**
 - CIBER, 7
- *Topic **utilities**
 - convert.threshold.to.er, 10
 - detStructAddVarLabels, 15
 - nnc, 18

- abcd, 2, 5
- abcd_specs_complete
 - (abcd_specs_examples), 5
- abcd_specs_dutch_xtc
 - (abcd_specs_examples), 5
- abcd_specs_examples, 5
- abcd_specs_single_po_without_conditions
 - (abcd_specs_examples), 5
- abcd_specs_without_conditions
 - (abcd_specs_examples), 5
- apply_graph_theme, 6

- biAxisDiamondPlot, 9

- CIBER, 4, 7
- convert.er.to.threshold
 - (convert.threshold.to.er), 10
- convert.threshold.to.er, 10

- data.tree, 14
- data.tree::ToDiagrammeRGraph, 14
- determinantStructure, 9, 10, 13, 15–17
- determinantVar, 17
- determinantVar (determinantStructure), 13
- detStructAddVarLabels, 14, 15
- detStructAddVarNames, 14
- detStructAddVarNames
 - (detStructAddVarLabels), 15
- detStructCIBER, 13, 14, 17
- detStructCIBER (CIBER), 7

- detStructComputeProducts, 14
- detStructComputeProducts
 - (detStructAddVarLabels), 15
- detStructComputeScales, 14
- detStructComputeScales
 - (detStructAddVarLabels), 15
- detStructPreprocessing
 - (detStructAddVarLabels), 15
- DiagrammeR::DiagrammeR, 3, 4, 6
- DiagrammeR::export_graph, 3
- DiagrammeR::render_graph, 14
- DiagrammeR::render_graph(), 3
- diamondPlot, 9

- erDataSeq (convert.threshold.to.er), 10

- ggNNC (convert.threshold.to.er), 10
- ggplot2, 9
- ggplot2::ggplot(), 12
- gtable, 9

- nnc, 18
- nnc(), 12
- nncvis (convert.threshold.to.er), 10
- nnt (nnc), 18

- plot.determinantStructure
 - (determinantStructure), 13
- print.abcdiagram (abcd), 2
- print.determinantStructure
 - (determinantStructure), 13
- print.nnc (nnc), 18
- processLSvarLabels, 16

- subdeterminantProducts, 17
- subdeterminantProducts
 - (determinantStructure), 13
- subdeterminants, 17
- subdeterminants (determinantStructure), 13

- ufs::disattenuate.d(), 19