

Package ‘moveVis’

April 30, 2019

Type Package

Title Movement Data Visualization

Version 0.10.2

Depends R (>= 3.5.0)

Date 2019-04-30

Description Tools to visualize movement data (e.g. from GPS tracking) and temporal changes of environmental data (e.g. from remote sensing) by creating video animations.

License GPL-3

Encoding UTF-8

RoxygenNote 6.1.1

Imports raster, sp, sf, move, RStoolbox, geosphere, slippymath, lubridate, ggplot2, cowplot, gifski, magick, av, pbapply, curl, plyr, dplyr, zoo, magrittr, methods, grDevices

BugReports <http://www.github.com/16eagle/moveVis/issues>

SystemRequirements ImageMagick, FFmpeg, libav

URL <http://movevis.org>

Suggests mapview, leaflet, testthat

NeedsCompilation no

Author Jakob Schwalb-Willmann [aut, cre]

Maintainer Jakob Schwalb-Willmann <movevis@schwalb-willmann.de>

Repository CRAN

Date/Publication 2019-04-30 20:20:04 UTC

R topics documented:

moveVis-package	2
add_colourscale	4
add_gg	5
add_labels	8

add_northarrow	10
add_progress	11
add_scalebar	12
add_text	14
add_timestamps	15
align_move	17
animate_frames	18
basemap_data	20
deprecated	21
df2move	22
frames_graph	23
frames_spatial	25
get_frametimes	30
get_maptypes	31
join_frames	32
move_data	33
subset_move	34
suggest_formats	35
view_spatial	36
%>%	37

Index 38

moveVis-package	<i>Tools to visualize movement data in R</i>
-----------------	--

Description

moveVis provides tools to visualize movement data (e.g. from GPS tracking) and temporal changes of environmental data (e.g. from remote sensing) by creating video animations. The moveVis package is closely connected to the move package and builds up on ggplot2 grammar of graphics.

Details

The package includes the following functions, sorted by the order they would be applied to create an animation from movement data:

- [df2move](#) converts a `data.frame` into a `move` or `moveStack` object. This is useful if you do not usually work with the `move` classes and your tracks are present as `data.frames`.
- [align_move](#) aligns single and multi-individual movement data to a uniform time scale with a uniform temporal resolution needed for creating an animation from it. Use this function to prepare your movement data for animation depending on the temporal resolution that suits your data.
- [subset_move](#) subsets a `move` or `moveStack` by a given time span. This is useful if you want to create a movement animation of only a temporal subset of your data, e.g. a particular day.
- [get_maptypes](#) returns a character vector of available map types that can be used with [frames_spatial](#). moveVis supports OpenStreetMaps and Mapbox basemap imagery. Alternatively, you can provide custom imagery to [frames_spatial](#).

- `frames_spatial` creates a list of ggplot2 maps displaying movement. Each object represents a single frame. Each frame can be viewed or modified individually. The returned list of frames can be animated using `animate_frames`.
- `frames_graph` creates a list of ggplot2 graphs displaying movement-environment interaction. Each object represents a single frame. Each frame can be viewed or modified individually. The returned list of frames can be animated using `animate_frames`.
- `add_gg` adds ggplot2 functions (e.g. to add layers such as points, polygons, lines, or to change scales etc.) to the animation frames created with `frames_spatial` or `frames_graph`. Instead of creating your own ggplot2 functions, you can use one of the other moveVis add_ functions:
- `add_labels` adds character labels such as title or axis labels to animation frames created with `frames_spatial` or `frames_graph`.
- `add_scalebar` adds a scalebar to the animation frames created with `frames_spatial` or `frames_graph`.
- `add_northarrow` adds a north arrow to the animation frames created with `frames_spatial` or `frames_graph`.
- `add_progress` adds a progress bar to animation frames created with `frames_spatial` or `frames_graph`.
- `add_timestamps` adds timestamps to animation frames created with `frames_spatial` or `frames_graph`.
- `add_text` adds static or dynamically changing text to the animation frames created with `frames_spatial` or `frames_graph`.
- `add_colourscale` adjusts the colour scales of the animation frames created with `frames_spatial` and custom map imagery.
- `join_frames` side-by-side joins the ggplot2 objects of two or more frames lists of equal lengths into a single list of ggplot2 objects per frame using `plot_grid`. This is useful if you want to side-by-side combine spatial frames returned by `frames_spatial` with graph frames returned by `frames_graph`.
- `get_frametimes` extracts the timestamps associated with each frame of a list of frames created using `frames_spatial` or `frames_graph` and returns them as a vector.
- `suggest_formats` returns a selection of suggested file formats that can be used with `out_file` of `animate_frames` on your system.
- `animate_frames` creates an animation from a list of frames computed with `frames_spatial` or `frames_graph`.
- `view_spatial` displays movement tracks on an interactive mapview or leaflet map.

The majority of this functions can be used with the forward pipe operator `%>%`, which is re-exported by moveVis.

Author(s)

Jakob Schwalb-Willmann. Maintainer: Jakob Schwalb-Willmann, moveVis@schwalb-willmann.de

See Also

Useful links:

- <http://movevis.org>
- Report bugs at <http://www.github.com/16eagle/moveVis/issues>

add_colourscale *Add scale to frames*

Description

This function adjusts the colour scales of the animation frames created with `frames_spatial` and custom map imagery.

Usage

```
add_colourscale(frames, type, colours, labels = waiver(),
  na.colour = "grey50", na.show = TRUE, legend_title = NULL,
  verbose = TRUE)
```

Arguments

frames	list of ggplot2 objects, crated with <code>frames_spatial</code> .
type	character, either "gradient" or "discrete". Must be equal to the defintion of argument <code>r_type</code> with which frames have been created (see <code>frames_spatial</code>).
colours	character, a vector of colours. If <code>type = "discrete"</code> , number of colours must be equal to the number of classes contained in the raster imagery with which frames have been created. Optioanlly, the vector can be named to associate map values with colours and define the scale limits, e.g. <code>c("-1" = "red", "0" = "blue", "1" = "green")</code>
labels	character, a vector of labels with the same length as colours. Ignored, if <code>type = "gradient"</code> .
na.colour	character, colour to use for missing values.
na.show	logical, whether to display NA values in discrete scaling. Ignored, if <code>type = "gradient"</code> .
legend_title	character, a legend title.
verbose	logical, if TRUE, messages on the function's progress are displayed (default).

Value

List of frames.

Author(s)

Jakob Schwalb-Willmann

See Also

[frames_spatial](#) [frames_graph](#) [animate_frames](#)

Examples

```
library(moveVis)
library(move)

data("move_data", "basemap_data")
# align movement
m <- align_move(move_data, res = 4, unit = "mins")

# create spatial frames with frames_spatial:
r_list <- basemap_data[[1]]
r_times <- basemap_data[[2]]

frames <- frames_spatial(m, r_list = r_list, r_times = r_times, r_type = "gradient",
                        fade_raster = TRUE)
frames[[100]] # take a look at one of the frames

# default blue is boring, let's change the colour scale of all frames
frames <- add_colourscale(frames, type = "gradient", colours = c("orange", "white", "darkgreen"),
                        legend_title = "NDVI")
frames[[100]]

# let's make up some classification data with 10 classes
r_list <- lapply(r_list, function(x){
  y <- raster::setValues(x, round(raster::getValues(x)*10))
  return(y)
})
# turn fade_raster to FALSE, since it makes no sense to temporally interpolate discrete classes
frames <- frames_spatial(m, r_list = r_list, r_times = r_times, r_type = "discrete",
                        fade_raster = FALSE)
frames[[100]]

# now, let's assign a colour per class value to frames
colFUN <- colorRampPalette(c("orange", "lightgreen", "darkgreen"))
cols <- colFUN(10)
frames <- add_colourscale(frames, type = "discrete", colours = cols, legend_title = "Classes")
frames[[100]]
```

Description

This function adds ggplot2 functions (e.g. to add layers, change scales etc.) to the animation frames created with `frames_spatial`.

Usage

```
add_gg(frames, gg, data = NULL, ..., verbose = T)
```

Arguments

<code>frames</code>	list of ggplot2 objects, crated with <code>frames_spatial</code> .
<code>gg</code>	ggplot2 expressions (see details), either as <ul style="list-style-type: none"> • an expression of one or a list of ggplot2 functions to be added to every frame, • a list of such of the same length as <code>frames</code> to add different ggplot2 expressions per frame
<code>data</code>	optional data used by <code>gg</code> (see details), either <ul style="list-style-type: none"> • an object of any class, e.g. a <code>data.frame</code>, used by <code>gg</code> that will be added to all frames, • a list, e.g. of multiple <code>data.frames</code>, with length of <code>frames</code> to add different data to each frame.
<code>...</code>	additional (non-iterated) objects that should be visible to <code>gg</code> .
<code>verbose</code>	logical, if TRUE, messages on the function's progress are displayed (default).

Details

Argument `gg` expects ggplot2 functions handed over as expressions (see `expr`) to avoid their evaluation before they are called for the correct frame. Simply wrap your ggplot2 function into `expr()` and supply it to `gg`. To add multiple ggplot2 functions to be applied on every frame, supply an expression containing a list of ggplot2 functions (e.g. `expr(list(geom_label(...), geom_text(...)))`). This expression would be added to all frames. To add specific ggplot2 functions per frame, supply a list of expressions of the same length as `frames`. Each expression may contain a list of ggplot2 functions, if you want to add multiple functions per frame.

If `data` is used, the ggplot2 expressions supplied with `gg` can use the object by the name `data` for plotting. If `data` is a list, it must be of the same length as `frames`. The list will be iterated, so that functions in `gg` will have access to the individual objects within the list by the name `data` per each frame. If the data you want to display does not change with frames and may only be a character vector or similar, you may not need `data`, as you can supply the needed values within the expression supplied through `gg`.

If you supply `gg` as a list of expressions for each frame and `data` as a list of objects (e.g. `data.frames`) for each frame, each frame will be manipulated with the corresponding ggplot2 function and the corresponding data.

Value

List of frames.


```

# add a text label
frames <- add_text(frames, "Dynamic feature", x = 8.959, y = 47.7305,
                  colour = "black", size = 3)
frames[[100]]

# animate frames to see how the polygons "flip"
animate_frames(frames, out_file = tempfile(fileext = ".mov"))

# you can use add_gg on any list of ggplot2 objects,
# also on frames made using frames_gr
r_list <- basemap_data[[1]]
r_times <- basemap_data[[2]]

frames.gr <- frames_graph(m, r_list = r_list, r_times = r_times, r_type = "gradient",
                        fade_raster = TRUE, graph_type = "hist", val_by = 0.01)
frames.gr[[100]]
# manipulate the labels, since they are very dense:
# just replace the current scale
frames.gr <- add_gg(frames.gr, expr(scale_x_continuous(breaks=seq(0,1,0.1),
              labels=seq(0,1,0.1), expand = c(0,0))))
frames.gr[[100]]

```

add_labels

Add labels to frames

Description

This function adds character labels such as title or axis labels to animation frames created with [frames_spatial](#).

Usage

```

add_labels(frames, title = waiver(), subtitle = waiver(),
          caption = waiver(), tag = waiver(), x = waiver(), y = waiver(),
          verbose = TRUE)

```

Arguments

frames	list of ggplot2 objects, crated with frames_spatial .
title	character, frame title. If NULL, an existing title of frames is removed. If <code>wavier()</code> (default, see <code>ggplot2::wavier()</code>), an existing title of frames is kept.
subtitle	character, frame subtitle. If NULL, an existing title of frames is removed. If <code>wavier()</code> (default, see <code>ggplot2::wavier()</code>), an existing title of frames is kept.
caption	character, frame caption. If NULL, an existing title of frames is removed. If <code>wavier()</code> (default, see <code>ggplot2::wavier()</code>), an existing title of frames is kept.

tag	character, frame tag. If NULL, an existing title of frames is removed. If waiver() (default, see <code>ggplot2::waiver()</code>), an existing title of frames is kept.
x	character, label of the x axis. If NULL, an existing title of frames is removed. If waiver() (default, see <code>ggplot2::waiver()</code>), an existing title of frames is kept.
y	character, label of the y axis. If NULL, an existing title of frames is removed. If waiver() (default, see <code>ggplot2::waiver()</code>), an existing title of frames is kept.
verbose	logical, if TRUE, messages on the function's progress are displayed (default).

Value

List of frames.

Author(s)

Jakob Schwalb-Willmann

See Also

[frames_spatial](#) [frames_graph](#) [animate_frames](#)

Examples

```
library(moveVis)
library(move)

data("move_data", "basemap_data")
m <- align_move(move_data, res = 4, unit = "mins")

# create spatial frames using a custom NDVI base layer
r_list <- basemap_data[[1]]
r_times <- basemap_data[[2]]

frames <- frames_spatial(m, r_list = r_list, r_times = r_times, r_type = "gradient",
                        fade_raster = TRUE)

# add labels to frames:
frames <- add_labels(frames, title = "Example animation using moveVis::add_labels()",
                    subtitle = "Adding a subtitle to frames created using frames_spatial()",
                    caption = "Projection: Geographical, WGS84. Sources: moveVis examples.",
                    x = "Longitude", y = "Latitude")

# have a look at one frame
frames[[100]]
```

add_northarrow	<i>Add north arrow to frames</i>
----------------	----------------------------------

Description

This function adds a north arrow to the animation frames created with [frames_spatial](#).

Usage

```
add_northarrow(frames, height = 0.05, position = "bottomright",  
  x = NULL, y = NULL, colour = "black", size = 1,  
  label_text = "N", label_margin = 0.4, label_size = 5,  
  verbose = TRUE)
```

Arguments

frames	list of ggplot2 objects, crated with frames_spatial .
height	numeric, height of the north arrow in a range from 0 to 1 as the proportion of the overall height of the frame map.
position	character, position of the north arrow on the map. Either "bottomleft", "upperleft", "upperright", Ignored, if x and y are set.
x	numeric, position of the bottom left corner of the north arrow on the x axis. If not set, position is used to calculate the position of the north arrow.
y	numeric, position of the bottom left corner of the north arrow on the y axis. If not set, position is used to calculate the position of the north arrow.
colour	character, colour.
size	numeric, arrow size.
label_text	character, text below the north arrow.
label_margin	numeric, margin between label and north arrow as a proportion of the size of the north arrow.
label_size	numeric, label font size.
verbose	logical, if TRUE, messages on the function's progress are displayed (default).

Value

List of frames.

Author(s)

Jakob Schwalb-Willmann

See Also

[frames_spatial](#) [frames_graph](#) [animate_frames](#)

Examples

```
library(moveVis)
library(move)

data("move_data", "basemap_data")
m <- align_move(move_data, res = 4, unit = "mins")

# create spatial frames using a custom NDVI base layer
r_list <- basemap_data[[1]]
r_times <- basemap_data[[2]]

frames <- frames_spatial(m, r_list = r_list, r_times = r_times, r_type = "gradient",
                        fade_raster = TRUE)

# add a north arrow to frames:
frames.a <- add_northarrow(frames)
frames.a[[100]]

# or in white at another position
frames.b <- add_northarrow(frames, colour = "white", position = "bottomleft")
frames.b[[100]]
```

add_progress

Add progress bar to frames

Description

This function adds a progress bar to animation frames created with [frames_spatial](#).

Usage

```
add_progress(frames, colour = "grey", size = 1.8, verbose = TRUE)
```

Arguments

frames	list of ggplot2 objects, crated with frames_spatial .
colour	character, progress bar colour.
size	numeric, progress bar line size..
verbose	logical, if TRUE, messages on the function's progress are displayed (default).

Value

List of frames.

Author(s)

Jakob Schwalb-Willmann

See Also[frames_spatial](#) [frames_graph](#) [animate_frames](#)**Examples**

```
library(moveVis)
library(move)

data("move_data", "basemap_data")
m <- align_move(move_data, res = 4, unit = "mins")

# create spatial frames using a custom NDVI base layer
r_list <- basemap_data[[1]]
r_times <- basemap_data[[2]]

frames <- frames_spatial(m, r_list = r_list, r_times = r_times, r_type = "gradient",
                        fade_raster = TRUE)

# add a progress bar:
frames.a <- add_progress(frames)
frames.a[[100]]

# or in red and larger
frames.b <- add_progress(frames, colour = "red", size = 2.5)
frames.b[[100]]
```

`add_scalebar`*Add scalebar to frames*

Description

This function adds a scalebar to the animation frames created with [frames_spatial](#).

Usage

```
add_scalebar(frames, distance = NULL, height = 0.015,
             position = "bottomleft", x = NULL, y = NULL, colour = "black",
             label_margin = 1.2, verbose = TRUE)
```

Arguments

frames	list of ggplot2 objects, crated with frames_spatial .
distance	numeric, optional. Distance displayed by the scalebar in km. By default, the displayed distance is calculated automatically.
height	numeric, height of the scalebar in a range from 0 to 1 as the proportion of the overall height of the frame map. Default is 0.015.
position	character, position of the scalebar on the map. Either "bottomleft", "upperleft", "upperright", "b Ignored, if x and y are set.
x	numeric, position of the bottom left corner of the scalebar on the x axis. If not set, position is used to calculate the position of the scalebar.
y	numeric, position of the bottom left corner of the scalebar on the y axis. If not set, position is used to calculate the position of the scalebar.
colour	character, colour of the distance labels. Default is "black".
label_margin	numeric, distance of the labels to the scalebar as a proportion of the height of the scalebar (e.g. if set to 2, the labels will be positioned with a distance to the scalebar of twice the scalebar height).
verbose	logical, if TRUE, messages on the function's progress are displayed (default).

Value

List of frames.

Author(s)

Jakob Schwalb-Willmann

See Also

[frames_spatial](#) [frames_graph](#) [animate_frames](#)

Examples

```
library(moveVis)
library(move)

data("move_data", "basemap_data")
m <- align_move(move_data, res = 4, unit = "mins")

# create spatial frames using a custom NDVI base layer
r_list <- basemap_data[[1]]
r_times <- basemap_data[[2]]

frames <- frames_spatial(m, r_list = r_list, r_times = r_times, r_type = "gradient",
                        fade_raster = TRUE)

# add a scale bar to frames:
frames.a <- add_scalebar(frames)
```

```
frames.a[[100]]

# or in white at another position
frames.b <- add_scalebar(frames, colour = "white", position = "bottomright")
frames.b[[100]]

# or with another height
frames.c <- add_scalebar(frames, colour = "white", position = "bottomright", height = 0.025)
frames.c[[100]]
```

add_text

Add static or dynamic text to frames

Description

This function adds static or dynamically changing text to the animation frames created with [frames_spatial](#).

Usage

```
add_text(frames, labels, x, y, colour = "black", size = 3,
         type = "text", verbose = TRUE)
```

Arguments

frames	list of ggplot2 objects, crated with frames_spatial .
labels	character, text to be added to frames. Either a single character value or a character vector of same length as frames.
x	numeric, position of text on the x scale. Either a single numeric value or a numeric vector of same length as frames.
y	numeric, position of text on the y scale. Either a single numeric value or a numeric vector of same length as frames.
colour	character, the text colour(s). Either a single character value or a character vector of same length as frames.
size	numeric, the text size(s). Either a single numeric value or a numeric vector of same length as frames.
type	character, either "text" to draw text or "label" to draw text inside a box.
verbose	logical, if TRUE, messages on the function's progress are displayed (default).

Value

List of frames.

Author(s)

Jakob Schwalb-Willmann

See Also

[frames_spatial](#) [frames_graph](#) [animate_frames](#)

Examples

```
library(moveVis)
library(move)

data("move_data", "basemap_data")
m <- align_move(move_data, res = 4, unit = "mins")

# create spatial frames using a custom NDVI base layer
r_list <- basemap_data[[1]]
r_times <- basemap_data[[2]]

frames <- frames_spatial(m, r_list = r_list, r_times = r_times, r_type = "gradient",
                        fade_raster = TRUE)

# add text somewhere to all frames:
frames.a <- add_text(frames, "Water area", x = 8.959, y = 47.7305,
                    colour = "white", size = 3)
frames.a[[100]]

# or use the ggplot2 "label" type:
frames.b <- add_text(frames, "Water area", x = 8.959, y = 47.7305,
                    colour = "black", size = 3, type = "label")
frames.b[[100]]
```

add_timestamps

Add timestamps to frames

Description

This function adds timestamps to animation frames created with [frames_spatial](#).

Usage

```
add_timestamps(frames, m = NULL, x = NULL, y = NULL, ...,
              verbose = TRUE)
```

Arguments

frames	list of ggplot2 objects, crated with frames_spatial .
m	move or moveStack, optional. If defined, timestamps are extracted from m that must be the same object used to create frames with frames_spatial . If undefined (recommended), timestamps are extracted from the attributes of frames directly.

x	numeric, optional, position of timestamps on the x scale. By default, timestamps will be displayed in the top center.
y	numeric, optional, position of timestamps on the y scale.
...	optional, arguments passed to add_text , such as colour, size, type.
verbose	logical, if TRUE, messages on the function's progress are displayed (default).

Value

List of frames.

Author(s)

Jakob Schwalb-Willmann

See Also

[frames_spatial](#) [frames_graph](#) [animate_frames](#)

Examples

```
library(moveVis)
library(move)

data("move_data", "basemap_data")
m <- align_move(move_data, res = 4, unit = "mins")

# create spatial frames using a custom NDVI base layer
r_list <- basemap_data[[1]]
r_times <- basemap_data[[2]]

frames <- frames_spatial(m, r_list = r_list, r_times = r_times, r_type = "gradient",
                        fade_raster = TRUE)

# add timestamps as text
frames.a <- add_timestamps(frames, type = "text")
frames.a[[100]]

# or use the ggplot2 "label" type:
frames.b <- add_timestamps(frames, type = "label")
frames.b[[100]]
```

align_move	<i>Align movement data</i>
------------	----------------------------

Description

This function aligns movement data to a uniform time scale with a uniform temporal resolution throughout the complete movement sequence. This prepares the provided movement data to be interpretable by `frames_spatial`, which necessitates a uniform time scale and a consistent, unique temporal resolution for all moving individuals to turn recording times into frame times.

Usage

```
align_move(m, res = "min", digit = "min", unit = "secs",
           spaceMethod = "greatcircle")
```

Arguments

<code>m</code>	move or moveStack, which is allowed to contain irregular timestamps and diverging temporal resolutions to be aligned (see <code>df2move</code> to convert a <code>data.frame</code> to a move object).
<code>res</code>	either numeric, representing the temporal resolution, to which <code>m</code> should be aligned to (see argument <code>unit</code>), or character: <ul style="list-style-type: none"> • "min" to use the smallest temporal resolution of <code>m</code> (default) • "max" to use the largest temporal resolution of <code>m</code> • "mean" to use the rounded average temporal resolution of <code>m</code>
<code>digit</code>	either numeric, indicating to which digits of a specific unit (see argument <code>unit</code>) the time scale of <code>m</code> should be aligned (e.g. 0 to align the time scale to second ":00", if <code>unit</code> is set to <code>secs</code>), or character: <ul style="list-style-type: none"> • "min" to use the smallest digit of the defined unit (default) • "max" to use the largest digit of the defined unit • "mean" to use the rounded average digit of the defined unit
<code>unit</code>	character, either "secs", "mins", "hours", "days", indicating the temporal unit, to which <code>res</code> and <code>digit</code> are referring.
<code>spaceMethod</code>	character, either "euclidean", "greatcircle" or "rhumbline", indicating the interpolation function to be used to interpolate locations of <code>m</code> to the aligned time scale. Interpolation is performed using <code>move::interpolateTime</code> .

Value

Aligned move or moveStack, ready to be used with `frames_spatial`.

Author(s)

Jakob Schwalb-Willmann

See Also

[df2move](#) [frames_spatial](#) [frames_graph](#)

Examples

```
library(moveVis)
library(move)
data("move_data")

# the tracks in move_data have irregular timestamps and sampling rates.
# print unique timestamps and timeLag
unique(timestamps(move_data))
unique(unlist(timeLag(move_data, units = "secs")))

# use align_move to correct move_data to a uniform time scale and lag using interpolation.
# resolution of 4 minutes (240 seconds) at digit 0 (:00 seconds) per timestamp:
m <- align_move(move_data, res = 240, digit = 0, unit = "secs")
unique(unlist(timeLag(m, units = "secs")))

# resolution of 1 hour (3600 seconds) at digit 0 (:00 seconds) per timestamp:
m <- align_move(move_data, res = 3600, digit = 0, unit = "secs")
unique(unlist(timeLag(m, units = "secs")))

# resolution of 1 hour (15 seconds) at digit 0 (:00 seconds) per timestamp:
m <- align_move(move_data, res = 15, digit = 0, unit = "secs")
unique(unlist(timeLag(m, units = "secs")))

# resolution of 1 hour:
m <- align_move(move_data, res = 60, unit = "mins")
unique(unlist(timeLag(m, units = "secs")))
```

animate_frames

Animate frames

Description

animate_frames creates an animation from a list of frames computed with [frames_spatial](#).

Usage

```
animate_frames(frames, out_file, fps = 25, width = 700, height = 700,
  res = 100, end_pause = 0, display = TRUE, overwrite = FALSE,
  verbose = TRUE, ...)
```

Arguments

frames	list of ggplot2 objects, crated with frames_spatial .
out_file	character, the output file path, e.g. "/dir/to/file.mov". The file extension must correspond to a file format known by the available renderers of the running system. Use suggest_formats to get a vector of suggested known file formats.
fps	numeric, the number of frames to be displayed per second. Default is 2.
width	numeric, width of the output animation in pixels.
height	numeric, height of the output animation in pixels.
res	numeric, resolution of the output animation in ppi.
end_pause	numeric, defining how many seconds the last frame of the animation should be hold to add a pause at the the end of the animation. Default is 0 seconds to not add a pause.
display	logical, whether the animation should be displayed after rendering or not.
overwrite	logical, wether to overwrite an existing file, if out_file is already present.
verbose	logical, if TRUE, messages on the function's progress are displayed (default).
...	additional arguments to be passed to the render function.

Details

An appropriate render function is selected depending on the file extension in out_file: For .gif files, `gifski::save_gif` is used, for any other (video) format, `av::av_capture_graphics` is used.

Value

None or the default image/video viewer displaying the animation

Author(s)

Jakob Schwalb-Willmann

See Also

[frames_spatial](#) [frames_graph](#) [join_frames](#)

Examples

```
library(moveVis)
library(move)

data("move_data", "basemap_data")
# align movement
m <- align_move(move_data, res = 4, unit = "mins")

# create spatial frames with frames_spatial:
r_list <- basemap_data[[1]]
r_times <- basemap_data[[2]]
```

```
frames <- frames_spatial(m, r_list = r_list, r_times = r_times, r_type = "gradient",
                        fade_raster = TRUE)

# customize
frames <- add_colourscale(frames, type = "gradient",
                        colours = c("orange", "white", "darkgreen"), legend_title = "NDVI")
frames <- add_northarrow(frames, position = "bottomleft")
frames <- add_scalebar(frames, colour = "white", position = "bottomright")

frames <- add_progress(frames)
frames <- add_timestamps(frames, m, type = "label")

# check available formats
suggest_formats()

# animate frames as GIF
animate_frames(frames, out_file = tempfile(fileext = ".gif"))

# animate frames as mov
animate_frames(frames, out_file = tempfile(fileext = ".gif"))
```

basemap_data

Exemplary manipulated NDVI data

Description

This dataset contains two lists of equal lengths:

- a list of ten single-layer raster objects, representing NDVI images covering the Lake of Constance area.
- a list of made-up times that simulate acquisition times with a temporal resolution, remote sensing scientists would dream of...

Usage

```
basemap_data
```

Format

List containing two lists of equal lengths: a list of raster objects and a list of POSIXct times.

Details

This object is used by some moveVis examples and unit tests.

Note

All data contained should only be used for testing moveVis and are not suitable to be used for analysis or interpretation.

Source

MODIS (MOD13Q1 NDVI)

depreciated

Depreciated functions

Description

Several functions are depreciated due to a rewrite of moveVis with version 0.10.

Usage

`animate_move(...)`

`animate_raster(...)`

`animate_stats(...)`

`get_formats(...)`

`get_libraries(...)`

Arguments

... depreciated arguments.

Details

The new version of moveVis makes it much easier to animate movement data and multi-temporal imagery (see `?moveVis`). You gain more control about the preprocessing of your movement data as well as the visual customization of each animation frame through a more consequent link of moveVis to gplot2.

Note

To install the old version of moveVis (0.9.9), see <https://github.com/16EAGLE/moveVis/releases/tag/v0.9.9>.

See Also

[frames_spatial](#) [frames_graph](#) [join_frames](#) [animate_frames](#)

`df2move`*Convert a data.frame into a move or moveStack object*

Description

This function is a simple wrapper that converts a `data.frame` into a `move` or `moveStack` object. Both can be used as inputs to [frames_spatial](#) or [frames_graph](#).

Usage

```
df2move(df, proj, x, y, time, track_id = NULL, data = NULL, ...)
```

Arguments

<code>df</code>	<code>data.frame</code> , a <code>data.frame</code> with rows representing observations and columns representing <code>x</code> and <code>y</code> coordinates, <code>time</code> and optionally track IDs, if multiple tracks are contained.
<code>proj</code>	projection, character (<code>proj4string</code>) or CRS object, indicating the projection that the coordinates of <code>df</code> represent.
<code>x</code>	character, name of the column in <code>df</code> that represents <code>x</code> coordinates.
<code>y</code>	character, name of the column in <code>df</code> that represents <code>y</code> coordinates.
<code>time</code>	character, name of the column in <code>df</code> that represents timestamps. Timestamps need to be of class <code>POSIXct</code> .
<code>track_id</code>	character, optional, name of the column in <code>df</code> that represents track names or IDs. If set, a <code>moveStack</code> is returned, otherwise, a <code>move</code> object is returned.
<code>data</code>	<code>data.frame</code> , optional, to add additional data such as path colours (see move). Number of rows must equal number of rows of <code>df</code> .
<code>...</code>	additional arguments passed to <code>move</code> .

Value

A `move` or `moveStack` object.

See Also

[frames_spatial](#) [frames_graph](#) [subset_move](#)

Examples

```
library(moveVis)
library(move)

# load the example data and convert them into a data.frame
data("move_data")
move_df <- methods::as(move_data, "data.frame")
```

```
# use df2move to convert the data.frame into a moveStack
df2move(move_df,
        proj = "+init=epsg:4326 +proj=longlat +datum=WGS84 +no_defs +ellps=WGS84 +towgs84=0,0,0",
        x = "coords.x1", y = "coords.x2", time = "timestamps", track_id = "trackId")
```

frames_graph	<i>Create frames of movement-environment interaction graphs for animation</i>
--------------	---

Description

frames_graph creates a list of ggplot2 graphs displaying movement-environment interaction. Each object represents a single frame. Each frame can be viewed or modified individually. The returned list of frames can be animated using [animate_frames](#).

Usage

```
frames_graph(m, r_list, r_times, r_type = "gradient",
            fade_raster = FALSE, return_data = FALSE, graph_type = "flow",
            path_size = 1, path_legend = TRUE, path_legend_title = "Names",
            val_min = NULL, val_max = NULL, val_by = 0.1, verbose = T)
```

Arguments

m	move or moveStack of uniform time scale and time lag, e.g. prepared with align_move (recommended). May contain a column named colour to control path colours (see details).
r_list	list of raster or rasterStack. Each list element refers to the times given in r_times. Use single-layer raster objects for gradient or discrete data (see r_type). Use a rasterStack containing three bands for RGB imagery (in the order red, green, blue).
r_times	list of POSIXct times. Each list element represents the time of the corresponding element in r_list. Must be of same length as r_list.
r_type	character, either "gradient" or "discrete". Ignored, if r_list contains rasterStacks of three bands, which are treated as RGB.
fade_raster	logical, if TRUE, r_list is interpolated over time based on r_times. If FALSE, r_list elements are assigned to those frames closest to the equivalent times in r_times.
return_data	logical, if TRUE, instead of a list of frames, a data.frame containing the values extracted from r_list per individual, location and time is returned. This data.frame can be used to create your own multi- or monotemporal ggplot2 movement-environment interaction graphs.
graph_type	character, defines the type of multi-temporal graph that should be drawn as frames. Currently supported graphs are: <ul style="list-style-type: none"> "flow", a time flow graph with frame time on the x axis and values of the visited cell at x on the y axis per individual track

- "hist", a cumulative histogram with cell values on the x axis and time-cumulative counts of visits on the y axis per individual track.

path_size	numeric, size of each path.
path_legend	logical, whether to add a path legend from <code>m</code> or not. Legend tracks and colours will be ordered by the tracks' temporal appearances, not by their order in <code>m</code> .
path_legend_title	character, path legend title. Default is "Names".
val_min	numeric, minimum value of the value axis. If undefined, the minimum is collected automatically.
val_max	numeric, maximum value of the value axis. If undefined, the maximum is collected automatically.
val_by	numeric, increment of the value axis sequence. Default is 0.1. If <code>graph_type = "discrete"</code> , this value should be an integer of 1 or greater.
verbose	logical, if TRUE, messages on the function's progress are displayed (default).

Details

To later on side-by-side join spatial frames created using `frames_spatial` with frames created with `frames_graph` for animation, equal inputs must have been used for both function calls for each of the arguments `m`, `r_list`, `r_times` and `fade_raster`.

Value

List of ggplot2 objects, each representing a single frame. If `return_data` is TRUE, a `data.frame` is returned (see `return_data`).

Author(s)

Jakob Schwalb-Willmann

See Also

[frames_spatial](#) [join_frames](#) [animate_frames](#)

Examples

```
library(moveVis)
library(move)
library(ggplot2)

data("move_data", "basemap_data")
# align movement
m <- align_move(move_data, res = 4, unit = "mins")

r_list <- basemap_data[[1]]
r_times <- basemap_data[[2]]

# use the same inputs to create a non-spatial graph, e.g. a flow graph:
```



```

frames.gr <- frames_graph(m, r_list = r_list, r_times = r_times, r_type = "gradient",
                          fade_raster = TRUE, graph_type = "flow")

# take a look
frames.gr[[100]]

# make a histogram graph:
frames.gr <- frames_graph(m, r_list = r_list, r_times = r_times, r_type = "gradient",
                          fade_raster = TRUE, graph_type = "hist")

# change the value interval:
frames.gr <- frames_graph(m, r_list = r_list, r_times = r_times, r_type = "gradient",
                          fade_raster = TRUE, graph_type = "hist", val_by = 0.01)

frames.gr[[100]]
# manipulate the labels, since now they are very dense:
# just replace the current scale
frames.gr <- add_gg(frames.gr, expr(scale_x_continuous(breaks=seq(0,1,0.1),
                                                    labels=seq(0,1,0.1), expand = c(0,0))))

frames.gr[[100]]

# the same can be done for discrete data, histogram will then be shown as bin plots

# to make your own graphs, use frames_graph to return data instead of frames
data.gr <- frames_graph(m, r_list = r_list, r_times = r_times, r_type = "gradient",
                       fade_raster = TRUE, return_data = TRUE)

# animate the frames created with frames_graph;
animate_frames(frames, out_file = tempfile(fileext = ".gif"))

# see all add_ functions on how to customize your frames created with frames_spatial
# or frames_graph

# see ?animate_frames on how to animate your list of frames

```

frames_spatial

Create frames of spatial movement maps for animation

Description

frames_spatial creates a list of ggplot2 maps displaying movement. Each object represents a single frame. Each frame can be viewed or modified individually. The returned list of frames can be animated using [animate_frames](#).

Usage

```

frames_spatial(m, r_list = NULL, r_times = NULL, r_type = "gradient",
              fade_raster = FALSE, map_service = "osm", map_type = "streets",
              map_res = 1, map_token = NULL, map_dir = NULL,
              margin_factor = 1.1, equidistant = NULL, ext = NULL,

```

```

path_size = 3, path_end = "round", path_join = "round",
path_mitre = 10, path_arrow = NULL, path_colours = NA,
path_alpha = 1, path_fade = FALSE, path_legend = TRUE,
path_legend_title = "Names", tail_length = 19, tail_size = 1,
tail_colour = "white", trace_show = FALSE, trace_colour = "white",
..., verbose = TRUE)

```

Arguments

<code>m</code>	move or moveStack of uniform time scale and time lag, e.g. prepared with align_move (recommended). May contain a column named colour to control path colours (see details).
<code>r_list</code>	list of raster or rasterStack. Each list element refers to the times given in <code>r_times</code> . Use single-layer raster objects for gradient or discrete data (see <code>r_type</code>). Use a rasterStack containing three bands for RGB imagery (in the order red, green, blue).
<code>r_times</code>	list of POSIXct times. Each list element represents the time of the corresponding element in <code>r_list</code> . Must be of same length as <code>r_list</code> .
<code>r_type</code>	character, either "gradient" or "discrete". Ignored, if <code>r_list</code> contains rasterStacks of three bands, which are treated as RGB.
<code>fade_raster</code>	logical, if TRUE, <code>r_list</code> is interpolated over time based on <code>r_times</code> . If FALSE, <code>r_list</code> elements are assigned to those frames closest to the equivalent times in <code>r_times</code> .
<code>map_service</code>	character, either "osm", "carto" or "mapbox". Default is "osm".
<code>map_type</code>	character, a map type, e.g. "streets". For a full list of available map types, see get_maptypes .
<code>map_res</code>	numeric, resolution of base map in range from 0 to 1.
<code>map_token</code>	character, mapbox authentication token for mapbox basemaps. Register at https://www.mapbox.com/ to get a mapbox token. Mapbox is free of charge after registration for up to 50.000 map requests per month. Ignored, if <code>map_service = "osm"</code> .
<code>map_dir</code>	character, directory where downloaded basemap tiles can be stored. By default, a temporary directory is used. If you use <code>moveVis</code> often for the same area it is recommended to set this argument to a directory persistent throughout sessions (e.g. in your user folder), so that basemap tiles that had been already downloaded by <code>moveVis</code> do not have to be requested again.
<code>margin_factor</code>	numeric, factor relative to the extent of <code>m</code> by which the frame extent should be increased around the movement area. Ignored, if <code>ext</code> is set.
<code>equidistant</code>	logical, whether to make the map extent equidistant (squared) with y and x axis measuring equal distances or not. Especially in polar regions of the globe it might be necessary to set <code>equidistant</code> to FALSE to avoid strong stretches. By default (<code>equidistant = NULL</code>), <code>equidistant</code> is set automatically to FALSE, if <code>ext</code> is set, otherwise TRUE. Read more in the details.
<code>ext</code>	<code>sf</code> <code>bbox</code> or <code>sp</code> extent in same CRS as <code>m</code> , optional. If set, frames are cropped to this extent. If not set, a squared extent around <code>m</code> , optional with a margin set by <code>margin_factor</code> , is used (default).

path_size	numeric, size of each path.
path_end	character, either "round", "butt" or "square", indicating the path end style.
path_join	character, either "round", "mitre" or "bevel", indicating the path join style.
path_mitre	numeric, path mitre limit (number greater than 1).
path_arrow	arrow, path arrow specification, as created by <code>grid::arrow()</code> .
path_colours	character, a vector of colours. Must be of same length as number of individual tracks in <code>m</code> and refers to the order of tracks in <code>m</code> . If undefined (NA) and <code>m</code> contains a column named <code>colour</code> , colours provided within <code>m</code> are used (see details). Otherwise, colours are selected randomly per individual track.
path_alpha	numeric, defines alpha (transparency) of the path. Value between 0 and 1. Default is 1.
path_fade	logical, whether paths should be faded towards the last frame or not. Useful, if <code>trace_show = TRUE</code> and you want to hold the last frame using <code>end_pause</code> in <code>animate_frames</code> .
path_legend	logical, whether to add a path legend from <code>m</code> or not. Legend tracks and colours will be ordered by the tracks' temporal appearances, not by their order in <code>m</code> .
path_legend_title	character, path legend title. Default is "Names".
tail_length	numeric, length of tail per movement path.
tail_size	numeric, size of the last tail element. Default is 1.
tail_colour	character, colour of the last tail element, to which the path colour is faded. Default is "white".
trace_show	logical, whether to show the trace of the complete path or not.
trace_colour	character, colour of the trace. Default is "white". It is recommended to define the same colours for both <code>trace_colour</code> and <code>tail_colour</code> to enforce an uninterrupted colour transition from the tail to the trace.
...	Additional arguments customizing the frame background, passed to <code>RStoolbox::ggR</code> or <code>RStoolbox::ggRGB</code> : <ul style="list-style-type: none"> • <code>alpha</code>, numeric, background transparency (0-1). • <code>hue</code>, numeric, hue value for color calculation (0-1). Change if you need anything else than greyscale. Only effective if <code>sat > 0</code>. • <code>sat</code>, numeric, saturation value for color calculation (0,1). Change if you need anything else than greyscale. • <code>stretch</code>, character, either 'none', 'lin', 'hist', 'sqrt' or 'log' for no stretch, linear, histogram, square-root or logarithmic stretch. • <code>quantiles</code>, numeric vector with two elements, min and max quantiles to stretch to. Defaults to 2
verbose	logical, if TRUE, messages on the function's progress are displayed (default).

Details

If argument `path_colours` is not defined (set to NA), path colours can be defined by adding a character column named `colour` to `m`, containing a colour code or name per row (e.g. "red". This way, for example, column `colour` for all rows belonging to individual A can be set to "green", while column `colour` for all rows belonging to individual B can be set to "red". Colours could also be arranged to change through time or by behavioral segments, geographic locations, age, environmental or health parameters etc. If a column name `colour` in `m` is missing, colours will be selected automatically. Call `colours()` to see all available colours in R.

Basemap colour scales can be changed/added using `add_colourscale` or by using ggplot2 commands (see examples). For continuous scales, use `r_type = "gradient"`. For discrete scales, use `r_type = "discrete"`.

The projection of `m` is treated as target projection. Default base maps accessed through a map service will be reprojected into the projection of `m`. Thus, depending on the projection of `m`, it may happen that map labels are distorted. To get undistorted map labels, reproject `m` to the web mercator projection (the default projection of the base maps): `spTransform(m, crs("+init=epsg:3857"))`. The ggplot2 coordinate system will be computed based on the projection of `m` using `coord_sf`. If argument `equidistant` is set, the map extent is calculated (thus enlarged into one axis direction) to represent equal surface distances on the x and y axis.

Value

List of ggplot2 objects, each representing a single frame.

Author(s)

Jakob Schwalb-Willmann

See Also

[frames_graph](#) [join_frames](#) [animate_frames](#)

Examples

```
library(moveVis)
library(move)
library(ggplot2)

data("move_data")
# align movement
m <- align_move(move_data, res = 4, unit = "mins")

# with osm watercolor base map
frames <- frames_spatial(m, map_service = "osm", map_type = "watercolor")
# take a look at one of the frames, e.g. the 100th
frames[[100]]

# make base map a bit transparent
frames <- frames_spatial(m, map_service = "osm", map_type = "watercolor", alpha = 0.5)
frames[[100]] # take a look
```

```
# use a larger margin around extent
frames <- frames_spatial(m, map_service = "osm", map_type = "watercolor", alpha = 0.5,
  margin_factor = 1.8)

# use a extent object as your AOI
ext <- extent(m)
ext@xmin <- ext@xmin - (ext@xmin*0.003)
ext@xmax <- ext@xmax + (ext@xmax*0.003)
frames <- frames_spatial(m, map_service = "osm", map_type = "watercolor", alpha = 0.5,
  ext = ext)

# alter path appearance (make it longer and bigger)
frames <- frames_spatial(m, map_service = "osm", map_type = "watercolor", alpha = 0.5,
  path_size = 4, tail_length = 29)

# adjust path colours manually
frames <- frames_spatial(m, map_service = "osm", map_type = "watercolor", alpha = 0.5,
  path_colours = c("black", "blue", "purple"))

# or do it directly within your moveStack, e.g. like:
m.list <- split(m) # split m into list by individual
m.list <- mapply(x = m.list, y = c("orange", "purple", "darkgreen"), function(x, y){
  x$colour <- y
  return(x)
}) # add colour per individual
m <- moveStack(m.list) # putting it back together into a moveStack
frames <- frames_spatial(m, map_service = "osm", map_type = "watercolor", alpha = 0.5)
# this way, you do not have to assign colours per individual track
# instead, you could assign colours by segment, age, speed or other variables

# get available map types
get_maotypes()

# use mapbox to get a satellite or other map types (register to on mapbox.com to get a token)
frames <- frames_spatial(m, map_service = "mapbox",
  map_token = "your_token_from_your_mapbox_account",
  map_type = "satellite")

# if you make a lot of calls to frames_spatial during mutliple sessions, use a map directory
# to save all base maps offline so that you do not have to query the servers each time
frames <- frames_spatial(m, map_service = "mapbox",
  map_token = "your_token_from_your_mapbox_account",
  map_type = "satellite",
  map_dir = "your/map_directory/")

# use your own custom base maps
data("basemap_data")
r_list <- basemap_data[[1]]
r_times <- basemap_data[[2]]

# using gradient data (e.g. NDVI)
frames <- frames_spatial(m, r_list = r_list, r_times = r_times, r_type = "gradient",
```

```

fade_raster = TRUE)

# using discrete data (e.g. classifications)
# let's make up some classification data with 10 classes
r_list <- lapply(r_list, function(x){
  y <- raster::setValues(x, round(raster::getValues(x)*10))
  return(y)
})
# turn fade_raster to FALSE, since it makes no sense to temporally interpolate discrete classes
frames <- frames_spatial(m, r_list = r_list, r_times = r_times, r_type = "discrete",
  fade_raster = FALSE)

# animate the frames created with frames_spatial;
animate_frames(frames, out_file = tempfile(fileext = ".gif"))

# see ?add_colourscale to learn how to change colours of custom base maps
# see all add_ functions on how to customize your frames created with frames_spatial
# or frames_graph
# see ?animate_frames on how to animate your list of frames

```

get_frametimes

Get frame times from frames

Description

This function extracts the timestamps associated with each frame of a list of frames created using [frames_spatial](#) or [frames_graph](#) and returns them as a vector.

Usage

```
get_frametimes(frames)
```

Arguments

frames list, list of frames created using [frames_spatial](#) or [frames_graph](#).

Details

moveVis stores the times represented by a frame as an attribute "time" for each ggplot frame.

Value

A POSIXct vector of timestamps representing the time associated with each frame in frames.

See Also

[frames_spatial](#) [frames_graph](#)

Examples

```
library(moveVis)
library(move)

data("move_data")
# align movement
m <- align_move(move_data, res = 4, unit = "mins")

frames <- frames_spatial(m, map_service = "osm", map_type = "watercolor")
frames.ts <- get_frametimes(frames)
print(frames.ts)
```

get_maptypes

Get all supported map types

Description

This function returns every supported map type that can be used as input to the `map_type` argument of [frames_spatial](#).

Usage

```
get_maptypes(map_service = NULL)
```

Arguments

`map_service` character, optional, either "osm", "carto" or "mapbox". Otherwise, a list of map types for both services is returned.

Value

A character vector of supported map types

See Also

[frames_spatial](#)

Examples

```
# for all services
get_maptypes()

# for osm only
get_maptypes("osm")
# or
get_maptypes()$osm
```

```
# for mapbox only
get_maotypes("mapbox")
# or
get_maotypes()$mapbox

# same for all other map services
```

join_frames	<i>Join multiple frames lists into a single frames list</i>
-------------	---

Description

This function side-by-side joins the ggplot2 objects of two or more frames lists of equal lengths into a single plot per frame using `plot_grid`. This is useful if you want to side-by-side combine spatial frames returned by `frames_spatial` with graph frames returned by `frames_graph`.

Usage

```
join_frames(frames_lists, ..., verbose = T)
```

Arguments

<code>frames_lists</code>	list, a list of two or more frames lists that you want to combine. All frames lists contained in <code>frames_lists</code> must be of equal lengths. The contained ggplot2 objects are passed frame-wise to the <code>plotlist</code> argument of <code>plot_grid</code> .
<code>...</code>	Further arguments, specifying the appearance of the joined ggplot2 objects, passed to <code>plot_grid</code> . See <code>plot_grid</code> for further options.
<code>verbose</code>	logical, if TRUE, messages on the function's progress are displayed (default).

Value

List of ggplot2 objects, each representing a single frame.

See Also

[frames_spatial](#) [frames_graph](#) [animate_frames](#)

Examples

```
## Not run:
library(moveVis)
library(move)

data("move_data", "basemap_data")
# align movement
m <- align_move(move_data, res = 4, unit = "mins")
```



```

# create spatial frames and graph frames:
r_list <- basemap_data[[1]]
r_times <- basemap_data[[2]]

frames.sp <- frames_spatial(m, r_list = r_list, r_times = r_times, r_type = "gradient",
                           fade_raster = TRUE)
frames.sp <- add_colourscale(frames.sp, type = "gradient",
                           colours = c("orange", "white", "darkgreen"), legend_title = "NDVI")
frames.flow <- frames_graph(m, r_list, r_times, path_legend = FALSE, graph_type = "flow")
frames.hist <- frames_graph(m, r_list, r_times, path_legend = FALSE, graph_type = "hist")

# check lengths (must be equal)
sapply(list(frames.sp, frames.flow, frames.hist), length)

# Let's join the graph frames vertically
frames.join.gr <- join_frames(list(frames.flow, frames.hist), ncol = 1, nrow = 2)
frames.join.gr[[100]]

# Now, let's join the joined graph frames with the spatial frames horizontally
# in 2:1 ration and align all axis
frames.join <- join_frames(list(frames.sp, frames.join.gr),
                          ncol = 2, nrow = 1, rel_widths = c(2, 1), axis = "tb")
frames.join[[100]]
# in a standard graphics device, this looks a bit unproportional
# however when setting the correct width, height and resolution of a graphic device,
# it will come out well aligned.

# Do so for example with animate_move() with width = 900, dheight = 500 and res = 90
animate_frames(frames.join, out_file = tempfile(fileext = ".gif"), fps = 25,
              width = 900, height = 500, res = 90, display = TRUE, overwrite = TRUE)

## End(Not run)

```

move_data

Exemplary simulated movement tracks

Description

This dataset contains a Move object, representing coordinates and acquisition times of three simulated movement tracks, covering a location nearby Lake of Constance, Germany. Individual names are made up for demonstration purposes.

Usage

```
move_data
```

Format

Move object, as used by the move package.

Details

This object is used by some moveVis examples and unit tests.

Note

All data contained should only be used for testing moveVis and are not suitable to be used for analysis or interpretation.

subset_move

Subset a move or moveStack object by a given time span

Description

This function is a simple wrapper that subsets a move or moveStack by a given time span. A move or moveStack containing data only for the subset time span is returned.

Usage

```
subset_move(m, from, to, tz = "UTC")
```

Arguments

m	a move or moveStack object (see df2move to convert a data.frame to a move object).
from	character or POSIXct, representing the start time. If character, the format "%m-%d-%y %H:%M:%S" must be used (see strptime).
to	character or POSIXct, representing the stop time. If character, the format "%m-%d-%y %H:%M:%S" must be used (see strptime).
tz	character, time zone that should be used if from and/or to are of type character.

Value

A move or moveStack object.

See Also

[df2move](#)

Examples

```
library(moveVis)
library(move)

# load the example data
data("move_data")

# check min and max of move_data timestamps
```

```
min(timestamps(move_data))
max(timestamps(move_data))

# subset by character times
m <- subset_move(move_data, from = "2018-05-15 07:00:00", to = "2018-05-15 18:00:00")

# check min and max of result
min(timestamps(m))
max(timestamps(m))
```

suggest_formats	<i>Suggest known file formats</i>
-----------------	-----------------------------------

Description

This function returns a selection of suggested file formats that can be used with `out_file` of [animate_frames](#) on your system.

Usage

```
suggest_formats(suggested = c("gif", "mov", "mp4", "flv", "avi", "mpeg",
                              "3gp", "ogg"))
```

Arguments

`suggested` character, a vector of suggested file formats which are checked to be known by the available renderers on the running system. By default, these are `c("gif", "mov", "mp4", "flv", "a`

Value

A subset of `suggested`, containing only those file formats which are known by the renderers on the running system.

See Also

[animate_frames](#)

Examples

```
# find out which formats are available
suggest_formats()

# check for a particular format not listed in "suggested" that you want to use, e.g. m4v
suggest_formats("m4v")
# if "m4v" is returned, you can use this format with animate_frames
```

view_spatial	<i>View movements on an interactive map</i>
--------------	---

Description

view_spatial is a simple wrapper that displays movement tracks on an interactive mapview or leaflet map.

Usage

```
view_spatial(m, render_as = "mapview", time_labels = TRUE,
             stroke = TRUE, path_colours = NA, path_legend = TRUE,
             path_legend_title = "Names", verbose = TRUE)
```

Arguments

m	move or moveStack. May contain a column named colour to control path colours (see details).
render_as	character, either 'mapview' to return a mapview map or 'leaflet' to return a leaflet map.
time_labels	logical, whether to display timestamps for each track fix when hovering it with the mouse cursor.
stroke	logical, whether to draw stroke around circles.
path_colours	character, a vector of colours. Must be of same length as number of individual tracks in m and refers to the order of tracks in m. If undefined (NA) and m contains a column named colour, colours provided within m are used (see details). Otherwise, colours are selected randomly per individual track.
path_legend	logical, whether to add a path legend from m or not. Legend tracks and colours will be ordered by the tracks' temporal appearances, not by their order in m.
path_legend_title	character, path legend title. Default is "Names".
verbose	logical, if TRUE, messages on the function's progress are displayed (default).

Details

If argument path_colours is not defined (set to NA), path colours can be defined by adding a character column named colour to m, containing a colour code or name per row (e.g. "red"). This way, for example, column colour for all rows belonging to individual A can be set to "green", while column colour for all rows belonging to individual B can be set to "red". Colours could also be arranged to change through time or by behavioral segments, geographic locations, age, environmental or health parameters etc. If a column name colour in m is missing, colours will be selected automatically. Call colours() to see all available colours in R.

Value

An interactive mapview or leaflet map.

Author(s)

Jakob Schwalb-Willmann

See Also

[frames_spatial](#)

Examples

```
## Not run:
library(moveVis)
library(move)

data("move_data")

# return a mapview map (mapview must be installed)
view_spatial(move_data)

# return a leaflet map (leaflet must be installed)
view_spatial(move_data, render_as = "leaflet")

# turn off time labels and legend
view_spatial(move_data, time_labels = FALSE, path_legend = FALSE)

## End(Not run)
```

%>%

Re-exported magrittr forward pipe operator

Description

moveVis has been designed to work with the [magrittr](#) forward pipe operator %>%, which therefore is re-exported by moveVis.

Details

For a detailed documentation, follow this link: [%>%](#)

Index

*Topic **datasets**

- basemap_data, 20
- move_data, 33
- %>%, 37, 37

- add_colourscale, 3, 4, 28
- add_gg, 3, 5
- add_labels, 3, 8
- add_northarrow, 3, 10
- add_progress, 3, 11
- add_scalebar, 3, 12
- add_text, 3, 14, 16
- add_timestamps, 3, 15
- align_move, 2, 17, 23, 26
- animate_frames, 3, 5, 7, 9, 10, 12, 13, 15, 16, 18, 21, 23–25, 27, 28, 32, 35
- animate_move (deprecated), 21
- animate_raster (deprecated), 21
- animate_stats (deprecated), 21

- basemap_data, 20

- deprecated, 21
- df2move, 2, 17, 18, 22, 34

- expr, 6

- frames_graph, 3, 5, 7, 9, 10, 12, 13, 15, 16, 18, 19, 21, 22, 23, 24, 28, 30, 32
- frames_spatial, 2–19, 21, 22, 24, 25, 30–32, 37

- get_formats (deprecated), 21
- get_frametimes, 3, 30
- get_libraries (deprecated), 21
- get_maotypes, 2, 26, 31

- join_frames, 3, 19, 21, 24, 28, 32

- magrittr, 37
- move, 22

- move_data, 33
- moveVis (moveVis-package), 2
- moveVis-package, 2

- plot_grid, 3, 32

- strptime, 34
- subset_move, 2, 22, 34
- suggest_formats, 3, 19, 35

- view_spatial, 3, 36