

Using ‘buildmer’ to automatically find & compare maximal (mixed) models

Cesko C. Voeten

19 April 2019

Introduction

Barr, Levy, Scheepers, & Tily (2013) suggest that for valid statistical inference, a regression model must control for all possible confounding factors, specifically those coming from random effects such as subjects and items. Bates, Kliegl, Vasishth, & Baayen (2015) suggest that this proposed strategy leads to overfitting and that an appropriately-parsimonious model must be chosen, preferably based on theory but possibly also using stepwise elimination (Matuschek, Kliegl, Vasishth, Baayen, & Bates, 2017). Both strategies require a maximal model to be identified (for Barr et al. (2013), this is the final model; for Matuschek et al. (2017), this is the basis for backward stepwise elimination), but for many psycholinguistic experiments, the *truly* maximal model will fail to converge and a reasonable subset model needs to be chosen.

The `buildmer` package aims to automate the procedures identifying the maximal model that can still converge & performing backward stepwise elimination based on a variety of criteria (change in log-likelihood, AIC, BIC). The package does not contain any model-fitting code, but functions as an administrative loop around other packages by simply building up a maximal formula object and passing it along. Currently, the package supports models that can be fitted by `(g)lm`, `(g)lmer` (package `lme4`), `gls`, `lme` (package `nlme`), `gam`, `bam` (package `mgcv`), `gamm4` (package `gamm4`), `glmmTMB` (package `glmmTMB`), `multinom` (package `nnet`), and it can use `JuliaCall` to drive Douglas Bates’s `MixedModels` package for Julia.

A vowel study

To illustrate what `buildmer` can do for you, the package comes with a particularly pathological dataset called `vowels`. It looks like this:

```
library(buildmer)
head(vowels)
```

```
##   participant   word vowel neighborhood  timepoint      f1      f2
## 1           1 Keulen  oey      36.1961 0.05118788 407.8202 1838.611
## 2           1 Keulen  oey      36.1961 0.11941466 416.2701 1635.436
## 3           1 Keulen  oey      36.1961 0.18764143 450.6488 1654.561
## 4           1 Keulen  oey      36.1961 0.25586821 449.7890 1645.075
## 5           1 Keulen  oey      36.1961 0.32409498 444.6863 1606.261
## 6           1 Keulen  oey      36.1961 0.39232176 438.5311 1607.581
## following information stress
## 1          10ns    4.511475  TRUE
## 2          10ns    4.511475  TRUE
## 3          10ns    4.511475  TRUE
## 4          10ns    4.511475  TRUE
## 5          10ns    4.511475  TRUE
## 6          10ns    4.511475  TRUE
```

This is a pilot study that I conducted when I was just starting my PhD, and attempted to analyze in probably the worst way possible. The research question was whether vowel diphthongization in the Dutch vowels /e:,ø:,o:,ei,œy/ was affected by syllable structure, such that an /l/ within the same syllable would block diphthongization but an /l/ in the onset of the next syllable would permit it. In plain English, the question

was whether these five vowels in Dutch were pronounced like the vowel in English ‘fear’, with the tongue held constant for the duration of the vowel, or like the vowel in English ‘fade’, which has an upward tongue movement towards the position of the vowel in English ‘fit’. The position of the tongue can be measured in a simple word-list reading experiment by measuring the speech signal’s so-called ‘first formant’, labeled `f1` in this dataset, where lower F1 = higher tongue. Thus, the research question is if the F1 either changes or remains stable for the duration of each vowel depending on whether the following consonant is an ‘l’ in the same syllable (coded as `lCda` in column `following`) or in the next syllable (coded as `l0ns`). Additionally, I wanted to control for the factors `neighborhood` (a measure of entropy: ‘if only one sound is changed anywhere in this word, how many new words could be generated?’), `information` (another measure of entropy derived from the famous Shannon information measure), and `stress` (a dummy encoding whether the vowel was stressed or unstressed).

An entirely reasonable way to analyze these data, and the approach I ultimately pursued later in my PhD, would be to take samples from each vowel at 75% realization and at 25% realization, subtract these two, and use this ‘delta score’ as dependent variable: if this score is non-zero, the vowel changes over time, if it is approximately zero, the vowel was stable. In this dataset, however, I instead took as many samples as were present in the part of the wave file corresponding to these vowels, and wanted to fit a linear regression line through all of these samples as a function of the sample number. This number, scaled from 0 to 1 per token, is listed in column `timepoint`. To make the model even more challenging to fit, only six participants were tested in this pilot study, making it very difficult to find an optimum when including a full random-slope structure.

In `lme4` syntax, the fully maximal model would be given by the following formula:

```
f <- f1 ~ vowel*timepoint*following * neighborhood*information*stress +
      (vowel*timepoint*following * neighborhood+information+stress | participant) +
      (timepoint | word)
```

It should go without saying that this is a completely unreasonable model that will never converge. A first step towards reducing the model structure could be to reason that effects of `neighborhood`, `information`, and `stress`, which are all properties of the individual words in this data set, could be subsumed into the random effects by words. This reduces the maximal model to:

```
f <- f1 ~ vowel*timepoint*following +
      (vowel*timepoint*following | participant) +
      (timepoint | word)
```

This model is still somewhat on the large side, so we will now use `buildmer` to check: - if this model is capable of converging at all; - if all of these terms are really necessary.

Finding the maximal *feasible* model & doing stepwise elimination from it

To illustrate `buildmer`’s modular capabilities, we’ll fit this model in two steps. We start by identifying the maximal model that is still capable of converging. We do this by running `buildmer`, with the `direction` argument set to ‘`order`’. We also set `lme4`s optimizer to `bobyqa`, as this manages to get much further than the default `nloptwrap`. The output of the command is edited for brevity.

```
library(lme4)
m <- buildmer(f,data=vowels,direction='order',control=lmerControl(optimizer='bobyqa'))
```

The `order` step is useful if the maximal model includes random effects: `buildmer` will start out with an empty model and keeps adding terms to this model until convergence can no longer be achieved. The `order` step adds terms in order of their contribution to a certain criterion, such that the most important random slopes will be included first; this criterion is controlled by the `crit` argument. The default criterion is the significance of the change in log-likelihood (LRT: terms which provide lower chi-square *p* values are considered

more important), but other options are also supported. These are the raw log-likelihood (LL: terms which provide the largest increase in the log-likelihood; this measure will favor categorical predictors with many levels), AIC (AIC), and BIC (BIC); you can select among them by passing e.g. `crit='LRT'`. The default direction is `c('order', 'backward')`, i.e. proceeding directly to backward stepwise elimination, but for illustration purposes we separate those steps here. (The `crit` argument also accepts vectors, such that e.g. `direction=c('order', 'backward'), crit=c('LL', 'LRT')` is allowed.)

After a lot of model fits, the model converges onto the following maximal model:

```
(f <- formula(m@model))

## f1 ~ following + vowel + timepoint + vowel:timepoint + following:timepoint +
##   following:vowel + following:vowel:timepoint + (1 + timepoint |
##   word) + (1 + timepoint + following + timepoint:following |
##   participant)
## <environment: 0x559be131c450>
```

The maximal *feasible* model, i.e. the maximal model that is actually capable of converging, is one excluding random slopes for vowels by participants. This is not optimal for inference purposes, but for now it will do; we will see below that taking out the correlation parameters in the random effects makes it possible to include random slopes for vowels as well. We now proceed to the next step: stepwise elimination. This could also be done using e.g. `lmerTest`, but since the machinery was needed for `direction='order'` anyway it came at very little cost to also implement stepwise elimination in `buildmer` (both forward and backward are supported). This used the same elimination criterion as could be specified previously; if left unspecified, it defaults to `crit='LRT'`, for the likelihood-ratio test. This is the preferred test for mixed models in Matuschek et al. (2017).

```
m <- buildmer(f, data=vowels, direction='backward', control=lmerControl(optimizer='bobyqa'))
```

By default, `buildmer` automatically calculates summary and ANOVA statistics based on Wald z -scores (summary) or Wald χ^2 tests (ANOVA). For answering our research question, we look at the summary:

```
summary(m)

## Linear mixed model fit by REML (p-values based on Wald z-scores) [lmerMod]
## Formula:
## f1 ~ following + vowel + timepoint + vowel:timepoint + following:timepoint +
##   (1 + timepoint | word) + (1 + timepoint + following + timepoint:following |
##   participant)
## Data: vowels
##
## REML criterion at convergence: 149448.9
##
## Scaled residuals:
##   Min      1Q  Median      3Q      Max
## -6.2346 -0.4169  0.0102  0.3876 21.6814
##
## Random effects:
##   Groups      Name                Variance Std.Dev. Corr
##   word       (Intercept)           2538.6   50.38
##             timepoint            11082.8  105.27  -0.78
##   participant (Intercept)           2195.9   46.86
##             timepoint              3409.8   58.39  -0.50
##             following10ns           741.1   27.22   0.11  0.65
##             timepoint:following10ns 3046.0   55.19   0.64 -0.88 -0.67
## Residual                               10018.2  100.09
## Number of obs: 12351, groups:  word, 148; participant, 6
```

```

##
## Fixed effects:
##
##           Estimate Std. Error t value Pr(>|t|)
## (Intercept)      551.733    20.059  27.506 < 2e-16 ***
## followingl0ns      49.106    14.468   3.394 0.000688 ***
## vowel1           114.253     8.950  12.766 < 2e-16 ***
## vowel2           142.083     8.909  15.947 < 2e-16 ***
## vowel3           -125.955     8.625 -14.603 < 2e-16 ***
## vowel4            -79.211     9.969  -7.946 1.93e-15 ***
## timepoint        -15.445    26.812  -0.576 0.564579
## vowel1:timepoint  -39.662    18.234  -2.175 0.029616 *
## vowel2:timepoint  -91.032    18.166  -5.011 5.42e-07 ***
## vowel3:timepoint  105.886    17.550   6.033 1.61e-09 ***
## vowel4:timepoint   38.923    20.266   1.921 0.054774 .
## followingl0ns:timepoint -136.888    29.387  -4.658 3.19e-06 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##           (Intr) fllwn0 vowel1 vowel2 vowel3 vowel4 timpnt vw11:t vw12:t
## follwngl0ns -0.045
## vowel1      -0.014  0.020
## vowel2      -0.017  0.025 -0.225
## vowel3      -0.029  0.031 -0.210 -0.207
## vowel4       0.034 -0.031 -0.278 -0.276 -0.266
## timepoint   -0.535  0.595  0.017  0.020  0.034 -0.041
## vw11:tmpnt  0.011 -0.016 -0.787  0.177  0.165  0.218 -0.021
## vw12:tmpnt  0.013 -0.020  0.177 -0.787  0.163  0.217 -0.025 -0.226
## vw13:tmpnt  0.023 -0.024  0.166  0.164 -0.788  0.210 -0.044 -0.210 -0.208
## vw14:tmpnt -0.027  0.024  0.219  0.218  0.210 -0.788  0.051 -0.277 -0.276
## fllwngl0ns: 0.568 -0.720 -0.016 -0.020 -0.024  0.024 -0.788  0.020  0.024
##           vw13:t vw14:t
## follwngl0ns
## vowel1
## vowel2
## vowel3
## vowel4
## timepoint
## vw11:tmpnt
## vw12:tmpnt
## vw13:tmpnt
## vw14:tmpnt -0.265
## fllwngl0ns: 0.031 -0.030
## convergence code: 0
## Model failed to converge with max|grad| = 0.00780211 (tol = 0.002, component 1)

```

The highly-significant effect for `followingl0ns:timepoint` shows that if the following /l/ is in the onset of the next syllable, there is a much larger change in F1 compared to the reference condition of having the following /l/ in the coda of the same syllable.

Diagonal random-effects covariances

One hidden feature that is present in `buildmer` but that has not yet been discussed is the ability to group terms together in blocks for ordering and stepwise-elimination purposes. This is not documented because it

requires some knowledge of `buildmer` internals, but this vignette offers an opportunity to demonstrate how this can be done. While the first argument to `buildmer` functions is normally a formula, it is also possible to pass a data frame as generated by `tabulate.formula`:

```
tabulate.formula(f)
```

```
##      index      grouping      term
## 1  <NA>      <NA>          1
## 2  <NA>      <NA>      following
## 3  <NA>      <NA>          vowel
## 4  <NA>      <NA>      timepoint
## 5  <NA>      <NA>      vowel:timepoint
## 6  <NA>      <NA>      following:timepoint
## 7  <NA>      <NA>      following:vowel
## 8  <NA>      <NA>      following:vowel:timepoint
## 9    9 1      word          1
## 10   9 1      word      timepoint
## 11  10 1 participant      1
## 12  10 1 participant      timepoint
## 13  10 1 participant      following
## 14  10 1 participant      timepoint:following
##
##      code block
## 1      NA NA 1      1
## 2      NA NA following 2
## 3      NA NA vowel 3
## 4      NA NA timepoint 4
## 5      NA NA vowel:timepoint 5
## 6      NA NA following:timepoint 6
## 7      NA NA following:vowel 7
## 8      NA NA following:vowel:timepoint 8
## 9      9 1 word 1      9
## 10     9 1 word timepoint 10
## 11     10 1 participant 1 11
## 12     10 1 participant timepoint 12
## 13     10 1 participant following 13
## 14    10 1 participant timepoint:following 14
```

This is an internal `buildmer` data structure, but it is rather self-explanatory in how it is used. It is possible to modify the `block` column to force terms to be evaluated as a single group, rather than separately, by giving these terms the same `block` value. These values are not used in any other way than this purpose of selecting terms to be grouped together; they therefore do not even have to be numerics.

This data structure can be used to fit models with diagonal random-effects structures. The `buildmer()` function documentation provides an example, which we will follow here. The first step is to create explicit columns for the factor `vowel`; if this is not done, only random-effect correlations between vowels and *other* random slopes will be eliminated and those between the vowels themselves will remain.

```
vowels <- cbind(vowels,model.matrix(~vowel,vowels))
```

We next create a formula for this modified data set. To make it easier to type, we do not explicitly diagonalize the formula ourselves, but use `buildmer`'s `diag()` method for `formula` objects. We then call `tabulate.formula()` on the new formula. Note that we *cannot* use the simple `vowel` factor in the fixed-effects part of the formula, as this will break `buildmer`'s marginality checks when considering which terms are eligible for inclusion or removal.

```
form <- diag(f1 ~ (vowel1+vowel2+vowel3+vowel4)*timepoint*following +
             ((vowel1+vowel2+vowel3+vowel4)*timepoint*following | participant) +
```

```
(timepoint | word))
(terms <- tabulate.formula(form))
```

```
##      index      grouping      term
## 1  <NA>      <NA>          1
## 2  <NA>      <NA>        vowel1
## 3  <NA>      <NA>        vowel2
## 4  <NA>      <NA>        vowel3
## 5  <NA>      <NA>        vowel4
## 6  <NA>      <NA>        timepoint
## 7  <NA>      <NA>    vowel1:timepoint
## 8  <NA>      <NA>    vowel2:timepoint
## 9  <NA>      <NA>    vowel3:timepoint
## 10 <NA>      <NA>    vowel4:timepoint
## 11 <NA>      <NA>        following
## 12 <NA>      <NA>    vowel1:following
## 13 <NA>      <NA>    vowel2:following
## 14 <NA>      <NA>    vowel3:following
## 15 <NA>      <NA>    vowel4:following
## 16 <NA>      <NA>    timepoint:following
## 17 <NA>      <NA> vowel1:timepoint:following
## 18 <NA>      <NA> vowel2:timepoint:following
## 19 <NA>      <NA> vowel3:timepoint:following
## 20 <NA>      <NA> vowel4:timepoint:following
## 21 21 1 participant      1
## 22 22 1 participant    vowel1
## 23 23 1 participant    vowel2
## 24 24 1 participant    vowel3
## 25 25 1 participant    vowel4
## 26 26 1 participant    timepoint
## 27 27 1 participant    vowel1:timepoint
## 28 28 1 participant    vowel2:timepoint
## 29 29 1 participant    vowel3:timepoint
## 30 30 1 participant    vowel4:timepoint
## 31 31 1 participant    following
## 32 32 1 participant    vowel1:following
## 33 33 1 participant    vowel2:following
## 34 34 1 participant    vowel3:following
## 35 35 1 participant    vowel4:following
## 36 36 1 participant    timepoint:following
## 37 37 1 participant    vowel1:timepoint:following
## 38 38 1 participant    vowel2:timepoint:following
## 39 39 1 participant    vowel3:timepoint:following
## 40 40 1 participant    vowel4:timepoint:following
## 41 41 1      word      1
## 42 42 1      word      timepoint
##
##      code block
## 1      NA NA 1      1
## 2      NA NA vowel1  2
## 3      NA NA vowel2  3
## 4      NA NA vowel3  4
## 5      NA NA vowel4  5
## 6      NA NA timepoint 6
## 7      NA NA vowel1:timepoint 7
```

```

## 8          NA NA vowel2:timepoint      8
## 9          NA NA vowel3:timepoint      9
## 10         NA NA vowel4:timepoint     10
## 11                NA NA following     11
## 12         NA NA vowel1:following     12
## 13         NA NA vowel2:following     13
## 14         NA NA vowel3:following     14
## 15         NA NA vowel4:following     15
## 16                NA NA timepoint:following 16
## 17        NA NA vowel1:timepoint:following 17
## 18        NA NA vowel2:timepoint:following 18
## 19        NA NA vowel3:timepoint:following 19
## 20        NA NA vowel4:timepoint:following 20
## 21                21 1 participant 1     21
## 22                22 1 participant vowel1  22
## 23                23 1 participant vowel2  23
## 24                24 1 participant vowel3  24
## 25                25 1 participant vowel4  25
## 26                26 1 participant timepoint 26
## 27        27 1 participant vowel1:timepoint 27
## 28        28 1 participant vowel2:timepoint 28
## 29        29 1 participant vowel3:timepoint 29
## 30        30 1 participant vowel4:timepoint 30
## 31                31 1 participant following 31
## 32        32 1 participant vowel1:following 32
## 33        33 1 participant vowel2:following 33
## 34        34 1 participant vowel3:following 34
## 35        35 1 participant vowel4:following 35
## 36        36 1 participant timepoint:following 36
## 37 37 1 participant vowel1:timepoint:following 37
## 38 38 1 participant vowel2:timepoint:following 38
## 39 39 1 participant vowel3:timepoint:following 39
## 40 40 1 participant vowel4:timepoint:following 40
## 41                41 1 word 1     41
## 42                42 1 word timepoint     42

```

We next need to instruct `buildmer` that terms belonging to the same vowel terms should be evaluated as a single group. This can be done by giving them the same identifier in the `block` column. This can be any numeric or character string, as long as it is the same for terms belonging to the same block.

```

terms[ 2: 5, 'block'] <- 'same1'
terms[ 7:10, 'block'] <- 'same2'
terms[12:15, 'block'] <- 'same3'
terms[17:20, 'block'] <- 'same4'
terms[22:25, 'block'] <- 'same5'
terms[27:30, 'block'] <- 'same6'
terms[32:35, 'block'] <- 'same7'
terms[37:40, 'block'] <- 'same8'

```

Finally, we can instruct `buildmer` to use this specially-crafted `terms` object by simply passing it along instead of a regular formula. `buildmer` will recognize what is going on, and look for an additional `dep` argument for the name of the dependent variable in the data frame (provided as a character string).

```

m <- buildmer(terms, data=vowels, dep='f1', control=lmerControl(optimizer='bobyqa'))

```

This approach allows random slopes for `vowel` and for `vowel:timepoint` to make it in, both of which

significantly improve model fit. This model seems much more adequate for statistical inference.

Other options

Because `buildmer` does not do any model fitting by itself but is only an administrative formula processor around pre-existing modeling functions, it was straightforward to extend it beyond its original purpose of mixed-effects models. The logical extension of `buildmer` to GAMMs is fully supported (with the exception of `gamm` models; see `buildgamm()` for options). Relevant functions are available as `buildgam`, `buildbam`, and `buildgamm4`. `glmmTMB` models are also supported, although their syntax for covariance structures (e.g. `diag(timepoint | participant)`) is not; these models are still useful for their ability to handle autocorrelation, zero-inflation, and to use REML for GLMMs. At the request of Willemijn Heeren, `buildmer` was also extended to handle multinomial-logistic-regression models fitted by function `multinom` from package `nnet`. It is also possible to use `buildjulia` to drive Douglas Bates's `MixedModels` package for Julia.

References

- Barr, D. J., Levy, R., Scheepers, C., & Tily, H. J. (2013). Random effects structure for confirmatory hypothesis testing: Keep it maximal. *Journal of Memory and Language*, *68*(3), 255–278.
- Bates, D., Kliegl, R., Vasishth, S., & Baayen, H. (2015). Parsimonious mixed models. *arXiv Preprint arXiv:1506.04967*.
- Matuschek, H., Kliegl, R., Vasishth, S., Baayen, H., & Bates, D. (2017). Balancing Type I error and power in linear mixed models. *Journal of Memory and Language*, *94*, 305–315.