

Package ‘enviGCMS’

May 14, 2019

Type Package

Title GC/LC-MS Data Analysis for Environmental Science

Version 0.5.5

Date 2019-05-14

Maintainer Miao YU <yufreecas@gmail.com>

Description Gas/Liquid Chromatography-Mass Spectrometer(GC/LC-MS) Data Analysis for Environmental Science. This package covered topics such molecular isotope ratio, matrix effects and Short-Chain Chlorinated Paraffins analysis etc. in environmental analysis.

URL <https://github.com/yufree/enviGCMS>

License GPL-2

Encoding UTF-8

LazyData true

Suggests knitr, testthat, xcms, MSnbase

VignetteBuilder knitr

biocViews

Depends R (>= 2.10)

Imports rcdk, RColorBrewer, mixtools, BiocParallel, genefilter, grDevices, graphics, stats, utils, methods, reshape2, animation (>= 2.2.3), data.table, rmarkdown, shiny, shinythemes, DT, crosstalk, dplyr, plotly, broom, itertools, iterators, igraph, ggraph, ggplot2, ggridges

RoxygenNote 6.1.1

NeedsCompilation no

Author Miao YU [aut, cre] (<<https://orcid.org/0000-0002-2804-6014>>),
Thanh Wang [ctb] (<<https://orcid.org/0000-0002-5729-1908>>)

Repository CRAN

Date/Publication 2019-05-14 16:10:03 UTC

R topics documented:

batch	3
cbmd	4
findline	5
findohc	5
getarea	6
getareastd	7
getbgremove	8
getbiotechrep	8
getcsv	9
getdata	10
getdata2	11
getdoe	12
getfeaturesanova	13
getfeaturest	14
getfilter	14
getformula	15
getgrouprep	16
getimputation	16
GetIntegration	17
Getisotopologues	18
getmass	18
getmassdefect	19
getmd	20
getmdh	20
getmdr	21
getmr	22
getmzrt	23
getmzrt2	24
getmzrtcsv	25
getoverlapmass	25
getoverlappeak	26
getoverlaprt	26
getpower	27
getQCraw	28
getrmd	28
getsccp	29
getsim	29
gettechrep	30
gettimegrouprep	31
getupload	31
getupload2	32
getupload3	33
gifmr	34
Integration	35
list	35
ma	36

Mode	36
plotden	37
plote	37
plotgroup	38
plothist	39
plothm	39
plotint	40
plotintslope	40
plotkms	41
plotmr	41
plotmrc	42
plotms	43
plotmsrt	43
plotmz	44
plotpca	45
plotridges	46
plotrla	46
plotsrd	47
plotrtms	47
plotsms	48
plotsub	49
plott	49
plottic	50
qbatch	50
runMDPlot	51
runsccp	51
sccp	52
submd	52
svabatch	53
svacor	54
svadata	55
svapca	56
svaplot	57
svaupload	58
writeMSP	58

Index **60**

batch *Get the MIR and related information from the files*

Description

Get the MIR and related information from the files

Usage

batch(file, mz1, mz2)

Arguments

file data file, CDF or other format supported by xcmsRaw
mz1 the lowest mass
mz2 the highest mass

Value

Molecular isotope ratio

Examples

```
## Not run:  
mr <- batch(data,mz1 = 79, mz2 = 81)  
  
## End(Not run)
```

cbmd	<i>Combine two data with similar retention time while different mass range</i>
------	--

Description

Combine two data with similar retention time while different mass range

Usage

```
cbmd(data1, data2, mzstep = 0.1, rtstep = 0.01)
```

Arguments

data1 data file path of lower mass range
data2 data file path of higher mass range
mzstep the m/z step for generating matrix data from raw mass spectral data
rtstep the alignment accuracy of retention time, e.g. 0.01 means the retention times of combined data should be the same at the accuracy 0.01s. Higher rtstep would return less scans for combined data

Value

matrix with the row as scantime in second and column as m/z

Examples

```
## Not run:  
# mz100_200 and mz201_300 were the path to the raw data  
matrix <- getmd(mz100_200,mz201_300)  
  
## End(Not run)
```

findline	<i>find line of the regression model for GC-MS</i>
----------	--

Description

find line of the regression model for GC-MS

Usage

```
findline(data, threshold = 2, temp = c(100, 320))
```

Arguments

data	imported data matrix of GC-MS
threshold	the threshold of the response (log based 10)
temp	the scale of the oven temprature(constant rate)

Value

list linear regression model for the matrix

Examples

```
## Not run:  
data <- getmd(rawdata)  
findline(data)  
  
## End(Not run)
```

findohc	<i>Screen organohalogen compounds by retention time, mass defect analysis and isotope relationship modified by literature report. Also support compounds with [M] and [M+2] ratio cutoff.</i>
---------	---

Description

Screen organohalogen compounds by retention time, mass defect analysis and isotope relationship modified by literature report. Also support compounds with [M] and [M+2] ratio cutoff.

Usage

```
findohc(list, sf = 78/77.91051, step = 0.001, stepsd1 = 0.003,  
        stepsd2 = 0.005, mzc = 700, cutoffint = 1000, cutoffr = 0.4,  
        clusterfcf = 10)
```

Arguments

list	list with data as peaks list, mz, rt and group information, retention time should be in seconds
sf	scale factor, default 78/77.91051(Br)
step	mass defect step, default 0.001
stepsd1	mass defect uncertainty for lower mass, default 0.003
stepsd2	mass defect uncertainty for higher mass, default 0.005
mzc	threshold of lower mass and higher mass, default 700
cutoffint	the cutoff of intensity, default 1000
cutoffr	the cutoff of [M] and [M+2] ratio, default 0.4
clustercf	the cutoff of cluster analysis to separate two different ions groups for mass distances and retention time, default 10

Value

list with filtered organohalogen compounds

References

Identification of Novel Brominated Compounds in Flame Retarded Plastics Containing TBBPA by Combining Isotope Pattern and Mass Defect Cluster Analysis Ana Ballesteros-Gómez, Joaquín Ballesteros, Xavier Ortiz, Willem Jonker, Rick Helmus, Karl J. Jobst, John R. Parsons, and Eric J. Reiner *Environmental Science & Technology* 2017 51 (3), 1518-1526 DOI: 10.1021/acs.est.6b03294

getarea

Get the peak information from sampels for SCCPs detection

Description

Get the peak information from sampels for SCCPs detection

Usage

```
getarea(data, ismz = 323, ppm = 5, rt = NULL, rts = NULL)
```

Arguments

data	list from 'xcmsRaw' function
ismz	internal standards m/z
ppm	resolution of mass spectrum
rt	retention time range of sccps
rts	retention time range of internal standards

Value

list with peak information

See Also

[getareastd](#), [getsccp](#)

getareastd	<i>Get the peak information from SCCPs standards</i>
------------	--

Description

Get the peak information from SCCPs standards

Usage

```
getareastd(data = NULL, ismz = 323, ppm = 5, con = 2000,  
           rt = NULL, rts = NULL)
```

Arguments

data	list from 'xcmsRaw' function
ismz	internal standards m/z
ppm	resolution of mass spectrum
con	concentration of standards
rt	retention time range of sccps
rts	retention time range of internal standards

Value

list with peak information

See Also

[getarea](#), [getsccp](#)

getbgremove *Get the peak list with blank samples' peaks removed*

Description

Get the peak list with blank samples' peaks removed

Usage

```
getbgremove(xset, method = "medret", intensity = "into", file = NULL,  
            rsdcf = 30, inscf = 1000)
```

Arguments

xset	the xcmsset object with blank and certain group samples' data
method	parameter for groupval function
intensity	parameter for groupval function
file	file name for further annotation, default NULL
rsdcf	rsd cutoff for peaks, default 30
inscf	intensity cutoff for peaks, default 1000

Value

diff report

Examples

```
## Not run:  
library(faahK0)  
cdfpath <- system.file("cdf", package = "faahK0")  
xset <- getdata(cdfpath, pmethod = ' ')  
getbgremove(xset)  
  
## End(Not run)
```

getbiotechrep *Get the report for biological replicates.*

Description

Get the report for biological replicates.

Usage

```
getbiotechrep(xset, method = "medret", intensity = "into",  
             file = NULL, rsdcf = 30, inscf = 1000)
```


Arguments

xset	the xcmsset object which for all of your technique replicates for bio replicated sample in single group
method	parameter for groupval function
intensity	parameter for groupval function
file	file name for further annotation, default NULL
rsdcf	rsd cutoff for peaks, default 30
inscf	intensity cutoff for peaks, default 0

Value

dataframe with mean, standard deviation and RSD for those technique replicates & biological replicates combined with raw data

getcsv	<i>Convert an list object to csv file.</i>
--------	--

Description

Convert an list object to csv file.

Usage

```
getcsv(list, name, mzdigit = 4, rtdigit = 1, type = "o", ...)
```

Arguments

list	list with data as peaks list, mz, rt and group information
name	result name for csv and/or eic file, default NULL
mzdigit	m/z digits of row names of data frame, default 4
rtdigit	retention time digits of row names of data frame, default 1
type	csv formate for furthor analysis, m means Metaboanalyst, a means xMSannotator, p means Mummichog(NA values are imputed by ‘getimputation’, and F test is used here to generate stats and p vlaue), o means full infomation csv (for ‘pmd’ package), default o. mapo could output all those format files.
...	other parameters for ‘write.table’

Value

NULL, csv file

References

Li, S.; Park, Y.; Duraisingham, S.; Strobel, F. H.; Khan, N.; Soltow, Q. A.; Jones, D. P.; Pulendran, B. PLOS Computational Biology 2013, 9 (7), e1003123. Xia, J., Sinelnikov, I.V., Han, B., Wishart, D.S., 2015. MetaboAnalyst 3.0—making metabolomics more meaningful. Nucl. Acids Res. 43, W251–W257.

Examples

```
data(list)
getcsv(list,name='demo')
```

getdata	<i>Get xcmsset object in one step with optimized methods.</i>
---------	---

Description

Get xcmsset object in one step with optimized methods.

Usage

```
getdata(path, index = F, BPPARAM = BiocParallel::SnowParam(),
        pmethod = "hplcorbitrap", minfrac = 0.67, ...)
```

Arguments

path	the path to your data
index	the index of the files
BPPARAM	used for BiocParallel package
pmethod	parameters used for different instrumentals such as 'hplcorbitrap', 'uplcorbitrap', 'hplcqtof', 'hplchqtof', 'uplchqtof', 'uplchqtof'. The parameters were from the references
minfrac	minimum fraction of samples necessary in at least one of the sample groups for it to be a valid group, default 0.67
...	arguments for xcmsSet function

Details

the parameters are extracted from the papers. If you use name other than the name above, you will use the default setting of XCMS. Also I suggest IPO packages or apLCMS packages to get reasonable data for your own instrumental. If you want to summit the results to a paper, remember to include those parameters.

Value

a xcmsset object for that path or selected samples

References

Patti, G. J.; Tautenhahn, R.; Siuzdak, G. Nat. Protocols 2012, 7 (3), 508–516.

See Also

[getdata2](#), [getmzrt](#)

Examples

```
## Not run:
library(faahK0)
cdfpath <- system.file('cdf', package = 'faahK0')
xset <- getdata(cdfpath, pmethod = ' ')

## End(Not run)
```

getdata2	<i>Get XCMSnExp object in one step from structured folder path for xcms 3.</i>
----------	--

Description

Get XCMSnExp object in one step from structured folder path for xcms 3.

Usage

```
getdata2(path, index = F, snames = NULL, sclass = NULL,
  phenoData = NULL, BPPARAM = BiocParallel::SnowParam(),
  mode = "onDisk", ppp = xcms::CentWaveParam(ppm = 5, peakwidth = c(5,
  25), prefilter = c(3, 5000)), rtp = xcms::ObiwrapParam(binSize = 1),
  gpp = xcms::PeakDensityParam(sampleGroups = 1, minFraction = 0.67, bw =
  2, binSize = 0.025), fpp = xcms::FillChromPeaksParam())
```

Arguments

path	the path to your data
index	the index of the files
snames	sample names. By default the file name without extension is used
sclass	sample classes.
phenoData	data.frame or NAnnotatedDataFrame defining the sample names and classes and other sample related properties. If not provided, the argument sclass or the sub-directories in which the samples are stored will be used to specify sample grouping.
BPPARAM	used for BiocParallel package
mode	'inMemory' or 'onDisk' see '?MSnbase::readMSData' for details, default 'onDisk'
ppp	parameters for peaks picking, e.g. xcms::CentWaveParam()

rtp	parameters for retention time correction, e.g. <code>xcms::ObiwarpParam()</code>
gpp	parameters for peaks grouping, e.g. <code>xcms::PeakDensityParam()</code>
fpp	parameters for peaks filling, e.g. <code>xcms::FillChromPeaksParam()</code> , <code>PeakGroupsParam()</code>

Details

This is a wrap function for metabolomics data process for xcms 3.

Value

a `XCMSnExp` object with processed data

See Also

[getdata](#), [getmzrt](#)

getdoe	<i>Filter the data based on DoE, rsd, intensity</i>
--------	---

Description

Filter the data based on DoE, rsd, intensity

Usage

```
getdoe(list, inscf = 5, rsdcf = 100, rsdcft = 30, imputation = "1",
        tr = F, BPPARAM = BiocParallel::bpparam())
```

Arguments

list	list with data as peaks list, mz, rt and group information
inscf	Log intensity cutoff for peaks across samples. If any peaks show a intensity higher than the cutoff in any samples, this peaks would not be filtered. default 5
rsdcf	the rsd cutoff of all peaks in all group
rsdcft	the rsd cutoff of all peaks in technical replicates
imputation	parameters for ‘getimputation’ function method
tr	logical. TRUE means dataset with technical replicates at the base level folder
BPPARAM	An optional <code>BiocParallelParam</code> instance determining the parallel back-end to be used during evaluation.

Value

list with group mean, standard deviation, and relative standard deviation for all peaks, and filtered peaks index

See Also

[getdata2](#), [getdata](#), [getmzrt](#), [getimputation](#), [getmr](#), [getpower](#)

Examples

```
data(list)
getdoe(list)
```

getfeaturesanova	<i>Get the features from anova, with p value, q value, rsd and power restriction</i>
------------------	--

Description

Get the features from anova, with p value, q value, rsd and power restriction

Usage

```
getfeaturesanova(list, power = 0.8, pt = 0.05, qt = 0.05, n = 3,
  ng = 3, rsdcf = 100, inscf = 5, imputation = "1", index = NULL)
```

Arguments

list	list with data as peaks list, mz, rt and group information (more than two groups)
power	defined power
pt	p value threshold
qt	q value threshold, BH adjust
n	sample numbers in one group
ng	group numbers
rsdcf	the rsd cutoff of all peaks in all group
inscf	Log intensity cutoff for peaks across samples. If any peaks show a intensity higher than the cutoff in any samples, this peaks would not be filtered. default 5
imputation	parameters for 'getimputation' function method
index	the index of peaks considered, default NULL

Value

dataframe with peaks fit the setting above

getfeaturest	<i>Get the features from t test, with p value, q value, rsd and power restriction</i>
--------------	---

Description

Get the features from t test, with p value, q value, rsd and power restriction

Usage

```
getfeaturest(list, power = 0.8, pt = 0.05, qt = 0.05, n = 3,  
  imputation = "l")
```

Arguments

list	list with data as peaks list, mz, rt and group information (two groups)
power	defined power
pt	p value threshold
qt	q value threshold, BH adjust
n	sample numbers in one group
imputation	parameters for 'getimputation' function method

Value

dataframe with peaks fit the setting above

getfilter	<i>Filter the data based on row and column index</i>
-----------	--

Description

Filter the data based on row and column index

Usage

```
getfilter(list, rowindex = T, colindex = T, name = NULL,  
  type = "o", ...)
```

Arguments

list	list with data as peaks list, mz, rt and group information
rowindex	logical, row index to keep
colindex	logical, column index to keep
name	file name for csv and/or eic file, default NULL
type	csv formate for further analysis, m means Metaboanalyst, a means xMSannotator, p means Mummichog(NA values are imputed by 'getimputation', and F test is used here to generate stats and p vlaue), o means full infomation csv (for 'pmd' package), default o. mapo could output all those format files.
...	other parameters for 'getcsv'

Value

list with remain peaks, and filtered peaks index

See Also

[getdata2](#), [getdata](#), [getmzrt](#), [getimputation](#), [getmr](#), [getcsv](#)

Examples

```
data(list)
li <- getdoe(list)
lif <- getfilter(li,rowindex = li$rsdindex)
```

getformula

Get chemical formula for mass to charge ratio.

Description

Get chemical formula for mass to charge ratio.

Usage

```
getformula(mz, charge = 1, window = 0.001, elements = list(C = c(1,
  50), H = c(1, 50), N = c(0, 50), O = c(0, 50), P = c(0, 1), S = c(0, 1)))
```

Arguments

mz	a vector with mass to charge ratio
charge	The charge value of the formula.
window	The window accuracy in the same units as mass
elements	Elements list to take into account.

Value

list with chemical formula

getgrouprep	<i>Get the report for samples with biological and technique replicates in different groups</i>
-------------	--

Description

Get the report for samples with biological and technique replicates in different groups

Usage

```
getgrouprep(xset, file = NULL, method = "medret", intensity = "into",
            rsdcf = 30, inscf = 1000)
```

Arguments

xset	the xcmsset object all of samples with technique replicates
file	file name for the peaklist to MetaboAnalyst
method	parameter for groupval function
intensity	parameter for groupval function
rsdcf	rsd cutoff for peaks, default 30
inscf	intensity cutoff for peaks, default 1000

Value

dataframe with mean, standard deviation and RSD for those technique replicates & biological replicates combined with raw data in different groups if file are defaults NULL.

getimputation	<i>Impute the peaks list data</i>
---------------	-----------------------------------

Description

Impute the peaks list data

Usage

```
getimputation(list, method = "1")
```

Arguments

list	list with data as peaks list, mz, rt and group information
method	'r' means remove, 'l' means use half the minimum of the values across the peaks list, 'mean' means mean of the values across the samples, 'median' means median of the values across the samples, '0' means 0, '1' means 1. Default '1'.

Value

list with imputed peaks

See Also

[getdata2](#), [getdata](#), [getmzrt](#), [getdoe](#), [getmr](#)

Examples

```
data(list)
getimputation(list)
```

GetIntegration	<i>GetIntegration was mainly used for get the intergration of certain ion's chromatogram data and plot the data</i>
----------------	---

Description

GetIntegration was mainly used for get the intergration of certain ion's chromatogram data and plot the data

Usage

```
GetIntegration(data, rt = c(8.3, 9), n = 5, m = 5, slope = c(2, 2),
  baseline = 10, noslope = T, smoothit = T, half = F)
```

Arguments

data	file should be a dataframe with the first column RT and second column intensity of the SIM ions.
rt	a rough RT range contained only one peak to get the area
n	points in the moving average smooth box, default value is 5
m	numbers of points for regression to get the slope
slope	the threshold value for start/stop peak as percentage of max slope
baseline	numbers of the points for the baseline of the signal
noslope	logical, if using a horizon line to get area or not
smoothit	logical, if using an average smooth box or not. If using, n will be used
half	logical, if using the left half peak to caculate the area

Value

intergration data such as peak area, peak hight, signal and the slope data.

Examples

```
## Not run:
list <- GetIntergration(data)

## End(Not run)
```

Getisotopologues *Get the selected isotopologues at certain MS data*

Description

Get the selected isotopologues at certain MS data

Usage

```
Getisotopologues(formula = "C12OH6Br4", charge = "1", width = 0.3)
```

Arguments

formula	the molecular formula. C12OH6Br4 means BDE-47 as default
charge	the charge of that molecular. 1 in EI mode as default
width	the width of the peak width on mass spectrum. 0.3 as default for low resolution mass spectrum.

Examples

```
# show isotopologues for BDE-47
Getisotopologues(formula = 'C12OH6Br4')
```

getmass *Get the exact mass of the isotopologues from a chemical formula or reaction's isotope patterns with the highest abundances*

Description

Get the exact mass of the isotopologues from a chemical formula or reaction's isotope patterns with the highest abundances

Usage

```
getmass(data)
```

Arguments

data	a chemical formula or reaction e.g. 'Cl-H', 'C2H4'
------	--

Value

numerical vector

Examples

```
getmass('CH2')
```

getmassdefect	<i>Get mass defect with certain scaled factor</i>
---------------	---

Description

Get mass defect with certain scaled factor

Usage

```
getmassdefect(mass, sf)
```

Arguments

mass	vector of mass
sf	scaled factors

Value

dataframe with mass, scaled mass and scaled mass defect

See Also

[plotkms](#)

Examples

```
mass <- c(100.1022, 245.2122, 267.3144, 400.1222, 707.2294)
sf <- 0.9988
mf <- getmassdefect(mass, sf)
```

getmd	<i>Import data and return the annotated matrix for GC/LC-MS by m/z range and retention time</i>
-------	---

Description

Import data and return the annotated matrix for GC/LC-MS by m/z range and retention time

Usage

```
getmd(data, mzstep = 0.1, mzrange = F, rtrange = F)
```

Arguments

data	file type which xcmsRaw could handle
mzstep	the m/z step for generating matrix data from raw mass spectral data
mzrange	vector range of the m/z, default all
rtrange	vector range of the retention time, default all

Value

matrix with the row as increasing m/z second and column as increasing scantime

Examples

```
## Not run:  
library(faahK0)  
cdfpath <- system.file('cdf', package = 'faahK0')  
cdffiles <- list.files(cdfpath, recursive = TRUE, full.names = TRUE)  
matrix <- getmd(cdffiles[1])  
  
## End(Not run)
```

getmdh	<i>Get the high order unit based Mass Defect</i>
--------	--

Description

Get the high order unit based Mass Defect

Usage

```
getmdh(mz, cus = c("CH2,H2"), method = "round")
```

Arguments

- mz numeric vector for exact mass
- cus chemical formula or reaction
- method you could use 'round', 'floor' or 'ceiling'

Value

high order Mass Defect with details

Examples

```
getmdh(getmass('C2H4'))
```

getmdr *Get the raw Mass Defect*

Description

Get the raw Mass Defect

Usage

```
getmdr(mz)
```

Arguments

- mz numeric vector for exact mass

Value

raw Mass Defect

Examples

```
getmdr(getmass('C2H4'))
```

getmr	<i>Get the mzrt profile and group information for batch correction and plot as a list directly from path with default setting</i>
-------	---

Description

Get the mzrt profile and group information for batch correction and plot as a list directly from path with default setting

Usage

```
getmr(path, index = F, BPPARAM = BiocParallel::SnowParam(),  
      pmethod = "hplcorbitrap", minfrac = 0.67, ...)
```

Arguments

path	the path to your data
index	the index of the files
BPPARAM	used for BiocParallel package
pmethod	parameters used for different instrumentals such as 'hplcorbitrap', 'uplcorbitrap', 'hplcqtof', 'hplchqtof', 'uplcqtof', 'uplchqtof'. The parameters were from the references
minfrac	minimum fraction of samples necessary in at least one of the sample groups for it to be a valid group, default 0.67
...	arguments for xcmsSet function

Value

list with rtmz profile and group information

See Also

[getdata](#), [getupload](#), [getmzrt](#), [getdoe](#)

Examples

```
## Not run:  
library(faahK0)  
cdfpath <- system.file('cdf', package = 'faahK0')  
list <- getmr(cdfpath, pmethod = ' ')  
  
## End(Not run)
```

getmzrt *Get the mzrt profile and group information as a mzrt list and/or save them as csv or rds for further analysis.*

Description

Get the mzrt profile and group information as a mzrt list and/or save them as csv or rds for further analysis.

Usage

```
getmzrt(xset, name = NULL, mzdigit = 4, rtdigit = 1,  
        method = "medret", value = "into", eic = F, type = "o")
```

Arguments

xset	xcmsSet/XCMSnExp objects
name	file name for csv and/or eic file, default NULL
mzdigit	m/z digits of row names of data frame, default 4
rtdigit	retention time digits of row names of data frame, default 1
method	parameter for groupval or featureDefinitions function, default medret
value	parameter for groupval or featureDefinitions function, default into
eic	logical, save xcmsSet and xcmsEIC objects for further investigation with the same name of files, you will need raw files in the same directory as defined in xcmsSet to extract the EIC based on the binned data. You could use 'plot' to plot EIC for specific peaks. For example, 'plot(xcmsEIC,xcmsSet,groupidx = 'M123.4567T278.9')' could show the EIC for certain peaks with m/z 206 and retention time 2789. default F
type	csv formate for furthor analysis, m means Metaboanalyst, a means xMSannotator, p means Mummichog(NA values are imputed by 'getimputation', and F test is used here to generate stats and p vlaue), o means full infomation csv (for 'pmd' package), default o. mapo could output all those format files.

Value

mzrt object, a list with mzrt profile and group infomation

References

Smith, C.A., Want, E.J., O'Maille, G., Abagyan, R., Siuzdak, G., 2006. XCMS: Processing Mass Spectrometry Data for Metabolite Profiling Using Nonlinear Peak Alignment, Matching, and Identification. *Anal. Chem.* 78, 779–787.

See Also

[getdata](#), [getdata2](#), [getdoe](#), [getcsv](#), [getfilter](#)

Examples

```
## Not run:
library(faahK0)
cdfpath <- system.file('cdf', package = 'faahK0')
xset <- getdata(cdfpath, pmethod = ' ')
getmzrt(xset, name = 'demo', type = 'mapo')

## End(Not run)
```

getmzrt2

Get the mzrt profile and group information for batch correction and plot as a list for xcms 3 object

Description

Get the mzrt profile and group information for batch correction and plot as a list for xcms 3 object

Usage

```
getmzrt2(xset, name = NULL)
```

Arguments

xset	a XCMSnExp object with processed data
name	file name for csv file, default NULL

Value

list with rtmz profile and group information

See Also

[getdata2](#), [getupload2](#), [getmzrt](#), [getdoe](#), [getmzrtcsv](#)

Examples

```
## Not run:
library(faahK0)
cdfpath <- system.file('cdf', package = 'faahK0')
xset <- getdata2(cdfpath,
  ppp = xcms::MatchedFilterParam(),
  rtp = xcms::ObiwarpParam(),
  gpp = xcms::PeakDensityParam())
getmzrt2(xset)

## End(Not run)
```

getmzrtcsv	<i>Covert the peaks list csv file into list</i>
------------	---

Description

Covert the peaks list csv file into list

Usage

```
getmzrtcsv(path)
```

Arguments

path the path to your csv file

Value

list with rtmz profile and group infomation

See Also

[getmzrt](#)

getoverlapmass	<i>Get the overlap peaks by mass range</i>
----------------	--

Description

Get the overlap peaks by mass range

Usage

```
getoverlapmass(mzrange1, mzrange2)
```

Arguments

mzrange1 mass range 1 to be overlapped
mzrange2 mass range 2 to overlap

Value

logical index for mzrange1's peaks

See Also

[getmzrt](#), [getimputation](#), [getmr](#), [getdoe](#), [getoverlappeak](#), [getoverlapprt](#)

getoverlappeak	<i>Get the overlap peaks by mass and retention time range</i>
----------------	---

Description

Get the overlap peaks by mass and retention time range

Usage

```
getoverlappeak(list1, list2)
```

Arguments

list1	list with data as peaks list, mz, rt, mzrange, rtrange and group information to be overlapped
list2	list with data as peaks list, mz, rt, mzrange, rtrange and group information to overlap

Value

logical index for list 1's peaks

See Also

[getmzrt](#), [getimputation](#), [getmr](#), [getdoe](#), [getoverlapmass](#), [getoverlaprt](#)

getoverlaprt	<i>Get the overlap peaks by retention time</i>
--------------	--

Description

Get the overlap peaks by retention time

Usage

```
getoverlaprt(rtrange1, rtrange2)
```

Arguments

rtrange1	mass range 1 to be overlapped
rtrange2	mass range 2 to overlap

Value

logical index for rtrange1's peaks

See Also

[getmzrt](#), [getimputation](#), [getmr](#), [getdoe](#), [getoverlapmass](#), [getoverlapeak](#)

getpower	<i>Get the index with power restriction for certain study with BH adjusted p-value and certain power.</i>
----------	---

Description

Get the index with power restriction for certain study with BH adjusted p-value and certain power.

Usage

```
getpower(list, pt = 0.05, qt = 0.05, powert = 0.8,  
         imputation = "l")
```

Arguments

list	list with data as peaks list, mz, rt and group information
pt	p value threshold, default 0.05
qt	q value threshold, BH adjust, default 0.05
powert	power cutoff, default 0.8
imputation	parameters for 'getimputation' function method

Value

list with current power and sample numbers for each peaks

See Also

[getdata2](#), [getdata](#), [getmzrt](#), [getimputation](#), [getmr](#), [getdoe](#)

Examples

```
data(list)  
getpower(list)
```

getQCraw	<i>get the data of QC compound for a group of data</i>
----------	--

Description

get the data of QC compound for a group of data

Usage

```
getQCraw(path, mzrange, rtrange, index = NULL)
```

Arguments

path	data path for your QC samples
mzrange	mass of the QC compound
rtrange	retention time of the QC compound
index	index of the files contained QC compounds, default is all of the compounds

Value

number vector, each number indicate the peak area of that mass and retention time range

getrmd	<i>Get the Relative Mass Defect</i>
--------	-------------------------------------

Description

Get the Relative Mass Defect

Usage

```
getrmd(mz)
```

Arguments

mz	numeric vector for exact mass
----	-------------------------------

Value

Relative Mass Defect

Examples

```
getrmd(getmass('C2H4'))
```

getsccp *Quantitative analysis for short-chain chlorinated paraffins(SCCPs)*

Description

Quantitative analysis for short-chain chlorinated paraffins(SCCPs)

Usage

```
getsccp(pathstds, pathsample, ismz = 323, ppm = 5, con = 2000,  
        rt = NULL, rts = NULL, log = T)
```

Arguments

pathstds	mzxml file path for SCCPs standards
pathsample	mzxml file path for samples
ismz	internal standards m/z
ppm	resolution of mass spectrum
con	concentration of standards
rt	retention time range of sccps
rts	retention time range of internal standards
log	log transformation for response factor

Value

list with peak information

See Also

[getareastd](#), [getarea](#)

getsim *output the similarity of two dataset*

Description

output the similarity of two dataset

Usage

```
getsim(xset1, xset2)
```

Arguments

xset1	the first dataset
xset2	the second dataset

Value

similarity on retention time and rsd

gettechrep	<i>Get the report for technique replicates.</i>
------------	---

Description

Get the report for technique replicates.

Usage

```
gettechrep(xset, method = "medret", intensity = "into", file = NULL,  
           rsdcf = 30, inscf = 1000)
```

Arguments

xset	the xcmsset object which for all of your technique replicates for one sample
method	parameter for groupval function
intensity	parameter for groupval function
file	file name for further annotation, default NULL
rsdcf	rsd cutoff for peaks, default 30
inscf	intensity cutoff for peaks, default 1000

Value

dataframe with mean, standard deviation and RSD for those technique replicates combined with raw data

gettimegrouprep	<i>Get the time series or two factor DoE report for samples with biological and technique replicates in different groups</i>
-----------------	--

Description

Get the time series or two factor DoE report for samples with biological and technique replicates in different groups

Usage

```
gettimegrouprep(xset, file = NULL, method = "medret",
  intensity = "into", rsdcf = 30, inscf = 1000)
```

Arguments

xset	the xcmsset object all of samples with technique replicates in time series or two factor DoE
file	file name for the peaklist to MetaboAnalyst
method	parameter for groupval function
intensity	parameter for groupval function
rsdcf	rsd cutoff for peaks, default 30
inscf	intensity cutoff for peaks, default 1000

Value

dataframe with time series or two factor DoE mean, standard deviation and RSD for those technique replicates & biological replicates combined with raw data in different groups if file are defaults NULL.

getupload	<i>Get the csv files from xcmsset/XCMSnExp/list object</i>
-----------	--

Description

Get the csv files from xcmsset/XCMSnExp/list object

Usage

```
getupload(xset, method = "medret", value = "into", name = "Peaklist",
  type = "m", mzdigit = 4, rtdigit = 1)
```

Arguments

xset	the xcmsset/XCMSnExp/list object which you want to submitted to Metaboanalyst
method	parameter for groupval function
value	parameter for groupval function
name	file name
type	m means Metaboanalyst, a means xMSannotator, o means full infomation csv
mzdigit	m/z digits of row names of data frame
rtdigit	retention time digits of row names of data frame

Value

dataframe with data needed for Metaboanalyst/xMSannotator/pmd if your want to perform local analysis.

See Also

[getdata](#), [getmzrt](#)

Examples

```
## Not run:
library(faahK0)
cdfpath <- system.file('cdf', package = 'faahK0')
xset <- getdata(cdfpath, pmethod = ' ')
getupload(xset)

## End(Not run)
```

getupload2

Get the csv files to be submitted to Metaboanalyst

Description

Get the csv files to be submitted to Metaboanalyst

Usage

```
getupload2(xset, value = "into", name = "Peaklist")
```

Arguments

xset	a XCMSnExp object with processed data which you want to submitted to Metaboanalyst
value	value for 'xcms::featureValues'
name	file name

Value

dataframe with data needed for Metaboanalyst if your want to perform local analysis.

See Also

[getdata2](#), [getupload](#), [getmzrt2](#)

Examples

```
## Not run:  
library(faahK0)  
cdfpath <- system.file('cdf', package = 'faahK0')  
xset <- getdata2(cdfpath)  
getupload2(xset)  
  
## End(Not run)
```

getupload3

Get the csv files to be submitted to Metaboanalyst

Description

Get the csv files to be submitted to Metaboanalyst

Usage

```
getupload3(list, name = "Peaklist")
```

Arguments

list	list with data as peaks list, mz, rt and group information
name	file name

Value

dataframe with data needed for Metaboanalyst if your want to perform local analysis.

See Also

[getmzrt](#), [getmzrt2](#)

Examples

```
## Not run:
library(faahK0)
cdfpath <- system.file('cdf', package = 'faahK0')
xset <- getdata2(cdfpath,
ppp = xcms::MatchedFilterParam(),
rtp = xcms::ObiwarpParam(),
gpp = xcms::PeakDensityParam())
xset <- enviGCMS::getmzrt2(xset)
getupload3(xset)

## End(Not run)
```

 gifmr

plot scatter plot for rt-mz profile and output gif file for mutiple groups

Description

plot scatter plot for rt-mz profile and output gif file for mutiple groups

Usage

```
gifmr(list, ms = c(100, 500), rsdcf = 30, inscf = 5,
      imputation = "i", name = "test")
```

Arguments

list	list with data as peaks list, mz, rt and group information
ms	the mass range to plot the data
rsdcf	the rsd cutoff of all peaks in all group
inscf	Log intensity cutoff for peaks across samples. If any peaks show a intensity higher than the cutoff in any samples, this peaks would not be filtered. default 5
imputation	parameters for ‘getimputation’ function method
name	file name for gif file, default test
...	parameters for ‘plot’ function

Value

gif file

Examples

```
data(list)
gifmr(list)
```

Integration	<i>Just intergrate data according to fixed rt and fixed noise area</i>
-------------	--

Description

Just intergrate data according to fixed rt and fixed noise area

Usage

```
Integration(data, rt = c(8.3, 9), brt = c(8.3, 8.4), smoothit = T)
```

Arguments

data	file should be a dataframe with the first column RT and second column intensity of the SIM ions.
rt	a rough RT range contained only one peak to get the area
brt	a rough RT range contained only one peak and enough noises to get the area
smoothit	logical, if using an average smooth box or not. If using, n will be used

Value

area intergration data

Examples

```
## Not run:  
area <- Intergration(data)  
  
## End(Not run)
```

list	<i>Demo data</i>
------	------------------

Description

Demo data

Usage

```
data(list)
```

Format

A list object with data, mass to charge ratio, retention time and group information. The list is generated from faahKO package by 'getmr' function.

ma	<i>filter data by average moving box</i>
----	--

Description

filter data by average moving box

Usage

```
ma(x, n)
```

Arguments

x	a vector
n	A number to indentify the size of the moving box.

Value

The filtered data

Examples

```
ma(rnorm(1000), 5)
```

Mode	<i>define the Mode function</i>
------	---------------------------------

Description

define the Mode function

Usage

```
Mode(x)
```

Arguments

x	vector
---	--------

Value

Mode of the vector

plotden	<i>plot the density for multiple samples</i>
---------	--

Description

plot the density for multiple samples

Usage

```
plotden(data, lv, index = NULL, name = NULL, ...)
```

Arguments

data	mzrt profile with row peaks and column samples
lv	group information
index	index for selected peaks
name	name on the figure for samples
...	parameters for 'plot' function

Examples

```
data(list)
plotden(list$data, lv = as.character(list$group$class))
```

plote	<i>plot EIC and boxplot for all peaks and return diffreport</i>
-------	---

Description

plot EIC and boxplot for all peaks and return diffreport

Usage

```
plote(xset, name = "test", test = "t", nonpara = "n", ...)
```

Arguments

xset	xcmsset object
name	filebase of the sub dir
test	't' means two-sample welch t-test, 't.equalvar' means two-sample welch t-test with equal variance, 'wilcoxon' means rank sum wilcoxon test, 'f' means F-test, 'pairt' means paired t test, 'blockf' means Two-way analysis of variance, default 't'
nonpara	'y' means using nonparametric ranked data, 'n' means original data
...	other parameters for 'diffreport'

Value

diffreport and pdf figure for EIC and boxplot

Examples

```
## Not run:  
library(faahK0)  
cdfpath <- system.file('cdf', package = 'faahK0')  
xset <- getdata(cdfpath, pmethod = ' ')  
plote(xset)  
  
## End(Not run)
```

plotgroup

Plot the response group of GC-MS

Description

Plot the response group of GC-MS

Usage

```
plotgroup(data, threshold = 2)
```

Arguments

data	imported data matrix of GC-MS
threshold	the threshold of the response (log based 10) to seperate the group

Value

list linear regression model for the data matrix

Examples

```
## Not run:  
data <- getmd(rawdata)  
plotgroup(data)  
  
## End(Not run)
```

plothist	<i>plot the density of the GC-MS data with EM algorithm to separate the data into two log normal distribution.</i>
----------	--

Description

plot the density of the GC-MS data with EM algorithm to separate the data into two log normal distribution.

Usage

```
plothist(data)
```

Arguments

data	imported data matrix of GC-MS
------	-------------------------------

Examples

```
## Not run:  
matrix <- getmd(rawdata)  
plothist(matrix)  
  
## End(Not run)
```

plothm	<i>Plot the heatmap of mzrt profiles</i>
--------	--

Description

Plot the heatmap of mzrt profiles

Usage

```
plothm(data, lv, index = NULL)
```

Arguments

data	mzrt profile with row peaks and column samples
lv	group information
index	index for selected peaks

Examples

```
data(list)  
plothm(list$data, lv = list$group$class)
```

plotint *plot the information of intergreion*

Description

plot the information of intergreion

Usage

```
plotint(list, name = NULL)
```

Arguments

list	list from getinteragtion
name	the title of the plot

Examples

```
## Not run:  
list <- getinteragtion(rawdata)  
plotint(list)  
  
## End(Not run)
```

plotintslope *plot the slope information of intergreion*

Description

plot the slope information of intergreion

Usage

```
plotintslope(list, name = NULL)
```

Arguments

list	list from getinteragtion
name	the title of the plot

Examples

```
## Not run:  
list <- getinteragtion(rawdata)  
plotintslope(list)  
  
## End(Not run)
```

plotkms *plot the kendrick mass defect diagram*

Description

plot the kendrick mass defect diagram

Usage

```
plotkms(data, cutoff = 1000)
```

Arguments

data	vector with the name m/z
cutoff	remove the low intensity

See Also

[getmassdefect](#)

Examples

```
## Not run:  
mz <- c(10000,5000,20000,100,40000)  
names(mz) <- c(100.1022,245.2122,267.3144,400.1222,707.2294)  
plotkms(mz)  
  
## End(Not run)
```

plotmr *plot the scatter plot for peaks list with threshold*

Description

plot the scatter plot for peaks list with threshold

Usage

```
plotmr(list, rt = NULL, ms = NULL, inscf = 5, rsdcf = 30,  
      imputation = "1", ...)
```

Arguments

<code>list</code>	list with data as peaks list, mz, rt and group information
<code>rt</code>	vector range of the retention time
<code>ms</code>	vector vector range of the m/z
<code>inscf</code>	Log intensity cutoff for peaks across samples. If any peaks show a intensity higher than the cutoff in any samples, this peaks would not be filtered. default 5
<code>rsdcf</code>	the rsd cutoff of all peaks in all group, default 30
<code>imputation</code>	parameters for 'getimputation' function method
<code>...</code>	parameters for 'plot' function

Value

data fit the cutoff

Examples

```
data(list)
plotmr(list)
```

<code>plotmrc</code>	<i>plot the diff scatter plot for one xcmsset objects with threshold between two groups</i>
----------------------	---

Description

plot the diff scatter plot for one xcmsset objects with threshold between two groups

Usage

```
plotmrc(list, ms = c(100, 800), inscf = 5, rsdcf = 30,
        imputation = "l", ...)
```

Arguments

<code>list</code>	list with data as peaks list, mz, rt and group information
<code>ms</code>	the mass range to plot the data
<code>inscf</code>	Log intensity cutoff for peaks across samples. If any peaks show a intensity higher than the cutoff in any samples, this peaks would not be filtered. default 5
<code>rsdcf</code>	the rsd cutoff of all peaks in all group
<code>imputation</code>	parameters for 'getimputation' function method
<code>...</code>	parameters for 'plot' function

Examples

```
data(list)
plotmrc(list)
```

plotms	<i>plot GC/LC-MS data as a heatmap with TIC</i>
--------	---

Description

plot GC/LC-MS data as a heatmap with TIC

Usage

```
plotms(data, log = F)
```

Arguments

data	imported data matrix of GC-MS
log	transform the intensity into log based 10

Value

heatmap

Examples

```
## Not run:  
library(faahK0)  
cdfpath <- system.file('cdf', package = 'faahK0')  
cdffiles <- list.files(cdfpath, recursive = TRUE, full.names = TRUE)  
matrix <- getmd(cdffiles[1])  
png('test.png')  
plotms(matrix)  
dev.off()  
  
## End(Not run)
```

plotmsrt	<i>Plot EIC of certain m/z and return dataframe for intergration</i>
----------	--

Description

Plot EIC of certain m/z and return dataframe for intergration

Usage

```
plotmsrt(data, ms, rt, n = F)
```

Arguments

data	imported data matrix of GC-MS
ms	m/z to be extracted
rt	vector range of the retention time
n	logical smooth or not

Value

dataframe with with the first column RT and second column intensity of the SIM ions.

Examples

```
## Not run:  
matrix <- getmd(rawdata)  
plotmz(matrix,rt = c(500,1000),ms = 300)  
  
## End(Not run)
```

plotmz	<i>plot GC/LC-MS data as scatter plot</i>
--------	---

Description

plot GC/LC-MS data as scatter plot

Usage

```
plotmz(data, inscf = 5, ...)
```

Arguments

data	imported data matrix of GC-MS
inscf	Log intensity cutoff for peaks, default 5
...	parameters for 'plot' function

Value

scatter plot

Examples

```
## Not run:
library(faahKO)
cdfpath <- system.file('cdf', package = 'faahKO')
cdffiles <- list.files(cdfpath, recursive = TRUE, full.names = TRUE)
matrix <- getmd(cdffiles[1])
png('test.png')
plotmz(matrix)
dev.off()

## End(Not run)
```

plotpca

plot the PCA for multiple samples

Description

plot the PCA for multiple samples

Usage

```
plotpca(data, lv = NULL, index = NULL, center = T, scale = T,
        xrange = NULL, yrange = NULL, pch = NULL, ...)
```

Arguments

data	mzrt profile with row peaks and column samples
lv	group information
index	index for selected peaks
center	parameters for PCA
scale	parameters for scale
xrange	x axis range for return samples, default NULL
yrange	y axis range for return samples, default NULL
pch	default pch would be the first character of group information or samples name
...	other parameters for 'plot' function

Value

if xrange and yrange are not NULL, return file name of all selected samples on 2D score plot

Examples

```
data(list)
plotpca(list$data, lv = as.character(list$group$class))
```

plotridges *Relative Log Abundance Ridge (RLAR) plots*

Description

Relative Log Abundance Ridge (RLAR) plots

Usage

```
plotridges(data, lv, type = "g")
```

Arguments

data data as mzrt profile
 lv factor vector for the group information
 type 'g' means group median based, other means all samples median based.

Value

Relative Log Abundance Ridge(RLA) plots

Examples

```
data(list)
plotridges(list$data, as.factor(list$group$class))
```

plotrla *Relative Log Abundance (RLA) plots*

Description

Relative Log Abundance (RLA) plots

Usage

```
plotrla(data, lv, type = "g")
```

Arguments

data data as mzrt profile
 lv factor vector for the group information
 type 'g' means group median based, other means all samples median based.

Value

Relative Log Abundance (RLA) plots

Examples

```
data(list)
plotrla(list$data, as.factor(list$group$class))
```

plotrsd	<i>plot the rsd influences of data in different groups</i>
---------	--

Description

plot the rsd influences of data in different groups

Usage

```
plotrsd(list, ms = c(100, 800), inscf = 5, rsdcf = 100,
  imputation = "1", ...)
```

Arguments

list	list with data as peaks list, mz, rt and group information
ms	the mass range to plot the data
inscf	Log intensity cutoff for peaks across samples. If any peaks show a intensity higher than the cutoff in any samples, this peaks would not be filtered. default 5
rsdcf	the rsd cutoff of all peaks in all group
imputation	parameters for 'getimputation' function method
...	other parameters for 'plot' function

Examples

```
data(list)
plotrsd(list)
```

plotrtms	<i>Plot mass spectrum of certain retention time and return mass spectrum vector (MSP file) for NIST search</i>
----------	--

Description

Plot mass spectrum of certain retention time and return mass spectrum vector (MSP file) for NIST search

Usage

```
plotrtms(data, rt, ms)
```

Arguments

data imported data matrix of GC-MS
rt vector range of the retention time
ms vector range of the m/z

Value

plot, vector and MSP files for NIST search

Examples

```
## Not run:  
matrix <- getmd(rawdata)  
plotrtms(matrix,rt = c(500,1000),ms = (300,500))  
  
## End(Not run)
```

plotsms *Plot the intensity distribution of GC-MS*

Description

Plot the intensity distribution of GC-MS

Usage

```
plotsms(meanmatrix, rsdmatrix)
```

Arguments

meanmatrix mean data matrix of GC-MS(n=5)
rsdmatrix standard deviation matrix of GC-MS(n=5)

Examples

```
## Not run:  
data1 <- getmd('sample1-1')  
data2 <- getmd('sample1-2')  
data3 <- getmd('sample1-3')  
data4 <- getmd('sample1-4')  
data5 <- getmd('sample1-5')  
data <- (data1+data2+data3+data4+data5)/5  
datasd <- sqrt((((data1-data)^2+(data2-data)^2+(data3-data)^2+(data4-data)^2+(data5-data)^2)/4)  
databrsd <- datasd/data  
plotsms(meanmatrix,rsdmatrix)  
  
## End(Not run)
```

plotsub	<i>Plot the background of data</i>
---------	------------------------------------

Description

Plot the background of data

Usage

```
plotsub(data)
```

Arguments

data	imported data matrix of GC-MS
------	-------------------------------

Examples

```
## Not run:  
matrix <- getmd(rawdata)  
plotsub(matrix)  
  
## End(Not run)
```

plott	<i>plot GC-MS data as a heatmap for constant speed of temperature rising</i>
-------	--

Description

plot GC-MS data as a heatmap for constant speed of temperature rising

Usage

```
plott(data, log = F, temp = c(100, 320))
```

Arguments

data	imported data matrix of GC-MS
log	transform the intensity into log based 10
temp	temperature range for constant speed

Value

heatmap

Examples

```
## Not run:  
matrix <- getmd(rawdata)  
plott(matrix)  
  
## End(Not run)
```

plottic

Plot Total Ion Chromatogram (TIC)

Description

Plot Total Ion Chromatogram (TIC)

Usage

```
plottic(data, n = F)
```

Arguments

data	imported data matrix of GC-MS
n	logical smooth or not

Value

plot

Examples

```
## Not run:  
matrix <- getmd(rawdata)  
plottic(matrix)  
  
## End(Not run)
```

qbatch

Get the MIR from the file

Description

Get the MIR from the file

Usage

```
qbatch(file, mz1, mz2, rt = c(8.65, 8.74), brt = c(8.74, 8.85))
```

Arguments

file	data file, CDF or other format supported by xcmsRaw
mz1	the lowest mass
mz2	the highest mass
rt	a rough RT range contained only one peak to get the area
brt	a rough RT range contained only one peak and enough noises to get the area

Value

arearatio

Examples

```
## Not run:  
arearatio <- qbatch(datafile)  
  
## End(Not run)
```

runMDPlot

Shiny application for interactive mass defect plots analysis

Description

Shiny application for interactive mass defect plots analysis

Usage

```
runMDPlot()
```

runsccp

Shiny application for Short-Chain Chlorinated Paraffins analysis

Description

Shiny application for Short-Chain Chlorinated Paraffins analysis

Usage

```
runsccp()
```

sccp	<i>Short-Chain Chlorinated Paraffins(SCCPs) peaks information for quantitative analysis</i>
------	---

Description

A dataset containing the ions, formula, Cl

Usage

```
data(sccp)
```

Format

A data frame with 24 rows and 8 variables:

Cln Chlorine atom numbers

Cn Carbon atom numbers

formula molecular formula

Hn hydrogen atom numbers

ions [M-Cl]- ions

mz m/z for the isotopologues with highest intensity

intensity abundance of the isotopologues with highest intensity

Clp Chlorine contents

submd	<i>Get the differences of two GC/LC-MS data</i>
-------	---

Description

Get the differences of two GC/LC-MS data

Usage

```
submd(data1, data2, mzstep = 0.1, rtstep = 0.01)
```

Arguments

data1 data file path of first data

data2 data file path of second data

mzstep the m/z step for generating matrix data from raw mass spectral data

rtstep the alignment accuracy of retention time, e.g. 0.01 means the retention times of combined data should be the same at the accuracy 0.01s. Higher rtstep would return less scans for combined data

Value

list four matrix with the row as scantime in second and column as m/z, the first matrix refer to data 1, the second matrix refer to data 2, the third matrix refer to data1 - data2 while the fourth refer to data2 - data1, minus values are imputed by 0

Examples

```
## Not run:
library(faahK0)
cdfpath <- system.file('cdf', package = 'faahK0')
cdffiles <- list.files(cdfpath, recursive = TRUE, full.names = TRUE)
matrix <- submd(cdffiles[1],cdffiles[7])

## End(Not run)
```

svabatch

Plot the influences of DoE and Batch effects on each peaks

Description

Plot the influences of DoE and Batch effects on each peaks

Usage

```
svabatch(df, dfsv, dfanova)
```

Arguments

df	data output from 'svacor' function
dfsv	data output from 'svaplot' function for corrected data
dfanova	data output from 'svaplot' function for raw data

Value

influences plot

See Also

[svacor](#), [svaplot](#), [svapca](#)

Examples

```
## Not run:
library(faahK0)
cdfpath <- system.file("cdf", package = "faahK0")
cdffiles <- list.files(cdfpath, recursive = TRUE, full.names = TRUE)
xset <- xcmsSet(cdffiles)
xset <- group(xset)
xset2 <- retcor(xset, family = "symmetric", plotype = "mdevden")
xset2 <- group(xset2, bw = 10)
xset3 <- fillPeaks(xset2)
df <- svacor(xset3)
dfsv <- svaplot(xset3)
dfanova <- svaplot(xset3, pqvalues = "anova")
svabatch(df,dfsv,dfanova)

## End(Not run)
```

svacor

Surrogate variable analysis(SVA) to correct the unknown batch effects

Description

Surrogate variable analysis(SVA) to correct the unknown batch effects

Usage

```
svacor(xset, lv = NULL, method = "medret", intensity = "into")
```

Arguments

xset	xcmsset object
lv	group information
method	parameter for groupval function
intensity	parameter for groupval function

Details

this is used for revised version of SVA to correct the unknown batch effects

Value

list object with various components such raw data, corrected data, signal part, random errors part, batch part, p-values, q-values, mass, rt, Posterior Probabilities of Surrogate variables and Posterior Probabilities of Mod. If no surrogate variable found, corresponding part would miss.

See Also

[svapca](#), [svaplot](#), [svabatch](#)

Examples

```
## Not run:
library(faahK0)
cdfpath <- system.file("cdf", package = "faahK0")
cdffiles <- list.files(cdfpath, recursive = TRUE, full.names = TRUE)
xset <- xcmsSet(cdffiles)
xset <- group(xset)
xset2 <- retcor(xset, family = "symmetric", plotype = "mdevden")
xset2 <- group(xset2, bw = 10)
xset3 <- fillPeaks(xset2)
df <- svacor(xset3)

## End(Not run)
```

svadata	<i>Filter the data with p value and q value</i>
---------	---

Description

Filter the data with p value and q value

Usage

```
svadata(list, pqvalues = "sv", pt = 0.05, qt = 0.05)
```

Arguments

list	results from svacor function
pqvalues	method for ANOVA or SVA
pt	threshold for p value, default is 0.05
qt	threshold for q value, default is 0.05

Value

data, corrected data, mz and retention for fileted data

Examples

```
## Not run:
library(faahK0)
cdfpath <- system.file("cdf", package = "faahK0")
cdffiles <- list.files(cdfpath, recursive = TRUE, full.names = TRUE)
xset <- xcmsSet(cdffiles)
xset <- group(xset)
xset2 <- retcor(xset, family = "symmetric", plotype = "mdevden")
xset2 <- group(xset2, bw = 10)
xset3 <- fillPeaks(xset2)
df <- svacor(xset3)
```

```
svadata(df)

## End(Not run)
```

svapca	<i>Principal component analysis(PCA) for SVA corrected data and raw data</i>
--------	--

Description

Principal component analysis(PCA) for SVA corrected data and raw data

Usage

```
svapca(list, center = T, scale = T, lv = NULL)
```

Arguments

list	results from svacor function
center	parameters for PCA
scale	parameters for scale
lv	group information

Value

plot

See Also

[svacor](#), [svaplot](#), [svabatch](#)

Examples

```
## Not run:
library(faahK0)
cdfpath <- system.file("cdf", package = "faahK0")
cdffiles <- list.files(cdfpath, recursive = TRUE, full.names = TRUE)
xset <- xcmsSet(cdffiles)
xset <- group(xset)
xset2 <- retcor(xset, family = "symmetric", plotype = "mdevden")
xset2 <- group(xset2, bw = 10)
xset3 <- fillPeaks(xset2)
df <- svacor(xset3)
svapca(df)

## End(Not run)
```

svaplot*Filter the data with p value and q value and show them*

Description

Filter the data with p value and q value and show them

Usage

```
svaplot(list, pqvalues = "sv", pt = 0.05, qt = 0.05, lv = NULL,  
        index = NULL)
```

Arguments

list	results from svacor function
pqvalues	method for ANOVA or SVA
pt	threshold for p value, default is 0.05
qt	threshold for q value, default is 0.05
lv	group information
index	index for selected peaks

Value

heatmap for the data

See Also

[svacor](#), [svapca](#), [svabatch](#)

Examples

```
## Not run:  
library(faahKO)  
cdfpath <- system.file("cdf", package = "faahKO")  
cdffiles <- list.files(cdfpath, recursive = TRUE, full.names = TRUE)  
xset <- xcmsSet(cdffiles)  
xset <- group(xset)  
xset2 <- retcor(xset, family = "symmetric", plotype = "mdevden")  
xset2 <- group(xset2, bw = 10)  
xset3 <- fillPeaks(xset2)  
df <- svacor(xset3)  
svaplot(df)  
  
## End(Not run)
```

`svaupload`*Get the corrected data after SVA for metabolanalyst*

Description

Get the corrected data after SVA for metabolanalyst

Usage

```
svaupload(xset, lv = NULL)
```

Arguments

<code>xset</code>	xcmsset object
<code>lv</code>	group information

Value

csv files for both raw and corrected data for metabolanalyst if SVA could be applied

Examples

```
## Not run:
library(faahK0)
cdfpath <- system.file("cdf", package = "faahK0")
cdffiles <- list.files(cdfpath, recursive = TRUE, full.names = TRUE)
xset <- xcmsSet(cdffiles)
xset <- group(xset)
xset2 <- retcor(xset, family = "symmetric", plotype = "mdevden")
xset2 <- group(xset2, bw = 10)
xset3 <- fillPeaks(xset2)
svaupload(xset3)

## End(Not run)
```

`writeMSP`*Write MSP files for NIST search*

Description

Write MSP files for NIST search

Usage

```
writeMSP(mz, outfilename = "unknown")
```

Arguments

mz a intensity vector, who name is the mass in m/z
outfilename the name of the MSP file, default is 'unknown'

Value

none a MSP file will be created at the subfolder working dictionary with name 'MSP'

Examples

```
mz <- c(10000,20000,10000,30000,5000)  
names(mz) <- c(101,143,189,221,234)  
writeMSP(mz, 'test')
```

Index

*Topic **datasets**

- list, 35
 - sccp, 52
- batch, 3
- cbmd, 4
- findline, 5
- findohc, 5
-
- getarea, 6, 7, 29
- getareastd, 7, 7, 29
- getbgremove, 8
- getbiotechrep, 8
- getcsv, 9, 15, 23
- getdata, 10, 12, 13, 15, 17, 22, 23, 27, 32
- getdata2, 11, 11, 13, 15, 17, 23, 24, 27, 33
- getdoe, 12, 17, 22–27
- getfeaturesanova, 13
- getfeaturest, 14
- getfilter, 14, 23
- getformula, 15
- getgrouprep, 16
- getimputation, 13, 15, 16, 25–27
- GetIntegration, 17
- Getisotopologues, 18
- getmass, 18
- getmassdefect, 19, 41
- getmd, 20
- getmdh, 20
- getmdr, 21
- getmr, 13, 15, 17, 22, 25–27
- getmzrt, 11–13, 15, 17, 22, 23, 24–27, 32, 33
- getmzrt2, 24, 33
- getmzrtcsv, 24, 25
- getoverlapmass, 25, 26, 27
- getoverlappeak, 25, 26, 27
- getoverlapprt, 25, 26, 26
- getpower, 13, 27
-
- getQCraw, 28
- getrmd, 28
- getsccp, 7, 29
- getsim, 29
- gettechrep, 30
- gettimegrouprep, 31
- getupload, 22, 31, 33
- getupload2, 24, 32
- getupload3, 33
- gifmr, 34
-
- Integration, 35
-
- list, 35
-
- ma, 36
- Mode, 36
-
- plotden, 37
- plote, 37
- plotgroup, 38
- plothist, 39
- plotmh, 39
- plotint, 40
- plotintslope, 40
- plotkms, 19, 41
- plotmr, 41
- plotmrc, 42
- plotms, 43
- plotmsrt, 43
- plotmz, 44
- plotpca, 45
- plotridges, 46
- plotrla, 46
- plotrsd, 47
- plotrtms, 47
- plotsms, 48
- plotsub, 49
- plott, 49
- plottic, 50

qbatch, [50](#)

runMDPlot, [51](#)

runsccp, [51](#)

sccp, [52](#)

submd, [52](#)

svabatch, [53](#), [54](#), [56](#), [57](#)

svacor, [53](#), [54](#), [56](#), [57](#)

svadata, [55](#)

svapca, [53](#), [54](#), [56](#), [57](#)

svaplot, [53](#), [54](#), [56](#), [57](#)

svaupload, [58](#)

writeMSP, [58](#)