

# Package ‘genpathmox’

June 1, 2017

**Title** Generalized Pathmox Approach Segmentation Tree Analysis

**Version** 0.3

**Description** Provides a very interesting solution for handling segmentation variables in complex statistical methodology. It contains an extended version of the “Pathmox” algorithm (Lamberti, Sanchez and Aluja, (2016) <doi:10.1002/asmb.2168>) in the context of Partial Least Squares Path Modeling including the F-block test (to detect the responsible latent endogenous equations of the difference), the F-coefficient (to detect the path coefficients responsible of the difference) and the “invariance” test (to realize a comparison between the sub-models’ latent variables). Furthermore, the package contains a generalized version of the “Pathmox” algorithm to approach different methodologies: linear regression and least absolute regression models.

**Depends** R (>= 3.1.2), stats, graphics, grDevices, utils, diagram, methods, mice, plsrm, quantreg,

**License** GPL-3

**LazyData** true

**Author** Giuseppe Lamberti [aut, cre]

**Maintainer** Giuseppe Lamberti <giuseppelamb@hotmail.com>

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2017-05-31 16:01:31

## R topics documented:

fibtele . . . . .	2
fibtelereg . . . . .	4
info.pls_class . . . . .	5
info.reg_class . . . . .	5
invariance_test . . . . .	5
node-class . . . . .	8

node.reg_class . . . . .	9
plot.treemodel . . . . .	9
plot.treemodelreg . . . . .	12
plot.xtree.pls . . . . .	14
plot.xtree.reg . . . . .	17
pls.pathmox . . . . .	19
pls.treemodel . . . . .	23
print.xtree.pls . . . . .	26
print.xtree.reg . . . . .	28
reg.pathmox . . . . .	29
reg.treemodel . . . . .	32
summary.xtree.pls . . . . .	34
summary.xtree.reg . . . . .	36
tree-class . . . . .	38

## Index 39

---

fibtele	<i>Fibtele</i>
---------	----------------

---

### Description

Fibtele

### Usage

fibtele

### Format

A data frame with 147 observations on the following 35 variables. The first ten variables are segmentation variables. The rest of the variables refer to five latent concepts: 1) Image=Image, 2) Qual.spec=Specific Quality, 3) Qual.gen=Generic Quality, 4) Value=Value, 5) Satis=Satisfaction. Variables description

- Image: Generic students perception of ICT schools: (internationally recognized, ranges of courses, leader in research).
- Qual.spec: Perception about the achieved quality on the specific skills in the school.
- Qual.gen: Perception about achieved quality on the generic skills in the school (abilities in solving problem, communication skills).
- Value: The advantage or profit that the alumni may draw from the school degree (well paid job, motivated job, prospectives in improvement and promotion).
- Satis: Degree of alumni satisfaction about the formation in school respect to their actual work conditions.

Manifest variables description

- ima1MV:It is the best college to study IE

- ima2MV:It is internationally recognized
- ima3MV:It has a wide range of courses
- ima4MV:The Professors are good
- ima5MV:Facilities and equipment are good
- ima6MV:It is leader in research
- ima7MV:It is well regarded by the companies
- ima8MV:It is oriented to new needs and technologies
- quaf1MV:Basic skills
- quaf2MV:Specific Technic skills
- quaf3MV:Applied skills
- qutr1MV:Achieved abilities in solving problem
- qutr2MV:Training in business management
- qutr3MV:The written and oral communication skills
- qutr4MV:Planning and time management acquired
- qutr5MV:Team-work skills
- val1MV:It has allowed me to find a well paid job
- val2MV:I have good prospectives in improvement and promotion
- val3MV:It has allowed me to find a job that motivates me
- val4MV:The training received is the basis on which I will develope my career
- sat1MV:I am satisfied with the training received
- sat2MV:I am satisfied with my current situation
- sat3MV:I think I will have a good career
- sat4MV:What do you think is the prestige of your work

#### Segmentation Variables description

- Careera factor with levels EI ETS TEL
- Gendera factor with levels female male
- Agea factor with levels 25-26years 27-28years 29-30years 31years+
- Studyinga factor with levels no . stud yes . stud
- Contract a factor with levels fix .cont other .cont temp .cont
- Salarya factor with levels 18k >45k 25k 35k 45k
- Firmtypea factor with levels priva publi
- Accgradea factor with levels 7-8accnote accnote<7 accnote>8
- Gradea factor with levels <6 .5note >7 .5note 6 .5-7note 7-7 .5note
- Startworka factor with levels after .grad befor .grad

#### Source

Laboratory of Information Analysis and Modeling (LIAM). Facultat de Informatica de Barcelona, Universitat Politecnica de Catalunya.

## References

Lamberti, G. (2014) *Modeling with Heterogeneity*. PhD Dissertation.

---

fibtelereg

*Fibtelereg*

---

## Description

Fibtelereg dataset

## Usage

fibtelereg

## Format

A data frame with 147 observations on the following 18 variables. The first ten variables are segmentation variables. The rest of the variables refer to five variables 1) Image = Image, 2) Exp.spec = Specific Expectation, 3) Exp.gen = Generic Expectation, 4)Qual.spec = Specific Quality, 5) Qual.gen = Generic Quality, 6) Value = Value, 7) Satis = Satisfaction. Variables description

- Image: Generic students perception of ICT schools: (internationally recognized, ranges of courses, leader in research).
- Exp.spec: Specific Expectation on specific skills (technic or applied skills).
- Exp.gen: Generic Expectation on generic skills (abilities in problem solving, communication skills).
- Qual.spec: Perception about the achieved quality on the specific skills in the school.
- Qual.gen: Perception about achieved quality on the generic skills in the school (abilities in solving problem, communication skills).
- Value: The advantage or profit that the alumni may draw from the school degree (well paid job, motivated job, perspectives in improvement and promotion).
- Satis: Degree of alumni satisfaction about the formation in school respect to their actual work conditions.

Segmentation Variables description

- Careera factor with levels EI ETS TEL
- Gendera factor with levels female male
- Agea factor with levels 25-26years 27-28years 29-30years 31years+
- Studyinga factor with levels no.stud yes.stud
- Contract a factor with levels fix.cont other.cont temp.cont
- Salarya factor with levels 18k >45k 25k 35k 45k
- Firmtypa factor with levels priva publi
- Accgrada factor with levels 7-8accnote accnote<7 accnote>8
- Gradea factor with levels <6.5note >7.5note 6.5-7note 7-7.5note
- Startworka factor with levels after.grad befor.grad

**Source**

Laboratory of Information Analysis and Modeling (LIAM). Facultat de Informatica de Barcelona, Universitat Politecnica de Catalunya.

**References**

Lamberti, G. (2014) *Modeling with Heterogeneity*. PhD Dissertation.

---

info.pls_class	<i>info.pls class</i>
----------------	-----------------------

---

**Description**

info.pls is a S4 class that contains info on the variable and his levels that provides the best binary split and the the the Fischers statististes: F-global, F- block, F-coefficientes

---

info.reg_class	<i>info.reg class</i>
----------------	-----------------------

---

**Description**

info.pls is a S4 class that contains info on the variable and his levels that provides the best binary split and the the the Fischers statististes: F-global, F-coefficientes

---

invariance_test	<i>Invariance Test</i>
-----------------	------------------------

---

**Description**

The invariance test is a test that allows to verify the existence of common weights for the different local PLS-PM models identified by one or more segmentation variable.

**Usage**

```
invariance_test(x, nodes, inner, outer, mode, scheme, scaled)
```

**Arguments**

x	Matrix or data frame containing the manifest variables.
nodes	List of vectors. Each vector contains the position of the individual that belongs to a specific node.
inner	A square (lower triangular) boolean matrix representing the inner model (i.e. the path relationships between latent variables).
outer	list of vectors with column indices or column names from Data indicating the sets of manifest variables forming each block (i.e. which manifest variables correspond to each block).
mode	character vector indicating the type of measurement for each block. Possible values are: "A", "B", "newA", "PLScore", "PLScow". The length of mode must be equal to the length of outer.
scheme	string indicating the type of inner weighting scheme. Possible values are "centroid", "factorial", or "path".
scaled	whether manifest variables should be standardized. Only used when scaling = NULL. When (TRUE, data is scaled to standardized values (mean=0 and variance=1).

**Details**

The "x" refers to a matrix or a data.frame that contains all individuals used for the global PLS-PM estimation. The "nodes" is a list of vectors. Each vector contains the position of the individual that belongs to a specific node. The position is identified by the number of row. For example, the row 4 corresponds to the individual 4. The other parameters are the classical parameters of the function "plspm".

**Value**

An data.frame res. Basically a list with the following results:

chisq.statistic	A Number; $X^2$ statistic
p.value	A Number; p-value
dfH0	A Number; degree of freedom null Hypothesis
dfH1	A Number; degree of freedom alternative Hypothesis
avg.weights	data frame of the common weights if they exist
test	data frame with summary information of the invariance test

**Author(s)**

Giuseppe Lamberti

**References**

- Lamberti, G., Banet, T. (2017) *Invariance Test: Detecting Difference Between Latent Variables Structure in Partial Least Squares Path Modeling*. International Journal of Statistics and Probability, 6(2); doi: 10.5539/ijsp.v6n2p54
- Lamberti, G. (2014) *Modeling with Heterogeneity*. PhD Dissertation.

**Examples**

```

## Not run:
## example of PLS-PM in alumni satisfaction

data(fibtele)

data.fib <-fibtele[,12:35]

#define inner model matrix
Image      = rep(0,5)
Qual.spec  = rep(0,5)
Qual.gen   = rep(0,5)
Value     = c(1,1,1,0,0)
Satis     = c(1,1,1,1,0)
inner.fib = rbind(Image,Qual.spec, Qual.gen, Value, Satis)
colnames(inner.fib) = rownames(inner.fib)

#define blocks of indicators (outer model)
outer.fib = list(1:8,9:11,12:16,17:20,21:24)

#efine de mode
modes.fib = rep("A", 5)

#apply plspm
pls.fib = plspm(data.fib, inner.fib, outer.fib, modes.fib)

seg.fib = fibtele[,2:11]

seg.fib$Age = factor(seg.fib$Age, ordered=TRUE)
seg.fib$Salary = factor(seg.fib$Salary,
                        levels=c("<18k","25k","35k","45k",">45k"), ordered=TRUE)
seg.fib$Accgrade = factor(seg.fib$Accgrade,
                          levels=c("accnote<7","7-8accnote","accnote>8"), ordered=TRUE)
seg.fib$Grade = factor(seg.fib$Grade,
                       levels=c("<6.5note","6.5-7note","7-7.5note",">7.5note"), ordered=TRUE)

#pathmox Analysis
fib.pathmox=pls.pathmox(pls.fib,seg.fib,signif=0.05,deep=2,size=0.2,n.node=20)

#pelect the terminal nodes
ls(fib.pathmox)

terminal.nodes=fib.pathmox$terminal[-1]

#Invariance test
inv.test=invariance_test(data.fib,terminal.nodes,inner.fib,
                        outer.fib,modes.fib,scheme="centroid",scaled=FALSE)
inv.test

## End(Not run)

## example of PLS-PM in alumni satisfaction

```

```

data(fibtele)

data.fib <-fibtele[,12:35]

#define inner model matrix
Image      = rep(0,5)
Qual.spec  = rep(0,5)
Qual.gen   = rep(0,5)
Value     = c(1,1,1,0,0)
Satis     = c(1,1,1,1,0)
inner.fib = rbind(Image,Qual.spec, Qual.gen, Value, Satis)
colnames(inner.fib) = rownames(inner.fib)

#define blocks of indicators (outer model)
outer.fib = list(1:8,9:11,12:16,17:20,21:24)

#efine de mode
modes.fib = rep("A", 5)

#apply plspm
pls.fib = plspm(data.fib, inner.fib, outer.fib, modes.fib)

seg.fib = fibtele[,2:11]

seg.fib$Age = factor(seg.fib$Age, ordered=TRUE)
seg.fib$Salary = factor(seg.fib$Salary,
                        levels=c("<18k", "25k", "35k", "45k", ">45k"), ordered=TRUE)
seg.fib$Accgrade = factor(seg.fib$Accgrade,
                          levels=c("accnote<7", "7-8accnote", "accnote>8"), ordered=TRUE)
seg.fib$Grade = factor(seg.fib$Grade,
                      levels=c("<6.5note", "6.5-7note", "7-7.5note", ">7.5note"), ordered=TRUE)

#pathmox Analysis
fib.pathmox=pls.pathmox(pls.fib,seg.fib,signif=0.05,deep=2,size=0.2,n.node=20)

terminal.nodes=fib.pathmox$terminal[-1]

#Invariance test
inv.test=invariance_test(data.fib,terminal.nodes,inner.fib,
                        outer.fib,modes.fib,scheme="centroid",scaled=FALSE)

```

---

node-class

*node class*


---

## Description

node is a S4 class that contains info on each node of the binary segmentation tree



---

node.reg_class	<i>node.reg class</i>
----------------	-----------------------

---

**Description**

info.pls is a S4 class that contains element of the node class

---

plot.treemodel	<i>Comparative plot between nodes from the Pathmox Segmentation Trees: PLS-PM</i>
----------------	---

---

**Description**

Plot method for objects of class "treemodel". Barplots of path coefficients of terminal nodes with respect to those of the global (root) model

**Usage**

```
## S3 method for class 'treemodel'
plot(x, comp.by = "nodes", nodes.names = NULL,
     ordered = TRUE, decreasing = FALSE, color = NULL, show.box = TRUE,
     border = NA, cex.names = 0.75, cex.axis = 0.75, short.labs = TRUE,
     short.min = NULL, cex.main = 1, ...)
```

**Arguments**

x	An object of class "treemodel" returned by <a href="#">pls.treemodel</a> .
comp.by	One of "nodes" or "latents". This argument indicates the type of barplots comparison.
nodes.names	Optional vector of names for the terminal nodes (must be a vector of length equal to the number of terminal nodes).
ordered	A logical value indicating whether the barplots are shown in increasing ordered.
decreasing	A logical value indicating if the sort order should be increasing or decreasing.
color	Optional vector of colors for the bars. When color=NULL rainbow colors are used.
show.box	A logical value indicating whether a box is drawn around each barplot.
border	The color to be used for the border of the bars. Use border=NA to omit borders.
cex.names	Expansion factor for axis names (bar labels).
cex.axis	Expansion factor for numeric axis labels.
short.labs	Logical value indicating if the labels of the barplots should be abbreviated (TRUE by default).
short.min	Integer number indicating the minimum length of the abbreviations for the labels. Only used when short.labs=TRUE.
cex.main	Allows to fix the size of the main. Equal to 1 to default
...	Further arguments are ignored.

## Details

This function aims to visualize the comparison between path coefficients of the terminal nodes against the path coefficients of the global model in the root node.

When `comp.by="nodes"` a graphic window is displayed for each endogenous latent variable of the PLS model, and barplots of nodes are shown.

When `comp.by="latents"` a graphic window is displayed for each endogenous relationship of the PLS model, and barplots of independent latent variables are shown.

## Author(s)

Giuseppe Lamberti

## References

Lamberti, G. et al. (2016) *The Pathmox approach for PLS path modeling segmentation*. Applied Stochastic Models in Business and Industry; doi: 10.1002/asmb.2168;

Aluja, T., Lamberti, G., Sanchez, G. (2013). Extending the PATHMOX approach to detect which constructs differentiate segments. In H., Abdi, W. W., Chin, V., Esposito Vinzi, G., Russolillo, and L., Trinchera (Eds.), Book title: *New Perspectives in Partial Least Squares and Related Methods* (pp.269-280). Springer.

Lamberti, G. (2014) *Modeling with Heterogeneity*. PhD Dissertation.

Sanchez, G. (2009) *PATHMOX Approach: Segmentation Trees in Partial Least Squares Path Modeling*. PhD Dissertation.

Tenenhaus M., Esposito Vinzi V., Chatelin Y.M., and Lauro C. (2005) PLS path modeling. *Computational Statistics & Data Analysis*, **48**, pp. 159-205.

## Examples

```
## Not run:
## example of PLS-PM in alumni satisfaction

# select manifest variables
data.fib <-fibtele[,12:35]

# define inner model matrix
Image      = rep(0,5)
Qual.spec  = rep(0,5)
Qual.gen   = rep(0,5)
Value     = c(1,1,1,0,0)
Satis     = c(1,1,1,1,0)
inner.fib = rbind(Image,Qual.spec, Qual.gen, Value, Satis)
colnames(inner.fib) = rownames(inner.fib)

# blocks of indicators (outer model)
outer.fib = list(1:8,9:11,12:16,17:20,21:24)
modes.fib = rep("A", 5)

# apply plspm
pls.fib = plspm(data.fib, inner.fib, outer.fib, modes.fib)
```

```

# re-ordering those segmentation variables with ordinal scale
seg.fib= fibtele[,2:11]

seg.fib$Age = factor(seg.fib$Age, ordered=T)
seg.fib$Salary = factor(seg.fib$Salary,
levels=c("<18k", "25k", "35k", "45k", ">45k"), ordered=T)
seg.fib$Accgrade = factor(seg.fib$Accgrade,
levels=c("accnote<7", "7-8accnote", "accnote>8"), ordered=T)
seg.fib$Grade = factor(seg.fib$Grade,
  levels=c("<6.5note", "6.5-7note", "7-7.5note", ">7.5note"), ordered=T)

# Pathmox Analysis
fib.pathmox=pls.pathmox(pls.fib,seg.fib,signif=0.05,
deep=2,size=0.2,n.node=20)

fib.comp=pls.treemodel(pls.fib,fib.pathmox)

plot(fib.comp)

## End(Not run)

library(genpathmox)
data(fibtele)

# select manifest variables
data.fib <-fibtele[1:50,12:35]

# define inner model matrix
Image      = rep(0,5)
Qual.spec = rep(0,5)
Qual.gen   = rep(0,5)
Value     = c(1,1,1,0,0)
Satis     = c(1,1,1,1,0)
inner.fib = rbind(Image,Qual.spec, Qual.gen, Value, Satis)
colnames(inner.fib) = rownames(inner.fib)

# blocks of indicators (outer model)
outer.fib = list(1:8,9:11,12:16,17:20,21:24)
modes.fib = rep("A", 5)

# apply plspm
pls.fib = plspm(data.fib, inner.fib, outer.fib, modes.fib)

# re-ordering those segmentation variables with ordinal scale
seg.fib = fibtele[1:50,c(2,7)]
seg.fib$Salary = factor(seg.fib$Salary,
levels=c("<18k", "25k", "35k", "45k", ">45k"), ordered=TRUE)

# Pathmox Analysis
fib.pathmox = pls.pathmox(pls.fib,seg.fib,signif=0.5,

```

```

deep=1,size=0.01,n.node=10)

fib.comp = pls.treemodel(pls.fib,fib.pathmox)
plot(fib.comp)
library(genpathmox)
data(fibtele)

# select manifest variables
data.fib <-fibtele[1:50,12:35]

# define inner model matrix
Image      = rep(0,5)
Qual.spec  = rep(0,5)
Qual.gen   = rep(0,5)
Value     = c(1,1,1,0,0)
Satis     = c(1,1,1,1,0)
inner.fib  = rbind(Image,Qual.spec, Qual.gen, Value, Satis)
colnames(inner.fib) = rownames(inner.fib)

# blocks of indicators (outer model)
outer.fib = list(1:8,9:11,12:16,17:20,21:24)
modes.fib = rep("A", 5)

# apply plspm
pls.fib = plspm(data.fib, inner.fib, outer.fib, modes.fib)

# re-ordering those segmentation variables with ordinal scale
seg.fib = fibtele[1:50,c(2,7)]
seg.fib$Salary = factor(seg.fib$Salary,
levels=c("<18k","25k","35k","45k",">45k"), ordered=TRUE)

# Pathmox Analysis
fib.pathmox = pls.pathmox(pls.fib,seg.fib,signif=0.5,
deep=1,size=0.01,n.node=10)

plot(fib.pathmox)

```

---

plot.treemodelreg      *Comparative plot between nodes from or the Pathmox Segmentation  
Trees: linear and LAD regression*

---

### Description

Plot method for objects of class "treemodelreg". Barplots of path coefficients of terminal nodes with respect to those of the global (root) model

### Usage

```
## S3 method for class 'treemodelreg'
```

```
plot(x, main.node = FALSE, names.nodes = NULL,
     eti = FALSE, lab.vec = NULL, short.min = NULL, cex.names = 1,
     cex.axis = 1.2, cex.main = 1, lim = c(-0.5, 0.5), short.labs = TRUE,
     ...)
```

### Arguments

x	An object of class "treemodelreg" returned by <a href="#">reg.treemodel</a> .
main.node	It is string. If iequal to TRUE you have to indicate the main of each barplot in "names.nodes".
names.nodes	Optional vector of names for each the terminal node (must be a vector of length equal to the number of terminal nodes).
eti	is string. If it is TRUE the label of each coefficients for all the terminal nodes must be specify in "lab.vec". If it is false the labels are defined by the programe.
lab.vec	Optional vector of names for each coefficient of the terminal nodes (must be a vector of length equal to the number of coefficients).
short.min	Integer number indicating the minimum length of the.
cex.names	Allows to fix the size of coefficient labels. Equal to 1 to default.
cex.axis	Allows to fix the size of axes. Equal to 1.2 to default.
cex.main	Allows to fix the size of the main. Equal to 1 to default.
lim	Allows to fix the axes interval. Equal to (-0.5,0.5) to default.
short.labs	Logical value indicating if the labels of the barplots.
...	Further arguments passed on to <a href="#">plot.treemodelreg</a> . <a href="#">reg.treemodel</a> , <a href="#">reg.pathmox</a>

### Details

This function aims to visualize the comparison between coefficients of the terminal nodes against the coefficients coefficients of the global model in the root node.

### Author(s)

Giuseppe Lamberti

### References

- Aluja, T. Lamberti, G. Sanchez, G. (2013). Modeling with heterogeneity. Meetings of Italian Statistical Society, Advances in Latent Variables - Methods, Models and Applications. Brescia.
- Lamberti, G. (2014) *Modeling with Heterogeneity*. PhD Dissertation.
- Sanchez, G. (2009) *PATHMOX Approach: Segmentation Trees in Partial Least Squares Path Modeling*. PhD Dissertation.

**Examples**

```

## Not run:
##example of LM in alumni satisfaction

data(fibtelereg)

segvar = fibtelereg[,2:11]

#select the variables
data.fib = fibtelereg[,12:18]

segvar$Age = factor(segvar$Age, ordered=T)
segvar$Salary = factor(segvar$Salary,
levels=c("<18k", "25k", "35k", "45k", ">45k"), ordered=T)
segvar$Accgrade = factor(segvar$Accgrade,
levels=c("accnote<7", "7-8accnote", "accnote>8"), ordered=T)
segvar$Grade = factor(segvar$Grade,
levels=c("<6.5note", "6.5-7note", "7-7.5note", ">7.5note"), ordered=T)

#regression PATHMOX
fib.reg.pathmox = reg.pathmox(Satisfact~., data=data.fib, segvar,
signif=0.05, deep=2, method="lm", size=0.15)

#terminal nodes comparison
fib.node.comp = reg.treemodel(fib.reg.pathmox)

#Drawing the bar-plots
plot(fib.node.comp)

## End(Not run)

data(fibtelereg)

#identify the segmentation variables
segvar= fibtelereg[1:50,3:4]

#select the variables
data.fib=fibtelereg[1:50,12:18]

fib.reg.pathmox=reg.pathmox(Satisfact~., data=data.fib, segvar,
signif=0.05, deep=1, method="lm", size=0.15)

fib.node.comp=reg.treemodel(fib.reg.pathmox)

plot(fib.node.comp)

```

**Description**

The function `plot.xtree.pls` allows to draw PATHMOX tree for PLS-PM

**Usage**

```
## S3 method for class 'xtree.pls'
plot(x, root.col = "grey", node.col = "orange",
     leaf.col = "green2", shadow.size = 0.003, node.shadow = "red",
     leaf.shadow = "darkgreen", cex = 0.7, seg.col = "blue3", lwd = 1,
     show.pval = TRUE, pval.col = "blue", main = NULL, cex.main = 1, ...)
```

**Arguments**

<code>x</code>	An object of class "xtree.pls" returned by <code>pls.pathmox</code>
<code>root.col</code>	Fill color of root node.
<code>node.col</code>	Fill color of child nodes.
<code>leaf.col</code>	Fill color of leaf.
<code>shadow.size</code>	Relative size of shadows.
<code>node.shadow</code>	Color of shadow of child nodes.
<code>leaf.shadow</code>	Color of shadow of leaf nodes.
<code>cex</code>	A numerical value indicating the magnification to be used for plotting text.
<code>seg.col</code>	The color to be used for the labels of the segmentation variables.
<code>lwd</code>	The line width, a positive number, defaulting to 1
<code>show.pval</code>	Logical value indicating whether the p-values should be plotted.
<code>pval.col</code>	The color to be used for the labels of the p-values.
<code>main</code>	A main title for the plot.
<code>cex.main</code>	The magnification to be used for the main title.
<code>...</code>	Further arguments passed on to <code>plot.xtree.pls</code> .

**Author(s)**

Giuseppe Lamberti

**References**

- Lamberti, G. et al. (2016) *The Pathmox approach for PLS path modeling segmentation*. Applied Stochastic Models in Business and Industry; doi: 10.1002/asmb.2168;
- Aluja, T., Lamberti, G., Sanchez, G. (2013). Extending the PATHMOX approach to detect which constructs differentiate segments. In H., Abdi, W. W., Chin, V., Esposito Vinzi, G., Russolillo, and L., Trinchera (Eds.), Book title: *New Perspectives in Partial Least Squares and Related Methods* (pp.269-280). Springer.
- Lamberti, G. (2014) *Modeling with Heterogeneity*. PhD Dissertation.
- Sanchez, G. (2009) *PATHMOX Approach: Segmentation Trees in Partial Least Squares Path Modeling*. PhD Dissertation.

Tenenhaus M., Esposito Vinzi V., Chatelin Y.M., and Lauro C. (2005) PLS path modeling. *Computational Statistics & Data Analysis*, **48**, pp. 159-205.

### Examples

```
## Not run:
## example of PLS-PM in alumni satisfaction

# select manifest variables
data.fib <-fibtele[,12:35]

# define inner model matrix
Image      = rep(0,5)
Qual.spec  = rep(0,5)
Qual.gen   = rep(0,5)
Value     = c(1,1,1,0,0)
Satis     = c(1,1,1,1,0)
inner.fib = rbind(Image,Qual.spec, Qual.gen, Value, Satis)
colnames(inner.fib) = rownames(inner.fib)

# blocks of indicators (outer model)
outer.fib = list(1:8,9:11,12:16,17:20,21:24)
modes.fib = rep("A", 5)

# apply plspm
pls.fib = plspm(data.fib, inner.fib, outer.fib, modes.fib)

# re-ordering those segmentation variables with ordinal scale
seg.fib= fibtele[,2:11]

seg.fib$Age = factor(seg.fib$Age, ordered=T)
seg.fib$Salary = factor(seg.fib$Salary,
levels=c("<18k","25k","35k","45k",">45k"), ordered=T)
seg.fib$Accgrade = factor(seg.fib$Accgrade,
levels=c("accnote<7","7-8accnote","accnote>8"), ordered=T)
seg.fib$Grade = factor(seg.fib$Grade,
  levels=c("<6.5note","6.5-7note","7-7.5note",">7.5note"), ordered=T)

# Pathmox Analysis
fib.pathmox=pls.pathmox(pls.fib,seg.fib,signif=0.05,
deep=2,size=0.2,n.node=20)

# plot pathmox tree
plot(pls.fib)

## End(Not run)

library(genpathmox)
data(fibtele)

# select manifest variables
data.fib <-fibtele[1:50,12:35]
```



```

# define inner model matrix
Image      = rep(0,5)
Qual.spec  = rep(0,5)
Qual.gen   = rep(0,5)
Value     = c(1,1,1,0,0)
Satis     = c(1,1,1,1,0)
inner.fib  = rbind(Image,Qual.spec, Qual.gen, Value, Satis)
colnames(inner.fib) = rownames(inner.fib)

# blocks of indicators (outer model)
outer.fib  = list(1:8,9:11,12:16,17:20,21:24)
modes.fib  = rep("A", 5)

# apply plspm
pls.fib    = plspm(data.fib, inner.fib, outer.fib, modes.fib)

# re-ordering those segmentation variables with ordinal scale
seg.fib    = fibtele[1:50,c(2,7)]
seg.fib$Salary = factor(seg.fib$Salary,
levels=c("<18k","25k","35k","45k",">45k"), ordered=TRUE)

# Pathmox Analysis
fib.pathmox = pls.pathmox(pls.fib,seg.fib,signif=0.5,
deep=1,size=0.01,n.node=10)

plot(fib.pathmox)

```

---

plot.xtree.reg	<i>Plot function for the Pathmox Segmentation Trees: linear regression and LAD</i>
----------------	--

---

## Description

The function `plot.xtree.reg` allows to draw PATHMOX tree for linear and LAD regression

## Usage

```

## S3 method for class 'xtree.reg'
plot(x, root.col = "grey", node.col = "orange",
leaf.col = "green2", shadow.size = 0.003, node.shadow = "red",
leaf.shadow = "darkgreen", cex = 0.7, seg.col = "blue3", lwd = 1,
show.pval = TRUE, pval.col = "blue", main = NULL, cex.main = 1, ...)

```

## Arguments

<code>x</code>	An object of class "xtree.reg" returned by <code>reg.pathmox</code>
<code>root.col</code>	Fill color of root node.
<code>node.col</code>	Fill color of child nodes.

leaf.col	Fill color of col.
shadow.size	Relative size of shadows.
node.shadow	Color of shadow of child nodes.
leaf.shadow	Color of shadow of leaf nodes.
cex	A numerical value indicating the magnification to be used for plotting text.
seg.col	The color to be used for the labels of the segmentation variables.
lwd	The line width, a positive number, defaulting to 1.
show.pval	Logical value indicating whether the p-values should be plotted.
pval.col	The color to be used for the labels of the p-values.
main	A main title for the plot.
cex.main	The magnification to be used for the main title.
...	Further arguments are ignored.

### Author(s)

Giuseppe Lamberti

### References

- Aluja, T. Lamberti, G. Sanchez, G. (2013). Modeling with heterogeneity. Meetings of Italian Statistical Society, Advances in Latent Variables - Methods, Models and Applications. Brescia.
- Lamberti, G. (2014) *Modeling with Heterogeneity*. PhD Dissertation.
- Sanchez, G. (2009) *PATHMOX Approach: Segmentation Trees in Partial Least Squares Path Modeling*. PhD Dissertation.

### Examples

```
## Not run:
## example of LM in alumni satisfaction

data(fibtelereg)

#identify the segmentation variables
segvar = fibtelereg[,2:11]

data.fib = fibtelereg[,12:18]

segvar$Age = factor(segvar$Age, ordered=T)
segvar$Salary = factor(segvar$Salary,
  levels=c("<18k", "25k", "35k", "45k", ">45k"), ordered=T)
segvar$Accgrade = factor(segvar$Accgrade,
  levels=c("accnote<7", "7-8accnote", "accnote>8"), ordered=T)
segvar$Grade = factor(segvar$Grade,
  levels=c("<6.5note", "6.5-7note", "7-7.5note", ">7.5note"), ordered=T)

#regression PATHMOX
fib.reg.pathmox=reg.pathmox(Satisfact~., data=data.fib, segvar,
```

```

signif=0.05,deep=2,method="lm",size=0.15)

plot(fib.reg.pathmox)

## End(Not run)
data(fibtelereg)

#identify the segmentation variables
segvar= fibtelereg[1:50,3:4]

#select the variables
data.fib=fibtelereg[1:50,12:18]

fib.reg.pathmox=reg.pathmox(Satisfact~,data=data.fib,segvar,
signif=0.05,deep=1,method="lm",size=0.15)

plot(fib.reg.pathmox)

```

---

pls.pathmox

---

*PATHMOX-PLS: Extended Segmentation Trees in Partial Least Squares Path Modeling*


---

## Description

The function `pathmox.pls` calculates a binary segmentation tree in the context PLS-PM following the PATHMOX algorithm. The procedure can be resumed in the following way. It starts with the estimation of the global PLS Path Model at the root node. Then, using the segmentation variables, all possible binary splits of data are produced, and for each partition local models are calculated. Among all the splits, the best one is selected by means of the F-test comparing the inner models. This process is recursively applied for each child node. The stop criterion is based on the significance level of the p-value associated with the F statistic. Additionally, two stop parameters are also considered: the number of individuals in a node and the growing level of the depth of the tree. This function extends the pathmox algorithm introduced by Sanchez in 2009 including the two new test: the F-block test (to detect the responsible latent endogenous equations of the difference), the F-coefficient test (to detect the path coefficients responsible of the difference). The F-tests used in the split process are implemented following the classic least square estimation. An implementation of the tests following the LAD regression also are proposed to overcome the parametric hypothesis of the F-test.

## Usage

```

pls.pathmox(xpls, SVAR, signif, deep, method = "lm", size, X = NULL,
tree = TRUE, n.node = 30, ...)

```

## Arguments

`xpls` An object of class "plsmpm" returned by `plsmpm`.

SVAR	A data frame of factors containing the segmentation variables.
signif	A numeric value indicating the significance threshold of the F-statistic. Must be a decimal number between 0 and 1.
deep	An integer indicating the depth level of the tree. Must be an integer greater than 1.
method	A string indicating the criterion used to calculate the the test can be equal to "lm" or "lad".
size	A numeric value indicating the minimum size of elements inside a node.
X	Optional dataset (matrix or data frame) used when argument dataset=NULL inside pls.
tree	A logical value indicating if the tree should be displayed (TRUE by default).
n.node	It is the minimum number of individuals to consider a candidate partition (30 by default).
...	Further arguments passed on to <a href="#">pls.pathmox</a> .

### Details

The argument `xpls` is object of class "plspm" returned by [plspm](#).

The argument `SVAR` must be a data frame containing segmentation variables as factors. The number of rows in `SVAR` must be the same as the number of rows in the data used in `pls`.

The argument `signif` represent the p-value level takes as reference to stop the tree partitions.

The argument `deep` represent the depth level of the tree takes as reference to stop the tree partitions.

The argument `method` is a string containing the criterion used to calculate the tests; if `method="lm"` the classic least square approach is used to perform the tests; if `method="lad"` the LAD (least absolute deviation regression) is used.

The argument `size` is defined as a decimal value (i.e. proportion of elements inside a node).

The argument `n.node` is the minimum number of individuals to consider a candidate partition. If the candidate split produces a partition where the number of individuals is less then `n.node`, the partition is not considered.

When the object `pls` does not contain a data matrix (i.e. `pls$data=NULL`), the user must provide the data matrix or data frame in `X`.

### Value

An object of class "xtree.pls". Basically a list with the following results:

MOX	Data frame with the results of the segmentation tree
root	List of elements contained in the root node
terminal	List of elements contained in terminal nodes
nodes	List of elements contained in all nodes: terminal and intermediate
candidates	List of data frames containing the candidate splits of each node partition
Fg.r	Data frame containing the results of the F-global test for each node partition

Fb.r	List of data frames containing the results of the F-block test for each node partition
Fc.r	A list of data frames containing the results of the F-coefficients test for each node partition
model	Informations about the internal parameters

**Author(s)**

Giuseppe Lamberti

**References**

Lamberti, G. et al. (2016) *The Pathmox approach for PLS path modeling segmentation*. Applied Stochastic Models in Business and Industry; doi: 10.1002/asmb.2168;

Aluja, T., Lamberti, G., Sanchez, G. (2013). Extending the PATHMOX approach to detect which constructs differentiate segments. In H., Abdi, W. W., Chin, V., Esposito Vinzi, G., Russolillo, and L., Trinchera (Eds.), Book title: *New Perspectives in Partial Least Squares and Related Methods* (pp.269-280). Springer.

Lamberti, G. (2014) *Modeling with Heterogeneity*. PhD Dissertation.

Sanchez, G. (2009) *PATHMOX Approach: Segmentation Trees in Partial Least Squares Path Modeling*. PhD Dissertation.

Tenenhaus M., Esposito Vinzi V., Chatelin Y.M., and Lauro C. (2005) PLS path modeling. *Computational Statistics & Data Analysis*, **48**, pp. 159-205.

**Examples**

```
## Not run:
## example of PLS-PM in alumni satisfaction

data(fibtele)

# select manifest variables
data.fib <-fibtele[,12:35]

# define inner model matrix
Image = rep(0,5)
Qual.spec = rep(0,5)
Qual.gen = rep(0,5)
Value = c(1,1,1,0,0)
Satis = c(1,1,1,1,0)
inner.fib = rbind(Image,Qual.spec, Qual.gen, Value, Satis)
colnames(inner.fib) = rownames(inner.fib)

# blocks of indicators (outer model)
outer.fib = list(1:8,9:11,12:16,17:20,21:24)
modes.fib = rep("A", 5)

# apply plspm
pls.fib = plspm(data.fib, inner.fib, outer.fib, modes.fib)
```

```

# re-ordering those segmentation variables with ordinal scale
seg.fib= fibtele[,2:11]

seg.fib$Age = factor(seg.fib$Age, ordered=T)
seg.fib$Salary = factor(seg.fib$Salary,
levels=c("<18k", "25k", "35k", "45k", ">45k"), ordered=T)
seg.fib$Accgrade = factor(seg.fib$Accgrade,
levels=c("accnote<7", "7-8accnote", "accnote>8"), ordered=T)
seg.fib$Grade = factor(seg.fib$Grade,
  levels=c("<6.5note", "6.5-7note", "7-7.5note", ">7.5note"), ordered=T)

# Pathmox Analysis
fib.pathmox=pls.pathmox(pls.fib,seg.fib,signif=0.05,
deep=2,size=0.2,n.node=20)

## End(Not run)

library(genpathmox)
data(fibtele)

# select manifest variables
data.fib <-fibtele[1:50,12:35]

# define inner model matrix
Image      = rep(0,5)
Qual.spec = rep(0,5)
Qual.gen   = rep(0,5)
Value     = c(1,1,1,0,0)
Satis     = c(1,1,1,1,0)
inner.fib = rbind(Image,Qual.spec, Qual.gen, Value, Satis)
colnames(inner.fib) = rownames(inner.fib)

# blocks of indicators (outer model)
outer.fib = list(1:8,9:11,12:16,17:20,21:24)
modes.fib = rep("A", 5)

# apply plspm
pls.fib = plspm(data.fib, inner.fib, outer.fib, modes.fib)

# re-ordering those segmentation variables with ordinal scale
seg.fib = fibtele[1:50,c(2,7)]
seg.fib$Salary = factor(seg.fib$Salary,
levels=c("<18k", "25k", "35k", "45k", ">45k"), ordered=TRUE)

# Pathmox Analysis
fib.pathmox = pls.pathmox(pls.fib,seg.fib,signif=0.5,
deep=1,size=0.01,n.node=10)

```

---

pls.treemodel	<i>PLS-PM results of terminal nodes from the Pathmox Segmentation Trees</i>
---------------	---

---

### Description

Calculates basic PLS-PM results for the terminal nodes of PATHMOX trees

### Usage

```
pls.treemodel(xpls, xtree, X = NULL, alpha = 0.05, terminal = TRUE,
             scaled = FALSE, label = FALSE, label.nodes = NULL, ...)
```

### Arguments

xpls	An object of class "plspm" returned by <a href="#">plspm</a> .
xtree	An object of class "xtree.pls" returned by <a href="#">pls.pathmox</a> .
X	Optional dataset (matrix or data frame) used when argument dataset=NULL inside xpls.
alpha	is numeric value indicating the significance threshold of the invariance test
terminal	is string, if equal to TRUE, just the terminal nodes are considered for the output results. when it is equal to FALSE, the PLS-PM results are generated for all nodes of the tree
scaled	to standardize the latent variables or not
label	is a string. It is false for defect. If it is TRUE, label.nodes has to be fix.
label.nodes	is a vector with the name of the nodes. It is null for defect.
...	Further arguments passed on to <a href="#">pls.treemodel</a> .

### Details

The argument xpls must be the same used for calculating the xtree object. When the object xpls does not contain a data matrix (i.e. pls\$data=NULL), the user must provide the data matrix or data frame in X.

The argument xtree is an object of class "xtree.pls" returned by [pls.pathmox](#).

### Value

An object of class "treemodel.pls". Basically a list with the following results:

inner	Matrix of the inner relationship between latent variables of the PLS-PM model
invariance.test	A data frame containing the results of the invariance test
weights	Matrix of outer weights for each terminal node
loadings	Matrix of loadings for each terminal node

paths	Matrix of path coefficients for each terminal node
r2	Matrix of r-squared coefficients for each terminal node
sign	list of matrix with the significance for each terminal node

**Author(s)**

Giuseppe Lamberti

**References**

Lamberti, G. et al. (2016) *The Pathmox approach for PLS path modeling segmentation*. Applied Stochastic Models in Business and Industry; doi: 10.1002/asmb.2168;

Aluja, T., Lamberti, G., Sanchez, G. (2013). Extending the PATHMOX approach to detect which constructs differentiate segments. In H., Abdi, W. W., Chin, V., Esposito Vinzi, G., Russolillo, and L., Trinchera (Eds.), Book title: *New Perspectives in Partial Least Squares and Related Methods* (pp.269-280). Springer.

Lamberti, G. (2014) *Modeling with Heterogeneity*. PhD Dissertation.

Sanchez, G. (2009) *PATHMOX Approach: Segmentation Trees in Partial Least Squares Path Modeling*. PhD Dissertation.

Tenenhaus M., Esposito Vinzi V., Chatelin Y.M., and Lauro C. (2005) PLS path modeling. *Computational Statistics & Data Analysis*, **48**, pp. 159-205.

**See Also**

[pls.pathmox,plot.xtree.pls](#)

**Examples**

```
## Not run:
## example of PLS-PM in alumni satisfaction

data(fibtele)

# select manifest variables
data.fib <-fibtele[,12:35]

# define inner model matrix
Image   = rep(0,5)
Qual.spec = rep(0,5)
Qual.gen = rep(0,5)
Value   = c(1,1,1,0,0)
Satis   = c(1,1,1,1,0)
inner.fib = rbind(Image,Qual.spec, Qual.gen, Value, Satis)
colnames(inner.fib) = rownames(inner.fib)

# blocks of indicators (outer model)
outer.fib = list(1:8,9:11,12:16,17:20,21:24)
modes.fib = rep("A", 5)
```



```

# apply plspm
pls.fib = plspm(data.fib, inner.fib, outer.fib, modes.fib)

# re-ordering those segmentation variables with ordinal scale
seg.fib= fibtele[,2:11]

seg.fib$Age = factor(seg.fib$Age, ordered=T)
seg.fib$Salary = factor(seg.fib$Salary,
levels=c("<18k", "25k", "35k", "45k", ">45k"), ordered=T)
seg.fib$Accgrade = factor(seg.fib$Accgrade,
levels=c("accnote<7", "7-8accnote", "accnote>8"), ordered=T)
seg.fib$Grade = factor(seg.fib$Grade,
  levels=c("<6.5note", "6.5-7note", "7-7.5note", ">7.5note"), ordered=T)

# Pathmox Analysis
fib.pathmox=pls.pathmox(pls.fib,seg.fib,signif=0.05,
deep=2,size=0.2,n.node=20)

fib.comp=pls.treemodel(pls.fib,fib.pathmox)

## End(Not run)

library(genpathmox)
data(fibtele)

# select manifest variables
data.fib <-fibtele[1:50,12:35]

# define inner model matrix
Image      = rep(0,5)
Qual.spec  = rep(0,5)
Qual.gen   = rep(0,5)
Value      = c(1,1,1,0,0)
Satis      = c(1,1,1,1,0)
inner.fib  = rbind(Image,Qual.spec, Qual.gen, Value, Satis)
colnames(inner.fib) = rownames(inner.fib)

# blocks of indicators (outer model)
outer.fib = list(1:8,9:11,12:16,17:20,21:24)
modes.fib = rep("A", 5)

# apply plspm
pls.fib = plspm(data.fib, inner.fib, outer.fib, modes.fib)

# re-ordering those segmentation variables with ordinal scale
seg.fib = fibtele[1:50,c(2,7)]
seg.fib$Salary = factor(seg.fib$Salary,
levels=c("<18k", "25k", "35k", "45k", ">45k"), ordered=TRUE)

# Pathmox Analysis
fib.pathmox = pls.pathmox(pls.fib,seg.fib,signif=0.5,

```

```
deep=1,size=0.01,n.node=10)
```

---

```
print.xtree.pls      Print function for the Pathmox Segmentation Trees: PLS-PM
```

---

### Description

The function `print.xtree.pls` print the `pls.pathmox` tree

### Usage

```
## S3 method for class 'xtree.pls'
print(x, ...)
```

### Arguments

```
x          An object of class "xtree.pls".
...        Further arguments are ignored.
```

### Author(s)

Giuseppe Lamberti

### References

Lamberti, G. et al. (2016) *The Pathmox approach for PLS path modeling segmentation*. Applied Stochastic Models in Business and Industry; doi: 10.1002/asmb.2168;

Aluja, T., Lamberti, G., Sanchez, G. (2013). Extending the PATHMOX approach to detect which constructs differentiate segments. In H., Abdi, W. W., Chin, V., Esposito Vinzi, G., Russolillo, and L., Trinchera (Eds.), Book title: *New Perspectives in Partial Least Squares and Related Methods* (pp.269-280). Springer.

Lamberti, G. (2014) *Modeling with Heterogeneity*. PhD Dissertation.

Sanchez, G. (2009) *PATHMOX Approach: Segmentation Trees in Partial Least Squares Path Modeling*. PhD Dissertation.

Tenenhous M., Esposito Vinzi V., Chatelin Y.M., and Lauro C. (2005) PLS path modeling. *Computational Statistics & Data Analysis*, **48**, pp. 159-205.

[summary.xtree.pls](#).

### Examples

```
## Not run:
## example of PLS-PM in alumni satisfaction

data(fibtele)

# select manifest variables
```

```

data.fib <-fibtele[,12:35]

# define inner model matrix
Image    = rep(0,5)
Qual.spec = rep(0,5)
Qual.gen = rep(0,5)
Value    = c(1,1,1,0,0)
Satis    = c(1,1,1,1,0)
inner.fib = rbind(Image,Qual.spec, Qual.gen, Value, Satis)
colnames(inner.fib) = rownames(inner.fib)

# blocks of indicators (outer model)
outer.fib = list(1:8,9:11,12:16,17:20,21:24)
modes.fib = rep("A", 5)

# apply plspm
pls.fib = plspm(data.fib, inner.fib, outer.fib, modes.fib)

# re-ordering those segmentation variables with ordinal scale
seg.fib= fibtele[,2:11]

seg.fib$Age = factor(seg.fib$Age, ordered=T)
seg.fib$Salary = factor(seg.fib$Salary,
levels=c("<18k", "25k", "35k", "45k", ">45k"), ordered=T)
seg.fib$Accgrade = factor(seg.fib$Accgrade,
levels=c("accnote<7", "7-8accnote", "accnote>8"), ordered=T)
seg.fib$Grade = factor(seg.fib$Grade,
  levels=c("<6.5note", "6.5-7note", "7-7.5note", ">7.5note"), ordered=T)

# Pathmox Analysis
fib.pathmox=pls.pathmox(pls.fib,seg.fib,signif=0.05,
deep=2,size=0.2,n.node=20)

print(fib.pathmox)

## End(Not run)

library(genpathmox)
data(fibtele)

# select manifest variables
data.fib <-fibtele[1:50,12:35]

# define inner model matrix
Image    = rep(0,5)
Qual.spec = rep(0,5)
Qual.gen = rep(0,5)
Value    = c(1,1,1,0,0)
Satis    = c(1,1,1,1,0)
inner.fib = rbind(Image,Qual.spec, Qual.gen, Value, Satis)
colnames(inner.fib) = rownames(inner.fib)

# blocks of indicators (outer model)

```

```
outer.fib = list(1:8,9:11,12:16,17:20,21:24)
modes.fib = rep("A", 5)

# apply plspm
pls.fib = plspm(data.fib, inner.fib, outer.fib, modes.fib)

# re-ordering those segmentation variables with ordinal scale
seg.fib = fibtele[1:50,c(2,7)]
seg.fib$Salary = factor(seg.fib$Salary,
levels=c("<18k", "25k", "35k", "45k", ">45k"), ordered=TRUE)

# Pathmox Analysis
fib.pathmox = pls.pathmox(pls.fib,seg.fib,signif=0.5,
deep=1,size=0.01,n.node=10)

print(fib.pathmox)
```

---

print.xtree.reg	<i>Print function for the Pathmox Segmentation Trees: linear regression and LAD</i>
-----------------	---

---

## Description

The function `print.xtree.reg` print the `reg.pathmox` tree

## Usage

```
## S3 method for class 'xtree.reg'
print(x, ...)
```

## Arguments

x	An object of class "xtree.reg".
...	Further arguments are ignored.

## Author(s)

Giuseppe Lamberti

## References

Aluja, T. Lamberti, G. Sanchez, G. (2013). Modeling with heterogeneity. Meetings of Italian Statistical Society, Advances in Latent Variables - Methods, Models and Applications. Brescia.

Lamberti, G. (2014) *Modeling with Heterogeneity*. PhD Dissertation.

Sanchez, G. (2009) *PATHMOX Approach: Segmentation Trees in Partial Least Squares Path Modeling*. PhD Dissertation.

[summary.xtree.pls](#).

**Examples**

```
## Not run:
##example of LM in alumni satisfaction

data(fibtelereg)

#identify the segmentation variables
segvar = fibtelereg[,2:11]

#select the variables
data.fib = fibtelereg[,12:18]

#re-ordering those segmentation variables with ordinal scale
segvar$Age = factor(segvar$Age, ordered=T)
segvar$Salary = factor(segvar$Salary,
levels=c("<18k", "25k", "35k", "45k", ">45k"), ordered=T)
segvar$Accgrade = factor(segvar$Accgrade,
levels=c("accnote<7", "7-8accnote", "accnote>8"), ordered=T)
segvar$Grade = factor(segvar$Grade,
levels=c("<6.5note", "6.5-7note", "7-7.5note", ">7.5note"), ordered=T)

fib.reg.pathmox=reg.pathmox(Satisfact~., data=data.fib, segvar,
signif=0.05, deep=2, method="lm", size=0.15)

print(fib.reg.pathmox)

## End(Not run)
data(fibtelereg)

#Identify the segmentation variables
segvar= fibtelereg[1:50,3:4]

#Select the variables
data.fib=fibtelereg[1:50,12:18]

fib.reg.pathmox=reg.pathmox(Satisfact~., data=data.fib, segvar,
signif=0.05, deep=1, method="lm", size=0.15)

print(fib.reg.pathmox)
```

---

reg.pathmox

*PATHMOX-REG: Segmentation Trees in linear and LAD regression model*


---

**Description**

The function `reg.pathmox` calculates a binary segmentation tree in the context of linear regression following the `PATHMOX` algorithm. This function also generalizes the `Pathmox` algorithm introduced by Sanchez in 2009 to the context of linear and LAD regression.

**Usage**

```
reg.pathmox(formula, SVAR, signif, deep, method, size, tree = TRUE,
            data = NULL, ...)
```

**Arguments**

formula	An object of class "formula".
SVAR	A data frame of factors containing the segmentation variables.
signif	A numeric value indicating the significance threshold of the F-statistic. Must be a decimal number between 0 and 1.
deep	An integer indicating the depth level of the tree. Must be an integer greater than 1.
method	A string indicating the criterion used to calculate the test can be equal to "lm" or "lad" node.
size	A numeric value indicating the minimum size of elements inside a node.
tree	A logical value indicating if the tree should be displayed (TRUE by default).
data	an optional data frame.
...	Further arguments passed on to <a href="#">reg.pathmox</a> .

**Details**

The argument `formula` is an object of class "formula" (or one that can be coerced to that class): a symbolic description of the model to be fitted.

The argument `SVAR` must be a data frame containing segmentation variables as factors. The number of rows in `SVAR` must be the same as the number of rows in the data

The argument `signif` represent the p-value level takes as reference to stop the tree partitions.

The argument `deep` represent the p-value level takes as reference to stop the tree partitions.

The argument `method` is a string containing the criterion used to calculate the test; if `method="lm"` the classic least square approach is used to perform the test; if `method="lad"` the lad (least absolute deviation) is used.

The argument `size` has defined as a decimal value (i.e. proportion of elements inside a node).

**Value**

An object of class "xtree.reg". Basically a list with the following results:

MOX	Data frame with the results of the segmentation tree
root	element of containing in the root node
terminal	element of containing in the terminal nodes
nodes	element of containing in all nodes terminal and intermediate
candidates	List of data frames containing the candidate splits of each node partition
Fg.r	Data frame containing the results of the F-global test for each node partition
Fc.r	A list of Data frames containing the results of the F-coefficients test for each node partition
model	Information about the internal parameters

**Author(s)**

Giuseppe Lamberti

**References**

Aluja, T. Lamberti, G. Sanchez, G. (2013). Modeling with heterogeneity. Meetings of Italian Statistical Society, Advances in Latent Variables - Methods, Models and Applications. Brescia.

Lamberti, G. (2014) *Modeling with Heterogeneity*. PhD Dissertation.

Sanchez, G. (2009) *PATHMOX Approach: Segmentation Trees in Partial Least Squares Path Modeling*. PhD Dissertation.

**Examples**

```
## Not run:
##example of LM in alumni satisfaction

data(fibtelereg)

#identify the segmentation variables
segvar = fibtelereg[,2:11]

#select the variables
data.fib = fibtelereg[,12:18]

#re-ordering those segmentation variables with ordinal scale
segvar$Age      = factor(segvar$Age, ordered=T)
segvar$Salary   = factor(segvar$Salary,
  levels=c("<18k", "25k", "35k", "45k", ">45k"), ordered=T)
segvar$Accgrade = factor(segvar$Accgrade,
  levels=c("accnote<7", "7-8accnote", "accnote>8"), ordered=T)
segvar$Grade    = factor(segvar$Grade,
  levels=c("<6.5note", "6.5-7note", "7-7.5note", ">7.5note"), ordered=T)

#regression PATHMOX
fib.reg.pathmox = reg.pathmox(Satisfact~., data=data.fib, segvar,
  signif=0.05, deep=2, method="lm", size=0.15)

## End(Not run)

data(fibtelereg)

#identify the segmentation variables
segvar= fibtelereg[1:50,3:4]

#select the variables
data.fib=fibtelereg[1:50,12:18]

fib.reg.pathmox=reg.pathmox(Satisfact~., data=data.fib, segvar,
  signif=0.05, deep=1, method="lm", size=0.15)
```

---

reg.treemodel	<i>Regression results of terminal nodes from the Pathmox Segmentation Trees</i>
---------------	---

---

### Description

Calculates basic regression results for the terminal nodes of Pathmox Segmentation Trees: liner regression and LAD trees

### Usage

```
reg.treemodel(xtree.reg, terminal = TRUE, intercept = FALSE,
  label = FALSE, label.nodes = NULL, ...)
```

### Arguments

xtree.reg	An object of class "xtree.reg" returned by <a href="#">reg.pathmox</a> .
terminal	is string, if equal to TRUE, just the terminal nodes are considered for the output results. when it is equal to FALSE, the regression results are generated for all nodes of the tree
intercept	if equal to TRUE also the intercept is considered in the estimation
label	is a boolean. tI is false for defect. If it is TRUE, label.nodes has to be fix.
label.nodes	is a vector with the name of the nodes. It is null for defect.
...	Further arguments passed on to <a href="#">reg.treemodel</a> .

### Details

The argument xtree.reg is an object of class "xtree.reg" returned by [reg.pathmox](#).

### Value

An object of class "regtreemodel". Basically a list with the following results:

inner	Matrix of the inner relationship between latent variables of the PLS-PM model
method	A string containing the used method ("lm" or "lad")
coefficients	Matrix coefficients for each terminal node
Std.	Matrix of estandard deviation of coefficients for each terminal node
pval.coef	Matrix of p-value significance for each terminal node
r2	Matrix of r-squared coefficients for each terminal node

### Author(s)

Giuseppe Lamberti



## References

- Aluja, T. Lamberti, G. Sanchez, G. (2013). Modeling with heterogeneity. Meetings of Italian Statistical Society, Advances in Latent Variables - Methods, Models and Applications. Brescia.
- Lamberti, G. (2014) *Modeling with Heterogeneity*. PhD Dissertation.
- Sanchez, G. (2009) *PATHMOX Approach: Segmentation Trees in Partial Least Squares Path Modeling*. PhD Dissertation.

## See Also

[pls.pathmox](#), [plot.xtree.pls](#)

## Examples

```
## Not run:
#example of LM in alumni satisfaction

data(fibtelereg)

#identify the segmentation variables
segvar= fibtelereg[,2:11]

#select the variables
data.fib= fibtelereg[,12:18]

segvar$Age = factor(segvar$Age, ordered=T)
segvar$Salary = factor(segvar$Salary,
  levels=c("<18k", "25k", "35k", "45k", ">45k"), ordered=T)
segvar$Accgrade = factor(segvar$Accgrade,
  levels=c("accnote<7", "7-8accnote", "accnote>8"), ordered=T)
segvar$Grade = factor(segvar$Grade,
  levels=c("<6.5note", "6.5-7note", "7-7.5note", ">7.5note"), ordered=T)

#regression PATHMOX
fib.reg.pathmox=reg.pathmox(Satisfact~., data=data.fib, segvar,
  signif=0.05, deep=2, method="lm", size=0.15)

#terminal nodes comparison
fib.node.comp=reg.treemodel(fib.reg.pathmox)

## End(Not run)

data(fibtelereg)

#identify the segmentation variables
segvar= fibtelereg[1:50,3:4]

#select the variables
data.fib=fibtelereg[1:50,12:18]

fib.reg.pathmox=reg.pathmox(Satisfact~., data=data.fib, segvar,
```

```
signif=0.05,deep=1,method="lm",size=0.15)
fib.node.comp=reg.treemodel(fib.reg.pathmox)
```

---

summary.xtree.pls      *Summary function for the Pathmox Segmentation Trees: PLS-PM*

---

## Description

The function `summary.xtree.pls` returns the most important results obtained by the function `pls.pathmox`. In order, it provides the parameters algorithm ( threshold significance,node size limit",tree depth level and the method used for the split partition), the basic characteristics of the tree (deep and number of terminal nodes), the basic characteristics of the nodes and the F-global the F-block and F-coefficients results. For the test results the significance level is also indicated.

## Usage

```
## S3 method for class 'xtree.pls'
summary(object, ...)
```

## Arguments

<code>object</code>	An object of class "xtree.pls".
<code>...</code>	Further arguments are ignored.

## Author(s)

Giuseppe Lamberti

## References

Lamberti, G. et al. (2016) *The Pathmox approach for PLS path modeling segmentation*. Applied Stochastic Models in Business and Industry; doi: 10.1002/asmb.2168;

Aluja, T., Lamberti, G., Sanchez, G. (2013). Extending the PATHMOX approach to detect which constructs differentiate segments. In H., Abdi, W. W., Chin, V., Esposito Vinzi, G., Russolillo, and L., Trinchera (Eds.), Book title: *New Perspectives in Partial Least Squares and Related Methods* (pp.269-280). Springer.

Lamberti, G. (2014) *Modeling with Heterogeneity*. PhD Dissertation.

Sanchez, G. (2009) *PATHMOX Approach: Segmentation Trees in Partial Least Squares Path Modeling*. PhD Dissertation.

Tenenhaus M., Esposito Vinzi V., Chatelin Y.M., and Lauro C. (2005) PLS path modeling. *Computational Statistics & Data Analysis*, **48**, pp. 159-205.

[pls.pathmox](#)

**Examples**

```

## Not run:
## example of PLS-PM in alumni satisfaction

# select manifest variables
data.fib <-fibtele[,12:35]

# define inner model matrix
Image      = rep(0,5)
Qual.spec  = rep(0,5)
Qual.gen   = rep(0,5)
Value     = c(1,1,1,0,0)
Satis     = c(1,1,1,1,0)
inner.fib = rbind(Image,Qual.spec, Qual.gen, Value, Satis)
colnames(inner.fib) = rownames(inner.fib)

# blocks of indicators (outer model)
outer.fib = list(1:8,9:11,12:16,17:20,21:24)
modes.fib = rep("A", 5)

# apply plspm
pls.fib = plspm(data.fib, inner.fib, outer.fib, modes.fib)

# re-ordering those segmentation variables with ordinal scale
seg.fib= fibtele[,2:11]

seg.fib$Age = factor(seg.fib$Age, ordered=T)
seg.fib$Salary = factor(seg.fib$Salary,
levels=c("<18k", "25k", "35k", "45k", ">45k"), ordered=T)
seg.fib$Accgrade = factor(seg.fib$Accgrade,
levels=c("accnote<7", "7-8accnote", "accnote>8"), ordered=T)
seg.fib$Grade = factor(seg.fib$Grade,
  levels=c("<6.5note", "6.5-7note", "7-7.5note", ">7.5note"), ordered=T)

# Pathmox Analysis
fib.pathmox=pls.pathmox(pls.fib,seg.fib,signif=0.05,
deep=2,size=0.2,n.node=20)

summary(fib.pathmox)

## End(Not run)

library(genpathmox)
data(fibtele)

# select manifest variables
data.fib <-fibtele[1:50,12:35]

# define inner model matrix
Image      = rep(0,5)
Qual.spec  = rep(0,5)
Qual.gen   = rep(0,5)

```

```

Value = c(1,1,1,0,0)
Satis = c(1,1,1,1,0)
inner.fib = rbind(Image,Qual.spec, Qual.gen, Value, Satis)
colnames(inner.fib) = rownames(inner.fib)

# blocks of indicators (outer model)
outer.fib = list(1:8,9:11,12:16,17:20,21:24)
modes.fib = rep("A", 5)

# apply plspm
pls.fib = plspm(data.fib, inner.fib, outer.fib, modes.fib)

# re-ordering those segmentation variables with ordinal scale
seg.fib = fibtele[1:50,c(2,7)]
seg.fib$Salary = factor(seg.fib$Salary,
levels=c("<18k","25k","35k","45k",">45k"), ordered=TRUE)

# Pathmox Analysis
fib.pathmox = pls.pathmox(pls.fib,seg.fib,signif=0.5,
deep=1,size=0.01,n.node=10)

summary(fib.pathmox)

```

---

summary.xtree.reg	<i>Summary function for the Pathmox Segmentation Trees: linear regression and LAD</i>
-------------------	---

---

## Description

The function `summary.xtree.reg` returns the most important results obtained by the function `reg.pathmox`. In order, it provides the parameters algorithm ( threshold significance,node size limit,tree depth level and the method used for the split partition), the basic characteristics of the tree (deep and number of terminal nodes), the basic characteristics of the nodes and the F-global and F-coefficients results. For the test results the significance level is indicated.

## Usage

```
## S3 method for class 'xtree.reg'
summary(object, ...)
```

## Arguments

```
object      An object of class "xtree.reg".
...         Further arguments are ignored.
```

## Author(s)

Giuseppe Lamberti

## References

Aluja, T. Lamberti, G. Sanchez, G. (2013). Modeling with heterogeneity. Meetings of Italian Statistical Society, Advances in Latent Variables - Methods, Models and Applications. Brescia.

Lamberti, G. (2014) *Modeling with Heterogeneity*. PhD Dissertation.

Sanchez, G. (2009) *PATHMOX Approach: Segmentation Trees in Partial Least Squares Path Modeling*. PhD Dissertation.

[summary.xtree.pls](#), [reg.pathmox](#).

## Examples

```
## Not run:
##example of LM in alumni satisfaction

data(fibtelereg)

#identify the segmentation variables
segvar = fibtelereg[,2:11]

#select the variables
data.fib = fibtelereg[,12:18]

#re-ordering those segmentation variables with ordinal scale
segvar$Age = factor(segvar$Age, ordered=T)
segvar$Salary = factor(segvar$Salary,
levels=c("<18k","25k","35k","45k",">45k"), ordered=T)
segvar$Accgrade = factor(segvar$Accgrade,
levels=c("accnote<7","7-8accnote","accnote>8"), ordered=T)
segvar$Grade = factor(segvar$Grade,
levels=c("<6.5note","6.5-7note","7-7.5note",">7.5note"), ordered=T)

#regression PATHMOX
fib.reg.pathmox = reg.pathmox(Satisfact~.,data=data.fib,segvar,
signif=0.05,deep=2,method="lm",size=0.15)

summary(fib.reg.pathmox)

## End(Not run)

data(fibtelereg)

#identify the segmentation variables
segvar= fibtelereg[1:50,3:4]

#select the variables
data.fib=fibtelereg[1:50,12:18]

fib.reg.pathmox=reg.pathmox(Satisfact~.,data=data.fib,segvar,
signif=0.05,deep=1,method="lm",size=0.15)

summary(fib.reg.pathmox)
```

---

`tree-class`*tree class*

---

**Description**

tree is a S4 class that contains info on the binary segmentation tree

# Index

## \*Topic **datasets**

fibtele, [2](#)

fibtelereg, [4](#)

fibtele, [2](#)

fibtelereg, [4](#)

info.pls\_class, [5](#)

info.reg\_class, [5](#)

invariance\_test, [5](#)

node-class, [8](#)

node.reg\_class, [9](#)

plot.treemodel, [9](#)

plot.treemodelreg, [12](#), [13](#)

plot.xtree.pls, [14](#), [15](#), [24](#), [33](#)

plot.xtree.reg, [17](#)

pls.pathmox, [15](#), [19](#), [20](#), [23](#), [24](#), [33](#), [34](#)

pls.treemodel, [9](#), [23](#), [23](#)

plspm, [19](#), [20](#), [23](#)

print.xtree.pls, [26](#)

print.xtree.reg, [28](#)

reg.pathmox, [13](#), [17](#), [29](#), [30](#), [32](#), [37](#)

reg.treemodel, [13](#), [32](#), [32](#)

summary.xtree.pls, [26](#), [28](#), [34](#), [37](#)

summary.xtree.reg, [36](#)

tree-class, [38](#)