

# Package ‘js’

July 28, 2017

**Type** Package

**Title** Tools for Working with JavaScript in R

**Version** 1.1

**Author** Jeroen Ooms

**Maintainer** Jeroen Ooms <jeroen@berkeley.edu>

**Description** A set of utilities for working with JavaScript syntax in R.  
Includes tools to parse, tokenize, compile, validate, reformat, optimize  
and analyze JavaScript code.

**License** MIT + file LICENSE

**URL** <https://github.com/jeroen/js>

**BugReports** <https://github.com/jeroen/js/issues>

**VignetteBuilder** knitr

**Imports** V8 (>= 0.5)

**Suggests** knitr, rmarkdown

**RoxygenNote** 6.0.1

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2017-07-28 21:32:04 UTC

## R topics documented:

coffee_compile . . . . .	2
esprima . . . . .	2
jshint . . . . .	3
js_eval . . . . .	4
js_typeof . . . . .	4
js_validate_script . . . . .	5
uglify . . . . .	5
<b>Index</b>	<b>7</b>

---

coffee_compile	<i>Coffee Script</i>
----------------	----------------------

---

### Description

Compiles coffee script into JavaScript.

### Usage

```
coffee_compile(code, ...)
```

### Arguments

code	a string with JavaScript code
...	additional options passed to the compiler

### Examples

```
# Hello world
coffee_compile("square = (x) -> x * x")
coffee_compile("square = (x) -> x * x", bare = TRUE)

# Simple script
demo <- readLines(system.file("example/demo.coffee", package = "js"))
js <- coffee_compile(demo)
cat(js)
cat(uglify_optimize(js))
```

---

esprima	<i>JavaScript Syntax Tree</i>
---------	-------------------------------

---

### Description

**Esprima** is a high performance, standard-compliant ECMAScript parser. It has full support for ECMAScript 2017 and returns a sensible syntax tree format as standardized by ESTree project.

### Usage

```
esprima_tokenize(text, range = FALSE, loc = FALSE, comment = FALSE)
```

```
esprima_parse(text, jsx = FALSE, range = FALSE, loc = FALSE,
  tolerant = FALSE, tokens = FALSE, comment = FALSE)
```

**Arguments**

text	a character vector with JavaScript code
range	Annotate each token with its zero-based start and end location
loc	Annotate each token with its column and row-based location
comment	Include every line and block comment in the output
jsx	Support JSX syntax
tolerant	Tolerate a few cases of syntax errors
tokens	Collect every token

**Details**

The `esprima_tokenize` function returns a data frame with JavaScript tokens. The `esprima_parse` function returns the Syntax Tree in JSON format. This can be parsed to R using e.g. `jsonlite::fromJSON`.

**References**

Esprima documentation: <http://esprima.readthedocs.io/en/4.0/>.

**Examples**

```
code <- "function test(x, y){ x = x || 1; y = y || 1; return x*y;}"
esprima_tokenize(code)
esprima_parse(code)
```

---

jshint

*Static analysis tool for JavaScript*


---

**Description**

JSHint is a community-driven tool to detect errors and potential problems in JavaScript code. It is very flexible so you can easily adjust it to your particular coding guidelines and the environment you expect your code to execute in.

**Usage**

```
jshint(text, ..., globals = NULL)
```

**Arguments**

text	a string of JavaScript code
...	additional jshint <a href="#">configuration options</a>
globals	a white list of global variables that are not formally defined in the source code

**Value**

a data frame where each row represents a jshint error or NULL if there were no errors

**Examples**

```
code = "var foo = 123"  
jshint(code)  
jshint(code, asi = TRUE)
```

---

`js_eval`*Evaluate JavaScript*

---

**Description**

Evaluate a piece of JavaScript code in a disposable context.

**Usage**

```
js_eval(text)
```

**Arguments**

<code>text</code>	JavaScript code
-------------------	-----------------

**Examples**

```
# Stateless evaluation  
js_eval("(function() {return 'foo'}})()")  
  
# Use V8 for stateful evaluation  
ct <- V8::new_context()  
ct$eval("var foo = 123")  
ct$get("foo")
```

---

`js_typeof`*Get the type of a JavaScript object*

---

**Description**

JavaScript wrapper to `typeof` to test if a piece of JavaScript code is syntactically valid, and the type of object it evaluates to. Useful to verify that a piece of JavaScript code contains a proper function/object.

**Usage**

```
js_typeof(text)
```

**Arguments**

<code>text</code>	JavaScript code
-------------------	-----------------

### Examples

```
js_typeof("function(x){return x+1}")
js_typeof("(function() {return 'foo'})()")
js_typeof("{foo : 123, bar : true}")
```

---

js\_validate\_script      *Validate JavaScript*

---

### Description

Simple wrapper for `ct$validate` in [V8](#). Tests if code constitutes a syntactically valid JS script.

### Usage

```
js_validate_script(text, error = TRUE)
```

### Arguments

text	character vector with JavaScript code
error	raise error on invalid code

### Examples

```
js_validate_script("function foo(x){2*x}") #TRUE
js_validate_script("foo = function(x){2*x}") #TRUE

# Anonymous functions in global scope are invalid
js_validate_script("function(x){2*x}", error = FALSE) #FALSE

# Use ! or () to check anonymous function syntax
js_validate_script("!function(x){2*x}") #TRUE
js_validate_script("(function(x){2*x})") #TRUE
```

---

uglify                      *Compress and Reformat JavaScript Code*

---

### Description

**UglifyJS** is a JavaScript compressor/minifier written in JavaScript. It also contains tools that allow one to automate working with JavaScript code.

### Usage

```
uglify_reformat(text, beautify = FALSE, ...)

uglify_optimize(text, ...)
```

**Arguments**

text	a character vector with JavaScript code
beautify	prettify (instead of minify) code
...	additional arguments for the <b>optimizer</b> or <b>generator</b> .

**References**

UglifyJS2 Documentation: <http://lisperator.net/uglifyjs/>.

**Examples**

```
code <- "function test(x, y){ x = x || 1; y = y || 1; return x*y;}"
cat(uglify_optimize(code))
cat(uglify_reformat(code, beautify = TRUE, indent_level = 2))
```

# Index

coffee (coffee\_compile), 2  
coffee\_compile, 2

esprima, 2  
esprima\_parse (esprima), 2  
esprima\_tokenize (esprima), 2

js\_eval, 4  
js\_typeof, 4  
js\_validate\_script, 5  
jshint, 3

uglify, 5  
uglify\_optimize (uglify), 5  
uglify\_reformat (uglify), 5

V8, 5