

# Package 'expss'

July 1, 2019

**Type** Package

**Title** Tables, Labels and Some Useful Functions from Spreadsheets and 'SPSS' Statistics

**Version** 0.9.0

**Maintainer** Gregory Demin <gdemin@gmail.com>

**URL** <https://gdemin.github.io/expss/>

**BugReports** <https://github.com/gdemin/expss/issues>

**Depends** R (>= 3.3.0),

**Imports** foreign, utils, stats, magrittr (>= 1.5), htmlTable (>= 1.11.0), matrixStats (>= 0.51.0), data.table (>= 1.10),

**Suggests** DT, htmltools, knitr, repr, ggplot2, testthat, openxlsx, fst

**Description** Package computes and displays tables with support for 'SPSS'-style labels, multiple and nested banners, weights, multiple-response variables and significance testing. There are facilities for nice output of tables in 'knitr', 'Shiny', '\*.xlsx' files, R and 'Jupyter' notebooks. Methods for labelled variables add value labels support to base R functions and to some functions from other packages. Additionally, the package brings popular data transformation functions from 'SPSS' Statistics and 'Excel': 'RECODE', 'COUNT', 'COMPUTE', 'DO IF', 'COUNTIF', 'VLOOKUP' and etc. These functions are very useful for data processing in marketing research surveys. Package intended to help people to move data processing from 'Excel' and 'SPSS' to R.

**VignetteBuilder** knitr

**LazyData** yes

**License** GPL (>= 2)

**RoxygenNote** 6.1.1

**NeedsCompilation** no

**Author** Gregory Demin [aut, cre]

**Repository** CRAN

**Date/Publication** 2019-07-01 04:20:05 UTC

**R topics documented:**

add_rows	3
apply_labels	4
as.category	5
as.datatable_widget	7
as.dichotomy	8
as.etable	11
as.labelled	11
compare_proportions	12
compute	13
count_if	17
criteria	23
cro	27
cro_fun	31
default_dataset	36
do_repeat	37
drop_empty_rows	39
experimental	40
expss	43
expss.options	44
fctr	46
fre	47
htmlTable.etable	49
if_na	51
info	53
keep	54
match_row	56
merge.etable	57
mrset	58
names2labels	60
name_dots	61
nest	61
net	62
prepend_values	65
product_test	67
prop	68
qc	69
read_spss	70
recode	71
ref	75
set_caption	76
sheet	77
sort_asc	78
split_by	79
split_labels	81
sum_row	83
tables	85

tab_significance_options . . . . .	93
tab_sort_asc . . . . .	99
text_to_columns . . . . .	101
unlab . . . . .	102
values2labels . . . . .	103
val_lab . . . . .	104
vars . . . . .	106
var_lab . . . . .	109
vectors . . . . .	111
vlookup . . . . .	113
where . . . . .	116
window_fun . . . . .	118
write_labelled_csv . . . . .	118
w_mean . . . . .	122
xl_write . . . . .	124

## Index 129

---

add_rows	<i>Add rows to data.frame/matrix/table</i>
----------	--

---

### Description

add\_rows is similar to [rbind](#) but it handles non-matching column names. %add\_rows% is an infix version of add\_rows. There is also special method for the results of [cro/cro\\_fun/tables/fre](#). .add\_rows is version for adding rows to default dataset. See [default\\_dataset](#).

### Usage

```
add_rows(..., nomatch_columns = c("add", "drop", "stop"))

## S3 method for class 'data.frame'
add_rows(..., nomatch_columns = c("add", "drop",
  "stop"))

x %add_rows% y

.add_rows(..., nomatch_columns = c("add", "drop", "stop"))
```

### Arguments

...	data.frame/matrix/table for binding
nomatch_columns	action if there are non-matching columns between data.frames. Possible values are "add", "drop", "stop". "add" will combine all columns, "drop" will leave only common columns, "stop" will raise an error.
x	data.frame/matrix/table for binding
y	data.frame/matrix/table for binding

**Value**

See [rbind](#), [cro](#), [cro\\_fun](#), [fre](#), [tables](#)

**Examples**

```
a = data.frame(x = 1:5, y = 6:10)
b = data.frame(y = 6:10, z = 11:15)

add_rows(a, b) # x, y, z
a %add_rows% b # the same result

add_rows(a, b, nomatch_columns = "drop") # y

# simple tables
data(mtcars)
# apply labels
mtcars = apply_labels(mtcars,
  mpg = "Miles/(US) gallon",
  cyl = "Number of cylinders",
  disp = "Displacement (cu.in.)",
  hp = "Gross horsepower",
  drat = "Rear axle ratio",
  wt = "Weight (lb/1000)",
  qsec = "1/4 mile time",
  vs = "V/S",
  vs = c("V-engine" = 0, "Straight engine" = 1),
  am = "Transmission (0 = automatic, 1 = manual)",
  am = c(automatic = 0, manual = 1),
  gear = "Number of forward gears",
  carb = "Number of carburetors"
)

tbl_mean = calculate(mtcars, cro_mean(cyl, am))
tbl_percent = calculate(mtcars, cro_cpct(cyl, am))

tbl_mean %add_rows% tbl_percent
```

---

apply\_labels

*Set variable labels/value labels on variables in the data.frame*

---

**Description**

apply\_labels tries automatically detect what is variable label and what are value labels. .apply\_labels is version for working with default dataset. See also [var\\_lab](#) and [val\\_lab](#).

**Usage**

```
apply_labels(data, ...)

.apply_labels(...)
```

**Arguments**

data	data.frame/list
...	named arguments. Name of argument is a variable name in data. Argument values are variable or value labels. Unnamed characters of length 1 are considered as variable labels and named vectors are considered as value labels.

**Value**

data with applied labels

**Examples**

```
data(mtcars)
mtcars = apply_labels(mtcars,
                      vs = "Engine",
                      vs = num_lab("
                                0 V-engine
                                1 Straight engine
                                "),
                      am = "Transmission",
                      am = num_lab("
                                0 Automatic
                                1 Manual
                                ")
)

# 'table' from base R
table(mtcars$vs, mtcars$am)

# more sophisticated crosstable
calculate(mtcars, cro(vs, am))
```

---

as.category

---

*Convert dichotomy data.frame/matrix to data.frame with category encoding*


---

**Description**

Convert dichotomy data.frame/matrix to data.frame with category encoding

**Usage**

```
as.category(x, prefix = NULL, counted_value = 1, compress = FALSE)
```

```
is.category(x)
```

**Arguments**

x	Dichotomy data.frame/matrix (usually with 0,1 coding).
prefix	If is not NULL then column names will be added in the form prefix+column number.
counted_value	Vector. Values that will be considered as indicator of category presence. By default it equals to 1.
compress	Logical. Should we drop columns with all NA? FALSE by default. TRUE significantly decreases performance of the function.

**Value**

data.frame of class category with numeric values that correspond to column numbers of counted values. Column names of x or variable labels are added as value labels.

**See Also**

[as.dichotomy](#) for reverse conversion, [mrset](#), [mdset](#) for usage multiple-response variables with tables.

**Examples**

```
set.seed(123)

# Let's imagine it's matrix of consumed products
dichotomy_matrix = matrix(sample(0:1,40,replace = TRUE,prob=c(.6,.4)),nrow=10)
colnames(dichotomy_matrix) = c("Milk","Sugar","Tea","Coffee")

as.category(dichotomy_matrix, compress = TRUE) # compressed version
category_encoding = as.category(dichotomy_matrix)

# should be TRUE
identical(val_lab(category_encoding), c(Milk = 1L, Sugar = 2L, Tea = 3L, Coffee = 4L))
all(as.dichotomy(category_encoding, use_na = FALSE) == dichotomy_matrix)

# with prefix
as.category(dichotomy_matrix, prefix = "products_")

# data.frame with variable labels
dichotomy_dataframe = as.data.frame(dichotomy_matrix)
colnames(dichotomy_dataframe) = paste0("product_", 1:4)
var_lab(dichotomy_dataframe[[1]]) = "Milk"
var_lab(dichotomy_dataframe[[2]]) = "Sugar"
var_lab(dichotomy_dataframe[[3]]) = "Tea"
var_lab(dichotomy_dataframe[[4]]) = "Coffee"
```

```
as.category(dichotomy_dataframe, prefix = "products_")
```

---

as.datatable\_widget *Create an HTML table widget for usage with Shiny*

---

## Description

This is method for rendering results of [tables/fre/cro](#) in Shiny. DT package should be installed for this feature (`install.packages('DT')`). For detailed description of function and its arguments see [datatable](#).

## Usage

```
as.datatable_widget(data, ...)  
  
## S3 method for class 'etable'  
as.datatable_widget(data, repeat_row_labels = FALSE,  
  show_row_numbers = FALSE, digits = get_expss_digits(), ...)  
  
## S3 method for class 'with_caption'  
as.datatable_widget(data,  
  repeat_row_labels = FALSE, show_row_numbers = FALSE,  
  digits = get_expss_digits(), ...)
```

## Arguments

data	a data object (result of <a href="#">tables/fre/cro</a> ).
...	further parameters for <a href="#">datatable</a>
repeat_row_labels	logical Should we repeat duplicated row labels in the every row? Default is FALSE.
show_row_numbers	logical Default is FALSE.
digits	integer By default, all numeric columns are rounded to one digit after decimal separator. Also you can set this argument by option 'expss.digits' - for example, <code>expss_digits(2)</code> . If it is NA than all numeric columns remain unrounded.

## Value

Object of class [datatable](#)

## See Also

[htmlTable](#) for knitting

**Examples**

```

## Not run:

data(mtcars)
mtcars = apply_labels(mtcars,
  mpg = "Miles/(US) gallon",
  cyl = "Number of cylinders",
  disp = "Displacement (cu.in.)",
  hp = "Gross horsepower",
  drat = "Rear axle ratio",
  wt = "Weight (1000 lbs)",
  qsec = "1/4 mile time",
  vs = "Engine",
  vs = c("V-engine" = 0,
        "Straight engine" = 1),
  am = "Transmission",
  am = c("Automatic" = 0,
        "Manual"=1),
  gear = "Number of forward gears",
  carb = "Number of carburetors"
)

mtcars_table = mtcars %>%
  tab_cols(total(), am %nest% vs) %>%
  tab_cells(mpg, hp) %>%
  tab_stat_mean() %>%
  tab_cells(cyl) %>%
  tab_stat_cpct() %>%
  tab_pivot() %>%
  set_caption("Table 1. Some variables from mtcars dataset.")

library(shiny)
shinyApp(
  ui = fluidPage(fluidRow(column(12, DT::dataTableOutput('tbl')))),
  server = function(input, output) {
    output$tbl = DT::renderDataTable(
      as.datatable_widget(mtcars_table)
    )
  }
)

## End(Not run)

```

**Description**

This function converts variable/multiple response variable (vector/matrix/data.frame) with category encoding into data.frame/matrix with dichotomy encoding (0/1) suited for most statistical analysis, e. g. clustering, factor analysis, linear regression and so on.

- `as.dichotomy` returns data.frame of class 'dichotomy' with 0, 1 and possibly NA.
- `dummy` returns matrix of class 'dichotomy' with 0, 1 and possibly NA.
- `dummy1` drops last column in dichotomy matrix. It is useful in many cases because any column of such matrix usually is linear combinations of other columns.

**Usage**

```
as.dichotomy(x, prefix = "v", keep_unused = FALSE, use_na = TRUE,
  keep_values = NULL, keep_labels = NULL, drop_values = NULL,
  drop_labels = NULL, presence = 1, absence = 0)
```

```
dummy(x, keep_unused = FALSE, use_na = TRUE, keep_values = NULL,
  keep_labels = NULL, drop_values = NULL, drop_labels = NULL,
  presence = 1, absence = 0)
```

```
dummy1(x, keep_unused = FALSE, use_na = TRUE, keep_values = NULL,
  keep_labels = NULL, drop_values = NULL, drop_labels = NULL,
  presence = 1, absence = 0)
```

```
is.dichotomy(x)
```

**Arguments**

<code>x</code>	vector/factor/matrix/data.frame.
<code>prefix</code>	character. By default "v".
<code>keep_unused</code>	Logical. Should we create columns for unused value labels/factor levels? FALSE by default.
<code>use_na</code>	Logical. Should we use NA for rows with all NA or use 0's instead. TRUE by default.
<code>keep_values</code>	Numeric/character. Values that should be kept. By default all values will be kept.
<code>keep_labels</code>	Numeric/character. Labels/levels that should be kept. By default all labels/levels will be kept.
<code>drop_values</code>	Numeric/character. Values that should be dropped. By default all values will be kept. Ignored if <code>keep_values/keep_labels</code> are provided.
<code>drop_labels</code>	Numeric/character. Labels/levels that should be dropped. By default all labels/levels will be kept. Ignored if <code>keep_values/keep_labels</code> are provided.
<code>presence</code>	numeric value which will code presence of the level. By default it is 1. Note that all tables functions need that presence and absence will be 1 and 0.
<code>absence</code>	numeric value which will code absence of the level. By default it is 0. Note that all tables functions need that presence and absence will be 1 and 0.

**Value**

as.dichotomy returns data.frame of class dichotomy with 0,1. Columns of this data.frame have variable labels according to value labels of original data. If label doesn't exist for particular value then this value will be used as variable label. dummy returns matrix of class dichotomy. Column names of this matrix are value labels of original data.

**See Also**

[as.category](#) for reverse conversion, [mrset](#), [mdset](#) for usage multiple-response variables with tables.

**Examples**

```
# toy example
# brands - multiple response question
# Which brands do you use during last three months?
set.seed(123)
brands = as.sheet(t(replicate(20, sample(c(1:5, NA), 4, replace = FALSE))))
# score - evaluation of tested product
score = sample(-1:1, 20, replace = TRUE)
var_lab(brands) = "Used brands"
val_lab(brands) = autonum("
                                Brand A
                                Brand B
                                Brand C
                                Brand D
                                Brand E
                                ")

var_lab(score) = "Evaluation of tested brand"
val_lab(score) = make_labels("
                                -1 Dislike it
                                0 So-so
                                1 Like it
                                ")

cro_cpct(as.dichotomy(brands), score)
# the same as
cro_cpct(mrset(brands), score)

# customer segmentation by used brands
kmeans(dummy(brands), 3)

# model of influence of used brands on evaluation of tested product
summary(lm(score ~ dummy(brands)))

# prefixed data.frame
as.dichotomy(brands, prefix = "brand_")
```

---

as.etable	<i>Convert data.frame/matrix to object of class 'etable'</i>
-----------	--

---

**Description**

If `x` is `data.frame` then `as.etable` just adds `etable` to class attribute of `x`. If `x` is matrix then it will be converted to `data.frame`.

**Usage**

```
as.etable(x, rownames_as_row_labels = NULL)
```

```
is.etable(x)
```

**Arguments**

`x` data.frame/matrix  
`rownames_as_row_labels`

logical. If it is TRUE than rownames of `x` will be added to result as first column with name `row_labels`. By default row names will be added if they are not NULL and are not sequential numerics.

**Value**

object of class `etable`

**Examples**

```
data(mtcars)
etable_mtcars = as.etable(mtcars)
is.etable(etable_mtcars) #TRUE

etable_mtcars #another 'print' method is used

cor(mtcars) %>% as.etable()
```

---

as.labelled	<i>Recode vector into numeric vector with value labels</i>
-------------	--

---

**Description**

Recode vector into numeric vector with value labels

**Usage**

```
as.labelled(x, label = NULL)
```

```
is.labelled(x)
```

**Arguments**

x	numeric vector/character vector/factor
label	optional variable label

**Value**

numeric vector with value labels

**Examples**

```
character_vector = c("one", "two", "two", "three")
as.labelled(character_vector, label = "Numbers")
```

---

compare_proportions	<i>Calculate significance (p-values) of differences between proportions/means</i>
---------------------	---

---

**Description**

compare\_proportions calculates p-values (via z-test) for comparison between each proportion in the prop1 and prop2. Results are calculated with the same formula as in [prop.test](#) without continuity correction. compare\_means calculates p-values (via t-test) for comparison between each mean in the mean1 and mean2. Results are calculated on the aggregated statistics (means, std. devs, N) with the same formula as in [t.test](#). These functions mainly intended for usage inside [significance\\_cpct](#) and [significance\\_means](#).

**Usage**

```
compare_proportions(prop1, prop2, base1, base2, common_base = 0)

compare_means(mean1, mean2, sd1, sd2, base1, base2, common_base = 0,
  var_equal = FALSE)
```

**Arguments**

prop1	a numeric vector of proportions in the group 1. Values should be between 0 and 1
prop2	a numeric vector of proportions in the group 2. Values should be between 0 and 1
base1	a numeric vector for compare_means and single number for compare_proportions. Number of valid cases for each mean in the first group for compare_means and number of cases for compare_proportions.
base2	a numeric vector for compare_means and single number for compare_proportions. Number of valid cases for each mean in the second group for compare_means and number of cases for compare_proportions.

common_base	numeric. Number of cases that belong to both values in the first and the second argument. It can occur in the case of overlapping samples. Calculations are made according to algorithm in IBM SPSS Statistics Algorithms v20, p. 263. Note that with these adjustments t-tests between means are made with equal variance assumed (as with <code>var_equal = TRUE</code> ).
mean1	a numeric vector of the means in the first group.
mean2	a numeric vector of the means in the second group.
sd1	a numeric vector of the standard deviations in the first group. Values should be non-negative.
sd2	a numeric vector of the standard deviations in the second group. Values should be non-negative.
var_equal	a logical variable indicating whether to treat the variances in the groups as being equal. For details see <a href="#">t.test</a> .

**Value**

numeric vector with p-values

**See Also**

[significance\\_cpct](#), [significance\\_means](#), [prop.test](#), [t.test](#)

**Examples**

```
# proportions
data(mtcars)
counts = table(mtcars$am, mtcars$vs)
props = prop.table(counts)
compare_proportions(props[,1], props[,2],
                    colSums(counts)[1], colSums(counts)[2])

# means
t.test(mpg ~ am, data = mtcars)$p.value
# the same result
calculate(mtcars,
          compare_means(
            mean(mpg[am==0]), mean(mpg[am==1]),
            sd(mpg[am==0]), sd(mpg[am==1]),
            length(mpg[am==0]), length(mpg[am==1])
          ))
```

## Description

- `compute` evaluates expression `expr` in the context of `data.frame` `data` and return original data possibly modified. It works similar to `within` in base R but try to return new variables in order of their occurrence in the expression and make available full-featured `%to%` and `.N` in the expressions. See `vars`.
- `calculate` evaluates expression `expr` in the context of `data.frame` `data` and return value of the evaluated expression. It works similar to `with` in base R but make available full-featured `%to%` and `.N` in the expressions. See `vars`. Function `use_labels` is shortcut for `calculate` with argument `use_labels` set to `TRUE`. When `use_labels` is `TRUE` there is a special shortcut for entire `data.frame` - `..data`.
- `do_if` modifies only rows for which `cond` equals to `TRUE`. Other rows remain unchanged. Newly created variables also will have values only in rows for which `cond` have `TRUE`. There will be `NA`'s in other rows. This function tries to mimic SPSS "DO IF(). ... END IF." statement.

There is a special constant `.N` which equals to number of cases in `data` for usage in expression inside `compute/calculate`. Inside `do_if` `.N` gives number of rows which will be affected by expressions. For parametrization (variable substitution) see `..` or examples. Sometimes it is useful to create new empty variable inside `compute`. You can use `.new_var` function for this task. This function creates variable of length `.N` filled with `NA`. See examples. `modify` is an alias for `compute`, `modify_if` is an alias for `do_if` and `calc` is an alias for `calculate`.

## Usage

```
compute(data, ...)

modify(data, ...)

do_if(data, cond, ...)

modify_if(data, cond, ...)

calculate(data, expr, use_labels = FALSE)

use_labels(data, expr)

calc(data, expr, use_labels = FALSE)

data %calc% expr

data %use_labels% expr

data %calculate% expr
```

## Arguments

`data` `data.frame`/list of `data.frames`. If `data` is list of `data.frames` then expression `expr` will be evaluated inside each `data.frame` separately.

...	expressions that should be evaluated in the context of data.frame data. It can be arbitrary code in curly brackets or assignments. See examples.
cond	logical vector or expression. Expression will be evaluated in the context of the data.
expr	expression that should be evaluated in the context of data.frame data
use_labels	logical. Experimental feature. If it equals to TRUE then we will try to replace variable names with labels. So many base R functions which show variable names will show labels.

### Value

compute and do\_if functions return modified data.frame/list of modified data.frames, calculate returns value of the evaluated expression/list of values.

### Examples

```
dfs = data.frame(
  test = 1:5,
  a = rep(10, 5),
  b_1 = rep(11, 5),
  b_2 = rep(12, 5),
  b_3 = rep(13, 5),
  b_4 = rep(14, 5),
  b_5 = rep(15, 5)
)

# compute sum of b* variables and attach it to 'dfs'
compute(dfs, {
  b_total = sum_row(b_1 %to% b_5)
  var_lab(b_total) = "Sum of b"
  random_numbers = runif(.N) # .N usage
})

# calculate sum of b* variables and return it
calculate(dfs, sum_row(b_1 %to% b_5))

# set values to existing/new variables
compute(dfs, {
  (b_1 %to% b_5) %into% text_expand('new_b{1:5}')
})

# .new_var usage
compute(dfs, {
  new_var = .new_var()
  new_var[1] = 1 # this is not possible without preliminary variable creation
})

# conditional modification
do_if(dfs, test %in% 2:4, {
```

```

    a = a + 1
    b_total = sum_row(b_1 %to% b_5)
    random_numbers = runif(.N) # .N usage
  })

# variable substitution
name1 = "a"
name2 = "new_var"

compute(dfs, {
  ..$name2 = ..$name1*2
})

compute(dfs, {
  for(name1 in paste0("b_", 1:5)){
    name2 = paste0("new_", name1)
    ..$name2 = ..$name1*2
  }
  rm(name1, name2) # we don't need this variables as columns in 'dfs'
})

# square brackets notation
compute(dfs, {
  ..[(name2)] = ..[(name1)]*2
})

compute(dfs, {
  for(name1 in paste0("b_", 1:5)){
    ..[paste0("new_", name1)] = ..$name1*2
  }
  rm(name1) # we don't need this variable as column in 'dfs'
})

# '..$' doesn't work for case below so we need to use square brackets form
name1 = paste0("b_", 1:5)
name2 = paste0("new_", name1)
compute(dfs, {
  for(i in 1:5){
    ..[name2[i]] = ..[name1[i]]*3
  }
  rm(i) # we don't need this variable as column in 'dfs'
})

# 'use_labels' examples. Utilization of labels in base R.
data(mtcars)
mtcars = apply_labels(mtcars,
  mpg = "Miles/(US) gallon",
  cyl = "Number of cylinders",
  disp = "Displacement (cu.in.)",
  hp = "Gross horsepower",
  drat = "Rear axle ratio",
  wt = "Weight (lb/1000)",

```

```

        qsec = "1/4 mile time",
        vs = "Engine",
        vs = c("V-engine" = 0,
              "Straight engine" = 1),
        am = "Transmission",
        am = c("Automatic" = 0,
              "Manual"=1),
        gear = "Number of forward gears",
        carb = "Number of carburetors"
    )

    use_labels(mtcars, table(am, vs))

    ## Not run:
    use_labels(mtcars, plot(mpg, hp))

    ## End(Not run)

    mtcars %>%
      use_labels(lm(mpg ~ disp + hp + wt)) %>%
      summary()

```

---

count\_if

*Count/sum/average/other functions on values that meet a criterion*


---

## Description

These functions calculate count/sum/average/etc on values that meet a criterion that you specify. `apply_if_*` apply custom functions. There are different flavors of these functions: `*_if` work on entire dataset/matrix/vector, `*_row_if` works on each row and `*_col_if` works on each column.

## Usage

```

count_if(criterion, ...)

count_row_if(criterion, ...)

count_col_if(criterion, ...)

x %row_in% criterion

x %has% criterion

x %col_in% criterion

sum_if(criterion, ..., data = NULL)

sum_row_if(criterion, ..., data = NULL)

```

```
sum_col_if(criterion, ..., data = NULL)
mean_if(criterion, ..., data = NULL)
mean_row_if(criterion, ..., data = NULL)
mean_col_if(criterion, ..., data = NULL)
sd_if(criterion, ..., data = NULL)
sd_row_if(criterion, ..., data = NULL)
sd_col_if(criterion, ..., data = NULL)
median_if(criterion, ..., data = NULL)
median_row_if(criterion, ..., data = NULL)
median_col_if(criterion, ..., data = NULL)
max_if(criterion, ..., data = NULL)
max_row_if(criterion, ..., data = NULL)
max_col_if(criterion, ..., data = NULL)
min_if(criterion, ..., data = NULL)
min_row_if(criterion, ..., data = NULL)
min_col_if(criterion, ..., data = NULL)
apply_row_if(fun, criterion, ..., data = NULL)
apply_col_if(fun, criterion, ..., data = NULL)
```

### Arguments

criterion	Vector with counted values, logical vector/matrix or function. See details and examples.
...	Data on which criterion will be applied. Vector, matrix, data.frame, list. Shorter arguments will be recycled.
x	Data on which criterion will be applied. Vector, matrix, data.frame, list. Shorter arguments will be recycled.
data	Data on which function will be applied. Doesn't applicable to count_*_if functions. If omitted then function will be applied on the ... argument.
fun	Custom function that will be applied based on criterion.

## Details

Possible type for criterion argument:

- vector/single value All values in . . . which equal to elements of vector in criteria will be used as function fun argument.
- function Values for which function gives TRUE will be used as function fun argument. There are some special functions for convenience (e. g. `gt(5)` is equivalent "`>5`" in spreadsheet) - see [criteria](#).
- logical vector/matrix/data.frame Values for which element of criterion equals to TRUE will be used as function fun argument. Logical vector will be recycled across all columns of . . . data. If criteria is logical matrix/data.frame then column from this matrix/data.frame will be used for corresponding column/element of . . . data. Note that this kind of criterion doesn't use . . . so . . . can be used instead of data argument.

`count*` and `%in*` never returns NA's. Other functions remove NA's before calculations (as `na.rm = TRUE` in base R functions).

Function criterion should return logical vector of same size and shape as its argument. This function will be applied to each column of supplied data and TRUE results will be used. There is asymmetrical behavior in `*_row_if` and `*_col_if` for function criterion: in both cases function criterion will be applied columnwise.

## Value

`*_if` return single value (vector of length 1). `*_row_if` returns vector for each row of supplied arguments. `*_col_if` returns vector for each column of supplied arguments. `%row_in%/col_in%` return logical vector - indicator of presence of criterion in each row/column. `%has%` is an alias for `%row_in%`.

## Examples

```
set.seed(123)
dfs = as.data.frame(
  matrix(sample(c(1:10,NA), 30, replace = TRUE), 10)
)

result = modify(dfs, {
  # count 8
  exact = count_row_if(8, V1, V2, V3)
  # count values greater than 8
  greater = count_row_if(gt(8), V1, V2, V3)
  # count integer values between 5 and 8, e. g. 5, 6, 7, 8
  integer_range = count_row_if(5:8, V1, V2, V3)
  # count values between 5 and 8
  range = count_row_if(5 %thru% 8, V1, V2, V3)
  # count NA
  na = count_row_if(is.na, V1, V2, V3)
  # count not-NA
  not_na = count_row_if(not_na, V1, V2, V3)
  # are there any 5 in each row?
  has_five = cbind(V1, V2, V3) %row_in% 5
})
```

```

    })
  result

  mean_row_if(6, dfs$V1, data = dfs)
  median_row_if(gt(2), dfs$V1, dfs$V2, dfs$V3)
  sd_row_if(5 %thru% 8, dfs$V1, dfs$V2, dfs$V3)

  if_na(dfs) = 5 # replace NA

  # custom apply
  apply_col_if(prod, gt(2), dfs$V1, data = dfs) # product of all elements by columns
  apply_row_if(prod, gt(2), dfs$V1, data = dfs) # product of all elements by rows

  # Examples borrowed from Microsoft Excel help for COUNTIF
  df1 = data.frame(
    a = c("apples", "oranges", "peaches", "apples"),
    b = c(32, 54, 75, 86)
  )

  count_if("apples", df1$a) # 2

  count_if("apples", df1) # 2

  with(df1, count_if("apples", a, b)) # 2

  count_if(gt(55), df1$b) # greater than 55 = 2

  count_if(ne(75), df1$b) # not equal 75 = 3

  count_if(ge(32), df1$b) # greater than or equal 32 = 4

  count_if(gt(32) & lt(86), df1$b) # 2

  # count only integer values between 33 and 85
  count_if(33:85, df1$b) # 2

  # values with letters
  count_if(regex("^[A-z]+$"), df1) # 4

  # values that started on 'a'
  count_if(regex("^a"), df1) # 2

  # count_row_if
  count_row_if(regex("^a"), df1) # c(1,0,0,1)

  df1 %row_in% 'apples' # c(TRUE,FALSE,FALSE,TRUE)

  # Some of Microsoft Excel examples for SUMIF/AVERAGEIF/etc
  dfs = read.csv(
    text = "
    property_value,commission,data
    100000,7000,250000
    200000,14000,

```

```

    300000,21000,
    400000,28000,"
  )

# Sum of commission for property value greater than 160000
with(dfs, sum_if(gt(160000), property_value, data = commission)) # 63000

# Sum of property value greater than 160000
with(dfs, sum_if(gt(160000), property_value)) # 900000

# Sum of commission for property value equals to 300000
with(dfs, sum_if(300000, property_value, data = commission)) # 21000

# Sum of commission for property value greater than first value of data
with(dfs, sum_if(gt(data[1]), property_value, data = commission)) # 49000

dfs = data.frame(
  category = c("Vegetables", "Vegetables", "Fruits", "", "Vegetables", "Fruits"),
  food = c("Tomatoes", "Celery", "Oranges", "Butter", "Carrots", "Apples"),
  sales = c(2300, 5500, 800, 400, 4200, 1200),
  stringsAsFactors = FALSE
)

# Sum of sales for Fruits
with(dfs, sum_if("Fruits", category, data = sales)) # 2000

# Sum of sales for Vegetables
with(dfs, sum_if("Vegetables", category, data = sales)) # 12000

# Sum of sales for food which is ending on 'es'
with(dfs, sum_if(perl("es$"), food, data = sales)) # 4300

# Sum of sales for empty category
with(dfs, sum_if("", category, data = sales)) # 400

dfs = read.csv(
  text = "
  property_value,commission,data
  100000,7000,250000
  200000,14000,
  300000,21000,
  400000,28000,"
)

# Commission average for commission less than 23000
with(dfs, mean_if(lt(23000), commission)) # 14000

# Property value average for property value less than 95000
with(dfs, mean_if(lt(95000), property_value)) # NaN

```

```
# Commission average for property value greater than 250000
with(dfs, mean_if(gt(250000), property_value, data = commission)) # 24500

dfs = data.frame(
  region = c("East", "West", "North", "South (New Office)", "MidWest"),
  profits = c(45678, 23789, -4789, 0, 9678),
  stringsAsFactors = FALSE
)

# Mean profits for 'west' regions
with(dfs, mean_if(fixed("West"), region, data = profits)) # 16733.5

# Mean profits for regions wich doesn't contain New Office
with(dfs, mean_if(!fixed("(New Office)"), region, data = profits)) # 18589

dfs = read.csv(
  text = '
grade,weight
89,1
93,2
96,2
85,3
91,1
88,1'
  ,stringsAsFactors = FALSE
)

# Minimum grade for weight equals to 1
with(dfs, min_if(1, weight, data = grade)) # 88

# Maximum grade for weight equals to 1
with(dfs, max_if(1, weight, data = grade)) #91

# Example with offset
dfs = read.csv(
  text = '
weight,grade
10,b
11,a
100,a
111,b
1,a
1,a'
  ,stringsAsFactors = FALSE
)

with(dfs, min_if("a", grade[2:5], data = weight[1:4])) # 10
```

---

 criteria

*Criteria functions*


---

## Description

Produce criteria which could be used in the different situations - see `'recode'`, `'na_if'`, `'count_if'`, `'match_row'`, `'%i%'` and etc. For example, `'greater(5)'` returns function which tests whether its argument greater than five. `'fixed("apple")'` returns function which tests whether its argument contains "apple". For criteria logical operations (`|`, `&`, `!`, `xor`) are defined, e. g. you can write something like: `'greater(5) | equals(1)'`. List of functions:

- comparison criteria - `'equals'`, `'greater'` and etc. return functions which compare its argument against value.
- `'thru'` checks whether a value is inside interval. `'thru(0,1)'` is equivalent to `'x>=0 & x<=1'`
- `'%thru%'` is infix version of `'thru'`, e. g. `'0 %thru% 1'`
- `'is_max'` and `'is_min'` return TRUE where vector value is equals to maximum or minimum.
- `'contains'` searches for the pattern in the strings. By default, it works with fixed patterns rather than regular expressions. For details about its arguments see [grepl](#)
- `'like'` searches for the Excel-style pattern in the strings. You can use wildcards: `'*'` means any number of symbols, `'?'` means single symbol. Case insensitive.
- `'fixed'` alias for `contains`.
- `'perl'` such as `'contains'` but the pattern is perl-compatible regular expression (`'perl = TRUE'`). For details see [grepl](#)
- `'regex'` use POSIX 1003.2 extended regular expressions (`'fixed = FALSE'`). For details see [grepl](#)
- `'has_label'` searches values which have supplied label(-s). We can used criteria as an argument for `'has_label'`.
- `'to'` returns function which gives TRUE for all elements of vector before the first occurrence of `'x'` and for `'x'`.
- `'from'` returns function which gives TRUE for all elements of vector after the first occurrence of `'x'` and for `'x'`.
- `'not_na'` returns TRUE for all non-NA vector elements.
- `'other'` returns TRUE for all vector elements. It is intended for usage with `'recode'`.
- `'items'` returns TRUE for the vector elements with the given sequential numbers.
- `'and'`, `'or'`, `'not'` spreadsheet-style boolean functions.

Shortcuts for comparison criteria:

- `'equals'` - `'eq'`
- `'not_equals'` - `'neq'`, `'ne'`

- 'greater' - 'gt'
- 'greater\_or\_equal' - 'gte', 'ge'
- 'less' - 'lt'
- 'less\_or\_equal' - 'lte', 'le'

**Usage**

as.criterion(crit)

equals(x)

not\_equals(x)

less(x)

less\_or\_equal(x)

greater(x)

greater\_or\_equal(x)

thru(lower, upper)

lower %thru% upper

is\_max(x)

is\_min(x)

contains(pattern, ignore.case = FALSE, perl = FALSE, fixed = TRUE,  
useBytes = FALSE)

like(pattern)

fixed(pattern, ignore.case = FALSE, perl = FALSE, fixed = TRUE,  
useBytes = FALSE)

perl(pattern, ignore.case = FALSE, perl = TRUE, fixed = FALSE,  
useBytes = FALSE)

regex(pattern, ignore.case = FALSE, perl = FALSE, fixed = FALSE,  
useBytes = FALSE)

has\_label(x)

from(x)

to(x)

```

items(...)
not_na(x)
other(x)
and(...)
or(...)
not()

```

### Arguments

crit	vector of values/function which returns logical or vector. It will be converted to function of class criterion.
x	vector
lower	vector/single value - lower bound of interval
upper	vector/single value - upper bound of interval
pattern	character string containing a regular expression (or character string for 'fixed') to be matched in the given character vector. Coerced by as.character to a character string if possible.
ignore.case	logical see <a href="#">grepl</a>
perl	logical see <a href="#">grepl</a>
fixed	logical see <a href="#">grepl</a>
useBytes	logical see <a href="#">grepl</a>
...	numeric indexes of desired items for items, logical vectors or criteria for boolean functions.

### Value

function of class 'criterion' which tests its argument against condition and return logical value

### See Also

[recode](#), [count\\_if](#), [match\\_row](#), [na\\_if](#), [%i%](#)

### Examples

```

# operations on vector, '%d%' means 'diff'
1:6 %d% greater(4) # 1:4
1:6 %d% (1 | greater(4)) # 2:4
# '%i%' means 'intersect'
1:6 %i% (is_min() | is_max()) # 1, 6
# with Excel-style boolean operators
1:6 %i% or(is_min(), is_max()) # 1, 6

```

```

letters %i% (contains("a") | contains("z")) # a, z

letters %i% perl("a|z") # a, z

letters %i% from("w") # w, x, y, z

letters %i% to("c") # a, b, c

letters %i% (from("b") & to("e")) # b, d, e

c(1, 2, NA, 3) %i% not_na() # c(1, 2, 3)

# examples with count_if
df1 = data.frame(
  a=c("apples", "oranges", "peaches", "apples"),
  b = c(32, 54, 75, 86)
)

count_if(greater(55), df1$b) # greater than 55 = 2

count_if(not_equals(75), df1$b) # not equals 75 = 3

count_if(greater(32) & less(86), df1$b) # greater than 32 and less than 86 = 2
count_if(and(greater(32), less(86)), df1$b) # the same result

# infix version
count_if(35 %thru% 80, df1$b) # greater than or equals to 35 and less than or equals to 80 = 2

# values that started on 'a'
count_if(like("a*"), df1) # 2

# the same with Perl-style regular expression
count_if(perl("^a"), df1) # 2

# count_row_if
count_row_if(perl("^a"), df1) # c(1,0,0,1)

# examples with 'n_intersect' and 'n_diff'
data(iris)
iris %>% n_intersect(to("Petal.Width")) # all columns up to 'Species'

# 'Sepal.Length', 'Sepal.Width' will be left
iris %>% n_diff(from("Petal.Length"))

# except first column
iris %n_d% items(1)

# 'recode' examples
qvar = c(1:20, 97, NA, NA)
recode(qvar, 1 %thru% 5 ~ 1, 6 %thru% 10 ~ 2, 11 %thru% hi ~ 3, other ~ 0)
# the same result
recode(qvar, 1 %thru% 5 ~ 1, 6 %thru% 10 ~ 2, greater_or_equal(11) ~ 3, other ~ 0)

```

---

cro	<i>Cross tabulation with support of labels, weights and multiple response variables.</i>
-----	--

---

### Description

- `cro`, `cro_cases` build a contingency table of the counts.
- `cro_cpct`, `cro_cpct_responses` build a contingency table of the column percent. These functions give different results only for multiple response variables. For `cro_cpct` base of percent is number of valid cases. Case is considered as valid if it has at least one non-NA value. So for multiple response variables sum of percent may be greater than 100. For `cro_cpct_responses` base of percent is number of valid responses. Multiple response variables can have several responses for single case. Sum of percent of `cro_cpct_responses` always equals to 100%.
- `cro_rpct` build a contingency table of the row percent. Base for percent is number of valid cases.
- `cro_tpct` build a contingency table of the table percent. Base for percent is number of valid cases.
- `calc_cro_*` are the same as above but evaluate their arguments in the context of the first argument data.
- `total` auxiliary function - creates variables with 1 for valid case of its argument `x` and NA in opposite case.

You can combine tables with [add\\_rows](#) and [merge.etable](#). For sorting table see [tab\\_sort\\_asc](#). To provide multiple-response variables as arguments use [mrset](#) for multiples with category encoding and [mdset](#) for multiples with dichotomy (dummy) encoding. To compute statistics with nested variables/banners use [nest](#). For more sophisticated interface with modern piping via [magrittr](#) see [tables](#).

### Usage

```
cro(cell_vars, col_vars = total(), row_vars = NULL, weight = NULL,
    subgroup = NULL, total_label = NULL, total_statistic = "u_cases",
    total_row_position = c("below", "above", "none"))
```

```
cro_cases(cell_vars, col_vars = total(), row_vars = NULL,
           weight = NULL, subgroup = NULL, total_label = NULL,
           total_statistic = "u_cases", total_row_position = c("below", "above",
           "none"))
```

```
cro_cpct(cell_vars, col_vars = total(), row_vars = NULL,
          weight = NULL, subgroup = NULL, total_label = NULL,
          total_statistic = "u_cases", total_row_position = c("below", "above",
```

```
"none"))

cro_rpct(cell_vars, col_vars = total(), row_vars = NULL,
  weight = NULL, subgroup = NULL, total_label = NULL,
  total_statistic = "u_cases", total_row_position = c("below", "above",
  "none"))

cro_tpct(cell_vars, col_vars = total(), row_vars = NULL,
  weight = NULL, subgroup = NULL, total_label = NULL,
  total_statistic = "u_cases", total_row_position = c("below", "above",
  "none"))

cro_cpct_responses(cell_vars, col_vars = total(), row_vars = NULL,
  weight = NULL, subgroup = NULL, total_label = NULL,
  total_statistic = "u_responses", total_row_position = c("below",
  "above", "none"))

calc_cro(data, cell_vars, col_vars = total(), row_vars = NULL,
  weight = NULL, subgroup = NULL, total_label = NULL,
  total_statistic = "u_cases", total_row_position = c("below", "above",
  "none"))

calc_cro_cases(data, cell_vars, col_vars = total(), row_vars = NULL,
  weight = NULL, subgroup = NULL, total_label = NULL,
  total_statistic = "u_cases", total_row_position = c("below", "above",
  "none"))

calc_cro_cpct(data, cell_vars, col_vars = total(), row_vars = NULL,
  weight = NULL, subgroup = NULL, total_label = NULL,
  total_statistic = "u_cases", total_row_position = c("below", "above",
  "none"))

calc_cro_rpct(data, cell_vars, col_vars = total(), row_vars = NULL,
  weight = NULL, subgroup = NULL, total_label = NULL,
  total_statistic = "u_cases", total_row_position = c("below", "above",
  "none"))

calc_cro_tpct(data, cell_vars, col_vars = total(), row_vars = NULL,
  weight = NULL, subgroup = NULL, total_label = NULL,
  total_statistic = "u_cases", total_row_position = c("below", "above",
  "none"))

calc_cro_cpct_responses(data, cell_vars, col_vars = total(),
  row_vars = NULL, weight = NULL, subgroup = NULL,
  total_label = NULL, total_statistic = "u_responses",
  total_row_position = c("below", "above", "none"))

total(x = 1, label = "#Total")
```

**Arguments**

<code>cell_vars</code>	vector/data.frame/list. Variables on which percentage/cases will be computed. Use <a href="#">mrset/mdset</a> for multiple-response variables.
<code>col_vars</code>	vector/data.frame/list. Variables which breaks table by columns. Use <a href="#">mrset/mdset</a> for multiple-response variables.
<code>row_vars</code>	vector/data.frame/list. Variables which breaks table by rows. Use <a href="#">mrset/mdset</a> for multiple-response variables.
<code>weight</code>	numeric vector. Optional cases weights. Cases with NA's, negative and zero weights are removed before calculations.
<code>subgroup</code>	logical vector. You can specify subgroup on which table will be computed.
<code>total_label</code>	By default "#Total". You can provide several names - each name for each total statistics.
<code>total_statistic</code>	By default it is "u_cases" (unweighted cases). Possible values are "u_cases", "u_responses", "u_cpct", "u_rpct", "u_tpct", "w_cases", "w_responses", "w_cpct", "w_rpct", "w_tpct". "u_" means unweighted statistics and "w_" means weighted statistics.
<code>total_row_position</code>	Position of total row in the resulting table. Can be one of "below", "above", "none".
<code>data</code>	data.frame in which context all other arguments will be evaluated (for <code>calc_cro_*</code> ).
<code>x</code>	vector/data.frame of class 'category'/'dichotomy'.
<code>label</code>	character. Label for total variable.

**Value**

object of class 'etable'. Basically it's a data.frame but class is needed for custom methods.

**See Also**

[tables](#), [fre](#), [cro\\_fun](#).

**Examples**

```
data(mtcars)
mtcars = apply_labels(mtcars,
  mpg = "Miles/(US) gallon",
  cyl = "Number of cylinders",
  disp = "Displacement (cu.in.)",
  hp = "Gross horsepower",
  drat = "Rear axle ratio",
  wt = "Weight (1000 lbs)",
  qsec = "1/4 mile time",
  vs = "Engine",
  vs = c("V-engine" = 0,
        "Straight engine" = 1),
  am = "Transmission",
```

```

        am = c("Automatic" = 0,
              "Manual"=1),
        gear = "Number of forward gears",
        carb = "Number of carburetors"
    )

    calculate(mtcars, cro(am, vs))
    calc_cro(mtcars, am, vs) # the same result

# column percent with multiple banners
calculate(mtcars, cro_cpct(cyl, list(total(), vs, am)))
calc_cro_cpct(mtcars, cyl, list(total(), vs, am)) # the same result

# nested banner
calculate(mtcars, cro_cpct(cyl, list(total(), vs %nest% am)))

# stacked variables
calculate(mtcars, cro(list(cyl, carb), list(total(), vs %nest% am)))

# nested variables
calculate(mtcars, cro_cpct(am %nest% cyl, list(total(), vs)))

# row variables
calculate(mtcars, cro_cpct(cyl, list(total(), vs), row_vars = am))

# several totals above table
calculate(mtcars, cro_cpct(cyl,
                          list(total(), vs),
                          row_vars = am,
                          total_row_position = "above",
                          total_label = c("number of cases", "row %"),
                          total_statistic = c("u_cases", "u_rpct")
                          ))

# multiple-choice variable
# brands - multiple response question
# Which brands do you use during last three months?
set.seed(123)
brands = data.frame(t(replicate(20, sample(c(1:5, NA), 4, replace = FALSE))))
# score - evaluation of tested product
score = sample(-1:1, 20, replace = TRUE)
var_lab(brands) = "Used brands"
val_lab(brands) = make_labels("
    1 Brand A
    2 Brand B
    3 Brand C
    4 Brand D
    5 Brand E
    ")

var_lab(score) = "Evaluation of tested brand"
val_lab(score) = num_lab("
    -1 Dislike it

```

```

      0 So-so
      1 Like it
    ")

cro_cpct(mrset(brands), list(total(), score))
# responses
cro_cpct_responses(mrset(brands), list(total(), score))

```

---

cro\_fun

*Cross-tabulation with custom summary function.*


---

## Description

- `cro_mean`, `cro_sum`, `cro_median` calculate mean/sum/median by groups. NA's are always omitted.
- `cro_mean_sd_n` calculates mean, standard deviation and N simultaneously. Mainly intended for usage with [significance\\_means](#).
- `cro_pearson`, `cro_spearman` calculate correlation of first variable in each data.frame in `cell_vars` with other variables. NA's are removed pairwise.
- `cro_fun`, `cro_fun_df` return table with custom summary statistics defined by `fun` argument. NA's treatment depends on your fun behavior. To use weight you should have formal weight argument in fun and some logic for its processing inside. Several functions with weight support are provided - see [w\\_mean](#). `cro_fun` applies fun on each variable in `cell_vars` separately, `cro_fun_df` gives to fun each data.frame in `cell_vars` as a whole. So `cro_fun(iris[, -5], iris$Species, fun = mean)` gives the same result as `cro_fun_df(iris[, -5], iris$Species, fun = mean)`. For `cro_fun_df` names of `cell_vars` will converted to labels if they are available before the fun will be applied. Generally it is recommended that fun will always return object of the same form. Row names/vector names of fun result will appear in the row labels of the table and column names/names of list will appear in the column labels. If your fun returns data.frame/matrix/list with element named 'row\_labels' then this element will be used as row labels. And it will have precedence over rownames.
- `calc_cro_*` are the same as above but evaluate their arguments in the context of the first argument data.
- `combine_functions` is auxiliary function for combining several functions into one function for usage with `cro_fun/cro_fun_df`. Names of arguments will be used as statistic labels. By default, results of each function are combined with `c`. But you can provide your own method function with `method` argument. It will be applied as in the expression `do.call(method, list_of_functions_results)`. Particular useful method is `list`. When it used then statistic labels will appear in the column labels. See examples. Also you may be interested in `data.frame`, `rbind`, `cbind` methods.

## Usage

```

cro_fun(cell_vars, col_vars = total(), row_vars = total(label = ""),
        weight = NULL, subgroup = NULL, fun, ..., unsafe = FALSE)

```

```
cro_fun_df(cell_vars, col_vars = total(), row_vars = total(label = ""),
  weight = NULL, subgroup = NULL, fun, ..., unsafe = FALSE)

cro_mean(cell_vars, col_vars = total(), row_vars = total(label = ""),
  weight = NULL, subgroup = NULL)

cro_mean_sd_n(cell_vars, col_vars = total(), row_vars = total(label =
  ""), weight = NULL, subgroup = NULL, weighted_valid_n = FALSE,
  labels = NULL)

cro_sum(cell_vars, col_vars = total(), row_vars = total(label = ""),
  weight = NULL, subgroup = NULL)

cro_median(cell_vars, col_vars = total(), row_vars = total(label = ""),
  weight = NULL, subgroup = NULL)

cro_pearson(cell_vars, col_vars = total(), row_vars = total(label =
  ""), weight = NULL, subgroup = NULL)

cro_spearman(cell_vars, col_vars = total(), row_vars = total(label =
  ""), weight = NULL, subgroup = NULL)

calc_cro_fun(data, cell_vars, col_vars = total(),
  row_vars = total(label = ""), weight = NULL, subgroup = NULL, fun,
  ..., unsafe = FALSE)

calc_cro_fun_df(data, cell_vars, col_vars = total(),
  row_vars = total(label = ""), weight = NULL, subgroup = NULL, fun,
  ..., unsafe = FALSE)

calc_cro_mean(data, cell_vars, col_vars = total(),
  row_vars = total(label = ""), weight = NULL, subgroup = NULL)

calc_cro_mean_sd_n(data, cell_vars, col_vars = total(),
  row_vars = total(label = ""), weight = NULL, subgroup = NULL,
  weighted_valid_n = FALSE, labels = NULL)

calc_cro_sum(data, cell_vars, col_vars = total(),
  row_vars = total(label = ""), weight = NULL, subgroup = NULL)

calc_cro_median(data, cell_vars, col_vars = total(),
  row_vars = total(label = ""), weight = NULL, subgroup = NULL)

calc_cro_pearson(data, cell_vars, col_vars = total(),
  row_vars = total(label = ""), weight = NULL, subgroup = NULL)

calc_cro_spearman(data, cell_vars, col_vars = total(),
  row_vars = total(label = ""), weight = NULL, subgroup = NULL)
```

```
combine_functions(..., method = c)
```

### Arguments

cell_vars	vector/data.frame/list. Variables on which summary function will be computed.
col_vars	vector/data.frame/list. Variables which breaks table by columns. Use <a href="#">mrset/mdset</a> for multiple-response variables.
row_vars	vector/data.frame/list. Variables which breaks table by rows. Use <a href="#">mrset/mdset</a> for multiple-response variables.
weight	numeric vector. Optional cases weights. Cases with NA's, negative and zero weights are removed before calculations.
subgroup	logical vector. You can specify subgroup on which table will be computed.
fun	custom summary function. Generally it is recommended that fun will always return object of the same form. Rownames/vector names of fun result will appear in the row labels of the table and column names/names of list will appear in the column labels. To use weight you should have formal weight argument in fun and some logic for its processing inside. For <code>cro_fun_df</code> fun will receive <a href="#">data.table</a> with all names converted to variable labels (if labels exists). So it is not recommended to rely on original variables names in your fun.
...	further arguments for fun in <code>cro_fun/cro_fun_df</code> or functions for <code>combine_functions</code> . Ignored in <code>cro_fun/cro_fun_df</code> if <code>unsafe</code> is TRUE.
unsafe	logical/character If not FALSE than fun will be evaluated as is. It can lead to significant increase in the performance. But there are some limitations. For <code>cro_fun</code> it means that your function fun should return vector. If length of this vector is greater than one than you should provide with <code>unsafe</code> argument vector of unique labels for each element of this vector. There will be no attempts to automatically make labels for the results of fun. For <code>cro_fun_df</code> your function should return vector or list/data.frame (optionally with 'row_labels' element - statistic labels). If <code>unsafe</code> is TRUE or not logical then further arguments (...) for fun will be ignored.
weighted_valid_n	logical. Should we show weighted valid N in <code>cro_mean_sd_n</code> ? By default it is FALSE.
labels	character vector of length 3. Labels for mean, standard deviation and valid N in <code>cro_mean_sd_n</code> .
data	data.frame in which context all other arguments will be evaluated (for <code>calc_cro_*</code> ).
method	function which will combine results of multiple functions in <code>combine_functions</code> . It will be applied as in the expression <code>do.call(method, list_of_functions_results)</code> . By default it is <code>c</code> .

### Value

object of class 'etable'. Basically it's a data.frame but class is needed for custom methods.

**See Also**

[tables](#), [fre](#), [cro](#).

**Examples**

```

data(mtcars)
mtcars = apply_labels(mtcars,
  mpg = "Miles/(US) gallon",
  cyl = "Number of cylinders",
  disp = "Displacement (cu.in.)",
  hp = "Gross horsepower",
  drat = "Rear axle ratio",
  wt = "Weight (1000 lbs)",
  qsec = "1/4 mile time",
  vs = "Engine",
  vs = c("V-engine" = 0,
        "Straight engine" = 1),
  am = "Transmission",
  am = c("Automatic" = 0,
        "Manual"=1),
  gear = "Number of forward gears",
  carb = "Number of carburetors"
)

# Simple example - there is special shortcut for it - 'cro_mean'
calculate(mtcars, cro_fun(list(mpg, disp, hp, wt, qsec),
  col_vars = list(total(), am),
  row_vars = vs,
  fun = mean)
)

# the same result
calc_cro_fun(mtcars, list(mpg, disp, hp, wt, qsec),
  col_vars = list(total(), am),
  row_vars = vs,
  fun = mean
)

# The same example with 'subgroup'
calculate(mtcars, cro_fun(list(mpg, disp, hp, wt, qsec),
  col_vars = list(total(), am),
  row_vars = vs,
  subgroup = vs == 0,
  fun = mean)
)

# 'combine_functions' usage
calculate(mtcars, cro_fun(list(mpg, disp, hp, wt, qsec),
  col_vars = list(total(), am),
  row_vars = vs,
  fun = combine_functions(Mean = mean,

```

```

        'Std. dev.' = sd,
        'Valid N' = valid_n)
    ))
# 'combine_functions' usage - statistic labels in columns
calculate(mtcars, cro_fun(list(mpg, disp, hp, wt, qsec),
    col_vars = list(total(), am),
    row_vars = vs,
    fun = combine_functions(Mean = mean,
        'Std. dev.' = sd,
        'Valid N' = valid_n,
        method = list
    )
))

# 'summary' function
calculate(mtcars, cro_fun(list(mpg, disp, hp, wt, qsec),
    col_vars = list(total(), am),
    row_vars = list(total(), vs),
    fun = summary
))

# comparison 'cro_fun' and 'cro_fun_df'
calculate(mtcars, cro_fun(
    sheet(mpg, disp, hp, wt, qsec),
    col_vars = am,
    fun = mean
)
)

# same result
calculate(mtcars, cro_fun_df(
    sheet(mpg, disp, hp, wt, qsec),
    col_vars = am,
    fun = colMeans
)
)

# usage for 'cro_fun_df' which is not possible for 'cro_fun'
# linear regression by groups
calculate(mtcars, cro_fun_df(
    sheet(mpg, disp, hp, wt, qsec),
    col_vars = am,
    fun = function(x){
        frm = reformulate(".", response = names(x)[1])
        model = lm(frm, data = x)
        sheet(
            'Coef. estimate' = coef(model),
            confint(model)
        )
    }
))

```

---

default_dataset	<i>Get or set reference to default dataset. Experimental feature.</i>
-----------------	---

---

### Description

Use `data.frame` or `data.frame` name to set it as default. Use `NULL` as an argument to disable default dataset. If argument is missing then function will return reference to default dataset. Use [ref](#) to modify it. Also see [.compute](#) for usage patterns.

### Usage

```
default_dataset(x)
```

### Arguments

`x` `data.frame` or `data.frame` name which we want to make default for some operations.

### Value

formula reference to default dataset or `NULL`

### See Also

[ref](#)

### Examples

```
data(iris)
default_iris = iris
default_dataset(default_iris) # set default dataset

.compute({
  new_col = 1
  Sepal.Length = Sepal.Length*2
})

# for comparison

iris$new_col = 1
iris$Sepal.Length = iris$Sepal.Length*2
identical(iris, default_iris) # should be TRUE

default_dataset(NULL) # disable default dataset
```

---

do_repeat	<i>Repeats the same transformations on a specified set of variables/values</i>
-----------	--

---

### Description

Repeats the same transformations on a specified set of variables/values

### Usage

```
do_repeat(data, ...)
```

```
.do_repeat(...)
```

```
as_is(...)
```

### Arguments

data	data.frame/list. If data is list then do_repeat will be applied to each element of the list.
...	stand-in name(s) followed by equals sign and a vector/list of replacement variables or values. They can be numeric/characters or variables names. Names at the top-level can be unquoted (non-standard evaluation). Quoted characters also considered as variables names. To avoid this behavior use as_is function. For standard evaluation of parameters you can surround them by round brackets. Also you can use %to% operator and other <a href="#">criteria</a> functions. Last argument should be expression in curly brackets which will be evaluated in the scope of data.frame data. See examples.

### Details

There is a special constant .N which equals to number of cases in data for usage in expression inside do\_repeat. Also there are a variables .item\_num which is equal to the current iteration number and .item\_value which is named list with current stand-in variables values.

### Value

transformed data.frame data

### See Also

[compute](#), [do\\_if](#)

**Examples**

```

data(iris)
scaled_iris = do_repeat(iris,
  i = Sepal.Length %to% Petal.Width,
  {
    i = scale(i)
  })
head(scaled_iris)

# several stand-in names and standard evaluation
old_names = qc(Sepal.Length, Sepal.Width, Petal.Length, Petal.Width)
new_names = paste0("scaled_", old_names)
scaled_iris = do_repeat(iris,
  orig = ((old_names)),
  scaled = ((new_names)),
  {
    scaled = scale(orig)
  })
head(scaled_iris)

# numerics
new_df = data.frame(id = 1:20)
# note the automatic creation of the sequence of variables
new_df = do_repeat(new_df,
  item = i1 %to% i3,
  value = c(1, 2, 3),
  {
    item = value
  })
head(new_df)

# the same result with internal variable '.item_num'
new_df = data.frame(id = 1:20)
new_df = do_repeat(new_df,
  item = i1 %to% i3,
  {
    item = .item_num
  })
head(new_df)

# functions
set.seed(123)
new_df = data.frame(id = 1:20)
new_df = do_repeat(new_df,
  item = c(i1, i2, i3),
  fun = c("rnorm", "runif", "rexp"),
  {
    item = fun(.N)
  })
head(new_df)

```

---

drop_empty_rows	<i>Drop empty (with all NA's) rows/columns from data.frame/table</i>
-----------------	--

---

## Description

By default tables produced by functions `tables`, `cro`, `cro_fun` and `cro_fun_df` are created with all possible value labels. If values for these labels are absent in variable there are NA's in rows and columns. `drop_empty_rows/drop_empty_columns` are intended to remove these empty rows/columns. `drop_r` and `drop_c` are the same functions with shorter names. `drop_rc` drops rows and columns simultaneously.

## Usage

```
drop_empty_rows(x, excluded_rows = NULL, excluded_columns = NULL)
```

```
drop_empty_columns(x, excluded_rows = NULL, excluded_columns = NULL)
```

```
drop_r(x, excluded_rows = NULL, excluded_columns = NULL)
```

```
drop_c(x, excluded_rows = NULL, excluded_columns = NULL)
```

```
drop_rc(x)
```

## Arguments

<code>x</code>	data.frame/etable(result of <code>cro</code> and etc.)
<code>excluded_rows</code>	character/logical/numeric rows which won't be dropped and in which NAs won't be counted. If it is characters then they will be considered as pattern/vector of patterns. Patterns will be matched with Perl-style regular expression with values in the first column of <code>x</code> (see <code>grep</code> , <code>perl = TRUE</code> argument). Rows which have such patterns will be excluded. By default for class 'etable' pattern is "#" because "#" marks totals in the result of <code>cro</code> .
<code>excluded_columns</code>	logical/numeric/characters columns which won't be dropped and in which NAs won't be counted. By default for class 'etable' it is first column - column with labels in table.

## Value

data.frame with removed rows/columns

## Examples

```
data(mtcars)
mtcars = apply_labels(mtcars,
  vs = "Engine",
  vs = num_lab("))
```

```

        0 V-engine
        1 Straight engine
        9 Other
    ),
    am = "Transmission",
    am = num_lab("
        0 Automatic
        1 Manual
        9 Other
    ")
)
with_empty = calculate(mtcars, cro(am, vs))

drop_empty_rows(with_empty)
drop_empty_columns(with_empty)
drop_rc(with_empty)

```

---

 experimental

*Experimental functions for operations with default dataset*


---

## Description

Workflow for these functions is rather simple. You should set up default data.frame with [default\\_dataset](#) and then operate with it without any reference to your data.frame. There are two kinds of operations. The first kind modify default dataset, the second kind will be evaluated in the context of the default dataset but doesn't modify it. It is not recommended to use one of these functions in the scope of another of these functions. By now their performance is not so high, especially `.do_if/.modify_if` can be very slow.

## Usage

```

.compute(expr)

.do_if(cond, expr)

.modify_if(cond, expr)

.modify(expr)

.calculate(expr, use_labels = FALSE)

.calc(expr, use_labels = FALSE)

.val_lab(...)

.var_lab(...)

```

```
.recode(x, ...)  
.fre(...)  
.cro(...)  
.cro_cases(...)  
.cro_cpct(...)  
.cro_rpct(...)  
.cro_tpct(...)  
.cro_mean(...)  
.cro_sum(...)  
.cro_median(...)  
.cro_mean_sd_n(...)  
.cro_fun(...)  
.cro_fun_df(...)
```

### Arguments

expr	set of expressions in curly brackets which will be evaluated in the context of default dataset
cond	logical vector/expression
use_labels	logical. Experimental feature. If it equals to TRUE then we will try to replace variable names with labels. Many base R functions which show variable names will show labels.
...	further arguments
x	vector/data.frame - variable names in the scope of default dataset

### Details

Functions which modify default dataset:

- `.modify` Add and modify variables inside default data.frame. See [modify](#).
- `.compute` Shortcut for `.modify`. Name is inspired by SPSS COMPUTE operator. See [modify](#).
- `.modify_if` Add and modify variables inside subset of default data.frame. See [modify\\_if](#).
- `.do_if` Shortcut for `.modify_if`. Name is inspired by SPSS DO IF operator. See [modify\\_if](#).
- `.where` Leave subset of default data.frame which meet condition. See [where](#), [subset](#).

- `.recode` Change, rearrange or consolidate the values of an existing variable inside default data.frame. See [recode](#).

Other functions:

- `.var_lab` Return variable label from default dataset. See [var\\_lab](#).
- `.val_lab` Return value labels from default dataset. See [val\\_lab](#).
- `.fre` Simple frequencies of variable in the default data.frame. See [fre](#).
- `.cro/.cro_cpct/.cro_rpct/.cro_tpct` Simple crosstabulations of variable in the default data.frame. See [cro](#).
- `.cro_mean/.cro_sum/.cro_median/.cro_fun/.cro_fun_df` Simple crosstabulations of variable in the default data.frame. See [cro\\_fun](#).
- `.calculate` Evaluate arbitrary expression in the context of data.frame. See [calculate](#).

## Examples

```
data(mtcars)

default_dataset(mtcars) # set mtcars as default dataset

# calculate new variables
.compute({
  mpg_by_am = ave(mpg, am, FUN = mean)
  hi_low_mpg = ifs(mpg < mean(mpg) ~ 0, TRUE ~ 1)
})

# set labels
.apply_labels(
  mpg = "Miles/(US) gallon",
  cyl = "Number of cylinders",
  disp = "Displacement (cu.in.)",
  hp = "Gross horsepower",
  mpg_by_am = "Average mpg for transmission type",
  hi_low_mpg = "Miles per gallon",
  hi_low_mpg = num_lab("
    0 Low
    1 High
  "),

  vs = "Engine",
  vs = num_lab("
    0 V-engine
    1 Straight engine
  "),

  am = "Transmission",
  am = num_lab("
    0 Automatic
    1 Manual
  ")
)
```

```

# calculate frequencies
.fre(hi_low_mpg)
.cro(cyl, hi_low_mpg)
.cro_mean(data.frame(mpg, disp, hp), vs)

# disable default dataset
default_dataset(NULL)

# Example of .recode

data(iris)

default_dataset(iris) # set iris as default dataset

.recode(Sepal.Length, lo %thru% median(Sepal.Length) ~ "small", other ~ "large")

.fre(Sepal.Length)

# example of .do_if

.do_if(Species == "setosa",{
  Petal.Length = NA
  Petal.Width = NA
})

.cro_mean(data.frame(Petal.Length, Petal.Width), Species)

# disable default dataset
default_dataset(NULL)

```

---

expss

*expss: Tables with Labels and Some Useful Functions from Spreadsheets and SPSS Statistics*


---

## Description

'expss' package implements some popular functions from spreadsheets and SPSS Statistics software. Implementations are not complete copies of their originals. I try to make them consistent with other R functions. See examples in the vignette and in the help.

## Excel

- IF [ifelse](#)
- AVERAGE [mean\\_row](#)
- SUM [sum\\_row](#)
- MIN [min\\_row](#)
- MAX [max\\_row](#)
- VLOOKUP [vlookup](#)

- COUNTIF [count\\_if](#)
- AVERAGEIF [mean\\_row\\_if](#)
- SUMIF [sum\\_row\\_if](#)
- MINIF [min\\_row\\_if](#)
- MAXIF [max\\_row\\_if](#)
- IFS [ifs](#)
- IFNA [if\\_na](#)
- MATCH [match\\_row](#)
- INDEX [index\\_row](#)
- PIVOT TABLES [tables](#), [cro\\_fun](#), [cro](#)

## SPSS

- COMPUTE [compute](#)
- RECODE [recode](#)
- COUNT [count\\_row\\_if](#)
- DO IF [do\\_if](#)
- DO REPEAT [do\\_repeat](#)
- VARIABLE LABELS [var\\_lab](#)
- VALUE LABELS [val\\_lab](#)
- ANY [any\\_in\\_row](#)
- FREQUENCIES [fre](#)
- CROSSTABS [cro](#)
- CUSTOM TABLES [tables](#)

---

expss.options

*Options for controlling behavior of the package*

---

## Description

All options can be set with `options(option.name = option.value)` or with special functions (see below). You can get value of option with `getOption("option.name")`.

- `expss.digits` Number of digits after decimal separator which will be shown for tables. This parameter is supported in the [as.datatable\\_widget](#), [htmlTable.etable](#) and `print` methods. `NULL` is default and means one digit. `NA` means no rounding. There is a convenience function for this option: `expss_digits`.

- `expss.enable_value_labels_support` By default, all labelled variables will use labels as labels for factor levels when `factor` is called. So, any function which calls `factor/as.factor` will use value labels. In details this option changes behavior of two methods for class `labelled` - `as.character` and `unique` - on which `factor` depends entirely. If you have compatibility problems set this option to zero: `options(expss.enable_value_labels_support = 0)`. Additionally there is an option for extreme value labels support: `options(expss.enable_value_labels_support_extreme = 2)`. With this value `factor/as.factor` will take into account empty levels. See example. It is recommended to turn off this option immediately after usage because `unique.labelled` will give weird result. Labels without values will be added to unique values. There are shortcuts for these options: `expss_enable_value_labels_support()`, `expss_enable_value_labels_support_extreme()` and `expss_disable_value_labels_support()`.
- `expss.output` By default tables are printed in the console. You can change this behavior by setting this option. There are four possible values: `'rnotebook'`, `'viewer'`, `'commented'` or `'raw'`. First option is useful when you run your code in the R Notebook - output will be rendered to nice HTML. The second option will render tables to RStudio viewer. `knitr` is supported automatically via `knit_print` method. `'commented'` prints default output to the console with comment symbol (`#`) at the beginning of the each line. With comment symbol you can easily copy and paste your output into the script. Option `raw` disables any formatting and all tables are printed as `data.frames`. Shortcuts for options: `expss_output_default()`, `expss_output_raw()`, `expss_output_viewer()`, `expss_output_commented()` and `expss_output_rnotebook()`.
- `expss_fix_encoding_on/expss_fix_encoding_off` If you experience problems with character encoding in RStudio Viewer/RNotebooks under Windows try `expss_fix_encoding_on()`. In some cases, it can help.

## Usage

```
expss_digits(digits = NULL)
```

```
get_expss_digits()
```

```
expss_enable_value_labels_support()
```

```
expss_enable_value_labels_support_extreme()
```

```
expss_disable_value_labels_support()
```

```
expss_output_default()
```

```
expss_output_commented()
```

```
expss_output_raw()
```

```
expss_output_viewer()
```

```
expss_output_rnotebook()
```

```
expss_fix_encoding_on()
```

```
expss_fix_encoding_off()
```

### Arguments

`digits` integer. Number of digits after decimal point. NULL is default and means 1 digit. NA means no rounding.

### Examples

```
# example of different levels of value labels support
my_scale = c(1, 2, 2, 2)
# note that we have label 'Hard to say' for which there are no values in 'my_scale'
val_lab(my_scale) = num_lab("
  1 Yes
  2 No
  3 Hard to say
")
# disable labels support
expss_disable_value_labels_support()
table(my_scale) # there is no labels in the result
unique(my_scale)
# default value labels support
expss_enable_value_labels_support()
# table with labels but there are no label "Hard to say"
table(my_scale)
unique(my_scale)
# extreme value labels support
expss_enable_value_labels_support_extreme()
# now we see "Hard to say" with zero counts
table(my_scale)
# weird 'unique'! There is a value 3 which is absent in 'my_scale'
unique(my_scale)
# return immediately to defaults to avoid issues
expss_enable_value_labels_support()
```

---

fctr

*Convert labelled variable to factor*

---

### Description

fctr converts variable to factor. It force labels usage as factor labels for labelled variables even if 'expss.enable\_value\_labels\_support' set to 0. For other types of variables base [factor](#) is called. Factor levels are constructed as values labels. If label doesn't exist for particular value then this value remain as is - so there is no information lost. This levels look like as "Variable\_label|Value label" if argument prepend set to TRUE.

### Usage

```
fctr(x, ..., drop_unused_labels = FALSE, prepend_var_lab = TRUE)
```

**Arguments**

`x` a vector of data with labels.

`...` optional arguments for [factor](#)

`drop_unused_labels` logical. Should we drop unused value labels? Default is FALSE.

`prepend_var_lab` logical. Should we prepend variable label before value labels? Default is TRUE.

**Value**

an object of class factor. For details see base [factor](#) documentation.

**See Also**

[values2labels](#), [names2labels](#), [val\\_lab](#), [var\\_lab](#). Materials for base functions: [factor](#), [as.factor](#), [ordered](#), [as.ordered](#)

**Examples**

```
data(mtcars)

var_lab(mtcars$am) = "Transmission"
val_lab(mtcars$am) = c(automatic = 0, manual=1)

summary(lm(mpg ~ am, data = mtcars)) # no labels
summary(lm(mpg ~ fctr(am), data = mtcars)) # with labels
summary(lm(mpg ~ fctr(unvr(am)), data = mtcars)) # without variable label
```

---

fre *Simple frequencies with support of labels, weights and multiple response variables.*

---

**Description**

`fre` returns `data.frame` with six columns: labels or values, counts, valid percent (excluding NA), percent (with NA), percent of responses (for single-column `x` it equals to valid percent) and cumulative percent of responses.

**Usage**

```
fre(x, weight = NULL, drop_unused_labels = TRUE,
    prepend_var_lab = FALSE)
```

**Arguments**

<code>x</code>	vector/data.frame/list. data.frames are considered as multiple response variables. If <code>x</code> is list then vertically stacked frequencies for each element of list will be generated,
<code>weight</code>	numeric vector. Optional case weights. NA's and negative weights treated as zero weights.
<code>drop_unused_labels</code>	logical. Should we drop unused value labels? Default is TRUE.
<code>prepend_var_lab</code>	logical. Should we prepend variable label before value labels? By default we will add variable labels to value labels only if <code>x</code> or predictor is list (several variables).

**Value**

object of class 'etable'. Basically it's a data.frame but class is needed for custom methods.

**Examples**

```
data(mtcars)
mtcars = modify(mtcars,{
  var_lab(vs) = "Engine"
  val_lab(vs) = c("V-engine" = 0,
                 "Straight engine" = 1)
  var_lab(am) = "Transmission"
  val_lab(am) = c(automatic = 0,
                 manual=1)
})

fre(mtcars$vs)

# stacked frequencies
fre(list(mtcars$vs, mtcars$am))

# multiple-choice variable
# brands - multiple response question
# Which brands do you use during last three months?
set.seed(123)
brands = data.frame(t(replicate(20,sample(c(1:5,NA),4,replace = FALSE))))
# score - evaluation of tested product
score = sample(-1:1,20,replace = TRUE)
var_lab(brands) = "Used brands"
val_lab(brands) = make_labels("
      1 Brand A
      2 Brand B
      3 Brand C
      4 Brand D
      5 Brand E
      ")
```

```

var_lab(score) = "Evaluation of tested brand"
val_lab(score) = make_labels("
    -1 Dislike it
    0 So-so
    1 Like it
    ")

fre(brands)

# stacked frequencies
fre(list(score, brands))

```

---

htmlTable.etable      *Outputting HTML tables in RStudio viewer/R Notebooks*

---

### Description

This is method for rendering results of [fre/cro/tables](#) in Shiny/RMarkdown/Jupyter notebooks and etc. For detailed description of function and its arguments see [htmlTable](#). You can pack your tables in the list and render them all simultaneously. See examples. You may be interested in [expss\\_output\\_viewer\(\)](#) for automatical rendering tables in the RStudio viewer or [expss\\_output\\_rnotebook\(\)](#) for rendering in the R notebooks. See [expss.options](#). [repr\\_html](#) is method for rendering table in the Jupyter notebooks and [knit\\_print](#) is method for rendering table in the knitr HTML-documents. Jupyter notebooks and knitr documents are supported automatically but in the R notebooks it is needed to set output to notebook via [expss\\_output\\_rnotebook\(\)](#).

### Usage

```

## S3 method for class 'etable'
htmlTable(x, digits = get_expss_digits(),
  escape.html = FALSE, ..., row_groups = TRUE)

## S3 method for class 'with_caption'
htmlTable(x, digits = get_expss_digits(),
  escape.html = FALSE, ..., row_groups = TRUE)

## S3 method for class 'list'
htmlTable(x, gap = "<br>", ...)

knit_print.etable(x, digits = get_expss_digits(), escape.html = FALSE,
  ...)

knit_print.with_caption(x, digits = get_expss_digits(),
  escape.html = FALSE, ...)

repr_html.etable(obj, digits = get_expss_digits(), escape.html = FALSE,
  ...)

```

```
repr_html.with_caption(obj, digits = get_expss_digits(),
  escape.html = FALSE, ...)
```

```
repr_text.etable(obj, digits = get_expss_digits(), ...)
```

```
repr_text.with_caption(obj, digits = get_expss_digits(), ...)
```

### Arguments

<code>x</code>	a data object of class 'etable' - result of <a href="#">fre/cro</a> and etc.
<code>digits</code>	integer By default, all numeric columns are rounded to one digit after decimal separator. Also you can set this argument by setting option 'expss.digits' - for example, <code>expss_digits(2)</code> . If it is NA than all numeric columns remain unrounded.
<code>escape.html</code>	logical: should HTML characters be escaped? Defaults to FALSE.
<code>...</code>	further parameters for <a href="#">htmlTable</a> .
<code>row_groups</code>	logical Should we create row groups? TRUE by default.
<code>gap</code>	character Separator between tables if we output list of tables. By default it is line break ' '. By default it is line break ' '.
<code>obj</code>	a data object of class 'etable' - result of <a href="#">fre/cro</a> and etc.

### Value

Returns a string of class `htmlTable`

### Examples

```
## Not run:
data(mtcars)
mtcars = apply_labels(mtcars,
  mpg = "Miles/(US) gallon",
  cyl = "Number of cylinders",
  disp = "Displacement (cu.in.)",
  hp = "Gross horsepower",
  drat = "Rear axle ratio",
  wt = "Weight (1000 lbs)",
  qsec = "1/4 mile time",
  vs = "Engine",
  vs = c("V-engine" = 0,
    "Straight engine" = 1),
  am = "Transmission",
  am = c("Automatic" = 0,
    "Manual"=1),
  gear = "Number of forward gears",
  carb = "Number of carburetors"
)

expss_output_viewer()
```

```

mtcars %>%
  tab_cols(total(), am %nest% vs) %>%
  tab_cells(mpg, hp) %>%
  tab_stat_mean() %>%
  tab_cells(cyl) %>%
  tab_stat_cpct() %>%
  tab_pivot() %>%
  set_caption("Table 1. Some variables from mtcars dataset.")

# several tables in a list
mtcars %>%
  calc(list(
    cro_cpct(list(am, vs, cyl), list(total(), am)) %>% set_caption("Table 1. Percent."),
    cro_mean_sd_n(list(mpg, hp, qsec), list(total(), am)) %>% set_caption("Table 2. Means.")
  )) %>%
  htmlTable()

expss_output_default()

## End(Not run)

```

---

if\_na

---

*Replace values with NA and vice-versa*


---

## Description

- `if_na` replaces NA values in vector/data.frame/matrix/list with supplied value. For single value argument label can be provided with `label` argument. If replacement value is vector then `if_na` uses for replacement values from appropriate positions. An opposite operation is `na_if`.
- `na_if` replaces values with NA in vector/data.frame/matrix/list. Another alias for this is `mis_val`.
- `valid` returns logical vector which indicate the presence of at least one not-NA value in row. For vector or single column data.frame result is the same as with [complete.cases](#). There is a special case for data.frame of class `dichotomy`. In this case result indicate the presence of at least one 1 in a row.

## Usage

```

if_na(x, value, label = NULL)

if_na(x, label = NULL) <- value

x %if_na% value

na_if(x, value, with_labels = FALSE)

```

```

na_if(x, with_labels = FALSE) <- value
x %na_if% value

mis_val(x, value, with_labels = FALSE)

mis_val(x, with_labels = FALSE) <- value

valid(x)

```

### Arguments

x	vector/matrix/data.frame/list
value	single value, vector of the same length as number of rows in x, or function ( <a href="#">criteria</a> ) for na_if. See <a href="#">recode</a> for details.
label	a character of length 1. Label for value which replace NA.
with_labels	logical. FALSE by default. Should we also remove labels of values which we recode to NA?

### Format

An object of class character of length 1.

### Value

object of the same form and class as x. valid returns logical vector.

### Examples

```

# simple case
a = c(NA, 2, 3, 4, NA)
if_na(a, 99)

# the same result
a %if_na% 99

# with label
a = c(NA, 2, 3, 4, NA)
if_na(a, 99, label = "Hard to say")

# in-place replacement. The same result:
if_na(a, label = "Hard to say") = 99
a # c(99, 2, 3, 4, 99)

# replacement with values from other variable
a = c(NA, 2, 3, 4, NA)
b = 1:5
if_na(a, b)

```

```

# replacement with group means
# make data.frame
set.seed(123)
group = sample(1:3, 30, replace = TRUE)
param = runif(30)
param[sample(30, 10)] = NA # place 10 NA's
df = data.frame(group, param)

# replace NA's with group means
if_na(df$param) = window_fun(df$param, df$group, mean_col)
df

#####
### na_if examples ###
#####

a = c(1:5, 99)
# 99 to NA
na_if(a, 99) # c(1:5, NA)

a %na_if% 99 # same result

# values which greater than 4 to NA
na_if(a, gt(4)) # c(1:4, NA, NA)

# alias 'mis_val', with_labels = TRUE
a = c(1, 1, 2, 2, 99)
val_lab(a) = c(Yes = 1, No = 2, "Hard to say" = 99)
mis_val(a, 99, with_labels = TRUE)

set.seed(123)
dfs = data.frame(
  a = c("bad value", "bad value", "good value", "good value", "good value"),
  b = runif(5)
)

# rows with 'bad value' will be filled with NA
# logical argument and recycling by columns
na_if(dfs, dfs$a=="bad value")

a = rnorm(50)
# values greater than 1 or less than -1 will be set to NA
# special functions usage
na_if(a, lt(-1) | gt(1))

# values inside [-1, 1] to NA
na_if(a, -1 %thru% 1)

```

**Description**

`info` returns `data.frame` with variables description and some summary statistics. Resulting `data.frame` mainly intended to keep in front of eyes in RStudio viewer or to be saved as `csv` to view in the spreadsheet software as reference about working dataset.

**Usage**

```
info(x, stats = TRUE, frequencies = TRUE, max_levels = 10)
```

**Arguments**

<code>x</code>	vector/factor/list/data.frame.
<code>stats</code>	Logical. Should we calculate summary for each variable?
<code>frequencies</code>	Logical. Should we calculate frequencies for each variable? This calculation can take significant amount of time for large datasets.
<code>max_levels</code>	Numeric. Maximum levels for using in frequency calculations. Levels above this value will convert to 'Other values'.

**Value**

`data.frame` with following columns: Name, Class, Length, NotNA, NA, Distincts, Label, ValueLabels, Min., 1st Qu., Median, Mean, 3rd Qu., Max., Frequency.

**Examples**

```
data(mtcars)
var_lab(mtcars$am) = "Transmission"
val_lab(mtcars$am) = c("Automatic"=0, "Manual"=1)
info(mtcars, max_levels = 5)
```

---

keep

*Keep or drop elements by name/criteria in data.frame/matrix*

---

**Description**

`keep` selects variables/elements from `data.frame` by their names or by criteria (see [criteria](#)). `except` drops variables/elements from `data.frame` by their names or by criteria. Names at the top-level can be unquoted (non-standard evaluation). For standard evaluation of parameters you can surround them by round brackets. See examples. Methods for list will apply `keep/except` to each element of the list separately. `.keep/.``except` are versions which works with [default\\_dataset](#).

**Usage**

```
keep(data, ...)

.keep(...)

except(data, ...)

.except(...)
```

**Arguments**

data	data.frame/matrix/list
...	column names of type character/numeric or criteria/logical functions

**Value**

object of the same type as data

**Examples**

```
data(iris)
keep(iris, Sepal.Length, Sepal.Width)
except(iris, Species)

keep(iris, Species, other()) # move 'Species' to the first position
keep(iris, to("Petal.Width")) # keep all columns up to 'Species'

except(iris, perl("^Petal")) # remove columns which names start with 'Petal'

except(iris, 5) # remove fifth column

data(mtcars)
keep(mtcars, from("mpg") & to("qsec")) # keep columns from 'mpg' to 'qsec'
keep(mtcars, mpg %to% qsec) # the same result

# standard and non-standard evaluation
many_vars = c("am", "vs", "cyl")
## Not run:
keep(mtcars, many_vars) # error - names not found: 'many_vars'

## End(Not run)
keep(mtcars, (many_vars)) # ok

# character expansion
dfs = data.frame(
  a = 10 %r% 5,
  b_1 = 11 %r% 5,
  b_2 = 12 %r% 5,
  b_3 = 12 %r% 5,
  b_4 = 14 %r% 5,
  b_5 = 15 %r% 5
```

```

)
i = 1:5
keep(dfs, b_1 %to% b_5)
keep(dfs, text_expand("b_{i}")) # the same result

```

---

match_row	<i>Match finds value in rows or columns/index returns value by index from rows or columns</i>
-----------	---

---

### Description

match finds value in rows or columns. index returns value by index from row or column. One can use functions as criteria for match. In this case position of first value on which function equals to TRUE will be returned. For convenience there are special predefined functions - see [criteria](#). If value is not found then NA will be returned.

### Usage

```

match_row(criterion, ...)
match_col(criterion, ...)
index_row(index, ...)
index_col(index, ...)
value_row_if(criterion, ...)
value_col_if(criterion, ...)

```

### Arguments

criterion	Vector of values to be matched, or function.
...	data. Vectors, matrixes, data.frames, lists. Shorter arguments will be recycled.
index	vector of positions in rows/columns from which values should be returned.

### Value

vector with length equals to number of rows for \*\_row and equals to number of columns for \*\_col.

### Examples

```

# toy data
v1 = 1:3
v2 = 2:4
v3 = 7:5

# postions of 1,3,5 in rows

```

```

match_row(c(1, 3, 5), v1, v2, v3) # 1:3
# postions of 1,3,5 in columns
match_col(1, v1, v2, v3) # c(v1 = 1, v2 = NA, v3 = NA)

# postion of first value greater than 2
ix = match_row(gt(2), v1, v2, v3)
ix # c(3,2,1)
# return values by result of previous 'match_row'
index_row(ix, v1, v2, v3) # c(7,3,3)

# the same actions with data.frame
dfs = data.frame(v1, v2, v3)

# postions of 1,3,5 in rows
match_row(c(1, 3, 5), dfs) # 1:3
# postions of 1,3,5 in columns
match_col(1, dfs) # c(v1 = 1, v2 = NA, v3 = NA)

# postion of first value greater than 2
ix = match_row(gt(2), dfs)
ix # c(3,2,1)
# return values by result of previous 'match_row'
index_row(ix, dfs) # c(7,3,3)

```

---

merge.etable

Merge two tables/data.frames

---

## Description

`%merge%` is infix shortcut for base [merge](#) with `all.x = TRUE` and `all.y = FALSE` (left join). There is also special method for combining results of `cro_*` and `fre`. For them `all = TRUE` (full join). It allows make complex tables from simple ones. See examples. Strange result is possible if one or two arguments have duplicates in first column (column with labels).

## Usage

```
x %merge% y
```

## Arguments

x	data.frame or results of <code>fre/cro_*/table_*</code>
y	data.frame or results of <code>fre/cro_*/table_*</code>

## Value

data.frame

## See Also

[fre](#), [cro](#), [cro\\_fun](#), [merge](#)

## Examples

```

data(mtcars)
# apply labels
mtcars = apply_labels(mtcars,
  mpg = "Miles/(US) gallon",
  cyl = "Number of cylinders",
  disp = "Displacement (cu.in.)",
  hp = "Gross horsepower",
  drat = "Rear axle ratio",
  wt = "Weight (lb/1000)",
  qsec = "1/4 mile time",
  vs = "V/S",
  vs = c("V-engine" = 0, "Straight engine" = 1),
  am = "Transmission (0 = automatic, 1 = manual)",
  am = c(automatic = 0, manual = 1),
  gear = "Number of forward gears",
  carb = "Number of carburetors"
)

# table by 'am'
tab1 = calculate(mtcars, cro_cpct(gear, am))
# table with percents
tab2 = calculate(mtcars, cro_cpct(gear, vs))

# combine tables
tab1 %merge% tab2

# complex tables
# table with counts
counts = calculate(mtcars, cro(list(vs, am, gear, carb), list("Count")))
# table with percents
percents = calculate(mtcars, cro_cpct(list(vs, am, gear, carb), list("Column, %")))

# combine tables
counts %merge% percents

```

---

 mrset

---

*Create multiple response set/multiple dichotomy set from variables*


---

## Description

These functions are intended for usage with tables - [tables](#), [cro](#), [cro\\_fun](#). Result of `mrset` is considered as multiple-response set with category encoding and result of `mdset` is considered as multiple response set with dichotomy (dummy) encoding e. g. with 0 or 1 in the each column. Each column in the dichotomy is indicator of absence or presence of particular feature. Both functions don't convert its arguments to anything - it is supposed that arguments already have appropriate encoding. For conversation see [as.dichotomy](#) or [as.category](#).

- `mrset_f` and `mdset_f` select variables by fixed pattern. Fixed pattern can be unquoted. For details see [..f](#).

- `mrset_p` and `mdset_p` select variables for multiple-responses by perl-style regular expression. For details see [.p](#).
- `mrset_t` and `mdset_t` select variables by expanding text arguments. For details see [.t](#) and [text\\_expand](#).

### Usage

```
mrset(..., label = NULL)
mdset(..., label = NULL)
mrset_f(..., label = NULL)
mdset_f(..., label = NULL)
mrset_p(..., label = NULL)
mdset_p(..., label = NULL)
mrset_t(..., label = NULL)
mdset_t(..., label = NULL)
```

### Arguments

```
...          variables
label        character optional label for multiple response set
```

### Value

data.frame of class category/dichotomy

### See Also

[as.dichotomy](#), [as.category](#)

### Examples

```
data(product_test)

calc_cro_cpct(product_test, mrset(a1_1 %to% a1_6))

# same result
calc_cro_cpct(product_test, mrset_f(a1_))

# same result
calc_cro_cpct(product_test, mrset_p("a1_"))

# same result
calc_cro_cpct(product_test, mrset_t("a1_{1:6}"))
```

---

names2labels	<i>Replace data.frame/list names with corresponding variables labels.</i>
--------------	---

---

### Description

names2labels replaces data.frame/list names with corresponding variables labels. If there are no labels for some variables their names remain unchanged. n2l is just shortcut for names2labels.

### Usage

```
names2labels(x, exclude = NULL, keep_names = FALSE)
```

```
n2l(x, exclude = NULL, keep_names = FALSE)
```

### Arguments

x	data.frame/list.
exclude	logical/integer/character columns which names should be left unchanged. Only applicable to list/data.frame.
keep_names	logical. If TRUE original column names will be kept with labels. Only applicable to list/data.frame.

### Value

Object of the same type as x but with variable labels instead of names.

### See Also

[values2labels](#), [val\\_lab](#), [var\\_lab](#)

### Examples

```
data(mtcars)
mtcars = modify(mtcars,{
  var_lab(mpg) = "Miles/(US) gallon"
  var_lab(cyl) = "Number of cylinders"
  var_lab(displ) = "Displacement (cu.in.)"
  var_lab(hp) = "Gross horsepower"
  var_lab(drat) = "Rear axle ratio"
  var_lab(wt) = "Weight (lb/1000)"
  var_lab(qsec) = "1/4 mile time"
  var_lab(vs) = "V/S"
  var_lab(am) = "Transmission (0 = automatic, 1 = manual)"
  var_lab(gear) = "Number of forward gears"
  var_lab(carb) = "Number of carburetors"
})

# without original names
```

```
# note: we exclude dependent variable 'mpg' from conversion to use its short name in formula
summary(lm(mpg ~ ., data = names2labels(mtcars, exclude = "mpg")))
# with names
summary(lm(mpg ~ ., data = names2labels(mtcars, exclude = "mpg", keep_names = TRUE)))
```

---

name\_dots

*Bug workaround*


---

### Description

Function is added to workaround strange bug with data.table (issue #10).

### Usage

```
name_dots(...)
```

### Arguments

```
...          arguments
```

### Value

```
list
```

---

nest

*Compute nested variable(-s) from several variables*


---

### Description

nest mainly intended for usage with table functions such as [cro](#). See examples. %nest% is infix version of this function. You can apply nest on multiple-response variables/list of variables and data.frames.

### Usage

```
nest(...)
```

```
x %nest% y
```

### Arguments

```
...          vectors/data.frames/lists
```

```
x           vector/data.frame/list
```

```
y           vector/data.frame/list
```

**Value**

vector/data.frame/list

**See Also**

See also [interaction](#)

**Examples**

```
data(mtcars)

mtcars = apply_labels(mtcars,
  cyl = "Number of cylinders",
  vs = "Engine",
  vs = num_lab("
    0 V-engine
    1 Straight engine
  "),
  am = "Transmission",
  am = num_lab("
    0 Automatic
    1 Manual
  "),
  carb = "Number of carburetors"
)

calc(mtcars, cro(cyl, am %nest% vs))

# list of variables
calc(mtcars, cro(cyl, am %nest% list(vs, cyl)))

# list of variables - multiple banners/multiple nesting
calc(mtcars, cro(cyl, list(total(), list(am, vs) %nest% cyl)))

# three variables
calc(mtcars, cro(am %nest% vs %nest% carb, cyl))

# the same with usual version
calc(mtcars, cro(cyl, nest(am, vs)))

# three variables
calc(mtcars, cro(nest(am, vs, carb), cyl))
```

## Description

'subtotal' adds subtotal to set of categories, 'net' replaces categories with their net value. If you provide named arguments then name will be used as label for subtotal. In other case labels will be automatically generated taking into account arguments 'new\_label' and 'prefix'. Note that if you provide overlapping categories then net and subtotals will also be overlapping. 'subtotal' and 'net' are intended for usage with [cro](#) and friends. 'tab\_subtotal\_\*' and 'tab\_net\_\*' are intended for usage with custom tables - see [tables](#).

## Usage

```
net(x, ..., position = c("below", "above", "top", "bottom"),
    prefix = "TOTAL ", new_label = c("all", "range", "first", "last"),
    add = FALSE)

subtotal(x, ..., position = c("below", "above", "top", "bottom"),
         prefix = "TOTAL ", new_label = c("all", "range", "first", "last"),
         add = TRUE)

tab_net_cells(data, ..., position = c("below", "above", "top", "bottom"),
              prefix = "TOTAL ", new_label = c("all", "range", "first", "last"))

tab_net_cols(data, ..., position = c("below", "above", "top", "bottom"),
             prefix = "TOTAL ", new_label = c("all", "range", "first", "last"))

tab_net_rows(data, ..., position = c("below", "above", "top", "bottom"),
             prefix = "TOTAL ", new_label = c("all", "range", "first", "last"))

tab_subtotal_cells(data, ..., position = c("below", "above", "top",
                                           "bottom"), prefix = "TOTAL ", new_label = c("all", "range", "first",
                                                                                       "last"))

tab_subtotal_cols(data, ..., position = c("below", "above", "top",
                                           "bottom"), prefix = "TOTAL ", new_label = c("all", "range", "first",
                                                                                       "last"))

tab_subtotal_rows(data, ..., position = c("below", "above", "top",
                                           "bottom"), prefix = "TOTAL ", new_label = c("all", "range", "first",
                                                                                       "last"))
```

## Arguments

x	variable, list, data.frame or multiple response set
...	list of categories for grouping. It can be numeric vectors (for example, 1:2), ranges (for example, 4 greater(5)). If an argument is named then this name will be used as label for subtotal.
position	position of the subtotal or net relative to original categories. "below" by default. One of the "below", "above", "top", "bottom". "top" and "bottom" place nets

	and subtotals above or below all other categories. For nets "below" and "above" have no difference because original categories are removed.
prefix	character, "TOTAL " by default. It is a prefix to automatically created labels for nets and subtotals.
new_label	how we will combine original values for automatically generated subtotal labels. Possible values are "all", "range", "first", "last". "all" collapse all labels, "range" take only first and last label,
add	logical. Auxiliary argument. Should we add subtotal to categories or replace categories with a net?
data	intermediate table. See <a href="#">tables</a> .

### Value

multiple response set or list of the multiple response sets

### Examples

```

ol = c(1:7, 99)
var_lab(ol) = "Liking"
val_lab(ol) = num_lab("
    1 Disgusting
    2 Very Poor
    3 Poor
    4 So-so
    5 Good
    6 Very good
    7 Excellent
    99 Hard to say
")

cro(subtotal(ol, TOP = 6:7, BOTTOM = 1:3, position = "top"))
# autolabelling
cro(subtotal(ol, 6:7, 1:3))
# replace original codes and another way of autolabelling
cro(net(ol, 6:7, 1:3, new_label = "range", prefix = "NET "))

# character variable and criteria usage
items = c("apple", "banana", "potato", "orange", "onion", "tomato", "pineapple")
cro(
  subtotal(items,
    "TOTAL FRUITS" = like("*ap*") | like("*an*"),
    "TOTAL VEGETABLES" = like("*to*") | like("*on*"),
    position = "bottom")
)

# 'tab_net_*' usage
data(mtcars)
mtcars = apply_labels(mtcars,
  mpg = "Miles/(US) gallon",
  am = "Transmission",
  am = c("Automatic" = 0,

```

```

        "Manual"=1),
gear = "Number of forward gears",
gear = c(
  One = 1,
  Two = 2,
  Three = 3,
  Four = 4,
  Five = 5
)
)
mtcars %>%
  tab_cells(mpg) %>%
  tab_net_cells("Low mpg" = less(mean(mpg)), "High mpg" = greater_or_equal(mean(mpg))) %>%
  tab_cols(total(), am) %>%
  tab_stat_cases() %>%
  tab_pivot()

mtcars %>%
  tab_cells(mpg) %>%
  tab_rows(gear) %>%
  tab_subtotal_rows(1:2, 3:4, "5 and more" = greater(4)) %>%
  tab_stat_mean() %>%
  tab_pivot()

```

---

```
prepend_values
```

---

*Prepend values/variable names to value/variable labels*

---

## Description

These functions add values/variable names as prefixes to value/variable labels. Functions which start with `tab_` intended for usage inside table creation sequences. See examples and [tables](#). It is recommended to use `tab_prepend_*` at the start of sequence of tables creation. If you use it in the middle of the sequence then previous statements will not be affected.

## Usage

```
prepend_values(x)
```

```
prepend_names(x)
```

```
prepend_all(x)
```

```
tab_prepend_values(data)
```

```
tab_prepend_names(data)
```

```
tab_prepend_all(data)
```

**Arguments**

x                    vector/data.frame. prepend\_names can be applied only to data.frames.  
 data                data.frame/intermediate result of tables construction. See [tables](#).

**Value**

original object with prepended names/values to labels

**Examples**

```
data(mtcars)
mtcars = apply_labels(mtcars,
  mpg = "Miles/(US) gallon",
  cyl = "Number of cylinders",
  disp = "Displacement (cu.in.)",
  hp = "Gross horsepower",
  drat = "Rear axle ratio",
  wt = "Weight (lb/1000)",
  qsec = "1/4 mile time",
  vs = "Engine",
  vs = c("V-engine" = 0,
        "Straight engine" = 1),
  am = "Transmission",
  am = c("Automatic" = 0,
        "Manual"=1),
  gear = "Number of forward gears",
  carb = "Number of carburetors"
)

# prepend names and 'cro_cpct'
mtcars %>%
  prepend_names %>%
  calculate(
    cro_cpct(list(cyl, gear), list(total(), vs, am))
  )

# prepend values to value labels
mtcars %>%
  tab_prepend_values %>%
  tab_cols(total(), vs, am) %>%
  tab_cells(cyl, gear) %>%
  tab_stat_cpct() %>%
  tab_pivot()

# prepend names and labels
mtcars %>%
  tab_prepend_all %>%
  tab_cols(total(), vs, am) %>%
  tab_cells(cyl, gear) %>%
  tab_stat_cpct() %>%
  tab_pivot()
```

```
# variable in rows without prefixes
mtcars %>%
  tab_cells(cyl, gear) %>%
  tab_prepend_all %>%
  tab_cols(total(), vs, am) %>%
  tab_stat_cpct() %>%
  tab_pivot()
```

---

 product\_test

*Data from product test of chocolate confectionary*


---

## Description

It is truncated dataset with data from product test of two samples of chocolate sweets. 150 respondents tested two kinds of sweets (codenames: VSX123 and SDF546). Sample was divided into two groups (cells) of 75 respondents in each group. In cell 1 product VSX123 was presented first and then SDF546. In cell 2 sweets were presented in reversed order. Questions about respondent impressions about first product are in the block A (and about second tested product in the block B). At the end of the questionnaire there is a question about preferences between sweets.

## Usage

```
product_test
```

## Format

A data frame with 150 rows and 18 variables:

**id** Respondent Id.

**cell** First tested product (cell number).

**s2a** Age.

**a1\_1** What did you like in these sweets? Multiple response. First tested product.

**a1\_2** (continue) What did you like in these sweets? Multiple response. First tested product.

**a1\_3** (continue) What did you like in these sweets? Multiple response. First tested product.

**a1\_4** (continue) What did you like in these sweets? Multiple response. First tested product.

**a1\_5** (continue) What did you like in these sweets? Multiple response. First tested product.

**a1\_6** (continue) What did you like in these sweets? Multiple response. First tested product.

**a22** Overall liking. First tested product.

**b1\_1** What did you like in these sweets? Multiple response. Second tested product.

**b1\_2** (continue) What did you like in these sweets? Multiple response. Second tested product.

**b1\_3** (continue) What did you like in these sweets? Multiple response. Second tested product.

**b1\_4** (continue) What did you like in these sweets? Multiple response. Second tested product.

**b1\_5** (continue) What did you like in these sweets? Multiple response. Second tested product.

**b1\_6** (continue) What did you like in these sweets? Multiple response. Second tested product.

**b22** Overall liking. Second tested product.

**c1** Preferences.

---

**prop***Compute proportions from numeric vector/matrix/data.frame*

---

**Description**

prop returns proportion to sum of entire x. prop\_col returns proportion to sum of each column of x. prop\_row returns proportion to sum of each row of x. Non-numeric columns in the data.frame are ignored. NA's are also ignored.

**Usage**

```
prop(x)
```

```
prop_col(x)
```

```
prop_row(x)
```

**Arguments**

x                    numeric vector/matrix/data.frame

**Value**

the same structure as x but with proportions of original values from sum of original values.

**Examples**

```
a = c(25, 25, NA)
prop(a)

# data.frame with non-numeric columns
fac = factor(c("a", "b", "c"))
char = c("a", "b", "c")
dat = as.POSIXct("2016-09-27")
a = sheet(fac, a = c(25, 25, NA), b = c(100, NA, 50), char, dat)

prop(a)
prop_row(a)
prop_col(a)

# the same as result as with 'prop.table'
tbl = table(state.division, state.region)

prop(tbl)
prop_row(tbl)
prop_col(tbl)
```

---

qc *Create vector of characters from unquoted strings (variable names)*

---

### Description

- qc It is often needed to address variables in the data.frame in the such manner: `dfs[ , c("var1", "var2", "var3")]`. qc ("quoted c") is a shortcut for the such cases to reduce keystrokes. With qc you can write: `dfs[ , qc(var1, var2, var3)]`.
- qe returns list of expression. It is useful to create substitution list for `..$arg`.
- text\_expand is simple string interpolation function. It searches in its arguments expressions in curly brackets {expr}, evaluate them and substitute with the result of evaluation. See examples.

### Usage

```
qc(...)

qe(...)

text_expand(..., delim = c("\\{", "\\}")

subst(...)
```

### Arguments

...	characters in text_expand, unquoted names of variables in qc or unquoted expressions in qe.
delim	character vector of length 2 - pair of opening and closing delimiters for the templating tags. By default it is curly brackets. Note that delim will be used in the perl-style regular expression so you need to escape special characters, e. g. use "\\{" instead of "\{".

### Value

Vector of characters

### Examples

```
## qc
qc(a, b, c)
identical(qc(a, b, c), c("a", "b", "c"))

mtcars[, qc(am, mpg, gear)]

## text_expand
i = 1:5
```

```
text_expand("q{i}")

i = 1:3
j = 1:3
text_expand("q1_{i}_{j}")

data(iris)
text_expand("'iris' has {nrow(iris)} rows.")

## qe
qe(mrset(a1 %to% a6), mrset(b1 %to% b6), mrset(c1 %to% c6))
```

---

read\_spss

*Read an SPSS Data File*

---

## Description

`read_spss` reads data from a file stored in SPSS \*.sav format. It returns data.frame and never converts string variables to factors. Also it prepares SPSS values/variables labels for working with `val_lab/var_lab` functions. User-missings values are ignored. `read_spss` is simple wrapper around `read.spss` function from package `foreign`.

## Usage

```
read_spss(file, reencode = TRUE)

read_spss_to_list(file, reencode = TRUE)
```

## Arguments

<code>file</code>	Character string: the name of the file or URL to read.
<code>reencode</code>	logical: should character strings be re-encoded to the current locale. The default is TRUE. NA means to do so in a UTF-8 locale, only. Alternatively, a character string specifying an encoding to assume for the file.

## Value

`read_spss` returns data.frame.

`read_spss_to_list` returns list of variables from SPSS files.

## See Also

[read.spss](#) in package `foreign`, [val\\_lab](#), [var\\_lab](#)

**Examples**

```
## Not run:

w = read_spss("project_123.sav") # to data.frame
list_w = read_spss_to_list("project_123.sav") # to list

## End(Not run)
```

---

recode	<i>Change, rearrange or consolidate the values of an existing or new variable. Inspired by the RECODE command from SPSS.</i>
--------	--

---

**Description**

recode change, rearrange or consolidate the values of an existing variable based on conditions. Design of this function inspired by RECODE from SPSS. Sequence of recodings provided in the form of formulas. For example, 1:2 ~ 1 means that all 1's and 2's will be replaced with 1. Each value will be recoded only once. In the assignment form `recode(...)` = ... of this function values which doesn't meet any condition remain unchanged. In case of the usual form ... = `recode(...)` values which doesn't meet any condition will be replaced with NA. One can use values or more sophisticated logical conditions and functions as a condition. There are several special functions for usage as criteria - for details see [criteria](#). Simple common usage looks like: `recode(x, 1:2 ~ -1, 3 ~ 0, 1:2 ~ 1, 99 ~ NA)`. For more information, see details and examples. The `ifs` function checks whether one or more conditions are met and returns a value that corresponds to the first TRUE condition. `ifs` can take the place of multiple nested `ifelse` statements and is much easier to read with multiple conditions. `ifs` works in the same manner as `recode` - e. g. with formulas. But conditions should be only logical and it doesn't operate on multicolumn objects.

**Usage**

```
recode(x, ..., with_labels = FALSE, new_label = c("all", "range",
  "first", "last"))

rec(x, ..., with_labels = TRUE, new_label = c("all", "range", "first",
  "last"))

recode(x, with_labels = FALSE, new_label = c("all", "range", "first",
  "last")) <- value

rec(x, with_labels = TRUE, new_label = c("all", "range", "first",
  "last")) <- value

ifs(...)

lo
```

```

hi
copy(x)
from_to(from, to)
values %into% names

```

### Arguments

<code>x</code>	vector/matrix/data.frame/list
<code>...</code>	sequence of formulas which describe recodings. They are used when <code>from/to</code> arguments are not provided.
<code>with_labels</code>	logical. FALSE by default for 'recode' and TRUE for 'rec'. Should we also recode value labels with the same recodings as variable?
<code>new_label</code>	one of "all", "range", "first", or "last". If we recode value labels ('with_labels = TRUE') how we will combine labels for duplicated values? "all" will use all labels, "range" will use first and last labels. See examples.
<code>value</code>	list with formulas which describe recodings in assignment form of function/to list if <code>from/to</code> notation is used.
<code>from</code>	list of conditions for values which should be recoded (in the same format as LHS of formulas).
<code>to</code>	list of values into which old values should be recoded (in the same format as RHS of formulas).
<code>values</code>	object(-s) which will be assigned to names for %into% operation. %into% supports multivalue assignments. See examples.
<code>names</code>	name(-s) which will be given to values expression. For %into%.

### Format

An object of class numeric of length 1.

### Details

Input conditions - possible values for left-hand side (LHS) of formula or element of `from` list:

- vector/single value All values in `x` which equal to elements of the vector in LHS will be replaced with RHS.
- logical vector All elements in `x` for which elements of vector in LHS is TRUE will be replaced with RHS. It means you can use logical condition on the other variable during recoding.
- function Values for which function gives TRUE will be replaced with RHS. There are some special functions for the convenience - see [criteria](#).
- single logical value TRUE It means all other unrecoded values (ELSE in SPSS RECODE). All other unrecoded values will be changed to RHS of the formula or appropriate element of `to`.

Output values - possible values for right-hand side (RHS) of formula or element of `to` list:

- value replace elements of  $x$ . This value will be recycled across rows and columns of  $x$ .
- vector values of this vector will replace values in the corresponding position in rows of  $x$ . Vector will be recycled across columns of  $x$ .
- function This function will be applied to values of  $x$  which satisfy recoding condition. There is a special auxiliary function `copy` which just returns its argument. So, in the `recode` it just copies old value (`COPY` in SPSS `RECODE`). See examples.

`%into%` tries to mimic SPSS 'INTO'. Values from left-hand side will be assigned to right-hand side. You can use `%to%` expression in the RHS of `%into%`. See examples. `lo` and `hi` are shortcuts for `-Inf` and `Inf`. They can be useful in expressions with `%thru%`, e. g. `1 %thru% hi`.

## Value

object of the same form as  $x$  with recoded values

## Examples

```
# some examples from SPSS manual
# RECODE V1 TO V3 (0=1) (1=0) (2, 3=-1) (9=9) (ELSE=SYSMIS)
v1 = c(0, 1, 2, 3, 9, 10)
recode(v1) = c(0 ~ 1, 1 ~ 0, 2:3 ~ -1, 9 ~ 9, TRUE ~ NA)
v1

# RECODE QVAR(1 THRU 5=1)(6 THRU 10=2)(11 THRU HI=3)(ELSE=0).
qvar = c(1:20, 97, NA, NA)
recode(qvar, 1 %thru% 5 ~ 1, 6 %thru% 10 ~ 2, 11 %thru% hi ~ 3, TRUE ~ 0)
# the same result
recode(qvar, 1 %thru% 5 ~ 1, 6 %thru% 10 ~ 2, ge(11) ~ 3, TRUE ~ 0)

# RECODE STRNGVAR ('A', 'B', 'C'='A')('D', 'E', 'F'='B')(ELSE=' ').
strngvar = LETTERS
recode(strngvar, c('A', 'B', 'C') ~ 'A', c('D', 'E', 'F') ~ 'B', TRUE ~ ' ')

# recode in place. Note that we recode only first six letters
recode(strngvar) = c(c('A', 'B', 'C') ~ 'A', c('D', 'E', 'F') ~ 'B')
strngvar

# RECODE AGE (MISSING=9) (18 THRU HI=1) (0 THRU 18=0) INTO VOTER.
age = c(NA, 2:40, NA)
voter = recode(age, NA ~ 9, 18 %thru% hi ~ 1, 0 %thru% 18 ~ 0)
voter
# the same result with '%into%'
recode(age, NA ~ 9, 18 %thru% hi ~ 1, 0 %thru% 18 ~ 0) %into% voter2
voter2
# recode with adding labels
voter = recode(age, "Refuse to answer" = NA ~ 9,
                "Vote" = 18 %thru% hi ~ 1,
                "Don't vote" = 0 %thru% 18 ~ 0)
voter

# recoding with labels
ol = c(1:7, 99)
```

```

var_lab(ol) = "Liking"
val_lab(ol) = num_lab("
    1 Disgusting
    2 Very Poor
    3 Poor
    4 So-so
    5 Good
    6 Very good
    7 Excellent
    99 Hard to say
")

recode(ol, 1:3 ~ 1, 5:7 ~ 7, TRUE ~ copy, with_labels = TRUE)
# 'rec' is a shortcut for recoding with labels. Same result:
rec(ol, 1:3 ~ 1, 5:7 ~ 7, TRUE ~ copy)
# another method of combining labels
recode(ol, 1:3 ~ 1, 5:7 ~ 7, TRUE ~ copy, with_labels = TRUE, new_label = "range")
# example with from/to notation
# RECODE QVAR(1 THRU 5=1)(6 THRU 10=2)(11 THRU HI=3)(ELSE=0).
list_from = list(1 %thru% 5, 6 %thru% 10, ge(11), TRUE)
list_to = list(1, 2, 3, 0)
recode(qvar, from_to(list_from, list_to))

list_from = list(NA, 18 %thru% hi, 0 %thru% 18)
list_to = list("Refuse to answer" = 9, "Vote" = 1, "Don't vote" = 0)
voter = recode(age, from_to(list_from, list_to))
voter

# 'ifs' examples
a = 1:5
b = 5:1
ifs(b>3 ~ 1) # c(1, 1, NA, NA, NA)
ifs(b>3 ~ 1, TRUE ~ 3) # c(1, 1, 3, 3, 3)
ifs(b>3 ~ 1, a>4 ~ 7, TRUE ~ 3) # c(1, 1, 3, 3, 7)
ifs(b>3 ~ a, TRUE ~ 42) # c(1, 2, 42, 42, 42)

# advanced usage
#' # multiple assignment with '%into%'
set.seed(123)
x1 = runif(30)
x2 = runif(30)
x3 = runif(30)
# note nessesary brackets around RHS of '%into%'
recode(x1 %to% x3, gt(0.5) ~ 1, other ~ 0) %into% (x_rec_1 %to% x_rec_3)
fre(x_rec_1)
# the same operation with characters expansion
i = 1:3
recode(x1 %to% x3, gt(0.5) ~ 1, other ~ 0) %into% text_expand('x_rec2_{i}')
fre(x_rec2_1)

# factor recoding
a = factor(letters[1:4])

```

```

recode(a, "a" ~ "z", TRUE ~ copy) # we get factor

# example with function in RHS
data(iris)
new_iris = recode(iris, is.numeric ~ scale, other ~ copy)
str(new_iris)

set.seed(123)
a = rnorm(20)
# if a<(-0.5) we change it to absolute value of a (abs function)
recode(a, lt(-0.5) ~ abs, other ~ copy)

# the same example with logical criteria
recode(a, a<(-.5) ~ abs, other ~ copy)

```

---

ref

---

*Auxiliary functions to pass arguments to function by reference*


---

### Description

These two functions aimed to simplify build functions with side-effects (e. g. for modifying variables in place). Of course it is not the R way of doing things but sometimes it can save several keystrokes.

### Usage

```

ref(x)

ref(x) <- value

```

### Arguments

x	Reference to variable, it is formula, ~var_name.
value	Value that should be assigned to modified variable.

### Details

To create reference to variable one can use formula: `b = ~a`. `b` is reference to `a`. So `ref(b)` returns value of `a` and `ref(b) = new_val` will modify `a`. If argument `x` of these functions is not formula then these functions have no effect e. g. `ref(a)` is identical to `a` and after `ref(a) = value` `a` is identical to `value`. It is not possible to use function as argument `x` in assignment form. For example, `ref(some_function(x)) = some_value` will rise error. Use `y = some_function(x); ref(y) = some_value` instead.

### Value

`ref` returns value of referenced variable. `ref<-` modifies referenced variable.

## Examples

```
# Simple example
a = 1:3
b = ~a # b is reference to 'a'
identical(ref(b),a) # TRUE

ref(b)[2] = 4 # here we modify 'a'
identical(a, c(1,4,3)) # TRUE

# usage inside function

# top 10 rows
head10 = function(x){
  ds = head(ref(x), 10)
  ref(x) = ds
  invisible(ds) # for usage without references
}

data(iris)
ref_to_iris = ~iris
head10(ref_to_iris) # side-effect
nrow(iris) # 10

# argument is not formula - no side-effect
data(mtcars)
mtcars10 = head10(mtcars)

nrow(mtcars10) # 10
nrow(mtcars) # 32
```

---

set\_caption

*Add caption to the table*

---

## Description

To drop caption use `set_caption` with `caption = NULL`. Captions are supported by [htmlTable.etable](#), [xl\\_write](#) and [as.datatable\\_widget](#) functions.

## Usage

```
set_caption(obj, caption)
```

```
get_caption(obj)
```

```
is.with_caption(obj)
```

**Arguments**

obj                    object of class etable - result of cro\_cpct and etc.  
caption                character caption for the table.

**Value**

object of class with\_caption.

**Examples**

```
data(mtcars)
mtcars = apply_labels(mtcars,
                      vs = "Engine",
                      vs = num_lab("
                                0 V-engine
                                1 Straight engine
                                "),
                      am = "Transmission",
                      am = num_lab("
                                0 Automatic
                                1 Manual
                                ")
)
tbl_with_caption = calc_cro(mtcars, am, vs) %>%
  set_caption("Table 1. Type of transmission.")

tbl_with_caption
```

---

sheet	<i>Make data.frame without conversion to factors and without fixing names</i>
-------	---

---

**Description**

sheet and as.sheet are shortcuts to data.frame and as.data.frame with stringsAsFactors = FALSE, check.names = FALSE. .sheet is the same as above but works in the scope of default dataset.

**Usage**

```
sheet(...)

as.sheet(x, ...)
```

.sheet(...)

**Arguments**

... objects, possibly named  
x object to be coerced to data.frame

**Value**

data.frame/list

**See Also**

[default\\_dataset](#), [data.frame](#), [as.data.frame](#)

**Examples**

```
# see the difference
df1 = data.frame(a = letters[1:3], "This is my long name" = 1:3)
df2 = sheet(a = letters[1:3], "This is my long name" = 1:3)

str(df1)
str(df2)

data(iris)
default_dataset(iris)

.sheet(Sepal.Width, Sepal.Length)
```

---

sort\_asc

*Sort data.frames/matrices/vectors*

---

**Description**

sort\_asc sorts in ascending order and sort\_desc sorts in descending order. .sort\_asc/.sort\_desc are versions for working with [default\\_dataset](#).

**Usage**

```
sort_asc(data, ..., na.last = FALSE)

.sort_asc(..., na.last = FALSE)

sort_desc(data, ..., na.last = TRUE)

.sort_desc(..., na.last = TRUE)
```

**Arguments**

data	data.frame/matrix/vector
...	character/numeric or criteria/logical functions (see <a href="#">criteria</a> ). Column names/numbers for data.frame/matrix by which object will be sorted. Names at the top-level can be unquoted (non-standard evaluation). For standard evaluation of parameters you can surround them by round brackets. See examples. Ignored for vectors.
na.last	for controlling the treatment of NAs. If TRUE, missing values in the data are put last; if FALSE, they are put first; if NA, they are removed.

**Value**

sorted data

**Examples**

```
data(mtcars)
sort_asc(mtcars, mpg)
sort_asc(mtcars, cyl, mpg) # by two column

# same results with column nums
sort_asc(mtcars, 1)
sort_asc(mtcars, 2:1) # by two column
sort_asc(mtcars, 2, 1) # by two column

# call with parameter
sorting_columns = c("cyl", "mpg")
sort_asc(mtcars, (sorting_columns))
```

---

split_by	<i>Splits data.frame into list of data.frames that can be analyzed separately</i>
----------	---

---

**Description**

Splits data.frame into list of data.frames that can be analyzed separately. These data.frames are sets of cases that have the same values for the specified split variables. Any missing values in split variables are dropped together with the corresponding values of data. split\_off works with lists of data.frames or objects that can be coerced to data.frame and assumed to have compatible structure. Resulting rows will be sorted in order of the split variables.

**Usage**

```
split_by(data, ..., drop = TRUE)

split_separate(data, ..., drop = TRUE)

split_off(data, groups = NULL, rownames = NULL)
```

**Arguments**

data	data.frame for split_by/list for split_off
...	unquoted variables names (see <a href="#">keep</a> ) by which data will be split into list.
drop	should we drop combination of levels with zero observation? TRUE by default.
groups	character If it is not NULL then we add list names as variable to result of split_off with the name specified by groups. If it is TRUE then name will be .groups.
rownames	character If it is not NULL then we add data.frames rownames as variable to result of split_off with the name specified by rownames. If it is TRUE then name will be .rownames.

**Value**

split\_by returns list of data.frames/split\_off returns data.frame

**See Also**

[split](#), [compute](#), [calculate](#), [do\\_repeat](#), [where](#)

**Examples**

```
# example from base R 'split'
data(airquality)
airquality2 = airquality %>%
  split_by(Month) %>%
  compute({
    Ozone_zscore = scale(Ozone)
  }) %>%
  split_off()

head(airquality2)

# usage of 'groups', 'rownames'
data(mtcars)
# add labels to dataset
mtcars %>%
  apply_labels(mpg = "Miles/(US) gallon",
              disp = "Displacement (cu.in.)",
              wt = "Weight",
              hp = "Gross horsepower",
              vs = "Engine",
              vs = num_lab("
                                0 V-engine
                                1 Straight engine
                              "),
              am = "Transmission",
              am = num_lab("
                                0 Automatic
                                1 Manual
                              ")
```

```

) %>%
split_by(am, vs) %>%
use_labels({
  res = lm(mpg ~ hp + disp + wt)
  cbind(Coef. = coef(res), confint(res))
}) %>%
split_off(groups = TRUE, rownames = "variable")

```

---

split\_labels

*Split character vector to matrix/split columns in data.frame*


---

## Description

split\_labels/split\_columns are auxiliary functions for post-processing tables resulted from [cro/cro\\_fun](#) and etc. In these tables all labels collapsed in the first column with "|" separator. split\_columns split first column into multiple columns with separator (split argument). split\_table\_to\_df split first column of table and column names. Result of this operation is data.frame with character columns.

## Usage

```
split_labels(x, remove_repeated = TRUE, split = "\\|",
  fixed = FALSE, perl = FALSE)
```

```
split_columns(data, columns = 1, remove_repeated = TRUE,
  split = "\\|", fixed = FALSE, perl = FALSE)
```

```
split_table_to_df(data, digits = get_expss_digits(),
  remove_repeated = TRUE, split = "\\|", fixed = FALSE,
  perl = FALSE)
```

```
make_subheadings(data, number_of_columns = 1)
```

## Arguments

x	character vector which will be split
remove_repeated	logical. Default is TRUE. Should we remove repeated labels?
split	character vector (or object which can be coerced to such) containing regular expression(s) (unless fixed = TRUE) to use for splitting.
fixed	logical. If TRUE match split exactly, otherwise use regular expressions. Has priority over perl.
perl	logical. Should Perl-compatible regexps be used?
data	data.frame vector which will be split
columns	character/numeric/logical columns in the data.frame data which should be split
digits	numeric. How many digits after decimal point should be left in split_table_to_df?

number\_of\_columns

integer. Number of columns from row labels which will be used as subheadings in table.

### Value

split\_labels returns character matrix, split\_columns returns data.frame with columns replaced by possibly multiple columns with split labels. split\_table\_to\_df returns data.frame with character columns.

### See Also

[strsplit](#)

### Examples

```
data(mtcars)

# apply labels
mtcars = apply_labels(mtcars,
  cyl = "Number of cylinders",
  vs = "Engine",
  vs = c("V-engine" = 0,
        "Straight engine" = 1),
  am = "Transmission",
  am = c(automatic = 0,
        manual=1),
  gear = "Number of forward gears",
  carb = "Number of carburetors"
)

# all row labels in the first column
tabl = mtcars %>%
  calculate(cro_cpct(list(cyl, gear, carb), list(total(), vs, am)))

tabl # without subheadings

make_subheadings(tabl) # with subheadings

split_labels(tabl[[1]])
split_labels(colnames(tabl))

# replace first column with new columns
split_columns(tabl) # remove repeated

split_columns(tabl, remove_repeated = FALSE)

split_columns(tabl)

split_table_to_df(tabl)

split_table_to_df(tabl)
```

---

sum_row	<i>Compute sum/mean/sd/median/max/min/custom function on rows/columns</i>
---------	---

---

### Description

These functions are intended for usage inside [modify](#), [modify\\_if](#), [with](#) and [within](#) functions. `sum/mean/sd/median/max/min` by default omits NA. `any_in_*` checks existence of any TRUE in each row/column. It is equivalent of [any](#) applied to each row/column. `all_in_*` is equivalent of [all](#) applied to each row/column.

### Usage

```
sum_row(..., na.rm = TRUE)
```

```
sum_col(..., na.rm = TRUE)
```

```
mean_row(..., na.rm = TRUE)
```

```
mean_col(..., na.rm = TRUE)
```

```
sd_row(..., na.rm = TRUE)
```

```
sd_col(..., na.rm = TRUE)
```

```
median_row(..., na.rm = TRUE)
```

```
median_col(..., na.rm = TRUE)
```

```
max_row(..., na.rm = TRUE)
```

```
max_col(..., na.rm = TRUE)
```

```
min_row(..., na.rm = TRUE)
```

```
min_col(..., na.rm = TRUE)
```

```
apply_row(fun, ...)
```

```
apply_col(fun, ...)
```

```
any_in_row(..., na.rm = TRUE)
```

```
any_in_col(..., na.rm = TRUE)
```

```
all_in_row(..., na.rm = TRUE)
```

```
all_in_col(..., na.rm = TRUE)
```

### Arguments

...	data. Vectors, matrixes, data.frames, list. Shorter arguments will be recycled.
na.rm	logical. Contrary to the base 'sum' it is TRUE by default. Should missing values (including NaN) be removed?
fun	custom function that will be applied to ...

### Value

All functions except `apply_*` return numeric vector of length equals the number of argument columns/rows. Value of `apply_*` depends on supplied fun function.

### See Also

[modify](#), [modify\\_if](#), [%to%](#), [count\\_if](#), [sum\\_if](#), [mean\\_if](#), [median\\_if](#), [sd\\_if](#), [min\\_if](#), [max\\_if](#)

### Examples

```
## Inside example
iris = compute(iris,{
  new_median = median_row(Sepal.Length, Sepal.Width, Petal.Length, Petal.Width)
  new_mean = mean_row(Sepal.Length, Sepal.Width, Petal.Length, Petal.Width)
})

dfs = data.frame(
  test = 1:5,
  aa = rep(10, 5),
  b_ = rep(20, 5),
  b_1 = rep(11, 5),
  b_2 = rep(12, 5),
  b_4 = rep(14, 5),
  b_5 = rep(15, 5)
)

# calculate sum of b* variables
compute(dfs, {
  b_total = sum_row(b_, b_1 %to% b_5)
})

# conditional modification
do_if(dfs, test %in% 2:4, {
  b_total = sum_row(b_, b_1 %to% b_5)
})
```

tables

*Functions for custom tables construction***Description**

Table construction consists of at least of three functions chained with magrittr pipe operator: `%>%`. At first we need to specify variables for which statistics will be computed with `tab_cells`. Secondary, we calculate statistics with one of `tab_stat_*` functions. And last, we finalize table creation with `tab_pivot`: `dataset %>% tab_cells(variable) %>% tab_stat_cases() %>% tab_pivot()`. After that we can optionally sort table with `tab_sort_asc`, drop empty rows/columns with `drop_rc` and transpose with `tab_transpose`. Generally, table is just a data.frame so we can use arbitrary operations on it. Statistic is always calculated with the last cell, column/row variables, weight, missing values and subgroup. To define new cell/column/row variables we can call appropriate function one more time. `tab_pivot` defines how we combine different statistics and where statistic labels will appear - inside/outside rows/columns. See examples. For significance testing see [significance](#).

**Usage**

```
tab_cols(data, ...)

tab_cells(data, ...)

tab_rows(data, ...)

tab_weight(data, weight = NULL)

tab_mis_val(data, ...)

tab_total_label(data, ...)

tab_total_statistic(data, ...)

tab_total_row_position(data, total_row_position = c("below", "above",
  "none"))

tab_subgroup(data, subgroup = NULL)

tab_row_label(data, ..., label = NULL)

tab_stat_fun(data, ..., label = NULL, unsafe = FALSE)

tab_stat_mean_sd_n(data, weighted_valid_n = FALSE, labels = c("Mean",
  "Std. dev.", ifelse(weighted_valid_n, "Valid N", "Unw. valid N")),
  label = NULL)

tab_stat_mean(data, label = "Mean")
```

```
tab_stat_median(data, label = "Median")
tab_stat_se(data, label = "S. E.")
tab_stat_sum(data, label = "Sum")
tab_stat_min(data, label = "Min.")
tab_stat_max(data, label = "Max.")
tab_stat_sd(data, label = "Std. dev.")
tab_stat_valid_n(data, label = "Valid N")
tab_stat_unweighted_valid_n(data, label = "Unw. valid N")
tab_stat_fun_df(data, ..., label = NULL, unsafe = FALSE)
tab_stat_cases(data, total_label = NULL, total_statistic = "u_cases",
  total_row_position = c("below", "above", "none"), label = NULL)
tab_stat_cpct(data, total_label = NULL, total_statistic = "u_cases",
  total_row_position = c("below", "above", "none"), label = NULL)
tab_stat_cpct_responses(data, total_label = NULL,
  total_statistic = "u_responses", total_row_position = c("below",
  "above", "none"), label = NULL)
tab_stat_tpct(data, total_label = NULL, total_statistic = "u_cases",
  total_row_position = c("below", "above", "none"), label = NULL)
tab_stat_rpct(data, total_label = NULL, total_statistic = "u_cases",
  total_row_position = c("below", "above", "none"), label = NULL)
tab_last_vstack(data, stat_position = c("outside_rows", "inside_rows"),
  stat_label = c("inside", "outside"), label = NULL)
tab_last_hstack(data, stat_position = c("outside_columns",
  "inside_columns"), stat_label = c("inside", "outside"), label = NULL)
tab_pivot(data, stat_position = c("outside_rows", "inside_rows",
  "outside_columns", "inside_columns"), stat_label = c("inside",
  "outside"))
tab_transpose(data)
```

### Arguments

data                    data.frame/intermediate\_table

...	vector/data.frame/list. Variables for tables. Use <a href="#">mrset/mdset</a> for multiple-response variables.
weight	numeric vector in <code>tab_weight</code> . Cases with NA's, negative and zero weights are removed before calculations.
total_row_position	Position of total row in the resulting table. Can be one of "below", "above", "none".
subgroup	logical vector in <code>tab_subgroup</code> . You can specify subgroup on which table will be computed.
label	character. Label for the statistic in the <code>tab_stat_*</code> .
unsafe	logical If TRUE than <code>fun</code> will be evaluated as is. It can lead to significant increase in the performance. But there are some limitations. For <code>tab_stat_fun</code> it means that your function <code>fun</code> should return vector of length one. Also there will be no attempts to make labels for statistic. For <code>tab_stat_fun_df</code> your function should return vector of length one or list/data.frame (optionally with 'row_labels' element - statistic labels). If <code>unsafe</code> is TRUE then further arguments (...) for <code>fun</code> will be ignored.
weighted_valid_n	logical. Should we show weighted valid N in <code>tab_stat_mean_sd_n</code> ? By default it is FALSE.
labels	character vector of length 3. Labels for mean, standard deviation and valid N in <code>tab_stat_mean_sd_n</code> .
total_label	By default "#Total". You can provide several names - each name for each total statistics.
total_statistic	By default it is "u_cases" (unweighted cases). Possible values are "u_cases", "u_responses", "u_cpct", "u_rpct", "u_tpct", "w_cases", "w_responses", "w_cpct", "w_rpct", "w_tpct". "u_" means unweighted statistics and "w_" means weighted statistics.
stat_position	character one of the values "outside_rows", "inside_rows", "outside_columns" or "inside_columns". It defines how we will combine statistics in the table.
stat_label	character one of the values "inside" or "outside". Where will be placed labels for the statistics relative to column names/row labels? See examples.

### Details

- `tab_cells` variables on which percentage/cases/summary functions will be computed. Use [mrset/mdset](#) for multiple-response variables.
- `tab_cols` optional variables which breaks table by columns. Use [mrset/mdset](#) for multiple-response variables.
- `tab_rows` optional variables which breaks table by rows. Use [mrset/mdset](#) for multiple-response variables.
- `tab_weight` optional weight for the statistic.
- `tab_mis_val` optional missing values for the statistic. It will be applied on variables specified by `tab_cells`. It works in the same manner as [na\\_if](#).

- `tab_subgroup` optional logical vector/expression which specify subset of data for table.
- `tab_row_label` Add to table empty row with specified row labels. It is useful for making section headings and etc.
- `tab_total_row_position` Default value for `total_row_position` argument in `tab_stat_cases` and etc. Can be one of "below", "above", "none".
- `tab_total_label` Default value for `total_label` argument in `tab_stat_cases` and etc. You can provide several names - each name for each total statistics.
- `tab_total_statistic` Default value for `total_statistic` argument in `tab_stat_cases` and etc. You can provide several values. Possible values are "u\_cases", "u\_responses", "u\_cpct", "u\_rpct", "u\_tpct", "w\_cases", "w\_responses", "w\_cpct", "w\_rpct", "w\_tpct". "u\_" means unweighted statistics and "w\_" means weighted statistics.
- `tab_stat_fun`, `tab_stat_fun_df` `tab_stat_fun` applies function on each variable in cells separately, `tab_stat_fun_df` gives to function each data.frame in cells as a whole [data.table](#) with all names converted to variable labels (if labels exists). So it is not recommended to rely on original variables names in your fun. For details see [cro\\_fun](#). You can provide several functions as arguments. They will be combined as with [combine\\_functions](#). So you can use method argument. For details see documentation for [combine\\_functions](#).
- `tab_stat_cases` calculate counts.
- `tab_stat_cpct`, `tab_stat_cpct_responses` calculate column percent. These functions give different results only for multiple response variables. For `tab_stat_cpct` base of percent is number of valid cases. Case is considered as valid if it has at least one non-NA value. So for multiple response variables sum of percent may be greater than 100. For `tab_stat_cpct_responses` base of percent is number of valid responses. Multiple response variables can have several responses for single case. Sum of percent of `tab_stat_cpct_responses` always equals to 100%.
- `tab_stat_rpct` calculate row percent. Base for percent is number of valid cases.
- `tab_stat_tpct` calculate table percent. Base for percent is number of valid cases.
- `tab_stat_mean`, `tab_stat_median`, `tab_stat_se`, `tab_stat_sum`, `tab_stat_min`, `tab_stat_max`, `tab_stat_sd`, `tab_stat_valid_n`, `tab_stat_unweighted_valid_n` different summary statistics. NA's are always omitted.
- `tab_pivot` finalize table creation and define how different `tab_stat_*` will be combined
- `tab_transpose` transpose final table after `tab_pivot` or last statistic.

### Value

All of these functions return object of class `intermediate_table` except `tab_pivot` which returns final result - object of class `etable`. Basically it's a data.frame but class is needed for custom methods.

### See Also

[fre](#), [cro](#), [cro\\_fun](#), [tab\\_sort\\_asc](#), [drop\\_empty\\_rows](#), [significance](#).

**Examples**

```

data(mtcars)
mtcars = apply_labels(mtcars,
                      mpg = "Miles/(US) gallon",
                      cyl = "Number of cylinders",
                      disp = "Displacement (cu.in.)",
                      hp = "Gross horsepower",
                      drat = "Rear axle ratio",
                      wt = "Weight (1000 lbs)",
                      qsec = "1/4 mile time",
                      vs = "Engine",
                      vs = c("V-engine" = 0,
                             "Straight engine" = 1),
                      am = "Transmission",
                      am = c("Automatic" = 0,
                             "Manual"=1),
                      gear = "Number of forward gears",
                      carb = "Number of carburetors"
)
# some examples from 'cro'
# simple example - generally with 'cro' it can be made with less typing
mtcars %>%
  tab_cells(cyl) %>%
  tab_cols(vs) %>%
  tab_stat_cpct() %>%
  tab_pivot()

# split rows
mtcars %>%
  tab_cells(cyl) %>%
  tab_cols(vs) %>%
  tab_rows(am) %>%
  tab_stat_cpct() %>%
  tab_pivot()

# multiple banners
mtcars %>%
  tab_cells(cyl) %>%
  tab_cols(total(), vs, am) %>%
  tab_stat_cpct() %>%
  tab_pivot()

# nested banners
mtcars %>%
  tab_cells(cyl) %>%
  tab_cols(total(), vs %nest% am) %>%
  tab_stat_cpct() %>%
  tab_pivot()

# summary statistics
mtcars %>%
  tab_cells(mpg, disp, hp, wt, qsec) %>%

```

```

    tab_cols(am) %>%
    tab_stat_fun(Mean = w_mean, "Std. dev." = w_sd, "Valid N" = w_n) %>%
    tab_pivot()

# summary statistics - labels in columns
mtcars %>%
  tab_cells(mpg, disp, hp, wt, qsec) %>%
  tab_cols(am) %>%
  tab_stat_fun(Mean = w_mean, "Std. dev." = w_sd, "Valid N" = w_n, method = list) %>%
  tab_pivot()

# subgroup with dropping empty columns
mtcars %>%
  tab_subgroup(am == 0) %>%
  tab_cells(cyl) %>%
  tab_cols(total(), vs %nest% am) %>%
  tab_stat_cpct() %>%
  tab_pivot() %>%
  drop_empty_columns()

# total position at the top of the table
mtcars %>%
  tab_cells(cyl) %>%
  tab_cols(total(), vs) %>%
  tab_rows(am) %>%
  tab_stat_cpct(total_row_position = "above",
                total_label = c("number of cases", "row %"),
                total_statistic = c("u_cases", "u_rpct")) %>%
  tab_pivot()

# this example cannot be made easily with 'cro'
mtcars %>%
  tab_cells(am) %>%
  tab_cols(total(), vs) %>%
  tab_total_row_position("none") %>%
  tab_stat_cpct(label = "col %") %>%
  tab_stat_rpct(label = "row %") %>%
  tab_stat_tpct(label = "table %") %>%
  tab_pivot(stat_position = "inside_rows")

# statistic labels inside columns
mtcars %>%
  tab_cells(am) %>%
  tab_cols(total(), vs) %>%
  tab_total_row_position("none") %>%
  tab_stat_cpct(label = "col %") %>%
  tab_stat_rpct(label = "row %") %>%
  tab_stat_tpct(label = "table %") %>%
  tab_pivot(stat_position = "inside_columns")

# stacked statistics
mtcars %>%
  tab_cells(cyl) %>%

```

```

    tab_cols(total(), am) %>%
    tab_stat_mean() %>%
    tab_stat_se() %>%
    tab_stat_valid_n() %>%
    tab_stat_cpct() %>%
    tab_pivot()

# stacked statistics with section headings
mtcars %>%
  tab_cells(cyl) %>%
  tab_cols(total(), am) %>%
  tab_row_label("#Summary statistics") %>%
  tab_stat_mean() %>%
  tab_stat_se() %>%
  tab_stat_valid_n() %>%
  tab_row_label("#Column percent") %>%
  tab_stat_cpct() %>%
  tab_pivot()

# stacked statistics with different variables
mtcars %>%
  tab_cols(total(), am) %>%
  tab_cells(mpg, hp, qsec) %>%
  tab_stat_mean() %>%
  tab_cells(cyl, carb) %>%
  tab_stat_cpct() %>%
  tab_pivot()

# stacked statistics - label position outside row labels
mtcars %>%
  tab_cells(cyl) %>%
  tab_cols(total(), am) %>%
  tab_stat_mean() %>%
  tab_stat_se() %>%
  tab_stat_valid_n() %>%
  tab_stat_cpct(label = "Col %") %>%
  tab_pivot(stat_label = "outside")

# example from 'cro_fun_df' - linear regression by groups with sorting
mtcars %>%
  tab_cells(sheet(mpg, disp, hp, wt, qsec)) %>%
  tab_cols(total(), am) %>%
  tab_stat_fun_df(
    function(x){
      frm = reformulate(".", response = names(x)[1])
      model = lm(frm, data = x)
      sheet('Coef. estimate' = coef(model),
            confint(model)
          )
    }
  ) %>%
  tab_pivot() %>%
  tab_sort_desc()

```

```

# multiple-response variables and weight
data(product_test)
codeframe_likes = num_lab("
    1 Liked everything
    2 Disliked everything
    3 Chocolate
    4 Appearance
    5 Taste
    6 Stuffing
    7 Nuts
    8 Consistency
    98 Other
    99 Hard to answer
")

set.seed(1)
product_test = compute(product_test, {
  # recode age by groups
  age_cat = recode(s2a, lo %thru% 25 ~ 1, lo %thru% hi ~ 2)

  var_lab(age_cat) = "Age"
  val_lab(age_cat) = c("18 - 25" = 1, "26 - 35" = 2)

  var_lab(a1_1) = "Likes. VSX123"
  var_lab(b1_1) = "Likes. SDF456"
  val_lab(a1_1) = codeframe_likes
  val_lab(b1_1) = codeframe_likes

  wgt = runif(.N, 0.25, 4)
  wgt = wgt/sum(wgt)*.N
})

product_test %>%
  tab_cells(mrset(a1_1 %to% a1_6), mrset(b1_1 %to% b1_6)) %>%
  tab_cols(total(), age_cat) %>%
  tab_weight(wgt) %>%
  tab_stat_cpct() %>%
  tab_sort_desc() %>%
  tab_pivot()

# trick to place cell variables labels inside columns
# useful to compare two variables
# '|' is needed to prevent automatic labels creation from argument
# alternatively we can use list(...) to avoid this
product_test %>%
  tab_cols(total(), age_cat) %>%
  tab_weight(wgt) %>%
  tab_cells("|" = unvr(mrset(a1_1 %to% a1_6))) %>%
  tab_stat_cpct(label = var_lab(a1_1)) %>%
  tab_cells("|" = unvr(mrset(b1_1 %to% b1_6))) %>%
  tab_stat_cpct(label = var_lab(b1_1)) %>%
  tab_pivot(stat_position = "inside_columns")

```

```
# if you need standard evaluation, use 'vars'
tables = mtcars %>%
  tab_cols(total(), am %nest% vs)

for(each in c("mpg", "disp", "hp", "qsec")){
  tables = tables %>% tab_cells(vars(each)) %>%
    tab_stat_fun(Mean = w_mean, "Std. dev." = w_sd, "Valid N" = w_n)
}
tables %>% tab_pivot()
```

---

tab\_significance\_options

*Mark significant differences between columns in the table*

---

### Description

- `significance_cpct` conducts z-tests between column percent in the result of `cro_cpct`. Results are calculated with the same formula as in `prop.test` without continuity correction.
- `significance_means` conducts t-tests between column means in the result of `cro_mean_sd_n`. Results are calculated with the same formula as in `t.test`.
- `significance_cases` conducts chi-squared tests on the subtable of table with counts in the result of `cro_cases`. Results are calculated with the same formula as in `chisq.test`.
- `significance_cell_chisq` compute cell chi-square test on table with column percent. The cell chi-square test looks at each table cell and tests whether it is significantly different from its expected value in the overall table. For example, if it is thought that variations in political opinions might depend on the respondent's age, this test can be used to detect which cells contribute significantly to that dependence. Unlike the chi-square test (`significance_cases`), which is carried out on a whole set of rows and columns, the cell chi-square test is carried out independently on each table cell. Although the significance level of the cell chi-square test is accurate for any given cell, the cell tests cannot be used instead of the chi-square test carried out on the overall table. Their purpose is simply to point to the parts of the table where dependencies between row and column categories may exist.

For `significance_cpct` and `significance_means` there are three type of comparisons which can be conducted simultaneously (argument `compare_type`):

- `subtable` provide comparisons between all columns inside each subtable.
- `previous_column` is a comparison of each column of the subtable with the previous column. It is useful if columns are periods or survey waves.
- `first_column` provides comparison the table first column with all other columns in the table. `adjusted_first_column` is also comparison with the first column but with adjustment for common base. It is useful if the first column is total column and other columns are subgroups of this total. Adjustments are made according to algorithm in IBM SPSS Statistics Algorithms v20, p. 263. Note that with these adjustments t-tests between means are made with equal variance assumed (as with `var_equal = TRUE`).

By now there are no adjustments for multiple-response variables (results of `mrset`) in the table columns so significance tests are rather approximate for such cases. Also, there are functions for the significance testing in the sequence of custom tables calculations (see [tables](#)):

- `tab_last_sig_cpct`, `tab_last_sig_means` and `tab_last_sig_cpct` make the same tests as their analogs mentioned above. It is recommended to use them after appropriate statistic function: `tab_stat_cpct`, `tab_stat_mean_sd_n` and `tab_stat_cases`.
- `tab_significance_options` With this function we can set significance options for the entire custom table creation sequence.
- `tab_last_add_sig_labels` This function applies `add_sig_labels` to the last calculated table - it adds labels (letters by default) for significance to columns header. It may be useful if you want to combine a table with significance with table without it.
- `tab_last_round` This function rounds numeric columns in the last calculated table to specified number of digits. It is sometimes needed if you want to combine table with significance with table without it.

### Usage

```
tab_significance_options(data, sig_level = 0.05, min_base = 2,
  delta_cpct = 0, delta_means = 0, correct = TRUE,
  compare_type = "subtable", bonferroni = FALSE,
  subtable_marks = "greater", inequality_sign = "both" %in%
  subtable_marks, sig_labels = LETTERS,
  sig_labels_previous_column = c("v", "^"),
  sig_labels_first_column = c("-", "+"), sig_labels_chisq = c("<",
  ">"), keep = c("percent", "cases", "means", "sd", "bases"),
  row_margin = c("auto", "sum_row", "first_column"),
  total_marker = "#", total_row = 1, digits = get_expss_digits(),
  na_as_zero = FALSE, var_equal = FALSE, mode = c("replace",
  "append"))
```

```
tab_last_sig_cpct(data, sig_level = 0.05, delta_cpct = 0,
  min_base = 2, compare_type = "subtable", bonferroni = FALSE,
  subtable_marks = c("greater", "both", "less"),
  inequality_sign = "both" %in% subtable_marks, sig_labels = LETTERS,
  sig_labels_previous_column = c("v", "^"),
  sig_labels_first_column = c("-", "+"), keep = c("percent", "bases"),
  na_as_zero = FALSE, total_marker = "#", total_row = 1,
  digits = get_expss_digits(), mode = c("replace", "append"),
  label = NULL)
```

```
tab_last_sig_means(data, sig_level = 0.05, delta_means = 0,
  min_base = 2, compare_type = "subtable", bonferroni = FALSE,
  subtable_marks = c("greater", "both", "less"),
  inequality_sign = "both" %in% subtable_marks, sig_labels = LETTERS,
  sig_labels_previous_column = c("v", "^"),
  sig_labels_first_column = c("-", "+"), keep = c("means", "sd",
  "bases"), var_equal = FALSE, digits = get_expss_digits(),
```

```
mode = c("replace", "append"), label = NULL)

tab_last_sig_cases(data, sig_level = 0.05, min_base = 2,
  correct = TRUE, keep = c("cases", "bases"), total_marker = "#",
  total_row = 1, digits = get_expss_digits(), mode = c("replace",
  "append"), label = NULL)

tab_last_sig_cell_chisq(data, sig_level = 0.05, min_base = 2,
  subtable_marks = c("both", "greater", "less"),
  sig_labels_chisq = c("<", ">"), correct = TRUE, keep = c("percent",
  "bases", "none"), row_margin = c("auto", "sum_row", "first_column"),
  total_marker = "#", total_row = 1, total_column_marker = "#",
  digits = get_expss_digits(), mode = c("replace", "append"),
  label = NULL)

tab_last_round(data, digits = get_expss_digits())

tab_last_add_sig_labels(data, sig_labels = LETTERS)

significance_cases(x, sig_level = 0.05, min_base = 2, correct = TRUE,
  keep = c("cases", "bases"), total_marker = "#", total_row = 1,
  digits = get_expss_digits())

significance_cell_chisq(x, sig_level = 0.05, min_base = 2,
  subtable_marks = c("both", "greater", "less"),
  sig_labels_chisq = c("<", ">"), correct = TRUE, keep = c("percent",
  "bases", "none"), row_margin = c("auto", "sum_row", "first_column"),
  total_marker = "#", total_row = 1, total_column_marker = "#",
  digits = get_expss_digits())

cell_chisq(cases_matrix, row_base, col_base, total_base, correct)

significance_cpct(x, sig_level = 0.05, delta_cpct = 0, min_base = 2,
  compare_type = "subtable", bonferroni = FALSE,
  subtable_marks = c("greater", "both", "less"),
  inequality_sign = "both" %in% subtable_marks, sig_labels = LETTERS,
  sig_labels_previous_column = c("v", "^"),
  sig_labels_first_column = c("-", "+"), keep = c("percent", "bases"),
  na_as_zero = FALSE, total_marker = "#", total_row = 1,
  digits = get_expss_digits())

add_sig_labels(x, sig_labels = LETTERS)

significance_means(x, sig_level = 0.05, delta_means = 0,
  min_base = 2, compare_type = "subtable", bonferroni = FALSE,
  subtable_marks = c("greater", "both", "less"),
  inequality_sign = "both" %in% subtable_marks, sig_labels = LETTERS,
  sig_labels_previous_column = c("v", "^"),
```

```
sig_labels_first_column = c("-", "+"), keep = c("means", "sd",
"bases"), var_equal = FALSE, digits = get_expss_digits())
```

### Arguments

data	data.frame/intermediate_table for tab_* functions.
sig_level	numeric. Significance level - by default it equals to 0.05.
min_base	numeric. Significance test will be conducted if both columns have bases greater or equal to min_base. By default, it equals to 2.
delta_cpct	numeric. Minimal delta between percent for which we mark significant differences (in percent points) - by default it equals to zero. Note that, for example, for minimal 5 percent point difference delta_cpct should be equals 5, not 0.05.
delta_means	numeric. Minimal delta between means for which we mark significant differences - by default it equals to zero.
correct	logical indicating whether to apply continuity correction when computing the test statistic for 2 by 2 tables. Only for significance_cases and significance_cell_chisq. For details see <a href="#">chisq.test</a> . TRUE by default.
compare_type	Type of compare between columns. By default, it is subtable - comparisons will be conducted between columns of each subtable. Other possible values are: first_column, adjusted_first_column and previous_column. We can conduct several tests simultaneously.
bonferroni	logical. FALSE by default. Should we use Bonferroni adjustment by the number of comparisons in each row?
subtable_marks	character. One of "greater", "both" or "less". By default we mark only values which are significantly greater than some other columns. For significance_cell_chisq default is "both". We can change this behavior by setting an argument to less or both.
inequality_sign	logical. FALSE if subtable_marks is "less" or "greater". Should we show > or < before significance marks of subtable comparisons.
sig_labels	character vector. Labels for marking differences between columns of subtable.
sig_labels_previous_column	a character vector with two elements. Labels for marking a difference with the previous column. First mark means 'lower' (by default it is v) and the second means greater (^).
sig_labels_first_column	a character vector with two elements. Labels for marking a difference with the first column of the table. First mark means 'lower' (by default it is -) and the second means 'greater' (+).
sig_labels_chisq	a character vector with two labels for marking a difference with row margin of the table. First mark means 'lower' (by default it is <) and the second means 'greater' (>). Only for significance_cell_chisq.
keep	character. One or more from "percent", "cases", "means", "bases", "sd" or "none". This argument determines which statistics will remain in the table after significance marking.

row_margin	character. One of values "auto" (default), "sum_row", or "first_column". If it is "auto" we try to find total column in the subtable by total_column_marker. If the search is failed, we use the sum of each rows as row total. With "sum_row" option we always sum each row to get margin. Note that in this case result for multiple response variables in banners may be incorrect. With "first_column" option we use table first column as row margin for all subtables. In this case result for the subtables with incomplete bases may be incorrect. Only for significance_cell_chisq.
total_marker	character. Total rows mark in the table. "#" by default.
total_row	integer/character. In the case of the several totals per subtable it is a number or name of total row for the significance calculation.
digits	an integer indicating how much digits after decimal separator will be shown in the final table.
na_as_zero	logical. FALSE by default. Should we treat NA's as zero cases?
var_equal	a logical variable indicating whether to treat the two variances as being equal. For details see <a href="#">t.test</a> .
mode	character. One of replace(default) or append. In the first case the previous result in the sequence of table calculation will be replaced with result of significance testing. In the second case result of the significance testing will be appended to sequence of table calculation.
label	character. Label for the statistic in the tab_*. Ignored if the mode is equals to replace.
total_column_marker	character. Mark for total columns in the subtables. "#" by default.
x	table (class etable): result of <a href="#">cro_cpct</a> with proportions and bases for significance_cpct, result of <a href="#">cro_mean_sd_n</a> with means, standard deviations and valid N for significance_means, and result of <a href="#">cro_cases</a> with counts and bases for significance_cases.
cases_matrix	numeric matrix with counts size R*C
row_base	numeric vector with row bases, length R
col_base	numeric vector with col bases, length C
total_base	numeric single value, total base

**Value**

tab\_last\_\* functions return objects of class intermediate\_table. Use [tab\\_pivot](#) to get the final result - etable object. Other functions return etable object with significant differences.

**See Also**

[cro\\_cpct](#), [cro\\_cases](#), [cro\\_mean\\_sd\\_n](#), [tables](#), [compare\\_proportions](#), [compare\\_means](#), [prop.test](#), [t.test](#), [chisq.test](#)

**Examples**

```
data(mtcars)
mtcars = apply_labels(mtcars,
```



```

# cell chi-squared test
# increase number of cases to avoid warning about chi-square approximation
mtcars2 = add_rows(mtcars, mtcars, mtcars)

tbl = calc_cro_cpct(mtcars2, gear, am)
significance_cell_chisq(tbl)

# table with multiple variables
tbl = calc_cro_cpct(mtcars2, list(gear, cyl), list(total(), am, vs))
significance_cell_chisq(tbl, sig_level = .0001)

# custom tables with significance
mtcars %>%
  tab_significance_options(subtable_marks = "both") %>%
  tab_cells(mpg, hp) %>%
  tab_cols(total(), vs, am) %>%
  tab_stat_mean_sd_n() %>%
  tab_last_sig_means(keep = "means") %>%
  tab_cells(cyl, gear) %>%
  tab_stat_cpct() %>%
  tab_last_sig_cpct() %>%
  tab_pivot()

# Overcomplicated examples - we move significance marks to
# separate columns. Columns with statistics remain numeric
mtcars %>%
  tab_significance_options(keep = "none",
                          sig_labels = NULL,
                          subtable_marks = "both",
                          mode = "append") %>%
  tab_cols(total(), vs, am) %>%
  tab_cells(mpg, hp) %>%
  tab_stat_mean_sd_n() %>%
  tab_last_sig_means() %>%
  tab_last_hstack("inside_columns") %>%
  tab_cells(cyl, gear) %>%
  tab_stat_cpct() %>%
  tab_last_sig_cpct() %>%
  tab_last_hstack("inside_columns") %>%
  tab_pivot(stat_position = "inside_rows") %>%
  drop_empty_columns()

## End(Not run)

```

---

tab\_sort\_asc

*Partially (inside blocks) sort tables/data.frames*


---

### Description

tab\_sort\_asc/tab\_sort\_desc sort tables (usually result of [cro/tables](#)) in ascending/descending order between specified rows (by default, it is rows which contain '#' in the first column).

**Usage**

```
tab_sort_asc(x, ..., excluded_rows = "#", na.last = FALSE)
```

```
tab_sort_desc(x, ..., excluded_rows = "#", na.last = TRUE)
```

**Arguments**

x	data.frame
...	character/numeric or criteria/logical functions (see <a href="#">criteria</a> ). Column names/numbers for data.frame/matrix by which object will be sorted. Names at the top-level can be unquoted (non-standard evaluation). For standard evaluation of parameters you can surround them by round brackets. See examples. If this argument is missing then table will be sorted by second column. Usually second column is the first column with numbers in the table (there are row labels in the first column).
excluded_rows	character/logical/numeric rows which won't be sorted. Rows of the table will be sorted between excluded rows. If it is characters then they will be considered as pattern/vector of patterns. Patterns will be matched with Perl-style regular expression with values in the first column of x (see <a href="#">grep</a> , <code>perl = TRUE</code> argument). Rows which have such patterns will be excluded. By default, pattern is "#" because "#" marks totals in the result of <a href="#">cro</a> .
na.last	for controlling the treatment of NAs. If TRUE, missing values in the data are put last; if FALSE, they are put first; if NA, they are removed.

**Value**

sorted table('etable')/data.frame

**Examples**

```
data(mtcars)

# apply labels
mtcars = apply_labels(mtcars,
  cyl = "Number of cylinders",
  vs = "Engine",
  vs = c("V-engine" = 0,
        "Straight engine" = 1),
  am = "Transmission",
  am = c(automatic = 0,
        manual=1),
  gear = "Number of forward gears",
  carb = "Number of carburetors"
)

# without sorting
mtcars %>% calculate(cro_cpct(list(cyl, gear, carb), list("#total", vs, am)))

# with sorting
```

```
mtcars %>%
  calculate(cro_cpct(list(cyl, gear, carb), list("#total", vs, am))) %>%
  tab_sort_desc

# sort by parameter
sorting_column = "Engine|V-engine"

mtcars %>%
  calculate(cro_cpct(list(cyl, gear, carb), list("#total", vs, am))) %>%
  tab_sort_desc((sorting_column))
```

---

text_to_columns	<i>Make data.frame from text</i>
-----------------	----------------------------------

---

## Description

Convert delimited text lines to data.frame. Blank lines are always skipped, trailing whitespaces are trimmed. You can use comments with '#' inside your text. For details see [read.table](#).

## Usage

```
text_to_columns(text, header = TRUE, sep = "", quote = "",
  dec = ".", encoding = "unknown", ...)

text_to_columns_csv(text, header = TRUE, sep = ",", quote = "",
  dec = ".", encoding = "unknown", ...)

text_to_columns_csv2(text, header = TRUE, sep = ";", quote = "",
  dec = ",", encoding = "unknown", ...)

text_to_columns_tab(text, header = TRUE, sep = "\t", quote = "",
  dec = ".", encoding = "unknown", ...)

text_to_columns_tab2(text, header = TRUE, sep = "\t", quote = "",
  dec = ",", encoding = "unknown", ...)
```

## Arguments

text	character/vector of characters
header	a logical value indicating whether the text contains the names of the variables as its first line.
sep	the field separator character. Values on each line of the file are separated by this character. If sep = "" (the default for text_to_columns) the separator is 'white space', that is one or more spaces, tabs, newlines or carriage returns.
quote	the set of quoting characters. To disable quoting altogether, use quote = "".
dec	the character used in the file for decimal points.



---

values2labels	<i>Replace vector/matrix/data.frame/list values with corresponding value labels.</i>
---------------	--

---

## Description

values2labels replaces vector/matrix/data.frame/list values with corresponding value labels. If there are no labels for some values they are converted to characters in most cases. If there are no labels at all for variable it remains unchanged. v2l is just shortcut to values2labels.

## Usage

```
values2labels(x)
```

```
v2l(x)
```

## Arguments

x                   vector/matrix/data.frame/list

## Value

Object of the same form as x but with value labels instead of values.

## See Also

[names2labels](#), [val\\_lab](#), [var\\_lab](#)

## Examples

```
data(mtcars)
mtcars = modify(mtcars,{
  var_lab(mpg) = NULL
  val_lab(am) = c(" automatic" = 0, " manual" = 1)
})

summary(lm(mpg ~ ., data = values2labels(mtcars[,c("mpg","am")])))
```

---

`val_lab`*Set or get value labels*

---

### Description

These functions set/get/drop value labels. Duplicated values are not allowed. If argument `x` is `data.frame` or list then labels applied to all elements of `data.frame/list`. To drop value labels, use `val_lab(var) <-NULL` or `unvl(var)`. `make_labels` converts text from the form that usually used in questionnaires to named vector. For variable labels see [var\\_lab](#). For working with entire `data.frame` see [apply\\_labels](#).

- `val_lab` returns value labels or `NULL` if labels doesn't exist.
- `val_lab<-` set value labels.
- `set_val_lab` returns variable with value labels.
- `add_val_lab<-` add value labels to already existing value labels.
- `unvl` drops value labels.
- `make_labels` makes named vector from text for usage as value labels.
- `num_lab`, `lab_num` and `autonum` are shortcuts for `make_labels` with code\_position 'left', 'right' and 'autonum' accordingly.

### Usage

```
val_lab(x)
```

```
val_lab(x) <- value
```

```
set_val_lab(x, value, add = FALSE)
```

```
add_val_lab(x, value)
```

```
add_val_lab(x) <- value
```

```
unvl(x)
```

```
drop_val_labs(x)
```

```
make_labels(text, code_position = c("left", "right", "autonum"))
```

```
drop_unused_labels(x)
```

```
num_lab(text)
```

```
lab_num(text)
```

```
autonum(text)
```

**Arguments**

x	Variable(s). Vector/data.frame/list.
value	Named vector. Names of vector are labels for the appropriate values of variable x.
add	Logical. Should we add value labels to old labels or replace it? Deafult is FALSE - we completely replace old values. If TRUE new value labels will be combined with old value labels.
text	text that should be converted to named vector
code_position	Possible values "left", "right" - position of numeric code in text. "autonum" - makes codes by autonumbering lines of text.

**Details**

Value labels are stored in attribute "labels" (`attr(x, "labels")`). We set variable class to "labelled" for preserving labels from dropping during some operations (such as `c` and ``[``).

**Value**

`val_lab` return value labels (named vector). If labels doesn't exist it return `NULL`. `val_lab<-` and `set_val_lab` return variable (vector x) of class "labelled" with attribute "labels" which contains value labels. `make_labels` return named vector for usage as value labels.

**Examples**

```
# toy example
set.seed(123)
# score - evaluation of tested product

score = sample(-1:1,20,replace = TRUE)
var_lab(score) = "Evaluation of tested brand"
val_lab(score) = c("Dislike it" = -1,
                  "So-so" = 0,
                  "Like it" = 1
                  )

# frequency of product scores
fre(score)

# brands - multiple response question
# Which brands do you use during last three months?

brands = as.sheet(t(replicate(20,sample(c(1:5,NA),4,replace = FALSE))))

var_lab(brands) = "Used brands"
val_lab(brands) = make_labels("
1 Brand A
2 Brand B
3 Brand C
4 Brand D
5 Brand E")
```

```

    ")

# percentage of used brands
fre(brands)

# percentage of brands within each score
cro_cpct(brands, score)

## make labels from text copied from questionnaire

age = c(1, 2, 1, 2)

val_lab(age) = num_lab("
  1. 18 - 26
  2. 27 - 35
")

# note support of value lables in base R
table(age)

# or, if in original codes is on the right side

products = 1:8

val_lab(products) = lab_num("
Chocolate bars      1
Chocolate sweets (bulk) 2
Slab chocolate(packed) 3
Slab chocolate (bulk) 4
Boxed chocolate sweets 5
Marshmallow/pastilles in chocolate coating 6
Marmalade in chocolate coating 7
Other 8
")

table(products)

```

---

vars

*Get variables/range of variables by name/by pattern.*


---

### Description

- vars returns data.frame with all variables by their names or by criteria (see [criteria](#)). There is no non-standard evaluation in this function by design so use quotes for names of your variables. This function is intended to get variables by parameter/criteria. The only exception with non-standard evaluation is %to%. You can use %to% inside vars or independently.
- .p returns data.frame with all variables which names satisfy supplied perl-style regular expression. Arguments for this function is quoted characters. It is a shortcut for vars(per1(pattern)).

- `..f` returns data.frame with all variables which names contain supplied pattern. Arguments for this function can be unquoted. It is a shortcut for `vars(fixed(pattern))`.
- `..t` returns data.frame with variables which names are stored in the supplied arguments. Expressions in characters in curly brackets are expanded. See [text\\_expand](#).
- `..[]` returns data.frame with all variables by their names or by criteria (see [criteria](#)). Names at the top-level can be unquoted (non-standard evaluation). For standard evaluation of parameters you can surround them by round brackets. You can assign to this expression. If there are several names inside square brackets then each element of list/data.frame from right side will be assigned to appropriate name from left side. You can use `item1 %to% item2` notation to get/create sequence of variables. If there are no arguments inside square brackets than from each item of RHS will be created separate variable in the parent frame. In this case RHS should be named list or data.frame.
- `..$name` sets/returns object which name is stored in the variable name. It is convenient wrapper around [get/assign](#) functions.
- `%to%` returns range of variables between `e1` and `e2` (similar to SPSS 'to'). [modify](#), [modify\\_if](#), [calculate](#), [keep](#), [except](#) and [where](#) support `%to%`. Inside global environment [with](#), [within](#) `%to%` will take range from names of variables sorted in the alphabetic order.
- `indirect/indirect_list` are aliases for `vars/vars_list`.

Functions with word 'list' in name return lists of variables instead of dataframes.

## Usage

```
vars(...)
```

```
vars_list(...)
```

```
indirect(...)
```

```
indirect_list(...)
```

```
e1 %to% e2
```

```
e1 %to_list% e2
```

```
..
```

```
..f(...)
```

```
..p(...)
```

```
..t(...)
```

## Arguments

<code>...</code>	characters names of variables or criteria/logical functions
<code>e1</code>	unquoted name of start variable (e. g. <code>a_1</code> )
<code>e2</code>	unquoted name of start variable (e. g. <code>a_5</code> )

**Format**

An object of class parameter of length 1.

**Value**

data.frame/list with variables

**See Also**

[keep](#), [except](#), [do\\_repeat](#), [compute](#), [calculate](#), [where](#)

**Examples**

```
# In data.frame
dfs = data.frame(
  a = rep(1, 5),
  b_1 = rep(11, 5),
  b_2 = rep(12, 5),
  b_3 = rep(13, 5),
  b_4 = rep(14, 5),
  b_5 = rep(15, 5)
)

# calculate sum of b_* variables
compute(dfs, {
  b_total = sum_row(b_1 %to% b_5)
})

# identical result
compute(dfs, {
  b_total = sum_row(..f(b_))
})

compute(dfs, {
  b_total = sum_row(..t("b_{1:5}"))
})

# In global environment
a = rep(10, 5)
a1 = rep(1, 5)
a2 = rep(2, 5)
a3 = rep(3, 5)
a4 = rep(4, 5)
a5 = rep(5, 5)

# identical results
a1 %to% a5
vars(perl("^a[0-9]$"))
..[perl("^a[0-9]$")]
..p("^a[0-9]$")
..t("a{1:5}")
```

```

# sum each row
sum_row(a1 %to% a5)

# variable substitution
name1 = "a"
name2 = "new_var"

# in global environment
..$name1 # give as variable 'a'

..$name2 = ..$name1 * 2 # create variable 'new_var' which is equal to 'a' times 2
new_var

# inside data.frame
compute(dfs, {
  ..$name2 = ..$name1*2
})

compute(dfs, {
  for(name1 in paste0("b_", 1:5)){
    name2 = paste0("new_", name1)
    ..$name2 = ..$name1*2
  }
  rm(name1, name2) # we don't need this variables as columns in 'dfs'
})

# square brackets notation - multi-assignment
name1 = paste0("b_", 1:5)
compute(dfs, {
  # round brackets about 'name1' is needed to avoid using it 'as is'
  ..[paste0("new_", name1)] = ..[(name1)]*2
})

# the same result
# note the automatic creation of sequence of variables
compute(dfs, {
  ..[new_b_1 %to% new_b_5] = ..[b_1 %to% b_5]*2
})

# assignment form of 'recode' on multiple variables
compute(dfs, {
  recode(..[b_1 %to% b_5]) = 13 %thru% hi ~ 20
})

# empty brackets - unboxing of dichotomy.
compute(dfs, {
  ..[] = as.dichotomy(b_1 %to% b_5, prefix = "v_")
})

```

## Description

These functions set/get/drop variable labels. For value labels see [val\\_lab](#). For working with entire data.frame see [apply\\_labels](#).

- `var_lab` returns variable label or NULL if label doesn't exist.
- `var_lab<-` set variable label.
- `set_var_lab` returns variable with label.
- `unvr` drops variable label.
- `add_labelled_class` Add missing 'labelled' class. This function is needed when you load SPSS data with packages which in some cases don't set 'labelled' class for variables with labels. For example, haven package doesn't set 'labelled' class for variables which have variable label but don't have value labels. Note that to use 'expss' with 'haven' you need to load 'expss' strictly after 'haven' to avoid conflicts.

## Usage

```
var_lab(x)

var_lab(x) <- value

set_var_lab(x, value)

unvr(x)

drop_var_labs(x)

add_labelled_class(x, remove_classes = c("haven_labelled",
    "spss_labelled"))
```

## Arguments

<code>x</code>	Variable. In the most cases it is numeric vector.
<code>value</code>	A character scalar - label for the variable <code>x</code> .
<code>remove_classes</code>	A character vector of classes which should be removed from the class attribute of the <code>x</code> .

## Details

Variable label is stored in attribute "label" (`attr(x, "label")`). For preserving from dropping this attribute during some operations (such as `c`) variable class is set to "labelled". There are special methods of subsetting and concatenation for this class. To drop variable label use `var_lab(var) <- NULL` or `unvr(var)`.

## Value

`var_lab` return variable label. If label doesn't exist it return NULL . `var_lab<-` and `set_var_lab` return variable (vector `x`) of class "labelled" with attribute "label" which equals submitted value.

**Examples**

```

data(mtcars)
mtcars = modify(mtcars,{
  var_lab(mpg) = "Miles/(US) gallon"
  var_lab(cyl) = "Number of cylinders"
  var_lab(displ) = "Displacement (cu.in.)"
  var_lab(hp) = "Gross horsepower"
  var_lab(drat) = "Rear axle ratio"
  var_lab(wt) = "Weight (lb/1000)"
  var_lab(qsec) = "1/4 mile time"
  var_lab(vs) = "V/S"
  var_lab(am) = "Transmission (0 = automatic, 1 = manual)"
  val_lab(am) = c(automatic = 0, manual=1)
  var_lab(gear) = "Number of forward gears"
  var_lab(carb) = "Number of carburetors"
})

fre(mtcars$am)

calculate(mtcars,
  cro_mean(list(mpg, displ, hp, qsec), list(total(), am))
)

## Not run:
# 'add_labelled_class' example doesn't work intentionally
if(FALSE){ # to prevent execution
# you need to load packages strictly in this order to avoid conflicts
library(haven)
library(exps)
spss_data = haven::read_spss("spss_file.sav")
# add missing 'labelled' class
spss_data = add_labelled_class(spss_data)
}

## End(Not run)

```

vectors

*Infix operations on vectors - append, diff, intersection, union, replication***Description**

All these functions except `%n_d%`, `%n_i%` preserve names of vectors and don't remove duplicates.

- `%a%` `a`(ppends) second argument to the first argument. See also [append](#).
- `%u%` and `v_union u(nite)` first and second arguments. Remove elements from the second argument which exist in the first argument.

- `%d%` and `v_diff d(iff)` second argument from the first argument. Second argument could be a function which returns logical value. In this case elements of the first argument which give TRUE will be removed.
- `%i%` and `v_intersect i(ntersect)` first argument and second argument. Second argument could be a function which returns logical value. In this case elements of the first argument which give FALSE will be removed.
- `%e%` and `v_xor e(xclusive OR)`. Returns elements that contained only in one of arguments.
- `%r%` `r(epeats)` first argument second argument times. See also [rep](#).
- `%n_d%` and `n_diff n(ames) d(iff) - diff` second argument from names of first argument. Second argument could be a function which returns logical value. In this case elements of the first argument which names give TRUE will be removed.
- `%n_i%` and `n_intersect n(ames) i(ntersect) - intersect` names of the first argument with the second argument. Second argument could be a function which returns logical value. In this case elements of the first argument which names give FALSE will be removed.

For `%d%`, `%i%`, `%n_d%`, `%n_i%` one can use criteria functions. See [criteria](#) for details.

### Usage

`e1 %a% e2`

`v_union(e1, e2)`

`e1 %u% e2`

`v_diff(e1, e2)`

`e1 %d% e2`

`v_intersect(e1, e2)`

`e1 %i% e2`

`v_xor(e1, e2)`

`e1 %e% e2`

`e1 %r% e2`

`n_intersect(e1, e2)`

`e1 %n_i% e2`

`n_diff(e1, e2)`

`e1 %n_d% e2`

**Arguments**

e1                    vector or data.frame, matrix, list for %n\_d%, %n\_i%)  
 e2                    vector or function for %d%, %i%

**Value**

vector or data.frame, matrix, list for %n\_d%, %n\_i%)

**Examples**

```
1:4 %a% 5:6 # 1:6

1:4 %a% 4:5 # 1,2,3,4,4,5

1:4 %u% 4:5 # 1,2,3,4,5

1:6 %d% 5:6 # 1:4

# function as criterion
1:6 %d% greater(4) # 1:4

1:4 %i% 4:5 # 4

# with criteria functions
letters %i% (contains("a") | contains("z")) # a, z

letters %i% perl("[a-d]") # a,b,c,d

1:4 %e% 4:5 # 1, 2, 3, 5

1:2 %r% 2 # 1, 2, 1, 2

# %n_i%, %n_d%

# remove column Species
iris %n_d% "Species"

# leave only columns which names start with "Sepal"
iris %n_i% like("Sepal*")

# leave column "Species" and columns which names start with "Sepal"
iris %n_i% ("Species" | like("Sepal*"))
iris %n_i% or("Species", like("Sepal*")) # same result
```

**Description**

vlookup/vlookup\_df function is inspired by VLOOKUP spreadsheet function. It looks for a lookup\_value in the lookup\_column of the dict, and then returns values in the same rows from result\_column. add\_columns inspired by MATCH FILES (Add variables...) from SPSS Statistics. It works similar to SQL left join but number of cases in the left part always remain the same. If there are duplicated keys in the dict then error will be raised by default. .add\_columns is the same function for default dataset.

**Usage**

```
vlookup(lookup_value, dict, result_column = 2, lookup_column = 1)
```

```
vlookup_df(lookup_value, dict, result_column = NULL, lookup_column = 1)
```

```
add_columns(data, dict, by = NULL, ignore_duplicates = FALSE)
```

```
.add_columns(dict, by = NULL, ignore_duplicates = FALSE)
```

**Arguments**

lookup_value	Vector of looked up values
dict	data.frame/matrix. Dictionary. Can be vector for vlookup/vlookup_df.
result_column	numeric or character. Resulting columns of dict. There are special values: 'row.names', 'rownames', 'names'. If result_column equals to one of these special values and dict is matrix/data.frame then row names of dict will be returned. If dict is vector then names of vector will be returned. For vlookup_df default result_column is NULL and result will be entire rows. For vlookup default result_column is 2 - for frequent case of dictionary with keys in the first column and results in the second column.
lookup_column	Column of dict in which lookup value will be searched. By default it is the first column of the dict. There are special values: 'row.names', 'rownames', 'names'. If lookup_column equals to one of these special values and dict is matrix/data.frame then values will be searched in the row names of dict. If dict is vector then values will be searched in names of the dict.
data	data.frame to be joined with dict.
by	character vector or NULL(default) or 1. Names of common variables in the data and dict by which we will attach dict to data. If it is NULL then common names will be used. If it is equals to 1 then we will use the first column from both dataframes. To add columns by different variables on data and dict use a named vector. For example, by = c("a" = "b") will match data.a to dict.b.
ignore_duplicates	logical Should we ignore duplicates in the by variables in the dict? If it is TRUE than first occurrence of duplicated key will be used.

**Value**

vlookup always return vector, vlookup\_df always returns data.frame. row.names in result of vlookup\_df are not preserved.

**Examples**

```

# with data.frame
dict = data.frame(num=1:26, small=letters, cap=LETTERS, stringsAsFactors = FALSE)
rownames(dict) = paste0('rows', 1:26)
identical(vlookup_df(1:3, dict), dict[1:3,]) # should be TRUE
vlookup(c(45,1:3,58), dict, result_column='cap')
vlookup_df(c('z','d','f'), dict, lookup_column = 'small')
vlookup_df(c('rows7', 'rows2', 'rows5'), dict, lookup_column = 'row.names')

# with vector
dict=1:26
names(dict) = letters

vlookup(c(2,4,6), dict, result_column='row.names')

# The same results
vlookup(c(2,4,6), dict, result_column='rownames')
vlookup(c(2,4,6), dict, result_column='names')

# example for 'add_columns' from base 'merge'
authors = sheet(
  surname = c("Tukey", "Venables", "Tierney", "Ripley", "McNeil"),
  nationality = c("US", "Australia", "US", "UK", "Australia"),
  deceased = c("yes", rep("no", 4))
)

books = sheet(
  surname = c("Tukey", "Venables", "Tierney",
             "Ripley", "Ripley", "McNeil", "R Core"),
  title = c("Exploratory Data Analysis",
            "Modern Applied Statistics ...",
            "LISP-STAT",
            "Spatial Statistics", "Stochastic Simulation",
            "Interactive Data Analysis",
            "An Introduction to R")
)

add_columns(books, authors)

# Just for fun. Examples borrowed from Microsoft Excel.
# It is not the R way of doing things.

# Example 2

ex2 = utils::read.table(header = TRUE, text = "
Item_ID Item Cost Markup
ST-340 Stroller 145.67 0.30
BI-567 Bib 3.56 0.40
DI-328 Diapers 21.45 0.35
WI-989 Wipes 5.12 0.40
AS-469 Aspirator 2.56 0.45
", stringsAsFactors = FALSE)

```

```

# Calculates the retail price of diapers by adding the markup percentage to the cost.
vlookup("DI-328", ex2, 3) * (1 + vlookup("DI-328", ex2, 4)) # 28.9575

# Calculates the sale price of wipes by subtracting a specified discount from
# the retail price.
(vlookup("WI-989", ex2, "Cost") * (1 + vlookup("WI-989", ex2, "Markup"))) * (1 - 0.2) # 5.7344

A2 = ex2[1, "Item_ID"]
A3 = ex2[2, "Item_ID"]

# If the cost of an item is greater than or equal to $20.00, displays the string
# "Markup is nn%"; otherwise, displays the string "Cost is under $20.00".
ifelse(vlookup(A2, ex2, "Cost") >= 20,
       paste0("Markup is ", 100 * vlookup(A2, ex2, "Markup"), "%"),
       "Cost is under $20.00") # Markup is 30%

# If the cost of an item is greater than or equal to $20.00, displays the string
# Markup is nn%"; otherwise, displays the string "Cost is $n.nn".
ifelse(vlookup(A3, ex2, "Cost") >= 20,
       paste0("Markup is: ", 100 * vlookup(A3, ex2, "Markup") , "%"),
       paste0("Cost is $", vlookup(A3, ex2, "Cost"))) #Cost is $3.56

# Example 3

ex3 = utils::read.table(header = TRUE, text = "
  ID Last_name First_name Title Birth_date
  1 Davis Sara 'Sales Rep.' 12/8/1968
  2 Fontana Olivier 'V.P. of Sales' 2/19/1952
  3 Leal Karina 'Sales Rep.' 8/30/1963
  4 Patten Michael 'Sales Rep.' 9/19/1958
  5 Burke Brian 'Sales Mgr.' 3/4/1955
  6 Sousa Luis 'Sales Rep.' 7/2/1963
", stringsAsFactors = FALSE)

# If there is an employee with an ID of 5, displays the employee's last name;
# otherwise, displays the message "Employee not found".
if_na(vlookup(5, ex3, "Last_name"), "Employee not found") # Burke

# Many employees
if_na(vlookup(1:10, ex3, "Last_name"), "Employee not found")

# For the employee with an ID of 4, concatenates the values of three cells into
# a complete sentence.
paste0(vlookup(4, ex3, "First_name"), " ",
       vlookup(4, ex3, "Last_name"), " is a ",
       vlookup(4, ex3, "Title")) # Michael Patten is a Sales Rep.

```

## Description

For the data frame `cond` will be evaluated in the `data.frame`'s context. So columns can be referred as variables in the expression (see the examples). If `data` is list then `where` will be applied to each element of the list. For other types (vector/matrix) there is no non-standard evaluation. There is a special constant `.N` which equals to number of rows in `data` for usage in `cond` expression. `.where` is version for working with default dataset. See [default\\_dataset](#).

## Usage

```
where(data, cond)
```

```
.where(cond)
```

## Arguments

<code>data</code>	data.frame/matrix/vector/list to be subsetted
<code>cond</code>	logical or numeric expression indicating elements or rows to keep: missing values (NA) are taken as FALSE. If <code>data</code> is <code>data.frame</code> then <code>cond</code> will be evaluated in the scope of the data.

## Value

data.frame/matrix/vector/list which contains just selected rows.

## Examples

```
# leave only 'setosa'
where(iris, Species == "setosa")
# leave only first five rows
where(iris, 1:5)

# example of .N usage.
set.seed(42)
train = where(iris, sample(.N, 100))
str(train)

set.seed(42)
test = where(iris, -sample(.N, 100))
str(test)

# list example
set.seed(123)
rand_matr = matrix(sample(10, 60, replace = TRUE), ncol = 3)
rand_vec = sample(10, 20, replace = TRUE)
my_list = list(iris, rand_matr, rand_vec)
# two random elements from the each list item
where(my_list, sample(.N, 2))
```

---

window_fun	<i>Function over grouping variables (window function)</i>
------------	---

---

### Description

This is faster version of [ave](#). window\_fun applies function to every subset of x and return vector of the same length as x.

### Usage

```
window_fun(x, ...)
```

### Arguments

x	A vector
...	Grouping variables all of the same length as x or length 1 and function as last argument.

### Value

vector of the same length as x

### Examples

```
window_fun(1:3, mean) # no grouping -> grand mean

attach(warpbreaks)

window_fun(breaks, wool, mean)
window_fun(breaks, tension, function(x) mean(x, trim = 0.1))

detach(warpbreaks)
```

---

write_labelled_csv	<i>Write labelled data to file or export file to SPSS syntax.</i>
--------------------	---

---

### Description

- write\_labelled\_csv and read\_labelled\_csv writes csv file with labels. By default labels are stored in the commented lines at the beginning of the file before the data part. \*\_csv2 write and read data with a semicolon separator and comma as decimal delimiter. \*\_tab/\*\_tab2 write and read data with 'tab' separator and "."/"," as decimal delimiter.
- write\_labelled\_xlsx and read\_labelled\_xlsx write and read labelled 'xlsx' format. It is a simple Excel file with data and labels on separate sheets. It can help you with labelled data exchange in the corporate environment.

- `write_labelled_fst` and `read_labelled_fst` write and read labelled data in the 'fst' format. See [Fst Package](#). Data and labels are stored in the separate files. With 'fst' format you can read and write a huge amount of data very quickly.
- `write_labelled_spss` write 'csv' file with SPSS syntax for reading it. You can use it for the data exchange with SPSS.
- `create_dictionary` and `apply_dictionary` make data.frame with dictionary, e. g. variable and value labels for each variable. See format description in the 'Details' section.
- `write_labels` and `write_labels_spss` Write R code and SPSS syntax for labelling data. It allows to extract labels from \*.sav files that come without accompanying syntax.
- `old_write_labelled_csv` and `old_read_labelled_csv` Read and write labelled 'csv' in format of the 'expss' version before 0.9.0.

### Usage

```
write_labelled_csv(x, filename, remove_new_lines = TRUE,
  single_file = TRUE, ...)

write_labelled_csv2(x, filename, remove_new_lines = TRUE,
  single_file = TRUE, ...)

write_labelled_tab(x, filename, remove_new_lines = TRUE,
  single_file = TRUE, ...)

write_labelled_tab2(x, filename, remove_new_lines = TRUE,
  single_file = TRUE, ...)

write_labelled_xlsx(x, filename, data_sheet = "data",
  dict_sheet = "dictionary", remove_repeated = FALSE,
  use_references = TRUE)

write_labelled_fst(x, filename, ...)

read_labelled_csv(filename, undouble_quotes = TRUE, ...)

read_labelled_csv2(filename, undouble_quotes = TRUE, ...)

read_labelled_tab(filename, undouble_quotes = TRUE, ...)

read_labelled_tab2(filename, undouble_quotes = TRUE, ...)

read_labelled_xlsx(filename, data_sheet = 1, dict_sheet = "dictionary")

read_labelled_fst(filename, ...)

write_labelled_spss(x, filename, fileEncoding = "",
  remove_new_lines = TRUE, ...)

write_labels_spss(x, filename)
```

```

write_labels(x, filename, fileEncoding = "")

create_dictionary(x, remove_repeated = FALSE, use_references = TRUE)

apply_dictionary(x, dict)

old_write_labelled_csv(x, filename, fileEncoding = "",
  remove_new_lines = TRUE, ...)

old_read_labelled_csv(filename, fileEncoding = "",
  undouble_quotes = TRUE, ...)

```

### Arguments

x	data.frame to be written/data.frame whose labels to be written
filename	the name of the file which the data are to be read from/write to.
remove_new_lines	A logical indicating should we replace new lines with spaces in the character variables. TRUE by default.
single_file	logical. TRUE by default. Should we write labels into the same file as data? If it is FALSE dictionary will be written in the separate file.
...	additional arguments for <a href="#">fwrite/fread</a> , e. g. column separator, decimal separator, encoding and etc.
data_sheet	character "data" by default. Where data will be placed in the '*.xlsx' file.
dict_sheet	character "dictionary" by default. Where dictionary will be placed in the '*.xlsx' file.
remove_repeated	logical. FALSE by default. If TRUE then we remove repeated variable names. It makes a dictionary to look nicer for humans but less convenient for usage.
use_references	logical. When TRUE (default) then if the variable has the same value labels as the previous variable, we use reference to this variable. It makes dictionary significantly more compact for datasets with many variables with the same value labels.
undouble_quotes	A logical indicating should we undouble quotes which were escaped by doubling. TRUE by default. Argument will be removed when data.table issue #1109 will be fixed.
fileEncoding	character string: if non-empty declares the encoding to be used on a file (not a connection) so the character data can be re-encoded as they are written. Used for writing dictionary. See <a href="#">file</a> .
dict	data.frame with labels - a result of create_dictionary.

### Details

Dictionary is a data.frame with the following columns:

- variable name in the data set. It can be omitted (NA). In this case name from the previous row will be taken.
- value code for label in the column 'label'.
- label in most cases it is value label but its meaning can be changed by the column 'meta'.
- meta if it is NA then we have value label in the 'label' column. If it is 'varlab', then there is a variable label in the 'label' column and column 'value' is ignored. If it is 'reference', then there is a variable name in the 'label' column and we use value labels from this variable, column 'value' is ignored.

## Value

Functions for writing invisibly return NULL. Functions for reading return labelled data.frame.

## Examples

```
## Not run:
data(mtcars)
mtcars = modify(mtcars,{
  var_lab(mpg) = "Miles/(US) gallon"
  var_lab(cyl) = "Number of cylinders"
  var_lab(displ) = "Displacement (cu.in.)"
  var_lab(hp) = "Gross horsepower"
  var_lab(drat) = "Rear axle ratio"
  var_lab(wt) = "Weight (lb/1000)"
  var_lab(qsec) = "1/4 mile time"
  var_lab(vs) = "Engine"
  val_lab(vs) = c("V-engine" = 0,
                 "Straight engine" = 1)
  var_lab(am) = "Transmission"
  val_lab(am) = c(automatic = 0,
                 manual=1)
  var_lab(gear) = "Number of forward gears"
  var_lab(carb) = "Number of carburetors"
})

write_labelled_csv(mtcars, "mtcars.csv")
new_mtcars = read_labelled_csv("mtcars.csv")
str(new_mtcars)

# identically, for xlsx
write_labelled_xlsx(mtcars, "mtcars.xlsx")
new_mtcars = read_labelled_xlsx("mtcars.xlsx")
str(new_mtcars)

# to SPSS syntax
write_labelled_spss(mtcars, "mtcars.csv")

## End(Not run)
```

---

`w_mean`*Compute various weighted statistics*

---

**Description**

- `w_mean` weighted mean of a numeric vector
- `w_sd` weighted sample standard deviation of a numeric vector
- `w_var` weighted sample variance of a numeric vector
- `w_se` weighted standard error of a numeric vector
- `w_median` weighted median of a numeric vector
- `w_mad` weighted mean absolute deviation from median of a numeric vector
- `w_sum` weighted sum of a numeric vector
- `w_n` weighted number of values of a numeric vector
- `w_cov` weighted covariance matrix of a numeric matrix/data.frame
- `w_cor` weighted Pearson correlation matrix of a numeric matrix/data.frame
- `w_pearson` shortcut for `w_cor`. Weighted Pearson correlation matrix of a numeric matrix/data.frame
- `w_spearman` weighted Spearman correlation matrix of a numeric matrix/data.frame

**Usage**

```
w_mean(x, weight = NULL, na.rm = TRUE)
```

```
w_median(x, weight = NULL, na.rm = TRUE)
```

```
w_var(x, weight = NULL, na.rm = TRUE)
```

```
w_sd(x, weight = NULL, na.rm = TRUE)
```

```
w_se(x, weight = NULL, na.rm = TRUE)
```

```
w_mad(x, weight = NULL, na.rm = TRUE)
```

```
w_sum(x, weight = NULL, na.rm = TRUE)
```

```
w_n(x, weight = NULL, na.rm = TRUE)
```

```
unweighted_valid_n(x, weight = NULL)
```

```
valid_n(x, weight = NULL)
```

```
w_max(x, weight = NULL, na.rm = TRUE)
```

```
w_min(x, weight = NULL, na.rm = TRUE)
```

```
w_cov(x, weight = NULL, use = c("pairwise.complete.obs",
  "complete.obs"))

w_cor(x, weight = NULL, use = c("pairwise.complete.obs",
  "complete.obs"))

w_pearson(x, weight = NULL, use = c("pairwise.complete.obs",
  "complete.obs"))

w_spearman(x, weight = NULL, use = c("pairwise.complete.obs",
  "complete.obs"))
```

### Arguments

x	a numeric vector (matrix/data.frame for correlations) containing the values whose weighted statistics is to be computed.
weight	a vector of weights to use for each element of x. Cases with missing, zero or negative weights will be removed before calculations. If weight is missing then unweighted statistics will be computed.
na.rm	a logical value indicating whether NA values should be stripped before the computation proceeds. Note that contrary to base R statistic functions the default value is TRUE (remove missing values).
use	"pairwise.complete.obs" (default) or "complete.obs". In the first case the correlation or covariance between each pair of variables is computed using all complete pairs of observations on those variables. If use is "complete.obs" then missing values are handled by casewise deletion.

### Details

If argument of correlation functions is data.frame with variable labels then variables names will be replaced with labels. If this is undesirable behavior use `unvr` function: `w_cor(unvr(x))`. Weighted spearman correlation coefficients are calculated with rounded to nearest integer weights. It gives the same result as in SPSS Statistics software. By now this algorithm is not memory efficient.

### Value

a numeric value of length one/correlation matrix

### Examples

```
data(mtcars)
dfs = mtcars %>% keep(mpg, disp, hp, wt)

with(dfs, w_mean(hp, weight = 1/wt))

# apply labels
dfs = modify(dfs, {
  var_lab(mpg) = "Miles/(US) gallon"
```

```

    var_lab(displ) = "Displacement (cu.in.)"
    var_lab(hp) = "Gross horsepower"
    var_lab(wt) = "Weight (1000 lbs)"
  })

# weighted correlations with labels
w_cor(dfs, weight = 1/dfs$wt)

# without labels
w_cor(unvr(dfs), weight = 1/dfs$wt)

```

---

xl\_write

---

*Write tables and other objects to an xlsx file with formatting*


---

## Description

Note that openxlsx package is required for these functions. It can be installed by printing `install.packages('openxlsx')` in the console. On Windows system you also may need to install `tools`. You can export several tables at once by combining them in a list. See examples.

## Usage

```

xl_write(obj, wb, sheet, row = 1, col = 1, ...)

## Default S3 method:
xl_write(obj, wb, sheet, row = 1, col = 1,
         rownames = FALSE, colnames = !is.atomic(obj), ...)

## S3 method for class 'list'
xl_write(obj, wb, sheet, row = 1, col = 1, gap = 1,
         ...)

## S3 method for class 'etable'
xl_write(obj, wb, sheet, row = 1, col = 1,
         remove_repeated = c("all", "rows", "columns", "none"),
         format_table = TRUE, borders = list(borderColour = "black",
         borderStyle = "thin"), header_format = openxlsx::createStyle(fgFill =
         "#EBEBEB", halign = "left", wrapText = FALSE),
         main_format = openxlsx::createStyle(halign = "right", numFmt =
         format(0, nsmall = get_expss_digits())),
         row_labels_format = openxlsx::createStyle(halign = "left"),
         total_format = openxlsx::createStyle(fgFill = "#EBEBEB", border =
         "TopBottom", borderStyle = "thin", halign = "right", numFmt = "0"),
         total_row_labels_format = openxlsx::createStyle(fgFill = "#EBEBEB",
         border = "TopBottom", borderStyle = "thin", halign = "left"),
         top_left_corner_format = header_format, row_symbols_to_remove = NULL,
         col_symbols_to_remove = NULL, other_rows_formats = NULL,
         other_row_labels_formats = NULL, other_cols_formats = NULL,

```

```

    other_col_labels_formats = NULL, additional_cells_formats = NULL,
    ...)

## S3 method for class 'with_caption'
xl_write(obj, wb, sheet, row = 1, col = 1,
  remove_repeated = c("all", "rows", "columns", "none"),
  format_table = TRUE, borders = list(borderColour = "black",
  borderStyle = "thin"), header_format = openxlsx::createStyle(fgFill =
  "#EBEBEB", halign = "left", wrapText = FALSE),
  main_format = openxlsx::createStyle(halign = "right", numFmt =
  format(0, nsmall = get_expss_digits())),
  row_labels_format = openxlsx::createStyle(halign = "left"),
  total_format = openxlsx::createStyle(fgFill = "#EBEBEB", border =
  "TopBottom", borderStyle = "thin", halign = "right", numFmt = "0"),
  total_row_labels_format = openxlsx::createStyle(fgFill = "#EBEBEB",
  border = "TopBottom", borderStyle = "thin", halign = "left"),
  top_left_corner_format = header_format, row_symbols_to_remove = NULL,
  col_symbols_to_remove = NULL, other_rows_formats = NULL,
  other_row_labels_formats = NULL, other_cols_formats = NULL,
  other_col_labels_formats = NULL, additional_cells_formats = NULL,
  caption_format = openxlsx::createStyle(textDecoration = "bold", halign
  = "left"), ...)

```

## Arguments

obj	table - result of <a href="#">cro</a> , <a href="#">fre</a> and etc. obj also can be data.frame, list or other objects.
wb	xlsx workbook object, result of <a href="#">createWorkbook</a> function.
sheet	numeric or character - worksheet name/number in the workbook wb
row	numeric - starting row for writing data
col	numeric - starting column for writing data
...	not yet used
rownames	logical should we write data.frame row names?
colnames	logical should we write data.frame column names?
gap	integer. Number of rows between list elements.
remove_repeated	Should we remove duplicated row or column labels in the rows/columns of the etable? Possible values: "all", "rows", "columns", "none".
format_table	logical should we format table? If FALSE all format arguments will be ignored.
borders	list Style of the table borders. List with two named elements: borderColour and borderStyle. For details see <a href="#">createStyle</a> function. If it is NULL then no table borders will be produced.
header_format	table header format - result of the <a href="#">createStyle</a> function.
main_format	result of the <a href="#">createStyle</a> function. Format of the table main area except total rows. Total rows is rows which row labels contain '#'.

row_labels_format	result of the <a href="#">createStyle</a> function. Format of the row labels area except total rows. Total rows is rows which row labels contain '#'.
total_format	result of the <a href="#">createStyle</a> function. Format of the total rows in the table main area. Total rows is rows which row labels contain '#'.
total_row_labels_format	result of the <a href="#">createStyle</a> function. Format of the total rows in the row labels area. Total rows is rows which row labels contain '#'.
top_left_corner_format	result of the <a href="#">createStyle</a> function.
row_symbols_to_remove	character vector. Perl-style regular expressions for substrings which will be removed from row labels.
col_symbols_to_remove	character vector. Perl-style regular expressions for substrings which will be removed from column names.
other_rows_formats	named list. Names of the list are perl-style regular expression patterns, items of the list are results of the <a href="#">createStyle</a> function. Rows in the main area which row labels contain pattern will be formatted according to the appropriate style.
other_row_labels_formats	named list. Names of the list are perl-style regular expression patterns, items of the list are results of the <a href="#">createStyle</a> function. Rows in the row labels area which row labels contain pattern will be formatted according to the appropriate style.
other_cols_formats	named list. Names of the list are perl-style regular expression patterns, items of the list are results of the <a href="#">createStyle</a> function. Columns in the main area which column labels contain pattern will be formatted according to the appropriate style.
other_col_labels_formats	named list. Names of the list are perl-style regular expression patterns, items of the list are results of the <a href="#">createStyle</a> function. Columns in the header area which column labels contain pattern will be formatted according to the appropriate style.
additional_cells_formats	list Each item of the list is list which consists of two elements. First element is two columns matrix or data.frame with row number and column numbers in the main area of the table. Such matrix can be produced with code <code>which(logical_condition, arr.ind = TRUE)</code> . Instead of matrix one can use function which accepts original table (obj) and return such matrix. Second element is result of the <a href="#">createStyle</a> function. Cells in the main area will be formatted according to this style.
caption_format	result of the <a href="#">createStyle</a> function.

**Value**

invisibly return vector with rows and columns (c(rows, columns)) occupied by outputted object.

**Examples**

```

## Not run:
library(openxlsx)
data(mtcars)
# add labels to dataset
mtcars = apply_labels(mtcars,
                      mpg = "Miles/(US) gallon",
                      cyl = "Number of cylinders",
                      disp = "Displacement (cu.in.)",
                      hp = "Gross horsepower",
                      drat = "Rear axle ratio",
                      wt = "Weight (lb/1000)",
                      qsec = "1/4 mile time",
                      vs = "Engine",
                      vs = c("V-engine" = 0,
                            "Straight engine" = 1),
                      am = "Transmission",
                      am = c("Automatic" = 0,
                            "Manual"=1),
                      gear = "Number of forward gears",
                      carb = "Number of carburetors"
                      )

# create table with caption
mtcars_table = calc_cro_cpct(mtcars,
                             cell_vars = list(cyl, gear),
                             col_vars = list(total(), am, vs)
                             ) %>%
  set_caption("Table 1")

wb = createWorkbook()
sh = addWorksheet(wb, "Tables")
# export table
xl_write(mtcars_table, wb, sh)
saveWorkbook(wb, "table1.xlsx", overwrite = TRUE)

## custom cells formatting
wb = createWorkbook()
sh = addWorksheet(wb, "Tables")

# we want to mark cells which are greater than total column
my_formatter = function(tbl){
  greater_than_total = tbl[,-1]>tbl[[2]]
  which(greater_than_total, arr.ind = TRUE)
}
# export table
xl_write(mtcars_table, wb, sh,
         additional_cells_formats = list(
           list(my_formatter, createStyle(textDecoration = "bold", fontColour = "blue"))
         )
)

```

```
saveWorkbook(wb, "table_with_additional_format.xlsx", overwrite = TRUE)

## automated report generation on multiple variables with the same banner

banner = calc(mtcars, list(total(), am, vs))

# create list of tables
list_of_tables = lapply(mtcars, function(variable) {
  if(length(unique(variable))<7){
    cro_cpct(variable, banner) %>% significance_cpct()
  } else {
    # if number of unique values greater than seven we calculate mean
    cro_mean_sd_n(variable, banner) %>% significance_means()
  }
})

wb = createWorkbook()
sh = addWorksheet(wb, "Tables")
# export list of tables with additional formatting
xl_write(list_of_tables, wb, sh,
  # remove '#' sign from totals
  col_symbols_to_remove = "#",
  row_symbols_to_remove = "#",
  # format total column as bold
  other_col_labels_formats = list("#" = createStyle(textDecoration = "bold")),
  other_cols_formats = list("#" = createStyle(textDecoration = "bold")),
)
saveWorkbook(wb, "report.xlsx", overwrite = TRUE)

## End(Not run)
```

# Index

## \*Topic **datasets**

- if\_na, 51
- product\_test, 67
- recode, 71
- vars, 106
- ..., 14
- .. (vars), 106
- ..f, 58
- ..f (vars), 106
- ..p, 59
- ..p (vars), 106
- ..t, 59
- ..t (vars), 106
- .add\_columns (vlookup), 113
- .add\_rows (add\_rows), 3
- .apply\_labels (apply\_labels), 4
- .apply\_val\_labs (apply\_labels), 4
- .apply\_var\_labs (apply\_labels), 4
- .calc (experimental), 40
- .calculate (experimental), 40
- .compute, 36
- .compute (experimental), 40
- .cro (experimental), 40
- .cro\_cases (experimental), 40
- .cro\_cpct (experimental), 40
- .cro\_fun (experimental), 40
- .cro\_fun\_df (experimental), 40
- .cro\_mean (experimental), 40
- .cro\_mean\_sd\_n (experimental), 40
- .cro\_median (experimental), 40
- .cro\_rpct (experimental), 40
- .cro\_sum (experimental), 40
- .cro\_tpct (experimental), 40
- .do\_if (experimental), 40
- .do\_repeat (do\_repeat), 37
- .except (keep), 54
- .fre (experimental), 40
- .if\_val (experimental), 40
- .keep (keep), 54
- .modify (experimental), 40
- .modify\_if (experimental), 40
- .recode (experimental), 40
- .sheet (sheet), 77
- .sort\_asc (sort\_asc), 78
- .sort\_desc (sort\_asc), 78
- .val\_lab (experimental), 40
- .var\_lab (experimental), 40
- .where (where), 117
- %a% (vectors), 111
- %add\_rows% (add\_rows), 3
- %calc% (compute), 13
- %calculate% (compute), 13
- %col\_in% (count\_if), 17
- %d% (vectors), 111
- %e% (vectors), 111
- %has% (count\_if), 17
- %i% (vectors), 111
- %if\_na% (if\_na), 51
- %into% (recode), 71
- %merge% (merge.etable), 57
- %mis\_val% (if\_na), 51
- %n\_d% (vectors), 111
- %n\_i% (vectors), 111
- %na\_if% (if\_na), 51
- %nest% (nest), 61
- %r% (vectors), 111
- %row\_in% (count\_if), 17
- %thru% (criteria), 23
- %to% (vars), 106
- %to\_list% (vars), 106
- %u% (vectors), 111
- %use\_labels% (compute), 13
- %>%, 85
- %i%, 23, 25
- %to%, 37, 84
- add\_columns (vlookup), 113
- add\_labelled\_class (var\_lab), 109
- add\_rows, 3, 27

- add\_sig\_labels
  - (tab\_significance\_options), 93
- add\_val\_lab (val\_lab), 104
- add\_val\_lab<- (val\_lab), 104
- all, 83
- all\_in\_col (sum\_row), 83
- all\_in\_row (sum\_row), 83
- and (criteria), 23
- any, 83
- any\_in\_col (sum\_row), 83
- any\_in\_row, 44
- any\_in\_row (sum\_row), 83
- append, 111
- apply\_col (sum\_row), 83
- apply\_col\_if (count\_if), 17
- apply\_dictionary (write\_labelled\_csv), 118
- apply\_labels, 4, 104, 110
- apply\_row (sum\_row), 83
- apply\_row\_if (count\_if), 17
- apply\_val\_labs (apply\_labels), 4
- apply\_var\_labs (apply\_labels), 4
- as.category, 5, 10, 58, 59
- as.criterion (criteria), 23
- as.data.frame, 78
- as.datatable\_widget, 7, 44, 76
- as.dichotomy, 6, 8, 58, 59
- as.etable, 11
- as.factor, 45, 47
- as.labelled, 11
- as.ordered, 47
- as.sheet (sheet), 77
- as\_is (do\_repeat), 37
- assign, 107
- autonom (val\_lab), 104
- ave, 118
- c, 31
- calc (compute), 13
- calc\_cro (cro), 27
- calc\_cro\_cases (cro), 27
- calc\_cro\_cpct (cro), 27
- calc\_cro\_cpct\_responses (cro), 27
- calc\_cro\_fun (cro\_fun), 31
- calc\_cro\_fun\_df (cro\_fun), 31
- calc\_cro\_mean (cro\_fun), 31
- calc\_cro\_mean\_sd\_n (cro\_fun), 31
- calc\_cro\_median (cro\_fun), 31
- calc\_cro\_pearson (cro\_fun), 31
- calc\_cro\_rpct (cro), 27
- calc\_cro\_spearman (cro\_fun), 31
- calc\_cro\_sum (cro\_fun), 31
- calc\_cro\_tpct (cro), 27
- calculate, 42, 80, 107, 108
- calculate (compute), 13
- cell\_chisq (tab\_significance\_options), 93
- chisq.test, 93, 96, 97
- combine\_functions, 88
- combine\_functions (cro\_fun), 31
- compare\_means, 97
- compare\_means (compare\_proportions), 12
- compare\_proportions, 12, 97
- complete.cases, 51
- compute, 13, 37, 44, 80, 108
- contains (criteria), 23
- copy (recode), 71
- count\_col\_if (count\_if), 17
- count\_if, 17, 23, 25, 44, 84
- count\_row\_if, 44
- count\_row\_if (count\_if), 17
- create\_dictionary (write\_labelled\_csv), 118
- createStyle, 125, 126
- createWorkbook, 125
- criteria, 19, 23, 37, 52, 54, 56, 71, 72, 79, 100, 106, 107, 112
- cro, 3, 4, 7, 27, 34, 39, 42, 44, 49, 50, 57, 58, 61, 63, 81, 88, 99, 100, 125
- cro\_cases, 93, 97
- cro\_cases (cro), 27
- cro\_cpct, 93, 97
- cro\_cpct (cro), 27
- cro\_cpct\_responses (cro), 27
- cro\_fun, 3, 4, 29, 31, 39, 42, 44, 57, 58, 81, 88
- cro\_fun\_df, 39
- cro\_fun\_df (cro\_fun), 31
- cro\_mean (cro\_fun), 31
- cro\_mean\_sd\_n, 93, 97
- cro\_mean\_sd\_n (cro\_fun), 31
- cro\_median (cro\_fun), 31
- cro\_pearson (cro\_fun), 31
- cro\_rpct (cro), 27
- cro\_spearman (cro\_fun), 31
- cro\_sum (cro\_fun), 31
- cro\_tpct (cro), 27
- data.frame, 78

- data.table, 33, 88
- datatable, 7
- default\_dataset, 3, 36, 40, 54, 78, 117
- do\_if, 37, 44
- do\_if (compute), 13
- do\_repeat, 37, 44, 80, 108
- drop\_all\_labels (unlab), 102
- drop\_c (drop\_empty\_rows), 39
- drop\_empty\_columns (drop\_empty\_rows), 39
- drop\_empty\_rows, 39, 88
- drop\_r (drop\_empty\_rows), 39
- drop\_rc, 85
- drop\_rc (drop\_empty\_rows), 39
- drop\_unused\_labels (val\_lab), 104
- drop\_val\_labs (val\_lab), 104
- drop\_var\_labs (var\_lab), 109
- dummy (as.dichotomy), 8
- dummy1 (as.dichotomy), 8
  
- eq (criteria), 23
- equals (criteria), 23
- except, 107, 108
- except (keep), 54
- experimental, 40
- expss, 43
- expss-package (expss), 43
- expss.options, 44, 49
- expss\_digits (expss.options), 44
- expss\_disable\_value\_labels\_support (expss.options), 44
- expss\_enable\_value\_labels\_support (expss.options), 44
- expss\_enable\_value\_labels\_support\_extreme (expss.options), 44
- expss\_fix\_encoding\_off (expss.options), 44
- expss\_fix\_encoding\_on (expss.options), 44
- expss\_output\_commented (expss.options), 44
- expss\_output\_default (expss.options), 44
- expss\_output\_raw (expss.options), 44
- expss\_output\_rnotebook (expss.options), 44
- expss\_output\_viewer (expss.options), 44
  
- factor, 45–47
- fctr, 46
- file, 120
  
- fixed (criteria), 23
- fre, 3, 4, 7, 29, 34, 42, 44, 47, 49, 50, 57, 88, 125
- fread, 120
- from (criteria), 23
- from\_to (recode), 71
- fwrite, 120
  
- ge (criteria), 23
- get, 107
- get\_caption (set\_caption), 76
- get\_expss\_digits (expss.options), 44
- greater (criteria), 23
- greater\_or\_equal (criteria), 23
- grep, 39, 100
- grepl, 23, 25
- gt (criteria), 23
- gte (criteria), 23
  
- has\_label (criteria), 23
- hi (recode), 71
- htmlTable, 7, 49, 50
- htmlTable.etable, 44, 49, 76
- htmlTable.list (htmlTable.etable), 49
- htmlTable.with\_caption (htmlTable.etable), 49
  
- if\_na, 44, 51
- if\_na<- (if\_na), 51
- if\_val (recode), 71
- if\_val<- (recode), 71
- ifelse, 43
- ifs, 44
- ifs (recode), 71
- index\_col (match\_row), 56
- index\_row, 44
- index\_row (match\_row), 56
- indirect (vars), 106
- indirect\_list (vars), 106
- info, 53
- interaction, 62
- is.category (as.category), 5
- is.dichotomy (as.dichotomy), 8
- is.etable (as.etable), 11
- is.labelled (as.labelled), 11
- is.with\_caption (set\_caption), 76
- is\_max (criteria), 23
- is\_min (criteria), 23
- items (criteria), 23

- keep, [54](#), [80](#), [107](#), [108](#)
- knit\_print.etable (htmlTable.etable), [49](#)
- knit\_print.with\_caption  
(htmlTable.etable), [49](#)
- lab\_num (val\_lab), [104](#)
- le (criteria), [23](#)
- less (criteria), [23](#)
- less\_or\_equal (criteria), [23](#)
- like (criteria), [23](#)
- lo (recode), [71](#)
- lt (criteria), [23](#)
- lte (criteria), [23](#)
- make\_labels (val\_lab), [104](#)
- make\_subheadings (split\_labels), [81](#)
- match\_col (match\_row), [56](#)
- match\_row, [23](#), [25](#), [44](#), [56](#)
- max\_col (sum\_row), [83](#)
- max\_col\_if (count\_if), [17](#)
- max\_if, [84](#)
- max\_if (count\_if), [17](#)
- max\_row, [43](#)
- max\_row (sum\_row), [83](#)
- max\_row\_if, [44](#)
- max\_row\_if (count\_if), [17](#)
- mdset, [6](#), [10](#), [27](#), [29](#), [33](#), [87](#)
- mdset (mrset), [58](#)
- mdset\_f (mrset), [58](#)
- mdset\_p (mrset), [58](#)
- mdset\_t (mrset), [58](#)
- mean\_col (sum\_row), [83](#)
- mean\_col\_if (count\_if), [17](#)
- mean\_if, [84](#)
- mean\_if (count\_if), [17](#)
- mean\_row, [43](#)
- mean\_row (sum\_row), [83](#)
- mean\_row\_if, [44](#)
- mean\_row\_if (count\_if), [17](#)
- median\_col (sum\_row), [83](#)
- median\_col\_if (count\_if), [17](#)
- median\_if, [84](#)
- median\_if (count\_if), [17](#)
- median\_row (sum\_row), [83](#)
- median\_row\_if (count\_if), [17](#)
- merge, [57](#)
- merge.etable, [27](#), [57](#)
- min\_col (sum\_row), [83](#)
- min\_col\_if (count\_if), [17](#)
- min\_if, [84](#)
- min\_if (count\_if), [17](#)
- min\_row, [43](#)
- min\_row (sum\_row), [83](#)
- min\_row\_if, [44](#)
- min\_row\_if (count\_if), [17](#)
- mis\_val (if\_na), [51](#)
- mis\_val<- (if\_na), [51](#)
- modify, [41](#), [83](#), [84](#), [107](#)
- modify (compute), [13](#)
- modify\_if, [41](#), [83](#), [84](#), [107](#)
- modify\_if (compute), [13](#)
- mrset, [6](#), [10](#), [27](#), [29](#), [33](#), [58](#), [87](#), [94](#)
- mrset\_f (mrset), [58](#)
- mrset\_p (mrset), [58](#)
- mrset\_t (mrset), [58](#)
- n2l (names2labels), [60](#)
- n\_diff (vectors), [111](#)
- n\_intersect (vectors), [111](#)
- na\_if, [23](#), [25](#), [87](#)
- na\_if (if\_na), [51](#)
- na\_if<- (if\_na), [51](#)
- name\_dots, [61](#)
- names2labels, [47](#), [60](#), [103](#)
- ne (criteria), [23](#)
- neq (criteria), [23](#)
- nest, [27](#), [61](#)
- net, [62](#)
- not (criteria), [23](#)
- not\_equals (criteria), [23](#)
- not\_na (criteria), [23](#)
- num\_lab (val\_lab), [104](#)
- old\_read\_labelled\_csv  
(write\_labelled\_csv), [118](#)
- old\_write\_labelled\_csv  
(write\_labelled\_csv), [118](#)
- or (criteria), [23](#)
- ordered, [47](#)
- other (criteria), [23](#)
- perl (criteria), [23](#)
- prepend\_all (prepend\_values), [65](#)
- prepend\_names (prepend\_values), [65](#)
- prepend\_values, [65](#)
- product\_test, [67](#)
- prop, [68](#)
- prop.test, [12](#), [13](#), [93](#), [97](#)

- prop\_col (prop), 68
- prop\_row (prop), 68
- qc, 69
- qe (qc), 69
- rbind, 3, 4
- read.spss, 70
- read.table, 101, 102
- read\_labelled\_csv (write\_labelled\_csv), 118
- read\_labelled\_csv2 (write\_labelled\_csv), 118
- read\_labelled\_fst (write\_labelled\_csv), 118
- read\_labelled\_tab (write\_labelled\_csv), 118
- read\_labelled\_tab2 (write\_labelled\_csv), 118
- read\_labelled\_xlsx (write\_labelled\_csv), 118
- read\_spss, 70
- read\_spss\_to\_list (read\_spss), 70
- rec (recode), 71
- rec<- (recode), 71
- recode, 23, 25, 42, 44, 52, 71
- recode<- (recode), 71
- ref, 36, 75
- ref<- (ref), 75
- regex (criteria), 23
- rep, 112
- repr\_html.etable (htmlTable.etable), 49
- repr\_html.with\_caption (htmlTable.etable), 49
- repr\_text.etable (htmlTable.etable), 49
- repr\_text.with\_caption (htmlTable.etable), 49
- sd\_col (sum\_row), 83
- sd\_col\_if (count\_if), 17
- sd\_if, 84
- sd\_if (count\_if), 17
- sd\_row (sum\_row), 83
- sd\_row\_if (count\_if), 17
- set\_caption, 76
- set\_val\_lab (val\_lab), 104
- set\_var\_lab (var\_lab), 109
- sheet, 77
- significance, 85, 88
  - significance (tab\_significance\_options), 93
  - significance\_cases (tab\_significance\_options), 93
  - significance\_cell\_chisq (tab\_significance\_options), 93
  - significance\_cpct, 12, 13
  - significance\_cpct (tab\_significance\_options), 93
  - significance\_means, 12, 13, 31
  - significance\_means (tab\_significance\_options), 93
  - sort\_asc, 78
  - sort\_desc (sort\_asc), 78
  - split, 80
  - split\_by, 79
  - split\_columns (split\_labels), 81
  - split\_labels, 81
  - split\_off (split\_by), 79
  - split\_separate (split\_by), 79
  - split\_table\_to\_df (split\_labels), 81
  - strsplit, 82
  - subset, 41
  - subst (qc), 69
  - subtotal (net), 62
  - sum\_col (sum\_row), 83
  - sum\_col\_if (count\_if), 17
  - sum\_if, 84
  - sum\_if (count\_if), 17
  - sum\_row, 43, 83
  - sum\_row\_if, 44
  - sum\_row\_if (count\_if), 17
  - t.test, 12, 13, 93, 97
  - tab\_cells (tables), 85
  - tab\_cols (tables), 85
  - tab\_last\_add\_sig\_labels (tab\_significance\_options), 93
  - tab\_last\_hstack (tables), 85
  - tab\_last\_round (tab\_significance\_options), 93
  - tab\_last\_sig\_cases (tab\_significance\_options), 93
  - tab\_last\_sig\_cell\_chisq (tab\_significance\_options), 93
  - tab\_last\_sig\_cpct (tab\_significance\_options), 93
  - tab\_last\_sig\_means (tab\_significance\_options), 93

- tab\_last\_vstack (tables), 85
- tab\_mis\_val (tables), 85
- tab\_net\_cells (net), 62
- tab\_net\_cols (net), 62
- tab\_net\_rows (net), 62
- tab\_pivot, 97
- tab\_pivot (tables), 85
- tab\_prepend\_all (prepend\_values), 65
- tab\_prepend\_names (prepend\_values), 65
- tab\_prepend\_values (prepend\_values), 65
- tab\_row\_label (tables), 85
- tab\_rows (tables), 85
- tab\_significance\_options, 93
- tab\_sort\_asc, 27, 85, 88, 99
- tab\_sort\_desc (tab\_sort\_asc), 99
- tab\_stat\_cases, 94
- tab\_stat\_cases (tables), 85
- tab\_stat\_cpct, 94
- tab\_stat\_cpct (tables), 85
- tab\_stat\_cpct\_responses (tables), 85
- tab\_stat\_fun (tables), 85
- tab\_stat\_fun\_df (tables), 85
- tab\_stat\_max (tables), 85
- tab\_stat\_mean (tables), 85
- tab\_stat\_mean\_sd\_n, 94
- tab\_stat\_mean\_sd\_n (tables), 85
- tab\_stat\_median (tables), 85
- tab\_stat\_min (tables), 85
- tab\_stat\_rpct (tables), 85
- tab\_stat\_sd (tables), 85
- tab\_stat\_se (tables), 85
- tab\_stat\_sum (tables), 85
- tab\_stat\_tpct (tables), 85
- tab\_stat\_unweighted\_valid\_n (tables), 85
- tab\_stat\_valid\_n (tables), 85
- tab\_subgroup (tables), 85
- tab\_subtotal\_cells (net), 62
- tab\_subtotal\_cols (net), 62
- tab\_subtotal\_rows (net), 62
- tab\_total\_label (tables), 85
- tab\_total\_row\_position (tables), 85
- tab\_total\_statistic (tables), 85
- tab\_transpose (tables), 85
- tab\_weight (tables), 85
- tables, 3, 4, 7, 27, 29, 34, 39, 44, 49, 58, 63–66, 85, 94, 97, 99
- text\_expand, 59, 107
- text\_expand (qc), 69
- text\_to\_columns, 101
- text\_to\_columns\_csv (text\_to\_columns), 101
- text\_to\_columns\_csv2 (text\_to\_columns), 101
- text\_to\_columns\_tab (text\_to\_columns), 101
- text\_to\_columns\_tab2 (text\_to\_columns), 101
- thru (criteria), 23
- to (criteria), 23
- total (cro), 27
- unlab, 102
- unvl, 102
- unvl (val\_lab), 104
- unvr, 102, 123
- unvr (var\_lab), 109
- unweighted\_valid\_n (w\_mean), 122
- use\_labels (compute), 13
- v2l (values2labels), 103
- v\_diff (vectors), 111
- v\_intersect (vectors), 111
- v\_union (vectors), 111
- v\_xor (vectors), 111
- val\_lab, 4, 42, 44, 47, 60, 70, 103, 104, 110
- val\_lab<- (val\_lab), 104
- valid (if\_na), 51
- valid\_n (w\_mean), 122
- value\_col\_if (match\_row), 56
- value\_row\_if (match\_row), 56
- values2labels, 47, 60, 103
- var\_lab, 4, 42, 44, 47, 60, 70, 103, 104, 109
- var\_lab<- (var\_lab), 109
- vars, 14, 106
- vars\_list (vars), 106
- vectors, 111
- vlookup, 43, 113
- vlookup\_df (vlookup), 113
- w\_cor (w\_mean), 122
- w\_cov (w\_mean), 122
- w\_mad (w\_mean), 122
- w\_max (w\_mean), 122
- w\_mean, 31, 122
- w\_median (w\_mean), 122
- w\_min (w\_mean), 122
- w\_n (w\_mean), 122

w\_pearson (w\_mean), 122  
w\_sd (w\_mean), 122  
w\_se (w\_mean), 122  
w\_spearman (w\_mean), 122  
w\_sum (w\_mean), 122  
w\_var (w\_mean), 122  
where, 41, 80, 107, 108, 116  
window\_fun, 118  
with, 14, 83, 107  
within, 14, 83, 107  
write\_labelled\_csv, 118  
write\_labelled\_csv2  
    (write\_labelled\_csv), 118  
write\_labelled\_fst  
    (write\_labelled\_csv), 118  
write\_labelled\_spss  
    (write\_labelled\_csv), 118  
write\_labelled\_tab  
    (write\_labelled\_csv), 118  
write\_labelled\_tab2  
    (write\_labelled\_csv), 118  
write\_labelled\_xlsx  
    (write\_labelled\_csv), 118  
write\_labels (write\_labelled\_csv), 118  
write\_labels\_spss (write\_labelled\_csv),  
    118  
  
xl\_write, 76, 124