

Package ‘matahari’

May 17, 2019

Type Package

Title Spy on Your R Session

Version 0.1.0

Description Conveniently log everything you type into the R console. Logs are stored as tidy data frames which can then be analyzed using 'tidyverse' style tools.

Depends R (>= 3.5.0)

Imports rstudioapi, tibble, readr, jsonlite, clipr, purrr, rlang

Suggests testthat, knitr, rmarkdown

License MIT + file LICENSE

URL <https://github.com/jhudsl/matahari>

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

BugReports <https://github.com/jhudsl/matahari/issues>

VignetteBuilder knitr

NeedsCompilation no

Author Sean Kross [aut, cre] (<<https://orcid.org/0000-0001-5215-0316>>),
Lucy D'Agostino McGowan [aut] (<<https://orcid.org/0000-0001-7297-9359>>),
Jeff Leek [ldr] (<<https://orcid.org/0000-0002-2873-2671>>)

Maintainer Sean Kross <sean@seankross.com>

Repository CRAN

Date/Publication 2019-05-17 08:20:12 UTC

R topics documented:

dance_recital	2
dance_remove	2
dance_report	3

dance_save	4
dance_start	4
dance_stop	5
dance_tbl	6

Index	7
--------------	----------

dance_recital	<i>Create a matahari-esque data frame from a file.</i>
---------------	--

Description

Create a matahari-esque data frame from a file.

Usage

```
dance_recital(code, evaluate = TRUE)
```

Arguments

code	A string or the path to a file containing R code.
evaluate	Logical, indicating whether to evaluate the code, default is TRUE

Examples

```
code_file <- system.file("test", "sample_code.R", package = "matahari")
dance_recital(code_file)
```

dance_remove	<i>Remove your logging history.</i>
--------------	-------------------------------------

Description

Remove your logging history.

Usage

```
dance_remove()
```

Value

Either TRUE if the log was removed or FALSE if the log does not exist (invisibly).

Examples

```
## Not run:  
  
dance_start()  
"Hello!"  
4 + 4  
dance_stop()  
dance_tbl()  
dance_remove()  
dance_tbl()  
  
## End(Not run)
```

dance_report

Copy the log to your clipboard.

Description

Copy the log to your clipboard.

Usage

```
dance_report(...)
```

Arguments

... Developer options.

Examples

```
## Not run:  
  
dance_start()  
"Hello!"  
4 + 4  
dance_stop()  
dance_report()  
  
## End(Not run)
```

dance_save	<i>Save the log as an rds file.</i>
------------	-------------------------------------

Description

Save the log as an rds file.

Usage

```
dance_save(path)
```

Arguments

path	The path to the rds file.
------	---------------------------

Examples

```
## Not run:  
  
dance_start()  
"Hello!"  
4 + 4  
dance_stop()  
dance_save("session.rds")  
  
## End(Not run)
```

dance_start	<i>Start Spying</i>
-------------	---------------------

Description

Start logging your R console activity. If you're using RStudio the contents of your current editor tab will also be tracked. All logging takes place when R code is executed in the R console.

Usage

```
dance_start(expr = TRUE, value = FALSE, path = FALSE,  
            contents = FALSE, selection = FALSE)
```

Arguments

expr	The R expressions typed into the R console will be logged unless this is set to FALSE.
value	Values that are computed on the R console will be logged unless this is set to FALSE.
path	The path to the file in focus on the RStudio editor will be logged unless this is set to FALSE.
contents	The file contents of the RStudio editor tab in focus will be logged unless this is set to FALSE.
selection	The text that is highlighted in the RStudio editor tab in focus will be logged unless this is set to FALSE.

Examples

```
## Not run:  
  
dance_start()  
"Hello!"  
4 + 4  
x <- 7  
x^2  
rm(x)  
x  
dance_stop()  
  
## End(Not run)
```

dance_stop

Stop Spying

Description

Pause the current logging session.

Usage

```
dance_stop()
```

Value

TRUE if logging was taking place, otherwise FALSE (invisibly).

Examples

```
## Not run:  
  
dance_start()  
"Hello!"  
4 + 4  
x <- 7  
x^2  
rm(x)  
x  
dance_stop()  
  
## End(Not run)
```

dance_tbl

Get the log as a data frame

Description

Get the log as a data frame

Usage

```
dance_tbl()
```

Value

Either a data frame containing your logged history or NULL if there is no log.

Examples

```
## Not run:  
  
dance_start()  
"Hello!"  
4 + 4  
dance_stop()  
dance_tbl()  
  
## End(Not run)
```

Index

dance_recital, 2
dance_remove, 2
dance_report, 3
dance_save, 4
dance_start, 4
dance_stop, 5
dance_tbl, 6