

Package ‘EDA’

July 2, 2018

Type Package

Title Energy Decomposition Analysis

Date 2018-07-02

Version 1.2

Maintainer Yongze Song <yongze.song@postgrad.curtin.edu.au>

Description Energy decomposition analysis for measuring contributions of components and factors on energy or carbon emission changes, as described in B.W. Ang (2005) <doi:10.1016/j.enpol.2003.10.010>. Includes Log Mean Devisia Index method and multi-year energy decomposition analysis using five methods.

Imports ggplot2, stats

Depends R (>= 3.3.0)

License GPL-2

RoxygenNote 6.0.1

LazyData true

Suggests knitr, rmarkdown

VignetteBuilder knitr

NeedsCompilation no

Author Yongze Song [aut, cre] (<<https://orcid.org/0000-0003-3420-9622>>),
Peng Wu [aut]

Repository CRAN

Date/Publication 2018-07-02 12:20:06 UTC

R topics documented:

CarbonEmission	2
EDA	2
LMDI	4
Index	6

CarbonEmission *Carbon emission data for energy decomposition analysis.*

Description

Carbon emission data for energy decomposition analysis.

Usage

carbon

energy

buildingarea

factordata

Format

carbon: A data frame of carbon emissions from multiple types of fuels and building sectors.

energy: A data frame energy consumptions from multiple types of fuels and building sectors.

buildingarea: A data frame of annual building areas. factordata: A list of data frames of factors of carbon emission changes.

Author(s)

Yongze Song <yongze.song@postgrad.curtin.edu.au>

EDA *Energy consumption analysis for calculating carbon emission changes*

Description

Energy consumption analysis for calculating carbon emission changes

Usage

```
EDA(cdata, factordata, Year = Year, Factor = Factor,
     Fuel = 1, Sector = 1, method = "LMDI")
## S3 method for class 'EDA'
print(x, ...)
## S3 method for class 'EDA'
plot(x, ...)
```

Arguments

<code>cdata</code>	A data.frame of annual carbon emission or energy consumption data, which can include multiple Fuels stored by columns.
<code>factordata</code>	A list of factors' data.frame.
<code>Year</code>	A numeric vector of year.
<code>Factor</code>	A vector of factor names.
<code>Fuel</code>	A vector of fuel names.
<code>Sector</code>	A vector of carbon emission or energy consumption sector names or number. If only one sector of carbon emission or energy consumption, set <code>Sector = 1</code> .
<code>method</code>	A character of energy consumption analysis method's name. One of "LMDI", "Laspeyres", "Paasche", "Marshall-Edgeworth" or "Walsh".
<code>x</code>	A list of EDA result.
<code>...</code>	Ignore

Author(s)

Yongze Song <yongze.song@postgrad.curtin.edu.au> and Peng Wu <peng.wu@curtin.edu.au>.

References

- Ang, B. W. (2005). The LMDI approach to decomposition analysis: a practical guide. *Energy policy*, 33(7), 867-871.
- Marlay, R. C. (1984). Trends in industrial use of energy. *Science*, 226, 1277-1284.
- Paasche, H. *Über die Preisentwicklung der letzten Jahre. Jahrbücher für Nationalökonomie und Statistik*, 23(1874), 168.
- Marshall, A. (1887). Remedies for fluctuations of general prices.
- Edgeworth, F. Y. (1925). *Papers relating to political economy*.
- Walsh, C. M. (1921). The Problem of Estimation, a Seventeenth-century Controversy and Its Bearing on Modern Statistical Questions, Especially Index-numbers, by Correa Moylan Walsh.

See Also

[LMDI](#)

Examples

```
library(EDA)
data(carbon)
data(factordata)
## set parameters
cdata <- carbon[, -c(1,2)]
Year <- 2001:2005
Sector <- c("b1", "b2", "b3")
Fuel <- colnames(cdata)
Factor <- names(factordata)
## run EDA model
```

```
eda1 <- EDA(cdata, factordata, Year = Year, Factor = Factor,
           Fuel = Fuel, Sector = Sector, method = "LMDI")
eda1
plot(eda1)
```

LMDI

Log Mean Devisia Index method for energy decomposition analysis

Description

Log Mean Devisia Index method for energy decomposition analysis

Usage

```
LMDI(C0, CT, X0, XT)
## S3 method for class 'LMDI'
print(x, ...)
```

Arguments

C0	A numeric vector or a data.frame of carbon emission or energy consumption in the initial year.
CT	A numeric vector or a data.frame of carbon emission or energy consumption in the year T.
X0	A numeric vector or a data.frame of an impact factor in the initial year.
XT	A numeric vector or a data.frame of an impact factor in the year T.
x	A list of LMDI result.
...	Ignore

Author(s)

Yongze Song <yongze.song@postgrad.curtin.edu.au> and Peng Wu <peng.wu@curtin.edu.au>.

References

Ang, B. W. (2005). The LMDI approach to decomposition analysis: a practical guide. *Energy policy*, 33(7), 867-871.

See Also

[EDA](#)

Examples

```
library(EDA)
data(carbon)
data(factordata)
## set parameters
cdata <- carbon[,-c(1,2)]
C0 <- cdata[1,]
CT <- cdata[2,]
X0 <- factordata[[2]][1,]
XT <- factordata[[2]][2,]
## run LMDI model
ed1 <- LMDI(C0, CT, X0, XT)
ed1
```

Index

*Topic **Carbon**

CarbonEmission, 2

*Topic **Emission**

CarbonEmission, 2

*Topic **datasets**

CarbonEmission, 2

buildingarea (CarbonEmission), 2

carbon (CarbonEmission), 2

CarbonEmission, 2

EDA, 2, 4

energy (CarbonEmission), 2

factordata (CarbonEmission), 2

LMDI, 3, 4

plot.EDA (EDA), 2

print.EDA (EDA), 2

print.LMDI (LMDI), 4