

Package ‘diagmeta’

April 11, 2019

Title Meta-Analysis of Diagnostic Accuracy Studies with Several Cutpoints

Version 0.3-1

Date 2019-04-09

Depends meta (>= 4.9-0)

Imports lme4, grDevices

URL <https://github.com/guido-s/diagmeta>

Description Provides methods by Steinhauser et al. (2016) <DOI:10.1186/s12874-016-0196-1> for meta-analysis of diagnostic accuracy studies with several cutpoints.

License GPL (>= 2)

Encoding UTF-8

RoxygenNote 6.1.1

NeedsCompilation no

Author Gerta Rücker [aut] (<<https://orcid.org/0000-0002-2192-2560>>),
Susanne Steinhauser [aut],
Srinath Kolampally [aut],
Guido Schwarzer [aut, cre] (<<https://orcid.org/0000-0001-6214-9087>>)

Maintainer Guido Schwarzer <sc@imbi.uni-freiburg.de>

Repository CRAN

Date/Publication 2019-04-11 11:55:39 UTC

R topics documented:

diagmeta-package	2
as.data.frame.diagmeta	3
diagmeta	4
diagstats	7
ipd2diag	9
plot.diagmeta	10
print.diagmeta	13
print.diagstats	14

print.summary.diagmeta	15
Schneider2017	16
summary.diagmeta	17

Index	19
--------------	-----------

diagmeta-package	<i>diagmeta: Brief overview of methods and general hints</i>
------------------	--

Description

R package **diagmeta** implements the method by Steinhauser et al. (2016) for the meta-analysis of diagnostic test accuracy studies with multiple cutoffs.

Details

Main function of R package **diagmeta** is the eponymous `diagmeta`. Corresponding functions for printing and plotting are available: `print.diagmeta`, `plot.diagmeta`

Furthermore, a summary function and corresponding print function are available to provide a briefer output: `summary.diagmeta`, `print.summary.diagmeta`

Additional functions provided in **diagmeta** are `diagstats` to calculate additional statistical measures for the diagnostic test accuracy meta-analysis and `ipd2diag` to transform individual participant data to the data format required by `diagmeta`.

Type `help(package = "diagmeta")` for a listing of R functions and datasets available in **diagmeta**.

Type `citation("diagmeta")` for the preferred citation of R package **diagmeta**.

To report problems and bugs

- type `bug.report(package = "diagmeta")` if you do not use RStudio,
- send an email to Guido Schwarzer <sc@imbi.uni-freiburg.de> if you use RStudio.

The development version of **diagmeta** is available on GitHub <https://github.com/guido-s/diagmeta>.

Author(s)

Gerta Rucker <ruecker@imbi.uni-freiburg.de>, Susanne Steinhauser <susanne.steinhauser@uni-koeln.de>, Srinath Kolampally <kolampal@imbi.uni-freiburg.de>, Guido Schwarzer <sc@imbi.uni-freiburg.de>

References

Steinhauser S, Schumacher M, Rucker G (2016): Modelling multiple thresholds in meta-analysis of diagnostic test accuracy studies. *BMC Medical Research Methodology*, **16**, 97

`as.data.frame.diagmeta`*Extract data frame from diagmeta objects*

Description

Extract data frame from objects of class `diagmeta`.

Usage

```
## S3 method for class 'diagmeta'  
as.data.frame(x, row.names = NULL, optional = FALSE,  
  ...)
```

Arguments

<code>x</code>	An object of class <code>diagmeta</code> .
<code>row.names</code>	Argument of R function <code>as.data.frame</code> (ignored).
<code>optional</code>	Argument of R function <code>as.data.frame</code> (ignored).
<code>...</code>	Other arguments.

Value

A data frame is returned by the function `as.data.frame`.

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

See Also

[diagmeta summary.diagmeta](#)

Examples

```
# FENO dataset  
#  
data(Schneider2017)  
  
diag1 <- diagmeta(tpos, fpos, tneg, fneg, cutpoint,  
  studlab = paste(author, year, group),  
  data = Schneider2017,  
  model = "DIDS", log.cutoff = TRUE)  
  
as.data.frame(diag1)
```

diagmeta	<i>Meta-analysis of diagnostic test accuracy studies with the multiple cutoffs model</i>
----------	--

Description

Diagnostic tests may be based on an ordinal or continuous biomarker or an ordinal score together with a cutoff. The decision whether the target condition is present or not (positive or negative test result) depends on whether the observed value is above or below the cutoff. Here we assume that higher values of the biomarker indicate a greater probability for the target condition (e.g., a disease); otherwise, the pooling must be changed by multiplying all values of the biomarker by -1. Sensitivity and specificity of the test depend on the chosen cutoff and vary with the cutoff. In meta-analysis of diagnostic accuracy studies, results are often reported for multiple cutoffs within a study, and the cutoffs may differ between studies. The multiple cutoffs model creates a link between the range of cutoffs and the respective pairs of sensitivity and specificity and thus allows identifying cutoffs at which the test is likely to perform best (Steinhauser et al., 2016).

Usage

```
diagmeta(TP, FP, TN, FN, cutoff, studlab, data = NULL,
         distr = "logistic", model = "DICS", equalvar = FALSE,
         lambda = 0.5, log.cutoff = FALSE, method.weights = "invvar",
         level = 0.95, incr = 0.5, n.iter.max = 1000, tol = 1e-08,
         silent = TRUE, ...)
```

Arguments

TP, FP, TN, FN	Numeric vectors giving the number of true positives, false positives, true negatives and false negatives
cutoff	A number vector indicating the cutoff values
studlab	A numeric or a character vector with study labels
data	An optional data frame containing the study information
distr	A character indicating the distribution (see Details)
model	A character indicating the model (see Details)
equalvar	A logical indicating whether the variances of the biomarker in both groups are thought equal (see Details)
lambda	A numeric between 0 and 1 indicating the weight of the sensitivity (such that specificity receives weight 1 - lambda)
log.cutoff	A logical indicating whether the cutoffs should be log-transformed
method.weights	A character indicating the method for weighting the studies: invvar (default) means inverse variance weighting, size means weighting by group sample size, equal means that all studies are equally weighted
level	A numeric indicating the significance level (1 - alpha) for tests (default is 0.95)
incr	A numeric between 0 and 1 that is added as a continuity correction

<code>n.iter.max</code>	A numeric indicating the maximal number of fixed point iterations for finding the optimal cutoff
<code>tol</code>	A numeric indicating the tolerance for convergence of the fixed point iteration
<code>silent</code>	A logical indicating whether iterations should be suppressed
<code>...</code>	additional arguments

Details

Each row of the data set provides at least a study label, a cutoff and the numbers of true positives, false positives, true negatives and false negatives. Different studies may contribute a varying number of cutoffs, as well as different sets of cutoffs.

The multiple cutoffs model is a multi-level random effects model. At the study level, for the group of patients without the target condition (in short disease-free), the specificities at all available cutoffs together provide an estimate of the cumulative distribution function (cdf) of the test results within the disease-free individuals. Likewise, for patients with the target condition (in short diseased), via the observed sensitivities at all observed cutoffs we obtain an estimate of the cdf of the test results within the diseased patients. At the meta-analytic level, the model fits the data for both groups and all available cutoffs over all studies. Based on a parametric model, it provides estimates of the two cdfs for the two groups across all studies, accounting for the between-study heterogeneity and correlation between groups.

Users have the choice between the normal (argument `distr="normal"`) and the logistic distribution (argument `distr="logistic"` which is the default). In addition, it is possible to log-transform the cutoffs (argument `log.cutoff`, default is `FALSE`).

The cdf, transformed using the quantile function of the chosen distribution, is modelled by one of eight mixed linear models ("DIDS", "CIDS", "DICS", "CICS", "DS", "CS", "DI", "CI") as described in Steinhauser et al. (2016). The argument `equalvar` indicates if the variances of the biomarker in both groups are assumed to be equal (`equalvar = TRUE`) or unequal (`equalvar = FALSE`).

The pooled sensitivity and specificity values can be obtained at every cutoff; a multiple cutoffs summary ROC (sROC) naturally follows while preserving cutoff information. The optimal cutoff is defined as the cutoff where the maximum of a weighted sum of sensitivity and specificity is obtained: $\lambda * \text{sensitivity} + (1 - \lambda) * \text{specificity}$. The 95% confidence intervals of sensitivities, specificities and the optimal cutoff are estimated using the delta method (Steinhauser et al., 2016).

Value

An object of class "diagmeta" with corresponding print, summary, and plot function. The object is a list containing the following components

<code>TP, FP, TN, FN</code>	As defined above.
<code>cutoff, studlab</code>	As defined above.
<code>Sens</code>	Sensitivity (original data).
<code>Spec</code>	Specificity (original data).
<code>distr, model, equalvar, lambda</code>	As defined above.

<code>log.cutoff</code> , <code>method.weights</code>	As defined above.
<code>level</code> , <code>incr</code>	As defined above.
<code>k</code>	The number of studies in the meta-analysis.
<code>optcut</code>	The optimal cutoff.
<code>lower.optcut</code> , <code>upper.optcut</code>	Corresponding lower and upper confidence limits (for normal distribution).
<code>Sens.optcut</code>	The sensitivity at the optimal cutoff.
<code>lower.Sens.optcut</code> , <code>upper.Sens.optcut</code>	Corresponding lower and upper confidence limits.
<code>Spec.optcut</code>	The specificity at the optimal cutoff.
<code>lower.Spec.optcut</code> , <code>upper.Spec.optcut</code>	Corresponding lower and upper confidence limits.
<code>AUC</code>	Area under the curve (AUC)
<code>AUCSens.lower</code> , <code>AUCSens.upper</code>	Corresponding lower and upper confidence limits (based on the confidence region for the sensitivity, given the specificity)
<code>AUCSpec.lower</code> , <code>AUCSpec.upper</code>	Corresponding lower and upper confidence limits (based on the confidence region for the specificity, given the sensitivity)
<code>var.diseased</code> , <code>var.nondiseased</code>	The within-study variance for the diseased and non-diseased group, respectively.
<code>AIC</code>	The value of the Akaike information criterion of the <code>lmer</code> object.
<code>BIC</code>	The value of the Bayesian information criterion of the <code>lmer</code> object.
<code>data.lmer</code>	A list with elements <code>Study</code> (study labels), <code>Group</code> (group labels (0 or 1)), <code>Cutoff</code> , <code>N</code> (group sizes), <code>Negative</code> (number of negative test results), <code>NN</code> (frequencies of negative test results).
<code>result.lmer</code>	An object of class <code>lmer</code> .
<code>weights</code>	Normalized weights per study, group, and cutoff such that the sum of weights is twice the number of cutoffs over all studies.
<code>regr</code>	A list with point estimates, variances, and covariances from regression parameters of <code>lmer</code> object.
<code>dist</code>	A list containing estimated means, standard deviations, and variances of distributions from diseased (ending with 1) and non-diseased (ending with 0).
<code>n.iter.max</code>	As defined above.
<code>call</code>	Function call.
<code>version</code>	Version of R package diagmeta used to create object.

Author(s)

Gerta Rucker <ruecker@imbi.uni-freiburg.de>, Susanne Steinhauser <susanne.steinhauser@uni-koeln.de>, Srinath Kolampally <kolampal@imbi.uni-freiburg.de>, Guido Schwarzer <sc@imbi.uni-freiburg.de>

References

Steinhauser S, Schumacher M, Rucker G (2016): Modelling multiple thresholds in meta-analysis of diagnostic test accuracy studies. *BMC Medical Research Methodology*, **16**, 97

See Also

[plot.diagmeta](#), [summary.diagmeta](#)

Examples

```
# FENO dataset
#
data(Schneider2017)

diag1 <- diagmeta(tpos, fpos, tneg, fneg, cutpoint,
                  studlab = paste(author, year, group),
                  data = Schneider2017,
                  model = "DIDS", log.cutoff = TRUE)

summary(diag1)
plot(diag1)
```

diagstats	<i>Calculate statistical measures of test performance for objects of class diagmeta</i>
-----------	---

Description

The user can provide cutoffs, sensitivities, and / or specificities to calculate the respective quantities (with confidence intervals). Furthermore, positive predictive values (PPV), negative predictive values (NPV), and probabilities of disease (PD) are calculated if the prevalence is provided.

Usage

```
diagstats(x, cutoff = x$optcut, sens, spec, prevalence, level = 0.95)
```

Arguments

x	An object of class diagmeta
cutoff	A numeric or vector with cutoff value(s)
sens	A numeric or vector with sensitivity value(s)
spec	A numeric or vector with specificity value(s)
prevalence	A numeric or vector with the prevalence(s)
level	The level used to calculate confidence intervals

Value

A data frame of class "diagstats" with the following variables:

cutoff	Cutoffs provided in argument "cutoff" and / or model-based cutoff values for given sensitivities / specificities.
Sens	Sensitivities provided in argument "sens" and / or model-based estimates of the sensitivity for given cutoffs / specificities
seSens	Standard error of sensitivity
lower.Sens, upper.Sens	Lower and upper confidence limits of the sensitivity
Spec	Specificities provided in argument "spec" and / or model-based estimates of the specificity for given cutoffs / sensitivities
seSpec	Standard error of specificity
lower.Spec, upper.Spec	Lower and upper confidence limits of the specificity
prevalence	As defined above.
PPV	Positive predictive value (based on the cutoff)
NPV	Negative predictive value (based on the cutoff)
PD	Probability of disease if the given cutoff value was observed as the measurement for an individual
dens.nondiseased	Value of the model-based density function at the cutoff(s) for non-diseased individuals
dens.diseased	Value of the model-based density function at the cutoff(s) for diseased individuals

Author(s)

Gerta Rücker <ruecker@imbi.uni-freiburg.de>, Srinath Kolampally <kolampal@imbi.uni-freiburg.de>, Guido Schwarzer <sc@imbi.uni-freiburg.de>

See Also

[diagmeta print.diagstats](#)

Examples

```
# FENO dataset
#
data(Schneider2017)

diag1 <- diagmeta(tpos, fpos, tneg, fneg, cutpoint,
                 studlab = paste(author, year, group),
                 data = Schneider2017,
                 model = "DIDS", log.cutoff = TRUE)

# Results at the optimal cutoff
```

```
#
diagstats(diag1)

# Results for cutoffs 25 and 50 (and a prevalence of 10%)
#
diagstats(diag1, c(25, 50), prevalence = 0.10)

# Results for sensitivity and specificity of 0.95
#
diagstats(diag1, sens = 0.95, spec = 0.95)
```

ipd2diag	<i>Individual participant data to enter them into diagmeta</i>
----------	--

Description

Function to transform individual patient data (IPD) to enter them into `diagmeta`

Usage

```
ipd2diag(studlab, value, status)
```

Arguments

<code>studlab</code>	A vector with study labels
<code>value</code>	A vector with individual patients' measurements of a discrete or continuous variable
<code>status</code>	A vector with information of the individual's status (0 = non-diseased, 1 = diseased)

Value

A data frame with values that can be entered into [diagmeta](#).

Author(s)

Gerta Rücker <ruecker@imbi.uni-freiburg.de>, Srinath Kolampally <kolampal@imbi.uni-freiburg.de>

See Also

[diagmeta](#), [plot.diagmeta](#), [print.diagmeta](#), [summary.diagmeta](#)

Examples

```

# Simulate IPD data for three studies, each with 30 patients based
# on normally distributed marker values
#
k <- 3
n <- 30
m <- c(20, 23, 26)
d <- 10
s <- 5
studlab <- c(rep(1, n), rep(2, n), rep(3, n))
status <- rep(c(rep(0, n / 2), rep(1, n / 2)), k)
measurement <- c(rnorm(n / 2, m[1], s), rnorm(n/2, m[1] + d, s),
                 rnorm(n / 2, m[2], s), rnorm(n/2, m[2] + d, s),
                 rnorm(n / 2, m[3], s), rnorm(n/2, m[3] + d, s))

#
IPDdata <- data.frame(studlab, measurement, status)
str(IPDdata)

# Transform these data using ipd2diag()
#
diagdata <- ipd2diag(studlab, value = measurement, status = status)
str(diagdata)

# Run diagmeta()
#
diag1 <- diagmeta(TP, FP, TN, FN, cutoff, studlab,
                 data = diagdata,
                 model = "DIDS", distr = "normal")

summary(diag1)
plot(diag1)
par(mfrow = c(1, 2))
plot(diag1, which = "ROC", lines = TRUE)
plot(diag1, which = "SROC", ciSens = TRUE,
     ciSpec = TRUE, lines = TRUE, shading = "hatch")

```

plot.diagma

Plot for meta-analysis of diagnostic test accuracy studies with the multiple cutoffs model

Description

Provides several plots for meta-analysis of diagnostic test accuracy studies with the multiple cutoffs model

Usage

```

## S3 method for class 'diagmeta'
plot(x, which = c("survival", "youden", "roc",

```

```
"sroc"), xlab = "threshold", main, ci = FALSE, ciSens = FALSE,
ciSpec = FALSE, mark.optcut = FALSE, mark.cutpoints = FALSE,
points = TRUE, lines = FALSE, rlines = TRUE, line.optcut = TRUE,
col.points = "rainbow", cex = 1, pch.points = 16,
col.ci = "gray", cex.marks = 0.7 * cex, lwd = 1, lwd.optcut = 2 *
lwd, shading = "none", ellipse = FALSE, xlim = NULL, ...)
```

Arguments

x	An object of class <code>diagmeta</code>
which	A character vector indicating the type of plot, either "reg" or "cdf" or "survival" or "Youden" or "ROC" or "SROC" or "density"
xlab	An x axis label
main	A logical indicating title to the plot
ci	A logical indicating whether confidence intervals should be plotted for "reg", "cdf", "survival", "Youden", and "sensspec"
ciSens	A logical indicating whether confidence intervals should be plotted for sensitivity, given the specificity in "SROC" plot
ciSpec	A logical indicating whether confidence intervals should be plotted for specificity, given the sensitivity in "SROC" plot
mark.optcut	A logical indicating whether the optimal cutoff should be marked on "SROC" plot
mark.cutpoints	A logical indicating whether the given cutoffs should be marked on "SROC" plot
points	A logical indicating whether points should be plotted on "ROC" plot
lines	A logical indicating whether polygonal lines connecting points belonging to the same study should be printed in plots "reg", "cdf", "survival", "Youden", and "sensspec"
rlines	A logical indicating whether regression lines or curves should be plotted for plots "reg", "cdf", "survival", "Youden", and "sensspec"
line.optcut	A logical indicating whether a vertical line should be plotted at the optimal cut-off line for plots "cdf", "survival", "Youden", and "density"
col.points	A character string indicating color of points, either "rainbow", "topo", "heat", "terrain", "cm", "grayscale" or any color defined in colours
cex	A numeric indicating magnification to be used for plotting text and symbols
pch.points	A numeric indicating plot symbol(s) for points
col.ci	A character string indicating color of confidence lines
cex.marks	A numeric indicating magnification(s) to be used for marking cutoffs
lwd	A numeric indicating line width
lwd.optcut	A numeric indicating line width of optimal cutoff
shading	A character indicating shading and hatching confidence region in "SROC" plot, either "none" or "shade" or "hatch"
ellipse	A logical indicating whether a confidence ellipse should be drawn around the optimal cutoff

xlim	A character or numerical vector indicating the minimum and maximum value for the horizontal axes
...	Additional graphical arguments

Details

The first argument of the plot function is an object of class "diagmeta".

The second argument which indicates which sort of plot(s) should be shown. For which="reg", a scatter plot of the quantil-transformed proportions of negative test results with two regression lines is shown. Points belonging to the same study are marked with the same colour. For which="cdf", the two cumulative distribution functions are shown, corresponding to the proportions of negative test results. For which="survival", the survival functions are shown, corresponding to the proportions of positive test results. For which="Youden", the (potentially weighted) sum of sensitivity and specificity minus 1 is shown; in case of $\lambda=0.5$ (the default) this is the Youden index. For which="ROC", study-specific ROC curves are shown. For which="SROC", the model-based summary ROC curve is shown. For which="density", the model-based densities of both groups are shown. For which="sensspec", the sensitivity (decreasing with increasing cutoff) and the specificity (increasing with increasing cutoff) are shown. Instead of character strings, a numeric value or vector can be used to specify plots with numbers corresponding to the following order of plots: "regression", "cdf", "survival", "youden", "roc", "sroc", "density", and "sensspec".

Other arguments refer to further plot parameters, such as lines (whether points belonging to the same study should be joined), rlines (whether regression curves should be drawn), ci / ciSens / ciSpec / ellipse (whether confidence regions should be shown), line.optcut / mark.optcut (whether the optimal cutoff should be indicated), and additional plot parameters (see Arguments).

If no further arguments are provided, four standard plots ("survival", "Youden", "ROC", and "SROC") are produced in a 2 x 2 format.

Author(s)

Gerta Rucker <ruecker@imbi.uni-freiburg.de>, Susanne Steinhauser <susanne.steinhauser@uni-koeln.de>, Srinath Kolampally <kolampal@imbi.uni-freiburg.de>, Guido Schwarzer <sc@imbi.uni-freiburg.de>

References

Schneider A, Linde K, Reitsma JB, Steinhauser S, Rucker G (2017): A novel statistical model for analyzing data of a systematic review generates optimal cutoff values for fractional exhaled nitric oxide for asthma diagnosis. *Journal of Clinical Epidemiology*, **92**, 69–78

Steinhauser S, Schumacher M, Rucker G (2016): Modelling multiple thresholds in meta-analysis of diagnostic test accuracy studies. *BMC Medical Research Methodology*, **16**, 97

See Also

[diagmeta](#)

Examples

```
# FENO dataset
#
```

```
data(Schneider2017)

diag1 <- diagmeta(tpos, fpos, tneg, fneg, cutpoint,
                 studlab = paste(author, year, group),
                 data = Schneider2017,
                 model = "DIDS", log.cutoff = TRUE)

# Regression plot with confidence intervals
#
plot(diag1, which = "reg", lines = FALSE, ci = TRUE)

# Cumulative distribution plot with optimal cutoff line and
# confidence intervals
#
plot(diag1, which = "cdf", line.optcut = TRUE, ci = TRUE)

# Survival plot with optimal cutoff line and confidence intervals
#
plot(diag1, which = "survival", line.optcut = TRUE, ci = TRUE)

# Youden plot of optimal cutoff line and confidence intervals
#
plot(diag1, which = "youden",
     lines = TRUE, line.optcut = TRUE, ci = TRUE)

# ROC plot of lines connecting points belonging to the same study
#
plot(diag1, which = "ROC", lines = TRUE)

# SROC plot of confidence regions for sensitivity and specificity
# with optimal cutoff mark
#
plot(diag1, which = "SROC",
     ciSens = TRUE, ciSpec = TRUE, mark.optcut = TRUE,
     shading = "hatch")

# Density plot of densities for both groups with optimal cutoff
# line
#
plot(diag1, which = "density", line.optcut = TRUE)
```

print.diagmeta

Print method for diagmeta objects

Description

Print method for objects of class `diagmeta`.

Usage

```
## S3 method for class 'diagmeta'
print(x, digits = 3, ...)
```

Arguments

x	An object of class diagmeta.
digits	Number of significant digits for printing.
...	Additional arguments.

Author(s)

Gerta Rücker <ruecker@imbi.uni-freiburg.de>, Susanne Steinhauser <susanne.steinhauser@uni-koeln.de>, Srinath Kolampally <kolampal@imbi.uni-freiburg.de>

See Also

[diagmeta summary.diagmeta](#)

Examples

```
# FENO dataset
#
data(Schneider2017)

diag1 <- diagmeta(tpos, fpos, tneg, fneg, cutpoint,
                 studlab = paste(author, year, group),
                 data = Schneider2017,
                 model = "DIDS", log.cutoff = TRUE)

diag1
```

print.diagstats

Print method for diagstats objects

Description

Print method for objects of class diagstats.

Usage

```
## S3 method for class 'diagstats'
print(x, sensspec = TRUE, predicted = TRUE,
      density = FALSE, digits = 3, ...)
```

Arguments

x	An object of class diagmeta.
sensspec	A logical indicating whether sensitivities and specificities should be printed.
predicted	A logical indicating whether predicted values should be printed.
density	A logical indicating whether values of the model-based density functions should be printed.
digits	Number of significant digits for printing.
...	Additional arguments.

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

See Also

[diagstats diagmeta](#)

Examples

```
# FENO dataset
#
data(Schneider2017)

diag1 <- diagmeta(tpos, fpos, tneg, fneg, cutpoint,
                 studlab = paste(author, year, group),
                 data = Schneider2017,
                 model = "DIDS", log.cutoff = TRUE)

# Values for prevalence 10% at cutoffs 25 and 50
#
ds1 <- diagstats(diag1, c(25, 50), 0.10)
ds1
print(ds1, predicted = FALSE)
```

```
print.summary.diagmeta
```

Print method for summary of diagmeta objects

Description

Print method for objects of class summary.diagmeta.

Usage

```
## S3 method for class 'summary.diagmeta'
print(x, digits = 3, ...)
```

Arguments

x An object of class `summary.diagmeta`.
 digits Number of significant digits for printing.
 ... Additional arguments.

Author(s)

Gerta Rücker <ruecker@imbi.uni-freiburg.de>, Susanne Steinhauser <susanne.steinhauser@uni-koeln.de>, Srinath Kolampally <kolampal@imbi.uni-freiburg.de>, Guido Schwarzer <sc@imbi.uni-freiburg.de>

See Also

[diagmeta summary.diagmeta](#)

Examples

```
# FENO dataset
#
data(Schneider2017)

diag1 <- diagmeta(tpos, fpos, tneg, fneg, cutpoint,
                 studlab = paste(author, year, group),
                 data = Schneider2017,
                 model = "DIDS", log.cutoff = TRUE)

summary(diag1)
print(summary(diag1), digits = 2)
```

Schneider2017

Meta-analysis of studies of the diagnostic test accuracy of FENO for diagnosis of asthma

Description

Meta-analysis of studies of the diagnostic test accuracy of fractional exhaled nitric oxide (FENO) for diagnosis of asthma.

The data were collected for a systematic review by Karrasch et al. (2017) and are published as a supplement (Appendix 1) to Schneider et al. (2017). They have been preprocessed for use in R package **diagmeta**.

Usage

```
Schneider2017
```

Format

A data frame with the following columns:

study_id	numeric study ID
author	first author
year	year of publication
group	information on subgroup
cutpoint	cutpoint (FeNO [ppb])
tpos	number of true positives
fneg	number of false negatives
fpos	number of false positives
tneg	number of true negatives

Source

Karrasch S, Linde K, Rücker G, Sommer H, Karsch-Volk M, Kleijnen J, Jörres RA, Schneider A (2017): Accuracy of FENO for diagnosing asthma: a systematic review. *Thorax*, **72**, 109e16

Schneider A, Linde K, Reitsma JB, Steinhauser S, Rücker G (2017): A novel statistical model for analyzing data of a systematic review generates optimal cutoff values for fractional exhaled nitric oxide for asthma diagnosis. *Journal of Clinical Epidemiology*, **92**, 69–78

Examples

```
# FENO dataset
#
data(Schneider2017)

diag1 <- diagmeta(tpos, fpos, tneg, fneg, cutpoint,
                  studlab = paste(author, year, group),
                  data = Schneider2017,
                  model = "DIDS", log.cutoff = TRUE)

plot(diag1)
```

summary.diagmeta	<i>Summary method for diagmeta</i>
------------------	------------------------------------

Description

Summary method for objects of class `diagmeta`.

Usage

```
## S3 method for class 'diagmeta'
summary(object, ...)
```

Arguments

<code>object</code>	An object of class <code>diagmeta</code> .
<code>...</code>	Additional arguments.

Value

A list with classes 'summary.diagmeta' and 'diagmeta' is returned. The list elements are identical to a [diagmeta](#) object.

Author(s)

Srinath Kolampally <kolampal@imbi.uni-freiburg.de>, Guido Schwarzer <sc@imbi.uni-freiburg.de>

See Also

[diagmeta](#)

Examples

```
# FENO dataset
#
data(Schneider2017)

diag1 <- diagmeta(tpos, fpos, tneg, fneg, cutpoint,
                 studlab = paste(author, year, group),
                 data = Schneider2017,
                 model = "DIDS", log.cutoff = TRUE)

summary(diag1)
```

Index

*Topic **datasets**

Schneider2017, 16

*Topic **hplot**

plot.diagmeta, 10

*Topic **package**

diagmeta-package, 2

*Topic **print**

print.diagmeta, 13

print.diagstats, 14

print.summary.diagmeta, 15

as.data.frame, 3

as.data.frame.diagmeta, 3

colours, 11

diagmeta, 2, 3, 4, 8, 9, 12, 14–16, 18

diagmeta-package, 2

diagstats, 2, 7, 15

ipd2diag, 2, 9

lmer, 6

plot.diagmeta, 2, 7, 9, 10

print.diagmeta, 2, 9, 13

print.diagstats, 8, 14

print.summary.diagmeta, 2, 15

Schneider2017, 16

summary.diagmeta, 2, 3, 7, 9, 14, 16, 17