

Package ‘grainscape’

August 9, 2019

Type Package

Title Landscape Connectivity, Habitat, and Protected Area Networks

Description Given a landscape resistance surface, creates grains of connectivity (Galpern et al. (2012) <doi:10.1111/j.1365-294X.2012.05677.x>) and minimum planar graph (Fall et al. (2007) <doi:10.1007/s10021-007-9038-7>) models that can be used to calculate effective distances for landscape connectivity at multiple scales.

URL <https://achubaty.github.io/grainscape>,
<https://github.com/achubaty/grainscape>

Version 0.4.0

Date 2019-08-06

License GPL (>= 2)

Imports ggplot2, graphics, grDevices, igraph, methods, sp, raster,
Rcpp (>= 0.12.11.4), rgdal, utils

LinkingTo Rcpp

Suggests cowplot, ggthemes, hunspell, knitr, parallel, rgeos,
rmarkdown, spelling, testthat

VignetteBuilder knitr, rmarkdown

BugReports <https://github.com/achubaty/grainscape/issues>

ByteCompile yes

Collate 'grainscape-package.R' 'classes.R' 'GOC.R' 'MPG.R'
'RcppExports.R' 'grain.R' 'corridor.R' 'deprecated.R'
'distance.R' 'export.R' 'extract.R' 'ggGS.R' 'graphdf.R'
'habitatConnectivityEngine.R' 'patchFilter.R' 'plot.R'
'point.R' 'theme_grainscape.R' 'threshold.R' 'zzz.R'

Encoding UTF-8

Language en-CA

RoxygenNote 6.1.1

NeedsCompilation yes

Author Paul Galpern [aut, cph],
 Sam Doctolero [aut],
 Alex M Chubaty [aut, cre] (<<https://orcid.org/0000-0001-7146-8135>>)

Maintainer Alex M Chubaty <alex.chubaty@gmail.com>

Repository CRAN

Date/Publication 2019-08-09 10:30:02 UTC

R topics documented:

grainscape-package	2
corridor	4
corridor-class	6
distance	6
export	8
ggGS	11
GOC	14
goc-class	16
grain	16
grain-class	18
grainscape-maps	19
graphdf	19
gsGOC	21
gsMPGstitch	22
MPG	23
mpg-class	25
patchFilter	25
plot,corridor,ANY-method	27
point	29
show,goc-method	31
theme_grainscape	32
threshold	33
\$	35
Index	36

grainscape-package	<i>Efficient Modelling of Landscape Connectivity, Habitat, and Protected Area Networks</i>
--------------------	--

Description

Given a landscape resistance surface, creates grains of connectivity and minimum planar graph models that can be used to calculate effective distances for landscape connectivity at multiple scales.

Details

Landscape connectivity modelling to understand the movement and dispersal of organisms has been done using raster resistance surfaces and landscape graph methods. Grains of connectivity (GOC) models combine elements of both approaches to produce a continuous and scalable tool that can be applied in a variety of study systems. The purpose of this package is to implement grains of connectivity analyses. Routines accept raster-based resistance surfaces as input and return raster, vector and graph-based data structures to represent connectivity at multiple scales. Effective distances describing connectivity between geographic locations can be determined at multiple scales. Analyses of this sort can contribute to corridor identification, landscape genetics, as well as other connectivity assessments. Minimum planar graph (MPG; Fall *et al.*, 2007) models of resource patches on landscapes can also be generated using the software.

MPG calculations and generalization of the Voronoi tessellation used in GOC models is based on the routines in SELES software (Fall and Fall, 2001). Routines also depend on the `sp` (Pebesma and Bivand, 2005), `raster` (Hijmans and van Etten, 2011), `igraph` (Csardi and Nepusz, 2006), and optionally `rgeos` packages (Bivand and Rundel, 2012).

A vignette detailing the use of this package for landscape connectivity modelling is included. See `browseVignettes('grainscape')`.

A detailed tutorial is available as a vignette.

Author(s)

Maintainer: Alex M Chubaty <alex.chubaty@gmail.com> (0000-0001-7146-8135)

Authors:

- Paul Galpern <pgalpern@gmail.com> [copyright holder]
- Sam Doctolero <sam.doctolero@gmail.com>

References

- Bivand, R.S. and C. Rundel. (2016). `rgeos`: Interface to Geometry Engine - Open Source (GEOS). R package version 0.3-19, <https://CRAN.R-project.org/package=rgeos>.
- Csardi, G. and T. Nepusz. (2006). The `igraph` software package for complex network research. *InterJournal Complex Systems* 1695. <http://igraph.org>.
- Fall, A. and J. Fall. (2001). A domain-specific language for models of landscape dynamics. *Ecological Modelling* 141:1-18.
- Fall, A., M.-J. Fortin, M. Manseau, D. O'Brien. (2007) Spatial graphs: Principles and applications for habitat connectivity. *Ecosystems* 10:448:461.
- Galpern, P., M. Manseau. (2013a) Finding the functional grain: comparing methods for scaling resistance surfaces. *Landscape Ecology* 28:1269-1291.
- Galpern, P., M. Manseau. (2013b) Modelling the influence of landscape connectivity on animal distribution: a functional grain approach. *Ecography* 36:1004-1016.
- Galpern, P., M. Manseau, A. Fall. (2011) Patch-based graphs of landscape connectivity: A guide to construction, analysis and application for conservation. *Biological Conservation* 144:44-55.
- Galpern, P., M. Manseau, P.J. Wilson. (2012) Grains of connectivity: analysis at multiple spatial scales in landscape genetics. *Molecular Ecology* 21:3996-4009.

Hijmans, R.J. and J. van Etten. (2016). raster: Geographic analysis and modeling with raster data. R package version 2.5-8, <https://CRAN.R-project.org/package=raster>.

Pebesma, E.J. and R.S. Bivand. (2005). Classes and methods for spatial data in R. R News 5 (2), <https://cran.r-project.org/doc/Rnews/>.

See Also

Useful links:

- <https://achubaty.github.io/grainscape>
- <https://github.com/achubaty/grainscape>
- Report bugs at <https://github.com/achubaty/grainscape/issues>

corridor	<i>Visualize corridors between two points using a grains of connectivity (GOC)</i>
----------	--

Description

Given a series of GOC models built at different scales, visualize the corridor (or shortest path) between two points using one of the tessellations (i.e., scales) in these models.

Usage

```
corridor(x, ...)
```

```
## S4 method for signature 'goc'
corridor(x, whichThresh, coords, weight = "meanWeight",
...)
```

Arguments

x	A goc object created by GOC .
...	Additional arguments (not used).
whichThresh	Integer giving the index of the threshold to visualize.
coords	A two column matrix or a SpatialPoints object giving coordinates at the end points of the corridor.
weight	The GOC graph link weight to use in calculating the distance. Please see details in distance .

Value

An object of class [corridor](#).

Author(s)

Paul Galpern and Alex Chubaty

References

- Fall, A., M.-J. Fortin, M. Manseau, D. O'Brien. (2007) Spatial graphs: Principles and applications for habitat connectivity. *Ecosystems* 10:448-461.
- Galpern, P., M. Manseau. (2013a) Finding the functional grain: comparing methods for scaling resistance surfaces. *Landscape Ecology* 28:1269-1291.
- Galpern, P., M. Manseau. (2013b) Modelling the influence of landscape connectivity on animal distribution: a functional grain approach. *Ecography* 36:1004-1016.
- Galpern, P., M. Manseau, A. Fall. (2011) Patch-based graphs of landscape connectivity: a guide to construction, analysis, and application for conservation. *Biological Conservation* 144:44-55.
- Galpern, P., M. Manseau, P.J. Wilson. (2012) Grains of connectivity: analysis at multiple spatial scales in landscape genetics. *Molecular Ecology* 21:3996-4009.

See Also

[GOC](#), [visualize](#)

Examples

```
## Load raster landscape
tiny <- raster::raster(system.file("extdata/tiny.asc", package = "grainscape"))

## Create a resistance surface from a raster using an is-becomes reclassification
tinyCost <- raster::reclassify(tiny, rcl = cbind(c(1, 2, 3, 4), c(1, 5, 10, 12)))

## Produce a patch-based MPG where patches are resistance features=1
tinyPatchMPG <- MPG(cost = tinyCost, patch = tinyCost == 1)

## Extract a representative subset of 5 grains of connectivity
tinyPatchGOC <- GOC(tinyPatchMPG, nThresh = 5)

## Quick visualization of a corridor
corridorStartEnd <- rbind(c(10, 10), c(90, 90))
tinyPatchCorridor <- corridor(tinyPatchGOC, whichThresh = 3, coords = corridorStartEnd)
if (interactive())
  plot(tinyPatchCorridor)

## More control over a corridor visualization
if (interactive()) {
  plot(tinyPatchCorridor@voronoi, col = "lightgrey", lwd = 2)
  plot(tinyPatchCorridor@linksSP, col = "darkred", lty = "dashed", add = TRUE)
  plot(tinyPatchCorridor@nodesSP, col = "darkred", pch = 21, bg = "white", add = TRUE)
  plot(tinyPatchCorridor@shortestLinksSP, col = "darkred", lty = "solid", lwd = 2, add = TRUE)
  plot(tinyPatchCorridor@shortestNodesSP, col = "darkred", pch = 21, bg = "darkred", add = TRUE)
  mtext(paste("Corridor shortest path length:",
             round(tinyPatchCorridor@corridorLength, 2),
             "resistance units"), side = 1)
}
```

corridor-class *The corridor class*

Description

The corridor class

Slots

voronoi A RasterLayer representation of the boundaries of the voronoi polygons.

linksSP A SpatialLinesDataFrame representation of links in the grains of connectivity graph.

nodesSP A SpatialPoints representation of the nodes in the grains of connectivity graph

shortestLinksSP A SpatialLines representation of the links in the shortest path between coordinates

shortestNodesSP A SpatialPoints representation of the nodes in the shortest path between coordinates

corridorLength A numeric of length 1 giving the length of the shortest path between coordinates in accumulated resistance units.

See [corridor](#) for more information.

Author(s)

Alex Chubaty and Paul Galpern

distance *Find the grains of connectivity network distance*

Description

Find the shortest network distance between pairs of points using the GOC graph. This can be used as an effective distance for landscape connectivity assessments.

Usage

```
distance(x, y, ...)
```

```
## S4 method for signature 'goc,SpatialPoints'
distance(x, y, weight = "meanWeight", ...)
```

```
## S4 method for signature 'goc,matrix'
distance(x, y, weight = "meanWeight", ...)
```

```
## S4 method for signature 'goc,numeric'
distance(x, y, weight = "meanWeight", ...)
```

Arguments

x	A goc object produced by GOC .
y	A two column matrix or a SpatialPoints object giving the coordinates of points of interest.
...	Additional arguments (not used).
weight	The GOC graph link weight to use in calculating the distance. Please see Details for explanation.

Value

A list object giving a distance matrix for each threshold in the GOC object. Distance matrices give the pairwise grains of connectivity network distances between sampling locations. Matrix indices correspond to rows in the coordinates matrix (y).

Author(s)

Paul Galpern and Alex Chubaty

References

Fall, A., M.-J. Fortin, M. Manseau, D. O'Brien. (2007) Spatial graphs: Principles and applications for habitat connectivity. *Ecosystems* 10:448:461.

Galpern, P., M. Manseau. (2013a) Finding the functional grain: comparing methods for scaling resistance surfaces. *Landscape Ecology* 28:1269-1291.

Galpern, P., M. Manseau. (2013b) Modelling the influence of landscape connectivity on animal distribution: a functional grain approach. *Ecography* 36:1004-1016.

Galpern, P., M. Manseau, A. Fall. (2011) Patch-based graphs of landscape connectivity: a guide to construction, analysis, and application for conservation. *Biological Conservation* 144:44-55.

Galpern, P., M. Manseau, P.J. Wilson. (2012) Grains of connectivity: analysis at multiple spatial scales in landscape genetics. *Molecular Ecology* 21:3996-4009.

See Also

[GOC](#), [point](#)

Examples

```
## Load raster landscape
tiny <- raster::raster(system.file("extdata/tiny.asc", package = "grainscape"))

## Create a resistance surface from a raster using an is-becomes reclassification
tinyCost <- raster::reclassify(tiny, rcl = cbind(c(1, 2, 3, 4), c(1, 5, 10, 12)))

## Produce a patch-based MPG where patches are resistance features=1
tinyPatchMPG <- MPG(cost = tinyCost, patch = tinyCost == 1)

## Extract a representative subset of 5 grains of connectivity
tinyPatchGOC <- GOC(tinyPatchMPG, nThresh = 5)
```

```
## Three sets of coordinates in the study area
loc <- cbind(c(30, 60, 90), c(30, 60, 90))

## Find the GOC network distance matrices between these points
## for each of the 5 grains of connectivity
tinyDist <- grainscape::distance(tinyPatchGOC, loc)
```

export

Export spatial data from MPG and GOC models

Description

This function automates the export of raster and vector spatial data from `mpg` and `grain` objects. By default it places them in a new directory, unless an existing one is specified with `overwrite = TRUE`.

It can also be used to process `mpg` and `grain` objects to produce R spatial objects that are convenient for plotting or analysis within R. Use `R = TRUE` in which case all parameters related to file export are ignored. (Default `R = FALSE`)

The raster package `writeRaster` is used for rasters, and `writeOGR` in the `rgdal` package is used to export ESRI compatible shape files.

Usage

```
export(x, dirname = NULL, path = ".", rasterFormat = "GTiff",
       overwrite = FALSE, R = FALSE, vorBound = FALSE, ...)
```

```
## S4 method for signature 'mpg'
export(x, dirname = NULL, path = ".",
       rasterFormat = "GTiff", overwrite = FALSE, R = FALSE,
       vorBound = FALSE, ...)
```

```
## S4 method for signature 'grain'
export(x, dirname = NULL, path = ".",
       rasterFormat = "GTiff", overwrite = FALSE, R = FALSE,
       vorBound = FALSE, ...)
```

```
## S4 method for signature 'goc'
export(x, dirname = NULL, path = ".",
       rasterFormat = "GTiff", overwrite = FALSE, R = FALSE,
       vorBound = FALSE, ...)
```

Arguments

<code>x</code>	A <code>mpg</code> or <code>grain</code> object
<code>dirname</code>	The name of a new directory to create. If <code>NULL</code> a directory with a name containing the date and time will be created.

path	A path to where this new directory dirname should be created. Defaults to the working directory.
rasterFormat	The format for exported rasters. See writeFormats for options. Defaults to GeoTiff (rasterFormat='GTiff'). Use rasterFormat='raster' to save .grd files in native raster package format.
overwrite	If directory already exists will overwrite existing files inside. Defaults to FALSE.
R	If TRUE, return the spatial objects that would be written to files. Do not write these files and ignore dirname, path, rasterFormat, overwrite parameters. This is useful for visualization using R plotting functions, or spatial analysis within R. Defaults to FALSE
vorBound	Specify whether to create a raster with the boundaries of the Voronoi polygons =1 and the remainder =NA. This may be useful for visualizing relationships among polygons in a grain of connectivity. This can add time to the export on very large rasters. Defaults to FALSE.
...	Additional arguments (not used).

Value

Invisibly returns the path to the folder created.

Side effect of exporting files representing raster and vector spatial data in the object.

Please note that for vector data export the attribute name is limited to 8 characters in shape files. See the tables below for the abbreviations used and their meaning.

Exported from mpg objects:

nodes, linksCentroid, linksPerim are shape files giving the locations of the patch centroids, links among centroids, and links among perimeters of patches respectively. patchId, voronoi are rasters giving the patch identifier of the patch, or of the patch that the Voronoi polygon refers to. lcpPerimWeight, lcplLinkId give the weight in cost surface units of the shortest paths between perimeters, and the identifiers of those links respectively. vorBound gives the boundaries of the Voronoi polygons (if specified).

Description of node (vertex) and link (edge) weights in mpg objects and their corresponding attribute names in the shape files created.

type	MPG name	SHP name	Description
node	patchId	patchId	Patch ID from patchId raster
node	patchArea	patchA	Area of patch
node	patchEdgeArea	patchEA	Edge area of patch
node	coreArea	coreA	Area excluding edge of patch
node	centroidX	ctrX	Centroid of the patch (X)
node	centroidY	ctrY	Centroid of the patch (Y)
link	e1	e1	Id of first patch at end of link
link	e2	e2	Id of second patch at end of link
link	linkId	linkId	Link ID from lcplLinkId raster
link	lcPerimWeight	lcpPerWt	Cost length of link from patch perimeters
link	startPerimX	strtPerX	Coordinate of link endpoint on first patch (X)
link	startPerimY	strtPerY	Coordinate of link endpoint on first patch (Y)
link	endPerimX	endPerX	Coordinate of link endpoint on second patch (X)

link endPerimY endPerY Coordinate of link endpoint on second patch (Y)

Exported from grain objects:

nodes, linksCentroid are shape files giving the locations of the Voronoi polygon centroids and links among them respectively. voronoi are rasters gives the polygon identifier of each cluster of patches. vorBound gives the boundaries of the Voronoi polygons (if specified).

Description of node (vertex) and link (edge) weights in grain objects and their corresponding attribute names in the shape files created.

Type	GOC name	SHP name	Description
node	polyonId	polyId	Polygon ID from grain voronoi raster
node	polyonArea	polyA	Area of polygon from grain voronoi raster
node	totalPatchArea	patchA	Total area of all patches in polygon
node	totalPatchEdgeArea	patchEA	Total area of all patch edges in polygon
node	totalCoreArea	coreA	Total area of patches in polygon excluding edges
node	centroidX	ctrX	Centroid of the polygon (X)
node	centroidY	ctrY	Centroid of the polygon (Y)
link	e1	e1	ID of first patch at end of link
link	e2	e2	ID of second patch at end of link
link	maxWeight	maxWt	The maximum weight of all links connecting patches between polygons
link	linkIdMaxWeight	maxWt	The link id of that maximum weight link (lcpLinkId)
link	minWeight	min	The minimum weight of all links connecting patches between polygons
link	linkIdMinWeight	minWt	The link id of that minimum weight link (lcpLinkId)
link	medianWeight	medWt	The median weight of all links connecting patches between polygons
link	meanWeight	meanWT	The minimum weight of all links connecting patches between polygons
link	numlinksWeight	numEWt	The number of links connecting patches between polygons
link	eucCentroidWeight	eucCtrWt	The Euclidean distance between centroids of polygons

Author(s)

Paul Galpern and Alex Chubaty

See Also

[MPG](#), [GOC](#), [grain](#)

Examples

```
## Load raster landscape
tiny <- raster::raster(system.file("extdata/tiny.asc", package = "grainscape"))

## Create a resistance surface from a raster using an is-becomes reclassification
tinyCost <- raster::reclassify(tiny, rcl = cbind(c(1, 2, 3, 4), c(1, 5, 10, 12)))

## Produce a patch-based MPG where patches are resistance features=1
tinyPatchMPG <- MPG(cost = tinyCost, patch = tinyCost == 1)
```

```
## Extract a representative subset of 5 grains of connectivity
tinyPatchGOC <- GOC(tinyPatchMPG, nThresh = 5)

## Export raster and vectors of a grain to a specified directory
tmpdir <- tempdir()
export(grain(tinyPatchGOC, 2), dirname = "tiny_goc_thresh2", path = tmpdir)
unlink(file.path(tmpdir, "tiny_goc_thresh2"), recursive = TRUE)

## Export rasters and vectors of the MPG and place in an R object
sp_tinyPatchMPG <- export(tinyPatchMPG, R = TRUE)
```

ggGS

Prepare data in MPG and grain objects for use with ggplot2

Description

This is an informal fortify-type method that prepares either `RasterLayer` or `igraph` objects contained as slots within MPG or grain objects for easy plotting with `ggplot`.

Usage

```
ggGS(x, type = NULL, ...)

## S4 method for signature 'RasterLayer'
ggGS(x, type = NULL, ...)

## S4 method for signature 'list'
ggGS(x, type = NULL, ...)

## S4 method for signature 'mpg'
ggGS(x, type = NULL, ...)

## S4 method for signature 'grain'
ggGS(x, type = NULL, ...)

## S4 method for signature 'goc'
ggGS(x, type = NULL, ...)
```

Arguments

<code>x</code>	A <code>mpg</code> , <code>grain</code> , or <code>RasterLayer</code> object.
<code>type</code>	If a <code>mpg</code> or <code>grain</code> object is supplied, this gives the name of the slot to prepare for plotting. Options are discussed below. Not required if a <code>RasterLayer</code> is supplied.
<code>...</code>	Additional arguments (not used).

Value

A data.frame suitable for plotting with `ggplot`.

Where `type` is a raster the data.frame will have the following columns:

`value` the value of the raster cell
`x` the x coordinate of the centre of the raster cell
`y` the y coordinate of the centre of the raster cell

Where `type = 'nodes'` the data.frame will have the following columns:

`x` the x coordinate of the node
`y` the y coordinate of the node
 ... other attributes associated with the network nodes

Where `type = 'links'` the data.frame will have the following columns:

`x1` the x coordinate of the first node
`y1` the y coordinate of the first node
`x2` the x coordinate of the second node
`y2` the y coordinate of the second node
`x1p` the x coordinate at the perimeter of the first node
`y1p` the y coordinate at the perimeter of the first node
`x2p` the x coordinate at the perimeter of the second node
`y2p` the y coordinate at the perimeter of the second node
 ... other attributes associated with the network links

Note**Options for type parameter**

If a `RasterLayer` is supplied `type` is optional.

For `mpg` type options are `"node"` or `"links"`. This prepares the nodes and links of the minimum planar graph network for plotting. Also `"patchId"`, `"voronoi"`, `"lcpPerimWeight"`, `"lcpLinkId"`, `"mpgPlot"` will prepare rasters for plotting.

For grain objects type options are `"nodes"` or `"links"` to prepare the nodes and links of the grains of connectivity network for plotting. Also `"voronoi"` will prepare the grains of connectivity Voronoi polygons raster for plotting.

For either `mpg` or grain objects `type = "vorBound"` will identify the boundaries of the Voronoi polygons for plotting. This is potentially time consuming for large rasters.

Author(s)

Paul Galpern and Alex Chubaty

See Also[MPG, GOC](#)**Examples**

```

## Load raster landscape
tiny <- raster::raster(system.file("extdata/tiny.asc", package = "grainscape"))

## Create a resistance surface from a raster using an is-becomes reclassification
tinyCost <- raster::reclassify(tiny, rcl = cbind(c(1, 2, 3, 4), c(1, 5, 10, 12)))

## Produce a patch-based MPG where patches are resistance features=1
tinyPatchMPG <- MPG(cost = tinyCost, patch = tinyCost == 1)

## Extract a representative subset of 5 grains of connectivity
tinyPatchGOC <- GOC(tinyPatchMPG, nThresh = 5)

if (interactive()) {
  library(ggplot2)

  ## Plot the patches in a minimum planar graph
  theme_set(theme_grainscape())
  ggplot() +
    geom_tile(data = ggGS(tinyPatchMPG, "patchId"),
              aes(x = x, y = y, fill = value))

  ## Plot the grain polygons in a grain of connectivity
  ggplot() +
    geom_tile(data = ggGS(grain(tinyPatchGOC, 3), "voronoi"),
              aes(x = x, y = y, fill = value))

  ## Plot the grain polygon boundaries
  ggplot() +
    geom_tile(data = ggGS(grain(tinyPatchGOC, 3), "vorBound"),
              aes(x = x, y = y, fill = value))

  ## Plot the patches and perimeter links of a minimum planar graph
  ggplot() +
    geom_tile(data = ggGS(tinyPatchMPG, "patchId"),
              aes(x = x, y = y, fill = value)) +
    geom_segment(data = ggGS(tinyPatchMPG, "links"),
                 aes(x = x1p, y = y1p, xend = x2p, yend = y2p))

  ## Plot the patches and linear representations of the perimeter links
  ## of a minimum planar graph
  ggplot() +
    geom_tile(data = ggGS(tinyPatchMPG, "patchId"),
              aes(x = x, y = y, fill = value)) +
    geom_segment(data = ggGS(tinyPatchMPG, "links"),
                 aes(x = x1p, y = y1p, xend = x2p, yend = y2p))

  ## Plot the nodes and links of a grains of connectivity network

```

```

## superimposed over the grain polygons
focalGrain <- grain(tinyPatchGOC, 3)
ggplot() +
  geom_tile(data = ggGS(focalGrain, "vorBound"),
            aes(x = x, y = y, fill = value)) +
  geom_point(data = ggGS(focalGrain, "nodes"), aes(x = x, y = y)) +
  geom_segment(data = ggGS(focalGrain, "links"),
              aes(x = x1, y = y1, xend = x2, yend = y2))
}

```

GOC

Produce a grains of connectivity model at multiple scales (patch-based or lattice GOC)

Description

Produce a grains of connectivity (GOC) model at multiple scales (resistance thresholds) by scalar analysis. Patch-based or lattice GOC modelling can be done with this function.

Usage

```
GOC(x, ...)
```

```

## S4 method for signature 'mpg'
GOC(x, nThresh = NULL, doThresh = NULL,
    weight = "lcpPerimWeight", verbose = 0, ...)

```

Arguments

x	A mpg object produced by MPG . For lattice GOC MPG must be run with patch set as an integer value.
...	Additional arguments (not used).
nThresh	Optional. An integer giving the number of thresholds (or scales) at which to create GOC models. Thresholds are selected to produce a maximum number of unique grains (i.e., models). nThresh thresholds are also approximately evenly spread between 0 and the threshold at which all patches or focal points on the landscape are connected. This is a simple way to get a representative subset of all possible GOC models. Provide either nThresh or doThresh not both.
doThresh	Optional. A vector giving the link thresholds at which to create GOC models. Use link{threshold} to identify thresholds of interest. Provide either nThresh or doThresh not both.
weight	A string giving the link weight or attribute to use for threshold. "lcpPerimWeight" uses the accumulated resistance or least-cost path distance from the perimeters of patches as the link weight. "eucPerimWeight" use the Euclidean distance from the perimeters of patches as the link weight.
verbose	Set verbose=0 for no progress information to console.

Details

Grain or scalar analysis of connectivity may be appropriate for a variety of purposes, not limited to visualization and improving connectivity estimates for highly-mobile organisms. See Galpern *et al.* (2012), Galpern & Manseau (2013a, 2013b) for applications and review of these capabilities.

Value

A [goc](#) object.

Note

Researchers should consider whether the use of a patch-based GOC or a lattice GOC model is appropriate based on the patch-dependency of the organism under study. Patch-based models make most sense when animals are restricted to, or dependent on, a resource patch. Lattice models can be used as a generalized and functional approach to scaling resistance surfaces.

See [MPG](#) for warning related to areal measurements.

Author(s)

Paul Galpern

References

Fall, A., M.-J. Fortin, M. Manseau, D. O'Brien. (2007) Spatial graphs: Principles and applications for habitat connectivity. *Ecosystems* 10:448:461.

Galpern, P., M. Manseau. (2013a) Finding the functional grain: comparing methods for scaling resistance surfaces. *Landscape Ecology* 28:1269-1291.

Galpern, P., M. Manseau. (2013b) Modelling the influence of landscape connectivity on animal distribution: a functional grain approach. *Ecography* 36:1004-1016.

Galpern, P., M. Manseau, A. Fall. (2011) Patch-based graphs of landscape connectivity: a guide to construction, analysis, and application for conservation. *Biological Conservation* 144:44-55.

Galpern, P., M. Manseau, P.J. Wilson. (2012) Grains of connectivity: analysis at multiple spatial scales in landscape genetics. *Molecular Ecology* 21:3996-4009.

See Also

[MPG](#), [grain](#), [distance](#), [point](#)

Examples

```
## Load raster landscape
tiny <- raster::raster(system.file("extdata/tiny.asc", package = "grainscape"))

## Create a resistance surface from a raster using an is-becomes reclassification
tinyCost <- raster::reclassify(tiny, rcl = cbind(c(1, 2, 3, 4), c(1, 5, 10, 12)))

## Produce a patch-based MPG where patches are resistance features=1
tinyPatchMPG <- MPG(cost = tinyCost, patch = tinyCost == 1)
```

```
## Extract a representative subset of 5 grains of connectivity
tinyPatchGOC <- GOC(tinyPatchMPG, nThresh = 5)

## Examine the properties of the GOC graph of grain 3 of 5
graphdf(grain(tinyPatchGOC, whichThresh = 3))

## Extract grains of connectivity
## representation of the finest grain and three others
## by giving thresholds in link weights (doThresh)
tinyPatchGOC <- GOC(tinyPatchMPG, doThresh = c(0, 20, 40))
```

goc-class

The goc class

Description

The goc class

Slots

voronoi A RasterLayer describing the regions of proximity in resistance units around the focal patches or points.

summary A summary of the the grains of connectivity generated and their properties.

th A list giving the GOC graph at each threshold.

Each element of **th** contains a goc object giving the GOC graph as class [igraph](#). Vertex attributes describes qualities of each polygon including the coordinates of each polygon centroid, the area of these polygons, and the original patch IDs in the MPG that are included in each polygon. All areal measurements are given as raster cell counts. A variety of edge attributes are also given in the GOC graph. See [distance](#) for more information.

Author(s)

Alex Chubaty and Paul Galpern

grain

Extract a grain of connectivity (GOC) tessellation at a given scale

Description

Extract a grain (i.e. a scaled version of a Voronoi tessellation) from a GOC model.

Usage

```
grain(x, ...)
```

```
## S4 method for signature 'goc'
grain(x, whichThresh, ...)
```


Arguments

x	A goc object created by GOC .
...	Additional arguments (not used).
whichThresh	Integer giving the grain threshold to extract. This is the index of the threshold extracted by GOC .

Value

A list object containing the following elements:

summary gives the properties of the specified scale/grain whichThresh of the GOC model;

voronoi a RasterLayer giving the Voronoi tessellation the specified scale/grain whichThresh of the GOC model;

centroids a SpatialPoints objects giving the centroids of the polygons in the Voronoi tessellation at the specified scale/grain whichThresh;

th a igraph object giving the graph describing the relationship among the polygons at the specified scale/grain whichThresh

Author(s)

Paul Galpern and Alex Chubaty

References

- Fall, A., M.-J. Fortin, M. Manseau, D. O'Brien. (2007) Spatial graphs: Principles and applications for habitat connectivity. *Ecosystems* 10:448-461.
- Galpern, P., M. Manseau. (2013a) Finding the functional grain: comparing methods for scaling resistance surfaces. *Landscape Ecology* 28:1269-1291.
- Galpern, P., M. Manseau. (2013b) Modelling the influence of landscape connectivity on animal distribution: a functional grain approach. *Ecography* 36:1004-1016.
- Galpern, P., M. Manseau, A. Fall. (2011) Patch-based graphs of landscape connectivity: a guide to construction, analysis, and application for conservation. *Biological Conservation* 144:44-55.
- Galpern, P., M. Manseau, P.J. Wilson. (2012) Grains of connectivity: analysis at multiple spatial scales in landscape genetics. *Molecular Ecology* 21:3996-4009.

See Also

[GOC](#)

Examples

```
## Load raster landscape
tiny <- raster::raster(system.file("extdata/tiny.asc", package = "grainscape"))

## Create a resistance surface from a raster using an is-becomes reclassification
tinyCost <- raster::reclassify(tiny, rcl = cbind(c(1, 2, 3, 4), c(1, 5, 10, 12)))
```

```

## Produce a patch-based MPG where patches are resistance features=1
tinyPatchMPG <- MPG(cost = tinyCost, patch = tinyCost == 1)

## Extract a representative subset of 5 grains of connectivity
tinyPatchGOC <- GOC(tinyPatchMPG, nThresh = 5)

## Very quick visualization at the finest scale/grain/threshold
tinyPatchGOCgrain <- grain(tinyPatchGOC, whichThresh = 1)
if (interactive())
  plot(tinyPatchGOCgrain, col = topo.colors(10))

## Visualize the model at the finest scale/grain/threshold
## Manual control of plotting
if (interactive()) {
  plot(grain(tinyPatchGOC, whichThresh = 1)@voronoi,
       col = sample(rainbow(100)), legend = FALSE, main = "Threshold 1")
}

```

grain-class

The grain class

Description

The grain class

Slots

`voronoi` A `RasterLayer` describing the regions of proximity in resistance units around the focal patches or points.

`summary` A summary of the the grains of connectivity generated and their properties.

`centroids` A `SpatialPoints` object indicating the grain's polygon centroids.

`th` A list of `igraph` objects giving the graphs describing the relationship among the polygons in that grain

See [grain](#) for more information.

Author(s)

Alex Chubaty and Paul Galpern

grainscape-maps	<i>Test maps included with grainscape</i>
-----------------	---

Description

Intended for users to explore the functionality of the package using simple and artificial land cover maps. These maps have four or five discrete land cover classes (integers from 1 to 5) intended to represent distinct land cover types. Typical analyses begin by reclassifying these to reflect resistance to movement.

Format

raster

Details

`patchy.asc` A caricatured map of four land cover classes, where patches are large and easy to identify polygonal regions for heuristic purposes. This unrealistic map can be used to illustrate the method and understand how it works. The map also serves a similar heuristic purpose in a review of graph-based connectivity methods (Galpern *et al.*, 2011). (400 x 400 raster cells.)

`fragmented.asc` A simulated land cover map with five land cover classes using an algorithm that produces fragmentation. (400 x 400 raster cells.)

`tiny.asc` Similar to `fragmented.asc` but smaller in extent for lightning-fast computation and experimental use. (100 x 100 raster cells.)

<code>graphdf</code>	<i>Produce a data.frame containing the structure and associated attributes</i>
----------------------	--

Description

Produce a data.frame containing the node (vertex) and link (edge) structure as well as the associated attributes for these. This provides an easy way to create data tables describing graphs, particularly helpful for users unfamiliar with the structure of igraph objects.

Usage

```
graphdf(x, ...)

## S4 method for signature 'list'
graphdf(x, ...)

## S4 method for signature 'goc'
graphdf(x, ...)
```

```
## S4 method for signature 'grain'
graphdf(x, ...)

## S4 method for signature 'mpg'
graphdf(x, ...)

## S4 method for signature 'igraph'
graphdf(x, ...)
```

Arguments

x A goc, mpg, igraph, or list object.
 ... Additional arguments (not used).

Value

A list object containing:

v node (vertex) names and associated attributes;
 e link (edge) lists and associated attributes.

Please see [MPG](#) and [GOC](#) for details about the attributes.

For [GOC](#) objects which typically contain multiple thresholds, an enumerated list of the same length as the number of thresholds is returned each containing v and e elements.

Author(s)

Paul Galpern and Alex Chubaty

See Also

[MPG](#), [GOC](#)

Examples

```
## Load raster landscape
tiny <- raster::raster(system.file("extdata/tiny.asc", package = "grainscape"))

## Create a resistance surface from a raster using an is-becomes reclassification
tinyCost <- raster::reclassify(tiny, rcl = cbind(c(1, 2, 3, 4), c(1, 5, 10, 12)))

## Produce a patch-based MPG where patches are resistance features=1
tinyPatchMPG <- MPG(cost = tinyCost, patch = tinyCost == 1)

## Extract a representative subset of 5 grains of connectivity
tinyPatchGOC <- GOC(tinyPatchMPG, nThresh = 5)

## Create a data.frame with the structure and attributes of a MPG object
tinyPatchMPG_df <- graphdf(tinyPatchMPG)
```

```
## Create a data.frame with the structure and attributes of a GOC object
tinyPatchGOC_df <- graphdf(tinyPatchGOC)

## Create a data.frame with the structure and attributes of any igraph object
graphdf(tinyPatchGOC@th[[1]]$goc)
```

gsGOC

grainscape: *Deprecated*

Description

These have been deprecated and will be removed in a future release.

Usage

```
gsGOC(mpg, nThresh = NULL, doThresh = NULL,
      weight = "lcpPerimWeight", sp = FALSE, verbose = 3)

gsGOCCorridor(GOC, whichThresh, coords, doPlot = FALSE,
              weight = "meanWeight")

gsGOCDistance(GOC, coords, weight = "meanWeight")

gsGOCPoint(GOC, coords)

gsGOCVisualize(GOC, whichThresh, sp = FALSE, doPlot = FALSE)

visualize(GOC, whichThresh, sp = FALSE, doPlot = FALSE)

gsGraphDataFrame(x)

gsMPG(cost, patch, sa = NULL, filterPatch = NULL, spreadFactor = 0)
```

Arguments

mpg	A mpg object.
nThresh	Optional. An integer giving the number of thresholds (or scales) at which to create GOC models. Thresholds are selected to produce a maximum number of unique grains (i.e., models). nThresh thresholds are also approximately evenly spread between 0 and the threshold at which all patches or focal points on the landscape are connected. This is a simple way to get a representative subset of all possible GOC models. Provide either nThresh or doThresh not both.
doThresh	Optional. A vector giving the link thresholds at which to create GOC models. Use link{threshold} to identify thresholds of interest. Provide either nThresh or doThresh not both.

weight	A string giving the link weight or attribute to use for threshold. "lcpPerimWeight" uses the accumulated resistance or least-cost path distance from the perimeters of patches as the link weight. "eucPerimWeight" use the Euclidean distance from the perimeters of patches as the link weight.
sp	Logical. If TRUE the rgeos package is used to create a vector of class <code>SpatialPolygonsDataFrame</code> describing the finest grain of connectivity.
verbose	Set verbose=0 for no progress information to console.
GOC	A goc object.
whichThresh	Integer giving the index of the threshold to visualize.
coords	A two column matrix or a <code>SpatialPoints</code> object giving coordinates at the end points of the corridor.
doPlot	Logical. If TRUE plots a vector visualization of the corridor at the given scale
x	A mpg object produced by MPG. For lattice GOC MPG must be run with patch set as an integer value.
cost	A RasterLayer giving a landscape resistance surface, where the values of each raster cell are proportional to the resistance to movement, dispersal, or gene flow for an organism in the landscape feature they represent. Missing values NA are acceptable (but see below). Negative values are not. To extract an MPG with Euclidean links (i.e., and not least-cost path links) set <code>cost[] <- 1</code> .
patch	A raster of class RasterLayer for a patch-based analysis OR an integer for a lattice analysis. If a raster is given it must be of the same extent, origin and projection as cost and be binary, without missing values, where patches=1 and non-patches=0. For lattice analyses, an integer gives the spacing in raster cells between focal points in the lattice.
filterPatch, sa, spreadFactor	No longer used.

Note

the sp argument has also been deprecated from all functions.

 gsMPGstitch

 grainscape: *Defunct*

Description

These functions have removed from grainscape.

Usage

```
gsMPGstitch(...)
```

Arguments

... Any arguments passed to defunct functions.

MPG	<i>Extract a minimum planar graph (MPG) model from a landscape resistance surface</i>
-----	---

Description

Extracts a minimum planar graph (MPG) and is also the first step in grains of connectivity (GOC) modelling. Both patch-based and lattice MPGs can be extracted.

Usage

```
MPG(cost, patch, ...)
```

```
## S4 method for signature 'RasterLayer,RasterLayer'
MPG(cost, patch, ...)
```

```
## S4 method for signature 'RasterLayer,numeric'
MPG(cost, patch, ...)
```

Arguments

cost	A RasterLayer giving a landscape resistance surface, where the values of each raster cell are proportional to the resistance to movement, dispersal, or gene flow for an organism in the landscape feature they represent. Missing values NA are acceptable (but see below). Negative values are not. To extract an MPG with Euclidean links (i.e., and not least-cost path links) set <code>cost[] <-1</code> .
patch	A raster of class RasterLayer for a patch-based analysis OR an integer for a lattice analysis. If a raster is given it must be of the same extent, origin and projection as cost and be binary, without missing values, where patches=1 and non-patches=0. For lattice analyses, an integer gives the spacing in raster cells between focal points in the lattice.
...	Additional arguments (not used).

Details

Use this function to create a minimum planar graph (MPG) that can be further analyzed using [igraph](#) routines. It is also the first step in grains of connectivity (GOC) modelling.

Value

A `mpg` object.

Note

Researchers should consider whether the use of a patch-based MPG or a lattice MPG model is appropriate based on the patch-dependency of the organism under study. Patch-based models make

most sense when animals are restricted to, or dependent on, a resource patch. Lattice models can be used as a generalized and functional approach to scaling resistance surfaces.

Rasters should be projected and not in geographic coordinates (i.e. `projection(cost)` should not contain `"+proj=longlat"`) or the function will issue a warning. In unprojected cases consider using `projectRaster` to change to an appropriate coordinate system for the location and extent of interest that balances both distance and areal accuracy. See <http://www.spatialreference.org> for location-specific suggestions. Use of geographic coordinates will result in inaccurate areal and distance measurements, rendering the models themselves inaccurate.

Author(s)

Paul Galpern, Sam Doctolero, Alex Chubaty

References

Fall, A., M.-J. Fortin, M. Manseau, D. O'Brien. (2007) Spatial graphs: Principles and applications for habitat connectivity. *Ecosystems* 10:448-461.

Galpern, P., M. Manseau. (2013a) Finding the functional grain: comparing methods for scaling resistance surfaces. *Landscape Ecology* 28:1269-1291.

Galpern, P., M. Manseau. (2013b) Modelling the influence of landscape connectivity on animal distribution: a functional grain approach. *Ecography* 36:1004-1016.

Galpern, P., M. Manseau, A. Fall. (2011) Patch-based graphs of landscape connectivity: a guide to construction, analysis, and application for conservation. *Biological Conservation* 144:44-55.

Galpern, P., M. Manseau, P.J. Wilson. (2012) Grains of connectivity: analysis at multiple spatial scales in landscape genetics. *Molecular Ecology* 21:3996-4009.

See Also

[GOC](#), [threshold](#)

Examples

```
## Load raster landscape
tiny <- raster::raster(system.file("extdata/tiny.asc", package = "grainscape"))

## Create a resistance surface from a raster using an is-becomes reclassification
tinyCost <- raster::reclassify(tiny, rcl = cbind(c(1, 2, 3, 4), c(1, 5, 10, 12)))

## Produce a patch-based MPG where patches are resistance features=1
tinyPatchMPG <- MPG(cost = tinyCost, patch = tinyCost == 1)

## Explore the graph structure and node/link attributes
graphdf(tinyPatchMPG)

## Find the mean patch area (see igraph manual for use of V() and E())
mean(igraph::V(tinyPatchMPG@mpg)$patchArea)

## Quick visualization of the MPG
if (interactive())
```



```

plot(tinyPatchMPG, col = c("grey", "black"), legend = FALSE)

## Additional graph extraction scenarios
## Produce a lattice MPG where focal points are spaced 10 cells apart
tinyLatticeMPG <- MPG(cost = tinyCost, patch = 10)
if (interactive())
  plot(tinyLatticeMPG)

```

mpg-class

The mpg class

Description

The mpg class

Slots

mpg The minimum planar graph as class `igraph`.

patchId The input patch raster with patch cells assigned to their id (`RasterLayer`).

voronoi The Voronoi tessellation of the patches and resistance surface (`RasterLayer`).

lcpPerimWeight The paths of the links between patches and their accumulated costs (`RasterLayer`).

lcpLinkId The paths of the links between patches and their id (`RasterLayer`).

mpgPlot A `RasterLayer` version of the mpg, which can be easily plotted to visualize the MPG.

The mpg slot contains useful vertex and edge attributes. Vertex attributes give attributes of patches including patch area, the area of patch edges, the core area of each patch, and the coordinates of the patch centroid. All areal measurements are given as raster cell counts. Edge attributes give attributes of the graph links including link weights giving accumulated resistance/least-cost path distance, Euclidean distance, and the start and end coordinates of each link.

Author(s)

Alex Chubaty and Paul Galpern

patchFilter

Filter out patches smaller than a specified area

Description

Pre-process patch rasters prior to their use with [MPG](#).

Usage

```
patchFilter(x, cells = NULL, area = NULL, ...)

## S4 method for signature 'RasterLayer'
patchFilter(x, cells = NULL, area = NULL, ...)
```

Arguments

x	A binary raster (i.e. consisting of 0, 1, or NA cells), where cells =1 represent patches
cells	The minimum number of cells that constitute a patch. Default NULL. Only one of cells or area may be specified.
area	The minimum area that constitutes a patch (where area is calculated in the coordinate reference system of the raster by multiplying the count of cells in patch by the x and y resolution of a raster cell). Default NULL. Only one of cells or area may be specified.
...	Additional arguments passed to the clump function in the raster package. For example <code>directions = 4</code> may be used to be more conservative about which cells constitute a patch.

Details

It examines a binary raster to identify all patches or clumps of cells with values =1, determines their area, and returns a binary raster where only patches of area greater than or equal to the specified amount are represented.

This is helpful when analyzing habitat connectivity models where patches represent a land cover or habitat type. For example, a raster may have patches of a certain habitat type of insufficient area to support the ecological process of interest. Another use case is remote sensing classification errors that have introduced artifacts. Filtering can help in both cases.

Value

A binary raster where all patches (i.e. clumped areas =1) are greater than the specified area.

Author(s)

Paul Galpern and Alex Chubaty

See Also

[MPG](#)

Examples

```
## Load raster landscape
tiny <- raster::raster(system.file("extdata/tiny.asc", package = "grainscape"))

## Create a resistance surface from a raster using an is-becomes reclassification
```

```

tinyCost <- raster::reclassify(tiny, rcl = cbind(c(1, 2, 3, 4), c(1, 5, 10, 12)))

## Produce a patch-based MPG where patches are resistance features = 10
## and all patches are greater than or equal to 2 cells in size
filteredPatch <- patchFilter(tinyCost == 10, cells = 2)
tinyPatchMPG <- MPG(cost = tinyCost, patch = filteredPatch)
if (interactive()) plot(tinyPatchMPG)

## Compare to removal of patches greater than or equal to 40 cells in size!
filteredPatch <- patchFilter(tinyCost == 10, cells = 40)
tinyPatchMPG <- MPG(cost = tinyCost, patch = filteredPatch)
if (interactive()) plot(tinyPatchMPG)

## Use a rook/castle 4-direction case rather than the queen 8-direction case
## to identify neighbouring cells in a patch
filteredPatch <- patchFilter(tinyCost == 10, cells = 40, directions = 4)
tinyPatchMPG <- MPG(cost = tinyCost, patch = filteredPatch)
if (interactive()) plot(tinyPatchMPG)

```

plot,corridor,ANY-method

Plot quick visualizations of grainscape objects

Description

Plot quick visualizations of mpg, grain, and corridor objects.

This function is intended to get a quick look at the state of a grainscape object by rendering what are likely to be the most universally useful visualizations of the spatial data within these objects.

Much more control is available using [ggGS](#) with [ggplot](#) enabling the layering of different different analytical products, and the visualization of node and link attributes.

For high-resolution visualization and the greatest level of control use [export](#) to export spatial objects for cartographic representation in a geographic information system (GIS).

Usage

```

## S4 method for signature 'corridor,ANY'
plot(x, y, quick = NULL, print = TRUE,
     theme = TRUE, ...)

## S4 method for signature 'grain,ANY'
plot(x, y, quick = NULL, print = TRUE,
     theme = TRUE, ...)

## S4 method for signature 'mpg,ANY'
plot(x, y, quick = NULL, print = TRUE,
     theme = TRUE, ...)

```

Arguments

<code>x</code>	A grainscape object (<code>corridor</code> , <code>grain</code> , or <code>mpg</code>).
<code>y</code>	Ignored.
<code>quick</code>	If NULL (the default) it will plot the most useful quick visualization for the supplied object type. See below for a description of the available quick plots, and the defaults.
<code>print</code>	Render the ggplot on the default graphics device. Default is TRUE.
<code>theme</code>	Apply grainscape theme and scale aesthetics. Default is TRUE.
<code>...</code>	Additional arguments (not used).

Value

Invisibly, a ggplot2 object to which additional ggplot geoms and adjustments can be applied. Has the side effect of rendering the plot, unless `print = FALSE`.

Types of visualization available with the `quick` parameter

"`mpgPerimPlot`" gives a vector rendering of the minimum planar graph with vector links connecting the perimeters of the patches. This doesn't accurately represent the sinuosity of paths of the links between patches but offers a good approximation that renders better at large extents. Default for `mpg` objects. Not available for other objects.

"`mpgPlot`" gives a raster-only rendering of the minimum planar graph where `patchId` are positive integers, and `linkId` are negative integers showing the shortest paths between patches. Only available for `mpg` objects.

"`network`" gives a vector rendering of the minimum planar graph or the grains of connectivity network with nodes and links plotted at the patch or polygon centroid locations. Available for `mpg` and `grain` objects. Default for `grain` objects.

"`grainPlot`" gives a raster and vector rendering of the grains of connectivity network with nodes and links plotted at polygon centroid locations, superimposed over the boundaries of the Voronoi polygons. Can be time consuming on large rasters due to the Voronoi boundary extraction. Only available for `grain` objects.

"`corridorPlot`" renders the output of a `corridor` analysis. It is the only option available with `corridor` objects and the default.

Author(s)

Alex Chubaty and Paul Galpern

See Also

[ggGS](#), [export](#), [corridor](#), [grain](#), [mpg](#)

Examples

```

## Load raster landscape
tiny <- raster::raster(system.file("extdata/tiny.asc", package = "grainscape"))

## Create a resistance surface from a raster using an is-becomes reclassification
tinyCost <- raster::reclassify(tiny, rcl = cbind(c(1, 2, 3, 4), c(1, 5, 10, 12)))

## Produce a patch-based MPG where patches are resistance features=1
tinyPatchMPG <- MPG(cost = tinyCost, patch = tinyCost == 1)

## Extract a representative subset of 5 grains of connectivity
tinyPatchGOC <- GOC(tinyPatchMPG, nThresh = 5)

if (interactive()) {
  library(ggplot2)

  ## MPG and showing simplified links among the perimeters of patches
  plot(tinyPatchMPG)

  ## MPG showing links among the nodes of connected patches
  plot(tinyPatchMPG, quick = "network")

  ## MPG showing the shortest paths between patches actually used to
  ## to calculate link weight values
  plot(tinyPatchMPG, quick = "mpgPlot")

  ## A grain of connectivity network plot with Voronoi boundaries
  plot(grain(tinyPatchGOC, 3), quick = "grainPlot")

  ## Capture plot output for further processing with ggplot
  g <- plot(tinyPatchMPG, print = FALSE, theme = FALSE)
  g <- g + theme_minimal() + ggtitle("Minimum planar graph") +
    theme(plot.title = element_text(size = 20, hjust = 0.5)) +
    theme(legend.position = "none") +
    xlab("Easting") + ylab("Northing")
  g

  ## To change aesthetics it is best to build the plot from scratch
  ## using grainscape::ggGS(). See examples therein.
}

```

point

Identify the polygons containing locations in grains of connectivity (GOC) tessellations

Description

Identify the polygon containing a location at multiple scales.

Usage

```
point(x, ...)

## S4 method for signature 'goc'
point(x, coords, ...)
```

Arguments

x	A goc object produced by GOC .
...	Additional arguments (not used).
coords	A two column matrix or a SpatialPoints object giving the coordinates of points of interest.

Value

A list with elements:

`pointPolygon` a matrix with elements giving the id of the polygon from the goc, where rows give points of interest and columns give thresholds;

`pointTotalPatchArea` is a matrix with elements giving the area of patches in a polygon (in cell counts), where rows give points of and columns give thresholds;

`pointTotalCoreArea` the same for core area of patches;

`pointECS` gives the patch area (in cell counts) averaged for all points of interest (defined by O'Brien *et al.*, 2006);

`pointECSCore` is the same for the core area of patches.

Note

See [MPG](#) for warning related to areal measurements.

Author(s)

Paul Galpern and Alex Chubaty

References

- Fall, A., M.-J. Fortin, M. Manseau, D. O'Brien. (2007) Spatial graphs: Principles and applications for habitat connectivity. *Ecosystems* 10:448-461.
- Galpern, P., M. Manseau. (2013a) Finding the functional grain: comparing methods for scaling resistance surfaces. *Landscape Ecology* 28:1269-1291.
- Galpern, P., M. Manseau. (2013b) Modelling the influence of landscape connectivity on animal distribution: a functional grain approach. *Ecography* 36:1004-1016.
- Galpern, P., M. Manseau, A. Fall. (2011) Patch-based graphs of landscape connectivity: a guide to construction, analysis, and application for conservation. *Biological Conservation* 144:44-55.
- Galpern, P., M. Manseau, P.J. Wilson. (2012) Grains of connectivity: analysis at multiple spatial scales in landscape genetics. *Molecular Ecology* 21:3996-4009.

O'Brien, D., M. Manseau, A. Fall, and M.-J. Fortin. (2006) Testing the importance of spatial configuration of winter habitat for woodland caribou: An application of graph theory. *Biological Conservation* 130:70-83.

See Also

[GOC, distance](#)

Examples

```
## Load raster landscape
tiny <- raster::raster(system.file("extdata/tiny.asc", package = "grainscape"))

## Create a resistance surface from a raster using an is-becomes reclassification
tinyCost <- raster::reclassify(tiny, rcl = cbind(c(1, 2, 3, 4), c(1, 5, 10, 12)))

## Produce a patch-based MPG where patches are resistance features=1
tinyPatchMPG <- MPG(cost = tinyCost, patch = tinyCost == 1)

## Extract a representative subset of 5 grains of connectivity
tinyPatchGOC <- GOC(tinyPatchMPG, nThresh = 5)

## Three sets of coordinates in the study area
loc <- cbind(c(30, 60, 90), c(30, 60, 90))

## Find the GOC polygon containing these three locations
## for each of the 5 grains of connectivity
tinyPts <- point(tinyPatchGOC, loc)
```

show,goc-method	<i>Show a grainscape object</i>
-----------------	---------------------------------

Description

Custom show method to safely print the contents of a goc or grain object.

Usage

```
## S4 method for signature 'goc'
show(object)

## S4 method for signature 'grain'
show(object)

## S4 method for signature 'corridor'
show(object)
```

Arguments

object A [goc](#) or [grain](#) object.

theme_grainscape	A ggplot2 theme for grainscape
------------------	--------------------------------

Description

A [ggplot2](#) theme designed for grainscape based on the [theme_map](#) theme, with several modifications.

Usage

```
theme_grainscape(base_size = 9, base_family = "")
```

Arguments

base_size	Base font size
base_family	Base font family

Value

A theme suitable for use with [ggplot](#)

Author(s)

Paul Galpern and Alex Chubaty

See Also

[ggGS](#), [plot](#), [theme_map](#)

Examples

```
## Load raster landscape
tiny <- raster::raster(system.file("extdata/tiny.asc", package = "grainscape"))

## Create a resistance surface from a raster using an is-becomes reclassification
tinyCost <- raster::reclassify(tiny, rcl = cbind(c(1, 2, 3, 4), c(1, 5, 10, 12)))

## Produce a patch-based MPG where patches are resistance features=1
tinyPatchMPG <- MPG(cost = tinyCost, patch = tinyCost == 1)

if (interactive()) {
  library(ggplot2)

  ## Plot the patches in a minimum planar graph
  ggplot() +
    geom_tile(ggGS(tinyPatchMPG, "patchId"), mapping = aes(x = x, y = y, fill = value)) +
    theme_grainscape()
}
```

 threshold

Produce a minimum planar graph (MPG) at multiple scales

Description

Perform a scalar analysis of a minimum planar graph (MPG) by building the graph at a series of link thresholds. As the threshold value increases more nodes in the graph become connected, forming increasingly fewer components, until the graph becomes connected (e.g., Brooks, 2003). N.B. Grains of connectivity (GOC) done by [GOC](#) is also a scalar analysis using Voronoi tessellations rather than patches (see Galpern *et al.*, 2012).

Usage

```
threshold(x, ...)

## S4 method for signature 'mpg'
threshold(x, weight = "lcpPerimWeight", nThresh = NULL,
  doThresh = NULL, ...)
```

Arguments

x	A mpg object produced by MPG .
...	Additional arguments (not used).
weight	A string giving the link weight or attribute to use for threshold. "lcpPerimWeight" uses the accumulated resistance or least-cost path distance from the perimeters of patches as the link weight. "eucPerimWeight" use the Euclidean distance from the perimeters of patches as the link weight.
nThresh	Optional. An integer giving the number of thresholds (or scales) at which to create GOC models. Thresholds are selected to produce a maximum number of unique grains (i.e., models). nThresh thresholds are also approximately evenly spread between 0 and the threshold at which all patches or focal points on the landscape are connected. This is a simple way to get a representative subset of all possible GOC models. Provide either nThresh or doThresh not both.
doThresh	Optional. A vector giving the link thresholds at which to create GOC models. Use link{threshold} to identify thresholds of interest. Provide either nThresh or doThresh not both.

Value

A list object with the following elements:

summary summarizes the thresholded graphs generated and their properties;

th a list of length nThresh or length(doThresh) giving the thresholded graph (class igraph) at each threshold.

Note

See [MPG](#) for warning related to areal measurements.

Author(s)

Paul Galpern and Alex Chubaty

References

- Brooks, C.P. (2003) A scalar analysis of landscape connectivity. *Oikos* 102:433-439.
- Fall, A., M.-J. Fortin, M. Manseau, D. O'Brien. (2007) Spatial graphs: Principles and applications for habitat connectivity. *Ecosystems* 10:448:461.
- Galpern, P., M. Manseau. (2013a) Finding the functional grain: comparing methods for scaling resistance surfaces. *Landscape Ecology* 28:1269-1291.
- Galpern, P., M. Manseau. (2013b) Modelling the influence of landscape connectivity on animal distribution: a functional grain approach. *Ecography* 36:1004-1016.
- Galpern, P., M. Manseau, A. Fall. (2011) Patch-based graphs of landscape connectivity: a guide to construction, analysis, and application for conservation. *Biological Conservation* 144:44-55.
- Galpern, P., M. Manseau, P.J. Wilson. (2012) Grains of connectivity: analysis at multiple spatial scales in landscape genetics. *Molecular Ecology* 21:3996-4009.

See Also

[MPG](#)

Examples

```
## Load raster landscape
tiny <- raster::raster(system.file("extdata/tiny.asc", package = "grainscape"))

## Create a resistance surface from a raster using an is-becomes reclassification
tinyCost <- raster::reclassify(tiny, rcl = cbind(c(1, 2, 3, 4), c(1, 5, 10, 12)))

## Produce a patch-based MPG where patches are resistance features=1
tinyPatchMPG <- MPG(cost = tinyCost, patch = tinyCost == 1)

## Threshold this graph at a representative subset of 10 thresholds
tinyThresh <- threshold(tinyPatchMPG, nThresh = 10)

## Examine the properties of one of these threshold graphs
print(tinyThresh$th[[7]], vertex = TRUE, edge = TRUE)
```

\$

Extract or Replace Parts of an Object

Description

Extract or Replace Parts of an Object

Usage

```
## S4 method for signature 'goc'  
x$name  
  
## S4 replacement method for signature 'goc'  
x$name <- value  
  
## S4 method for signature 'mpg'  
x$name  
  
## S4 replacement method for signature 'mpg'  
x$name <- value
```

Arguments

x	A <code>simList</code> object from which to extract element(s) or in which to replace element(s).
name	A literal character string or a name .
value	Any R object.

Index

- *Topic **connectivity**
 - grainscape-package, 2
- *Topic **graph**
 - grainscape-package, 2
- *Topic **maps**
 - grainscape-maps, 19
- *Topic **minimum**
 - grainscape-package, 2
- *Topic **planar**
 - grainscape-package, 2
- *Topic **spatial**
 - grainscape-package, 2
- \$, 35
- \$, goc-method (\$), 35
- \$, mpg-method (\$), 35
- \$<- (\$), 35
- \$<-, goc-method (\$), 35
- \$<-, mpg-method (\$), 35

- clump, 26
- corridor, 4, 4, 6, 28
- corridor, goc-method (corridor), 4
- corridor-class, 6

- distance, 4, 6, 15, 16, 31
- distance, goc, matrix-method (distance), 6
- distance, goc, numeric-method (distance), 6
- distance, goc, SpatialPoints-method (distance), 6

- export, 8, 27, 28
- export, goc-method (export), 8
- export, grain-method (export), 8
- export, mpg-method (export), 8

- ggGS, 11, 27, 28, 32
- ggGS, goc-method (ggGS), 11
- ggGS, grain-method (ggGS), 11
- ggGS, list-method (ggGS), 11

- ggGS, mpg-method (ggGS), 11
- ggGS, RasterLayer-method (ggGS), 11
- ggplot, 11, 12, 27, 32
- ggplot2, 32
- GOC, 4, 5, 7, 10, 13, 14, 17, 20, 24, 30, 31, 33
- goc, 15, 31
- GOC, mpg-method (GOC), 14
- goc-class, 16
- grain, 10, 15, 16, 18, 28, 31
- grain, goc-method (grain), 16
- grain-class, 18
- grainscape (grainscape-package), 2
- grainscape-maps, 19
- grainscape-package, 2
- graphdf, 19
- graphdf, goc-method (graphdf), 19
- graphdf, grain-method (graphdf), 19
- graphdf, igraph-method (graphdf), 19
- graphdf, list-method (graphdf), 19
- graphdf, mpg-method (graphdf), 19
- gsGOC, 21
- gsGOCCorridor (gsGOC), 21
- gsGOCDistance (gsGOC), 21
- gsGOCPoint (gsGOC), 21
- gsGOCVisualize (gsGOC), 21
- gsGraphDataFrame (gsGOC), 21
- gsMPG (gsGOC), 21
- gsMPGstitch, 22

- igraph, 16, 23

- MPG, 10, 13–15, 20, 22, 23, 25, 26, 30, 33, 34
- mpg, 23, 28
- MPG, RasterLayer, numeric-method (MPG), 23
- MPG, RasterLayer, RasterLayer-method (MPG), 23
- mpg-class, 25

- name, 35

- patchFilter, 25

patchFilter,RasterLayer-method
 (patchFilter), 25

plot, 32

plot,corridor,ANY-method, 27

plot,grain,ANY-method
 (plot,corridor,ANY-method), 27

plot,mpg,ANY-method
 (plot,corridor,ANY-method), 27

point, 7, 15, 29

point,goc-method (point), 29

projectRaster, 24

show,corridor-method (show,goc-method),
 31

show,goc-method, 31

show,grain-method (show,goc-method), 31

SpatialPoints, 4, 7, 22, 30

SpatialPolygonsDataFrame, 22

theme_grainscape, 32

theme_map, 32

threshold, 24, 33

threshold,mpg-method (threshold), 33

visualize, 5

visualize (gsGOC), 21

writeFormats, 9

writeOGR, 8

writeRaster, 8