

Package ‘wyz.code.offensiveProgramming’

October 28, 2019

Type Package

Title Wizardry Code Offensive Programming

Version 1.1.14

Author Fabien Gelineau <neonira@gmail.com>

Maintainer Fabien Gelineau <neonira@gmail.com>

Description Allows to change R coding from defensive programming (i.e. many input parameter checks implementation required) to offensive programming (none/reduced number of parameter checks required). Provides code instrumentation to ease this change. Should reduce the code size as many controls and type checks have no more reason to exist. Should also speed up processing as many checks will be reduced to single check.

Encoding UTF-8

LazyData true

License GPL-3

Depends R (>= 3.5)

Imports methods, data.table (>= 1.11.8), tidyr, lubridate (>= 1.7.4), stringr (>= 1.4.0), R6 (>= 2.4.0), crayon

Suggests testthat, knitr, rmarkdown

RoxygenNote 6.1.1

VignetteBuilder knitr

NeedsCompilation no

Repository CRAN

Date/Publication 2019-10-28 08:30:02 UTC

R topics documented:

defineEvaluationModes	2
defineFunctionReturnTypesParameterName	3
defineTestCaseDefinitionsParameterName	4
EvaluationMode	4

exploreObjectNamesVerification	5
FunctionParameterName	6
FunctionParameterTypeFactory	7
getEllipsisName	8
getObjectClassKind	9
getObjectClassNames	10
getObjectFunctionArgumentNames	11
getObjectFunctionNames	12
isAuditable	13
packageFunctionsInformation	13
print.EvaluationMode	14
print.FunctionParameterName	15
print.TestCaseDefinition	15
retrieveFactory	16
retrieveFunctionArgumentNames	17
retrieveFunctionArguments	18
retrieveFunctionReturnTypes	19
retrieveTestCaseDefinitions	20
runFunction	21
runTestCase	22
runTransientFunction	23
TestCaseDefinition	24
verifyClassName	25
verifyFunctionName	26
verifyFunctionReturnTypesDefinition	27
verifyObjectNames	28
verifyTestCaseDefinitions	29

Index **31**

defineEvaluationModes *Define evaluation modes*

Description

Get all predefined evaluation mode names

Usage

defineEvaluationModes()

Value

A vector of strings, each representing a reusable evaluation mode name.

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

See Also

Refer to [EvaluationMode](#).

Examples

```
##---- typical case ----  
defineEvaluationModes()
```

defineFunctionReturnTypesParameterName
define function return type parameter name

Description

Provides the parameter name to use to define function return type.

Usage

```
defineFunctionReturnTypesParameterName()
```

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

See Also

Refer to [EvaluationMode](#).

Examples

```
##---- typical case ----  
defineFunctionReturnTypesParameterName()
```

```
defineTestCaseDefinitionsParameterName  
    Test case definition parameter name
```

Description

Define the parameter name to hold test case definitions

Usage

```
defineTestCaseDefinitionsParameterName()
```

Value

A single string that is the parameter name to use.

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

See Also

Refer to [EvaluationMode](#). See sibling [EvaluationMode](#).

Examples

```
##---- typical case ----  
defineTestCaseDefinitionsParameterName()
```

```
EvaluationMode    Evaluation mode definition
```

Description

Class to define your evaluation mode

Usage

```
EvaluationMode(value_s_1 = defineEvaluationModes()[2])
```

Arguments

value_s_1 one string that must come from [defineEvaluationModes](#)

Value

An object that is an R environment.

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

See Also

Refer to [defineEvaluationModes](#)

Examples

```
##---- typical case ----  
EvaluationMode(defineEvaluationModes()[3])
```

```
exploreObjectNamesVerification  
      Verify object names
```

Description

Easier output and more human friendly interface to [verifyObjectNames](#)

Usage

```
exploreObjectNamesVerification(object_o_1,  
                               what_s_1 = c("names", "return type", "test cases", "*")[1],  
                               functionParameterTypeFactory_o_1 = retrieveFactory())
```

Arguments

object_o_1	the object to be checked
what_s_1	a single string that expresses what you want to focus on, should start by one of [nr]* character. Star means show all.
functionParameterTypeFactory_o_1	the type factory to check parameter types

Value

The same value as [verifyObjectNames](#) is returned in invisible mode.

It adds stdout output to give very short synthesis about object names and content.

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

See Also

Refer to [verifyClassName](#) and [verifyFunctionName](#).

Examples

```
##---- typical case ----  
library('data.table')  
source(system.file('code-samples/frt-defs/good/full/AdditionFI.R',  
                  package = 'wyz.code.offensiveProgramming'))  
fi <- AdditionFI()  
exploreObjectNamesVerification(fi)
```

FunctionParameterName *Function parameter name*

Description

Class to define and handle a function parameter

Usage

```
FunctionParameterName(name_s_1)
```

Arguments

name_s_1 the name of the parameter

Details

The name of the parameter should be a semantic name. A semantic name is a compound string based on a special format allowing to distinguish by the name, the parameter type, and to express some length constraints.

Value

An object that is an R environment. Use functions `isSemanticName`, `isPolymorphic`, `isEllipsis`, `isValid` to check the provided name. Functions `get*` allows to retrieve parts of the name.

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

See Also

Refer to [defineEvaluationModes](#)

Examples

```
##---- typical case ----
fpn <- FunctionParameterName('values_s_7m')
fpn$isPolymorphic()
fpn$isSemanticName()
fpn$isValid()
fpn$getTypeSuffix() # 's'
fpn$getLengthSpecification() # '7m'
fpn$getLengthSuffix() # 7
fpn$getLengthModifier() # 'm'

fpn <- FunctionParameterName('object_')
fpn$isPolymorphic()
fpn$isSemanticName()
fpn$isValid()
```

FunctionParameterTypeFactory

Function parameter type factory

Description

This factory is a parameter type check factory. It provides type checking for each allowed type.

Usage

```
FunctionParameterTypeFactory()
```

Details

Many common types are already recorded and available through the factory. Use the function `getRecordedTypes` to get more insight.

If you desire to verify a type instrumentation, just use `checkSuffix` function. If you want to add an instrumentation for a new type, use `addSuffix` function.

See examples below for more hands-on approach.

Value

An object that is an R environment.

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

See Also

Refer to [defineEvaluationModes](#)

Examples

```
##---- typical case ----
ff <- FunctionParameterTypeFactory()
ff$checkSuffix('b') # TRUE

# see verify_function recorded for 'boolean' entries
ff$getRecordedTypes()[suffix == 'b']$verify_function[[1]]

# record a new entry for suffix 'wo'
ff$addSuffix('wo', "wo class", function(o_) is(o, "wo")) # TRUE
ff$getRecordedTypes()[suffix == 'wo']
```

getEllipsisName	<i>Get ellipsis.</i>
-----------------	----------------------

Description

Use method getEllipsisName to get ellipsis argument value.

Usage

```
getEllipsisName()
```

Value

A string with value . . . , no more no less.

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

Examples

```
# typical test
getEllipsisName()
#[1] "..."
```

getObjectContextKind *Get R object class kind*

Description

Get the class kind of an R object as a string.

Usage

```
getObjectContextKind(object_o_1)
```

Arguments

object_o_1 the object to analyze. See [is.object](#).

Value

A single character value, taken in set "S3", "S4", "RC", "R6", "environment", "unknown".
When provided object_ is not an R object, then value NA_character_ is returned.

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

Examples

```
##---- typical case ----
getObjectContextKind(new.env())
# [1] NA

myrc <- setRefClass("RC",
  fields = list(x = "numeric"),
  methods = list(
    initialize = function(x = 1) .self$x <- x,
    getx = function() x,
    inc = function(n = 1) x <<- x + n
  )
)

getObjectContextKind(myrc$new())
# [1] RC

myr6 <- R6::R6Class("R6",
  public = list(
    x = NULL,
    initialize = function(x = 1) self$x <- x,
    getx = function() self$x,
    inc = function(n = 1) self$x <- x + n
  )
)
```

```

)
)

getObjectClassKind(myr6$new())
# [1] R6

```

getObjectClassNames *Retrieve Function Arguments.*

Description

Use method getObjectClassNames to get the class names of an object (see is.object.)

Usage

```

getObjectClassNames(object_o_1)
hasMainClass(object_o_1, classname_s_1)

```

Arguments

object_o_1 the object to analyze.
 classname_s_1 the class to match the classname entry of the returned value of getObjectClassNames).

Value

A list with two character entries. First one is named classname, provides the main classname (the one found in first position). Second one is named classnames, provides all the class names born by the object_.

Author(s)

Fabien Gelineau <neonira@gmail.com>
 Maintainer: Fabien Gelineau <neonira@gmail.com>

Examples

```

# typical test
getObjectClassNames(getObjectClassNames(factor(letters[1:3])))
# $classname
# [1] "factor"

# $classnames
# [1] "factor"

# another test
getObjectClassNames(new.env())
# $classname
# [1] NA

```

```
#$classnames  
#[1] "environment"
```

```
getObjectFunctionArgumentNames  
Retrieve Function Arguments.
```

Description

Use method `getObjectFunctionArgumentNames` to get the function argument names of an object (see `is.object`).

Usage

```
getObjectFunctionArgumentNames(object_o_1, allNames_b_1 = TRUE)
```

Arguments

`object_o_1` the object to analyze.
`allNames_b_1` A boolean value. Passed to function `getObjectFunctionNames` to restrict output if needed.

Value

A list. Entries are named with function names. Each entry is of type character, and holds function argument names. Could be empty if function takes no argument.

Author(s)

Fabien Gelineau <neonira@gmail.com>
Maintainer: Fabien Gelineau <neonira@gmail.com>

Examples

```
# typical test  
MyEnv <- function() {  
  self <- environment()  
  class(self) <- append('MyEnv', class(self))  
  f <- function(x_3, y_3n) x_3 + y_3n  
  self  
}  
  
getObjectFunctionArgumentNames(MyEnv())  
#$f  
#[1] "x_3" "y_3n"
```

`getObjectFunctionNames`*Retrieve Function Names From Object*

Description

Use method `getObjectFunctionNames` to get the function names of an object (see `is.object`.)

Usage

```
getObjectFunctionNames(object_o_1, allNames_b_1 = FALSE)
```

```
getClassTypicalFunctionNames(object_o_1)
```

Arguments

`object_o_1` the object to analyze.

`allNames_b_1` A boolean value. When TRUE, uses `getClassTypicalFunctionNames` to restrict the set of function names returned.

Details

Function `getClassTypicalFunctionNames` gives back function names that are related to R class style, and automatically added by R to your class object.

Value

A vector of function names (character).

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

Examples

```
# typical test
MyEnv <- function() {
  self <- environment()
  class(self) <- append('MyEnv', class(self))
  f <- function(x_3, y_3n) x_3 + y_3n
  self
}

getObjectFunctionNames(MyEnv())
# [1] "f"

# another test
```

```
getObjectFunctionNames(new.env())  
#[1] NA
```

isAuditable	<i>Is auditable.</i>
-------------	----------------------

Description

Use method `isAuditable` to know if code is auditable

Usage

```
isAuditable()
```

Value

A boolean value. To turn value to TRUE, environment variable `OP_AUDITABLE` must be set to a value that does not match an empty string.

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

Examples

```
# typical case  
isAuditable()  
# FALSE
```

packageFunctionsInformation	<i>Package functions information</i>
-----------------------------	--------------------------------------

Description

A reminder of available functions from this package, and, most common usage intent. A poor man CLI cheat sheet.

Usage

```
packageFunctionsInformation()
```

Value

A data.table with following column names

function	a function name provided by this package
elaboration	a boolean stating if function could/should be use for elaboration purpose
verification	a boolean stating if function could/should be use for verification purpose
exploitation	a boolean stating if function could/should be use for exploitation purpose
information	a boolean stating if function could/should be use for informative purpose
kind	the classification kind of the chosen function
user	a typical user role/profile that may use the function

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

See Also

Refer also to package vignettes.

Examples

```
##---- typical case ----  
packageFunctionsInformation()
```

```
print.EvaluationMode Print generic method for S3 class EvaluationMode
```

Description

Prints the EvaluationMode data

Usage

```
## S3 method for class 'EvaluationMode'  
print(x, ...)
```

Arguments

x	the EvaluationMode object to consider
...	any other argument, passed to print.

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

Examples

```
b <- EvaluationMode(defineEvaluationModes()[2])
print(b)
```

```
print.FunctionParameterName
      Print generic method for S3 class FunctionParameterName
```

Description

Prints the FunctionParameterName data

Usage

```
## S3 method for class 'FunctionParameterName'
print(x, ...)
```

Arguments

x the FunctionParameterName object to consider
... any other argument, passed to print.

Author(s)

Fabien Gelineau <neonira@gmail.com>
Maintainer: Fabien Gelineau <neonira@gmail.com>

Examples

```
fn <- FunctionParameterName('x_s')
print(fn)
```

```
print.TestCaseDefinition
      Print generic method for S3 class TestCaseDefinition
```

Description

Prints the TestCaseDefinition data

Usage

```
## S3 method for class 'TestCaseDefinition'
print(x, ...)
```

Arguments

x the TestCaseDefinition object to consider
... any other argument, passed to print.

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

Examples

```
b <- TestCaseDefinition(list(1L, 2L), 3L, 'sum of 2 integers')
print(b)
```

retrieveFactory	<i>Retrieve factory</i>
-----------------	-------------------------

Description

As factory may be modified, this function allows you to make changes and to record them in your own specialized type factory, to match various needs and ease reuse.

Usage

```
retrieveFactory()
```

Details

Retrieves a [FunctionParameterTypeFactory](#) from environment variable OP_TYPE_FACTORY or provides a default type factory.

Value

An R object that is a [FunctionParameterTypeFactory](#).

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

Examples

```
##---- typical case ----
ff <- FunctionParameterTypeFactory()
ff$addSuffix('wo', "wo class", function(o_) is(o_, "wo"))
ff$addSuffix('yo', "yo class", function(o_) is(o_, "yo"))
ff$addSuffix('zo', "zo class", function(o_) is(o_, "zo"))
Sys.setenv("OP_TYPE_FACTORY" = "ff")
fg <- retrieveFactory() # retrieves the factory pointed by R variable ff
fg$getRecordedTypes()[suffix %in% c('wo', 'yo', 'zo')] # right behavior !

# wrong behavior as retrieveFactory will provide the default factory and not yours!
Sys.setenv("OP_TYPE_FACTORY" = "")
fh <- retrieveFactory() # retrieves the default factory
fh$getRecordedTypes()[suffix %in% c('wo', 'yo', 'zo')]
```

```
retrieveFunctionArgumentNames
```

Retrieve Function Argument Names.

Description

Use method `retrieveFunctionArgumentNames` to get names of function or primitive arguments.

Usage

```
retrieveFunctionArgumentNames(fun_f_1)
```

Arguments

`fun_f_1` a function or primitive. Not a string!

Value

A vector. See [formalArgs](#).

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

Examples

```
# typical test on a primitive
retrieveFunctionArgumentNames(sin)
#[1] "x"

# typical test on a function
retrieveFunctionArguments(ls)
#[1] "name"      "pos"        "envir"      "all.names" "pattern"    "sorted"
```

retrieveFunctionArguments

Retrieve Function Arguments.

Description

Use method retrieveFunctionArguments to get function or primitive arguments.

Usage

```
retrieveFunctionArguments(fun_f_1)
```

Arguments

fun_f_1 a function or primitive. Not a string!

Value

A pairlist. See [formals](#).

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

Examples

```
# typical test on a primitive
retrieveFunctionArguments(sin)
# $x
#
```

```
# typical test on a function
retrieveFunctionArguments(ls)
# $name
```

```
# $pos
# -1L
```

```
# $envir
# as.environment(pos)
```

```
# $all.names
# [1] FALSE
```

```
# $pattern
#
```

```
##sorted
#[1] TRUE
```

```
retrieveFunctionReturnTypes
      Retrieve function return types
```

Description

From an instrumented class, retrieve the function return types definition.

Usage

```
retrieveFunctionReturnTypes(object_o_1,
  functionParameterTypeFactory_o_1 = retrieveFactory())
```

Arguments

```
object_o_1      the object to consider
functionParameterTypeFactory_o_1
                 the function parameter type factory to consider
```

Value

A polymorphic return that is either

```
a list          as returned by the verifyObjectNames function
another list    as returned by the verifyFunctionReturnTypesDefinition function
a data table    the function parameter types definition as declared in the source class
```

Author(s)

```
Fabien Gelineau <neonira@gmail.com>
Maintainer: Fabien Gelineau <neonira@gmail.com>
```

See Also

Refer to [defineEvaluationModes](#)

Examples

```
##---- typical case ----
library('data.table')
source(system.file('code-samples/no-defs/Addition.R',
  package = 'wyz.code.offensiveProgramming'))
source(system.file('code-samples/frt-defs/good/full/AdditionFI.R',
  package = 'wyz.code.offensiveProgramming'))
retrieveFunctionReturnTypes(AdditionFI()) # works, renders a data.table
retrieveFunctionReturnTypes(Addition()) # fails, renders a list
```

retrieveTestCaseDefinitions

Retrieve test case definitions or test case descriptions.

Description

From an instrumented class, retrieve the test case definitions or descriptions.

Usage

```
retrieveTestCaseDefinitions(object_o_1,  
    functionParameterTypeFactory_o_1 = retrieveFactory())  
retrieveTestCaseDescriptions(object_o_1,  
    functionParameterTypeFactory_o_1 = retrieveFactory())
```

Arguments

object_o_1 the object to consider
functionParameterTypeFactory_o_1
 the function parameter type factory to consider

Value

For function, *retrieveTestCaseDefinitions*, a polymorphic return that is either

a list as returned by the [verifyObjectNames](#) function
another list as returned by the [verifyFunctionReturnTypesDefinition](#) function
a data table the test case definitions as declared in the source class

For function, *retrieveTestCaseDescriptions*, either a string when no test case definitions exists or a data.table of the test case descriptions.

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

See Also

Refer to [defineEvaluationModes](#)

Examples

```
##---- typical case ----
library('data.table')
source(system.file('code-samples/tcd-defs/good/partial/AdditionTCPartial.R',
                  package = 'wyz.code.offensiveProgramming'))
source(system.file('code-samples/no-defs/Addition.R',
                  package = 'wyz.code.offensiveProgramming'))
retrieveTestCaseDefinitions(AdditionTCPartial()) # works, renders a data.table
retrieveTestCaseDefinitions(Addition()) # fails, renders a list

retrieveTestCaseDescriptions(Addition())
retrieveTestCaseDescriptions(AdditionTCPartial())
```

runFunction	<i>Run a function</i>
-------------	-----------------------

Description

Run a function from an object, according to the mentioned evaluation mode, and to the chosen type factory

Usage

```
runFunction(object_o_1, functionName_s_1, arguments_l,
            evaluationMode_o_1, functionParameterTypeFactory_o_1 = retrieveFactory())
```

Arguments

object_o_1 the object to consider
functionName_s_1
 a single string that is the name of the function to run
arguments_l a list of arguments to pass to the function
evaluationMode_o_1
 an evaluation mode object. See [EvaluationMode](#)
functionParameterTypeFactory_o_1
 A type factory. See [retrieveFactory](#)

Value

A list with names

status a single boolean. Always TRUE when evaluation mode is "standard_R_evaluation".
 Otherwise, will reflect result validity in the chose evaluation mode.
value the result of the computation, might be a scalar or not, a warning, an error, ...
mode the evaluation mode used to check the results
function_return_type_check
 available if mode is different of "standard_R_evaluation"
parameter_type_checks
 available if mode is "type_checking_inforcement"

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

See Also

Refer to [FunctionParameterTypeFactory](#) and [runFunction](#).

Examples

```
##---- typical case ----
library('data.table')
source(system.file('code-samples/frt-defs/good/full/AdditionFI.R',
                  package = 'wyz.code.offensiveProgramming'))
fi <- AdditionFI()
runFunction(fi, 'addDouble', list(34, 44.6), EvaluationMode(defineEvaluationModes()[1]))
runFunction(fi, 'addDouble', list(34, 44.6), EvaluationMode(defineEvaluationModes()[2]))
runFunction(fi, 'addDouble', list(34, 44.6), EvaluationMode(defineEvaluationModes()[3]))
```

runTestCase

Run test cases

Description

Run specified test cases under the given evaluation mode

Usage

```
runTestCase(object_o_1, testCaseIndexes_i, evaluationMode_o_1 = EvaluationMode())
```

Arguments

`object_o_1` The R object to consider

`testCaseIndexes_i`
 a vector of numbers identifying the test cases to run

`evaluationMode_o_1`
 the evaluation mode to use. see [EvaluationMode](#)

Value

A list with two names

`raw` a list with one entry for each test ran, holding all data and metadata related to the test

`synthesis` a summary data.table that allows to see at a glance all the tests results. Also eases comparisons of results between various evaluation modes.

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

See Also

Refer to [defineEvaluationModes](#)

Examples

```
##---- typical case ----  
library('data.table')  
source(system.file('code-samples/both-defs/good/full/AdditionTCFI_G1.R',  
                  package = 'wyz.code.offensiveProgramming'))  
em <- EvaluationMode('type_checking_enforcement')  
runTestCase(AdditionTCFI_G1(), c(3, 5, 7), em)
```

runTransientFunction *Run transient function*

Description

Run a function in a transient (non persistent) context.

Usage

```
runTransientFunction(function_f_1, arguments_l, evaluationMode_o_1,  
function_return_type_s_1, functionParameterTypeFactory_o_1 = retrieveFactory())
```

Arguments

function_f_1 a single R function

arguments_l a list of arguments to pass to the function

evaluationMode_o_1
 an evaluation mode object. See [EvaluationMode](#)

function_return_type_s_1
 a semantic parameter name, given as a string, to express expected function return
 type

functionParameterTypeFactory_o_1
 A type factory. See [retrieveFactory](#)

Value

A list with names

status a single boolean. Always TRUE when evaluation mode is "standard_R_evaluation".
 Otherwise, will reflect result validity in the chose evaluation mode.

value the result of the computation, might be a scalar or not, a warning, an error, ...

mode the evaluation mode used to check the results

function_return_type_check
 available if mode is different of "standard_R_evaluation"

parameter_type_checks
 available if mode is "type_checking_enforcement"

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

See Also

Refer to [runFunction](#)

Examples

```
##---- typical case ----
em <- EvaluationMode(defineEvaluationModes()[3])
h <- function(x_s) x_s
runTransientFunction(h, list('neonira'), em, 'x_s')
runTransientFunction(h, list(pi), em, 'x_s')
runTransientFunction(h, list(pi), em, 'x_d')
```

TestCaseDefinition *Test case definition*

Description

Defines a test case

Usage

```
TestCaseDefinition(params_l, expectedResult_, description_s_1)
```

Arguments

params_l a list that holds the test case input values

expectedResult_
 test case expected result. This will be used to compare with function execution
 results

description_s_1
 a single string, test case description

Details

Test case definition takes sense only when intimately correlated with a function

Value

An object that is an R environment.

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

See Also

Refer to [FunctionParameterTypeFactory](#)

Examples

```
##---- typical case ----
tcd <- TestCaseDefinition(list(1:5), 15, 'sum of 5 first non nul integers')
tcd <- TestCaseDefinition(list(1:7, 3:5, sample(1:100, 19, FALSE)),
                          list(3:5), 'extract smallest length from input')
```

verifyClassName	<i>Verify class name</i>
-----------------	--------------------------

Description

Class name must comply with a policy. This function allows to check compliance.

Usage

```
verifyClassName(name_s = "MyClassName", strictSyntax_b_1 = TRUE)
```

Arguments

name_s The class name to be checked

strictSyntax_b_1

A boolean value. When TRUE, allowed character set is [A-Za-z0-9]+. A class name must start with an uppercase letter. The name is required to be camel cased, although this cannot be checked.

When FALSE, allowed character set is [A-Za-z0-9_]+. Classic R class naming applies.

Value

A boolean value, either TRUE or FALSE

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

See Also

Refer to [defineEvaluationModes](#)

Examples

```
##---- typical case ----
verifyClassName('matrix')
verifyClassName('matrix', FALSE)
```

verifyFunctionName	<i>Verify function name</i>
--------------------	-----------------------------

Description

Function name must comply with a policy. This function allows to check compliance.

Usage

```
verifyFunctionName(name_s = "aSimpleFunctionName", strictSyntax_b_1 = TRUE)
```

Arguments

name_s The function name to be checked

strictSyntax_b_1

A boolean value. When TRUE, allowed character set is [A-Za-z0-9]+. A function name must start with a lowercase letter. The name is required to be camel cased, although this cannot be checked.

When FALSE, allowed character set is [A-Za-z0-9_]+. Classic R function naming applies.

Value

A boolean value, either TRUE or FALSE

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

See Also

Refer to [defineEvaluationModes](#)

Examples

```
##---- typical case ----  
verifyFunctionName('matrix')  
verifyFunctionName('matrix', FALSE)
```

verifyFunctionReturnTypesDefinition

Verify function return types definition

Description

Function return types definition has to comply with many rules. This functions checks for this compliances and helps in detection of uncompliances.

Usage

```
verifyFunctionReturnTypesDefinition(object_o_1,  
requiresFullInstrumentation_b_1 = TRUE,  
functionParameterTypeFactory_o_1 = retrieveFactory())
```

Arguments

object_o_1 The object to be considered
requiresFullInstrumentation_b_1
 a boolean stating if full instrumentation is required
functionParameterTypeFactory_o_1
 a type factory to check parameter values and types

Details

When requiresFullInstrumentation_b_1 is TRUE, each function must have an entry in the test case parameter definition.

Value

A list with names

validity a single boolean value
class the class name of the provided object
intent the stage of the failure, provides hint about the faced issue
message some hints to resolve the issue(s).

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

See Also

Refer to [defineTestCaseDefinitionsParameterName](#).

Examples

```
##---- typical case ----
library('data.table')
source(system.file('code-samples/frt-defs/good/full/AdditionFI.R',
                  package = 'wyz.code.offensiveProgramming'))
fi <- AdditionFI()
print(verifyFunctionReturnTypesDefinition(fi))
print(verifyFunctionReturnTypesDefinition(fi, FALSE))
```

verifyObjectNames	<i>Verify object names</i>
-------------------	----------------------------

Description

Verify object class name, object function names, and object function parameter names, and provides a synthesis of checks.

Proceeds also to some introspection on object to identify instrumentation of function return types and test case definitions. Provides information about completeness of instruction, and about missing functions and test cases.

Usage

```
verifyObjectNames(object_o_1, functionParameterTypeFactory_o_1 = retrieveFactory())
```

Arguments

object_o_1	the object to be checked
functionParameterTypeFactory_o_1	the type factory to check parameter types

Value

A list with following names

class_name	the class name of the provided object
supports_strict_compliance	a single boolean
supports_lazy_compliance	a single boolean
class_name_compliance	a boolean value expression class name compliance

`class_name_compliance`
a vector of booleans, where names are the function names and values express the name compliance

`class_name_compliance`
a `data.table` exposing the name compliance and the semanting name compliance for each paramter

`owns_function_return_type_information`
a single boolean

`can_be_type_checked`
a single boolean

`is_function_fully_instrumented`
a single boolean

`missing_function`
a vector of uninstrumented function names

`owns_test_case_definitions`
a single boolean

`is_test_case_fully_instrumented`
a single boolean

`missing_test_cases`
a single boolean

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

See Also

Refer to [verifyClassName](#) and [verifyFunctionName](#).

Examples

```
##---- typical case ----  
library('data.table')  
source(system.file('code-samples/frt-defs/good/full/AdditionFI.R',  
                  package = 'wyz.code.offensiveProgramming'))  
fi <- AdditionFI()  
print(verifyObjectNames(fi))
```

verifyTestCaseDefinitions

Verify test case definitions

Description

Test case definitions has to comply with many rules. This functions checks for this compliances and helps in dectection of uncompliances.

Usage

```
verifyTestCaseDefinitions(object_o_1, requiresFullInstrumentation_b_1 = TRUE,
functionParameterTypeFactory_o_1 = retrieveFactory())
```

Arguments

object_o_1 The object to be considered

requiresFullInstrumentation_b_1
 a boolean stating if full instrumentation is required

functionParameterTypeFactory_o_1
 a type factory to check parameter values and types

Details

When requiresFullInstrumentation_b_1 is TRUE, each function must have an entry in the test case parameter definition.

Value

A list with names

validity a single boolean value

class the class name of the provided object

intent the stage of the failure, provides hint about the faced issue

message some hints to resolve the issue(s).

Author(s)

Fabien Gelineau <neonira@gmail.com>

Maintainer: Fabien Gelineau <neonira@gmail.com>

See Also

Refer to [defineTestCaseDefinitionsParameterName](#).

Examples

```
##---- typical case ----
library('data.table')
source(system.file('code-samples/tcd-defs/good/full/AdditionTC.R',
                  package = 'wyz.code.offensiveProgramming'))
tc <- AdditionTC()
print(verifyTestCaseDefinitions(tc))
```

Index

*Topic **classes**

print.EvaluationMode, 14
print.FunctionParameterName, 15
print.TestCaseDefinition, 15

*Topic **programming**

defineEvaluationModes, 2
defineFunctionReturnTypesParameterName, 3
defineTestCaseDefinitionsParameterName, 4
EvaluationMode, 4
exploreObjectNamesVerification, 5
FunctionParameterName, 6
FunctionParameterTypeFactory, 7
getObjectClassKind, 9
packageFunctionsInformation, 13
retrieveFactory, 16
retrieveFunctionReturnTypes, 19
retrieveTestCaseDefinitions, 20
runFunction, 21
runTestCase, 22
runTransientFunction, 23
TestCaseDefinition, 24
verifyClassName, 25
verifyFunctionName, 26
verifyFunctionReturnTypesDefinition, 27
verifyObjectNames, 28
verifyTestCaseDefinitions, 29

*Topic **utilities**

defineEvaluationModes, 2
defineFunctionReturnTypesParameterName, 3
defineTestCaseDefinitionsParameterName, 4
EvaluationMode, 4
exploreObjectNamesVerification, 5
FunctionParameterName, 6
FunctionParameterTypeFactory, 7

getObjectClassKind, 9
packageFunctionsInformation, 13
retrieveFactory, 16
retrieveFunctionReturnTypes, 19
retrieveTestCaseDefinitions, 20
runFunction, 21
runTestCase, 22
runTransientFunction, 23
TestCaseDefinition, 24
verifyClassName, 25
verifyFunctionName, 26
verifyFunctionReturnTypesDefinition, 27
verifyObjectNames, 28
verifyTestCaseDefinitions, 29

defineEvaluationModes, 2, 4, 5, 7, 8, 19, 20, 23, 26

defineFunctionReturnTypesParameterName, 3

defineTestCaseDefinitionsParameterName, 4, 28, 30

EvaluationMode, 3, 4, 4, 21–23

exploreObjectNamesVerification, 5

formalArgs, 17

formals, 18

FunctionParameterName, 6

FunctionParameterTypeFactory, 7, 16, 22, 25

getClassTypicalFunctionNames
(getObjectFunctionNames), 12

getEllipsisName, 8

getObjectClassKind, 9

getObjectClassNames, 10

getObjectFunctionArgumentNames, 11

getObjectFunctionNames, 12

hasMainClass (getObjectClassNames), 10

is.object, [9](#)
isAuditable, [13](#)

packageFunctionsInformation, [13](#)
print.EvaluationMode, [14](#)
print.FunctionParameterName, [15](#)
print.TestCaseDefinition, [15](#)

retrieveFactory, [16](#), [21](#), [23](#)
retrieveFunctionArgumentNames, [17](#)
retrieveFunctionArguments, [18](#)
retrieveFunctionReturnTypes, [19](#)
retrieveTestCaseDefinitions, [20](#)
retrieveTestCaseDescriptions
 (retrieveTestCaseDefinitions),
 [20](#)

runFunction, [21](#), [22](#), [24](#)
runTestCase, [22](#)
runTransientFunction, [23](#)

TestCaseDefinition, [24](#)

verifyClassName, [6](#), [25](#), [29](#)
verifyFunctionName, [6](#), [26](#), [29](#)
verifyFunctionReturnTypesDefinition,
 [19](#), [20](#), [27](#)
verifyObjectNames, [5](#), [19](#), [20](#), [28](#)
verifyTestCaseDefinitions, [29](#)