

Package ‘gllvm’

September 17, 2019

Type Package

Title Generalized Linear Latent Variable Models

Version 1.1.7

Date 2019-09-17

Author

Jenni Niku, Wesley Brooks, Riki Herliansyah, Francis K.C. Hui, Sara Taskinen, David I. Warton

Maintainer Jenni Niku <jenni.m.e.niku@jyu.fi>

Description Analysis of multivariate data using generalized linear latent variable models (gllvm). Estimation is performed using either Laplace approximation method or variational approximation method implemented via TMB (Kristensen et al., (2016), <doi:10.18637/jss.v070.i05>). For details see Niku et al. (2019) <doi:10.1371/journal.pone.0216129>.

License GPL-2

Imports MASS, Matrix, mvtnorm, statmod, fishMod, mgcv

Depends TMB, mvabund

Encoding UTF-8

LazyData true

LinkingTo TMB, RcppEigen

RoxygenNote 6.1.1

NeedsCompilation yes

URL <https://github.com/JenniNiku/gllvm.git>

Suggests knitr, rmarkdown, testthat, gclus, corrplot, lattice

VignetteBuilder knitr

Repository CRAN

Date/Publication 2019-09-17 16:30:05 UTC

R topics documented:

anova.gllvm	2
coefplot.gllvm	3

confint.gllvm	4
getLV.gllvm	5
getPredictErr.gllvm	5
getResidualCor.gllvm	6
getResidualCov.gllvm	7
gllvm	9
logLik.gllvm	15
microbialdata	16
ordiplot.gllvm	16
plot.gllvm	18
predict.gllvm	19
predictLVs.gllvm	21
residuals.gllvm	22
simulate.gllvm	23
sim_bacteria	24
summary.gllvm	25

Index	26
--------------	-----------

anova.gllvm	<i>Analysis Of Deviance for gllvm</i>
-------------	---------------------------------------

Description

Computes an analysis of deviance table for two generalized linear latent variable model fits.

Usage

```
## S3 method for class 'gllvm'
anova(object, ...)
```

Arguments

object	an object of class 'gllvm'.
...	one or more objects of class 'gllvm'

Details

Computes likelihood-ratio test for two or more gllvm models. Test results makes sense only for nested models. Notice also that this test is not designed for testing models which have degrees of freedom difference larger than 20. For such models the P-value should be treated as very approximate.

Author(s)

Jenni Niku

Examples

```
## Load a dataset from the mvabund package
data(antTraits)
y <- antTraits$abund
X <- antTraits$env
TR <- antTraits$traits
# Fit gllvm model
fit1 <- gllvm(y, X, TR, formula = ~ Bare.cover + Shrub.cover, family = poisson())
fit2 <- gllvm(y, X, TR, formula = ~ Bare.cover +
              (Bare.cover + Shrub.cover) : Webers.length, family = poisson())
# Test if the model with fourth corner interaction terms is significantly
# better using likelihood-ratio test:
anova(fit1, fit2)
```

coefplot.gllvm

*Plot covariate coefficients and confidence intervals***Description**

Plots covariate coefficients and their confidence intervals.

Usage

```
## S3 method for class 'gllvm'
coefplot(object, y.label = TRUE, which.Xcoef = NULL,
         cex.ylab = 0.5, mfrow = NULL, mar = c(4, 6, 2, 1),
         xlim.list = NULL, ...)
```

Arguments

object	an object of class 'gllvm'.
y.label	logical, if TRUE (default) colnames of y with respect to coefficients are added to plot.
which.Xcoef	vector indicating which covariate coefficients will be plotted. Can be vector of covariate names or numbers. Default is NULL when all covariate coefficients are plotted.
cex.ylab	the magnification to be used for axis annotation relative to the current setting of cex.
mfrow	same as mfrow in par. If NULL (default) it is determined automatically.
mar	vector of length 4, which defines the margin sizes: c(bottom, left, top, right). Defaults to c(4, 5, 2, 1).
xlim.list	list of vectors with length of two to define the intervals for an x axis in each covariate plot. Defaults to NULL when the interval is defined by the range of point estimates and confidence intervals
...	additional graphical arguments.

Author(s)

Jenni Niku <jenni.m.e.niku@jyu.fi>, Francis K.C. Hui, Sara Taskinen

Examples

```
## Load a dataset from the mvabund package
data(antTraits)
y <- as.matrix(antTraits$abund)
X <- as.matrix(antTraits$env)
# Fit model with environmental covariates
fit <- gllvm(y, X, formula = ~ Bare.ground + Shrub.cover,
            family = poisson())
coefplot.gllvm(fit)

# Fit model with all environmental covariates
fitx <- gllvm(y, X, family = "negative.binomial")
coefplot(fitx, mfrow = c(3,2))
coefplot(fitx, which.Xcoef = 1:2)

# Fit gllvm model with environmental and trait covariates
TR <- antTraits$traits
fitT <- gllvm(y = y, X = X, TR = TR, family = "negative.binomial")
coefplot(fitT)
```

confint.gllvm

Confidence intervals for model parameters

Description

Computes confidence intervals for parameters in a fitted gllvm model.

Usage

```
## S3 method for class 'gllvm'
confint(object, parm = NULL, level = 0.95, ...)
```

Arguments

object	an object of class 'gllvm'.
parm	a specification of which parameters are to be given confidence intervals, a vector of names. If missing, all parameters are considered.
level	the confidence level. Scalar between 0 and 1.
...	not used.

Author(s)

Jenni Niku <jenni.m.e.niku@jyu.fi>

Examples

```
## Load a dataset from the mvabund package
data(antTraits)
y <- as.matrix(antTraits$abund)
X <- as.matrix(antTraits$env[,1:2])
# Fit gllvm model
fit <- gllvm(y = y, X = X, family = poisson())
# 95 % confidence intervals for coefficients of X variables
confint(fit, level = 0.95, parm = "Xcoef")
```

getLV.gllvm	<i>Extract latent variables</i>
-------------	---------------------------------

Description

Extract latent variables from gllvm object.

Usage

```
## S3 method for class 'gllvm'
getLV(object)
```

Arguments

object an object of class 'gllvm'.

getPredictErr.gllvm	<i>Extract prediction errors for latent variables from gllvm object</i>
---------------------	---

Description

Calculates the prediction errors for latent variables for gllvm model.

Usage

```
## S3 method for class 'gllvm'
getPredictErr(object)
```

Arguments

object an object of class 'gllvm'.

Details

If variational approximation is used, prediction errors are based on covariances of the variational distributions, and therefore they do not take into account the uncertainty in the estimation of (fixed) parameters.

Value

Function returns following components:

lvs	prediction errors for latent variables
row.effects	prediction errors for random row effects if included

Author(s)

Francis K.C. Hui, Jenni Niku, David I. Warton

Examples

```
# Load a dataset from the mvabund package
data(antTraits)
y <- as.matrix(antTraits$abund)
# Fit gllvm model
fit <- gllvm(y = y, family = poisson())
# prediction errors for latent variables:
getPredictErr(fit)
```

`getResidualCor.gllvm` *Extract residual correlations from gllvm object*

Description

Calculates the residual correlation matrix for gllvm model.

Usage

```
## S3 method for class 'gllvm'
getResidualCor(object, adjust = 1)
```

Arguments

object	an object of class 'gllvm'.
adjust	The type of adjustment used for negative binomial and binomial distribution when computing residual correlation matrix. Options are 0 (no adjustment), 1 (the default adjustment) and 2 (alternative adjustment for NB distribution). See details.

Details

Residual correlation matrix is calculated based on the residual covariance matrix, see details from [getResidualCov.gllvm](#).

Author(s)

Francis K.C. Hui, Jenni Niku, David I. Warton

Examples

```
# Load a dataset from the mvabund package
data(antTraits)
y <- as.matrix(antTraits$abund)
# Fit gllvm model
fit <- gllvm(y = y, family = poisson())
# residual correlations:
cr <- getResidualCor(fit)
## Not run:
# Plot residual correlations:
install.packages("corrplot", "gclus")
library(corrplot)
library(gclus)
corrplot(cr[order.single(cr), order.single(cr)], diag = F,
         type = "lower", method = "square", tl.cex = 0.8, tl.srt = 45, tl.col = "red")

## End(Not run)
```

getResidualCov.gllvm *Extract residual covariance matrix from gllvm object*

Description

Calculates the residual covariance matrix for gllvm model.

Usage

```
## S3 method for class 'gllvm'
getResidualCov(object, adjust = 1)
```

Arguments

object	an object of class 'gllvm'.
adjust	The type of adjustment used for negative binomial and binomial distribution when computing residual correlation matrix. Options are 0 (no adjustment), 1 (the default adjustment) and 2 (alternative adjustment for NB distribution), see details.

Details

Residual covariance matrix, storing information on species co-occurrence that is not explained by the environmental variables (if included), is calculated using the matrix of latent variables loadings, that is, $\Theta\Theta'$.

When the responses are modelled using the negative binomial distribution, the residual variances for each species must be adjusted for overdispersion. The two possible adjustment terms are $\log(\phi_j + 1)$ (adjust = 1) and $\psi^{(1)}(1/\phi_j)$ (adjust = 2), where $\psi^{(1)}$ is the trigamma function.

The negative binomial model can be written using different parametrizations. The residual covariance with adjust = 1 can be obtained using the lognormal-Poisson parametrization, that is,

$$Y_{ij} \sim \text{Poisson}(\mu_{ij}\lambda_j),$$

where $\lambda_j \sim \text{lognormal}(-\sigma^2/2, \sigma^2)$ and $\sigma^2 = \log(\phi_j + 1)$ and $\log(\mu_{ij}) = \eta_{ij}$. Now $E[Y_{ij}] = \mu_{ij}$ and variance $V(\mu_{ij}) = \mu_{ij} + \mu_{ij}^2(\exp(\sigma^2) - 1) = \mu_{ij} + \mu_{ij}^2\phi_j$, which are the same as for the NB distribution. Therefore, on linear predictor scale, we have the variance

$$V(\log(\mu_{ij}\lambda_j)) = V(\log\mu_{ij}) + V(\log\lambda_j) = V(u'_i\theta_j) + \sigma^2 = \theta'_j\theta_j + \log(\phi_j + 1).$$

which leads to the residual covariance matrix $\Theta\Theta' + \text{diag}(\Phi)$, where Φ is the diagonal matrix with $\log(\phi_j + 1)$ as diagonal elements (adjust = 1).

The residual covariance matrix with adjust = 2 can be obtained by using Poisson-Gamma parametrization

$$Y_{ij} \sim \text{Poisson}(\mu_{ij}\lambda_j),$$

where $\lambda_j \sim \text{Gamma}(1/\phi_j, 1/\phi_j)$ and μ_{ij} is as above. The mean and the variance are of similar form as above and we have that

$$V(\log(\mu_{ij}\lambda_j)) = V(\log\mu_{ij}) + V(\log\lambda_j) = \theta'_j\theta_j + \psi^{(1)}(1/\phi_j),$$

where $\psi^{(1)}$ is the trigamma function.

In the case of binomial distribution, the adjustment terms (adjust = 1) are 1 for probit link and $\pi^2/3$ for logit link. These are obtained by treating binomial model as latent variable model. Assume

$$Y_{ij}^* = \eta_{ij} + e_{ij},$$

where $e_{ij} \sim N(0, 1)$ for probit model, and $e_{ij} \sim \text{logistic}(0, 1)$ for logit model. Then binary response is defined as $Y_{ij} = 1$, if $Y_{ij}^* > 0$ and 0 otherwise. Now we have that $\mu_{ij} = P(Y_{ij} = 1) = P(Y_{ij}^* > 0) = P(\eta_{ij} > -e_{ij}) = P(e_{ij} \leq \eta_{ij})$ which leads to probit and logit models. On linear predictor scale we then have that

$$V(\eta_{ij} + e_{ij}) = V(\eta_{ij}) + V(e_{ij}).$$

For the probit model, the residual covariance matrix is then $\Theta\Theta' + I_m$, and for the logit model $\Theta\Theta' + \pi^2/3I_m$.

Value

Function returns following components:

cov	residual covariance matrix
trace	trace of the residual covariance matrix

Author(s)

Francis K.C. Hui, Jenni Niku, David I. Warton

Examples

```
# Load a dataset from the mvabund package
data(antTraits)
y <- as.matrix(antTraits$abund)
# Fit gllvm model
fit <- gllvm(y = y, family = poisson())
# residual covariance:
rescov <- getResidualCov(fit)
rescov$cov
# Trace of the covariance matrix
rescov$tr
```

gllvm

Generalized Linear Latent Variable Models

Description

Fits generalized linear latent variable model for multivariate data. The model can be fitted using Laplace approximation method or variational approximation method.

Usage

```
gllvm(y = NULL, X = NULL, TR = NULL, data = NULL, formula = NULL,
      num.lv = 2, family, method = "VA", row.eff = FALSE,
      offset = NULL, sd.errors = TRUE, Lambda.struc = "unstructured",
      diag.iter = 5, trace = FALSE, plot = FALSE,
      la.link.bin = "probit", n.init = 1, Power = 1.5, reltol = 1e-08,
      seed = NULL, max.iter = 200, maxit = 1000, start.fit = NULL,
      starting.val = "res", TMB = TRUE, optimizer = "optim",
      Lambda.start = c(0.1, 0.5), jitter.var = 0)
```

Arguments

y	(n x m) matrix of responses.
X	matrix or data.frame of environmental covariates.
TR	matrix or data.frame of trait covariates.
data	data in long format, that is, matrix of responses, environmental and trait covariates and row index named as 'id'. When used, model needs to be defined using formula. This is alternative data input for y, X and TR.
formula	an object of class "formula" (or one that can be coerced to that class): a symbolic description of the model to be fitted.

num.lv	number of latent variables, d, in gllvm model. Non-negative integer, less than number of response variables (m). Defaults to 2.
family	distribution function for responses. Options are <code>poisson(link = "log")</code> , <code>negative.binomial</code> (with log link), <code>binomial(link = "probit")</code> (and also <code>binomial(link = "logit")</code> when <code>method = "LA"</code>), zero inflated poisson (" <code>ZIP</code> "), <code>gaussian(link = "identity")</code> , Tweedie (" <code>tweedie</code> ") (with log link, only with " <code>LA</code> "-method) and " <code>ordinal</code> " (only with " <code>VA</code> "-method).
method	model can be fitted using Laplace approximation method (<code>method = "LA"</code>) or variational approximation method (<code>method = "VA"</code>). Defaults to " <code>VA</code> ".
row.eff	FALSE, TRUE or " <code>random</code> ", Indicating whether row effects are included in the model as a fixed or as a random effects. Defaults to FALSE when row effects are not included.
offset	vector or matrix of offset terms.
sd.errors	logical. If TRUE (default) standard errors for parameter estimates are calculated.
Lambda.struc	covariance structure of VA distributions for latent variables when <code>method = "VA"</code> , " <code>unstructured</code> " or " <code>diagonal</code> ".
diag.iter	non-negative integer which is used to speed up the updating of variational (covariance) parameters in VA method. Defaults to 5.
trace	logical, if TRUE in each iteration step information on current step will be printed. Defaults to FALSE. Only with <code>TMB = FALSE</code> .
plot	logical, if TRUE ordination plots will be printed in each iteration step when <code>TMB = FALSE</code> . Defaults to FALSE.
la.link.bin	link function for binomial family if <code>method = "LA"</code> . Options are " <code>logit</code> " and " <code>probit</code> ".
n.init	number of initial runs. Uses multiple runs and picks up the one giving highest log-likelihood value. Defaults to 1.
Power	fixed power parameter in Tweedie model. Scalar from interval (1,2). Defaults to 1.5.
reltol	convergence criteria for log-likelihood, defaults to 1e-6.
seed	a single seed value, defaults to NULL.
max.iter	maximum number of iterations when <code>TMB = FALSE</code> , defaults to 200.
maxit	maximum number of iterations within <code>optim</code> function, defaults to 1000.
start.fit	object of class ' <code>gllvm</code> ' which can be given as starting parameters for count data (poisson, NB, or ZIP).
starting.val	starting values can be generated by fitting model without latent variables, and applying factorial analysis to residuals to get starting values for latent variables and their coefficients (<code>starting.val = "res"</code>). Another options are to use zeros as a starting values (<code>starting.val = "zero"</code>) or initialize starting values for latent variables with (n x num.lv) matrix. Defaults to " <code>res</code> ", which is recommended.
TMB	logical, if TRUE model will be fitted using Template Model Builder (TMB). TMB is always used if <code>method = "LA"</code> . Defaults to TRUE.

optimizer	if TMB=TRUE, log-likelihood can be optimized using "optim" (default) or "nlminb".
Lambda.start	starting values for variances in VA distributions for latent variables in variational approximation method. Defaults to 0.1.
jitter.var	jitter variance for starting values of latent variables. Defaults to 0, meaning no jittering.

Details

Fits generalized linear latent variable models as in Hui et al. (2015 and 2017) and Niku et al. (2017). Method can be used with two types of latent variable models depending on covariates. If only site related environmental covariates are used, the expectation of response Y_{ij} is determined by

$$g(\mu_{ij}) = \eta_{ij} = \alpha_i + \beta_{0j} + x'_i \beta_j + u'_i \theta_j,$$

where $g(\cdot)$ is a known link function, u_i are d -variate latent variables ($d \ll m$), α_i is an optional row effect at site i , and it can be fixed or random effect, β_{0j} is an intercept term for species j , β_j and θ_j are column specific coefficients related to covariates and the latent variables, respectively.

An alternative model is the fourth corner model (Brown et al., 2014, Warton et al., 2015) which will be fitted if also trait covariates are included. The expectation of response Y_{ij} is

$$g(\mu_{ij}) = \alpha_i + \beta_{0j} + x'_i \beta_x + TR'_j \beta_t + \text{vec}(B) * \text{kroncker}(TR_j, X_i) + u'_i \theta_j$$

where $g(\cdot)$, u_i , β_{0j} and θ_j are defined as above. Vectors β_x and β_t are the main effects or coefficients related to environmental and trait covariates, respectively, matrix B includes interaction terms. The interaction/fourth corner terms are optional as well as are the main effects of trait covariates.

The method is sensitive for the choices of initial values of the latent variables. Therefore it is recommendable to use multiple runs and pick up the one giving the highest log-likelihood value. However, sometimes this is computationally too demanding, and default option `starting.val = "res"` is recommended. For more details on different starting value methods, see Niku et al., (2018).

Models are implemented using TMB (Kristensen et al., 2015) applied to variational approximation (Hui et al., 2017) and Laplace approximation (Niku et al., 2017).

With ordinal family response classes must start from 0 or 1.

Distributions:

Mean and variance for distributions are defined as follows.

- For count data family = `poisson()`: Expectation $E[Y_{ij}] = \mu_{ij}$, variance $V(\mu_{ij}) = \mu_{ij}$, or
- family = "negative.binomial": Expectation $E[Y_{ij}] = \mu_{ij}$, variance $V(\mu_{ij}) = \mu_{ij} + \phi_j * \mu_{ij}^2$, or
- family = "ZIP": Expectation $E[Y_{ij}] = (1 - p)\mu_{ij}$, variance $V(\mu_{ij}) = \mu_{ij}(1 - p)(1 + \mu_{ij}p)$.
- For binary data family = `binomial()`: Expectation $E[Y_{ij}] = \mu_{ij}$, variance $V(\mu_{ij}) = \mu_{ij}(1 - \mu_{ij})$.
- For biomass data family = "tweedie": Expectation $E[Y_{ij}] = \mu_{ij}$, variance $V(\mu_{ij}) = \phi_j * \mu_{ij}^\nu$, where ν is a power parameter of Tweedie distribution. See details Dunn and Smyth (2005).
- For ordinal data family = "ordinal": Cumulative probit model, see Hui et.al. (2016).
- For normal distributed data family = `gaussian()`: Expectation $E[Y_{ij}] = \mu_{ij}$, variance $V(y_{ij}) = \phi_j^2$.

Value

An object of class "gllvm" includes the following components:

call	function call
logL	log likelihood
lvs	latent variables
params	list of parameters <ul style="list-style-type: none"> • theta coefficients related to latent variables • beta0 column specific intercepts • Xcoef coefficients related to environmental covariates X • B coefficients in fourth corner model • row.params row-specific intercepts • phi dispersion parameters ϕ for negative binomial or Tweedie family, probability of zero inflation for ZIP family or standard deviation for gaussian family • inv.phi dispersion parameters $1/\phi$ for negative binomial
Power	power parameter ν for Tweedie family
sd	list of standard errors of parameters
prediction.errors	list of prediction covariances for latent variables and variances for random row effects when method "LA" is used
A, Ar	covariance matrices for variational densities of latent variables and variances for random row effects

Note

If function gives warning: 'In f(x, order = 0) : value out of range in 'lgamma'', optimizer have visited an area where gradients become too big. It is automatically fixed by trying another step in the optimization process, and can be ignored if errors do not occur.

Author(s)

Jenni Niku <jenni.m.e.niku@jyu.fi>, Wesley Brooks, Riki Herliansyah, Francis K.C. Hui, Sara Taskinen, David I. Warton, Bert van der Veen

References

- Brown, A. M., Warton, D. I., Andrew, N. R., Binns, M., Cassis, G., and Gibb, H. (2014). The fourth-corner solution - using predictive models to understand how species traits interact with the environment. *Methods in Ecology and Evolution*, 5:344-352.
- Dunn, P. K. and Smyth, G. K. (2005). Series evaluation of tweedie exponential dispersion model densities. *Statistics and Computing*, 15:267-280.
- Hui, F. K. C., Taskinen, S., Pledger, S., Foster, S. D., and Warton, D. I. (2015). Model-based approaches to unconstrained ordination. *Methods in Ecology and Evolution*, 6:399-411.

Hui, F. K. C., Warton, D., Ormerod, J., Haapaniemi, V., and Taskinen, S. (2017). Variational approximations for generalized linear latent variable models. *Journal of Computational and Graphical Statistics*. *Journal of Computational and Graphical Statistics*, 26:35-43.

Kasper Kristensen, Anders Nielsen, Casper W. Berg, Hans Skaug, Bradley M. Bell (2016). TMB: Automatic Differentiation and Laplace Approximation. *Journal of Statistical Software*, 70(5), 1-21.

Niku, J., Warton, D. I., Hui, F. K. C., and Taskinen, S. (2017). Generalized linear latent variable models for multivariate count and biomass data in ecology. *Journal of Agricultural, Biological, and Environmental Statistics*, 22:498-522

Niku, J., Brooks, W., Herliansyah, R., Hui, F. K. C., Taskinen, S., and Warton, D. I. (2018). Efficient estimation of generalized linear latent variable models. Submitted.

Warton, D. I., Guillaume Blanchet, F., O'Hara, R. B., Ovaskainen, O., Taskinen, S., Walker, S. C. and Hui, F. K. C. (2015). So many variables: Joint modeling in community ecology. *Trends in Ecology & Evolution*, 30:766-779.

See Also

[coefplot.gllvm](#), [confint.gllvm](#), [ordiplot.gllvm](#), [plot.gllvm](#), [residuals.gllvm](#), [summary.gllvm](#).

Examples

```
## Load a dataset from the mvabund package
data(antTraits)
y <- as.matrix(antTraits$abund)
X <- as.matrix(antTraits$env)
TR <- antTraits$traits
# Fit model with environmental covariates Bare.ground and Shrub.cover
fit <- gllvm(y, X, formula = ~ Bare.ground + Shrub.cover,
            family = poisson())
ordiplot(fit)
coefplot(fit)

## Example 1: Fit model with two latent variables
# Using variational approximation:
fitv0 <- gllvm(y, family = "negative.binomial", method = "VA")
ordiplot(fitv0)
plot(fitv0, mfrow = c(2,2))
summary(fitv0)
confint(fitv0)
# Using Laplace approximation: (this line may take about 30 sec to run)
fitl0 <- gllvm(y, family = "negative.binomial", method = "LA")
ordiplot(fitl0)

# Poisson family:
fit.p <- gllvm(y, family = poisson(), method = "LA")
ordiplot(fit.p)
# Use poisson model as a starting parameters for ZIP-model, this line may take few minutes to run
fit.z <- gllvm(y, family = "ZIP", method = "LA", start.fit = fit.p)
ordiplot(fit.z)
```

```

## Example 2: gllvm with environmental variables
# Fit model with two latent variables and all environmental covariates,
fitvX <- gllvm(formula = y ~ X, family = "negative.binomial")
ordiplot(fitvX, biplot = TRUE)
coefplot(fitvX)
# Fit model with environmental covariates Bare.ground and Shrub.cover
fitvX2 <- gllvm(y, X, formula = ~ Bare.ground + Shrub.cover,
  family = "negative.binomial")
ordiplot(fitvX2)
coefplot(fitvX2)
# Use 5 initial runs and pick the best one
fitvX_5 <- gllvm(y, X, formula = ~ Bare.ground + Shrub.cover,
  family = "negative.binomial", n.init = 5, jitter.var = 0.1)
ordiplot(fitvX_5)
coefplot(fitvX_5)

## Example 3: Data in long format
# Reshape data to long format:
datalong <- reshape(data.frame(cbind(y,X)), direction = "long",
  varying = colnames(y), v.names = "y")
head(datalong)
fitvLong <- gllvm(data = datalong, formula = y ~ Bare.ground + Shrub.cover,
  family = "negative.binomial")

## Example 4: Fourth corner model
# Fit fourth corner model with two latent variables
fitF1 <- gllvm(y = y, X = X, TR = TR, family = "negative.binomial")
coefplot(fitF1)
# Fourth corner can be plotted also with next lines
#fourth = fitF1$fourth.corner
#library(lattice)
#a = max( abs(fourth) )
#colort = colorRampPalette(c("blue","white","red"))
#plot.4th = levelplot(t(as.matrix(fourth)), xlab = "Environmental Variables",
#  ylab = "Species traits", col.regions = colort(100),
#  at = seq( -a, a, length = 100), scales = list( x = list(rot = 45)))
#print(plot.4th)

# Specify model using formula
fitF2 <- gllvm(y = y, X = X, TR = TR,
  formula = ~ Bare.ground + Canopy.cover * (Pilosity + Webers.length),
  family = "negative.binomial")
ordiplot(fitF2)
coefplot(fitF2)

## Example 5: Fit Tweedie model
# Load coral data
data(tikus)
ycoral <- tikus$abund
# Let's consider only years 1981 and 1983
ycoral <- ycoral[((tikus$x$time == 81) + (tikus$x$time == 83)) > 0, ]
# Exclude species which have observed at less than 4 sites

```

```
ycoral <- ycoral[-17, (colSums(ycoral > 0) > 3)]
# Fit Tweedie model for coral data (this line may take few minutes to run)
fit.twe <- gllvm(y = ycoral, family = "tweedie", method = "LA")
ordiplot(fit.twe)

## Example 6: Random row effects
fitRand <- gllvm(y, family = "negative.binomial", row.eff = "random")
ordiplot(fitRand, biplot = TRUE)
```

logLik.gllvm

Log-likelihood of gllvm

Description

Extracts Log-likelihood from 'gllvm' objects.

Usage

```
## S3 method for class 'gllvm'
logLik(object, ...)
```

Arguments

object	an object of class 'gllvm'.
...	not used.

Author(s)

David I. Warton, Jenni Niku

Examples

```
## Load a dataset from the mvabund package
data(antTraits)
y <- as.matrix(antTraits$abund)
# Fit gllvm model
fit <- gllvm(y = y, family = poisson())
# log-Likelihood:
logLik(fit)
```

 microbialdata

Microbial community data

Description

Microbial community data consist of abundances of 985 bacteria species measured at 56 soil sample sites from three regions, Kilpisjarvi (Finland), Ny-Alesund (Norway), and Mayrhofen (Austria). In addition to bacteria counts, three continuous environmental variables (pH, available phosphorous and soil organic matter) were measured from each soil sample.

Usage

```
data(microbialdata)
```

Format

- Y** A data frame with abundances of 985 bacteria species measured at 56 soil sample sites
- X** Environmental variables SOM: soil organic matter, pH: soil pH value and Phosp: available phosphorus and information from the samples, including Region: sampling region (Kilpisjarvi (Finland), Ny-Alesund (Norway), and Mayrhofen (Austria).), Site: sampling site and Soiltype: soil sample type (top soil (T) or bottom soil (B))

References

Kumar, M., Brader, G., Sessitsch, A., Mäki, A., van Elsas, J.D., and Nissinen, R. (2017). Plants Assemble Species Specific Bacterial Communities from Common Core Taxa in Three Arcto-Alpine Climate Zones. *Frontiers in Microbiology*, 8:12.

 ordiplot.gllvm

Plot latent variables from gllvm model

Description

Plots latent variables and their corresponding coefficients (biplot).

Usage

```
## S3 method for class 'gllvm'
ordiplot(object, biplot = FALSE, ind.spp = NULL,
  alpha = 0.5, main = NULL, which.lvs = c(1, 2), jitter = FALSE,
  jitter.amount = 0.2, s.colors = 1, symbols = FALSE,
  cex.spp = 0.7, ...)
```


Arguments

object	an object of class 'gllvm'.
biplot	TRUE if both latent variables and their coefficients are plotted, FALSE if only latent variables.
ind.spp	the number of response variables (usually, species) to include on the biplot. The default is none, or all if biplot = TRUE.
alpha	a numeric scalar between 0 and 1 that is used to control the relative scaling of the latent variables and their coefficients, when constructing a biplot.
main	main title.
which.lvs	indices of two latent variables to be plotted if number of the latent variables is more than 2. A vector with length of two. Defaults to c(1, 2).
jitter	if TRUE, jittering is applied on points.
jitter.amount	numeric, positive value indicating an amount of jittering for each point, defaults to 0.2 (jitter range).
s.colors	colors for sites
symbols	logical, if TRUE sites are plotted using symbols, if FALSE (default) site numbers are used
cex.spp	size of species labels in biplot
...	additional graphical arguments.

Details

Function constructs a scatter plot of two latent variables, i.e. an ordination plot. If only one latent variable is in the fitted model, latent variables are plotted against their corresponding row indices. The latent variables are labeled using the row index of the response matrix y .

Coefficients related to latent variables are plotted in the same figure with the latent variables if `biplot = TRUE`. They are labeled using the column names of y . The number of latent variable coefficients to be plotted can be controlled by `ind.spp`. An argument `alpha` is used to control the relative scaling of the latent variables and their coefficients. If `alpha = 0.5`, the latent variables and their coefficients are on the same scale. For details for constructing a biplot, see Gabriel (1971).

Author(s)

Jenni Niku <jenni.m.e.niku@jyu.fi>, Francis K.C. Hui

References

Gabriel, K. R. (1971). The biplot graphic display of matrices with application to principal component analysis. *Biometrika*, 58, 453-467.

Examples

```
### Load a dataset from the mvabund package
data(antTraits)
y <- as.matrix(antTraits$abund)
```

```
fit <- gllvm(y, family = poisson())
# Ordination plot:
ordiplot(fit)
# Biplot with 10 species
ordiplot(fit, biplot = TRUE, ind.spp = 10)
```

plot.gllvm

Plot Diagnostics for an gllvm Object

Description

Five plots (selectable by which) are currently available: a plot of residuals against linear predictors of fitted values, a Normal Q-Q plot of residuals with a simulated point-wise 95% confidence interval envelope, residuals against row index and column index and scale location plot.

Usage

```
## S3 method for class 'gllvm'
plot(x, which = 1:5,
     caption = c("Residuals vs linear predictors", "Normal Q-Q",
                 "Residuals vs row index", "Residuals vs column index", "Scale-Location"),
     var.colors = NULL, add.smooth = TRUE, envelopes = TRUE,
     reps = 150, envelope.col = c("blue", "lightblue"), n.plot = NULL,
     ...)
```

Arguments

x	an object of class 'gllvm'.
which	if a subset of the plots is required, specify a subset of the numbers 1:5, see caption below.
caption	captions to appear above the plots.
var.colors	colors for responses, vector with length of number of response variables or 1. Defaults to NULL, when different responses have different colors.
add.smooth	logical indicating if a smoother should be added.
envelopes	logical, indicating if simulated point-wise confidence interval envelope will be added to Q-Q plot, defaults to TRUE
reps	number of replications when simulating confidence envelopes for normal Q-Q plot
envelope.col	colors for envelopes, vector with length of two
n.plot	number of species (response variables) to be plotted. Defaults to NULL when all response variables are plotted. Might be useful when data is very high dimensional.
...	additional graphical arguments.

Details

plot.gllvm is used for model diagnostics. Dunn-Smyth residuals (randomized quantile residuals) (Dunn and Smyth, 1996) are used in plots. Colors indicate different species.

Author(s)

Jenni Niku <jenni.m.e.niku@jyu.fi>

References

Dunn, P. K., and Smyth, G. K. (1996). Randomized quantile residuals. *Journal of Computational and Graphical Statistics*, 5, 236-244.

Hui, F. K. C., Taskinen, S., Pledger, S., Foster, S. D., and Warton, D. I. (2015). Model-based approaches to unconstrained ordination. *Methods in Ecology and Evolution*, 6:399-411.

See Also

[gllvm](#), [residuals.gllvm](#)

Examples

```
## Load a dataset from the mvabund package
data(antTraits)
y <- as.matrix(antTraits$abund)
# Fit gllvm model with Poisson family
fit <- gllvm(y, family = poisson())
# Plot residuals
plot(fit, mfrow = c(3,2))

# Fit gllvm model with negative binomial family
fitnb <- gllvm(y = y, family = "negative.binomial")
# Plot residuals
plot(fitnb, mfrow = c(3,2))
# Plot only two first plots
plot(fitnb, which = 1:2, mfrow = c(1,2))
```

predict.gllvm

Predict Method for gllvm Fits

Description

Obtains predictions from a fitted generalized linear latent variable model object.

Usage

```
## S3 method for class 'gllvm'
predict(object, newX = NULL, newTR = NULL,
        newLV = NULL, type = "link", ...)
```

Arguments

object	an object of class 'gllvm'.
newX	A new data frame of environmental variables. If omitted, the original matrix of environmental variables is used.
newTR	A new data frame of traits for each response taxon. If omitted, the original matrix of traits is used.
newLV	A new matrix of latent variables. If omitted, the original matrix of latent variables is used.
type	the type of prediction required. The default ("link") is on the scale of the linear predictors; the alternative "response" is on the scale of the response variable. that is, the predictions for the binomial model are predicted probabilities. In case of ordinal data, type = "response" gives predicted probabilities for each level of ordinal variable.
...	not used.

Details

If newX, newTR and newLV are omitted the predictions are based on the data used for fitting the model. Notice that newTR need to match with the number of species in the original data. Instead, new sites can be specified in newX. If predictors newX (and newTR) are given, and newLV is not, latent variables are not used in the predictions.

Value

A matrix containing requested predictor types.

Author(s)

Jenni Niku <jenni.m.e.niku@jyu.fi>, David Warton

Examples

```
# Load a dataset from the mvabund package
data(antTraits)
y <- as.matrix(antTraits$abund)
X <- scale(antTraits$env[, 1:3])
# Fit gllvm model
fit <- gllvm(y = y, X, family = poisson())
# fitted values
predfit <- predict(fit, type = "response")

# linear predictors
predlin <- predict(fit)
# Predict new sites:
# Generate matrix of environmental variables for 10 new sites
xnew <- cbind(rnorm(10), rnorm(10), rnorm(10))
colnames(xnew) <- colnames(X)
predfit <- predict(fit, newX = xnew, type = "response")
```

```

TR <- (antTraits$str[, 1:3])
fitt <- gllvm(y = y, X, TR, family = poisson())
# linear predictors
predlin <- predict(fitt)
# Predict new sites:
# Generate matrix of environmental variables for 10 new sites
xnew <- cbind(rnorm(10), rnorm(10), rnorm(10))
colnames(xnew) <- colnames(X)
# Generate matrix of traits for species
trnew <- data.frame(Femur.length = rnorm(41), No.spines = rnorm(41),
  Pility = factor(sample(0:3, 41, replace = TRUE)))
predfit <- predict(fitt, newX = xnew, newTR = trnew, type = "response")

```

predictLVs.gllvm

Predict latent variables for gllvm Fits

Description

Obtains predictions for latent variables from a fitted generalized linear latent variable model object. Currently works only for the variational approximation method.

Usage

```

## S3 method for class 'gllvm'
predictLVs(object, newX = if (is.null(object$X)) NULL
  else object$X, newY = object$y, ...)

```

Arguments

object	an object of class 'gllvm'.
newX	A new data frame of environmental variables. If omitted, the original matrix of environmental variables is used.
newY	A new response data. Defaults to the dataset used for original model fit.
...	not used.

Details

Obtains predictions for latent variables from a fitted generalized linear latent variable model object.

Value

A matrix containing requested predictor types.

Author(s)

David Warton, Jenni Niku <jenni.m.e.niku@jyu.fi>

Examples

```
# Load a dataset from the mvabund package
data(antTraits)
y <- as.matrix(antTraits$abund)
X <- scale(antTraits$env[, 1:3])
# Fit gllvm model
fit <- gllvm(y = y, X, family = poisson())
# fitted values
predLVs <- predictLVs.gllvm(fit, type = "response")
```

residuals.gllvm

*Dunn-Smyth residuals for gllvm model***Description**

Calculates Dunn-Smyth residuals for gllvm model.

Usage

```
## S3 method for class 'gllvm'
residuals(object, ...)
```

Arguments

object	an object of class 'gllvm'.
...	not used.

Details

Computes Dunn-Smyth residuals (randomized quantile residuals, Dunn and Smyth, 1996) for gllvm model. For the observation Y_{ij} Dunn-Smyth residuals are defined as

$$r_{ij} = \Phi^{-1}(u_{ij}F_{ij}(y_{ij}) + (1 - u_{ij})F_{ij}^-(y_{ij})),$$

where $\Phi(\cdot)$ and $F_{ij}(\cdot)$ are the cumulative probability functions of the standard normal distribution, $F_{ij}^-(y)$ is the limit as $F_{ij}(y)$ is approached from the negative side, and u_{ij} has been generated at random from the standard uniform distribution.

Value

residuals	matrix of residuals
linpred	matrix of linear predictors

Author(s)

Jenni Niku <jenni.m.e.niku@jyu.fi>

References

Dunn, P. K., and Smyth, G. K. (1996). Randomized quantile residuals. *Journal of Computational and Graphical Statistics*, 5, 236-244.

Hui, F. K. C., Taskinen, S., Pledger, S., Foster, S. D., and Warton, D. I. (2015). Model-based approaches to unconstrained ordination. *Methods in Ecology and Evolution*, 6:399-411.

Examples

```
# Load a dataset from the mvabund package
data(antTraits)
y <- as.matrix(antTraits$abund)
# Fit gllvm model
fit <- gllvm(y = y, family = poisson())
# residuals
res <- residuals(fit)
```

simulate.gllvm	<i>Simulate data from gllvm fit</i>
----------------	-------------------------------------

Description

Generate new data using the fitted values of the parameters

Usage

```
## S3 method for class 'gllvm'
simulate(object, nsim = 1, seed = NULL, ...)
```

Arguments

object	an object of class 'gllvm'.
nsim	an optional positive integer specifying the number of simulated datasets. Defaults to 1.
seed	an optional integer to set seed number, passed to set.seed. Defaults to a random seed number.
...	not used.

Details

simulate function for gllvm objects. Note this simulates marginally over LVs. an option is to add a conditional argument, which would fix the LVs. David Warton

Value

A matrix containing generated data.

Author(s)

David Warton, Jenni Niku <jenni.m.e.niku@jyu.fi>

Examples

```
# Load a dataset from the mvabund package
data(antTraits)
y <- as.matrix(antTraits$abund)
X <- scale(antTraits$env[, 1:3])
# Fit gllvm model
fit <- gllvm(y = y, X, family = poisson())
# Simulate data
newdata <- simulate(fit)
```

sim_bacteria

Simulated bacteria data

Description

Simulated dataset of size 56 x 985 that can be used to illustrate the methods in Section 5.1 of Niku et al., (2017).

Usage

```
data(sim_bacteria)
```

Format

y A data frame with abundances of 985 species measured at 56 sites

X Environmental variables soil organic matter, pH and phosphorus and region variables

References

Niku, J., Warton, D. I., Hui, F. K. C., and Taskinen, S. (2017). Generalized Linear Latent Variable Models for Multivariate Count and Biomass Data in Ecology. *Journal of Agricultural, Biological, and Environmental Statistics*, 22, 498-522.

`summary.gllvm`*Summarizing gllvm model fits*

Description

A summary of the fitted 'gllvm' object, including function call, distribution family and model parameters.

Usage

```
## S3 method for class 'gllvm'  
summary(object, ...)
```

Arguments

<code>object</code>	an object of class 'gllvm'
<code>...</code>	not used.

Author(s)

Jenni Niku <jenni.m.e.niku@jyu.fi>

Examples

```
## Load a dataset from the mvabund package  
data(antTraits)  
y <- as.matrix(antTraits$abund)  
# Fit gllvm model  
fit <- gllvm(y = y, family = poisson())  
summary(fit)
```

Index

anova.gllvm, 2

coefplot (coefplot.gllvm), 3
coefplot.gllvm, 3, 13
confint.gllvm, 4, 13

getLV (getLV.gllvm), 5
getLV.gllvm, 5
getPredictErr (getPredictErr.gllvm), 5
getPredictErr.gllvm, 5
getResidualCor (getResidualCor.gllvm), 6
getResidualCor.gllvm, 6
getResidualCov (getResidualCov.gllvm), 7
getResidualCov.gllvm, 6, 7
gllvm, 9, 19

logLik.gllvm, 15

microbialdata, 16

n1minb, 11

optim, 11
ordiplot (ordiplot.gllvm), 16
ordiplot.gllvm, 13, 16

plot.gllvm, 13, 18
predict (predict.gllvm), 19
predict.gllvm, 19
predictLVs (predictLVs.gllvm), 21
predictLVs.gllvm, 21

residuals.gllvm, 13, 19, 22

sim_bacteria, 24
simulate (simulate.gllvm), 23
simulate.gllvm, 23
summary.gllvm, 13, 25