

Package ‘rbokeh’

October 12, 2016

Title R Interface for Bokeh

Version 0.5.0

Description A native R plotting library that provides a flexible declarative interface for creating interactive web-based graphics, backed by the Bokeh visualization library <<http://bokeh.pydata.org/>>.

URL <https://hafen.github.io/rbokeh> <https://github.com/bokeh/rbokeh>

BugReports <https://github.com/bokeh/rbokeh/issues>

License MIT + file LICENSE

LazyData true

NeedsCompilation no

Imports htmlwidgets (>= 0.5), maps, methods, jsonlite, digest, hexbin, lazyeval, pryr, magrittr, ggplot2, scales, gistr

Suggests testthat, data.table, lattice, lintr, roxygen2 (>= 5.0.0), knitr

Enhances shiny (>= 0.12)

RoxygenNote 5.0.1

VignetteBuilder knitr

Author Ryan Hafen [aut, cre],
Kenton Russell [ctb],
Jonathan Owen [ctb],
Barret Schloerke [ctb],
Saptasrhi Guha [ctb],
Continuum Analytics, Inc. [aut, cph] (Bokeh library in htmlwidgets/lib,
<http://bokeh.pydata.org>)

Maintainer Ryan Hafen <rhafen@gmail.com>

Repository CRAN

Date/Publication 2016-10-12 00:08:32

R topics documented:

rbokeh-package	3
bk_default_theme	4
bokeh_render_json	4
b_eval	5
catjitter	5
console_callback	6
custom_callback	6
data_name_list	7
debug_callback	7
elements	8
figure	9
figure_data	11
flightfreq	12
get_object_refs	12
gmap	13
gmap_style	14
grid_plot	15
ly_abline	18
ly_annular_wedge	19
ly_annulus	22
ly_arc	24
ly_bar	26
ly_bezier	29
ly_boxplot	31
ly_contour	33
ly_crect	34
ly_curve	37
ly_density	39
ly_hexbin	40
ly_hist	41
ly_image	42
ly_image_url	44
ly_lines	45
ly_map	46
ly_multi_line	49
ly_oval	50
ly_patch	52
ly_points	54
ly_polygons	56
ly_quadratic	58
ly_quantile	60
ly_ray	62
ly_rect	64
ly_segments	66
ly_text	67
ly_wedge	69

nyctaxihex	72
pal_color	73
phantom_install	73
point_types	74
print_model_json	74
rbokeh2html	75
rbokehOutput	75
renderRbokeh	77
set_palette	77
set_theme	79
shiny_callback	80
sub_names	81
theme_axis	81
theme_grid	85
theme_legend	87
theme_plot	88
theme_title	90
tool_box_select	92
tool_box_zoom	93
tool_crosshair	93
tool_hover	94
tool_lasso_select	95
tool_pan	96
tool_reset	97
tool_resize	97
tool_save	98
tool_selection	99
tool_tap	99
tool_wheel_zoom	100
widget2gist	101
widget2png	102
x_axis	102
x_range	104
y_axis	105
y_range	107
%>%	108

Index**109**

rbokeh-package

*rbokeh: R interface for Bokeh***Description**

R interface for creating plots in Bokeh. Bokeh by Continuum Analytics, <http://bokeh.pydata.org/en/latest/>

Details

For full documentation on the package, visit <http://hafen.github.io/rbokeh>

bk_default_theme	<i>Themes</i>
------------------	---------------

Description

Themes

Themes

Usage

bk_default_theme()

bk_ggplot_theme()

bokeh_render_json	<i>Plot a Bokeh JSON specification</i>
-------------------	--

Description

Take a path to a Bokeh JSON plot specification file and render it in the browser.

Usage

bokeh_render_json(json_file)

Arguments

json_file path to json file

Note

This is mainly useful for development / debugging purposes for reading in json created from another platform like Python, or to be used with tweaking json output from [print_model_json](#).

See Also

[print_model_json](#)

b_eval	<i>Eval lazy symbol</i>
--------	-------------------------

Description

Evaluate the argument from the env it came from, or from within the data. The arg supplied to the returned function must be lazy.

Usage

```
b_eval(data)
```

Arguments

data data set to be used for evaluation. May be NULL

Value

a function that takes in one lazy argument to be evaluated

catjitter	<i>Add a small amount of (rbokeh-compatible) noise to a character vector</i>
-----------	--

Description

Add a small amount of (rbokeh-compatible) noise to a character vector

Usage

```
catjitter(x, factor = 0.5)
```

Arguments

x numeric vector to which jitter should be added
factor a factor between 0 and 1 that

Examples

```
figure(data = lattice::singer) %>%  
  ly_points(catjitter(voice.part), jitter(height), color = "black") %>%  
  ly_boxplot(voice.part, height, with_outliers = FALSE)
```

console_callback	<i>Specify a console callback</i>
------------------	-----------------------------------

Description

This registers a callback that simply prints the callback objects in the javascript console of your web browser. A probably more useful callback is the [debug_callback](#) which will place you inside a debugger in your web browser allowing you to inspect the callback objects.

Usage

```
console_callback()
```

Examples

```
figure() %>%
  ly_points(1:10) %>%
  x_range(callback = console_callback()) %>%
  y_range(callback = console_callback())
```

custom_callback	<i>Specify a custom callback</i>
-----------------	----------------------------------

Description

This registers a callback that allows you to specify your own custom callback javascript code. A probably more useful callback to use in conjunction with this for working on the javascript code is the [debug_callback](#) which will place you inside a debugger in your web browser allowing you to inspect the callback objects.

Usage

```
custom_callback(code, lnames = NULL, args = NULL)
```

Arguments

code	a string of javascript callback code
lnames	vector of layer names to be made available inside the callback in addition to the default callback objects (see details)
args	named list of additional references to objects to be addressable in the callback

Details

If we add a layer and provide it, for example the lname "points", then if we refer to it using the lnames parameter to the callback, several objects will be made available inside the callback for you to access, given the names "points_data", "points_glyph", "points_glyph_rend", "points_hov_glyph", "points_ns_glyph", all pointers to different objects associated with the "points" layer that your callback can manipulate.

Examples

```
# hover over the blue points and make the orange points move
figure(title = "hover a blue point") %>%
  ly_points(1:10, lname = "blue", lgroup = "g1") %>%
  ly_points(2:12, lname = "orange", lgroup = "g1") %>%
  tool_hover(custom_callback(
    code = "debugger;if(cb_data.index['1d'].indices.length > 0)
    orange_data.get('data').x[cb_data.index['1d'].indices] += 0.1
    orange_data.trigger('change')", "orange"), "blue")
```

data_name_list	<i>List of all types of data name structures that could appear</i>
----------------	--

Description

List of all types of data name structures that could appear

Usage

```
data_name_list()
```

debug_callback	<i>Specify a "debug" callback</i>
----------------	-----------------------------------

Description

This registers a callback that simply places you inside a debugger in your web browser allowing you to inspect the callback objects.

Usage

```
debug_callback(lnames = NULL, args = NULL)
```

Arguments

`lnames` vector of layer names to be made available inside the callback in addition to the default callback objects (see [custom_callback](#) for details)

`args` named list of additional references to objects to be addressable in the callback

Examples

```
figure() %>%
  ly_points(1:10, lname = "points") %>%
  tool_tap(debug_callback("points"), "points")
```

elements	<i>"Periodic Table" dataset</i>
----------	---------------------------------

Description

Data for periodic table of the elements

Usage

elements

Examples

```
# prepare data
elements <- subset(elements, !is.na(group))
elements$group <- as.character(elements$group)
elements$period <- as.character(elements$period)

# add colors for groups
metals <- c("alkali metal", "alkaline earth metal", "halogen",
  "metal", "metalloid", "noble gas", "nonmetal", "transition metal")
colors <- c("#a6cee3", "#1f78b4", "#fdbf6f", "#b2df8a", "#33a02c",
  "#bbbb88", "#baa2a6", "#e08e79")
elements$color <- colors[match(elements$metal, metals)]
elements$type <- elements$metal

# make coordinates for labels
elements$symx <- paste(elements$group, ":0.1", sep = "")
elements$numbery <- paste(elements$period, ":0.8", sep = "")
elements$massy <- paste(elements$period, ":0.15", sep = "")
elements$namey <- paste(elements$period, ":0.3", sep = "")

# create figure
p <- figure(title = "Periodic Table", tools = "",
  ylim = as.character(c(7:1)), xlim = as.character(1:18),
```



```

xgrid = FALSE, ygrid = FALSE, xlab = "", ylab = "",
height = 600, width = 1200) %>%

# plot rectangles
ly_crect(group, period, data = elements, 0.9, 0.9,
  fill_color = color, line_color = color, fill_alpha = 0.6,
  hover = list(name, atomic.number, type, atomic.mass,
    electronic.configuration)) %>%

# add symbol text
ly_text(symx, period, text = symbol, data = elements,
  font_style = "bold", font_size = "15pt",
  align = "left", baseline = "middle") %>%

# add atomic number text
ly_text(symx, numbery, text = atomic.number, data = elements,
  font_size = "9pt", align = "left", baseline = "middle") %>%

# add name text
ly_text(symx, namey, text = name, data = elements,
  font_size = "6pt", align = "left", baseline = "middle") %>%

# add atomic mass text
ly_text(symx, massy, text = atomic.mass, data = elements,
  font_size = "6pt", align = "left", baseline = "middle")

p

```

figure

Initialize a Bokeh figure

Description

Initialize a Bokeh figure

Usage

```

figure(data = NULL, width = NULL, height = NULL, title = NULL,
  xlab = NULL, ylab = NULL, xlim = NULL, ylim = NULL,
  padding_factor = 0.07, xgrid = TRUE, ygrid = TRUE, xaxes = "below",
  yaxes = "left", legend_location = "top_right", tools = c("pan",
  "wheel_zoom", "box_zoom", "reset", "save", "help"),
  theme = getOption("bokeh_theme"), toolbar_location = "above",
  h_symmetry = TRUE, v_symmetry = FALSE, logo = NULL, lod_factor = 10,
  lod_interval = 300, lod_threshold = NULL, lod_timeout = 500,
  webgl = FALSE, ...)

```

Arguments

<code>data</code>	data to be supplied to all layers, if the layer doesn't supply a data value
<code>width</code>	figure width in pixels
<code>height</code>	figure width in pixels
<code>title</code>	a title to display above the plot. - "title" is also the prefix for a set of Text Properties, so you can set the font for the title with the parameter <code>text_font</code> .
<code>xlab</code>	label for x axis
<code>ylab</code>	label for y axis
<code>xlim</code>	the extent of the plotting area in the x-dimension (will be computed automatically if not specified).
<code>ylim</code>	the extent of the plotting area in the y-dimension (will be computed automatically if not specified).
<code>padding_factor</code>	if limits are not specified, by what factor should the extents of the data be padded
<code>xgrid</code>	whether to draw x axis grid lines
<code>ygrid</code>	whether to draw y axis grid lines
<code>xaxes</code>	where to put x axis, or FALSE if no x axis ticks / labels
<code>yaxes</code>	where to put y axis, or FALSE if no y axis ticks / labels
<code>legend_location</code>	('top_right', 'top_left', 'bottom_left', 'bottom_right') the location where the legend should draw itself, or NULL to omit the legend
<code>tools</code>	character vector of interactivity tools options (acceptable values are: "pan", "wheel_zoom", "box_zoom", "resize", "crosshair", "box_select", "lasso_select", "reset", "save", "help"). Additionally, tool functions can be called on a figure to specify more control - see the "See Also" section below for a list of tool functions. If NULL, the toolbar will not be drawn. If "" the toolbar will be drawn but no tools will be added by default.
<code>theme</code>	an rbokeh theme to use
<code>toolbar_location</code>	('above', 'below', 'left', 'right') Where the toolbar will be located. If set to NULL, no toolbar will be attached to the plot.
<code>h_symmetry</code>	(logical) Whether the total horizontal padding on both sides of the plot will be made equal (the left or right padding amount, whichever is larger).
<code>v_symmetry</code>	(logical) Whether the total vertical padding on both sides of the plot will be made equal (the top or bottom padding amount, whichever is larger).
<code>logo</code>	('normal', 'grey') What version of the Bokeh logo to display on the toolbar. If set to NULL, no logo will be displayed.
<code>lod_factor</code>	(integer) Decimation factor to use when applying level-of-detail decimation (see "Controlling level of detail").
<code>lod_interval</code>	(integer) Interval (in ms) during which an interactive tool event will enable level-of-detail downsampling (see "Controlling level of detail").
<code>lod_threshold</code>	(integer) A number of data points, above which level-of-detail downsampling may be performed by glyph renderers. Set to NULL to disable any level-of-detail downsampling (see "Controlling level of detail").

lod_timeout	(integer) Timeout (in ms) for checking whether interactive tool events are still occurring. Once level-of-detail mode is enabled, a check is made every lod_timeout ms. If no interactive tool events have happened, level-of-detail mode is disabled (see "Controlling level of detail").
webgl	(logical) should webgl be used for rendering?
...	parameters can be specified here that are available in theme_plot

Controlling level of detail

Although the HTML canvas can comfortably display tens or even hundreds of thousands of glyphs, doing so can have adverse affects on interactive performance. In order to accommodate large-ish (but not enormous) data sizes, Bokeh plots offer "Level of Detail" (LOD) capability in the client.

The basic idea is that during interactive operations (e.g., panning or zooming), the plot only draws some small fraction data points. This hopefully allows the general sense of the interaction to be preserved mid-flight, while maintaining interactive performance. See the lod_ parameters for information on how to control this.

See Also

Layers to add to a figure: [ly_abline](#); [ly_annular_wedge](#); [ly_annulus](#); [ly_arc](#); [ly_bezier](#); [ly_boxplot](#); [ly_contour](#); [ly_crect](#); [ly_curve](#); [ly_density](#); [ly_hist](#); [ly_image_url](#); [ly_image](#); [ly_lines](#); [ly_map](#); [ly_multi_line](#); [ly_oval](#); [ly_patch](#); [ly_points](#); [ly_polygons](#); [ly_quadratic](#); [ly_quantile](#); [ly_ray](#); [ly_segments](#); [ly_text](#); [ly_wedge](#) Tools to add to a figure: [tool_box_select](#); [tool_box_zoom](#); [tool_crosshair](#); [tool_lasso_select](#); [tool_reset](#); [tool_resize](#); [tool_save](#); [tool_wheel_zoom](#) Other figure types: [grid_plot](#); [gmap](#)

Examples

```
figure() %>% ly_points(1:10)
```

figure_data	<i>Retrieve rbokeh figure data</i>
-------------	------------------------------------

Description

Retrieve rbokeh figure data

Usage

```
figure_data(fig)
```

Arguments

fig	rbokeh figure
-----	---------------

flightfreq	<i>Flight frequency dataset</i>
------------	---------------------------------

Description

Daily counts of domestic flights in the U.S. from 1999 to mid-2008

Usage

```
flightfreq
```

Examples

```
p <- figure(width = 1000) %>%  
  ly_points(date, Freq, data = flightfreq,  
    hover = list(date, Freq, dow), size = 5) %>%  
  ly_abline(v = as.Date("2001-09-11"))  
p
```

get_object_refs	<i>Get object ids and types from a figure</i>
-----------------	---

Description

Get object ids and types from a figure

Usage

```
get_object_refs(fig)
```

Arguments

fig	a figure object
-----	-----------------

gmap

*Initialize a Bokeh Google Map plot***Description**

Initialize a Bokeh Google Map plot

Usage

```
gmap(lat = 0, lng = 0, zoom = 0, api_key = NULL, map_type = "hybrid",
     map_style = NULL, width = 480, height = 480, title = NULL,
     xlab = NULL, ylab = NULL, xlim = NULL, ylim = NULL,
     padding_factor = 0.07, xgrid = FALSE, ygrid = FALSE, xaxes = FALSE,
     yaxes = FALSE, tools = c("pan", "wheel_zoom", "save"),
     theme = getOption("bokeh_theme"))
```

Arguments

lat	latitude where the map should be centered
lng	longitude where the map should be centered
zoom	initial zoom level to use when displaying the map
api_key	Google Maps API key
map_type	map type to use for the plot - one of "hybrid", "satellite", "roadmap", "terrain"
map_style	a json string of a Google Maps style - see gmap_style
width	figure width in pixels
height	figure width in pixels
title	a title to display above the plot. - "title" is also the prefix for a set of Text Properties, so you can set the font for the title with the parameter text_font.
xlab	label for x axis
ylab	label for y axis
xlim	the extent of the plotting area in the x-dimension (will be computed automatically if not specified).
ylim	the extent of the plotting area in the y-dimension (will be computed automatically if not specified).
padding_factor	if limits are not specified, by what factor should the extents of the data be padded
xgrid	whether to draw x axis grid lines
ygrid	whether to draw y axis grid lines
xaxes	where to put x axis, or FALSE if no x axis ticks / labels
yaxes	where to put y axis, or FALSE if no y axis ticks / labels

tools	character vector of interactivity tools options (acceptable values are: "pan", "wheel_zoom", "box_zoom", "resize", "crosshair", "box_select", "lasso_select", "reset", "save", "help"). Additionally, tool functions can be called on a figure to specify more control - see the "See Also" section below for a list of tool functions. If NULL, the toolbar will not be drawn. If "" the toolbar will be drawn but no tools will be added by default.
theme	an rbokeh theme to use

Note

This can be used in the same way as [figure](#), adding layers on top of the Google Map. There is an open issue documenting points appearing to sometimes be a few pixels off from their intended location. Google has its own terms of service for using Google Maps API and any use of rbokeh with Google Maps must be within Google's Terms of Service

See Also

[gmap_style](#)

Examples

```
# custom map style
gmap(lat = 40.74, lng = -73.95, zoom = 11,
      width = 600, height = 600,
      map_style = gmap_style("blue_water"))

## Not run:
gmap(title = "NYC taxi pickups January 2013",
      lat = 40.74, lng = -73.95, zoom = 11,
      map_type = "roadmap", width = 1000, height = 800) %>%
  ly_hexbin(nyctaxihex, alpha = 0.5,
            palette = "Spectral10", trans = log, inv = exp)

## End(Not run)
```

gmap_style

Get a Google Map Style

Description

Get a Google Map Style

Usage

```
gmap_style(name)
```

Arguments

name name of map style to retrieve (see details)

Details

This function provides Google Maps themes that can be passed to the `map_style` argument of `gmap`. Currently the most popular styles from <https://snazzymaps.com> are available. You can also visit this site or others to specify a custom `map_style`. Available styles are: "subtle_grayscale", "shades_of_grey", "blue_water", "pale_dawn", "blue_essence", "apple_mapsesque", "midnight_commander", "light_monochrome", "paper", "retro", "flat_map", "cool_grey".

See Also

[gmap](#)

Examples

```
# custom map style
gmap(lat = 40.74, lng = -73.95, zoom = 11,
     width = 600, height = 600,
     map_style = gmap_style("blue_water"))

## Not run:
gmap(title = "NYC taxi pickups January 2013",
     lat = 40.74, lng = -73.95, zoom = 11,
     map_type = "roadmap", width = 1000, height = 800) %>%
  ly_hexbin(nyctaxihex, alpha = 0.5,
           palette = "Spectral10", trans = log, inv = exp)

## End(Not run)
```

grid_plot

Create a Bokeh grid plot from a list of Bokeh figures

Description

Create a Bokeh grid plot from a list of Bokeh figures

Usage

```
grid_plot(figs, width = NULL, height = NULL, nrow = 1, ncol = 1,
         byrow = TRUE, xlim = NULL, ylim = NULL, logo = NULL,
         same_axes = FALSE, simplify_axes = TRUE, y_margin = NULL,
         x_margin = NULL, link_data = FALSE)
```

Arguments

<code>figs</code>	list of Bokeh figures - see details for what is acceptable
<code>width</code>	width of the entire grid plot in pixels - if NULL, the sum of the grid widths of columns will be used - if not NULL, the widths of the plots will be proportionately shrunk to meet the specified width
<code>height</code>	height of the entire grid plot in pixels - if NULL, the sum of the grid heights of rows will be used - if not NULL, the heights of the plots will be proportionately shrunk to meet the specified height
<code>nrow</code>	number of rows in the grid
<code>ncol</code>	number of columns in the grid
<code>byrow</code>	populate the grid by row according to the order of figure elements supplied in <code>params</code>
<code>xlim</code>	the extent of the plotting area in the x-dimension to be applied to every panel (original individual panel limits will be honored if not specified).
<code>ylim</code>	the extent of the plotting area in the y-dimension to be applied to every panel (original individual panel limits will be honored if not specified).
<code>logo</code>	('normal', 'grey') What version of the Bokeh logo to display on the toolbar. If set to NULL, no logo will be displayed.
<code>same_axes</code>	logical or vector of two logicals specifying whether the x and/or y axis limits should be the same for each plot in the grid
<code>simplify_axes</code>	logical or vector of logicals specifying whether to simply the x and/or y axes (only show the axes along the bottom and left sides of the grid) - only valid if <code>same_axes</code> is TRUE for the axis
<code>x_margin, y_margin</code>	specify the margin space in pixels to be left for axes when using <code>simplify_axes=TRUE</code>
<code>link_data</code>	logical - should an attempt be made to join the data sources of each plot for linked brushing? (see details)

Details

The `figs` parameter can either be a list of figures or a list of lists of figures. If the latter, the list structure will determine the layout, with each super-list of figures defining a single row of the grid. If the former, the parameters `nrow` and `ncol` and `byrow` are used to determine the layout. The grid is from top to bottom left to right.

If `link_data` is TRUE, then an effort will be made to link all data sources that are common among the different figures in the plot. Note that at this point, only data sources that are specified in the `data` argument to the different layer functions are checked.

Examples

```
idx <- split(1:150, iris$Species)
figs <- lapply(idx, function(x) {
  figure(width = 300, height = 300) %>%
    ly_points(Sepal.Length, Sepal.Width, data = iris[x, ],
```



```

    hover = list(Sepal.Length, Sepal.Width))
  })

  # 1 row, 3 columns
  grid_plot(figs)
  # specify xlim and ylim to be applied to all panels
  grid_plot(figs, xlim = c(4, 8), ylim = c(1.5, 4.5))
  # unnamed list will remove labels
  grid_plot(unname(figs))
  # 2 rows, 2 columns
  grid_plot(figs, nrow = 2)
  # x and y axis with same (and linked) limits
  grid_plot(figs, same_axes = TRUE)
  # x axis with same (and linked) limits
  grid_plot(figs, same_axes = c(TRUE, FALSE), nrow = 2)
  # x axis with same (and linked) limits and custom xlim
  grid_plot(figs, same_axes = c(TRUE, FALSE), xlim = c(5, 7), nrow = 2)
  # send lists instead of specifying nrow and ncol
  grid_plot(list(
    c(list(figs[[1]]), list(figs[[3]])),
    c(list(NULL), list(figs[[2]]))
  ))
  # a null entry will be skipped in the grid
  figs2 <- figs
  figs2[1] <- list(NULL)
  grid_plot(figs2, nrow = 2)
  # with themes
  grid_plot(figs) %>%
    theme_title(text_color = "red") %>%
    theme_plot(background_fill_color = "#E6E6E6",
      outline_line_color = "white") %>%
    theme_grid(c("x", "y"), grid_line_color = "white",
      minor_grid_line_color = "white",
      minor_grid_line_alpha = 0.4) %>%
    theme_axis(c("x", "y"), axis_line_color = "white",
      major_label_text_color = "#7F7F7F",
      major_tick_line_color = "#7F7F7F",
      minor_tick_line_alpha = 0, num_minor_ticks = 2)
  # themes again
  grid_plot(figs) %>%
    set_theme(bk_ggplot_theme)

  # link data across plots in the grid (try box_select tool)
  # (data sources must be the same)
  tools <- c("pan", "wheel_zoom", "box_zoom", "box_select", "reset")
  p1 <- figure(tools = tools, width = 500, height = 500) %>%
    ly_points(Sepal.Length, Sepal.Width, data = iris, color = Species)
  p2 <- figure(tools = tools, width = 500, height = 500) %>%
    ly_points(Petal.Length, Petal.Width, data = iris, color = Species)
  grid_plot(list(p1, p2), same_axes = TRUE, link_data = TRUE)

```

ly_abline	<i>Add an "abline" layer to a Bokeh figure</i>
-----------	--

Description

Draws one or more straight lines.

Usage

```
ly_abline(fig, a = NULL, b = NULL, v = NULL, h = NULL, coef = NULL,
          color = "black", alpha = NULL, width = 1, type = 1, legend = NULL,
          lname = NULL, lgroup = NULL, visible = TRUE, ...)
```

Arguments

fig	figure to modify
a, b	the intercept and slope of the line(s) to draw
v	the x value(s) for vertical lines
h	the y value(s) for horizontal lines
coef	a vector of length two giving the intercept and slope
color	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo'
alpha	transparency value for the line between 0 (transparent) and 1 (opaque)
width	stroke width in units of pixels
type	an integer between 1 and 6 matching the lty property in par or an array of integer pixel distances that describe the on-off pattern of dashing to use
legend	either a logical specifying not to plot a legend for this layer (FALSE) or a string indicating the name of the legend entry for this layer (note that when mapping plot attributes to variables in data, a legend is automatically created and does not need to be specified - see "Mapped plot attributes and legends" below)
lname	layer name
lgroup	layer group
visible	should the layer be visible?
...	additional parameters for fine control over line properties (see "Additional parameters" below)

Mapped plot attributes and legends

When specifying an input data frame for a layer through the data argument, columns of data can be used to specify various plot attributes such as color, etc. For example, with `ly_points(..., data = iris, color = Species)` the Species variable is used to determine how to color the points. Here, Species is "mapped" to the color attribute. Both continuous and categorical variables can be mapped. In the case of continuous variables, the range is cut into slices and attributes are applied to each interval. The mapping from the values of the variable to the actual plot attributes is determined based on the theme.

Additional parameters

line_join how path segments should be joined together 'miter' 'round' 'bevel'
line_cap how path segments should be terminated 'butt' 'round' 'square'
line_dash an integer between 1 and 6 matching the lty property in [par](#) or an array of integer pixel distances that
line_dash_offset the distance in pixels into the line_dash that the pattern should start from

See Also

Other layer functions: [ly_annular_wedge](#), [ly_annulus](#), [ly_arc](#), [ly_bar](#), [ly_bezier](#), [ly_boxplot](#), [ly_contour](#), [ly_crect](#), [ly_curve](#), [ly_density](#), [ly_hist](#), [ly_image_url](#), [ly_image](#), [ly_lines](#), [ly_map](#), [ly_multi_line](#), [ly_oval](#), [ly_patch](#), [ly_points](#), [ly_polygons](#), [ly_quadratic](#), [ly_quantile](#), [ly_ray](#), [ly_rect](#), [ly_segments](#), [ly_text](#), [ly_wedge](#)

Examples

```

# abline with mixed axes for h and v
figure() %>%
  ly_points(1:26, letters) %>%
  ly_abline(h = "j") %>%
  ly_abline(v = 10)

# multiple hv lines
figure() %>%
  ly_points(1:10) %>%
  ly_abline(v = 1:10) %>%
  ly_abline(h = 1:10)

# multiple ab lines
figure() %>%
  ly_points(0:10) %>%
  ly_abline(0, seq(0, 1, by = 0.1))

z <- lm(dist ~ speed, data = cars)
p <- figure() %>%
  ly_points(cars, hover = cars) %>%
  ly_lines(lowess(cars), legend = "lowess") %>%
  ly_abline(z, type = 2, legend = "lm", width = 2)
p

```

ly_annular_wedge *Add an "annular_wedge" layer to a Bokeh figure*

Description

Add an "annular_wedge" layer to a Bokeh figure

Usage

```
ly_annular_wedge(fig, x, y = NULL, data = figure_data(fig),
  inner_radius = 0.1, outer_radius = 0.3, start_angle = 0, end_angle = 2
  * pi, direction = "anticlock", color = NULL, alpha = 1, hover = NULL,
  url = NULL, legend = NULL, lname = NULL, lgroup = NULL,
  visible = TRUE, ...)
```

Arguments

fig	figure to modify
x	values or field name of center x coordinates
y	values or field name of center y coordinates
data	an optional data frame, providing the source for inputs x, y, and other glyph properties
inner_radius	values or field name of inner radii
outer_radius	values or field name of outer radii
start_angle	the angles to start the annular wedges, in radians, as measured from the horizontal
end_angle	the angles to end the annular wedges, in radians, as measured from the horizontal
direction	direction to turn between starting and ending angles ("anticlock", "clock")
color	color for the glyph - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo' - for glyphs with both fill and line properties, see "Handling color" below
alpha	the alpha transparency of the glyph between 0 (transparent) and 1 (opaque) - if glyph has both fill and color properties, see "Handling alpha" below
hover	a data frame of variables to be displayed when hovering over the glyph or a vector of variable names that can be found and extracted from the data argument
url	a string of URLs or a single string that references a variable name (via @var_name) that can be found and extracted from the data argument
legend	either a logical specifying not to plot a legend for this layer (FALSE) or a string indicating the name of the legend entry for this layer (note that when mapping plot attributes to variables in data, a legend is automatically created and does not need to be specified - see "Mapped plot attributes and legends" below)
lname	layer name
lgroup	layer group
visible	should the layer be visible?
...	additional parameters for fine control over fill and line properties (see "Additional parameters" below)

Handling color

The color parameter is a high-level plot attribute that provides default behavior for coloring glyphs.

- When using a glyph that only has line properties, this will be the color of the line.
- When using a glyph that has line and fill properties, this will be the color of the line and the fill, with the alpha level of the fill reduced by 50%.
- If full control over fill and line color is desired, the `fill_color` and `line_color` attributes can be specified explicitly and will override `color`.

When `color` is NULL and `fill_color` or `line_color` are not specified, the color will be chosen from the theme.

Handling alpha

The alpha is a high-level plot attribute that sets the transparency of the glyph being plotted.

- When using a glyph that only has line properties, this will be the alpha of the line.
- When using a glyph that has line and fill properties, this will be the alpha of the line and the alpha of the fill will be set to 50% of this value.
- Individual fill and line alpha can be specified with `fill_alpha` and `line_alpha` and will override alpha.

Mapped plot attributes and legends

When specifying an input data frame for a layer through the `data` argument, columns of data can be used to specify various plot attributes such as `color`, etc. For example, with `ly_points(..., data = iris, color = Species)` the `Species` variable is used to determine how to color the points. Here, `Species` is "mapped" to the `color` attribute. Both continuous and categorical variables can be mapped. In the case of continuous variables, the range is cut into slices and attributes are applied to each interval. The mapping from the values of the variable to the actual plot attributes is determined based on the theme.

Additional parameters

<code>fill_color</code>	color to use to fill the glyph with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. '#f00'
<code>fill_alpha</code>	transparency value between 0 (transparent) and 1 (opaque)
<code>line_color</code>	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. '#f00'
<code>line_width</code>	stroke width in units of pixels
<code>line_alpha</code>	transparency value between 0 (transparent) and 1 (opaque)
<code>line_join</code>	how path segments should be joined together 'miter' 'round' 'bevel'
<code>line_cap</code>	how path segments should be terminated 'butt' 'round' 'square'
<code>line_dash</code>	array of integer pixel distances that describe the on-off pattern of dashing to use
<code>line_dash_offset</code>	the distance in pixels into the <code>line_dash</code> that the pattern should start from

See Also

Other layer functions: [ly_abline](#), [ly_annulus](#), [ly_arc](#), [ly_bar](#), [ly_bezier](#), [ly_boxplot](#), [ly_contour](#), [ly_crect](#), [ly_curve](#), [ly_density](#), [ly_hist](#), [ly_image_url](#), [ly_image](#), [ly_lines](#), [ly_map](#), [ly_multi_line](#), [ly_oval](#), [ly_patch](#), [ly_points](#), [ly_polygons](#), [ly_quadratic](#), [ly_quantile](#), [ly_ray](#), [ly_rect](#), [ly_segments](#), [ly_text](#), [ly_wedge](#)

Examples

```
rescale <- function(x)
  (x - min(x)) / diff(range(x))
figure() %>%
  ly_annular_wedge(Sepal.Length, Sepal.Width, data = iris,
    end_angle = rescale(Petal.Length) * 2 * pi, color = Species,
    inner_radius = 0.1, outer_radius = 0.15, alpha = 0.5,
    hover = Species)
```

`ly_annulus`*Add an "annulus" layer to a Bokeh figure*

Description

Add an "annulus" layer to a Bokeh figure

Usage

```
ly_annulus(fig, x, y = NULL, data = figure_data(fig), inner_radius = 0.1,
  outer_radius = 0.2, color = NULL, alpha = 1, hover = NULL,
  url = NULL, legend = NULL, lname = NULL, lgroup = NULL,
  visible = TRUE, ...)
```

Arguments

<code>fig</code>	figure to modify
<code>x</code>	values or field name of center x coordinates
<code>y</code>	values or field name of center y coordinates
<code>data</code>	an optional data frame, providing the source for inputs x, y, and other glyph properties
<code>inner_radius</code>	values or field name of inner radii
<code>outer_radius</code>	values or field name of outer radii
<code>color</code>	color for the glyph - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo' - for glyphs with both fill and line properties, see "Handling color" below
<code>alpha</code>	the alpha transparency of the glyph between 0 (transparent) and 1 (opaque) - if glyph has both fill and color properties, see "Handling alpha" below

hover	a data frame of variables to be displayed when hovering over the glyph or a vector of variable names that can be found and extracted from the data argument
url	a string of URLs or a single string that references a variable name (via @var_name) that can be found and extracted from the data argument
legend	either a logical specifying not to plot a legend for this layer (FALSE) or a string indicating the name of the legend entry for this layer (note that when mapping plot attributes to variables in data, a legend is automatically created and does not need to be specified - see "Mapped plot attributes and legends" below)
lname	layer name
lgroup	layer group
visible	should the layer be visible?
...	additional parameters for fine control over fill and line properties (see "Additional parameters" below)

Handling color

The color parameter is a high-level plot attribute that provides default behavior for coloring glyphs.

- When using a glyph that only has line properties, this will be the color of the line.
- When using a glyph that has has line and fill properties, this will be the color of the line and the fill, with the alpha level of the fill reduced by 50%.
- If full control over fill and line color is desired, the fill_color and line_color attributes can be specified explicitly and will override color.

When color is NULL and fill_color or line_color are not specified, the color will be chosen from the theme.

Handling alpha

The alpha is a high-level plot attribute that sets the transparency of the glyph being plotted.

- When using a glyph that only has line properties, this will be the alpha of the line.
- When using a glyph that has has line and fill properties, this will be the alpha of the line and the alpha of the fill will be set to 50% of this value.
- Individual fill and line alpha can be specified with fill_alpha and line_alpha and will override alpha.

Mapped plot attributes and legends

When specifying an input data frame for a layer through the data argument, columns of data can be used to specify various plot attributes such as color, etc. For example, with `ly_points(..., data = iris, color = Species)` the Species variable is used to determine how to color the points. Here, Species is "mapped" to the color attribute. Both continuous and categorical variables can be mapped. In the case of continuous variables, the range is cut into slices and attributes are applied to each interval. The mapping from the values of the variable to the actual plot attributes is determined based on the theme.

Additional parameters

fill_color	color to use to fill the glyph with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. 'red'
fill_alpha	transparency value between 0 (transparent) and 1 (opaque)
line_color	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. 'red'
line_width	stroke width in units of pixels
line_alpha	transparency value between 0 (transparent) and 1 (opaque)
line_join	how path segments should be joined together 'miter' 'round' 'bevel'
line_cap	how path segments should be terminated 'butt' 'round' 'square'
line_dash	array of integer pixel distances that describe the on-off pattern of dashing to use
line_dash_offset	the distance in pixels into the line_dash that the pattern should start from

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_arc](#), [ly_bar](#), [ly_bezier](#), [ly_boxplot](#), [ly_contour](#), [ly_crect](#), [ly_curve](#), [ly_density](#), [ly_hist](#), [ly_image_url](#), [ly_image](#), [ly_lines](#), [ly_map](#), [ly_multi_line](#), [ly_oval](#), [ly_patch](#), [ly_points](#), [ly_polygons](#), [ly_quadratic](#), [ly_quantile](#), [ly_ray](#), [ly_rect](#), [ly_segments](#), [ly_text](#), [ly_wedge](#)

Examples

```
rescale <- function(x)
  (x - min(x)) / diff(range(x))
figure() %>%
  ly_annulus(Sepal.Length, Sepal.Width, data = iris,
    color = Species, hover = Species, alpha = 0.5,
    outer_radius = rescale(Petal.Length) * 0.3,
    inner_radius = rescale(Petal.Length) * 0.1)
```

 ly_arc

Add an "arc" layer to a Bokeh figure

Description

Add an "arc" layer to a Bokeh figure

Usage

```
ly_arc(fig, x, y = NULL, data = figure_data(fig), color = NULL,
  alpha = 1, width = 2, type = 1, radius = 0.2, start_angle = 0,
  end_angle = 2 * pi, direction = "anticlock", legend = NULL,
  lname = NULL, lgroup = NULL, visible = TRUE, ...)
```


Arguments

fig	figure to modify
x	values or field name of center x coordinates
y	values or field name of center y coordinates
data	an optional data frame, providing the source for inputs x, y, and other glyph properties
color	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo'
alpha	transparency value for the line between 0 (transparent) and 1 (opaque)
width	stroke width in units of pixels
type	an integer between 1 and 6 matching the lty property in par or an array of integer pixel distances that describe the on-off pattern of dashing to use
radius	values or field name of arc radii
start_angle	values or field name of starting angles
end_angle	values or field name of ending angles
direction	direction to turn between starting and ending angles ("anticlock", "clock")
legend	either a logical specifying not to plot a legend for this layer (FALSE) or a string indicating the name of the legend entry for this layer (note that when mapping plot attributes to variables in data, a legend is automatically created and does not need to be specified - see "Mapped plot attributes and legends" below)
lname	layer name
lgroup	layer group
visible	should the layer be visible?
...	additional parameters for fine control over line properties (see "Additional parameters" below)

Mapped plot attributes and legends

When specifying an input data frame for a layer through the data argument, columns of data can be used to specify various plot attributes such as color, etc. For example, with `ly_points(..., data = iris, color = Species)` the Species variable is used to determine how to color the points. Here, Species is "mapped" to the color attribute. Both continuous and categorical variables can be mapped. In the case of continuous variables, the range is cut into slices and attributes are applied to each interval. The mapping from the values of the variable to the actual plot attributes is determined based on the theme.

Additional parameters

line_join	how path segments should be joined together 'miter' 'round' 'bevel'
line_cap	how path segments should be terminated 'butt' 'round' 'square'
line_dash	an integer between 1 and 6 matching the lty property in par or an array of integer pixel distances that
line_dash_offset	the distance in pixels into the line_dash that the pattern should start from

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_annulus](#), [ly_bar](#), [ly_bezier](#), [ly_boxplot](#), [ly_contour](#), [ly_crect](#), [ly_curve](#), [ly_density](#), [ly_hist](#), [ly_image_url](#), [ly_image](#), [ly_lines](#), [ly_map](#), [ly_multi_line](#), [ly_oval](#), [ly_patch](#), [ly_points](#), [ly_polygons](#), [ly_quadratic](#), [ly_quantile](#), [ly_ray](#), [ly_rect](#), [ly_segments](#), [ly_text](#), [ly_wedge](#)

Examples

```
rescale <- function(x)
  (x - min(x)) / diff(range(x))
figure() %>%
  ly_arc(Sepal.Length, Sepal.Width, data = iris,
         end_angle = rescale(Petal.Length) * 2 * pi, color = Species,
         alpha = 0.5)
```

ly_bar*Add a "barchart" layer to a Bokeh figure*

Description

Draws a bar chart

Usage

```
ly_bar(fig, x = NULL, y = NULL, data = figure_data(fig), color = NULL,
       alpha = 1, position = c("stack", "fill", "dodge"), width = 0.9,
       hover = FALSE, origin = NULL, breaks = NULL, right = FALSE,
       binwidth = NULL, lname = NULL, lgroup = NULL, legend = NULL,
       visible = TRUE, ...)
```

Arguments

fig	figure to modify
x	values or field name for x variable, or if NULL, x-axis will be counts of y
y	values or field name for y variable, or if NULL, y-axis will be counts of x
data	an optional data frame, providing the source for inputs x, y, and color properties
color	color for the glyph - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo' - for glyphs with both fill and line properties, see "Handling color" below
alpha	the alpha transparency of the glyph between 0 (transparent) and 1 (opaque) - if glyph has both fill and color properties, see "Handling alpha" below
position	either "stack", "fill", or "dodge" (see details)
width	width of each bar, a value between 0 (no width) and 1 (full width)

hover	logical - should a hover tool be added to show the value of each bar?
origin, breaks, right, binwidth	parameters to be used for binning x when it is continuous (not yet implemented)
lname	layer name
lgroup	layer group
legend	either a logical specifying not to plot a legend for this layer (FALSE) or a string indicating the name of the legend entry for this layer (note that when mapping plot attributes to variables in data, a legend is automatically created and does not need to be specified - see "Mapped plot attributes and legends" below)
visible	should the layer be visible?
...	additional parameters for fine control over fill and line properties (see "Additional parameters" below)

Details

This function expects one of either x or y to be categorical and the other to be numeric or NULL. The numeric variable is summed for each categorical variable and bars are plotted. If no numeric variable is supplied, the unique values of the categorical variable will be tabulated. Within each categorical variable, if color maps to another grouping variable then the bars are split up. In this case, there are three ways to display the bars with the position argument. The default, "stack" will stack the bars. The "fill" choice will show the relative proportion for each group within each categorical variable level, stacking the bars. The "dodge" choice will plot the bars for each level of the categorical variable side by side.

Handling color

The color parameter is a high-level plot attribute that provides default behavior for coloring glyphs.

- When using a glyph that only has line properties, this will be the color of the line.
- When using a glyph that has line and fill properties, this will be the color of the line and the fill, with the alpha level of the fill reduced by 50%.
- If full control over fill and line color is desired, the fill_color and line_color attributes can be specified explicitly and will override color.

When color is NULL and fill_color or line_color are not specified, the color will be chosen from the theme.

Handling alpha

The alpha is a high-level plot attribute that sets the transparency of the glyph being plotted.

- When using a glyph that only has line properties, this will be the alpha of the line.
- When using a glyph that has line and fill properties, this will be the alpha of the line and the alpha of the fill will be set to 50% of this value.
- Individual fill and line alpha can be specified with fill_alpha and line_alpha and will override alpha.

Mapped plot attributes and legends

When specifying an input data frame for a layer through the `data` argument, columns of data can be used to specify various plot attributes such as `color`, etc. For example, with `ly_points(..., data = iris, color = Species)` the `Species` variable is used to determine how to color the points. Here, `Species` is "mapped" to the `color` attribute. Both continuous and categorical variables can be mapped. In the case of continuous variables, the range is cut into slices and attributes are applied to each interval. The mapping from the values of the variable to the actual plot attributes is determined based on the theme.

Additional parameters

<code>fill_color</code>	color to use to fill the glyph with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. 'red'
<code>fill_alpha</code>	transparency value between 0 (transparent) and 1 (opaque)
<code>line_color</code>	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. 'red'
<code>line_width</code>	stroke width in units of pixels
<code>line_alpha</code>	transparency value between 0 (transparent) and 1 (opaque)
<code>line_join</code>	how path segments should be joined together 'miter' 'round' 'bevel'
<code>line_cap</code>	how path segments should be terminated 'butt' 'round' 'square'
<code>line_dash</code>	array of integer pixel distances that describe the on-off pattern of dashing to use
<code>line_dash_offset</code>	the distance in pixels into the <code>line_dash</code> that the pattern should start from

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_annulus](#), [ly_arc](#), [ly_bezier](#), [ly_boxplot](#), [ly_contour](#), [ly_crect](#), [ly_curve](#), [ly_density](#), [ly_hist](#), [ly_image_url](#), [ly_image](#), [ly_lines](#), [ly_map](#), [ly_multi_line](#), [ly_oval](#), [ly_patch](#), [ly_points](#), [ly_polygons](#), [ly_quadratic](#), [ly_quantile](#), [ly_ray](#), [ly_rect](#), [ly_segments](#), [ly_text](#), [ly_wedge](#)

Examples

```
# count of variety
figure() %>%
  ly_bar(variety, data = lattice::barley) %>%
  theme_axis("x", major_label_orientation = 90)

# total yield per variety
figure() %>%
  ly_bar(variety, yield, data = lattice::barley, hover = TRUE) %>%
  theme_axis("x", major_label_orientation = 90)

# swap axes and add hover
figure() %>%
  ly_bar(yield, variety, data = lattice::barley, hover = TRUE)

# stack by year
figure() %>%
  ly_bar(variety, yield, color = year, data = lattice::barley, hover = TRUE) %>%
```

```

    theme_axis("x", major_label_orientation = 90)

# proportional bars
figure() %>%
  ly_bar(variety, yield, color = year,
         data = lattice::barley, position = "fill", width = 1) %>%
  theme_axis("x", major_label_orientation = 90) %>%
  set_palette(discrete_color = pal_color(c("red", "blue")))

# swap axes and use different palette
figure() %>%
  ly_bar(yield, variety, color = year,
         data = lattice::barley, position = "fill") %>%
  set_palette(discrete_color = pal_color(c("red", "blue")))

# side by side bars
figure() %>%
  ly_bar(variety, yield, color = year,
         data = lattice::barley, position = "dodge") %>%
  theme_axis("x", major_label_orientation = 90)

# use a different theme
figure() %>%
  ly_bar(variety, yield, color = year,
         data = lattice::barley, position = "dodge") %>%
  theme_axis("x", major_label_orientation = 90)

```

 ly_bezier

 Add a "bezier" layer to a Bokeh figure

Description

Draws Bezier curves with the given starting, ending, and control points.

Usage

```

ly_bezier(fig, x0, y0, x1, y1, cx0, cy0, cx1, cy1, data = figure_data(fig),
          color = "black", alpha = 1, width = 1, type = 1, legend = NULL,
          lname = NULL, lgroup = NULL, visible = TRUE, ...)

```

Arguments

fig	figure to modify
x0	values or field name of starting x coordinates
y0	values or field name of starting y coordinates
x1	values or field name of ending x coordinates
y1	values or field name of ending y coordinates

cx0	values or field name of first control point x coordinates
cy0	values or field name of first control point y coordinates
cx1	values or field name of second control point x coordinates
cy1	values or field name of second control point y coordinates
data	an optional data frame, providing the source for start, end, and control point inputs, as well as other glyph properties
color	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo'
alpha	transparency value for the line between 0 (transparent) and 1 (opaque)
width	stroke width in units of pixels
type	an integer between 1 and 6 matching the lty property in par or an array of integer pixel distances that describe the on-off pattern of dashing to use
legend	either a logical specifying not to plot a legend for this layer (FALSE) or a string indicating the name of the legend entry for this layer (note that when mapping plot attributes to variables in data, a legend is automatically created and does not need to be specified - see "Mapped plot attributes and legends" below)
lname	layer name
lgroup	layer group
visible	should the layer be visible?
...	additional parameters for fine control over line properties (see "Additional parameters" below)

Mapped plot attributes and legends

When specifying an input data frame for a layer through the data argument, columns of data can be used to specify various plot attributes such as color, etc. For example, with `ly_points(..., data = iris, color = Species)` the Species variable is used to determine how to color the points. Here, Species is "mapped" to the color attribute. Both continuous and categorical variables can be mapped. In the case of continuous variables, the range is cut into slices and attributes are applied to each interval. The mapping from the values of the variable to the actual plot attributes is determined based on the theme.

Additional parameters

line_join	how path segments should be joined together 'miter' 'round' 'bevel'
line_cap	how path segments should be terminated 'butt' 'round' 'square'
line_dash	an integer between 1 and 6 matching the lty property in par or an array of integer pixel distances that
line_dash_offset	the distance in pixels into the line_dash that the pattern should start from

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_annulus](#), [ly_arc](#), [ly_bar](#), [ly_boxplot](#), [ly_contour](#), [ly_crect](#), [ly_curve](#), [ly_density](#), [ly_hist](#), [ly_image_url](#), [ly_image](#), [ly_lines](#),

[ly_map](#), [ly_multi_line](#), [ly_oval](#), [ly_patch](#), [ly_points](#), [ly_polygons](#), [ly_quadratic](#), [ly_quantile](#), [ly_ray](#), [ly_rect](#), [ly_segments](#), [ly_text](#), [ly_wedge](#)

ly_boxplot	<i>Add a "boxplot" layer to a Bokeh figure</i>
------------	--

Description

Add a "boxplot" layer to a Bokeh figure

Usage

```
ly_boxplot(fig, x, y = NULL, data = figure_data(fig), width = 0.9,
  coef = 1.5, color = "blue", alpha = 1, outlier_glyph = 1,
  outlier_size = 10, lname = NULL, lgroup = NULL, visible = TRUE, ...)
```

Arguments

fig	figure to modify
x	either a numeric vector or a factor
y	either a numeric vector or a factor
data	an optional data frame, providing the source for x and y
width	width of each box, a value between 0 (no width) and 1 (full width)
coef	see boxplot.stats
color	color for the glyph - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo' - for glyphs with both fill and line properties, see "Handling color" below
alpha	the alpha transparency of the glyph between 0 (transparent) and 1 (opaque) - if glyph has both fill and color properties, see "Handling alpha" below
outlier_glyph	the glyph used to plot the outliers. If set to NA, no outlier points are plotted. Run <code>point_types()</code> for possible values.
outlier_size	the size of the glyph used to plot outliers. If set to NA, no outlier points are plotted.
lname	layer name
lgroup	layer group
visible	should the layer be visible?
...	additional parameters for fine control over fill and line properties (see "Additional parameters" below)

Handling color

The color parameter is a high-level plot attribute that provides default behavior for coloring glyphs.

- When using a glyph that only has line properties, this will be the color of the line.
- When using a glyph that has line and fill properties, this will be the color of the line and the fill, with the alpha level of the fill reduced by 50%.
- If full control over fill and line color is desired, the `fill_color` and `line_color` attributes can be specified explicitly and will override `color`.

When `color` is NULL and `fill_color` or `line_color` are not specified, the color will be chosen from the theme.

Handling alpha

The alpha is a high-level plot attribute that sets the transparency of the glyph being plotted.

- When using a glyph that only has line properties, this will be the alpha of the line.
- When using a glyph that has line and fill properties, this will be the alpha of the line and the alpha of the fill will be set to 50% of this value.
- Individual fill and line alpha can be specified with `fill_alpha` and `line_alpha` and will override alpha.

Additional parameters

<code>fill_color</code>	color to use to fill the glyph with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. 'red'
<code>fill_alpha</code>	transparency value between 0 (transparent) and 1 (opaque)
<code>line_color</code>	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. 'red'
<code>line_width</code>	stroke width in units of pixels
<code>line_alpha</code>	transparency value between 0 (transparent) and 1 (opaque)
<code>line_join</code>	how path segments should be joined together 'miter' 'round' 'bevel'
<code>line_cap</code>	how path segments should be terminated 'butt' 'round' 'square'
<code>line_dash</code>	array of integer pixel distances that describe the on-off pattern of dashing to use
<code>line_dash_offset</code>	the distance in pixels into the <code>line_dash</code> that the pattern should start from

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_annulus](#), [ly_arc](#), [ly_bar](#), [ly_bezier](#), [ly_contour](#), [ly_crect](#), [ly_curve](#), [ly_density](#), [ly_hist](#), [ly_image_url](#), [ly_image](#), [ly_lines](#), [ly_map](#), [ly_multi_line](#), [ly_oval](#), [ly_patch](#), [ly_points](#), [ly_polygons](#), [ly_quadratic](#), [ly_quantile](#), [ly_ray](#), [ly_rect](#), [ly_segments](#), [ly_text](#), [ly_wedge](#)

Examples

```
figure(ylab = "Height (inches)", width = 600) %>%
  ly_boxplot(voice.part, height, data = lattice::singer)
```


ly_contour

*Add a "contour" layer to a Bokeh figure***Description**

Computes and draws contour lines.

Usage

```
ly_contour(fig, z, x = seq(0, 1, length.out = nrow(z)), y = seq(0, 1,
  length.out = ncol(z)), nlevels = 10, levels = pretty(range(z, na.rm =
  TRUE), nlevels), color = "black", alpha = 1, width = 1, type = 1,
  lname = NULL, lgroup = NULL, visible = TRUE, ...)
```

Arguments

fig	figure to modify
z	a matrix containing the values to compute contour lines for
x, y	locations of grid lines at which the values in image are measured (see contourLines)
nlevels, levels	parameters sent to contourLines)
color	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo'
alpha	transparency value for the line between 0 (transparent) and 1 (opaque)
width	stroke width in units of pixels
type	an integer between 1 and 6 matching the lty property in par or an array of integer pixel distances that describe the on-off pattern of dashing to use
lname	layer name
lgroup	layer group
visible	should the layer be visible?
...	additional parameters for fine control over line properties (see "Additional parameters" below)

Additional parameters

line_join	how path segments should be joined together 'miter' 'round' 'bevel'
line_cap	how path segments should be terminated 'butt' 'round' 'square'
line_dash	an integer between 1 and 6 matching the lty property in par or an array of integer pixel distances that
line_dash_offset	the distance in pixels into the line_dash that the pattern should start from

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_annulus](#), [ly_arc](#), [ly_bar](#), [ly_bezier](#), [ly_boxplot](#), [ly_crect](#), [ly_curve](#), [ly_density](#), [ly_hist](#), [ly_image_url](#), [ly_image](#), [ly_lines](#), [ly_map](#), [ly_multi_line](#), [ly_oval](#), [ly_patch](#), [ly_points](#), [ly_polygons](#), [ly_quadratic](#), [ly_quantile](#), [ly_ray](#), [ly_rect](#), [ly_segments](#), [ly_text](#), [ly_wedge](#)

Examples

```
p <- figure(xlim = c(0, 1), ylim = c(0, 1), title = "Volcano") %>%
  ly_image(volcano) %>%
  ly_contour(volcano)
p
```

 ly_crect

 Add a "crect" (centered rectangle) layer to a Bokeh figure

Description

Add a "crect" (centered rectangle) layer to a Bokeh figure

Usage

```
ly_crect(fig, x, y = NULL, data = figure_data(fig), width = 1,
  height = 1, angle = 0, dilate = FALSE, color = NULL, alpha = 1,
  hover = NULL, url = NULL, legend = NULL, lname = NULL,
  lgroup = NULL, visible = TRUE, ...)
```

Arguments

fig	figure to modify
x	values or field name of center x coordinates
y	values or field name of center y coordinates
data	an optional data frame, providing the source for inputs xleft, ybottom, xright, ytop, and other glyph properties
width	values or field name of widths
height	values or field name of heights
angle	values or field name of rotation angles
dilate	logical - whether to dilate pixel distance computations when drawing
color	color for the glyph - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo' - for glyphs with both fill and line properties, see "Handling color" below
alpha	the alpha transparency of the glyph between 0 (transparent) and 1 (opaque) - if glyph has both fill and color properties, see "Handling alpha" below

hover	a data frame of variables to be displayed when hovering over the glyph or a vector of variable names that can be found and extracted from the data argument
url	a string of URLs or a single string that references a variable name (via @var_name) that can be found and extracted from the data argument
legend	either a logical specifying not to plot a legend for this layer (FALSE) or a string indicating the name of the legend entry for this layer (note that when mapping plot attributes to variables in data, a legend is automatically created and does not need to be specified - see "Mapped plot attributes and legends" below)
lname	layer name
lgroup	layer group
visible	should the layer be visible?
...	additional parameters for fine control over fill and line properties (see "Additional parameters" below)

Handling color

The color parameter is a high-level plot attribute that provides default behavior for coloring glyphs.

- When using a glyph that only has line properties, this will be the color of the line.
- When using a glyph that has has line and fill properties, this will be the color of the line and the fill, with the alpha level of the fill reduced by 50%.
- If full control over fill and line color is desired, the fill_color and line_color attributes can be specified explicitly and will override color.

When color is NULL and fill_color or line_color are not specified, the color will be chosen from the theme.

Handling alpha

The alpha is a high-level plot attribute that sets the transparency of the glyph being plotted.

- When using a glyph that only has line properties, this will be the alpha of the line.
- When using a glyph that has has line and fill properties, this will be the alpha of the line and the alpha of the fill will be set to 50% of this value.
- Individual fill and line alpha can be specified with fill_alpha and line_alpha and will override alpha.

Mapped plot attributes and legends

When specifying an input data frame for a layer through the data argument, columns of data can be used to specify various plot attributes such as color, etc. For example, with `ly_points(..., data = iris, color = Species)` the Species variable is used to determine how to color the points. Here, Species is "mapped" to the color attribute. Both continuous and categorical variables can be mapped. In the case of continuous variables, the range is cut into slices and attributes are applied to each interval. The mapping from the values of the variable to the actual plot attributes is determined based on the theme.

Additional parameters

fill_color	color to use to fill the glyph with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. 'red'
fill_alpha	transparency value between 0 (transparent) and 1 (opaque)
line_color	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. 'red'
line_width	stroke width in units of pixels
line_alpha	transparency value between 0 (transparent) and 1 (opaque)
line_join	how path segments should be joined together 'miter' 'round' 'bevel'
line_cap	how path segments should be terminated 'butt' 'round' 'square'
line_dash	array of integer pixel distances that describe the on-off pattern of dashing to use
line_dash_offset	the distance in pixels into the line_dash that the pattern should start from

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_annulus](#), [ly_arc](#), [ly_bar](#), [ly_bezier](#), [ly_boxplot](#), [ly_contour](#), [ly_curve](#), [ly_density](#), [ly_hist](#), [ly_image_url](#), [ly_image](#), [ly_lines](#), [ly_map](#), [ly_multi_line](#), [ly_oval](#), [ly_patch](#), [ly_points](#), [ly_polygons](#), [ly_quadratic](#), [ly_quantile](#), [ly_ray](#), [ly_rect](#), [ly_segments](#), [ly_text](#), [ly_wedge](#)

Examples

```
# prepare data
elements <- subset(elements, !is.na(group))
elements$group <- as.character(elements$group)
elements$period <- as.character(elements$period)

# add colors for groups
metals <- c("alkali metal", "alkaline earth metal", "halogen",
  "metal", "metalloid", "noble gas", "nonmetal", "transition metal")
colors <- c("#a6cee3", "#1f78b4", "#fdbf6f", "#b2df8a", "#33a02c",
  "#bbbb88", "#baa2a6", "#e08e79")
elements$color <- colors[match(elements$metal, metals)]
elements$type <- elements$metal

# make coordinates for labels
elements$symx <- paste(elements$group, ":0.1", sep = "")
elements$numbery <- paste(elements$period, ":0.8", sep = "")
elements$massy <- paste(elements$period, ":0.15", sep = "")
elements$namey <- paste(elements$period, ":0.3", sep = "")

# create figure
p <- figure(title = "Periodic Table", tools = "",
  ylim = as.character(c(7:1)), xlim = as.character(1:18),
  xgrid = FALSE, ygrid = FALSE, xlab = "", ylab = "",
  height = 600, width = 1200) %>%

# plot rectangles
ly_crect(group, period, data = elements, 0.9, 0.9,
  fill_color = color, line_color = color, fill_alpha = 0.6,
  hover = list(name, atomic.number, type, atomic.mass,
```

```

        electronic.configuration)) %>%

# add symbol text
ly_text(symx, period, text = symbol, data = elements,
        font_style = "bold", font_size = "15pt",
        align = "left", baseline = "middle") %>%

# add atomic number text
ly_text(symx, numbery, text = atomic.number, data = elements,
        font_size = "9pt", align = "left", baseline = "middle") %>%

# add name text
ly_text(symx, namey, text = name, data = elements,
        font_size = "6pt", align = "left", baseline = "middle") %>%

# add atomic mass text
ly_text(symx, massy, text = atomic.mass, data = elements,
        font_size = "6pt", align = "left", baseline = "middle")

p

```

ly_curve

Add a "curve" layer to a Bokeh figure

Description

Draws a curve corresponding to a function over the interval [from, to].

Usage

```

ly_curve(fig, expr, from = NULL, to = NULL, n = 101, color = "black",
        alpha = 1, width = 1, type = 1, legend = NULL, lname = NULL,
        lgroup = NULL, visible = TRUE, ...)

```

Arguments

fig	figure to modify
expr, from, to, n	parameters sent to curve
color	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo'
alpha	transparency value for the line between 0 (transparent) and 1 (opaque)
width	stroke width in units of pixels
type	an integer between 1 and 6 matching the lty property in par or an array of integer pixel distances that describe the on-off pattern of dashing to use

legend	either a logical specifying not to plot a legend for this layer (FALSE) or a string indicating the name of the legend entry for this layer (note that when mapping plot attributes to variables in data, a legend is automatically created and does not need to be specified - see "Mapped plot attributes and legends" below)
lname	layer name
lgroup	layer group
visible	should the layer be visible?
...	additional parameters for fine control over line properties (see "Additional parameters" below)

Mapped plot attributes and legends

When specifying an input data frame for a layer through the data argument, columns of data can be used to specify various plot attributes such as color, etc. For example, with `ly_points(..., data = iris, color = Species)` the Species variable is used to determine how to color the points. Here, Species is "mapped" to the color attribute. Both continuous and categorical variables can be mapped. In the case of continuous variables, the range is cut into slices and attributes are applied to each interval. The mapping from the values of the variable to the actual plot attributes is determined based on the theme.

Additional parameters

line_join	how path segments should be joined together 'miter' 'round' 'bevel'
line_cap	how path segments should be terminated 'butt' 'round' 'square'
line_dash	an integer between 1 and 6 matching the lty property in par or an array of integer pixel distances that
line_dash_offset	the distance in pixels into the line_dash that the pattern should start from

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_annulus](#), [ly_arc](#), [ly_bar](#), [ly_bezier](#), [ly_boxplot](#), [ly_contour](#), [ly_crect](#), [ly_density](#), [ly_hist](#), [ly_image_url](#), [ly_image](#), [ly_lines](#), [ly_map](#), [ly_multi_line](#), [ly_oval](#), [ly_patch](#), [ly_points](#), [ly_polygons](#), [ly_quadratic](#), [ly_quantile](#), [ly_ray](#), [ly_rect](#), [ly_segments](#), [ly_text](#), [ly_wedge](#)

Examples

```
chippy <- function(x) sin(cos(x))*exp(-x/2)
figure(width = 800) %>%
  ly_curve(chippy, -8, 7, n = 2001)
```

ly_density	Add a "density" layer to a Bokeh figure
------------	---

Description

Draws a kernel density estimate

Usage

```
ly_density(fig, x, data = figure_data(fig), bw = "nrd0", adjust = 1,
  kernel = c("gaussian", "epanechnikov", "rectangular", "triangular",
    "biweight", "cosine", "optcosine"), weights = NULL, window = kernel,
  n = 512, cut = 3, na.rm = FALSE, color = "black", alpha = 1,
  width = 1, type = 1, legend = NULL, lname = NULL, lgroup = NULL,
  visible = TRUE, ...)
```

Arguments

fig	figure to modify
x, bw, adjust, kernel, weights, window, n, cut, na.rm	parameters passed to density
data	an optional data frame, providing the source for x
color	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo'
alpha	transparency value for the line between 0 (transparent) and 1 (opaque)
width	stroke width in units of pixels
type	an integer between 1 and 6 matching the lty property in par or an array of integer pixel distances that describe the on-off pattern of dashing to use
legend	text to display in the legend entry for the density line
lname	layer name
lgroup	layer group
visible	should the layer be visible?
...	additional parameters for fine control over line properties (see "Additional parameters" below)

Additional parameters

line_join	how path segments should be joined together 'miter' 'round' 'bevel'
line_cap	how path segments should be terminated 'butt' 'round' 'square'
line_dash	an integer between 1 and 6 matching the lty property in par or an array of integer pixel distances that
line_dash_offset	the distance in pixels into the line_dash that the pattern should start from

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_annulus](#), [ly_arc](#), [ly_bar](#), [ly_bezier](#), [ly_boxplot](#), [ly_contour](#), [ly_crect](#), [ly_curve](#), [ly_hist](#), [ly_image_url](#), [ly_image](#), [ly_lines](#), [ly_map](#), [ly_multi_line](#), [ly_oval](#), [ly_patch](#), [ly_points](#), [ly_polygons](#), [ly_quadratic](#), [ly_quantile](#), [ly_ray](#), [ly_rect](#), [ly_segments](#), [ly_text](#), [ly_wedge](#)

Examples

```
h <- figure(width = 600, height = 400) %>%
  ly_hist(eruptions, data = faithful, breaks = 40, freq = FALSE) %>%
  ly_density(eruptions, data = faithful)
h
```

`ly_hexbin`*Add a "hexbin" layer to a Bokeh figure*

Description

Add a "hexbin" layer to a Bokeh figure

Usage

```
ly_hexbin(fig, x, y = NULL, data = figure_data(fig), xbins = 30,
  shape = 1, xbnds = NULL, ybnds = NULL, style = "colorscale",
  trans = NULL, inv = NULL, lname = NULL, palette = "RdYlGn11",
  line = FALSE, alpha = 1, hover = TRUE, visible = TRUE)
```

Arguments

<code>fig</code>	figure to modify
<code>x</code>	values or field name of center x coordinates to be binned
<code>y</code>	values or field name of center y coordinates to be binned
<code>data</code>	an optional data frame, providing the source for x and y
<code>xbins, shape, xbnds, ybnds</code>	parameters passed to hexbin
<code>style</code>	type of plotting for hexbins (see grid.hexagons) - "colorramp" and "lattice" are currently supported
<code>trans, inv</code>	transformation and inverse transformation function for the bin counts
<code>lname</code>	layer name
<code>palette</code>	name of color palette to use for color ramp (see here for acceptable values)
<code>line</code>	logical - should hexagons have an outline?
<code>alpha</code>	the alpha transparency of the hexagons between 0 (transparent) and 1 (opaque)
<code>hover</code>	logical - should a hover tool be added to show the count in each hexagon?
<code>visible</code>	should the layer be visible?

Examples

```
figure() %>% ly_hexbin(rnorm(10000), rnorm(10000))
```

ly_hist	<i>Add a "hist" layer to a Bokeh figure</i>
---------	---

Description

Draws a histogram

Usage

```
ly_hist(fig, x, data = figure_data(fig), breaks = "Sturges", freq = TRUE,
  include.lowest = TRUE, right = TRUE, color = NULL, alpha = 1,
  lname = NULL, lgroup = NULL, visible = TRUE, ...)
```

Arguments

fig	figure to modify
x	either a vector to be passed to hist or an object of class "histogram"
data	an optional data frame, providing the source for x
breaks, freq, include.lowest, right	parameters passed to hist
color	color for the glyph - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo' - for glyphs with both fill and line properties, see "Handling color" below
alpha	the alpha transparency of the glyph between 0 (transparent) and 1 (opaque) - if glyph has both fill and color properties, see "Handling alpha" below
lname	layer name
lgroup	layer group
visible	should the layer be visible?
...	additional parameters for fine control over fill and line properties (see "Additional parameters" below)

Handling color

The color parameter is a high-level plot attribute that provides default behavior for coloring glyphs.

- When using a glyph that only has line properties, this will be the color of the line.
- When using a glyph that has line and fill properties, this will be the color of the line and the fill, with the alpha level of the fill reduced by 50%.
- If full control over fill and line color is desired, the `fill_color` and `line_color` attributes can be specified explicitly and will override color.

When color is NULL and `fill_color` or `line_color` are not specified, the color will be chosen from the theme.

Handling alpha

The alpha is a high-level plot attribute that sets the transparency of the glyph being plotted.

- When using a glyph that only has line properties, this will be the alpha of the line.
- When using a glyph that has line and fill properties, this will be the alpha of the line and the alpha of the fill will be set to 50% of this value.
- Individual fill and line alpha can be specified with `fill_alpha` and `line_alpha` and will override alpha.

Additional parameters

<code>fill_color</code>	color to use to fill the glyph with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. 'red'
<code>fill_alpha</code>	transparency value between 0 (transparent) and 1 (opaque)
<code>line_color</code>	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. 'red'
<code>line_width</code>	stroke width in units of pixels
<code>line_alpha</code>	transparency value between 0 (transparent) and 1 (opaque)
<code>line_join</code>	how path segments should be joined together 'miter' 'round' 'bevel'
<code>line_cap</code>	how path segments should be terminated 'butt' 'round' 'square'
<code>line_dash</code>	array of integer pixel distances that describe the on-off pattern of dashing to use
<code>line_dash_offset</code>	the distance in pixels into the <code>line_dash</code> that the pattern should start from

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_annulus](#), [ly_arc](#), [ly_bar](#), [ly_bezier](#), [ly_boxplot](#), [ly_contour](#), [ly_crect](#), [ly_curve](#), [ly_density](#), [ly_image_url](#), [ly_image](#), [ly_lines](#), [ly_map](#), [ly_multi_line](#), [ly_oval](#), [ly_patch](#), [ly_points](#), [ly_polygons](#), [ly_quadratic](#), [ly_quantile](#), [ly_ray](#), [ly_rect](#), [ly_segments](#), [ly_text](#), [ly_wedge](#)

Examples

```
h <- figure(width = 600, height = 400) %>%
  ly_hist(eruptions, data = faithful, breaks = 40, freq = FALSE) %>%
  ly_density(eruptions, data = faithful)
h
```

ly_image

Add an "image" layer to a Bokeh figure

Description

Draws a grid of rectangles with colors corresponding to the values in z

Usage

```
ly_image(fig, z, rows, byrow = TRUE, x = 0, y = 0, dw = 1, dh = 1,  
         palette = "Spectral10", dilate = FALSE, lname = NULL, lgroup = NULL,  
         visible = TRUE)
```

Arguments

fig	figure to modify
z	matrix or vector of image values
rows	if z is a vector, how many rows should be used in treating it as a matrix
byrow	if z is a vector, should it be turned into a matrix by row
x	lower left x coordinates
y	lower left y coordinates
dw	image width distances
dh	image height distances
palette	name of color palette to use for color ramp (see here for acceptable values)
dilate	logical - whether to dilate pixel distance computations when drawing
lname	layer name
lgroup	layer group
visible	should the layer be visible?

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_annulus](#), [ly_arc](#), [ly_bar](#), [ly_bezier](#), [ly_boxplot](#), [ly_contour](#), [ly_crect](#), [ly_curve](#), [ly_density](#), [ly_hist](#), [ly_image_url](#), [ly_lines](#), [ly_map](#), [ly_multi_line](#), [ly_oval](#), [ly_patch](#), [ly_points](#), [ly_polygons](#), [ly_quadratic](#), [ly_quantile](#), [ly_ray](#), [ly_rect](#), [ly_segments](#), [ly_text](#), [ly_wedge](#)

Examples

```
p <- figure(xlim = c(0, 1), ylim = c(0, 1), title = "Volcano") %>%  
  ly_image(volcano) %>%  
  ly_contour(volcano)  
p
```

ly_image_url *Add an "image_url" layer to a Bokeh figure*

Description

Renders raster images from URLs at provided coordinates

Usage

```
ly_image_url(fig, x = 0, y = 0, data = figure_data(fig), w = 10,
             h = 10, image_url, dilate = TRUE, anchor = "top_left", angle = 0,
             lname = NULL, lgroup = NULL, visible = TRUE)
```

Arguments

fig	figure to modify
x	x coordinates
y	y coordinates
data	an optional data frame, providing the source for inputs x, y, and other properties
w, h	values or field names of width and height of image
image_url	values or field name of image URLs
dilate	logical - whether to dilate pixel distance computations when drawing
anchor	where the image is anchored to with respect to x and y
angle	values or field name of the angle to rotate the image, in radians
lname	layer name
lgroup	layer group
visible	should the layer be visible?

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_annulus](#), [ly_arc](#), [ly_bar](#), [ly_bezier](#), [ly_boxplot](#), [ly_contour](#), [ly_crect](#), [ly_curve](#), [ly_density](#), [ly_hist](#), [ly_image](#), [ly_lines](#), [ly_map](#), [ly_multi_line](#), [ly_oval](#), [ly_patch](#), [ly_points](#), [ly_polygons](#), [ly_quadratic](#), [ly_quantile](#), [ly_ray](#), [ly_rect](#), [ly_segments](#), [ly_text](#), [ly_wedge](#)

Examples

```
url <- c(" http://bokeh.pydata.org/en/latest/_static/images/logo.png",
        "http://developer.r-project.org/Logo/Rlogo-4.png")

ss <- seq(0, 2*pi, length = 13)[-1]
ws <- runif(12, 2.5, 5) * rep(c(1, 0.8), 6)

imgdat <- data.frame(
```

```

x = sin(ss) * 10, y = cos(ss) * 10,
w = ws, h = ws * rep(c(1, 0.76), 6),
url = rep(url, 6)
)

p <- figure(xlab = "x", ylab = "y") %>%
  ly_image_url(x, y, w = w, h = h, image_url = url, data = imgdat,
  anchor = "center") %>%
  ly_lines(sin(c(ss, ss[1])) * 10, cos(c(ss, ss[1])) * 10,
  width = 15, alpha = 0.1)
p

```

ly_lines	<i>Add a "lines" layer to a Bokeh figure Draws lines with the given coordinates.</i>
----------	--

Description

Add a "lines" layer to a Bokeh figure Draws lines with the given coordinates.

Usage

```

ly_lines(fig, x, y = NULL, data = figure_data(fig), group = NULL,
  color = "black", type = 1, width = 1, alpha = 1, legend = NULL,
  lname = NULL, lgroup = NULL, visible = TRUE, ...)

```

Arguments

fig	figure to modify
x	values or field name of line x coordinates
y	values or field name of line y coordinates
data	an optional data frame, providing the source for inputs x, y, and other glyph properties
group	values or field name of a grouping variable to break lines up by
color	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo'
type	an integer between 1 and 6 matching the lty property in par or an array of integer pixel distances that describe the on-off pattern of dashing to use
width	stroke width in units of pixels
alpha	transparency value for the line between 0 (transparent) and 1 (opaque)
legend	either a logical specifying not to plot a legend for this layer (FALSE) or a string indicating the name of the legend entry for this layer (note that when mapping plot attributes to variables in data, a legend is automatically created and does not need to be specified - see "Mapped plot attributes and legends" below)

lname	layer name
lgroup	layer group
visible	should the layer be visible?
...	additional parameters for fine control over line properties (see "Additional parameters" below)

Mapped plot attributes and legends

When specifying an input data frame for a layer through the data argument, columns of data can be used to specify various plot attributes such as color, etc. For example, with `ly_points(..., data = iris, color = Species)` the Species variable is used to determine how to color the points. Here, Species is "mapped" to the color attribute. Both continuous and categorical variables can be mapped. In the case of continuous variables, the range is cut into slices and attributes are applied to each interval. The mapping from the values of the variable to the actual plot attributes is determined based on the theme.

Additional parameters

line_join	how path segments should be joined together 'miter' 'round' 'bevel'
line_cap	how path segments should be terminated 'butt' 'round' 'square'
line_dash	an integer between 1 and 6 matching the lty property in <code>par</code> or an array of integer pixel distances that
line_dash_offset	the distance in pixels into the line_dash that the pattern should start from

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_annulus](#), [ly_arc](#), [ly_bar](#), [ly_bezier](#), [ly_boxplot](#), [ly_contour](#), [ly_crect](#), [ly_curve](#), [ly_density](#), [ly_hist](#), [ly_image_url](#), [ly_image](#), [ly_map](#), [ly_multi_line](#), [ly_oval](#), [ly_patch](#), [ly_points](#), [ly_polygons](#), [ly_quadratic](#), [ly_quantile](#), [ly_ray](#), [ly_rect](#), [ly_segments](#), [ly_text](#), [ly_wedge](#)

Examples

```
z <- lm(dist ~ speed, data = cars)
p <- figure() %>%
  ly_points(cars, hover = cars) %>%
  ly_lines(lowess(cars), legend = "lowess") %>%
  ly_abline(z, type = 2, legend = "lm", width = 2)
p
```

Description

Draws lines and polygons as specified by a map database

Usage

```
ly_map(fig, database = "world", regions = ".", color = NULL, alpha = 1,
       lname = NULL, lgroup = NULL, visible = TRUE, ...)
```

Arguments

fig	figure to modify
database, regions	parameters passed to map
color	color for the glyph - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo' - for glyphs with both fill and line properties, see "Handling color" below
alpha	the alpha transparency of the glyph between 0 (transparent) and 1 (opaque) - if glyph has both fill and color properties, see "Handling alpha" below
lname	layer name
lgroup	layer group
visible	should the layer be visible?
...	additional parameters for fine control over fill and line properties (see "Additional parameters" below)

Handling color

The color parameter is a high-level plot attribute that provides default behavior for coloring glyphs.

- When using a glyph that only has line properties, this will be the color of the line.
- When using a glyph that has line and fill properties, this will be the color of the line and the fill, with the alpha level of the fill reduced by 50%.
- If full control over fill and line color is desired, the `fill_color` and `line_color` attributes can be specified explicitly and will override color.

When color is NULL and `fill_color` or `line_color` are not specified, the color will be chosen from the theme.

Handling alpha

The alpha is a high-level plot attribute that sets the transparency of the glyph being plotted.

- When using a glyph that only has line properties, this will be the alpha of the line.
- When using a glyph that has line and fill properties, this will be the alpha of the line and the alpha of the fill will be set to 50% of this value.
- Individual fill and line alpha can be specified with `fill_alpha` and `line_alpha` and will override alpha.

Additional parameters

fill_color	color to use to fill the glyph with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo'
fill_alpha	transparency value between 0 (transparent) and 1 (opaque)
line_color	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo'
line_width	stroke width in units of pixels
line_alpha	transparency value between 0 (transparent) and 1 (opaque)
line_join	how path segments should be joined together 'miter' 'round' 'bevel'
line_cap	how path segments should be terminated 'butt' 'round' 'square'
line_dash	array of integer pixel distances that describe the on-off pattern of dashing to use
line_dash_offset	the distance in pixels into the line_dash that the pattern should start from

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_annulus](#), [ly_arc](#), [ly_bar](#), [ly_bezier](#), [ly_boxplot](#), [ly_contour](#), [ly_crect](#), [ly_curve](#), [ly_density](#), [ly_hist](#), [ly_image_url](#), [ly_image](#), [ly_lines](#), [ly_multi_line](#), [ly_oval](#), [ly_patch](#), [ly_points](#), [ly_polygons](#), [ly_quadratic](#), [ly_quantile](#), [ly_ray](#), [ly_rect](#), [ly_segments](#), [ly_text](#), [ly_wedge](#)

ly_multi_line	<i>Add a "multi_line" layer to a Bokeh figure</i>
---------------	---

Description

Draws multiple lines with the given lists of coordinates.

Usage

```
ly_multi_line(fig, xs, ys, color = "black", alpha = 1, width = 1,
              type = 1, lname = NULL, lgroup = NULL, visible = TRUE, ...)
```

Arguments

fig	figure to modify
xs	list of vectors of x coordinates
ys	list of vectors of y coordinates
color	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo'
alpha	transparency value for the line between 0 (transparent) and 1 (opaque)
width	stroke width in units of pixels
type	an integer between 1 and 6 matching the lty property in par or an array of integer pixel distances that describe the on-off pattern of dashing to use
lname	layer name
lgroup	layer group
visible	should the layer be visible?
...	additional parameters for fine control over line properties (see "Additional parameters" below)

Additional parameters

line_join	how path segments should be joined together 'miter' 'round' 'bevel'
line_cap	how path segments should be terminated 'butt' 'round' 'square'
line_dash	an integer between 1 and 6 matching the lty property in par or an array of integer pixel distances that
line_dash_offset	the distance in pixels into the line_dash that the pattern should start from

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_annulus](#), [ly_arc](#), [ly_bar](#), [ly_bezier](#), [ly_boxplot](#), [ly_contour](#), [ly_crect](#), [ly_curve](#), [ly_density](#), [ly_hist](#), [ly_image_url](#), [ly_image](#), [ly_lines](#), [ly_map](#), [ly_oval](#), [ly_patch](#), [ly_points](#), [ly_polygons](#), [ly_quadratic](#), [ly_quantile](#), [ly_ray](#), [ly_rect](#), [ly_segments](#), [ly_text](#), [ly_wedge](#)

ly_oval	<i>Add an "oval" layer to a Bokeh figure</i>
---------	--

Description

Add an "oval" layer to a Bokeh figure

Usage

```
ly_oval(fig, x, y = NULL, data = figure_data(fig), width = 0.1,
        height = 0.1, angle = 0, color = NULL, alpha = 1, legend = NULL,
        lname = NULL, lgroup = NULL, visible = TRUE, ...)
```

Arguments

fig	figure to modify
x	values or field name of center x coordinates
y	values or field name of center y coordinates
data	an optional data frame, providing the source for inputs x, y, and other glyph properties
width	values or field name of widths
height	values or field name of heights
angle	values or field name of rotation angles
color	color for the glyph - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo' - for glyphs with both fill and line properties, see "Handling color" below
alpha	the alpha transparency of the glyph between 0 (transparent) and 1 (opaque) - if glyph has both fill and color properties, see "Handling alpha" below

legend	either a logical specifying not to plot a legend for this layer (FALSE) or a string indicating the name of the legend entry for this layer (note that when mapping plot attributes to variables in data, a legend is automatically created and does not need to be specified - see "Mapped plot attributes and legends" below)
lname	layer name
lgroup	layer group
visible	should the layer be visible?
...	additional parameters for fine control over fill and line properties (see "Additional parameters" below)

Handling color

The color parameter is a high-level plot attribute that provides default behavior for coloring glyphs.

- When using a glyph that only has line properties, this will be the color of the line.
- When using a glyph that has line and fill properties, this will be the color of the line and the fill, with the alpha level of the fill reduced by 50%.
- If full control over fill and line color is desired, the `fill_color` and `line_color` attributes can be specified explicitly and will override color.

When color is NULL and `fill_color` or `line_color` are not specified, the color will be chosen from the theme.

Handling alpha

The alpha is a high-level plot attribute that sets the transparency of the glyph being plotted.

- When using a glyph that only has line properties, this will be the alpha of the line.
- When using a glyph that has line and fill properties, this will be the alpha of the line and the alpha of the fill will be set to 50% of this value.
- Individual fill and line alpha can be specified with `fill_alpha` and `line_alpha` and will override alpha.

Mapped plot attributes and legends

When specifying an input data frame for a layer through the data argument, columns of data can be used to specify various plot attributes such as color, etc. For example, with `ly_points(..., data = iris, color = Species)` the Species variable is used to determine how to color the points. Here, Species is "mapped" to the color attribute. Both continuous and categorical variables can be mapped. In the case of continuous variables, the range is cut into slices and attributes are applied to each interval. The mapping from the values of the variable to the actual plot attributes is determined based on the theme.

Additional parameters

<code>fill_color</code>	color to use to fill the glyph with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. "#f00"
<code>fill_alpha</code>	transparency value between 0 (transparent) and 1 (opaque)
<code>line_color</code>	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. "#f00"

line_width	stroke width in units of pixels
line_alpha	transparency value between 0 (transparent) and 1 (opaque)
line_join	how path segments should be joined together 'miter' 'round' 'bevel'
line_cap	how path segments should be terminated 'butt' 'round' 'square'
line_dash	array of integer pixel distances that describe the on-off pattern of dashing to use
line_dash_offset	the distance in pixels into the line_dash that the pattern should start from

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_annulus](#), [ly_arc](#), [ly_bar](#), [ly_bezier](#), [ly_boxplot](#), [ly_contour](#), [ly_crect](#), [ly_curve](#), [ly_density](#), [ly_hist](#), [ly_image_url](#), [ly_image](#), [ly_lines](#), [ly_map](#), [ly_multi_line](#), [ly_patch](#), [ly_points](#), [ly_polygons](#), [ly_quadratic](#), [ly_quantile](#), [ly_ray](#), [ly_rect](#), [ly_segments](#), [ly_text](#), [ly_wedge](#)

ly_patch	<i>Add a "patch" layer to a Bokeh figure</i>
----------	--

Description

Add a "patch" layer to a Bokeh figure

Usage

```
ly_patch(fig, x, y, data = figure_data(fig), color = NULL, alpha = 1,
        hover = NULL, url = NULL, legend = NULL, lname = NULL,
        lgroup = NULL, visible = TRUE, ...)
```

Arguments

fig	figure to modify
x	values or field name of patch x coordinates
y	values or field name of patch y coordinates
data	an optional data frame, providing the source for inputs x, y, and other glyph properties
color	color for the glyph - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo' - for glyphs with both fill and line properties, see "Handling color" below
alpha	the alpha transparency of the glyph between 0 (transparent) and 1 (opaque) - if glyph has both fill and color properties, see "Handling alpha" below
hover	a data frame of variables to be displayed when hovering over the glyph or a vector of variable names that can be found and extracted from the data argument
url	a string of URLs or a single string that references a variable name (via @var_name) that can be found and extracted from the data argument

legend	either a logical specifying not to plot a legend for this layer (FALSE) or a string indicating the name of the legend entry for this layer (note that when mapping plot attributes to variables in data, a legend is automatically created and does not need to be specified - see "Mapped plot attributes and legends" below)
lname	layer name
lgroup	layer group
visible	should the layer be visible?
...	additional parameters for fine control over fill and line properties (see "Additional parameters" below)

Handling color

The color parameter is a high-level plot attribute that provides default behavior for coloring glyphs.

- When using a glyph that only has line properties, this will be the color of the line.
- When using a glyph that has line and fill properties, this will be the color of the line and the fill, with the alpha level of the fill reduced by 50%.
- If full control over fill and line color is desired, the `fill_color` and `line_color` attributes can be specified explicitly and will override color.

When color is NULL and `fill_color` or `line_color` are not specified, the color will be chosen from the theme.

Handling alpha

The alpha is a high-level plot attribute that sets the transparency of the glyph being plotted.

- When using a glyph that only has line properties, this will be the alpha of the line.
- When using a glyph that has line and fill properties, this will be the alpha of the line and the alpha of the fill will be set to 50% of this value.
- Individual fill and line alpha can be specified with `fill_alpha` and `line_alpha` and will override alpha.

Mapped plot attributes and legends

When specifying an input data frame for a layer through the data argument, columns of data can be used to specify various plot attributes such as color, etc. For example, with `ly_points(..., data = iris, color = Species)` the Species variable is used to determine how to color the points. Here, Species is "mapped" to the color attribute. Both continuous and categorical variables can be mapped. In the case of continuous variables, the range is cut into slices and attributes are applied to each interval. The mapping from the values of the variable to the actual plot attributes is determined based on the theme.

Additional parameters

<code>fill_color</code>	color to use to fill the glyph with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. "#f00"
<code>fill_alpha</code>	transparency value between 0 (transparent) and 1 (opaque)
<code>line_color</code>	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. "#f00"

line_width	stroke width in units of pixels
line_alpha	transparency value between 0 (transparent) and 1 (opaque)
line_join	how path segments should be joined together 'miter' 'round' 'bevel'
line_cap	how path segments should be terminated 'butt' 'round' 'square'
line_dash	array of integer pixel distances that describe the on-off pattern of dashing to use
line_dash_offset	the distance in pixels into the line_dash that the pattern should start from

Note

This function is included for completeness as it maps to Bokeh's patch glyph, but the same and more functionality can be obtained with [ly_polygons](#).

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_annulus](#), [ly_arc](#), [ly_bar](#), [ly_bezier](#), [ly_boxplot](#), [ly_contour](#), [ly_crect](#), [ly_curve](#), [ly_density](#), [ly_hist](#), [ly_image_url](#), [ly_image](#), [ly_lines](#), [ly_map](#), [ly_multi_line](#), [ly_oval](#), [ly_points](#), [ly_polygons](#), [ly_quadratic](#), [ly_quantile](#), [ly_ray](#), [ly_rect](#), [ly_segments](#), [ly_text](#), [ly_wedge](#)

 ly_points

Add a "points" layer to a Bokeh figure

Description

Add a "points" layer to a Bokeh figure

Usage

```
ly_points(fig, x, y = NULL, data = figure_data(fig), glyph = 21,
          color = NULL, alpha = 1, size = 10, hover = NULL, url = NULL,
          legend = NULL, lname = NULL, lgroup = NULL, visible = TRUE, ...)
```

Arguments

fig	figure to modify
x	values or field name of center x coordinates
y	values or field name of center y coordinates
data	an optional data frame, providing the source for inputs x, y, and other glyph properties
glyph	value(s) or field name of the glyph to use (see point_types)
color	color for the glyph - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo' - for glyphs with both fill and line properties, see "Handling color" below

alpha	the alpha transparency of the glyph between 0 (transparent) and 1 (opaque) - if glyph has both fill and color properties, see "Handling alpha" below
size	size of the glyph in screen units
hover	a data frame of variables to be displayed when hovering over the glyph or a vector of variable names that can be found and extracted from the data argument
url	a string of URLs or a single string that references a variable name (via @var_name) that can be found and extracted from the data argument
legend	either a logical specifying not to plot a legend for this layer (FALSE) or a string indicating the name of the legend entry for this layer (note that when mapping plot attributes to variables in data, a legend is automatically created and does not need to be specified - see "Mapped plot attributes and legends" below)
lname	layer name
lgroup	layer group
visible	should the layer be visible?
...	additional parameters for fine control over fill and line properties (see "Additional parameters" below)

Handling color

The color parameter is a high-level plot attribute that provides default behavior for coloring glyphs.

- When using a glyph that only has line properties, this will be the color of the line.
- When using a glyph that has line and fill properties, this will be the color of the line and the fill, with the alpha level of the fill reduced by 50%.
- If full control over fill and line color is desired, the fill_color and line_color attributes can be specified explicitly and will override color.

When color is NULL and fill_color or line_color are not specified, the color will be chosen from the theme.

Handling alpha

The alpha is a high-level plot attribute that sets the transparency of the glyph being plotted.

- When using a glyph that only has line properties, this will be the alpha of the line.
- When using a glyph that has line and fill properties, this will be the alpha of the line and the alpha of the fill will be set to 50% of this value.
- Individual fill and line alpha can be specified with fill_alpha and line_alpha and will override alpha.

Mapped plot attributes and legends

When specifying an input data frame for a layer through the data argument, columns of data can be used to specify various plot attributes such as color, etc. For example, with `ly_points(..., data = iris, color = Species)` the Species variable is used to determine how to color the points. Here, Species is "mapped" to the color attribute. Both continuous and categorical variables can be mapped. In the case of continuous variables, the range is cut into slices and attributes are applied to each interval. The mapping from the values of the variable to the actual plot attributes is determined based on the theme.

Additional parameters

fill_color	color to use to fill the glyph with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. 'red'
fill_alpha	transparency value between 0 (transparent) and 1 (opaque)
line_color	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. 'red'
line_width	stroke width in units of pixels
line_alpha	transparency value between 0 (transparent) and 1 (opaque)
line_join	how path segments should be joined together 'miter' 'round' 'bevel'
line_cap	how path segments should be terminated 'butt' 'round' 'square'
line_dash	array of integer pixel distances that describe the on-off pattern of dashing to use
line_dash_offset	the distance in pixels into the line_dash that the pattern should start from

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_annulus](#), [ly_arc](#), [ly_bar](#), [ly_bezier](#), [ly_boxplot](#), [ly_contour](#), [ly_crect](#), [ly_curve](#), [ly_density](#), [ly_hist](#), [ly_image_url](#), [ly_image](#), [ly_lines](#), [ly_map](#), [ly_multi_line](#), [ly_oval](#), [ly_patch](#), [ly_polygons](#), [ly_quadratic](#), [ly_quantile](#), [ly_ray](#), [ly_rect](#), [ly_segments](#), [ly_text](#), [ly_wedge](#)

Examples

```
figure() %>%
  ly_points(Sepal.Length, Sepal.Width, data = iris,
            color = Species, glyph = Species,
            hover = list(Sepal.Length, Sepal.Width))

# custom hover
mtcars$model <- row.names(mtcars)
figure() %>%
  ly_points(displ, mpg, data = mtcars, color = cyl,
            hover = "This <strong>@model</strong><br>has @hp horsepower!")

z <- lm(dist ~ speed, data = cars)
p <- figure() %>%
  ly_points(cars, hover = cars) %>%
  ly_lines(lowess(cars), legend = "lowess") %>%
  ly_abline(z, type = 2, legend = "lm", width = 2)
p
```


Description

Add a "polygons" layer to a Bokeh figure

Usage

```
ly_polygons(fig, xs, ys, group = NULL, data = figure_data(fig),
            color = NULL, alpha = 1, hover = NULL, url = NULL, lname = NULL,
            lgroup = NULL, visible = TRUE, ...)
```

Arguments

fig	figure to modify
xs	vector or list of values or field name of polygon x coordinates - see details
ys	vector or list of values or field name of polygon y coordinates - see details
group	vector or field name of grouping variable - see details
data	an optional data frame, providing the source for inputs xs, ys, group, and other glyph properties
color	color for the glyph - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo' - for glyphs with both fill and line properties, see "Handling color" below
alpha	the alpha transparency of the glyph between 0 (transparent) and 1 (opaque) - if glyph has both fill and color properties, see "Handling alpha" below
hover	a data frame of variables to be displayed when hovering over the glyph or a vector of variable names that can be found and extracted from the data argument
url	a string of URLs or a single string that references a variable name (via @var_name) that can be found and extracted from the data argument
lname	layer name
lgroup	layer group
visible	should the layer be visible?
...	additional parameters for fine control over fill and line properties (see "Additional parameters" below)

Details

xs and ys can be a list of vectors, each element for one polygon to be drawn, or can be vectors with the group argument specifying how to break them up into individual polygons.

Handling color

The color parameter is a high-level plot attribute that provides default behavior for coloring glyphs.

- When using a glyph that only has line properties, this will be the color of the line.
- When using a glyph that has line and fill properties, this will be the color of the line and the fill, with the alpha level of the fill reduced by 50%.

- If full control over fill and line color is desired, the `fill_color` and `line_color` attributes can be specified explicitly and will override `color`.

When `color` is `NULL` and `fill_color` or `line_color` are not specified, the color will be chosen from the theme.

Handling alpha

The alpha is a high-level plot attribute that sets the transparency of the glyph being plotted.

- When using a glyph that only has line properties, this will be the alpha of the line.
- When using a glyph that has line and fill properties, this will be the alpha of the line and the alpha of the fill will be set to 50% of this value.
- Individual fill and line alpha can be specified with `fill_alpha` and `line_alpha` and will override alpha.

Additional parameters

<code>fill_color</code>	color to use to fill the glyph with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. '#ff0000'
<code>fill_alpha</code>	transparency value between 0 (transparent) and 1 (opaque)
<code>line_color</code>	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. '#ff0000'
<code>line_width</code>	stroke width in units of pixels
<code>line_alpha</code>	transparency value between 0 (transparent) and 1 (opaque)
<code>line_join</code>	how path segments should be joined together 'miter' 'round' 'bevel'
<code>line_cap</code>	how path segments should be terminated 'butt' 'round' 'square'
<code>line_dash</code>	array of integer pixel distances that describe the on-off pattern of dashing to use
<code>line_dash_offset</code>	the distance in pixels into the <code>line_dash</code> that the pattern should start from

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_annulus](#), [ly_arc](#), [ly_bar](#), [ly_bezier](#), [ly_boxplot](#), [ly_contour](#), [ly_crect](#), [ly_curve](#), [ly_density](#), [ly_hist](#), [ly_image_url](#), [ly_image](#), [ly_lines](#), [ly_map](#), [ly_multi_line](#), [ly_oval](#), [ly_patch](#), [ly_points](#), [ly_quadratic](#), [ly_quantile](#), [ly_ray](#), [ly_rect](#), [ly_segments](#), [ly_text](#), [ly_wedge](#)

`ly_quadratic`

Add a "quadratic" layer to a Bokeh figure

Description

Draws quadratic curves with the given starting, ending, and control points.

Usage

```
ly_quadratic(fig, x0, y0, x1, y1, cx, cy, data = figure_data(fig),
             color = "black", alpha = 1, width = 1, type = 1, legend = NULL,
             lname = NULL, lgroup = NULL, visible = TRUE, ...)
```

Arguments

fig	figure to modify
x0	values or field name of starting x coordinates
y0	values or field name of starting y coordinates
x1	values or field name of ending x coordinates
y1	values or field name of ending y coordinates
cx	values or field name of control point x coordinates
cy	values or field name of control point y coordinates
data	an optional data frame, providing the source for start, end, and control point inputs, as well as other glyph properties
color	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo'
alpha	transparency value for the line between 0 (transparent) and 1 (opaque)
width	stroke width in units of pixels
type	an integer between 1 and 6 matching the lty property in par or an array of integer pixel distances that describe the on-off pattern of dashing to use
legend	either a logical specifying not to plot a legend for this layer (FALSE) or a string indicating the name of the legend entry for this layer (note that when mapping plot attributes to variables in data, a legend is automatically created and does not need to be specified - see "Mapped plot attributes and legends" below)
lname	layer name
lgroup	layer group
visible	should the layer be visible?
...	additional parameters for fine control over fill and line properties (see "Additional parameters" below)

Mapped plot attributes and legends

When specifying an input data frame for a layer through the data argument, columns of data can be used to specify various plot attributes such as color, etc. For example, with `ly_points(..., data = iris, color = Species)` the Species variable is used to determine how to color the points. Here, Species is "mapped" to the color attribute. Both continuous and categorical variables can be mapped. In the case of continuous variables, the range is cut into slices and attributes are applied to each interval. The mapping from the values of the variable to the actual plot attributes is determined based on the theme.

Additional parameters

fill_color	color to use to fill the glyph with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. 'red'
fill_alpha	transparency value between 0 (transparent) and 1 (opaque)
line_color	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. 'red'
line_width	stroke width in units of pixels
line_alpha	transparency value between 0 (transparent) and 1 (opaque)
line_join	how path segments should be joined together 'miter' 'round' 'bevel'
line_cap	how path segments should be terminated 'butt' 'round' 'square'
line_dash	array of integer pixel distances that describe the on-off pattern of dashing to use
line_dash_offset	the distance in pixels into the line_dash that the pattern should start from

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_annulus](#), [ly_arc](#), [ly_bar](#), [ly_bezier](#), [ly_boxplot](#), [ly_contour](#), [ly_crect](#), [ly_curve](#), [ly_density](#), [ly_hist](#), [ly_image_url](#), [ly_image](#), [ly_lines](#), [ly_map](#), [ly_multi_line](#), [ly_oval](#), [ly_patch](#), [ly_points](#), [ly_polygons](#), [ly_quantile](#), [ly_ray](#), [ly_rect](#), [ly_segments](#), [ly_text](#), [ly_wedge](#)

ly_quantile

Add a "quantile" layer to a Bokeh figure

Description

Draws quantiles

Usage

```
ly_quantile(fig, x, group = NULL, data = figure_data(fig), probs = NULL,
            distn = stats::qunif, ncutoff = 200, color = NULL, alpha = 1,
            legend = TRUE, lname = NULL, lgroup = NULL, visible = TRUE, ...)
```

Arguments

fig	figure to modify
x	numeric vector or field name of variable to compute sample quantiles for
group	values or field name of a grouping variable to break quantile computations up by
data	an optional data frame, providing the source for x
probs	numeric vector of probabilities with values in $[0, 1]$ at which to compute quantiles - if NULL, every point of x is a quantile
distn	quantile function to use on the x-axis (e.g. qnorm) - default is qunif ,
ncutoff	if the length of x exceeds this value and probs is not specified, compute quantiles at ncutoff points

color	color for the glyph - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo' - for glyphs with both fill and line properties, see "Handling color" below
alpha	the alpha transparency of the glyph between 0 (transparent) and 1 (opaque) - if glyph has both fill and color properties, see "Handling alpha" below
legend	either a logical specifying not to plot a legend for this layer (FALSE) or a string indicating the name of the legend entry for this layer (note that when mapping plot attributes to variables in data, a legend is automatically created and does not need to be specified - see "Mapped plot attributes and legends" below)
lname	layer name
lgroup	layer group
visible	should the layer be visible?
...	additional parameters for fine control over fill and line properties (see "Additional parameters" below)

Handling color

The color parameter is a high-level plot attribute that provides default behavior for coloring glyphs.

- When using a glyph that only has line properties, this will be the color of the line.
- When using a glyph that has line and fill properties, this will be the color of the line and the fill, with the alpha level of the fill reduced by 50%.
- If full control over fill and line color is desired, the `fill_color` and `line_color` attributes can be specified explicitly and will override color.

When color is NULL and `fill_color` or `line_color` are not specified, the color will be chosen from the theme.

Handling alpha

The alpha is a high-level plot attribute that sets the transparency of the glyph being plotted.

- When using a glyph that only has line properties, this will be the alpha of the line.
- When using a glyph that has line and fill properties, this will be the alpha of the line and the alpha of the fill will be set to 50% of this value.
- Individual fill and line alpha can be specified with `fill_alpha` and `line_alpha` and will override alpha.

Mapped plot attributes and legends

When specifying an input data frame for a layer through the data argument, columns of data can be used to specify various plot attributes such as color, etc. For example, with `ly_points(..., data = iris, color = Species)` the Species variable is used to determine how to color the points. Here, Species is "mapped" to the color attribute. Both continuous and categorical variables can be mapped. In the case of continuous variables, the range is cut into slices and attributes are applied to each interval. The mapping from the values of the variable to the actual plot attributes is determined based on the theme.

Additional parameters

fill_color	color to use to fill the glyph with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. 'red'
fill_alpha	transparency value between 0 (transparent) and 1 (opaque)
line_color	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. 'red'
line_width	stroke width in units of pixels
line_alpha	transparency value between 0 (transparent) and 1 (opaque)
line_join	how path segments should be joined together 'miter' 'round' 'bevel'
line_cap	how path segments should be terminated 'butt' 'round' 'square'
line_dash	array of integer pixel distances that describe the on-off pattern of dashing to use
line_dash_offset	the distance in pixels into the line_dash that the pattern should start from

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_annulus](#), [ly_arc](#), [ly_bar](#), [ly_bezier](#), [ly_boxplot](#), [ly_contour](#), [ly_crect](#), [ly_curve](#), [ly_density](#), [ly_hist](#), [ly_image_url](#), [ly_image](#), [ly_lines](#), [ly_map](#), [ly_multi_line](#), [ly_oval](#), [ly_patch](#), [ly_points](#), [ly_polygons](#), [ly_quadratic](#), [ly_ray](#), [ly_rect](#), [ly_segments](#), [ly_text](#), [ly_wedge](#)

Examples

```
figure(legend_location = "top_left") %>%
  ly_quantile(Sepal.Length, group = Species, data = iris)
```

ly_ray

Add a "ray" layer to a Bokeh figure

Description

Draws line segments starting at the given coordinate and extending the given length at the given angle.

Usage

```
ly_ray(fig, x, y = NULL, data = figure_data(fig), length = NULL,
  angle = 0, color = "black", type = 1, width = 1, alpha = NULL,
  legend = NULL, lname = NULL, lgroup = NULL, visible = TRUE, ...)
```

Arguments

fig	figure to modify
x	values or field name of center x coordinates
y	values or field name of center y coordinates
data	an optional data frame, providing the source for inputs x, y, and other glyph properties
length	values or field name of ray lengths in screen units

angle	values or field name of ray angles
color	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo'
type	an integer between 1 and 6 matching the lty property in par or an array of integer pixel distances that describe the on-off pattern of dashing to use
width	stroke width in units of pixels
alpha	transparency value for the line between 0 (transparent) and 1 (opaque)
legend	either a logical specifying not to plot a legend for this layer (FALSE) or a string indicating the name of the legend entry for this layer (note that when mapping plot attributes to variables in data, a legend is automatically created and does not need to be specified - see "Mapped plot attributes and legends" below)
lname	layer name
lgroup	layer group
visible	should the layer be visible?
...	additional parameters for fine control over line properties (see "Additional parameters" below)

Mapped plot attributes and legends

When specifying an input data frame for a layer through the data argument, columns of data can be used to specify various plot attributes such as color, etc. For example, with `ly_points(..., data = iris, color = Species)` the Species variable is used to determine how to color the points. Here, Species is "mapped" to the color attribute. Both continuous and categorical variables can be mapped. In the case of continuous variables, the range is cut into slices and attributes are applied to each interval. The mapping from the values of the variable to the actual plot attributes is determined based on the theme.

Additional parameters

line_join	how path segments should be joined together 'miter' 'round' 'bevel'
line_cap	how path segments should be terminated 'butt' 'round' 'square'
line_dash	an integer between 1 and 6 matching the lty property in par or an array of integer pixel distances that
line_dash_offset	the distance in pixels into the line_dash that the pattern should start from

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_annulus](#), [ly_arc](#), [ly_bar](#), [ly_bezier](#), [ly_boxplot](#), [ly_contour](#), [ly_crect](#), [ly_curve](#), [ly_density](#), [ly_hist](#), [ly_image_url](#), [ly_image](#), [ly_lines](#), [ly_map](#), [ly_multi_line](#), [ly_oval](#), [ly_patch](#), [ly_points](#), [ly_polygons](#), [ly_quadratic](#), [ly_quantile](#), [ly_rect](#), [ly_segments](#), [ly_text](#), [ly_wedge](#)

 ly_rect

 Add a "rect" layer to a Bokeh figure

Description

Add a "rect" layer to a Bokeh figure

Usage

```
ly_rect(fig, xleft, ybottom, xright, ytop, data = figure_data(fig),
        color = NULL, alpha = 1, hover = NULL, url = NULL, legend = NULL,
        lname = NULL, lgroup = NULL, visible = TRUE, ...)
```

Arguments

fig	figure to modify
xleft	values or field name of left edges
ybottom	values or field name of bottom edges
xright	values or field name of right edges
ytop	values or field name of top edges
data	an optional data frame, providing the source for inputs xleft, ybottom, xright, ytop, and other glyph properties
color	color for the glyph - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo' - for glyphs with both fill and line properties, see "Handling color" below
alpha	the alpha transparency of the glyph between 0 (transparent) and 1 (opaque) - if glyph has both fill and color properties, see "Handling alpha" below
hover	a data frame of variables to be displayed when hovering over the glyph or a vector of variable names that can be found and extracted from the data argument
url	a string of URLs or a single string that references a variable name (via @var_name) that can be found and extracted from the data argument
legend	either a logical specifying not to plot a legend for this layer (FALSE) or a string indicating the name of the legend entry for this layer (note that when mapping plot attributes to variables in data, a legend is automatically created and does not need to be specified - see "Mapped plot attributes and legends" below)
lname	layer name
lgroup	layer group
visible	should the layer be visible?
...	additional parameters for fine control over fill and line properties (see "Additional parameters" below)

Handling color

The color parameter is a high-level plot attribute that provides default behavior for coloring glyphs.

- When using a glyph that only has line properties, this will be the color of the line.
- When using a glyph that has line and fill properties, this will be the color of the line and the fill, with the alpha level of the fill reduced by 50%.
- If full control over fill and line color is desired, the `fill_color` and `line_color` attributes can be specified explicitly and will override `color`.

When `color` is NULL and `fill_color` or `line_color` are not specified, the color will be chosen from the theme.

Handling alpha

The alpha is a high-level plot attribute that sets the transparency of the glyph being plotted.

- When using a glyph that only has line properties, this will be the alpha of the line.
- When using a glyph that has line and fill properties, this will be the alpha of the line and the alpha of the fill will be set to 50% of this value.
- Individual fill and line alpha can be specified with `fill_alpha` and `line_alpha` and will override alpha.

Mapped plot attributes and legends

When specifying an input data frame for a layer through the `data` argument, columns of data can be used to specify various plot attributes such as `color`, etc. For example, with `ly_points(..., data = iris, color = Species)` the `Species` variable is used to determine how to color the points. Here, `Species` is "mapped" to the `color` attribute. Both continuous and categorical variables can be mapped. In the case of continuous variables, the range is cut into slices and attributes are applied to each interval. The mapping from the values of the variable to the actual plot attributes is determined based on the theme.

Additional parameters

<code>fill_color</code>	color to use to fill the glyph with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. <code>'red'</code>
<code>fill_alpha</code>	transparency value between 0 (transparent) and 1 (opaque)
<code>line_color</code>	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. <code>'red'</code>
<code>line_width</code>	stroke width in units of pixels
<code>line_alpha</code>	transparency value between 0 (transparent) and 1 (opaque)
<code>line_join</code>	how path segments should be joined together <code>'miter'</code> <code>'round'</code> <code>'bevel'</code>
<code>line_cap</code>	how path segments should be terminated <code>'butt'</code> <code>'round'</code> <code>'square'</code>
<code>line_dash</code>	array of integer pixel distances that describe the on-off pattern of dashing to use
<code>line_dash_offset</code>	the distance in pixels into the <code>line_dash</code> that the pattern should start from

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_annulus](#), [ly_arc](#), [ly_bar](#), [ly_bezier](#), [ly_boxplot](#), [ly_contour](#), [ly_crect](#), [ly_curve](#), [ly_density](#), [ly_hist](#), [ly_image_url](#), [ly_image](#), [ly_lines](#), [ly_map](#), [ly_multi_line](#), [ly_oval](#), [ly_patch](#), [ly_points](#), [ly_polygons](#), [ly_quadratic](#), [ly_quantile](#), [ly_ray](#), [ly_segments](#), [ly_text](#), [ly_wedge](#)

 ly_segments

 Add a "segments" layer to a Bokeh figure

Description

Draws line segments with the given starting and ending coordinates.

Usage

```
ly_segments(fig, x0, y0, x1, y1, data = figure_data(fig), color = "black",
            alpha = 1, width = 1, type = 1, legend = NULL, lname = NULL,
            lgroup = NULL, visible = TRUE, ...)
```

Arguments

fig	figure to modify
x0	values or field name of starting x coordinates
y0	values or field name of starting y coordinates
x1	values or field name of ending x coordinates
y1	values or field name of ending y coordinates
data	an optional data frame, providing the source for inputs x, y, and other glyph properties
color	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo'
alpha	transparency value for the line between 0 (transparent) and 1 (opaque)
width	stroke width in units of pixels
type	an integer between 1 and 6 matching the lty property in par or an array of integer pixel distances that describe the on-off pattern of dashing to use
legend	either a logical specifying not to plot a legend for this layer (FALSE) or a string indicating the name of the legend entry for this layer (note that when mapping plot attributes to variables in data, a legend is automatically created and does not need to be specified - see "Mapped plot attributes and legends" below)
lname	layer name
lgroup	layer group
visible	should the layer be visible?
...	additional parameters for fine control over line properties (see "Additional parameters" below)

Mapped plot attributes and legends

When specifying an input data frame for a layer through the data argument, columns of data can be used to specify various plot attributes such as color, etc. For example, with `ly_points(..., data = iris, color = Species)` the Species variable is used to determine how to color the points. Here, Species is "mapped" to the color attribute. Both continuous and categorical variables can be mapped. In the case of continuous variables, the range is cut into slices and attributes are applied to each interval. The mapping from the values of the variable to the actual plot attributes is determined based on the theme.

Additional parameters

<code>line_join</code>	how path segments should be joined together 'miter' 'round' 'bevel'
<code>line_cap</code>	how path segments should be terminated 'butt' 'round' 'square'
<code>line_dash</code>	an integer between 1 and 6 matching the <code>lty</code> property in <code>par</code> or an array of integer pixel distances that
<code>line_dash_offset</code>	the distance in pixels into the <code>line_dash</code> that the pattern should start from

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_annulus](#), [ly_arc](#), [ly_bar](#), [ly_bezier](#), [ly_boxplot](#), [ly_contour](#), [ly_crect](#), [ly_curve](#), [ly_density](#), [ly_hist](#), [ly_image_url](#), [ly_image](#), [ly_lines](#), [ly_map](#), [ly_multi_line](#), [ly_oval](#), [ly_patch](#), [ly_points](#), [ly_polygons](#), [ly_quadratic](#), [ly_quantile](#), [ly_ray](#), [ly_rect](#), [ly_text](#), [ly_wedge](#)

<code>ly_text</code>	<i>Add a "text" layer to a Bokeh figure</i>
----------------------	---

Description

Add a "text" layer to a Bokeh figure

Usage

```
ly_text(fig, x, y = NULL, text = NULL, data = figure_data(fig),
        color = "black", alpha = 1, angle = 0, align = NULL,
        baseline = NULL, font = NULL, font_size = NULL, font_style = NULL,
        x_offset = NULL, y_offset = NULL, legend = NULL, lname = NULL,
        lgroup = NULL, visible = TRUE)
```

Arguments

<code>fig</code>	figure to modify
<code>x</code>	x coordinates of text anchors
<code>y</code>	y coordinates of text anchors
<code>text</code>	text values to render

data	an optional data frame, providing the source for inputs x, y, text, and other glyph properties
color	text color values for the text
alpha	text alpha values for the text
angle	angle to rotate the text in radians
align	text align values for the text ("left", "right", "center")
baseline	text baseline values for the text ("top", "middle", "bottom", "alphabetic", "hanging")
font	text font values for the text
font_size	text font size values for the text
font_style	text font style values for the text ("normal", "italic", "bold")
x_offset	offset values to apply to the x-coordinates
y_offset	offset values to apply to the y-coordinates
legend	either a logical specifying not to plot a legend for this layer (FALSE) or a string indicating the name of the legend entry for this layer (note that when mapping plot attributes to variables in data, a legend is automatically created and does not need to be specified - see "Mapped plot attributes and legends" below)
lname	layer name
lgroup	layer group
visible	should the layer be visible?

Mapped plot attributes and legends

When specifying an input data frame for a layer through the data argument, columns of data can be used to specify various plot attributes such as color, etc. For example, with `ly_points(..., data = iris, color = Species)` the Species variable is used to determine how to color the points. Here, Species is "mapped" to the color attribute. Both continuous and categorical variables can be mapped. In the case of continuous variables, the range is cut into slices and attributes are applied to each interval. The mapping from the values of the variable to the actual plot attributes is determined based on the theme.

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_annulus](#), [ly_arc](#), [ly_bar](#), [ly_bezier](#), [ly_boxplot](#), [ly_contour](#), [ly_crect](#), [ly_curve](#), [ly_density](#), [ly_hist](#), [ly_image_url](#), [ly_image](#), [ly_lines](#), [ly_map](#), [ly_multi_line](#), [ly_oval](#), [ly_patch](#), [ly_points](#), [ly_polygons](#), [ly_quadratic](#), [ly_quantile](#), [ly_ray](#), [ly_rect](#), [ly_segments](#), [ly_wedge](#)

Examples

```
# prepare data
elements <- subset(elements, !is.na(group))
elements$group <- as.character(elements$group)
elements$period <- as.character(elements$period)
```

```

# add colors for groups
metals <- c("alkali metal", "alkaline earth metal", "halogen",
  "metal", "metalloid", "noble gas", "nonmetal", "transition metal")
colors <- c("#a6cee3", "#1f78b4", "#fdbf6f", "#b2df8a", "#33a02c",
  "#bbbb88", "#baa2a6", "#e08e79")
elements$color <- colors[match(elements$metal, metals)]
elements$type <- elements$metal

# make coordinates for labels
elements$symx <- paste(elements$group, ":0.1", sep = "")
elements$numbery <- paste(elements$period, ":0.8", sep = "")
elements$massy <- paste(elements$period, ":0.15", sep = "")
elements$namey <- paste(elements$period, ":0.3", sep = "")

# create figure
p <- figure(title = "Periodic Table", tools = "",
  ylim = as.character(c(7:1)), xlim = as.character(1:18),
  xgrid = FALSE, ygrid = FALSE, xlab = "", ylab = "",
  height = 600, width = 1200) %>%

# plot rectangles
ly_crect(group, period, data = elements, 0.9, 0.9,
  fill_color = color, line_color = color, fill_alpha = 0.6,
  hover = list(name, atomic.number, type, atomic.mass,
    electronic.configuration)) %>%

# add symbol text
ly_text(symx, period, text = symbol, data = elements,
  font_style = "bold", font_size = "15pt",
  align = "left", baseline = "middle") %>%

# add atomic number text
ly_text(symx, numbery, text = atomic.number, data = elements,
  font_size = "9pt", align = "left", baseline = "middle") %>%

# add name text
ly_text(symx, namey, text = name, data = elements,
  font_size = "6pt", align = "left", baseline = "middle") %>%

# add atomic mass text
ly_text(symx, massy, text = atomic.mass, data = elements,
  font_size = "6pt", align = "left", baseline = "middle")

p

```

Description

Add a "wedge" layer to a Bokeh figure

Usage

```
ly_wedge(fig, x, y = NULL, data = figure_data(fig), radius = 0.3,
         start_angle = 0, end_angle = 2 * pi, direction = "anticlock",
         color = NULL, alpha = 1, hover = NULL, url = NULL, legend = NULL,
         lname = NULL, lgroup = NULL, visible = TRUE, ...)
```

Arguments

fig	figure to modify
x	values or field name of center x coordinates
y	values or field name of center y coordinates
data	an optional data frame, providing the source for inputs x, y, and other glyph properties
radius	values or field name of wedge radii
start_angle	the angles to start the wedges, in radians, as measured from the horizontal
end_angle	the angles to end the wedges, in radians, as measured from the horizontal
direction	direction to turn between starting and ending angles ("anticlock", "clock")
color	color for the glyph - a hex code (with no alpha) or any of the 147 named CSS colors, e.g 'green', 'indigo' - for glyphs with both fill and line properties, see "Handling color" below
alpha	the alpha transparency of the glyph between 0 (transparent) and 1 (opaque) - if glyph has both fill and color properties, see "Handling alpha" below
hover	a data frame of variables to be displayed when hovering over the glyph or a vector of variable names that can be found and extracted from the data argument
url	a string of URLs or a single string that references a variable name (via @var_name) that can be found and extracted from the data argument
legend	either a logical specifying not to plot a legend for this layer (FALSE) or a string indicating the name of the legend entry for this layer (note that when mapping plot attributes to variables in data, a legend is automatically created and does not need to be specified - see "Mapped plot attributes and legends" below)
lname	layer name
lgroup	layer group
visible	should the layer be visible?
...	additional parameters for fine control over fill and line properties (see "Additional parameters" below)

Handling color

The color parameter is a high-level plot attribute that provides default behavior for coloring glyphs.

- When using a glyph that only has line properties, this will be the color of the line.
- When using a glyph that has line and fill properties, this will be the color of the line and the fill, with the alpha level of the fill reduced by 50%.
- If full control over fill and line color is desired, the `fill_color` and `line_color` attributes can be specified explicitly and will override `color`.

When `color` is NULL and `fill_color` or `line_color` are not specified, the color will be chosen from the theme.

Handling alpha

The alpha is a high-level plot attribute that sets the transparency of the glyph being plotted.

- When using a glyph that only has line properties, this will be the alpha of the line.
- When using a glyph that has line and fill properties, this will be the alpha of the line and the alpha of the fill will be set to 50% of this value.
- Individual fill and line alpha can be specified with `fill_alpha` and `line_alpha` and will override alpha.

Mapped plot attributes and legends

When specifying an input data frame for a layer through the `data` argument, columns of data can be used to specify various plot attributes such as `color`, etc. For example, with `ly_points(..., data = iris, color = Species)` the `Species` variable is used to determine how to color the points. Here, `Species` is "mapped" to the `color` attribute. Both continuous and categorical variables can be mapped. In the case of continuous variables, the range is cut into slices and attributes are applied to each interval. The mapping from the values of the variable to the actual plot attributes is determined based on the theme.

Additional parameters

<code>fill_color</code>	color to use to fill the glyph with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. <code>'#f00'</code>
<code>fill_alpha</code>	transparency value between 0 (transparent) and 1 (opaque)
<code>line_color</code>	color to use to stroke lines with - a hex code (with no alpha) or any of the 147 named CSS colors, e.g. <code>'#f00'</code>
<code>line_width</code>	stroke width in units of pixels
<code>line_alpha</code>	transparency value between 0 (transparent) and 1 (opaque)
<code>line_join</code>	how path segments should be joined together <code>'miter'</code> <code>'round'</code> <code>'bevel'</code>
<code>line_cap</code>	how path segments should be terminated <code>'butt'</code> <code>'round'</code> <code>'square'</code>
<code>line_dash</code>	array of integer pixel distances that describe the on-off pattern of dashing to use
<code>line_dash_offset</code>	the distance in pixels into the <code>line_dash</code> that the pattern should start from

See Also

Other layer functions: [ly_abline](#), [ly_annular_wedge](#), [ly_annulus](#), [ly_arc](#), [ly_bar](#), [ly_bezier](#), [ly_boxplot](#), [ly_contour](#), [ly_crect](#), [ly_curve](#), [ly_density](#), [ly_hist](#), [ly_image_url](#), [ly_image](#), [ly_lines](#), [ly_map](#), [ly_multi_line](#), [ly_oval](#), [ly_patch](#), [ly_points](#), [ly_polygons](#), [ly_quadratic](#), [ly_quantile](#), [ly_ray](#), [ly_rect](#), [ly_segments](#), [ly_text](#)

Examples

```
rescale <- function(x)
  (x - min(x)) / diff(range(x))
figure() %>%
  ly_wedge(Sepal.Length, Sepal.Width, data = iris,
           end_angle = rescale(Petal.Length) * 2 * pi, color = Species,
           radius = 0.15, alpha = 0.5,
           hover = Species)
```

nyctaxihex

Hexagon binned counts of NYC taxi pickup locations

Description

Counts of NYC taxi pickups by location for January 2013, obtained from [here](#).

Usage

```
nyctaxihex
```

Examples

```
## Not run:
gmap(title = "NYC taxi pickups January 2013",
     lat = 40.74, lng = -73.95, zoom = 11,
     map_type = "roadmap", width = 1000, height = 800) %>%
  ly_hexbin(nyctaxihex, alpha = 0.5,
           palette = "Spectral10", trans = log, inv = exp)

## End(Not run)
```

pal_color *Palettes for themes*

Description

Palettes for themes

Palettes for themes

Usage

pal_color(colors)

pal_tableau(pal = "Tableau10")

pal_bk_glyph()

pal_gradient(cols = c("#66C2A4", "#41AE76", "#238B45", "#006D2C", "#00441B"),
space = "rgb")

pal_size(min = 2, max = 20)

pal_bk_line_dash()

pal_bk_line_width()

Arguments

colors	a vector of colors to be used in the color palette
pal	palette name
cols	a vector of colors to ramp across for a continuous palette
space	passed on to colorRampPalette [grDevices]
min	minimum value
max	maximum value

phantom_install *Instructions for installing phantomjs*

Description

Instructions for installing phantomjs

Usage

phantom_install()

point_types	<i>Display glyph types available for ly_points()</i>
-------------	--

Description

Display glyph types available for ly_points()

Usage

```
point_types(size = 25, color = "blue", width = 800, height = 450)
```

Arguments

size	size of the glyph
color	color to use for line and fill properties
width, height	dimensions of output plot

Examples

```
point_types()
```

print_model_json	<i>Print the JSON of a Bokeh figure</i>
------------------	---

Description

Print the JSON of a Bokeh figure

Usage

```
print_model_json(fig, prepare = TRUE, pretty = TRUE, file = "",
  pbcopy = FALSE)
```

Arguments

fig	figure to print
prepare	logical - should the figure be sent through preparations that need to be done prior to plotting (TRUE), or printed as-is (FALSE)
pretty	parameter passed on to toJSON
file	parameter passed on to cat
pbcopy	logical - if on OSX, should the results be passed to the clipboard (TRUE) instead of printed to the screen (FALSE)?

Examples

```
## Not run:
p <- figure() %>% ly_points(1:10) %>%
  tool_pan(dimensions = "height")
print_model_json(p)

## End(Not run)
```

rbokeh2html

Get the HTML content required to embed a Bokeh figure

Description

Get the HTML content required to embed a Bokeh figure

Usage

```
rbokeh2html(fig, file = tempfile(fileext = ".html"), pretty = FALSE,
  secure = TRUE)
```

Arguments

fig	figure
file	html file name to write the figure to
pretty	should the json model be pretty printed to the html file?
secure	should https be used for cdn links?

Examples

```
p <- figure() %>% ly_points(1:10)
rbokeh2html(p)
```

rbokehOutput

Widget output function for use in Shiny

Description

Widget output function for use in Shiny

Usage

```
rbokehOutput(outputId, width = "100%", height = "400px")
```

Arguments

outputId	output variable to read from
width	a valid CSS unit for the width or a number, which will be coerced to a string and have "px" appended.
height	a valid CSS unit for the height or a number, which will be coerced to a string and have "px" appended.

Examples

```
## Not run:
library("shiny")
library("rbokeh")

ui <- fluidPage(
  rbokehOutput("rbokeh")
)

server <- function(input, output, session) {
  output$rbokeh <- renderRbokeh({
    # Use invalidateLater() and jitter() to add some motion
    invalidateLater(1000, session)
    figure() %>%
      ly_points(jitter(cars$speed), jitter(cars$dist))
  })
}

shinyApp(ui, server)

library("shiny")
library("rbokeh")

ui <- fluidPage(
  rbokehOutput("rbokeh", width = 500, height = 540),
  textOutput("x_range_text")
)

server <- function(input, output, session) {
  output$rbokeh <- renderRbokeh({
    figure() %>% ly_points(1:10) %>%
      x_range(callback = shiny_callback("x_range"))
  })

  output$x_range_text <- reactive({
    xrng <- input$x_range
    if(!is.null(xrng)) {
      paste0("factors: ", xrng$factors, ", start: ", xrng$start,
            ", end: ", xrng$end)
    } else {
      "waiting for axis event..."
    }
  })
}
```

```

    })
  }

  shinyApp(ui, server)

  ## End(Not run)

```

renderRbokeh	<i>Widget render function for use in Shiny</i>
--------------	--

Description

Widget render function for use in Shiny

Usage

```
renderRbokeh(expr, env = parent.frame(), quoted = FALSE)
```

Arguments

expr	an expression that generates a rbokeh figure
env	the environment in which to evaluate expr.
quoted	is expr a quoted expression (with quote())? This is useful if you want to save an expression in a variable.

See Also

[rbokehOutput](#) for an example in Shiny

set_palette	<i>Set palettes for various plot attributes</i>
-------------	---

Description

Set palettes for various plot attributes

Usage

```

set_palette(fig, discrete_color = NULL, discrete_alpha = NULL,
  continuous_color = NULL, continuous_alpha = NULL, discrete_glyph = NULL,
  discrete_fill_color = NULL, discrete_line_color = NULL,
  discrete_text_color = NULL, discrete_fill_alpha = NULL,
  discrete_line_alpha = NULL, discrete_text_alpha = NULL,
  discrete_line_dash = NULL, discrete_line_width = NULL,
  discrete_size = NULL, continuous_glyph = NULL,
  continuous_fill_color = NULL, continuous_line_color = NULL,

```

```

continuous_text_color = NULL, continuous_fill_alpha = NULL,
continuous_line_alpha = NULL, continuous_text_alpha = NULL,
continuous_line_dash = NULL, continuous_line_width = NULL,
continuous_size = NULL)

```

Arguments

```

fig           figure to update theme palettes for
discrete_color  a discrete color palette to override the theme (see details)
discrete_alpha  a discrete alpha palette to override the theme (see details)
continuous_color
                a continuous color palette to override the theme (see details)
continuous_alpha
                a continuous alpha palette to override the theme (see details)
discrete_glyph  a discrete glyph palette to override the theme
discrete_fill_color
                a discrete fill_color palette to override the theme
discrete_line_color
                a discrete line_color palette to override the theme
discrete_text_color
                a discrete text_color palette to override the theme
discrete_fill_alpha
                a discrete fill_alpha palette to override the theme
discrete_line_alpha
                a discrete line_alpha palette to override the theme
discrete_text_alpha
                a discrete text_alpha palette to override the theme
discrete_line_dash
                a discrete line_dash palette to override the theme
discrete_line_width
                a discrete line_width palette to override the theme
discrete_size   a discrete size palette to override the theme
continuous_glyph
                a continuous glyph palette to override the theme
continuous_fill_color
                a continuous fill_color palette to override the theme
continuous_line_color
                a continuous line_color palette to override the theme
continuous_text_color
                a continuous text_color palette to override the theme
continuous_fill_alpha
                a continuous fill_alpha palette to override the theme
continuous_line_alpha
                a continuous line_alpha palette to override the theme

```

```

continuous_text_alpha
    a continuous text_alpha palette to override the theme
continuous_line_dash
    a continuous line_dash palette to override the theme
continuous_line_width
    a continuous line_width palette to override the theme
continuous_size
    a continuous size palette to override the theme

```

Details

Palettes specified in this function will override the existing theme and apply the specified attributes when they are not otherwise explicitly specified in a layer function. See the contents of `bk_default_theme` for an example of the theme elements this will update. As a convenience, if you use `discrete_color`, the palette will apply to all the `discrete_***_color` attributes unless those are explicitly specified also. The same pattern is true for `discrete_alpha`, `continuous_color`, and `continuous_alpha`. For specifying discrete color palettes, the easiest thing to do is use `pal_color` with a vector of colors you want to use in the palette.

Examples

```

figure() %>%
  ly_points(Sepal.Length, Sepal.Width, data = iris,
    color = Species, glyph = Species) %>%
  set_palette(discrete_color = pal_color(c("red", "blue", "green")))

```

set_theme	<i>Set the theme for a figure</i>
-----------	-----------------------------------

Description

Set the theme for a figure

Usage

```
set_theme(fig, theme)
```

Arguments

fig	a figure to set the theme for
theme	theme

Examples

```

# manually specify a ggplot-like grid and background
figure() %>%
  ly_points(1:10) %>%
  theme_plot(background_fill_color = "#E6E6E6",
             outline_line_color = "white") %>%
  theme_grid(c("x", "y"), grid_line_color = "white",
            minor_grid_line_color = "white",
            minor_grid_line_alpha = 0.4) %>%
  theme_axis(c("x", "y"), axis_line_color = "white",
            major_label_text_color = "#7F7F7F",
            major_tick_line_color = "#7F7F7F",
            minor_tick_line_alpha = 0, num_minor_ticks = 2)

# or use the built in ggplot theme (under development)
figure(data = iris, legend = "top_left", tools = NULL) %>%
  ly_points(Sepal.Length, Petal.Length, color = Species) %>%
  set_theme(bk_ggplot_theme)

## Not run:
# or to set the theme for all future plots
options(bokeh_theme = bk_ggplot_theme)

figure() %>%
  ly_points(1:10)

figure() %>%
  ly_boxplot(1:10)

## End(Not run)

```

shiny_callback

Specify a Shiny callback

Description

Specify a Shiny callback

Usage

```
shiny_callback(id)
```

Arguments

`id` a name that will be made available in your Shiny app as `input$id`

Note

Depending on the type of callback you are using (selection, range, hover, tap), the value of `input$id` will change. The best way to get familiar with what to expect as these values is to debug inside your Shiny app and inspect the contents. You can also use `custom_callback` to write your own custom callbacks that can register other data in your Shiny app. To see what the callbacks look like for each callback type, see, for example, the contents of `rbokeh:::handle_range_callback.shinyCallback`

sub_names	<i>Retrieve and properly parse all data</i>
-----------	---

Description

Retrieve and properly parse all data

Usage

```
sub_names(fig, data, arg_obj, process_data_and_names = TRUE)
```

Arguments

fig	figure to be used
data	data to be used
arg_obj	args object supplied by grab
process_data_and_names	boolean to determine if the data and x_name and y_name should be post processed

Value

list of three groups: data, info, and params

theme_axis	<i>Override theme parameters for axis attributes</i>
------------	--

Description

Override theme parameters for axis attributes

Usage

```

theme_axis(fig, which = c("x", "y"), num_minor_ticks = 5,
  axis_label_standoff = NULL, axis_label_text_align = "left",
  axis_label_text_alpha = 1, axis_label_text_baseline = "bottom",
  axis_label_text_color = "#444444", axis_label_text_font = "Helvetica",
  axis_label_text_font_size = "12pt", axis_label_text_font_style = "normal",
  axis_line_alpha = 1, axis_line_cap = "butt", axis_line_color = "black",
  axis_line_dash = NULL, axis_line_dash_offset = 0,
  axis_line_join = "miter", axis_line_width = 1,
  major_label_orientation = "horizontal", major_label_standoff = NULL,
  major_label_text_align = "left", major_label_text_alpha = 1,
  major_label_text_baseline = "bottom", major_label_text_color = "#444444",
  major_label_text_font = "Helvetica", major_label_text_font_size = "12pt",
  major_label_text_font_style = "normal", major_tick_in = NULL,
  major_tick_line_alpha = 1, major_tick_line_cap = "butt",
  major_tick_line_color = "black", major_tick_line_dash = NULL,
  major_tick_line_dash_offset = 0, major_tick_line_join = "miter",
  major_tick_line_width = 1, major_tick_out = NULL, minor_tick_in = NULL,
  minor_tick_line_alpha = 1, minor_tick_line_cap = "butt",
  minor_tick_line_color = "black", minor_tick_line_dash = NULL,
  minor_tick_line_dash_offset = 0, minor_tick_line_join = "miter",
  minor_tick_line_width = 1, minor_tick_out = NULL, pars = NULL)

```

Arguments

<code>fig</code>	figure to modify
<code>which</code>	which grids to apply attributes to ("x" and/or "y")
<code>num_minor_ticks</code>	number of minor ticks
<code>axis_label_standoff</code>	(integer) The distance in pixels that the axis labels should be offset from the tick labels.
<code>axis_label_text_align</code>	('left', 'right', 'center') The text align of the axis label.
<code>axis_label_text_alpha</code>	(numeric) The text alpha of the axis label.
<code>axis_label_text_baseline</code>	('top', 'middle', 'bottom', 'alphabetic', 'hanging') The text baseline of the axis label.
<code>axis_label_text_color</code>	(color) The text color of the axis label.
<code>axis_label_text_font</code>	(string) The text font of the axis label.
<code>axis_label_text_font_size</code>	(string - e.g. '12pt') The text font size of the axis label.
<code>axis_label_text_font_style</code>	('normal', 'italic', 'bold') The text font style of the axis label.

`axis_line_alpha`
(numeric) The line alpha of the axis line.

`axis_line_cap` ('butt', 'round', 'square') The line cap of the axis line.

`axis_line_color`
(color) The line color of the axis line.

`axis_line_dash` The line dash of the axis line.

`axis_line_dash_offset`
(integer) The line dash offset of the axis line.

`axis_line_join` ('miter', 'round', 'bevel') The line join of the axis line.

`axis_line_width`
(integer) The line width of the axis line.

`major_label_orientation`
('horizontal', 'vertical', or angle in degrees) What direction the major label text should be oriented. If a number is supplied, the angle of the text is measured from horizontal.

`major_label_standoff`
(integer) The distance in pixels that the major tick labels should be offset from the associated ticks.

`major_label_text_align`
('left', 'right', 'center') The text align of the major tick labels.

`major_label_text_alpha`
(numeric) The text alpha of the major tick labels.

`major_label_text_baseline`
('top', 'middle', 'bottom', 'alphabetic', 'hanging') The text baseline of the major tick labels.

`major_label_text_color`
(color) The text color of the major tick labels.

`major_label_text_font`
(string - 'Helvetica') The text font of the major tick labels.

`major_label_text_font_size`
(string - e.g. '12pt') The text font size of the major tick labels.

`major_label_text_font_style`
('normal', 'italic', 'bold') The text font style of the major tick labels.

`major_tick_in` (integer) The distance in pixels that major ticks should extend into the main plot area.

`major_tick_line_alpha`
(numeric) The line alpha of the major ticks.

`major_tick_line_cap`
('butt', 'round', 'square') The line cap of the major ticks.

`major_tick_line_color`
(color) The line color of the major ticks.

`major_tick_line_dash`
The line dash of the major ticks.

`major_tick_line_dash_offset`
(integer) The line dash offset of the major ticks.

major_tick_line_join ('miter', 'round', 'bevel') The line join of the major ticks.

major_tick_line_width (integer) The line width of the major ticks.

major_tick_out (integer) The distance in pixels that major ticks should extend out of the main plot area.

minor_tick_in (integer) The distance in pixels that minor ticks should extend into the main plot area.

minor_tick_line_alpha (numeric) The line alpha of the minor ticks.

minor_tick_line_cap ('butt', 'round', 'square') The line cap of the minor ticks.

minor_tick_line_color (color) The line color of the minor ticks.

minor_tick_line_dash The line dash of the minor ticks.

minor_tick_line_dash_offset (integer) The line dash offset of the minor ticks.

minor_tick_line_join ('miter', 'round', 'bevel') The line join of the minor ticks.

minor_tick_line_width (integer) The line width of the minor ticks.

minor_tick_out (integer) The distance in pixels that major ticks should extend out of the main plot area.

pars optionally specify a named list of all parameters - useful when dealing with theme lists

Examples

```
# manually specify a ggplot-like grid and background
figure() %>%
  ly_points(1:10) %>%
  theme_plot(background_fill_color = "#E6E6E6",
             outline_line_color = "white") %>%
  theme_grid(c("x", "y"), grid_line_color = "white",
            minor_grid_line_color = "white",
            minor_grid_line_alpha = 0.4) %>%
  theme_axis(c("x", "y"), axis_line_color = "white",
            major_label_text_color = "#7F7F7F",
            major_tick_line_color = "#7F7F7F",
            minor_tick_line_alpha = 0, num_minor_ticks = 2)

# or use the built in ggplot theme (under development)
figure(data = iris, legend = "top_left", tools = NULL) %>%
  ly_points(Sepal.Length, Petal.Length, color = Species) %>%
  set_theme(bk_ggplot_theme)
```

```

## Not run:
# or to set the theme for all future plots
options(bokeh_theme = bk_ggplot_theme)

figure() %>%
  ly_points(1:10)

figure() %>%
  ly_boxplot(1:10)

## End(Not run)

```

 theme_grid

Override theme parameters for grid attributes

Description

Override theme parameters for grid attributes

Usage

```

theme_grid(fig, which = c("x", "y"), band_fill_alpha = 1,
  band_fill_color = "gray", grid_line_alpha = 1, grid_line_cap = "butt",
  grid_line_color = "black", grid_line_dash = NULL,
  grid_line_dash_offset = 0, grid_line_join = "miter",
  grid_line_width = 1, minor_grid_line_alpha = 1,
  minor_grid_line_cap = "butt", minor_grid_line_color = "black",
  minor_grid_line_dash = NULL, minor_grid_line_dash_offset = 0,
  minor_grid_line_join = "miter", minor_grid_line_width = 1, pars = NULL)

```

Arguments

fig	figure to modify
which	which grids to apply attributes to ("x" and/or "y")
band_fill_alpha	The fill alpha of alternating bands between Grid lines.
band_fill_color	The fill color of alternating bands between Grid lines.
grid_line_alpha	The line alpha of the Grid lines.
grid_line_cap	('butt', 'round', 'square') The line cap of the Grid lines.
grid_line_color	The line color of the Grid lines.
grid_line_dash	The line dash of the Grid lines.
grid_line_dash_offset	The line dash offset of the Grid lines.

`grid_line_join` ('miter', 'round', 'bevel') The line join of the Grid lines.
`grid_line_width`
 The line width of the Grid lines.
`minor_grid_line_alpha`
 The line alpha of the minor Grid lines.
`minor_grid_line_cap`
 ('butt', 'round', 'square') The line cap of the minor Grid lines.
`minor_grid_line_color`
 The line color of the minor Grid lines.
`minor_grid_line_dash`
 The line dash of the minor Grid lines.
`minor_grid_line_dash_offset`
 The line dash offset of the minor Grid lines.
`minor_grid_line_join`
 ('miter', 'round', 'bevel') The line join of the minor Grid lines.
`minor_grid_line_width`
 The line width of the minor Grid lines.
`pars` optionally specify a named list of all parameters - useful when dealing with theme lists

Examples

```

# manually specify a ggplot-like grid and background
figure() %>%
  ly_points(1:10) %>%
  theme_plot(background_fill_color = "#E6E6E6",
             outline_line_color = "white") %>%
  theme_grid(c("x", "y"), grid_line_color = "white",
            minor_grid_line_color = "white",
            minor_grid_line_alpha = 0.4) %>%
  theme_axis(c("x", "y"), axis_line_color = "white",
            major_label_text_color = "#7F7F7F",
            major_tick_line_color = "#7F7F7F",
            minor_tick_line_alpha = 0, num_minor_ticks = 2)

# or use the built in ggplot theme (under development)
figure(data = iris, legend = "top_left", tools = NULL) %>%
  ly_points(Sepal.Length, Petal.Length, color = Species) %>%
  set_theme(bk_ggplot_theme)

## Not run:
# or to set the theme for all future plots
options(bokeh_theme = bk_ggplot_theme)

figure() %>%
  ly_points(1:10)

figure() %>%
  ly_boxplot(1:10)

```

```
## End(Not run)
```

theme_legend	<i>Override theme parameters for legend attributes</i>
--------------	--

Description

Override theme parameters for legend attributes

Usage

```
theme_legend(fig, background_fill_alpha = 0.95,
             background_fill_color = "#fff", border_line_alpha = 0.5,
             border_line_cap = "butt", border_line_color = "black",
             border_line_dash = NULL, border_line_dash_offset = 0,
             border_line_join = "miter", border_line_width = 1, glyph_height = 20,
             glyph_width = 20, label_height = 20, label_standoff = 15,
             label_text_align = "left", label_text_alpha = 1,
             label_text_baseline = "bottom", label_text_color = "#444444",
             label_text_font = "Helvetica", label_text_font_size = "12pt",
             label_text_font_style = "normal", label_width = 50, legend_padding = 10,
             legend_spacing = 3, pars = NULL)
```

Arguments

fig	figure to modify
background_fill_alpha	(numeric) background color alpha of plot
background_fill_color	(color) background color of plot
border_line_alpha	The line alpha for the legend border outline.
border_line_cap	('butt', 'round', 'square') The line cap for the legend border outline.
border_line_color	The line color for the legend border outline.
border_line_dash	The line dash for the legend border outline.
border_line_dash_offset	The line dash offset for the legend border outline.
border_line_join	('miter', 'round', 'bevel') The line join for the legend border outline.
border_line_width	The line width for the legend border outline.

glyph_height	The height (in pixels) that the rendered legend glyph should occupy.
glyph_width	The width (in pixels) that the rendered legend glyph should occupy.
label_height	The height (in pixels) of the area that legend labels should occupy.
label_standoff	The distance (in pixels) to separate the label from its associated glyph.
label_text_align	(<code>'left'</code> , <code>'right'</code> , <code>'center'</code>) The text align for the legend labels.
label_text_alpha	The text alpha for the legend labels.
label_text_baseline	(<code>'top'</code> , <code>'middle'</code> , <code>'bottom'</code> , <code>'alphabetic'</code> , <code>'hanging'</code>) The text baseline for the legend labels.
label_text_color	The text color for the legend labels.
label_text_font	The text font for the legend labels.
label_text_font_size	The text font size for the legend labels.
label_text_font_style	(<code>'normal'</code> , <code>'italic'</code> , <code>'bold'</code>) The text font style for the legend labels.
label_width	The width (in pixels) of the area that legend labels should occupy.
legend_padding	Amount of padding around the legend.
legend_spacing	Amount of spacing between legend entries.
pars	optionally specify a named list of all parameters - useful when dealing with theme lists

Examples

```
figure(legend_location = "top_left") %>%
  ly_points(1:10, legend = "a") %>%
  theme_legend(border_line_width = 2)
```

theme_plot

Override theme parameters for general plot attributes

Description

Override theme parameters for general plot attributes

Usage

```
theme_plot(fig, pars = NULL, background_fill_color = "white",
           background_fill_alpha = 1, border_fill_color = "white",
           border_fill_alpha = 1, outline_line_alpha = 1,
           outline_line_cap = "butt", outline_line_color = "black",
           outline_line_dash = NULL, outline_line_dash_offset = 0,
           outline_line_join = "miter", outline_line_width = 1, min_border = 50,
           min_border_bottom = 50, min_border_left = 50, min_border_right = 50,
           min_border_top = 50)
```

Arguments

<code>fig</code>	figure to modify
<code>pars</code>	optionally specify a named list of all parameters - useful when dealing with theme lists
<code>background_fill_color</code>	(color) background color of plot
<code>background_fill_alpha</code>	(numeric) background color alpha of plot
<code>border_fill_color</code>	(color) fill color of border area of plot
<code>border_fill_alpha</code>	(numeric) fill color alpha of border area of plot
<code>outline_line_alpha</code>	(numeric) The line alpha for the plot border outline.
<code>outline_line_cap</code>	('butt', 'round', 'square') The line cap for the plot border outline.
<code>outline_line_color</code>	(color) The line color for the plot border outline.
<code>outline_line_dash</code>	The line dash for the plot border outline.
<code>outline_line_dash_offset</code>	(integer) The line dash offset for the plot border outline.
<code>outline_line_join</code>	('miter', 'round', 'bevel') The line join for the plot border outline.
<code>outline_line_width</code>	(integer) The line width for the plot border outline.
<code>min_border</code>	(integer) A convenience property to set all all the <code>min_X_border</code> properties to the same value. If an individual border property is explicitly set, it will override <code>min_border</code> .
<code>min_border_bottom</code>	(integer) Minimum size in pixels of the padding region below the bottom of the central plot region. This is a minimum. The padding region may expand as needed to accommodate titles or axes, etc.

`min_border_left` (integer) Minimum size in pixels of the padding region to the left of the central plot region. This is a minimum. The padding region may expand as needed to accommodate titles or axes, etc.

`min_border_right` (integer) Minimum size in pixels of the padding region to the right of the central plot region. This is a minimum. The padding region may expand as needed to accommodate titles or axes, etc.

`min_border_top` (integer) Minimum size in pixels of the padding region above the top of the central plot region. This is a minimum. The padding region may expand as needed to accommodate titles or axes, etc.

Examples

```
# manually specify a ggplot-like grid and background
figure() %>%
  ly_points(1:10) %>%
  theme_plot(background_fill_color = "#E6E6E6",
             outline_line_color = "white") %>%
  theme_grid(c("x", "y"), grid_line_color = "white",
            minor_grid_line_color = "white",
            minor_grid_line_alpha = 0.4) %>%
  theme_axis(c("x", "y"), axis_line_color = "white",
            major_label_text_color = "#7F7F7F",
            major_tick_line_color = "#7F7F7F",
            minor_tick_line_alpha = 0, num_minor_ticks = 2)

# or use the built in ggplot theme (under development)
figure(data = iris, legend = "top_left", tools = NULL) %>%
  ly_points(Sepal.Length, Petal.Length, color = Species) %>%
  set_theme(bk_ggplot_theme)

## Not run:
# or to set the theme for all future plots
options(bokeh_theme = bk_ggplot_theme)

figure() %>%
  ly_points(1:10)

figure() %>%
  ly_boxplot(1:10)

## End(Not run)
```

Description

Override theme parameters for general plot attributes

Usage

```
theme_title(fig, pars = NULL, background_fill_color = "white",
            background_fill_alpha = 1, border_fill_color = "white",
            border_fill_alpha = 1, text_align = "left", text_alpha = 1,
            text_baseline = "bottom", text_color = "#444444",
            text_font = "Helvetica", text_font_size = "12pt",
            text_font_style = "normal")
```

Arguments

fig	figure to modify
pars	optionally specify a named list of all parameters - useful when dealing with theme lists
background_fill_color	(color) background color of plot
background_fill_alpha	(numeric) background color alpha of plot
border_fill_color	(color) fill color of border area of plot
border_fill_alpha	(numeric) fill color alpha of border area of plot
text_align	('left', 'right', 'center') The text align for the plot title.
text_alpha	The text alpha for the plot title.
text_baseline	('top', 'middle', 'bottom', 'alphabetic', 'hanging') The text baseline for the plot title.
text_color	(color) The text color for the plot title.
text_font	(string) The text font for the plot title.
text_font_size	(string - e.g. '12pt') The text font size for the plot title.
text_font_style	('normal', 'italic', 'bold') The text font style for the plot title.

Examples

```
figure(title = "asdf") %>%
  ly_points(1:10) %>%
  theme_title(text_color = "red")
```

tool_box_select	<i>Add "box_select" tool to a Bokeh figure</i>
-----------------	--

Description

Add "box_select" tool to a Bokeh figure

Usage

```
tool_box_select(fig, callback = NULL, ref_layer = NULL,
  line_color = "black", line_alpha = 1, fill_color = "lightgrey",
  fill_alpha = 0.5, line_width = 2, line_dash = c(4, 4),
  level = "overlay")
```

Arguments

fig	figure to modify
callback	a callback to be applied to this tool - either a character string of javascript code or any one of debug_callback , shiny_callback , console_callback , custom_callback
ref_layer	name of the layer that the callback should be applied to
line_color, line_alpha, fill_color, fill_alpha, line_width, line_dash, level	parameters to control the look of the selection bounding region

Note

Tools can be easily specified as a vector of tool names in the `tools` argument when instantiating a [figure](#). In this case, they are added with defaults. Explicitly calling these `tool_` functions will manually add the tool to a figure and allow additional specification of parameters.

See Also

Other tools: [tool_box_zoom](#), [tool_crosshair](#), [tool_hover](#), [tool_lasso_select](#), [tool_pan](#), [tool_reset](#), [tool_resize](#), [tool_save](#), [tool_tap](#), [tool_wheel_zoom](#)

Examples

```
figure() %>% ly_points(1:10) %>%
  tool_box_select()
```

tool_box_zoom	<i>Add "box_zoom" tool to a Bokeh figure</i>
---------------	--

Description

Add "box_zoom" tool to a Bokeh figure

Usage

```
tool_box_zoom(fig, line_color = "black", line_alpha = 1,  
             fill_color = "lightgrey", fill_alpha = 0.5, line_width = 2,  
             line_dash = c(4, 4), level = "overlay")
```

Arguments

`fig` figure to modify
`line_color`, `line_alpha`, `fill_color`, `fill_alpha`, `line_width`, `line_dash`, `level`
parameters to control the look of the selection bounding region

Note

Tools can be easily specified as a vector of tool names in the `tools` argument when instantiating a [figure](#). In this case, they are added with defaults. Explicitly calling these `tool_` functions will manually add the tool to a figure and allow additional specification of parameters.

See Also

Other tools: [tool_box_select](#), [tool_crosshair](#), [tool_hover](#), [tool_lasso_select](#), [tool_pan](#), [tool_reset](#), [tool_resize](#), [tool_save](#), [tool_tap](#), [tool_wheel_zoom](#)

Examples

```
figure() %>% ly_points(1:10) %>%  
  tool_box_zoom()
```

tool_crosshair	<i>Add "crosshair" tool to a Bokeh figure</i>
----------------	---

Description

Add "crosshair" tool to a Bokeh figure

Usage

```
tool_crosshair(fig)
```

Arguments

fig figure to modify

Note

Tools can be easily specified as a vector of tool names in the `tools` argument when instantiating a `figure`. In this case, they are added with defaults. Explicitly calling these `tool_` functions will manually add the tool to a figure and allow additional specification of parameters.

See Also

Other tools: [tool_box_select](#), [tool_box_zoom](#), [tool_hover](#), [tool_lasso_select](#), [tool_pan](#), [tool_reset](#), [tool_resize](#), [tool_save](#), [tool_tap](#), [tool_wheel_zoom](#)

Examples

```
figure() %>% ly_points(1:10) %>%
  tool_crosshair()
```

tool_hover	<i>Add "hover" tool to a Bokeh figure</i>
------------	---

Description

Add "hover" tool to a Bokeh figure

Usage

```
tool_hover(fig, callback, ref_layer)
```

Arguments

fig figure to modify

callback a callback to be applied to this tool - either a character string of javascript code or any one of [debug_callback](#), [shiny_callback](#), [console_callback](#), [custom_callback](#)

ref_layer name of the layer that the callback should be applied to

Note

Tools can be easily specified as a vector of tool names in the `tools` argument when instantiating a `figure`. In this case, they are added with defaults. Explicitly calling these `tool_` functions will manually add the tool to a figure and allow additional specification of parameters.

See Also

Other tools: [tool_box_select](#), [tool_box_zoom](#), [tool_crosshair](#), [tool_lasso_select](#), [tool_pan](#), [tool_reset](#), [tool_resize](#), [tool_save](#), [tool_tap](#), [tool_wheel_zoom](#)

Examples

```
# hover over the blue points and make the orange points move
figure(title = "hover a blue point") %>%
  ly_points(1:10, lname = "blue", lgroup = "g1") %>%
  ly_points(2:12, lname = "orange", lgroup = "g1") %>%
  tool_hover(custom_callback(
    code = "debugger;if(cb_data.index['1d'].indices.length > 0)
    orange_data.get('data').x[cb_data.index['1d'].indices] += 0.1
    orange_data.trigger('change')", "orange"), "blue")
```

tool_lasso_select	Add "lasso_select" tool to a Bokeh figure
-------------------	---

Description

Add "lasso_select" tool to a Bokeh figure

Usage

```
tool_lasso_select(fig, callback = NULL, ref_layer = NULL,
  line_color = "black", line_alpha = 1, fill_color = "lightgrey",
  fill_alpha = 0.5, line_width = 2, line_dash = c(4, 4),
  level = "overlay")
```

Arguments

fig	figure to modify
callback	a callback to be applied to this tool - either a character string of javascript code or any one of debug_callback , shiny_callback , console_callback , custom_callback
ref_layer	name of the layer that the callback should be applied to
line_color, line_alpha, fill_color, fill_alpha, line_width, line_dash, level	parameters to control the look of the selection bounding region

Note

Tools can be easily specified as a vector of tool names in the `tools` argument when instantiating a [figure](#). In this case, they are added with defaults. Explicitly calling these `tool_` functions will manually add the tool to a figure and allow additional specification of parameters.

See Also

Other tools: [tool_box_select](#), [tool_box_zoom](#), [tool_crosshair](#), [tool_hover](#), [tool_pan](#), [tool_reset](#), [tool_resize](#), [tool_save](#), [tool_tap](#), [tool_wheel_zoom](#)

Examples

```
figure() %>% ly_points(1:10) %>%  
  tool_lasso_select()
```

tool_pan	<i>Add "pan" tool to a Bokeh figure</i>
----------	---

Description

Add "pan" tool to a Bokeh figure

Usage

```
tool_pan(fig, dimensions = c("width", "height"))
```

Arguments

fig	figure to modify
dimensions	a vector specifying whether the pan tool should pan with respect to the x axis ("width") and the y axis ("height") or both (c("width", "height"))

Note

Tools can be easily specified as a vector of tool names in the `tools` argument when instantiating a [figure](#). In this case, they are added with defaults. Explicitly calling these `tool_` functions will manually add the tool to a figure and allow additional specification of parameters.

See Also

Other tools: [tool_box_select](#), [tool_box_zoom](#), [tool_crosshair](#), [tool_hover](#), [tool_lasso_select](#), [tool_reset](#), [tool_resize](#), [tool_save](#), [tool_tap](#), [tool_wheel_zoom](#)

Examples

```
# only pan on x axis  
figure() %>% ly_points(1:10) %>%  
  tool_pan(dimensions = "height")
```

tool_reset	<i>Add "reset" tool to a Bokeh figure</i>
------------	---

Description

Add "reset" tool to a Bokeh figure

Usage

```
tool_reset(fig)
```

Arguments

fig figure to modify

Note

Tools can be easily specified as a vector of tool names in the `tools` argument when instantiating a [figure](#). In this case, they are added with defaults. Explicitly calling these `tool_` functions will manually add the tool to a figure and allow additional specification of parameters.

See Also

Other tools: [tool_box_select](#), [tool_box_zoom](#), [tool_crosshair](#), [tool_hover](#), [tool_lasso_select](#), [tool_pan](#), [tool_resize](#), [tool_save](#), [tool_tap](#), [tool_wheel_zoom](#)

Examples

```
figure() %>% ly_points(1:10) %>%  
  tool_reset()
```

tool_resize	<i>Add "resize" tool to a Bokeh figure</i>
-------------	--

Description

Add "resize" tool to a Bokeh figure

Usage

```
tool_resize(fig)
```

Arguments

fig figure to modify

Note

Tools can be easily specified as a vector of tool names in the `tools` argument when instantiating a `figure`. In this case, they are added with defaults. Explicitly calling these `tool_` functions will manually add the tool to a figure and allow additional specification of parameters.

See Also

Other tools: [tool_box_select](#), [tool_box_zoom](#), [tool_crosshair](#), [tool_hover](#), [tool_lasso_select](#), [tool_pan](#), [tool_reset](#), [tool_save](#), [tool_tap](#), [tool_wheel_zoom](#)

Examples

```
figure() %>% ly_points(1:10) %>%
  tool_resize()
```

tool_save	<i>Add "save" tool to a Bokeh figure</i>
-----------	--

Description

Add "save" tool to a Bokeh figure

Usage

```
tool_save(fig)
```

Arguments

`fig` figure to modify

Note

Tools can be easily specified as a vector of tool names in the `tools` argument when instantiating a `figure`. In this case, they are added with defaults. Explicitly calling these `tool_` functions will manually add the tool to a figure and allow additional specification of parameters.

See Also

Other tools: [tool_box_select](#), [tool_box_zoom](#), [tool_crosshair](#), [tool_hover](#), [tool_lasso_select](#), [tool_pan](#), [tool_reset](#), [tool_resize](#), [tool_tap](#), [tool_wheel_zoom](#)

Examples

```
figure() %>% ly_points(1:10) %>%
  tool_save()
```

tool_selection	<i>Add "selection" tool callback to a Bokeh figure</i>
----------------	--

Description

This adds a selection callback to be used with the box select or lasso select tools.

Usage

```
tool_selection(fig, callback, ref_layer)
```

Arguments

fig	figure to modify
callback	a callback to be applied to this tool - either a character string of javascript code or any one of debug_callback , shiny_callback , console_callback , custom_callback
ref_layer	name of the layer that the callback should be applied to

tool_tap	<i>Add "tap" tool to a Bokeh figure</i>
----------	---

Description

Add "tap" tool to a Bokeh figure

Usage

```
tool_tap(fig, callback, ref_layer)
```

Arguments

fig	figure to modify
callback	a callback to be applied to this tool - either a character string of javascript code or any one of debug_callback , shiny_callback , console_callback , custom_callback
ref_layer	name of the layer that the callback should be applied to

Note

Tools can be easily specified as a vector of tool names in the `tools` argument when instantiating a [figure](#). In this case, they are added with defaults. Explicitly calling these `tool_` functions will manually add the tool to a figure and allow additional specification of parameters.

See Also

Other tools: [tool_box_select](#), [tool_box_zoom](#), [tool_crosshair](#), [tool_hover](#), [tool_lasso_select](#), [tool_pan](#), [tool_reset](#), [tool_resize](#), [tool_save](#), [tool_wheel_zoom](#)

Examples

```
figure() %>%
  ly_points(1:10, lname = "points") %>%
  tool_tap(debug_callback("points"), "points")
```

tool_wheel_zoom	<i>Add "wheel_zoom" tool to a Bokeh figure</i>
-----------------	--

Description

Add "wheel_zoom" tool to a Bokeh figure

Usage

```
tool_wheel_zoom(fig, dimensions = c("width", "height"))
```

Arguments

fig	figure to modify
dimensions	a vector specifying whether the wheel_zoom tool should zoom with respect to the x axis ("width") and the y axis ("height") or both (c("width", "height"))

Note

Tools can be easily specified as a vector of tool names in the tools argument when instantiating a [figure](#). In this case, they are added with defaults. Explicitly calling these tool_ functions will manually add the tool to a figure and allow additional specification of parameters.

See Also

Other tools: [tool_box_select](#), [tool_box_zoom](#), [tool_crosshair](#), [tool_hover](#), [tool_lasso_select](#), [tool_pan](#), [tool_reset](#), [tool_resize](#), [tool_save](#), [tool_tap](#)

Examples

```
# only zoom on x axis
figure() %>% ly_points(1:10) %>%
  tool_wheel_zoom(dimensions = "height")
```

 widget2gist

Export htmlwidget plot to a gist

Description

Export htmlwidget plot to a gist

Usage

```
widget2gist(widget_string, name, created = NULL, description = "",
  license = c("none", "apache-2.0", "bsd-2-clause", "bsd-3-clause",
    "cc-by-4.0", "cc-by-nc-4.0", "cc-by-nc-nd-4.0", "cc-by-nc-sa-4.0",
    "cc-by-nd-4.0", "cc-by-sa-4.0", "cddl-1.0", "ep1-1.0", "gpl-2.0", "gpl-3.0",
    "lgpl-2.1", "lgpl-3.0", "mit", "mpl-2.0"), border = TRUE,
  scrolling = FALSE, secure = TRUE, view = TRUE)
```

Arguments

widget_string	a string containing R code to create an htmlwidget
name	name of the gist
created	optional string for a "Created by" to precede the README
description	optional text to go in README.md to describe the gist
license	license under which gist is released - one of those accepted here: http://bl.ocks.org/licenses.txt
border	should the bl.ocks.org iframe have a border?
scrolling	should the bl.ocks.org iframe scroll?
secure	should https be used for cdn links?
view	should the resulting gist be opened in the browser on bl.ocks.org?

Note

This requires that you have a github personal access token stored as an environment variable GITHUB_PAT. See [gist_create](#) for more information.

Also note that this currently can't handle thumbnails but we are looking into ways to do that.

Examples

```
## Not run:
widget2gist("figure() %>% ly_points(1:10)", name = "test")

## End(Not run)
```

widget2png	<i>Make a static png file for an htmlwidget</i>
------------	---

Description

Make a static png file for an htmlwidget

Usage

```
widget2png(p, file, timeout = 500)
```

Arguments

p	htmlwidget object
file	where to save png file
timeout	plot render timeout in milliseconds (see details)

Details

This uses phantomjs (<http://phantomjs.org>) to render your htmlwidget in a headless browser and take a screenshot of it, creating a static output. This assumes that phantomjs has been installed on your machine and is available as a system call. For plots that take longer to load and render, you may need to increase the value of timeout. Note that this function is experimental.

Examples

```
figure(tools = NULL) %>%
  ly_points(1:10) %>%
  widget2png("/tmp/test.png")
```

x_axis	<i>Customize x axis of a Bokeh figure</i>
--------	---

Description

Customize x axis of a Bokeh figure

Usage

```
x_axis(fig, label, position = "below", log = FALSE, grid = TRUE,
  desired_num_ticks = NULL, num_minor_ticks = 5, visible = TRUE,
  number_formatter = c("basic", "numeral", "printf"), power_limit_high = 5,
  power_limit_low = -3, precision = NULL, use_scientific = TRUE,
  format = NULL)
```

Arguments

fig	figure to modify
label	axis label
position	where to place the axis (either "above" or "below")
log	logical or integer - if TRUE, a log axis with base 10 is used - if an integer, a log axis with base of that integer will be used
grid	logical - should a reference grid be shown for this axis?
desired_num_ticks	desired target number of major tick positions to generate across the plot range
num_minor_ticks	number of minor ticks
visible	should axis be shown?
number_formatter	Bokeh numeric tick label formatter (" basic ", " numeral ", or " printf "); ignored if log is TRUE
power_limit_high	(int) Limit the use of scientific notation to when $\log(x) \geq$ value. Only applicable when number_formatter is "basic".
power_limit_low	(int) Limit the use of scientific notation to when $\log(x) \leq$ value. Only applicable when number_formatter is "basic".
precision	(int) How many digits of precision to display in tick labels. Automatically determined if not specified. Only applicable when number_formatter is "basic".
use_scientific	(logical) Whether to ever display scientific notation. If True, then when to use scientific notation is controlled by power_limit_low and power_limit_high. Only applicable when number_formatter is "basic".
format	Specification of format options. Specification depends on the value of number_formatter - see "details" below.

Details

format parameter: When number_formatter is "basic" and the axis type is datetime, format specifies how to display tick values from a continuous range as formatted datetimes. See [DatetimeTickFormatter](#) When number_formatter is "numeral", format specifies a human-readable format string. See [NumeralTickFormatter](#). When number_formatter is "printf", format is a printf-style format string. See [PrintfTickFormatter](#).

See Also

Other axes: [y_axis](#)

Examples

```

figure() %>%
  ly_points(rexp(1000), rexp(1000)) %>%
  x_axis(label = "x", log = TRUE) %>%
  y_axis(label = "y", log = TRUE)

figure() %>%
  ly_points(2 ^ (1:10)) %>%
  y_axis(log = 2)

# disable scientific tick labels
figure() %>%
  ly_points(rnorm(10), rnorm(10) / 1000) %>%
  y_axis(use_scientific = FALSE)

# specify datetime tick labels
# the appropriate datetime units are automatically chosen
big_range <- seq(as.Date("2012-01-01"), as.Date("2012-12-31"), by = "days")
small_range <- seq(as.Date("2012-01-01"), as.Date("2012-02-01"), by = "days")

figure() %>%
  ly_lines(big_range, rnorm(366)) %>%
  x_axis(label = "Date", format = list(months = "%b-%Y", days = "%d"))

figure() %>%
  ly_lines(small_range, rnorm(32)) %>%
  x_axis(label = "Date", format = list(months = "%b-%Y", days = "%d"))

# specify numeric tick labels
figure() %>%
  ly_points(rnorm(10), rnorm(10) * 10000) %>%
  y_axis(number_formatter = "numeral", format = "0,000")

figure() %>%
  ly_points(rnorm(10), rnorm(10) * 100) %>%
  y_axis(number_formatter = "printf", format = "%0.1f%")

```

x_range*Update x axis range in a Bokeh figure*

Description

Update x axis range in a Bokeh figure

Usage`x_range(fig, dat = NULL, callback = NULL)`

Arguments

fig	figure to modify
dat	either a vector (min, max) if the axis is numeric, or a vector of values if the axis is categorical. In the latter case, the order in which the values are supplied is how they will be arranged on the axis.
callback	TODO

See Also

Other ranges: [y_range](#)

Examples

```
# get data from Duluth site in 'barley' data
du <- subset(lattice::barley, site == "Duluth")

# plot with default ranges
p <- figure(width = 600) %>%
  ly_points(yield, variety, color = year, data = du)
p
# y axis is alphabetical

# manually set x and y axis (y in order of 1932 yield)
p %>%
  x_range(c(20, 40)) %>%
  y_range(du$variety[order(subset(du, year == 1932)$yield)])
```

y_axis

Customize x axis of a Bokeh figure

Description

Customize x axis of a Bokeh figure

Usage

```
y_axis(fig, label, position = "left", log = FALSE, grid = TRUE,
  desired_num_ticks = NULL, num_minor_ticks = 5, visible = TRUE,
  number_formatter = c("basic", "numeral", "printf"), power_limit_high = 5,
  power_limit_low = -3, precision = NULL, use_scientific = TRUE,
  format = NULL)
```

Arguments

fig	figure to modify
label	axis label
position	where to place the axis (either "left" or "right")
log	logical or integer - if TRUE, a log axis with base 10 is used - if an integer, a log axis with base of that integer will be used
grid	logical - should a reference grid be shown for this axis?
desired_num_ticks	desired target number of major tick positions to generate across the plot range
num_minor_ticks	number of minor ticks
visible	should axis be shown?
number_formatter	Bokeh numeric tick label formatter ("basic", "numeral", or "printf"); ignored if log is TRUE
power_limit_high	(int) Limit the use of scientific notation to when $\log(x) \geq$ value. Only applicable when number_formatter is "basic".
power_limit_low	(int) Limit the use of scientific notation to when $\log(x) \leq$ value. Only applicable when number_formatter is "basic".
precision	(int) How many digits of precision to display in tick labels. Automatically determined if not specified. Only applicable when number_formatter is "basic".
use_scientific	(logical) Whether to ever display scientific notation. If True, then when to use scientific notation is controlled by power_limit_low and power_limit_high. Only applicable when number_formatter is "basic".
format	Specification of format options. Specification depends on the value of number_formatter - see "details" below.

See Also

Other axes: [x_axis](#)

Examples

```
figure() %>%
  ly_points(rexp(1000), rexp(1000)) %>%
  x_axis(label = "x", log = TRUE) %>%
  y_axis(label = "y", log = TRUE)
```

```
figure() %>%
  ly_points(2 ^ (1:10)) %>%
  y_axis(log = 2)
```

```
# disable scientific tick labels
figure() %>%
```

```

ly_points(rnorm(10), rnorm(10) / 1000) %>%
y_axis(use_scientific = FALSE)

# specify datetime tick labels
# the appropriate datetime units are automatically chosen
big_range <- seq(as.Date("2012-01-01"), as.Date("2012-12-31"), by = "days")
small_range <- seq(as.Date("2012-01-01"), as.Date("2012-02-01"), by = "days")

figure() %>%
  ly_lines(big_range, rnorm(366)) %>%
  x_axis(label = "Date", format = list(months = "%b-%Y", days = "%d"))

figure() %>%
  ly_lines(small_range, rnorm(32)) %>%
  x_axis(label = "Date", format = list(months = "%b-%Y", days = "%d"))

# specify numeric tick labels
figure() %>%
  ly_points(rnorm(10), rnorm(10) * 10000) %>%
  y_axis(number_formatter = "numeral", format = "0,000")

figure() %>%
  ly_points(rnorm(10), rnorm(10) * 100) %>%
  y_axis(number_formatter = "printf", format = "%0.1f%")

```

y_range

Update y axis range in a Bokeh figure

Description

Update y axis range in a Bokeh figure

Usage

```
y_range(fig, dat = NULL, callback = NULL)
```

Arguments

fig	figure to modify
dat	either a vector (min, max) if the axis is numeric, or a vector of values if the axis is categorical. In the latter case, the order in which the values are supplied is how they will be arranged on the axis.
callback	TODO

See Also

Other ranges: [x_range](#)

Examples

```
# get data from Duluth site in 'barley' data
du <- subset(lattice::barley, site == "Duluth")

# plot with default ranges
p <- figure(width = 600) %>%
  ly_points(yield, variety, color = year, data = du)
p
# y axis is alphabetical

# manually set x and y axis (y in order of 1932 yield)
p %>%
  x_range(c(20, 40)) %>%
  y_range(du$variety[order(subset(du, year == 1932)$yield)])
```

%>%

Pipe figures

Description

Pipe figures

Arguments

lhs	a Bokeh figure
rhs	a layer to add to the figure

Index

- *Topic **data**
 - elements, 8
 - flightfreq, 12
 - nyctaxihex, 72
- %>%, 108

- b_eval, 5
- bk_default_theme, 4
- bk_ggplot_theme (bk_default_theme), 4
- bokeh_render_json, 4
- boxplot.stats, 31

- cat, 74
- catjitter, 5
- colorRampPalette, 73
- console_callback, 6, 92, 94, 95, 99
- contourLines, 33
- curve, 37
- custom_callback, 6, 8, 81, 92, 94, 95, 99

- data_name_list, 7
- debug_callback, 6, 7, 92, 94, 95, 99
- density, 39

- elements, 8

- figure, 9, 14, 92–100
- figure_data, 11
- flightfreq, 12

- get_object_refs, 12
- gist_create, 101
- gmap, 11, 13, 15
- gmap_style, 13, 14, 14
- grid.hexagons, 40
- grid_plot, 11, 15

- hexbin, 40
- hist, 41

- ly_abline, 11, 18, 22, 24, 26, 28, 30, 32, 34, 36, 38, 40, 42–44, 46, 49, 50, 52, 54, 56, 58, 60, 62, 63, 66–68, 72
- ly_annular_wedge, 11, 19, 19, 24, 26, 28, 30, 32, 34, 36, 38, 40, 42–44, 46, 49, 50, 52, 54, 56, 58, 60, 62, 63, 66–68, 72
- ly_annulus, 11, 19, 22, 22, 26, 28, 30, 32, 34, 36, 38, 40, 42–44, 46, 49, 50, 52, 54, 56, 58, 60, 62, 63, 66–68, 72
- ly_arc, 11, 19, 22, 24, 24, 28, 30, 32, 34, 36, 38, 40, 42–44, 46, 49, 50, 52, 54, 56, 58, 60, 62, 63, 66–68, 72
- ly_bar, 19, 22, 24, 26, 26, 30, 32, 34, 36, 38, 40, 42–44, 46, 49, 50, 52, 54, 56, 58, 60, 62, 63, 66–68, 72
- ly_bezier, 11, 19, 22, 24, 26, 28, 29, 32, 34, 36, 38, 40, 42–44, 46, 49, 50, 52, 54, 56, 58, 60, 62, 63, 66–68, 72
- ly_boxplot, 11, 19, 22, 24, 26, 28, 30, 31, 34, 36, 38, 40, 42–44, 46, 49, 50, 52, 54, 56, 58, 60, 62, 63, 66–68, 72
- ly_contour, 11, 19, 22, 24, 26, 28, 30, 32, 33, 36, 38, 40, 42–44, 46, 49, 50, 52, 54, 56, 58, 60, 62, 63, 66–68, 72
- ly_crect, 11, 19, 22, 24, 26, 28, 30, 32, 34, 34, 38, 40, 42–44, 46, 49, 50, 52, 54, 56, 58, 60, 62, 63, 66–68, 72
- ly_curve, 11, 19, 22, 24, 26, 28, 30, 32, 34, 36, 37, 40, 42–44, 46, 49, 50, 52, 54, 56, 58, 60, 62, 63, 66–68, 72
- ly_density, 11, 19, 22, 24, 26, 28, 30, 32, 34, 36, 38, 39, 42–44, 46, 49, 50, 52, 54, 56, 58, 60, 62, 63, 66–68, 72
- ly_hexbin, 40
- ly_hist, 11, 19, 22, 24, 26, 28, 30, 32, 34, 36, 38, 40, 41, 43, 44, 46, 49, 50, 52, 54, 56, 58, 60, 62, 63, 66–68, 72
- ly_image, 11, 19, 22, 24, 26, 28, 30, 32, 34, 36, 38, 40, 42, 42, 44, 46, 49, 50, 52,

- 54, 56, 58, 60, 62, 63, 66–68, 72
- ly_image_url, 11, 19, 22, 24, 26, 28, 30, 32, 34, 36, 38, 40, 42, 43, 44, 46, 49, 50, 52, 54, 56, 58, 60, 62, 63, 66–68, 72
- ly_lines, 11, 19, 22, 24, 26, 28, 30, 32, 34, 36, 38, 40, 42–44, 45, 49, 50, 52, 54, 56, 58, 60, 62, 63, 66–68, 72
- ly_map, 11, 19, 22, 24, 26, 28, 31, 32, 34, 36, 38, 40, 42–44, 46, 46, 50, 52, 54, 56, 58, 60, 62, 63, 66–68, 72
- ly_multi_line, 11, 19, 22, 24, 26, 28, 31, 32, 34, 36, 38, 40, 42–44, 46, 49, 49, 52, 54, 56, 58, 60, 62, 63, 66–68, 72
- ly_oval, 11, 19, 22, 24, 26, 28, 31, 32, 34, 36, 38, 40, 42–44, 46, 49, 50, 50, 54, 56, 58, 60, 62, 63, 66–68, 72
- ly_patch, 11, 19, 22, 24, 26, 28, 31, 32, 34, 36, 38, 40, 42–44, 46, 49, 50, 52, 52, 56, 58, 60, 62, 63, 66–68, 72
- ly_points, 11, 19, 22, 24, 26, 28, 31, 32, 34, 36, 38, 40, 42–44, 46, 49, 50, 52, 54, 54, 58, 60, 62, 63, 66–68, 72
- ly_polygons, 11, 19, 22, 24, 26, 28, 31, 32, 34, 36, 38, 40, 42–44, 46, 49, 50, 52, 54, 56, 56, 60, 62, 63, 66–68, 72
- ly_quadratic, 11, 19, 22, 24, 26, 28, 31, 32, 34, 36, 38, 40, 42–44, 46, 49, 50, 52, 54, 56, 58, 58, 62, 63, 66–68, 72
- ly_quantile, 11, 19, 22, 24, 26, 28, 31, 32, 34, 36, 38, 40, 42–44, 46, 49, 50, 52, 54, 56, 58, 60, 60, 63, 66–68, 72
- ly_ray, 11, 19, 22, 24, 26, 28, 31, 32, 34, 36, 38, 40, 42–44, 46, 49, 50, 52, 54, 56, 58, 60, 62, 62, 66–68, 72
- ly_rect, 19, 22, 24, 26, 28, 31, 32, 34, 36, 38, 40, 42–44, 46, 49, 50, 52, 54, 56, 58, 60, 62, 63, 64, 67, 68, 72
- ly_segments, 11, 19, 22, 24, 26, 28, 31, 32, 34, 36, 38, 40, 42–44, 46, 49, 50, 52, 54, 56, 58, 60, 62, 63, 66, 66, 68, 72
- ly_text, 11, 19, 22, 24, 26, 28, 31, 32, 34, 36, 38, 40, 42–44, 46, 49, 50, 52, 54, 56, 58, 60, 62, 63, 66, 67, 67, 72
- ly_wedge, 11, 19, 22, 24, 26, 28, 31, 32, 34, 36, 38, 40, 42–44, 46, 49, 50, 52, 54, 56, 58, 60, 62, 63, 66–68, 69
- map, 47
- nyctaxihex, 72
- pal_bk_glyph (pal_color), 73
- pal_bk_line_dash (pal_color), 73
- pal_bk_line_width (pal_color), 73
- pal_color, 73, 79
- pal_gradient (pal_color), 73
- pal_size (pal_color), 73
- pal_tableau (pal_color), 73
- par, 18, 19, 25, 30, 33, 37–39, 45, 46, 49, 50, 59, 63, 66, 67
- phantom_install, 73
- point_types, 54, 74
- print_model_json, 4, 74
- qnorm, 60
- qunif, 60
- rbokeh (rbokeh-package), 3
- rbokeh-package, 3
- rbokeh2html, 75
- rbokehOutput, 75, 77
- renderRbokeh, 77
- set_palette, 77
- set_theme, 79
- shiny_callback, 80, 92, 94, 95, 99
- sub_names, 81
- theme_axis, 81
- theme_grid, 85
- theme_legend, 87
- theme_plot, 11, 88
- theme_title, 90
- toJSON, 74
- tool_box_select, 11, 92, 93–98, 100
- tool_box_zoom, 11, 92, 93, 94–98, 100
- tool_crosshair, 11, 92, 93, 93, 95–98, 100
- tool_hover, 92–94, 94, 96–98, 100
- tool_lasso_select, 11, 92–95, 95, 96–98, 100
- tool_pan, 92–96, 96, 97, 98, 100
- tool_reset, 11, 92–96, 97, 98, 100
- tool_resize, 11, 92–97, 97, 98, 100
- tool_save, 11, 92–98, 98, 100
- tool_selection, 99
- tool_tap, 92–98, 99, 100
- tool_wheel_zoom, 11, 92–98, 100, 100
- widget2gist, 101

`widget2png`, [102](#)

`x_axis`, [102](#), [106](#)

`x_range`, [104](#), [107](#)

`y_axis`, [103](#), [105](#)

`y_range`, [105](#), [107](#)