

# Package ‘lessR’

December 7, 2019

**Version** 3.9.0

**Date** 2019-12-07

**Title** Less Code, More Results

**Author** David W. Gerbing, The School of Business, Portland State University

**Maintainer** David W. Gerbing <gerbing@pdx.edu>

**Depends** R (>= 2.15.0)

**Imports** graphics, grDevices, stats, utils, foreign, methods, lattice,  
latticeExtra, robustbase, ellipse, leaps, sas7bdat, openxlsx,  
triangle, png, colorspace, viridisLite, wesanderson, rmarkdown

**Suggests** KernSmooth

**Description** Each function accomplishes the work of several or more standard R functions. For example, two function calls, `Read()` and `CountAll()`, read the data and generate summary statistics for all variables in the data frame, plus histograms and bar charts as appropriate. Other functions provide for descriptive statistics, a comprehensive regression analysis, analysis of variance and t-test, plotting including the introduced here Violin/Box/Scatter plot for a numerical variable, bar chart, histogram, box plot, density curves, calibrated power curve, reading multiple data formats with the same function call, variable labels, color themes, Trellis graphics and a built-in help system. Also includes a confirmatory factor analysis of multiple indicator measurement models, pedagogical routines for data simulation such as for the Central Limit Theorem, and generation and rendering of R markdown instructions for interpretative output.

**License** GPL (>= 2)

**LazyLoad** yes

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2019-12-07 14:50:02 UTC

## R topics documented:

ANOVA . . . . .	3
BarChart . . . . .	7

corCFA	21
corEFA	28
corProp	30
corRead	32
corReflect	33
Correlation	35
corReorder	38
corScree	41
CountAll	43
dataBodyMeas	44
dataCars93	44
dataEmployee	45
dataEmployee_lbl	46
dataJackets	47
dataLearn	47
dataMach4	48
dataMach4_lbl	48
dataReading	49
dataStockPrice	50
Density	51
details	56
factors	58
getColors	59
Help	65
Histogram	67
label	77
LineChart	78
Logit	83
Merge	87
Model	89
Nest	91
PieChart	93
Plot	100
print.out	122
print.out_all	123
prob_norm	123
prob_tcut	125
prob_znorm	126
Read	128
Recode	133
regPlot	135
Regression	137
showColors	147
showPalettes	148
simCImean	149
simCLT	150
simFlips	152
simMeans	153

Sort	154
style	156
Subset	165
SummaryStats	167
to	172
Transform	173
ttest	176
ttestPower	182
values	184
VariableLabels	185
Write	187
xAnd	189
xNum	190
xP	190
xRow	191
xU	192
xW	193

<b>Index</b>	<b>194</b>
--------------	------------

ANOVA

*Analysis of Variance***Description**

Abbreviation: `av`, `av_brief`, `av.brief` [deprecated]

Analysis of variance from the R [aov](#) function plus graphics and effect sizes. Permitted designs are one-way between groups, two-way between groups and randomized blocks with one treatment factor with one observation for each treatment and block combination.

Output is generated into distinct segments by topic, organized and displayed in sequence by default. When the output is assigned to an object, such as a in a `<-reg(Y ~ X)`, the full or partial output can be accessed for later analysis and/or viewing. A primary such analysis is with `knitr` for dynamic report generation, run from R directly or from within RStudio. The input instructions to `knitr` are written comments and interpretation with embedded R code, called R~Markdown. Doing a `knitr` analysis is to "knit" these comments and subsequent output together so that the R output is embedded in the resulting document, either html, pdf or Word, by default with explanation and interpretation. Generate a complete, though preliminary at this time, R Markdown document from the `Rmd` option ready to knit. Simply specify the option with a file name, run the ANOVA function to create the file. Then open the newly created `.Rmd` file in RStudio and click the knit button to create a formatted document that consists of the statistical results and interpretative comments. See the sections arguments, value and examples for more information.

**Usage**

```
ANOVA(my_formula, data=d, filter=NULL,
      brief=getOption("brief"), digits_d=NULL,
      Rmd=NULL, graphics=TRUE,
```

```
rb_points=TRUE, res_rows=NULL, res_sort=c("zresid", "fitted", "off"),
pdf=FALSE, width=5, height=5, fun_call, ...)
```

```
av(...)
```

```
av.brief(..., brief=TRUE)
```

```
av_brief(..., brief=TRUE)
```

## Arguments

<code>my_formula</code>	Standard R <a href="#">formula</a> for specifying a model.
<code>data</code>	The default name of the data frame that contains the data for analysis is <code>d</code> , otherwise explicitly specify.
<code>filter</code>	A logical expression that specifies a subset of rows of the data frame to analyze.
<code>brief</code>	If set to <code>TRUE</code> , reduced text output with no Tukey multiple comparison of means and no residuals. Can change system default with <a href="#">style</a> function.
<code>digits_d</code>	For the Basic Analysis, it provides the number of decimal digits. For the rest of the output, it is a suggestion only.
<code>Rmd</code>	File name for the file of R Markdown instructions to be written, if specified. The file type is <code>.Rmd</code> , which automatically opens in RStudio, but it is a simple text file that can be edited with any text editor, including RStudio.
<code>graphics</code>	Produce graphics. Default is <code>TRUE</code> . In <code>Rmd</code> can be useful to set to <code>FALSE</code> so that <a href="#">regPlot</a> can be used to place the graphics within the output file.
<code>rb_points</code>	For a randomized block design, a plot of the fitted value for each cell is obtained as well as the individual data values. Set to <code>FALSE</code> to suppress the data values.
<code>res_rows</code>	Default is 20, which lists the first 20 rows of data and residuals sorted by the specified sort criterion. To disable residuals, specify a value of 0. To see the residuals output for all observations, specify a value of "all".
<code>res_sort</code>	Default is "zresid", for specifying standardized residuals as the sort criterion for the display of the rows of data and associated residuals. Other values are "fitted" for the fitted values and "off" to not sort the rows of data.
<code>pdf</code>	Indicator as to if the graphic files should be saved as pdf files instead of directed to the standard graphics windows.
<code>width</code>	Width of the pdf file in inches.
<code>height</code>	Height of the pdf file in inches.
<code>fun_call</code>	Function call. Used with <code>Rmd</code> to pass the function call when obtained from the abbreviated function call <code>av</code> .
<code>...</code>	Other parameter values for R function <a href="#">lm</a> which provides the core computations.

## Details

### OVERVIEW

The one-way ANOVA with Tukey HSD and corresponding plot is based on the R functions [aov](#), [TukeyHSD](#), and provides summary statistics for each level. Two-factor ANOVA also provides an

interaction plot of the means with `interaction.plot` as well as a table of means and other summary statistics. The two-factor analysis can be between groups or a randomized blocked design. Residuals are displayed by default. Tukey HSD comparisons and residuals are not displayed if `brief=TRUE`.

The `filter` parameter subsets rows (cases) of the input data frame according to a logical expression. Use the standard R operators for logical statements as described in [Logic](#) such as `&` for and, `|` for or and `!` for not, and use the standard R relational operators as described in [Comparison](#) such as `==` for logical equality `!=` for not equals, and `>` for greater than. See the Examples.

#### MODEL SPECIFICATION

In the following specifications, Y is the response variable, X is a treatment variable and Blocks is the blocking variable. The distinction between the one-way randomized blocks and the two-way between groups models is not the variable names, but rather the delimiter between the variable names. Use `*` to indicate a two-way crossed between groups design and `+` for a randomized blocks design.

one-way between groups: `ANOVA(Y ~ X)`

one-way randomized blocks: `ANOVA(Y ~ X + Blocks)`

two-way between groups: `ANOVA(Y ~ X1 * X2)`

For more complex designs, use the standard R function `avov` upon which ANOVA depends.

#### BALANCED DESIGN

The design for the two-factor analyses must be balanced. A check is performed and processing ceases if not balanced. For unbalanced designs, consider the function `lmer` in the `lme4` package.

#### DECIMAL DIGITS

The number of decimal digits displayed on the output is, by default, the maximum number of decimal digits for all the data values of the response variable. Or, this value can be explicitly specified with the `digits_d` parameter.

### Value

The output can optionally be returned and saved into an R object, otherwise it simply appears at the console. The components of this object are redesigned in `lessR` version 3.3.5 into (a) pieces of text that form the readable output and (b) a variety of statistics. The readable output are character strings such as tables amenable for viewing and interpretation. The statistics are numerical values amenable for further analysis, such as to be referenced in a subsequent R Markdown document. The motivation of these two types of output is to facilitate R markdown documents, as the name of each piece, preceded by the name of the saved object followed by a `$`, can be inserted into the R markdown document (see examples).

#### TEXT OUTPUT

`out_background`: variables in the model, rows of data and retained

1-predictor: `out_descriptive`: descriptive stats

2-predictors: `out_cell.n`: cell sample size

2-predictors: `out_cell.means`: cell means

2-predictors: `out_cell.marginals`: marginal means

2-predictors: `out_cell.gm`: grand mean

2-predictors: `out_cell.sd`: cell standard deviations

`out_anova`: analysis of variance summary table

`out_effects`: effect sizes

`out_hsd`: Tukey's honestly significant different analysis

out\_res: residuals  
 out\_plots: list of plots generated if more than one

Separated from the rest of the text output are the major headings, which can then be deleted from custom collations of the output. out\_title\_bck: BACKGROUND  
 out\_title\_des: DESCRIPTIVE STATISTICS  
 out\_title\_basic: BASIC ANALYSIS  
 out\_title\_res: RESIDUALS

#### STATISTICS

call: function call that generated the analysis  
 formula: model formula that specifies the model  
 n.vars: number of variables in the model  
 n.obs: number of rows of data submitted for analysis  
 n.keep: number of rows of data retained in the analysis  
 residuals: residuals  
 fitted: fitted values

Although not typically needed for analysis, if the output is assigned to an object named, for example, a, then the complete contents of the object can be viewed directly with the `unclass` function, here as `unclass(a)`. Invoking the `class` function on the saved object reveals a class of `out_all`. The class of each of the text pieces of output is `out`.

#### Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

#### References

Gerbing, D. W. (2014). R Data Analysis without Programming, Chapter 7, NY: Routledge.

#### See Also

[aov](#), [TukeyHSD](#), [interaction.plot](#)

#### Examples

```
# access the PlantGrowth data frame
ANOVA(weight ~ group, data=PlantGrowth)
#brief version
av_brief(weight ~ group, data=PlantGrowth)

# drop the second treatment, just control and 1 treatment
ANOVA(weight ~ group, data=PlantGrowth, filter=(group != "trt2"))

# variables of interest in a data frame that is not the default d
# two-factor between-groups ANOVA with replications and interaction
```

```
# warpbreaks is a data set provided with R
ANOVA(breaks ~ wool * tension, data=warpbreaks)

# randomized blocks design with the second term the blocking factor
# use short name
av(breaks ~ wool + tension, data=warpbreaks)
```

---

BarChart

*Bar Chart for One or Two Variables*


---

## Description

Abbreviation: bc

Plots a bar chart, one categorical variable,  $x$  against one numeric variable  $y$ , as well as an optional second categorical variable  $by$  with a provided `legend_`. One option is to enter the reduced data table, which consists of each level of  $x$  paired with the corresponding numerical value of  $y$ , with the number of rows the number of levels. Or, transform the full data table of original measurements. If no value of  $y$  is specified, by default the numeric variable is the computed frequency of values in each category, with default colors for one or two variables, which can be replaced with custom color scales. Or, if a  $y$  variable is specified, obtain the reduced data table from which the bar chart is computed by summarizing the value of  $y$  at each level of  $x$ , such as the mean or a variety of other summary statistics.

Also displays the frequency table for one or two variables, Cramer's  $V$  association, and the corresponding chi-square inferential analysis. For two variables, the frequencies include the joint and marginal frequencies. To activate Trellis graphics specify a `by1` variable. If the provided object to analyze is a set of multiple variables, including an entire data frame, then a bar chart is calculated for each non-numeric variable in the data frame.

## Usage

```
BarChart(x=NULL, y=NULL, by=NULL, data=d, filter=NULL,
         stat=NULL, n_cat=getOption("n_cat"), one_plot=NULL,

         by1=NULL, n_row=NULL, n_col=NULL, aspect="fill",

         horiz=FALSE, beside=FALSE, stack100=FALSE,
         gap=NULL, scale_y=NULL,

         theme=getOption("theme"),
         fill=NULL,
         color=getOption("bar_color_discrete"),
         trans=getOption("trans_bar_fill"),
         fill_split=NULL,

         legend_title=NULL, legend_position="right_margin",
         legend_labels=NULL, legend_horiz=FALSE,
         legend_size=NULL,
```

```

value_labels=NULL,
rotate_x=getOption("rotate_x"),
offset=getOption("offset"),
break_x=NULL, sort=c("0", "-", "+"),

label_max=100, out_size=80,

values=NULL,
values_color=getOption("values_color"),
values_size=getOption("values_size"),
values_digits=getOption("values_digits"),
values_position=getOption("values_position"),
values_cut=NULL,

xlab=NULL, ylab=NULL, main=NULL, sub=NULL,
lab_adj=c(0,0), margin_adj=c(0,0,0,0), add_top=0.05,

add=NULL, x1=NULL, y1=NULL, x2=NULL, y2=NULL,

eval_df=NULL, quiet=getOption("quiet"),
width=6.5, height=6, pdf=FALSE, ...)

```

```
bc(...)
```

### Arguments

- |        |   |
|--------|---|
| x      | Variable(s) to analyze. Can be a single variable, either within a data frame or as a vector in the users workspace, or multiple variables in a data frame such as designated with the <code>c</code> function, or an entire data frame. If not specified, then defaults to all non-numerical variables in the specified data frame, <code>d</code> by default. To manage large category values, unless <code>break_x</code> is <code>FALSE</code> , any space in each category value is converted to new line for the corresponding axis label in the plot. To keep two (small) words on the same line, replace the space that separates them with an underscore, which is converted to a blank for the corresponding axis label. |
| y      | Numeric variable for which the values are displayed on the vertical axis. If specified, then data frame is summary data (i.e., aggregated). See later example to create with R <code>link{aggregate}</code> function. If not specified, then its value is automatically tabulated as the frequency of each category or joint category.  |
| by     | A categorical variable to provide a bar chart for each level of the numeric primary variables <code>x</code> and <code>y</code> on the <i>same</i> plot, which applies to the panels of a Trellis plot if <code>by1</code> is specified.  |
| data   | Optional data frame that contains the variables of interest. Can contain data from which frequencies are computed for the <code>y</code> -values, or can contain values to plot on the <code>y</code> -axis instead of counts.  |
| filter | A logical expression that specifies a subset of rows of the data frame to analyze.  |



stat	Statistical transformation of the data. If no y variable, then "count" or "proportion", otherwise "mean", "sd", etc.
n_cat	When analyzing all the variables in a data frame, specifies the largest number of unique values of variable of a numeric data type for which the variable will be analyzed as a categorical. Default is 0.
one_plot	For bar charts of multiple x-variables, indicates if a bar plot is produced for each x-variable, or all are combined into a single plot, such as for items that all share common responses such as survey data with a common Likert scale across variables. Default is if variables share a common response scale set to TRUE, otherwise FALSE.
by1	A categorical variable called a conditioning variable that activates <b>Trellis graphics</b> , from the lattice package, to provide a separate bar chart (panel) of numeric primary variables x and y for each level of the variable.
n_row	Optional specification for the number of rows in the layout of a multi-panel display with Trellis graphics. Need not specify n_col.
n_col	Optional specification for the number of columns in the layout of a multi-panel display with Trellis graphics. Need not specify n_row. If set to 1, then the strip that labels each group locates to the left of each plot instead of the top.
aspect	Lattice parameter for the aspect ratio of the panels in a Trellis plot (multi-panel display), defined as height divided by width. The default value is "fill" to have the panels expand to occupy as much space as possible. Set to 1 for square panels. Set to "xy" to specify a ratio calculated to "bank" to 45 degrees, that is, with the line slope approximately 45 degrees.
horiz	By default the value is FALSE so bars are vertical, unless one_plot is TRUE.
beside	For a two variable plot, set to TRUE for the levels of the first variable to be plotted as adjacent bars instead of stacked on each other.
stack100	100% stacked bar chart when a by variable is present, also activated by setting stat to "proportion" with a by variable.
gap	Gap between bars. Provides the value of the space option from the standard R <code>barplot</code> function with a default of 0.2 unless two variables are plotted and beside=TRUE, in which case the default is c(1,1).
scale_y	If specified, a vector of three values that define the numerical values of the y-axis, the numerical axis, within the bounds of plot region: starting value, ending value, and number of intervals.
theme	Color theme for this analysis. Make persistent across analyses with <a href="#">style</a> .
fill	Fill color of the bars, override the default with a vector of colors: names, rgb, hex or hcl and many other possibilities from palettes such as viridis. Can generate these colors with pre-defined qualitative, sequential and divergent palettes generated by lessR <a href="#">getColor</a> s, such as "blues". Or set to the name of y to map the values of bar fill into the fill colors. Specified the name of y as (count) if tabulated from the data, or (count.v) for viridis palette. See the details and examples sections. Default is bar_color_discrete from the lessR <a href="#">style</a> function except sequential ordered factors.

color	Border color of the bars, can be a vector to customize the color for each bar. Default is <code>bar_color_discrete</code> from the lessR <a href="#">style</a> function.
trans	Transparency factor of the area of each slice from 0, no transparency to 1, full transparency. Default is <code>trans_bar_fill</code> from the lessR <a href="#">style</a> function.
fill_split	The value of the numeric variable <code>y</code> for which bars that correspond to values of <code>y &lt;= fill_split</code> are displayed in the first fill color and other values displayed in the second fill color, or as specified by a vector of exactly two fill colors.
legend_title	Title of the legend, which is usually set by default except when raw counts are entered as a matrix. Then a title must be specified to generate a legend_
legend_position	When plotting two variables, location of the legend, with the default in the right margin. Additional options from standard R are "topleft", "top", "topright" and others as shown in the help for the <a href="#">legend</a> function.
legend_labels	When plotting two variables, labels for the legend, which by default are the levels for the second or by variable.
legend_horiz	By default the legend is vertical, but can be changed to horizontal.
legend_size	Size of legend text.
value_labels	For factors, default is the factor labels, and for character variables, default is the character values_ Or, provide labels for the x-axis on the graph to override these values_ If the variable is a factor and <code>value_labels</code> is not specified (is NULL), then the <code>value_labels</code> are set to the factor levels with each space replaced by a new line character. If <code>x</code> and <code>y</code> -axes have the same scale, they also apply to the <code>y</code> -axis_ Control the plotted size with <code>axis_cex</code> and <code>axis_x_cex</code> from the lessR <a href="#">style</a> function.
rotate_x	Degrees that the axis values for the category values axis are rotated, usually to accommodate longer values, typically used in conjunction with <code>offset</code> . When equal 90 the value labels are perpendicular to the <code>x</code> -axis and a different algorithm places the labels so that <code>offset</code> is not needed.
offset	The amount of spacing between the axis values and the axis. Default is 0.5. Larger values such as 1.0 create space for the label when longer axis value names are rotated.
break_x	Replace spaces in the category values with a new line and replace underscores with a blank. By default, TRUE for vertical bar charts with <code>rotate_x</code> set to 0, and FALSE otherwise.
sort	Sort the categories by their frequency for one variable and by the column sums if a by variable. Not applicable to Trellis plots. By default "0" for no sort, or sort descending "-" or ascending "+", unless <code>one_plot</code> is TRUE, then is set to "+".
label_max	To improve readability, the maximum size of the value labels before the labels are abbreviated for text output only. Not a literal maximum as preserving unique values may require a larger number of characters than specified.

out_size	To improve the readability of the frequency distribution of a single variable displayed at the console, the maximum number of characters on a line of output at the console for one variable before the frequency distribution is written vertically.
values	If not "off", adds the numerical results to the plot according to the default "%" for tabulated counts and "input" for the input values for a y-variable explicitly provided, unless there are more than 15 levels or y is present and non-integer in which case the default is "off". For tabulated counts, "prop" is also available for proportions as well as "input".
values_color	Color of the plotted text. Could be a vector to specify a unique color for each value. If fewer colors are specified than the number of categories, the colors are recycled.
values_size	Character expansion factor, the size, of the plotted text, for which the default value is 0.95, or 0.9 of value if beside is TRUE and values_position is "in" because bars are narrower.
values_digits	Number of decimal digits for which to display the values_ Default is 0, round to the nearest integer for "%", 2 for "prop", and if "input" and y is entered directly, display the literal value unless > 9999, in which case set to 0.
values_position	Position of the plotted text. Default is inside the bar, or, if "out", as part of the label for each value outside of the bar.
values_cut	Threshold for displaying the value. If values_position equals "out", then default is 0.028 unless there is a by variable or multiple x-variables on the same plot, then default is 0.040
xlab	Label for x-axis_ If xlab is not specified, then the label becomes the name of the corresponding variable label if it exists, or, if not, the variable name. If xy_ticks is FALSE, then no label is displayed. If no y variable is specified, then xlab is set to Index unless xlab has been specified.
ylab	Label for y-axis_ If xlab is not specified, then the label becomes the name of the corresponding variable label if it exists, or, if not, the variable name. If xy_ticks is FALSE, then no label displayed.
main	Label for the title of the graph. Can set size with main_cex and color with main_color from the lessR <a href="#">style</a> function.
sub	Sub-title of graph, below xlab.
lab_adj	Two-element vector – x-axis label, y-axis label – adjusts the position of the axis labels in approximate inches. + values move the labels away from plot edge. Not applicable to Trellis graphics.
margin_adj	Four-element vector – top, right, bottom and left – adjusts the margins of the plotted figure in approximate inches. + values move the corresponding margin away from plot edge. Not applicable to Trellis graphics.
add_top	In the same scale as the corresponding axis, puts more space between the bars and the top of the plot area, usually to accommodate the legend when plotting two variables or a display of the values on top of the bars.

add	<b>Draw one or more objects</b> , text or a geometric figures, on the plot. Possible values are any text to be written, the first argument, which is "text", or, to indicate a figure, "rect" (rectangle), "line", "arrow", "v.line" (vertical line), and "h.line" (horizontal line). The value "means" is short-hand for vertical and horizontal lines at the respective means. Does not apply to Trellis graphics. Customize with parameters such as add_fill and add_color from the <a href="#">style</a> function.
x1	First x coordinate to be considered for each object. All coordinates vary from -1 to 1.
y1	First y coordinate to be considered for each object.
x2	Second x coordinate to be considered for each object. Only used for "rect", "line" and arrow.
y2	Second y coordinate to be considered for each object. Only used for "rect", "line" and arrow.
eval_df	Determines if to check for existing data frame and specified variables. By default is TRUE unless the shiny package is loaded then set to FALSE so that Shiny will run. Needs to be set to FALSE if using the pipe %\>% notation.
quiet	If set to TRUE, no text output. Can change system default with <a href="#">style</a> function.
width	Width of the plot window in inches, defaults to 4.5.
height	Height of the plot window in inches, defaults to 4.5.
pdf	If TRUE, indicate to direct pdf graphics for each specified variable to a pdf file named BarChart_name.pdf where name is the variable name.
...	Other parameter values for graphics as defined by <a href="#">barplot</a> , <a href="#">legend</a> , and <a href="#">par</a> including xlim and ylim for setting the range of the x and y-axes cex.main for the size of the title col.main for the color of the title "dotted", "dotdash" sub and col.sub for a subtitle and its color las=3 to reorient vertical axis labels space for one variable only

## Details

### OVERVIEW

Plot a bar chart with default colors for one or two categorical variables, that is, with a relatively small number of values for each variable. By default, colors are selected for the bars, background and grid lines, all of which can be customized. The basic computations of the chart are provided with the standard R functions [barplot](#), [chisq.test](#) and, for two variables, [legend](#). Horizontal bar charts, specified by `horiz=TRUE`, list the value labels horizontally and automatically extend the left margin to accommodate both the value labels and the variable label.

### DATA

Ultimately the bar chart is constructed from a simple table in which each row consists of a level of the categorical variable `x` paired with the corresponding value of the numerical variable, `y`, with as many rows as the number of levels of `x`. A data table of this form can be read by specifying

the variable  $x$  and the variable  $y$ . Alternatively, read a data table in the form in which the data are typically gathered, with many replications of the levels of the categorical variable  $x$ . In this situation, with just the specification of the variable  $x$ , the corresponding numerical variable is the tabulation of the counts of the number of occurrences for each level of  $x$ . Or, specify a numerical variable from a data table of this form and reduce to the smaller data table via statistical transformation of the values of  $y$  for each level of  $x$ , such as the mean.

The data may either be a vector from the global environment, the user's workspace, as illustrated in the examples below, or a variable in a data frame. The default input data frame is `d`. Specify a different data frame name with the `data` option. Regardless of its name, the variables in the data frame are referenced directly by their names.

If the name of the vector is in the global environment and of a variable in the input data frame has the same name, the vector from the global environment is analyzed, unless the data name frame is explicitly provided, not relying upon the default `d`. If two variables are specified, both variables should be in the data frame, or one of the variables is in the data frame and the other in the global environment.

To obtain a bar chart of each categorical variable in the `d` data frame, invoke `BarChart()`. Or, for a data frame with a different name, insert the data frame name between the parentheses as the first listed parameter value. To analyze a subset of the variables in a data frame, specify the variable list with either a `:` or the `c` function, such as `m01:m03` or `c(m01,m02,m03)`.

The `filter` parameter subsets rows (cases) of the input data frame according to a logical expression. Use the standard R operators for logical statements as described in [Logic](#) such as `&` for and, `|` for or and `!` for not. Use the standard R relational operators as described in [Comparison](#). Examples include `==` for logical equality, `!=` for not equals, and `>` for greater than. See the Examples.

The form of the entered data, the first variable, categorical  $x$ , and optionally a second variable, numerical  $y$ , is flexible. The data may be entered as factors, numeric values, characters, or a matrix. The data may be entered and the resulting frequencies computed, or the frequencies can be entered directly. The most natural type of data to enter, when entering the variables, is to enter factors.

#### STATISTICAL TRANSFORMATIONS

Ultimately the bar plot is constructed from a small table of data values with each row a level of the categorical variable  $x$  paired with the corresponding value of the numerical variable  $y$ , with as many rows as values of  $x$ . It is also possible to plot transformations of the values of  $y$  for each level of categorical variable  $x$  from a full data table with many replications of each value of  $x$  and corresponding  $y$ . Then reduce the larger data table down to the summary table with one of following transformations.

#### Transformation

---

```
"sum"
"mean"
"sd"
"dev"
"min"
"median"
"max"
```

---

The other statistical transformation is simply counting the number of occurrences of each level of  $x$ , which does not involve a

## COLORS

For a one variable plot, set the default color of the bars by the current color theme according to `bar_fill_discrete` argument of the function `style`, which includes the default color theme "hues" that defines a qualitative HCL color scale, or set the bar color with the `fill` parameter, which references a specified vector of color specifications, such as generated by the lessR `getColor`s function.

Set `fill` to a single color or a color palette, of which there are many possibilities. Define a qualitative color palette with "hues" that provides HCL colors of the same chroma (saturation) and luminance (brightness). Also available are the pre-specified R color palettes "rainbow", "terrain", and "heat". Pre-defined sequential and divergent color ranges are available as implicit calls to `getColor`s. The full list of pre-defined color ranges (defined in 30 degree increments around the HCL color wheel): "reds", "rusts", "browns", "olives", "greens", "emeralds", "turquoises", "aquas", "blues", "purples", "violets", "magentas", and "grays".

Define the default qualitative color scale with a `fill` set to "hues". Define a *sequential color scale* with single value of `fill` for a pre-defined palette such as "blues". Define a *divergent color scale* with value of `fill` that consists of a vector of two such pre-defined ranges, such as `c("purples", "rusts")`. Divergent color palettes are applicable in particular for plotting multiple bar charts on the same plot such as for a set of Likert response items, all on a common response scale. Or, *manually specify colors*. For example, for a two-level by variable, could set `fill` to `c("coral3", "seagreen3")`, where the specified colors are *not* pre-defined color ranges.

For the pre-defined color scales can obtain more control over the obtained color palettes with an explicit call to `getColor`s for the argument to `fill`. Here the value of chroma (c) and luminance (l) can be explicitly manipulated in conjunction with the specification of a pre-defined color range. Or, create a custom color range for any value of hue (h). See `getColor`s for more information.

The values of another variable can be mapped into the fill color of the bars. To do so, set `fill` to the value of the variable, which would usually be the name of the y variable if explicitly given. Or, if y is tabulated, refer to the variable name as (count). The larger the count for a level of x, the darker the bar.

## LEGEND

When two variables are plotted, a legend is produced, with values for each level of the second or by variable. By default, the location is placed in the right margin of the plot. This position can be changed with the `legend_position` option, which, in addition to the lessR option of `right_margin`, accepts any valid value consistent with the standard R `legend` function, used to generate the legend\_

If the default right margin is retained, variable labels are also accommodated for the legend title. To conserve horizontal space, the variable label is listed in multiple lines if needed. The legend title is constructed by forming lines of maximum length of 12 characters, with multiple words per line if possible. Any single word in the label of more than 12 characters is abbreviated to 12 characters with the R `abbreviate` function. Also, any value labels are abbreviated to a maximum of 6 characters.

If the legend is not in the right margin, sometimes bars from the graph may intrude into the legend\_ One response is to re-run the analysis with the legend in a new location. Another response is to invoke the `add_top` option to place more space between the top bar in the graph and the top of the graph. This option only applies for the default vertical bars. Also, the legend is displayed vertically by default, but can be changed to horizontal with the `legend_horiz` option.

## LONG CATEGORY NAMES

For many plots, the names of the categories tend to be long. To adjust the plot for these long names, they can be rotated using the `rotate_x` and `rotate_y` parameters, in conjunction with `offset`, from the `style` function. The `offset` parameter moves the category name out from the axis to compensate for the rotation. The changes from `style` persist until further changes. To reset to the default after obtaining an analysis, use `style()`.

Also, the following codes are used to adjust line spacing:

1. Any space in a category name is converted to a new line.
2. If the space should not be converted to a new line, the replace with an underscore, which will display as a space and no line break.

For the text output at the console, can specify the maximum number of characters in a label with `labels.max`. Longer value names are abbreviated to the specified length. This facilitates reading cross-tab tables. Also, a provided table pairs the abbreviated names with the actual names. For one variable frequency distributions, `out_size` provides the maximum number of characters for the text output before the horizontal display of the frequency distribution is shifted to a vertical presentation.

#### MULTIPLE BAR CHARTS ON THE SAME PANEL (PLOT)

For multiple x-variables, set the parameter `one_plot` to `TRUE` to specify that each bar chart should be produced on the same panel as all other bars. This is most meaningful when all items have the same set of responses, such as a common Likert scale found in survey data. By default the one panel plot is produced when a common response scale is detected.

The algorithm to detect if the response scale is common first identifies the first variable with the largest set of responses, then checks the responses of all other variables. If all responses to all other variables are contained within the set of responses to the reference variable, then the response scales are the same. This means that on a Likert scale, for example, some items may not contain all possible responses, such as no one selects Strongly Disagree for an item. However, for the response scales to be deemed the same, at least one item (variable) must contain all possible responses.

Regardless, the `one_plot` parameter can be set to either `TRUE` or `FALSE` regardless of the commonality of responses. Setting this parameter explicitly saves some CPU time as the algorithm to evaluate the communality of responses need not be activated.

#### ENTER NUMERIC VARIABLE DIRECTLY

Instead of calculating the counts from the data, the values of any numerical variable, including the counts, can be entered directly as the y-variable, in addition to the categorical x-variable, and perhaps a categorical by-variable. See the examples below, under "bar chart directly from data".

Or, include the already tabulated counts as the data which is read into R, either as a matrix or a data frame.

#### STATISTICS

In addition to the bar chart, descriptive and optional inferential statistics are also presented. First, the frequency table for one variable or the joint frequency table for two variables is displayed. Second, the corresponding Cramer's V and chi-square test are also displayed by default.

#### VARIABLE LABELS

If variable labels exist, then the corresponding variable label is listed as the label for the horizontal axis unless `xlab` is specified in the function call. If there are two variables to plot, the title of the resulting plot is based on the two variable labels, unless a specific title is listed with the `main` option. The variable label is also listed in the text output, next to the variable name. If the analysis is for two variables, then labels for both variables are included.

**PDF OUTPUT**

To obtain pdf output, set the pdf option to TRUE, perhaps with the optional width and height options. These files are written to the default working directory, which can be explicitly specified with the R `setwd` function.

**ONLY VARIABLES ARE REFERENCED**

The referenced variable in a `lessR` function can only be a variable name (or list of variable names). This referenced variable must exist in either the referenced data frame, such as the default `d`, or in the user's workspace, more formally called the global environment. That is, expressions cannot be directly evaluated. For example:

```
> BarChart(cut(rnorm(50), breaks=seq(-5,5))) # does NOT work
```

Instead, do the following:

```
> Y <- cut(rnorm(50), breaks=seq(-5,5)) # create vector Y in user workspace
> BarChart(Y) # directly reference Y
```

**Value**

The output can optionally be saved into an R object, otherwise it only appears in the console (unless `quiet` is set to TRUE). Two different types of components are provided: the pieces of readable output, and a variety of statistics. The readable output are character strings such as tables amenable for display. The statistics are numerical values amenable for further analysis. The motivation of these types of output is to facilitate R markdown documents, as the name of each piece, preceded by the name of the saved object and a `$`, can be inserted into the R~Markdown document (see examples), interspersed with explanation and interpretation.

Tabulated numerical variable `y`

---

**READABLE OUTPUT**

`out_title`: Title

`out_lbl`: Variable label

`out_counts`: Two-way frequency distribution

`out_chi`: Chi-square test

*One variable*: `out_miss`: Number of missing values

*Two variables*: `out_prop`: Cell proportions

*Two variables*: `out_row`: Cell proportions within each row

*Two variables*: `out_col`: Cell proportions within each col

**STATISTICS**

`n_dim`: Number of dimensions, 1 or 2

`p_value`: p-value for null of equal proportions or independence

`freq`: Data frame of the frequency distribution

*One variable*: `freq`: Frequency distribution

*One variable*: `values`: y-values read directly

*One variable*: `prop`: Frequency distribution of proportions

*One variable*: `n_miss`: Number of missing values

Numerical variable `y` read from data

---



out\_y: Values of y  
 n\_dim: Number of dimensions, 1 or 2

### Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

### References

Gerbing, D. W. (2014). R Data Analysis without Programming, Chapter 4, NY: Routledge.

### See Also

[getColor](#), [barplot](#), [table](#), [legend](#).

### Examples

```
# get the data
d <- rd("Employee")

# -----
# bar chart from tabulating the data for a single variable
# -----

# for each level of Dept, display the frequencies
BarChart(Dept)
# short name
# bc(Dept)

# save the values output by BarChart into the myOutput list
myOutput <- BarChart(Dept)
# display the saved output
myOutput

# just males with salaries larger than 75,000 USD
BarChart(Dept, filter=(Gender=="M" & Salary > 85000))

# rotate and offset the axis labels, sort categories by frequencies
BarChart(Dept, rotate_x=45, offset=1, sort="-")

# set bars to a single color of blue with some transparency
BarChart(Dept, fill="blue", trans=0.3)
# progressive (sequential) color scale of blues
BarChart(Dept, fill="blues")

# change the theme just for this analysis, as opposed to style()
BarChart(Dept, theme="darkgreen")

# set bar color to hcl custom hues with chroma and luminance
# at the values provided by the default hcl colors from
```

```

# the getColors function, which defaults to h=240 and h=60
# for the first two colors on the qualitative scale
bc(Gender, fill=c(hcl(h=180,c=100,l=55), hcl(h=0,c=100,l=55)))

# or set to unique colors via color names
BarChart(Gender, fill=c("palegreen3","tan"))

# darken the colors with an explicit call to getColors,
# do a lower value of luminance, set to l=25
BarChart(Dept, fill=getColors(l=25), trans=0.4)

# column proportions instead of frequencies
BarChart(Gender, stat="proportion")

# map value of tabulated count to bar fill
BarChart(Dept, fill=(count))
# viridis palette
BarChart(Dept, fill=(count.v))

# data with many values of categorical variable Make and large labels
myd <- Read("Cars93")
# perpendicular labels
bc(Make, rotate_x=90, data=myd)
# manage size of horizontal value labels
bc(Make, horiz=TRUE, label_max=4, data=myd)

# wes anderson move theme palette
# see getColors help file to see the full list of themes
BarChart(Dept, fill="GrandBudapest1", values="off")

# display bars for values of count <= 10 in a different color
# than values above
BarChart(Dept, sort="+", fill_split=10)

# read y variable, Salary, then bars are height of
# corresponding mean Salary
BarChart(Dept, Salary, stat="mean")

# -----
# bar chart from tabulating the data for two variables
# -----

# at each level of Dept, show the frequencies of the Gender levels
BarChart(Dept, by=Gender)

# at each level of Dept, show the row proportions of the Gender levels
# i.e., 100% stacked bar graph
BarChart(Dept, by=Gender, stack100=TRUE)

# at each level of Gender, show the frequencies of the Dept levels
# do not display percentages directly on the bars
BarChart(Gender, by=JobSat, fill="reds", values="off")

```

```

# specify two fill colors for Gender
BarChart(Dept, by=Gender, fill=getColors(c("deepskyblue", "black")))

# display bars beside each other instead of stacked, Female and Male
# the levels of Dept are included within each respective bar
# plot horizontally, display the value for each bar at the
# top of each bar
BarChart(Gender, by=Dept, beside=TRUE, horiz=TRUE, values_position="out")

# horizontal bar chart of two variables, put legend on the top
BarChart(Gender, by=Dept, horiz=TRUE, legend_position="top")

# for more info on base R graphic options, enter: help(par)
# for lessR options, enter: style(show=TRUE)
# here fill is set in the style function instead of BarChart
# along with the others
style(fill=c("coral3", "seagreen3"), lab_color="wheat4", lab_cex=1.2,
      panel_fill="wheat1", main_color="wheat4")
BarChart(Dept, by=Gender,
        legend_position="topleft", legend_labels=c("Girls", "Boys"),
        xlab="Dept Level", main="Gender for Different Dept Levels",
        value_labels=c("None", "Some", "Much", "Ouch!"))
style()

# -----
# multiple bar charts tabulated from data across multiple variables
# -----

# bar charts for all non-numeric variables in the data frame called d
# and all numeric variables with a small number of values, < n_cat
# BarChart(one_plot=FALSE)

d <- rd("Mach4", quiet=TRUE)

# all on the same plot, bar charts for 20 6-pt Likert scale items
# default scale is divergent from "browns" to "blues"
BarChart(m01:m20, horiz=TRUE, values="off", sort="+")

# custom scale with explicit call to getColors, HCL chroma at 50
clrs <- getColors("greens", "purples", n=6, c=50)
BarChart(m01:m20, horiz=TRUE, values="off", sort="+", fill=clrs)

# custom divergent scale with pre-defined color palettes
# with implicit call to getColors
BarChart(m01:m20, horiz=TRUE, values="off", fill=c("aquas", "rusts"))

# -----

```

```

# can enter many types of data
# -----

# generate and enter integer data
X1 <- sample(1:4, size=100, replace=TRUE)
X2 <- sample(1:4, size=100, replace=TRUE)
BarChart(X1)
BarChart(X1, by=X2)

# generate and enter type double data
X1 <- sample(c(1,2,3,4), size=100, replace=TRUE)
X2 <- sample(c(1,2,3,4), size=100, replace=TRUE)
BarChart(X1)
BarChart(X1, by=X2)

# generate and enter character string data
# that is, without first converting to a factor
Travel <- sample(c("Bike", "Bus", "Car", "Motorcycle"), size=25, replace=TRUE)
BarChart(Travel, horiz=TRUE)

# -----
# bar chart directly from data
# -----

# include a y-variable, here Salary, in the data table to read directly
d <- read.csv(text="
Dept, Salary
ACCT,51792.78
ADMN,71277.12
FINC,59010.68
MKTG,60257.13
SALE,68830.06", header=TRUE)
BarChart(Dept, Salary)

# specify two variables for a two variable bar chart
# also specify a y-variable to provide the counts directly
# when reading y values directly, must be a summary table,
# one row of data for each combination of levels with
# a numerical value of y
# use base R aggregate function to get summary table
d <- Read("Employee")
a <- aggregate(Salary ~ Dept + Gender, data=d, FUN=mean)
BarChart(Dept, Salary, by=Gender, data=a)
# do so just with BarChart, display bars in grayscale
# How does average salary vary by gender across the various departments?
BarChart(Dept, Salary, by=Gender, stat="mean", data=d, fill="grays")

# -----
# annotations
# -----

```

```

d <- rd("Employee")

# Place a message in the center of the plot
# \n indicates a new line
BarChart(Dept, add="Employees by\nDepartment", x1=3, y1=10)

# Use style to change some parameter values
style(add_trans=.8, add_fill="gold", add_color="gold4", add_lwd=0.5)
# Add a rectangle around the message centered at <3,10>
BarChart(Dept, add=c("rect", "Employees by\nDepartment"),
          x1=c(2,3), y1=c(11, 10), x2=4, y2=9)

```

corCFA

*Confirmatory Factor Analysis of a Multiple Indicator Measurement Model*

## Description

Abbreviation: cfa

A multiple indicator measurement model partitions a set of indicators, such as items on a survey, into mutually exclusive groups with one common factor per group of indicators. From the input correlation matrix of the indicator variables, this procedure uses iterated centroid estimation to estimate the coefficients of the model, the factor pattern and factor-factor correlations, as well as the correlations of each factor with each indicator. The analysis is an adaptation and extension of John Hunter's program PACKAGE (Hunter and Cohen, 1969).

Corresponding scale reliabilities are provided, as well as the residuals, the difference between the indicator correlations and those predicted by the model. To visualize the relationships, a heat map of the re-ordered correlation matrix is also provided, with indicator communalities in the diagonal. To understand the meaning of each factor, the corresponding indicator content is displayed for each factor if the indicators have been read as variable labels. Also provides the code to obtain the maximum likelihood solution of the corresponding multiple indicator measurement model (MIMM) with the `cfa` function from the `lavaan` package.

The `scales` is a wrapper that retains 1's in the diagonal of the indicator correlation matrix, so provides scale reliabilities and observed indicator-scale and scale-scale correlations.

Output is generated into distinct pieces by topic, organized and displayed in sequence by default. When the output is assigned to an object, such as `f` in `f <- cfa(Fac =~ X1 + X2 + X3)`, the full or partial output can be accessed for later analysis and/or viewing. A primary such analysis is with `knitr` for dynamic report generation, run from, for example, `RStudio`. The input instructions written to the R-Markdown file are written comments and interpretation with embedded R code. Doing a `knitr` analysis is to "knit" these comments and subsequent output together so that the R output is embedded in the resulting document, either `html`, `pdf` or `Word`, by default with explanation and interpretation. Generate a complete R-Markdown set of instructions ready to knit from the `Rmd` option. Simply specify the option and create the file and then open in `RStudio` and click the `knit` button to create a formatted document that consists of the statistical results and interpretative comments. See the following sections arguments, value and examples for more information.

**Usage**

```
corCFA(mimm=NULL, x=mycor, data=d, fac.names=NULL,
       Rmd=NULL, explain=getOption("explain"),
       interpret=getOption("interpret"), results=getOption("results"),
       labels=c("include", "exclude", "only"),
       min_cor=.10, min_res=.05, iter=50, grid=TRUE,
       resid=TRUE, item_cor=TRUE, sort=TRUE,
       main=NULL, heat_map=TRUE, bottom=3, right=3,
       pdf_file=NULL, width=5, height=5,
       F1=NULL, F2=NULL, F3=NULL, F4=NULL, F5=NULL,
       F6=NULL, F7=NULL, F8=NULL, F9=NULL, F10=NULL,
       F11=NULL, F12=NULL,
       fun_call=NULL, ...)

cfa(...)

scales(..., iter=0, resid=FALSE, item_cor=FALSE, sort=FALSE, heat_map=FALSE)
```

**Arguments**

mimm	Multiple indicator measurement model, a character string with the specification of each factor on a separate line: the factor name, an equals sign, and the indicators separated by plus signs. Each indicator is assigned to only one factor.
x	Correlation matrix to be analyzed.
data	Data frame of the original data to be checked for any variable labels, usually indicator (item) content. This is not to calculate correlations, which is separately provided for by the <code>lessR</code> function <a href="#">Correlation</a> .
fac.names	Optional factor names for the original, non-lavaan model specification.
Rmd	File name for the file of R Markdown instructions to be written, if specified. The file type is <code>.Rmd</code> , which automatically opens in RStudio, but it is a simple text file that can be edited with any text editor, including RStudio.
explain	If set to <code>FALSE</code> the explanations of the results are not provided in the R~Markdown file. Set globally with <code>options(explain=FALSE)</code> .
interpret	If set to <code>FALSE</code> the interpretations of the results are not provided in the R~Markdown file. Set globally with <code>options(interpret=FALSE)</code> .
results	If set to <code>FALSE</code> the results are not provided in the R~Markdown file, relying upon the interpretations. Set globally with <code>options(results=FALSE)</code> .

labels	If "include" or "exclude" then variable labels are displayed (if available) or not, organized by the items within each factor. If "only" then no data analysis performed, only the display of the labels by factor.
min_cor	Minimum correlation to display. To display all, set to 0.
min_res	Minimum residual to display. To display all, set to 0.
iter	Number of iterations for communality estimates.
grid	If TRUE, then separate items in different factors by a grid of horizontal and vertical lines in the output correlation matrix.
resid	If TRUE, then calculate and print the residuals.
item_cor	If TRUE, display the indicator correlations.
sort	If TRUE, re-order the output correlation matrix so that indicators within each factor are sorted by their factor loadings on their own factor.
main	Graph title of heat map. Set to main="" to turn off.
heat_map	If TRUE, display a heat map of the indicator correlations with indicator communalities in the diagonal.
bottom	Number of lines of bottom margin of heat map.
right	Number of lines of right margin of heat map.
pdf_file	Name of the pdf file to which graphics are redirected.
width	Width of the pdf file in inches.
height	Height of the pdf file in inches.
F1	Variables that define Factor 1.
F2	Variables that define Factor 2.
F3	Variables that define Factor 3.
F4	Variables that define Factor 4.
F5	Variables that define Factor 5.
F6	Variables that define Factor 6.
F7	Variables that define Factor 7.
F8	Variables that define Factor 8.
F9	Variables that define Factor 9.
F10	Variables that define Factor 10.
F11	Variables that define Factor 11.
F12	Variables that define Factor 12.
fun_call	Function call. Used internally with knitr to pass the function call when obtained from the abbreviated function call cfa. Not usually invoked by the user.
...	Parameter values_

## Details

### OVERVIEW

A multiple indicator measurement model defines one or more latent variables, called factors, in terms of mutually exclusive sets of indicator variables, such as items from a questionnaire or survey. That is, each factor is defined by a unique set or group of indicators, and each indicator only contributes to the definition of one factor. Two sets of parameters are estimated by the model, the factor pattern coefficients, the lambda's, and the factor-factor correlations, the phi's. Also estimated here are the correlations of each indicator with the other factors.

### INPUT

Unless `labels="only"`, the analysis requires the correlation matrix of the indicators and the specification of the groups of indicators, each of which defines a factor in the multiple indicator measurement model. The default name for the indicator correlation matrix is `mycor`, which is also the default name of the matrix produced by the `lessR` function `Correlation` that computes the correlations from the data, as well as the name of the matrix read by the `lessR` function `corRead` that reads the already computed correlation matrix from an external file.

For versions of `lessR` after 3.3, the correlation matrix computed by `Correlation` is now a list element called `R` within the returned list. For example, `mycor$R` from `mycor <- cr(d)`. The function `corCFA` automatically finds this correlation matrix from just entering the entire list name of the returned list, `mycor`, or the specific location, `mycor$R`, or as a stand-alone numerical matrix as done in versions of `lessR` previous to 3.3.

The data frame from which the correlation matrix was computed is required only if any associated variable labels are listed, organized by the items within each factor. By default, `labels="include"`, these labels are listed as part of the analysis if they are available.

Define the constituent variables, the indicators, of each factor with a listing of each variable by its name in the correlation matrix. Each of the up to 12 factors is named `F1`, `F2`, etc. If the specified variables of a factor are in consecutive order in the input correlation matrix, the list can be specified by listing the first variable, a colon, and then the last variable. To specify multiple variables, a single variable or a list, separate each by a comma, then invoke the R combine or `c` function, preceded by the factor's name and an equals sign. For example, if the first factor is defined by variables in the input correlation matrix from `m02` through `m05`, and the variable `Anxiety`, then define the factor in the `corCFA` function call according to `F1=c(m02:m05, Anxiety)`.

### OUTPUT

The result of the analysis is the correlation matrix of the indicator variables and resulting factors, plus the reliability analysis of the observed total scores or scale that corresponds to each factor. Each scale is defined as an unweighted composite. The corresponding code to analyze the model with the `cfa` function from the `lavaan` package is also provided with the default maximum likelihood estimation procedure. The comparable `lavaan` solution appears in the column that represents the fully standardized solution, factors and indicators, `Std.all`, the last column of the solution output. If the `lavaan` library is loaded, then explicitly refer to the `lessR` function `cfa` with `lessR::cfa` and the corresponding `lavaan` function with `lavaan::cfa`.

### VARIABLE LABELS

To display the indicator content, first read the indicators as variable labels with the `lessR` function `Read`. If this labels data frame exists, then the corresponding variable labels, such as the actual items on a survey, are listed by factor. For more information, see `Read`.

### HEAT MAP

To help visualize the overall patterning of the correlations, the corresponding heat map of the item



correlation matrix with communalities is produced when `heat_map=TRUE`, the default. As is true of the output correlation matrix, the correlations illustrated in the heat map are also sorted by their ordering within each factor. The corresponding color scheme is dictated by the system setting, according to the `lessR` function `style`. The default color scheme is `blue`.

#### ESTIMATION PROCEDURE

The estimation procedure is centroid factor analysis, which defines each factor, parallel to the definition of each scale score, as the unweighted composite of the corresponding items for that scale. The latent variables are obtained by replacing the 1's in the diagonal of the indicator variable correlation matrix with communality estimates. These estimates are obtained by iterating the solution to the specified number of iterations according to `iter`, which defaults to 50.

A communality is the percentage of the item's correlation attributable to, in this situation of a multiple indicator measurement model, its one underlying factor. As such, the communality is comparable to the item correlations for items within the same factor, which are also due only to the influence of the one common, underlying factor. A value of 0 for `iter` implies that the 1's remain in the observed variable correlation matrix, which then means that there are no latent factors defined. Instead the resulting correlation matrix is of the observed scale scores and the component items.

### Value

#### TEXT OUTPUT

`out_labels`: variables in the model  
`out_reliability`: reliability analysis with alpha and omega  
`out_indicators`: solution in terms of the analysis of each indicator  
`out_solution`: full solution  
`out_residuals`: residuals  
`out_res_stats`: stats for residuals  
`out_lavaan`: lavaan model specification

Separated from the rest of the text output are the major headings, which can then be deleted from custom collations of the output. `out_title_scales`: scales

`out_title_rel`: reliability analysis  
`out_title_solution`: solution  
`out_title_residuals`: residual analysis  
`out_title_lavaan`: lavaan specification

#### STATISTICS

Returns a list of six components.

1. `ff.cor`: matrix of the factor correlations
2. `if.cor`: matrix of the indicator-factor correlations that includes the estimated pattern coefficients of the model that link a factor to its indicators
3. `diag.cor`: the indicator communalities
4. `alpha`: coefficient alpha for each set of indicators
5. `omega`: if a factor analysis with communality estimates (`iter > 0`), contains coefficient omega for each set of indicators
6. `pred`: matrix of correlations predicted by the model and its estimates
7. `resid`: matrix of raw indicator residuals defined as the observed correlation minus that predicted by the model and its estimates

**Author(s)**

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

**References**

- Gerbing, D. W. (2014). *R Data Analysis without Programming*, Chapter 11, NY: Routledge.
- Gerbing, D. W., & Hamilton, J. G. (1994). The surprising viability of a simple alternate estimation procedure for the construction of large-scale structural equation measurement models. *Structural Equation Modeling: A Multidisciplinary Journal*, 1, 103-115.
- Hunter, J. E., Gerbing, D. W., & Boster, F. J. (1982). Machiavellian beliefs and personality: The construct invalidity of the Machiavellian dimension. *Journal of Personality and Social Psychology*, 43, 1293-1305.
- Hunter, J. & Cohen, J. (1969). PACKAGE: A system of computer routines for the analysis of correlational data. *Educational and Psychological Measurement*, 1969, 29, 697-700.
- Yves Rosseel (2012). lavaan: An R Package for Structural Equation Modeling. *Journal of Statistical Software*, 48(2), 1-36. URL <http://www.jstatsoft.org/v48/i02/>.

**See Also**

[Correlation](#).

**Examples**

```
# perfect input correlation matrix for two-factor model
# Population Factor Pattern of the 3 items for each respective
# Factor: 0.8, 0.6, 0.4
# Population Factor-Factor correlation: 0.3
mycor <- matrix(nrow=6, ncol=6, byrow=TRUE,
c(1.000,0.480,0.320,0.192,0.144,0.096,
  0.480,1.000,0.240,0.144,0.108,0.072,
  0.320,0.240,1.000,0.096,0.072,0.048,
  0.192,0.144,0.096,1.000,0.480,0.320,
  0.144,0.108,0.072,0.480,1.000,0.240,
  0.096,0.072,0.048,0.320,0.240,1.000))
colnames(mycor) <- c("X1", "X2", "X3", "X4", "X5", "X6")
rownames(mycor) <- colnames(mycor)

# the confirmatory factor analysis
# first three variables with first factor, last three with second
# default correlation matrix is mycor
MeasModel <-
"
  First =~ X1 + X2 + X3
  Second =~ X4 + X5 + X6
"
c <- cfa(MeasModel)

# access the solution directly by saving to an object called fit
cfa(MeasModel)
fit <- cfa(MeasModel)
```

```

fit
# get the pattern coefficients from the communalities
lambda <- sqrt(fit$diag.cor)
lambda

# alternative specification described in Gerbing(2014),
# retained to be consistent with that description
# can specify the items with a colon and with commas
# abbreviated form of function name: cfa
cfa(F1=c(X4,X5,X6), F2=X1:X3)

# component analysis, show observed scale correlations
scales(F1=X1:X3, F2=X4:X6)

# produce a gray scale heat map of the item correlations
# with communalities in the diagonal
# all subsequent graphics are in gray scale until changed
style("gray")
corCFA(F1=X1:X3, F2=X4:X6)

# access the lessR data set called datMach4, with variable labels
d <- Read("Mach4", quiet=TRUE)
# calculate the correlations and store in mycor
mycor <- cr(m01:m20)
# specify measurement model in Lavaan notation
MeasModel <-
"
  Deceit =~ m07 + m06 + m10 + m09
  Trust =~ m12 + m05 + m13 + m01
  Cynicism =~ m11 + m16 + m04
  Flattery =~ m15 + m02
"
# confirmatory factor analysis of 4-factor solution of Mach IV scale
# Hunter, Gerbing and Boster (1982)
# generate R Markdown instructions with the option: Rmd
# Output file will be m4.Rmd, a simple text file that can
# be edited with any text editor including RStudio, from which it
# can be knit to generate dynamic output such as to a Word document
#c <- cfa(MeasModel, Rmd="m4")
# view all the output
c
# view just the scale reliabilities
c$out_reliability

# analysis of item content only
cfa(MeasModel, data=d, labels="only")

# bad fitting model to illustrate indicator diagnostics
mycor <- corReflect(vars=c(m20))
MeasModel <-
"
  F1 =~ m06 + m09 + m19

```

```

F2 =~ m07
F3 =~ m04 + m11 + m16
F4 =~ m15 + m12 + m20 + m18
"
cfa(MeasModel)

```

---

corEFA

*Exploratory Factor Analysis and Multiple Indicator Measurement Model*


---

## Description

Abbreviation: efa

A maximum likelihood exploratory factor analysis of an input correlation matrix, provided by the standard R exploratory factor analysis [factanal](#), which requires the specified number of factors as an input to the analysis. Then constructs the code to run the corresponding multiple indicator measurement model (MIMM) suggested by the exploratory factor analysis loadings in terms of both the lessR [corCFA](#) and the `cfa` function from the `lavaan` package.

## Usage

```

corEFA(x=mycor, n_factors, rotate=c("promax", "varimax", "none"),
       min_loading=.2, sort=TRUE, Rmd=NULL, ...)

efa(...)

```

## Arguments

<code>x</code>	Correlation matrix.
<code>n_factors</code>	Number of factors.
<code>rotate</code>	Rotation method, if any.
<code>min_loading</code>	Minimum loading to include in suggested factor for confirmatory analysis and for the display of the loadings for the exploratory analysis. To ignore, set to 0.
<code>sort</code>	Sort the input variables by their highest factor loadings (but only first just list those items with loadings larger than 0.5).
<code>Rmd</code>	File name for the file of R markdown to be written, if specified. The file type is <code>.Rmd</code> , which automatically opens in RStudio, but it is a simple text file that can be edited with any text editor, including RStudio.
<code>...</code>	Parameter values_

## Details

Only the loadings from the exploratory factor analysis are provided, with either an oblique (promax), by default, or an orthogonal (varimax) rotation. If more information is desired, run [factanal](#) directly.

Also provides the associated multiple indicator measurement model suggested by the exploratory factor analysis. Each MIMM factor is defined by the items that have the highest loading on the corresponding exploratory factor.

For versions of `lessR` after 3.3, the correlation matrix computed by [Correlation](#) is now a list element called `R` within the returned list. For example, `mycor$R` from `mycor <- cr(d)`. The function `corEFA` automatically finds this correlation matrix from just entering the entire list name of the returned list, `mycor`, or the specific location, `mycor$R`, or as a stand-alone numerical matrix as done in versions of `lessR` previous to 3.3.

## Value

The output can optionally be returned and saved into an R object, otherwise it simply appears at the console. The components of this object are redesigned in `lessR` version 3.3 into three different types: pieces of text that form the readable output, a variety of statistics, and R markdown instructions. The readable output are character strings such as tables amenable for viewing and interpretation. The statistics are numerical values amenable for further analysis, such as to be referenced in a subsequent R markdown document. The R~Markdown input is available for entry direct into `knitr`, such as in RStudio. The motivation of these three types of output is to facilitate R markdown documents, as the name of each piece, preceded by the name of the saved object followed by a `\$`, can be inserted into the R markdown document (see examples).

### READABLE OUTPUT

`out_title`: Variables in the model, rows of data and retained  
`out_loadings`: Estimated coefficients, hypothesis tests and confidence intervals  
`out_sum_squares`: Fit indices  
`out_cfa_title`: Analysis of variance  
`out_ice`: Correlations among all variables in the model  
`out_lavaan`: Collinearity analysis  
`out_deleted`: R squared adjusted for all (or many) possible subsets

### STATISTICS

`Rmd`: Instructions to run through `knitr`, such as copy and paste, to obtain output in the form of a web file, pdf document or Word document. Can also obtain these instructions with the `Rmd` option, which writes them directly to the specified text file. Obtain a less detailed Rmd file by setting `explain=FALSE`.

Although not typically needed for analysis, if the output is assigned to an object named, for example, `fa`, then the complete contents of the object can be viewed directly with the [unclass](#) function, here as `unclass(fa)`. Invoking the [class](#) function on the saved object reveals a class of `out_all`. The class of each of the text pieces of output is `out`.

## Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

## References

- Gerbing, D. W. (2014). R Data Analysis without Programming, Chapter 11, NY: Routledge.
- Yves Rosseel (2012). lavaan: An R Package for Structural Equation Modeling. Journal of Statistical Software, 48(2), 1-36. URL <http://www.jstatsoft.org/v48/i02/>.

## See Also

[Correlation](#).

## Examples

```
# input correlation matrix of perfect two-factor model
# Factor Pattern for each Factor: 0.8, 0.6, 0.4
# Factor-Factor correlation: 0.3
mycor <- matrix(nrow=6, ncol=6, byrow=TRUE,
c(1.000,0.480,0.320,0.192,0.144,0.096,
  0.480,1.000,0.240,0.144,0.108,0.072,
  0.320,0.240,1.000,0.096,0.072,0.048,
  0.192,0.144,0.096,1.000,0.480,0.320,
  0.144,0.108,0.072,0.480,1.000,0.240,
  0.096,0.072,0.048,0.320,0.240,1.000))
colnames(mycor) <- c("X1", "X2", "X3", "X4", "X5", "X6")
rownames(mycor) <- colnames(mycor)

# default factor analysis of default correlation matrix mycor
# with two factors extracted
corEFA(n_factors=2)

# abbreviated form
# use all items to construct the MIMM, regardless of their loadings
# and show all loadings
# show the initial factor extraction
efa(n_factors=2, min_loading=0, show_initial=TRUE)
```

---

corProp

*Proportionality Coefficients from Correlations*

---

## Description

Abbreviation: prop

In the population, indicators of the same factor or latent variable have parallel correlations with all other variables. Of course, in the presence of sampling error, this parallelism will only be approximate. To assess this parallelism, proportionality coefficients are computed for each pair of variables in the input correlation matrix. Also output is a heat map of the resulting matrix of proportionality coefficients. Each graph is based on a default color theme. The original default is lightbronze, but other color palettes can be generated as well.

**Usage**

```
corProp(R=mycor,
        main=NULL, heat_map=TRUE, bottom=3, right=3,
        pdf_file=NULL, width=5, height=5, ...)

prop(...)
```

**Arguments**

R	Correlation matrix.
main	Graph title. Set to main="" to turn off.
heat_map	If TRUE, display a heat map of the item correlations with the diagonal ignored.
bottom	Number of lines of bottom margin.
right	Number of lines of right margin.
pdf_file	Name of the pdf file to which graphics are redirected.
width	Width of the pdf file in inches.
height	Height of the pdf file in inches.
...	Parameter values_

**Details**

Proportionality coefficients indicate the extent of proportionality between two variables. Perfect proportionality of two variables is consistent with both variables being indicators of the same latent variable or factor and indicators of no other factor.

In the current version the diagonal of the input correlation matrix is ignored. To maintain parallelism, the diagonal element of 1.00 would need to be replaced the corresponding communalities, which first requires a factor analysis.

**Author(s)**

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

**References**

Gerbing, D. W. (2014). R Data Analysis without Programming, Chapter 11, NY: Routledge.

**See Also**

[Correlation](#).

**Examples**

```
# input correlation matrix of perfect two-factor model
# Factor Pattern for each Factor: 0.8, 0.6, 0.4
# Factor-Factor correlation: 0.3
mycor <- matrix(nrow=6, ncol=6, byrow=TRUE,
c(1.000,0.480,0.320,0.192,0.144,0.096,
```

```

0.480,1.000,0.240,0.144,0.108,0.072,
0.320,0.240,1.000,0.096,0.072,0.048,
0.192,0.144,0.096,1.000,0.480,0.320,
0.144,0.108,0.072,0.480,1.000,0.240,
0.096,0.072,0.048,0.320,0.240,1.000))
colnames(mycor) <- c("X1", "X2", "X3", "X4", "X5", "X6")
rownames(mycor) <- colnames(mycor)

# proportionality coefficients of correlation matrix mycor
# indicators of the same factor have proportional correlations
corProp()

# abbreviated form
prop()

# calculate and store proportionality coefficients in myprop
# order the proportionality coefficients to help identify factors
myprop <- corProp()
corReorder(myprop)

```

---

corRead

*Read Specified Correlation Matrix*


---

## Description

Abbreviation: rd.cor

Read a correlation matrix into R. The resulting matrix is named mycor. All coefficients for each variable must be on one row. No variable names are in the file to be read.

## Usage

```
corRead(ref=NULL, names=NULL)
```

```
rd.cor(...)
```

## Arguments

ref	File reference, either omitted to browse for the data file, or a full path name or web URL, included in quotes. A URL begins with <code>http://</code> .
names	The names of the variables in the matrix.
...	Parameter values_

## Details

Read a correlation, or any square, matrix into R. The resulting matrix is named mycor. All coefficients for each variable must be on one row. No variable names are in the file to be read. The coefficients within each row, that is, for a single variable, are delimited by a white space, such as one or more blanks.



The standard R function used to read the matrix is [read.table](#).

By default the variables are named V1, V2, etc. If the names option is invoked, then the specified names are attached to the respective rows and columns of the matrix. Here it may be convenient to name the variables with the lessR function [to](#).

The alternative is to calculate the correlations from the data, such as with the lessR function [Correlation](#) or the standard R function [cor](#).

### Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

### References

Gerbing, D. W. (2014). R Data Analysis without Programming, Chapter 8, NY: Routledge.

### See Also

[Correlation](#), [read.table](#).

### Examples

```
# browse for the data file because ref is omitted
# name the variables with the lessR function to
mycor <- corRead(names=to("m",20))

# abbreviated form
# read a matrix with 4 variables and specify the names
mycor <- rd.cor(names=c("m06","m07","m09","m10"))
```

---

corReflect

*Reflect Specified Variables in a Correlation Matrix*

---

### Description

Abbreviation: reflect

Reflects the specified variables by multiplying each correlation of the variable by -1. Usually a prelude to a factor analysis, such as provided by [corCFA](#).

### Usage

```
corReflect(R=mycor, vars,
           main=NULL, heat_map=TRUE, bottom=3,right=3,
           pdf_file=NULL, width=5, height=5, ...)

reflect(...)
```

**Arguments**

R	Correlation matrix.
vars	List of the re-ordered variables, each variable listed by its ordinal position in the input correlation matrix.
main	Graph title. Set to main="" to turn off.
heat_map	If TRUE, display a heat map of the item correlations with item communalities in the diagonal.
bottom	Number of lines of bottom margin.
right	Number of lines of right margin.
pdf_file	Name of the pdf file to which graphics are redirected.
width	Width of the pdf file in inches.
height	Height of the pdf file in inches.
...	Parameter values_

**Details**

Reflects the specified variables by multiplying each correlation of the variable by -1. The original data from which the correlations are computed is unmodified unless the output of the function is written into the input correlation matrix, by default mycor.

Define the constituent variables, the items, with a listing of each variable by its name in the correlation matrix. If the specified variables are in consecutive order in the input correlation matrix, the list can be specified by listing the first variable, a colon, and then the last variable. To specify multiple variables, a single variable or a list, separate each by a comma, then invoke the R combine or `c` function. For example, if the list of variables in the input correlation matrix is from m02 through m05, and the variable Anxiety, then define the list in the corReflect function call according to `vars=c(m02:m05, Anxiety)`.

**Author(s)**

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

**See Also**

[Correlation, Recode.](#)

**Examples**

```
# input correlation matrix of perfect two-factor model
# Factor Pattern for each Factor: 0.8, 0.6, 0.4
# Factor-Factor correlation: 0.3
mycor <- matrix(nrow=6, ncol=6, byrow=TRUE,
  c(1.000,0.480,0.320,0.192,0.144,0.096,
    0.480,1.000,0.240,0.144,0.108,0.072,
    0.320,0.240,1.000,0.096,0.072,0.048,
    0.192,0.144,0.096,1.000,0.480,0.320,
    0.144,0.108,0.072,0.480,1.000,0.240,
```

```

0.096,0.072,0.048,0.320,0.240,1.000))
colnames(mycor) <- c("V1", "V2", "V3", "V4", "V5", "V6")
rownames(mycor) <- colnames(mycor)

# reflect all 3 indicators of the second factor
mynewcor <- corReflect(vars=c(V4,V5,V6))

# abbreviated form
# replace original mycor
mycor <- reflect(vars=c(V4,V5,V6))

```

---

Correlation

*Correlation Analysis*


---

## Description

Abbreviation: `cr`, `cr_brief`, `cr.brief` [deprecated]

For two variables yields the correlation coefficient with hypothesis test and confidence interval. For a data frame or list of variables from a data frame, yields the correlation matrix. The default computed coefficient(s) are the standard Pearson's product-moment correlation, with Spearman and Kendall coefficients available. For the default missing data technique of pairwise deletion, an analysis of missing data for each computed correlation coefficient is provided. For a correlation matrix a statistical summary of the missing data across all cells is provided.

Versions of this function from `lessR` 3.3 or earlier returned just a correlation matrix. Now other values are returned as well so that the correlation matrix is now stored as part of a returned list in R, directly available, for example, as `mycor$R` from `mycor <- cr(d)`. This revision is automatically adjusted for in the `lessR` routines that read the subsequent correlation matrix, so all pre-existing code continues to work. That is, the input into any of these routines could be, for example, `mycor`, `mycor$R` or a stand-alone correlation matrix such as in pre-`lessR` 3.3.

## Usage

```

Correlation(x, y, data=d,
            miss=c("pairwise", "listwise", "everything"),
            fill_low=NULL, fill_hi=NULL,
            show_n=NULL, brief=FALSE,
            digits_d=NULL, heat_map=TRUE,
            main=NULL, bottom=3, right=3,
            pdf=FALSE, width=5, height=5, ...)

```

```

cr.brief(..., brief=TRUE)
cr_brief(..., brief=TRUE)

```

```

cr(...)

```

**Arguments**

<code>x</code>	First variable, or list of variables for a correlation matrix.
<code>y</code>	Second variable or not specified if the first argument is a list.
<code>data</code>	Optional data frame that contains the variables of interest, default is <code>d</code> .
<code>miss</code>	Basis for deleting missing data values_
<code>fill_low</code>	Starting color for a custom sequential palette.
<code>fill_hi</code>	Ending color for a custom sequential palette.
<code>show_n</code>	For pairwise deletion, show the matrix of sample sizes for each correlation coefficient, regardless of sample size.
<code>brief</code>	Pertains to a single correlation coefficient analysis. If <code>FALSE</code> , then the sample covariance and number of non-missing and missing observations are displayed.
<code>digits_d</code>	Specifies the number of decimal digits to display in the output.
<code>heat_map</code>	If <code>TRUE</code> , generate a heat map.
<code>main</code>	Graph title of heat map. Set to <code>main=""</code> to turn off.
<code>bottom</code>	Number of lines of bottom margin of heat map.
<code>right</code>	Number of lines of right margin of heat map.
<code>pdf</code>	If <code>TRUE</code> , generate the heat map and write to pdf files.
<code>width</code>	Width of the pdf file in inches.
<code>height</code>	Height of the pdf file in inches.
<code>...</code>	Other parameter values for internally called functions, which include <code>method="spearman"</code> and <code>method="kendall"</code> and also <code>alternative="less"</code> and <code>alternative="more"</code> .

**Details**

When two variables are specified, both `x` and `y`, the output is the correlation coefficient with hypothesis test, for a null hypothesis of 0, and confidence interval. Also displays the sample covariance. Based on R functions [cor](#), [cor.test](#), [cov](#).

In place of two variables `x` and `y`, `x` can be a complete data frame, either specified with the name of a data frame, or blank to rely upon the default data frame `d`. Or, `x` can be a list of variables from the input data frame. In these situations `y` is missing. Any non-numeric variables in the data frame or specified variable list are automatically deleted from the analysis.

When `heat_map=TRUE`, generate a heat map to standard graphics windows. Set `pdf=TRUE` to generate these graphics but have them directed to their respective pdf files.

For treating missing data, the default is `pairwise`, which means that an observation is deleted only for the computation of a specific correlation coefficient if one or both variables are missing the value for the relevant variable(s). For `listwise` deletion, the entire observation is deleted from the analysis if any of its data values are missing. For the more extreme `everything` option, any missing data values for a variable result in all correlations for that variable reported as missing.

**Value**

From versions of lessR of 3.3 and earlier, if a correlation matrix is computed, the matrix is returned. Now more values are returned, so the matrix is embedded in a list of returned elements.

**READABLE OUTPUT****single coefficient**

out\_background: Variables in the model, any variable labels

out\_describe: Estimated coefficients

out\_inference: Hypothesis test and confidence interval estimated coefficient

**matrix**

out\_background: Variables in the model, any variable labels

out\_missing: Missing values analysis

out\_cor: Correlations

**STATISTICS****single coefficient**

r: Model formula that specifies the model

tvalue: t-statistic of estimated value of null hypothesis of no relationship

df: Degrees of freedom of hypothesis test pvalue: Number of rows of data submitted for analysis

lb: Lower bound of confidence interval

ub: Upper bound of confidence interval

**matrix**

R: Correlations

Usually assign the name of mycor to the output matrix, as in following examples. This matrix is ready for input into any of the lessR functions that analyze correlational data, including confirmatory factor analysis by [corCFA](#) and also exploratory factor analysis, either the standard R function [factanal](#) or the lessR function [corEFA](#)

**Author(s)**

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

**References**

Gerbing, D. W. (2013). R Data Analysis without Programming, Chapter 8, NY: Routledge.

**See Also**

[cor.test](#), [cov](#).

**Examples**

```

# data
n <- 12
f <- sample(c("Group1", "Group2"), size=n, replace=TRUE)
x1 <- round(rnorm(n=n, mean=50, sd=10), 2)
x2 <- round(rnorm(n=n, mean=50, sd=10), 2)
x3 <- round(rnorm(n=n, mean=50, sd=10), 2)
x4 <- round(rnorm(n=n, mean=50, sd=10), 2)
d <- data.frame(f, x1, x2, x3, x4)
rm(f); rm(x1); rm(x2); rm(x3); rm(x4)

# correlation and covariance
Correlation(x1, x2)
# short name
cr(x1, x2)
# brief form of output
cr_brief(x1, x2)

# Spearman rank correlation, one-sided test
Correlation(x1, x2, method="spearman", alternative="less")

# correlation matrix of the numerical variables in mycor
mycor <- Correlation()

# correlation matrix of Kendall's tau coefficients
mycor <- cr(method="kendall")

# correlation matrix of specified variables in mycor with heat_map
mycor <- Correlation(x1:x3, heat_map=TRUE)

# analysis with data not from data frame mycor
data(attitude)
mycor <- Correlation(rating, learning, data=attitude)

# analysis of entire data frame that is not mycor
data(attitude)
mycor <- Correlation(attitude)

```

**Description**

Abbreviation: reord

Re-arranges the order of the variables in the input correlation matrix. If no variable list is specified then the variables are re-ordered according to hierarchical clustering or the Hunter (2973) chain method in which the first variable is the variable with the largest sum of squared correlations of all the variables, then the variable that has the highest correlation with the first variable, and so forth.

**Usage**

```
corReorder(R=mycor, order=c("hclust", "chain", "manual"),
           hclust_type = c("complete", "ward.D", "ward.D2", "single",
                          "average", "mcquitty", "median", "centroid"),
           n_clusters=NULL, vars=NULL, chain_first=0,
           heat_map=TRUE, diagonal_new=TRUE,
           main=NULL, bottom=3, right=3,
           pdf_file=NULL, width=5, height=5, ...)

reord(...)
```

**Arguments**

R	Correlation matrix.
order	Source of ordering (seriation): Hierarchical cluster matrix, Hunter(1973) chain method, or manually specified with vars.
hclust_type	Type of hierarchical cluster analysis.
n_clusters	For a hierarchical cluster analysis, get the cluster membership for the specified number of clusters.
vars	List of the re-ordered variables, each variable listed by its ordinal position in the input correlation matrix. If this is set, then order set to "manual".
chain_first	The first variable listed in the ordered matrix with the chain method.
main	Graph title. Set to main="" to turn off.
heat_map	If TRUE, display a heat map of the item correlations.
diagonal_new	If TRUE, replace diagonal for the heat map only with an average of the correlation of item on the diagonal with the two adjacent items.
bottom	Number of lines of bottom margin.
right	Number of lines of right margin.
pdf_file	Name of the pdf file to which graphics are redirected.
width	Width of the pdf file in inches.
height	Height of the pdf file in inches.
...	Parameter values_

**Details**

Reorder and/or delete variables in the input correlation matrix.

Define the constituent variables, the items, with a listing of each variable by its name in the correlation matrix. If the specified variables are in consecutive order in the input correlation matrix, the list can be specified by listing the first variable, a colon, and then the last variable. To specify multiple variables, a single variable or a list, separate each by a comma, then invoke the R combine or `c` function. For example, if the list of variables in the input correlation matrix is from m02 through m05, and the variable Anxiety, then define the list in the `corReorder` function call according to `vars=c(m02:m05, Anxiety)`.

Or, define the ordering with a hierarchical cluster analysis from the base R function `hclust()`. The same default type of "complete" is provided, though this can be changed with the parameter `hclust_type` according to [hclust](#).

Or, use the Hunter (1973) chain method. Define the ordering of the variables according to the following algorithm. If no variable list is specified then the variables are re-ordered such that the first variable is that which has the largest sum of squared correlations of all the variables, then the variable that has the highest correlation with the first variable, and so forth.

In the absence of a variable list, the first variable in the re-ordered matrix can be specified with the `chain_first` option.

### Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

### References

Hunter, J.E. (1973), Methods of reordering the correlation matrix to facilitate visual inspection and preliminary cluster analysis, *Journal of Educational Measurement*, 10, p51-61.

### See Also

[Correlation](#), [hclust](#).

### Examples

```
# input correlation matrix of perfect two-factor model
# Factor Pattern for each Factor: 0.8, 0.6, 0.4
# Factor-Factor correlation: 0.3
mycor <- matrix(nrow=6, ncol=6, byrow=TRUE,
c(1.000,0.480,0.320,0.192,0.144,0.096,
  0.480,1.000,0.240,0.144,0.108,0.072,
  0.320,0.240,1.000,0.096,0.072,0.048,
  0.192,0.144,0.096,1.000,0.480,0.320,
  0.144,0.108,0.072,0.480,1.000,0.240,
  0.096,0.072,0.048,0.320,0.240,1.000))
colnames(mycor) <- c("V1", "V2", "V3", "V4", "V5", "V6")
rownames(mycor) <- colnames(mycor)

# leave only the 3 indicators of the second factor
# in reverse order
#replace original mycor
mycor <- corReorder(vars=c(V6,V5,V4))

# reorder according to results of a hierarchical cluster analysis
mynewcor <- corReorder()

# get cluster membership for two clusters
# specify each parameter
mynewcor <- corReorder(mycor, order="hclust", n_clusters=2)

# reorder with first variable with largest sums of squares
```



```

mynewcor <- corReorder(order="chain")

# reorder the variables according to the ordering algorithm
# with the 4th variable listed first
# no heat map
mynewcor <- corReorder(chain_first=2, heat_map=FALSE)

mycor <- matrix(nrow=6, ncol=6, byrow=TRUE,
c(1.000,0.480,0.320,0.192,0.144,0.096,
  0.480,1.000,0.240,0.144,0.108,0.072,
  0.320,0.240,1.000,0.096,0.072,0.048,
  0.192,0.144,0.096,1.000,0.480,0.320,
  0.144,0.108,0.072,0.480,1.000,0.240,
  0.096,0.072,0.048,0.320,0.240,1.000))
colnames(mycor) <- c("V1", "V2", "V3", "V4", "V5", "V6")
rownames(mycor) <- colnames(mycor)

# can also re=order with index position of each variable
mycor <- corReorder(vars=c(4,5,6,1,2,3))

```

---

corScree

*Eigenvalue Plot of a Correlation Matrix*


---

## Description

Abbreviation: scree

Plots the successive eigenvalues of an input correlation matrix. Also plots the successive differences of the eigenvalues\_ The purpose is usually to help determine the number of factors that explain the correlations in a correlation matrix. So usually a prelude to an exploratory factor analysis, such as provided by the lessR function `corEFA`. This program relies upon the standard R exploratory factor analysis `factanal`, which requires the specified number of factors as an input to the analysis.

## Usage

```
corScree(x=mycor,
         main=NULL, pdf=FALSE, width=5, height=5, ...)
```

```
scree(...)
```

## Arguments

x	Correlation matrix.
main	Graph title, which is blank by default.
pdf	Indicator as to if the graphic files should be saved as pdf files instead of directed to the standard graphics windows.
width	Width of the pdf file in inches.
height	Height of the pdf file in inches.
...	Parameter values_

## Details

Interpretation of the scree plot to assist in the assessment of the number of factors that account for the structure of a correlation matrix depends primarily on the analysis of the differences between the successive eigenvalues. The differences begin to diminish where the "scree" begins, analogous to the debris that falls off of a hill top. Accordingly both the scree plot itself, the plot of the successive eigenvalues, and the plot of the differences of the successive eigenvalues are presented.

### PDF OUTPUT

Because of the customized graphic windowing system that maintains a unique graphic window for the Help function, the standard graphic output functions such as `pdf` do not work with the `lessR` graphics functions. Instead, to obtain pdf output, use the `pdf_file` option, perhaps with the optional `width` and `height` options. These files are written to the default working directory, which can be explicitly specified with the R `setwd` function.

If the two plots, of the population and sample distributions respectively, are written to pdf files, according to `pdf=TRUE`, they are named `Scree.pdf` and `ScreeDiff.pdf`. Their names and the directory to which they are written are provided as part the console output.

## Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

## References

Gerbing, D. W. (2014). *R Data Analysis without Programming*, Chapters 9 and 10, NY: Routledge.

## See Also

[Correlation](#).

## Examples

```
# input correlation matrix of perfect two-factor model
# Factor Pattern for each Factor: 0.8, 0.6, 0.4
# Factor-Factor correlation: 0.3
mycor <- matrix(nrow=6, ncol=6, byrow=TRUE,
c(1.000,0.480,0.320,0.192,0.144,0.096,
  0.480,1.000,0.240,0.144,0.108,0.072,
  0.320,0.240,1.000,0.096,0.072,0.048,
  0.192,0.144,0.096,1.000,0.480,0.320,
  0.144,0.108,0.072,0.480,1.000,0.240,
  0.096,0.072,0.048,0.320,0.240,1.000))
colnames(mycor) <- c("V1", "V2", "V3", "V4", "V5", "V6")
rownames(mycor) <- colnames(mycor)

# obtain the scree plots
corScree()

# abbreviated form
scree()
```

---

CountAll

*CountAll Descriptive Analysis of all Variables in the Data Frame*

---

### Description

Automatically call the following functions in this package: [SummaryStats](#), [Histogram](#) and [BarChart](#). The result is set of summary statistics for every variable in the data frame, by default called d, a histogram for each numerical variable and a bar chart for each categorical variable.

### Usage

```
CountAll(x=d, quiet=FALSE, ...)
```

```
ca(...)
```

### Arguments

x	Data frame that contains the variables to analyze, by default d.
quiet	Suppress text output if TRUE.
...	Other parameter values for graphics.

### Details

CountAll is designed to work in conjunction with the lessR function [Read](#), which reads a csv or other formatted data file into the data frame d. All the bar charts and associated summary statistics are written to one file and all the histograms and associated summary statistics for the numerical variables are written to another file.

### Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

### See Also

[SummaryStats](#), [Histogram](#), [BarChart](#).

### Examples

```
# create data frame called d
n <- 12
X <- sample(c("Group1", "Group2"), size=n, replace=TRUE)
Y <- rnorm(n=n, mean=50, sd=10)
d <- data.frame(X, Y)
rm(X); rm(Y);

# CountAll descriptive analysis of d
CountAll()
# short name
ca()
```

dataBodyMeas

*Data: Body Measurements*

---

**Description**

Body measurements of 170 women and 170 men who purchased motorcycle clothing from Gerbing's Heated Clothing, Inc., now Gordon's Heated Clothing, LLC.

**Usage**

```
data(dataBodyMeas)
```

**Format**

A data table with 340 observations and the following 7 variables.

Gender, "M" or "F" (factor)

Weight (integer in pounds)

Height (integer in inches)

Waist (integer in inches)

Hips (integer in inches)

Chest (integer in inches)

Hand (numeric, circumference of hand in inches to nearest quarter of an inch)

Shoe (numeric, size including half sizes)

**Source**

author

---

dataCars93

*Data: Cars93*

---

**Description**

1993 New Car Data.

**Usage**

```
data(dataCars93)
```

**Format**

A data table with 93 observations and 25 variables.

**Variables**


---

Make: Model  
 Type: Small, Sporty, Compact, Midsize, Large  
 MinPrice: Minimum Price (in \$1,000) - Price for basic version of this model  
 MidPrice: Midrange Price (in \$1,000) - Average of Min and Max prices  
 MaxPrice: Maximum Price (in \$1,000) - Price for a premium version  
 MPGcity: City MPG  
 MPGhiway: Highway MPG  
 Airbags: 0 = none, 1 = driver only, 2 = driver & passenger  
 DriveTrain: 0 = rear wheel drive, 1 = front wheel drive, 2 = all wheel drive  
 Cylinders: Number of cylinders  
 Engine: Engine size (liters)  
 HP: maximum Horsepower  
 RPM: revolutions per minute at maximum horsepower  
 RevMile: Engine revolutions per mile in highest gear  
 Manual: Manual transmission available, 0 = No, 1 = Yes  
 FuelCap: Fuel tank capacity (gallons)  
 PassCap: Passenger capacity (persons)  
 Length: Length (inches)  
 Wheelbase: Wheelbase (inches)  
 Width: Width (inches)  
 Uturn: U-turn space (feet)  
 RearSeat: Rear seat room (inches)  
 LugCap: Luggage capacity (cu. ft.)  
 Weight: Weight (pounds)  
 Source: 0=non-USA manufacturer, 1=USA manufacturer

**Source**

Lock, R. H. (1993). 1993 new car data. *Journal of Statistics Education*, 1(1).

---

dataEmployee

*Data: Employees*

---

**Description**

Some human resource data on 37 employees with 6 variables. Variable labels and variable units are included in the data file.

**Usage**

data(dataEmployee)

**Format**

A data table with 37 observations.

Years,"Years Employed in the Company"  
 Gender,"Male or Female"  
 Dept,"Department Employed"  
 Salary,"Annual Salary (USD)"  
 JobSat,"JobSat with Work Environment"  
 Plan,"1=GoodHealth, 2=YellowCross, 3=BestCare"  
 Pre,"Test score on legal issues before instruction"  
 Post,"Test score on legal issues after instruction"

**Source**

author

---

dataEmployee_lbl	<i>VariableLabels: Employee Data Set</i>
------------------	--

---

**Description**

For the data on 37 employees with 6 variables, includes the variable labels and variable units.

**Usage**

data(dataEmployee\_lbl)

**Format**

Variable labels, and some unites..

Years,"Years Employed in the Company"  
 Gender,"Male or Female"  
 Dept,"Department Employed"  
 Salary,"Annual Salary (USD)"  
 JobSat,"JobSat with Work Environment"  
 Plan,"1=GoodHealth, 2=YellowCross, 3=BestCare"  
 Pre,"Test score on legal issues before instruction"  
 Post,"Test score on legal issues after instruction"

**Source**

author

---

`dataJackets`*Data: Motorcycle Type and Thickness of Jacket*

---

**Description**

Two variables, one is type of motorcycle and the other is the thickness of the purchased jacket.

**Usage**

```
data(dataJackets)
```

**Format**

A data table with 1025 observations.

Bike, "Type of Motorcycle, Honda or BMW"  
Jacket, "Lite, Med or Thick"

**Source**

author

---

`dataLearn`*Data: Distributed vs Massed Practice*

---

**Description**

Completely Randomized design, one-factor with two levels (CR-2): One grouping variable that specifies type of learning, distributed or massed practice, and one response variable, Learning.

**Usage**

```
data(dataLearn)
```

**Format**

A data table with 34 observations.

**Source**

author

dataMach4

*Data: Machiavellianism*

---

**Description**

Likert data responses to Christie and Geiss's (1970) Mach~IV scale from Hunter, Gerbing and Boster (1982).

All Likert items assessed on a 6-point scale from 0: Strongly Disagree to 5: Strongly Agree. Variable labels, the item content, are included.

The following items should be reverse scored: m03, m04, m06, m07, m09, m10, m11, m14, m16, m17, m19

**Usage**

```
data(dataMach4)
```

**Format**

A data table with 351 observations.

Gender, 1 column, 0:Male, 1:Female

Mach IV, 20 Likert items: m01, m02, . . . , m20, see [dataMach4\\_lbl](#) for the item content.

**Source**

author

**References**

Christie, R., & Geis, F. L., (1970). Studies in Machiavellianism. New York: Academic Press.

Hunter, J. E., Gerbing, D. W., and Boster, F. J. (1982). Machiavellian beliefs and personality: The construct invalidity of the Machiavellian dimension. *Journal of Personality and Social Psychology*, 43, 1293-1305.

---

dataMach4\_lbl*VariableLabels: Mach4 Data Set*

---

**Description**

For the data of 351 responses to the 20-item Mach IV scale.

**Usage**

```
data(dataMach4_lbl)
```



**Format**

Variable labels, the items of the Christie and Geiss Mach IV Scale

- m01: Never tell anyone the real reason you did something unless it is useful to do so
- m02: The best way to handle people is to tell them what they want to hear
- m03: One should take action only when sure it is morally right
- m04: Most people are basically good and kind
- m05: It is safest to assume that all people have a vicious streak and it will come out when they are given a chance
- m06: Honesty is the best policy in all cases
- m07: There is no excuse for lying to someone else
- m08: Generally speaking, people won't work hard unless they're forced to do so
- m09: All in all, it is better to be humble and honest than to be important and dishonest
- m10: When you ask someone to do something for you, it is best to give the real reasons for wanting it rather than giving reasons which carry more weight
- m11: Most people who get ahead in the world lead clean, moral lives
- m12: Anyone who completely trusts anyone else is asking for trouble
- m13: The biggest difference between most criminals and other people is that the criminals are stupid enough to get caught
- m14: Most people are brave
- m15: It is wise to flatter important people
- m16: It is possible to be good in all respects
- m17: Barnum was wrong when he said that there's a sucker born every minute
- m18: It is hard to get ahead without cutting corners here and there
- m19: People suffering from incurable diseases should have the choice of being put painlessly to death
- m20: Most people forget more easily the death of a parent than the loss of their property

**Source**

author

**References**

- Christie, R., & Geis, F. L., (1970). *Studies in Machiavellianism*. New York: Academic Press.
- Hunter, J. E., Gerbing, D. W., and Boster, F. J. (1982). Machiavellian beliefs and personality: The construct invalidity of the Machiavellian dimension. *Journal of Personality*

---

dataReading

*Data: Reading Ability*

---

**Description**

Reading ability test score and also verbal aptitude test score, number of absences from school and family income in USD \$1000's. Data are simulated.

**Usage**

```
data(dataReading)
```

**Format**

A data table with 100 observations.

**Source**

author

---

dataStockPrice	<i>Data: Stock price of Apple, IBM and Intel from 1980 through January of 2019</i>
----------------	--

---

**Description**

Monthly adjusted stock price of Apple, IBM and Intel from 1980 through January of 2019 from finance.yahoo.com.

**Usage**

```
data(dataStockPrice)
```

**Format**

A data table in tidy format with three variables: month, Company and Price. The variable month is a date expression expressed as a four digit year, followed by a month, then a day, separated by either dashes. A total of 1374 rows, 458 rows per company.

**Source**

author

**Description**

Abbreviation: dn

Plots a normal density curve and/or a general density curve superimposed over a histogram, all estimated from the data. Also reports the Shapiro-Wilk normality test and summary statistics.

If the provided object to analyze is a set of multiple variables, including an entire data frame, then each non-numeric variable in the data frame is analyzed and the results written to the current graphics device or to a pdf file in the current working directory. The name of each output pdf file that contains a bar chart and its path are specified in the output.

When output is assigned into an object, such as `d` in `d <- dn(Y)`, the pieces of output can be accessed for later analysis. A primary such analysis is `knitr` for dynamic report generation from an R markdown document in which R output is embedded in documents, facilitated by the `Rmd` option. See value below.

**Usage**

```
Density(x, data=d, filter=NULL,
        n_cat=getOption("n_cat"), Rmd=NULL,

        bw=NULL, type=c("general", "normal", "both"),
        histogram=TRUE, bin_start=NULL, bin_width=NULL,

        color_nrm="gray20", color_gen="gray20",
        fill_nrm=NULL, fill_gen=NULL,

        rotate_x=0, rotate_y=0, offset=0.5,

        x.pt=NULL, xlab=NULL, main=NULL, sub=NULL, y_axis=FALSE,
        x.min=NULL, x.max=NULL,
        rug=FALSE, color_rug="black", size_rug=0.5,

        eval_df=NULL, digits_d=NULL, quiet=getOption("quiet"),
        width=4.5, height=4.5, pdf=FALSE,
        fun_call=NULL, ...)

dn(...)
```

**Arguments**

`x` Variable(s) to analyze. Can be a single numerical variable, either within a data frame or as a vector in the user's workspace, or multiple variables in a data frame such as designated with the `c` function, or an entire data frame. If not specified, then defaults to all numerical variables in the specified data frame, `d` by default.

<code>data</code>	Optional data frame that contains the variable(s) of interest, default is <code>d</code> .
<code>filter</code>	A logical expression that specifies a subset of rows of the data frame to analyze.
<code>n_cat</code>	For the analysis of multiple variables, such as a data frame, specifies the largest number of unique values of variable of a numeric data type for which the variable will be analyzed as categorical. Default is 0.
<code>Rmd</code>	File name for the file of R markdown to be written, if specified. The file type is <code>.Rmd</code> , which automatically opens in RStudio, but it is a simple text file that can be edited with any text editor, including RStudio.
<code>bw</code>	Bandwidth of kernel estimation. Initial value is "nrd0", but unless specified, then may be iterated upward to create a smoother curve.
<code>type</code>	Type of density curve plotted. By default, the general density is plotted, though can request the normal density and both densities.
<code>histogram</code>	If TRUE overlay the density plot over a histogram.
<code>bin_start</code>	Optional specified starting value of the bins.
<code>bin_width</code>	Optional specified bin width, which can be specified with or without a <code>bin_start</code> value.
<code>color_nrm</code>	Color of the normal curve.
<code>color_gen</code>	Color of the general density curve.
<code>fill_nrm</code>	Fill color for the estimated normal curve, with a partially transparent blue as the default, and transparent for the gray theme.
<code>fill_gen</code>	Fill color for the estimated general density curve, with a partially transparent light red as the default, and a light transparent gray for the gray theme.
<code>rotate_x</code>	Degrees that the x-axis values are rotated, usually to accommodate longer values, typically used in conjunction with <code>offset</code> .
<code>rotate_y</code>	Degrees that the y-axis values are rotated.
<code>offset</code>	The amount of spacing between the axis values and the axis_ Default is 0.5. Larger values such as 1.0 are used to create space for the label when longer axis value names are rotated.
<code>x.pt</code>	Value of the point on the x-axis for which to draw a unit interval around illustrating the corresponding area under the general density curve. Only applies when requesting <code>type=general</code> .
<code>xlab</code>	Label for x-axis_ Defaults to variable name unless variable labels are present, the defaults to also include the corresponding variable label. Can style with the <code>lessR style</code> function.
<code>main</code>	Label for the title of the graph. Can set size with <code>main_cex</code> and color with <code>main_color</code> from the <code>lessR style</code> function.
<code>sub</code>	Sub-title of graph, below <code>xlab_</code>
<code>y_axis</code>	Specifies if the y-axis, the density axis, should be included.

x.min	Smallest value of the variable x plotted on the x-axis_
x.max	Largest value of the variable x plotted on the x-axis_
rug	If TRUE, add a rug plot, a direct display of density in the form of a narrow band beneath the density curve.
color_rug	Color of the rug ticks.
size_rug	Line width of the rug ticks.
eval_df	Determines if to check for existing data frame and specified variables. By default is TRUE unless the shiny package is loaded then set to FALSE so that Shiny will run. Needs to be set to FALSE if using the pipe %\>% notation.
digits_d	Number of significant digits for each of the displayed summary statistics.
quiet	If set to TRUE, no text output. Can change system default with <a href="#">style</a> function.
width	Width of the plot window in inches, defaults to 4.5.
height	Height of the plot window in inches, defaults to 4.5.
pdf	If TRUE, graphics are to be redirected to a pdf file.
fun_call	Function call. Used with <code>knitr</code> to pass the function call when obtained from the abbreviated function call <code>dn</code> .
...	Other parameter values for graphics as defined processed by <a href="#">plot</a> , including <code>xlim</code> , <code>ylim</code> , <code>lwd</code> and <code>lab_cex</code> , <code>color_main</code> , <code>color_lab</code> , <code>sub</code> , <code>color_sub</code> , and <code>color_ticks</code> to specify the color of the ticks used to label the axis values, <code>density</code> , for the general density calculations, can set bandwidth with the standard <code>bw</code> .

## Details

### OVERVIEW

Results are based on the standard [dnorm](#) function and [density](#) R functions for estimating densities from data, as well as the [hist](#) function for calculating a histogram. Colors are provided by default and can also be specified.

The default histogram can be modified with the `bin_start` and `bin_width` options. Use the [Histogram](#) function in this package for more control over the parameters of the histogram.

The limits for the axes are automatically calculated so as to provide sufficient space for the density curves and histogram, and should generally not require user intervention. Also, the curves are centered over the plot window so that the resulting density curves are symmetric even if the underlying histogram is not. The estimated normal curve is based on the corresponding sample mean and standard deviation.

If `x.pt` is specified, then `type` is set to `general` and `y_axis` set to `TRUE`.

### DATA

The data may either be a vector from the global environment, the user's workspace, as illustrated in the examples below, or one or more variable's in a data frame, or a complete data frame. The default input data frame is `d`. Can specify the source data frame name with the `data` option. If multiple variables are specified, only the numerical variables in the list of variables are analyzed. The variables in the data frame are referenced directly by their names, that is, no need to invoke the

standard R mechanisms of the `d$name` notation, the `with` function or the `attach` function. If the name of the vector in the global environment and of a variable in the input data frame are the same, the vector is analyzed.

The `filter` parameter subsets rows (cases) of the input data frame according to a logical expression. Use the standard R operators for logical statements as described in [Logic](#) such as `&` for and, `|` for or and `!` for not, and use the standard R relational operators as described in [Comparison](#) such as `==` for logical equality `!=` for not equals, and `>` for greater than.

#### COLOR THEME

Individual colors in the plot can be manipulated with options such as `color_bars` for the color of the histogram bars. A color theme for all the colors can be chosen for a specific plot with the `colors` option with the `lessR` function `style`. The default color theme is blue, but a gray scale is available with `"gray"`, and other themes are available as explained in `style`, such as `"red"` and `"green"`. Use the option `style(sub_theme="black")` for a black background and partial transparency of plotted colors.

#### VARIABLE LABELS

If variable labels exist, then the corresponding variable label is by default listed as the label for the horizontal axis and on the text output. For more information, see [Read](#).

#### PDF OUTPUT

To obtain pdf output, use the `pdf` option, perhaps with the optional `width` and `height` options. These files are written to the default working directory, which can be explicitly specified with the `setwd` function.

#### ONLY VARIABLES ARE REFERENCED

The referenced variable in a `lessR` function can only be a variable name (or list of variable names). This referenced variable must exist in either the referenced data frame, such as the default `d`, or in the user's workspace, more formally called the global environment. That is, expressions cannot be directly evaluated. For example:

```
> Density(rnorm(50)) # does NOT work
```

Instead, do the following:

```
> Y <- rnorm(50) # create vector Y in user workspace
> Density(Y)     # directly reference Y
```

### Value

The output can optionally be saved into an R object, otherwise it simply appears in the console. Re-designed in `lessR` version 3.3 to provide two different types of components: the pieces of readable output, and a variety of statistics. The readable output are character strings such as tables amenable for reading. The statistics are numerical values amenable for further analysis. The motivation of these types of output is to facilitate R markdown documents, as the name of each piece, preceded by the name of the saved object and a `$`, can be inserted into the R-Markdown document (see examples).

#### READABLE OUTPUT

`codeout_title`: Title of output

`codeout_stats`: Statistics

`codeout_file`: Name and location of optional R markdown file

**STATISTICS**

codebw: Bandwidth parameter  
coden: Number of data values analyzed  
coden.miss: Number of missing data values  
codeW: W statistic for Shapiro-Wilk normality test  
codepvalue: p-value for W statistic

Although not typically needed, if the output is assigned to an object named, for example, h, then the contents of the object can be viewed directly with the [unclass](#) function, here as `unclass(h)`.

**Author(s)**

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

**See Also**

[dnorm](#), [density](#), [hist](#), [plot](#), [rgb](#), [shapiro.test](#).

**Examples**

```
# make sure default style is active
style()

# create data frame, d, to mimic reading data with Read function
# d contains both numeric and non-numeric data
d <- data.frame(rnorm(50), rnorm(50), rnorm(50), rep(c("A","B"),25))
names(d) <- c("X","Y","Z","C")

# normal curve and general density curves superimposed over histogram
# all defaults
Density(Y, type="both")

# short name
dn(Y)

# save the density plot to a pdf file
#Density(Y, pdf=TRUE)

# specify (non-transparent) colors for the curves,
# to make transparent, need alpha option for the rgb function
Density(Y, color_nrm="darkgreen", color_gen="plum")

# rug with custom color and width of ticks
Density(Y, color_rug="steelblue", size.rug=1)

# display only the general estimated density
# so do not display the estimated normal curve
# specify the bandwidth for the general density curve,
# use the standard bw option for the density function
Density(Y, bw=.6)
```

```

# display only the general estimated density and a corresponding
# interval of unit width around x.pt
Density(Y, x.pt=2)

# generate R markdown file to be "knit" such as in RStudio
#dn(Y, Rmd="myout")

# variable of interest is in a data frame which is not the default d
# access the breaks variable in the R provided warpbreaks data set
# although data not attached, access the variable directly by its name
Density(breaks, data=warpbreaks)

# densities for all numeric variables in a data frame
Density()
# densities for an integer variable with less than n_cat equally
# spaced values, so treat as numeric instead of categorical
# Density(n_cat=0)

# densities for all specified numeric variables in a list of variables
# e.g., use the combine or c function to specify a list of variables
Density(c(X,Y))

```

---

 details

---

*Display Contents of a Data File and Optional Variable Labels*


---

## Description

Abbreviation: db

Provides feedback regarding a data frame which includes the variable names, the dimensions of the resulting data frame, the data type for each variable, and the values of the variables in the data file for the first and last rows of the data. In addition, an analysis of missing data is provided, listing the number of missing values for each variable and for each observation.

## Usage

```

details(data=d, n_mcut=1, miss_zero=FALSE, max_lines=30,
        miss_show=30, miss_matrix=FALSE, brief=getOption("brief"))

```

```

db(..., brief=TRUE)

```

## Arguments

data	Data frame for which to provide the details.
n_mcut	For the missing value analysis, list the row name and number of missing values if the number of missing exceeds or equals this cutoff.
miss_zero	For the missing value analysis, list the variable name or the row name even for values of 0. By default only variables and rows with missing data are listed.



<code>max_lines</code>	Maximum number of lines to list of the data and labels.
<code>miss_show</code>	For the missing value analysis, the number of rows, one row per observation, that has as many or missing values as <code>n_mcut</code> .
<code>miss_matrix</code>	For the missing value analysis, if there is any missing data, list a version of the complete data table with a 0 for a non-missing] value and a 1 for a missing value.
<code>brief</code>	If TRUE, display only variable names table plus any variable labels. The default for “details brief” abbreviation db.
<code>...</code>	Further arguments to be passed to or from methods consistent with the R <a href="#">read.table</a> function. For example, can set <code>stringsAsFactors</code> as TRUE.

## Details

### MISSING DATA

By default, `details` provides a list of each variable and each row with the display of the number of associated missing values, indicated by the standard R missing value code NA. To not list the variable name or row name of variables or rows without missing data, invoke the `miss_zero=FALSE` option, which can appreciably reduce the amount of output for large data sets. To view the entire data table in terms of 0's and 1's for non-missing and missing data, respectively, invoke the `miss_matrix=TRUE` option.

### VARIABLE LABELS

Standard R does not provide for variable labels, but `lessR` does. Variable labels can be provided for some or all of the variables in the data frames. One way to enter the variable labels is to read them from their own file with `details` with `labels` set to the full path name or URL of the labels file, or just the file name if the labels file is in the same directory as the data file. Another method is to include the labels directly in the data file. To do this, specify the file of variable labels with the `label="row2"` option. The web survey application Qualtrics downloads csv files in this format.

For a file that contains only labels, each row of the file, including the first row, consists of the variable name, a comma, and then the label, that is, standard csv format such as obtained with the `csv` option from a standard worksheet application such as Microsoft Excel or LibreOffice Calc. Not all variables in the data frame that contains the data, usually `d`, need have a label, and the variables with their corresponding labels can be listed in any order. An example follows.

```
I2,This instructor presents material in a clear and organized manner.
I4,Overall, this instructor was highly effective in this class.
I1,This instructor has command of the subject.
I3,This instructor relates course materials to real world situations.
```

If there is a comma in the variable label, then the label needs to be enclosed in quotes.

The `lessR` functions that provide analysis, such as `Histogram` for a histogram, automatically include the variable labels in their output, such as the title of a graph. Standard R functions can also use these variable labels by invoking the `label` function, such as setting `main=label(I4)` to put the variable label for a variable named `I4` in the title of a graph.

## Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

**See Also**[Read.](#)**Examples**

```
# read the built-in data set datEmployee
# this provides an automatic call to details
d <- Read("Employee")

# manually request the details for d
details()

# manually request just variable names, labels for d
db()
```

factors

*Create Factor Variables Across a Sequential Range or Vector of Variables***Description**

Creates factors for many variables. Specify a range from a given start variable and end variable. Applies only to variables in a data frame, `d` by default, and outputs the entire data frame including the factor transformation.

**Usage**

```
factors(x, levels, labels=NULL, data=d, ordered=FALSE,
        new=FALSE, suffix="_f", var_labels=FALSE, ...)
```

**Arguments**

<code>x</code>	Name of variable(s) to convert to a factor. List a single variable or a vector
<code>levels</code>	Levels for which to define the factor.
<code>labels</code>	Value labels to assign to the levels. If not present then assumes the character version of the levels.
<code>data</code>	The data frame of interest.
<code>ordered</code>	If <code>FALSE</code> , factor levels are not ordered.
<code>new</code>	If <code>FALSE</code> , original variables are replaced, otherwise new factor variables are created.
<code>suffix</code>	The appended suffix to newly created variables from the original variable names when <code>new</code> is <code>TRUE</code> .
<code>var_labels</code>	Just create new variable labels for newly created factor variables, without doing a factor conversion, presumably after a previous run with factors converted to new factor variables.
<code>...</code>	Other parameter values_

**Details**

Returns the entire data frame if applied to one or more variables in a data frame, including the new factors.

**Author(s)**

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

**Examples**

```
# get the data, variables Gender plus m01 through m20, 20 Mach IV items
# coded as integers from 0 to 5 on 6-pt Likert scales
d <- rd("Mach4", quiet=TRUE)

# single variable converted to a factor
d <- factors(Gender, 0:1, c("Male", "Female"))

# Define the labels
LikertCats <- c("Strongly Disagree", "Disagree", "Slightly Disagree",
               "Slightly Agree", "Agree", "Strongly Agree")

# Convert the integer responses to factors for the 20 Mach IV items
d <- factors(m01:m20, levels=0:5, labels=LikertCats)

# read the data again and this time also the variable labels
d <- rd("Mach4", quiet=TRUE)
l <- rd("Mach4_lbl")

# convert specified variables to factors according to the given vector
# of three variables only
# leave the original variables unmodified, create new variables
d <- factors(c(m06, m07, m20), levels=0:5, labels=LikertCats, new=TRUE)
# now copy the variable labels from the original integer variables to the
# newly created factor variables
l <- factors(c(m06, m07, m20), var_labels=TRUE)
```

---

getColors

*Hue, Chroma, Luminance (HCL) Color Wheel or Specified Colors*

---

**Description**

Generates vectors colors including HCL colors for qualitative and sequential color scales and displays colors, both those generated and also arbitrary colors manually specified. To avoid bias in the comparison of differently colored regions of a visualization, generates HCL colors by default with fixed values of chroma (saturation) and luminance (brightness) for a range of hues, by default ordered so that adjacent colors are as separated as possible. Also generates a sequence of HCL colors according to any chosen hue value in which chroma and luminance can be varied by implicit calls to Zeileis's et al. `sequential_hcl` function from Ihaka's et al. `colorspace` package, and also with pre-defined values such as "blues". Also processes any arbitrarily specified set of colors that are

specified, or generated from a custom range according to a beginning and ending specified color, and includes color palettes from the viridis and wesanderson packages.

In terms of workflow, use the function by itself to select a set of colors from the resulting color rectangle/wheel. The function outputs the colors so that the function call can serve as an argument to parameters in other functions that require a sequence of one or more colors as input, in which case the visualization of the color wheel or rectangle is not generated. So after the colors are selected, pass to an argument for a visualization function such as for the fill parameter.

## Usage

```
getColors(pal=NULL, end_pal=NULL,
          n=12, h=0, h2=NULL, c=NULL, l=NULL, trans=0,
          in_order=NULL, fixup=TRUE, power=NULL,
          shape=c("rectangle", "wheel"), radius=0.9, border="lightgray",
          main=NULL, labels=NULL, labels_cex=0.8, lty="solid",
          output=NULL, quiet=getOption("quiet"), ...)
```

## Arguments

pal	Palette of optional specified colors to plot. If a set of specified colors, then the following parameters are not relevant. Can also be pre-defined color codes that trigger a sequence of colors from light to dark, such as "blues", or "distinct" to maximize color separation.
end_pal	If specified, then generate a color continuum that begins at pal and ends at end_pal.
n	Number of colors to display.
h	Beginning HCL hue, 0 to 360.
h2	Ending HCL hue, 0 to 360. Defaults to a value close to 360. Requires in_order to be FALSE.
c	Value of HCL chroma (saturation). Respective default values for qualitative, sequential, and divergent scales are 60, c(35,75), and 50.
l	Value of HCL luminance (brightness). Respective default values for qualitative, sequential, and divergent scales are 50, c(80,25), and c(40,70).
trans	Transparency factor of the area of each slice from 0, no transparency to 1, full transparency.
in_order	If TRUE, orders the colors in order of their HCL hue values, the default for a "wheel". Otherwise maximizes the difference between adjacent colors hues to prepare for inclusion in visualizations with qualitative, discrete color scales.
fixup	R parameter name. If TRUE, then HCL values outside of the displayable RGB color space are transformed to fit into that space so as to display.
power	Power for generating a sequential or divergent HCL scale (via colorspace package) for potentially non-linear changes in chroma and luminance across the scale. Default for sequential is 1 and for divergent 0.75.

shape	Default is a "rectangle", or specify a "wheel".
radius	Size of wheel. Not applicable to the rectangular shape.
border	Color of the borders of each slice. Set to "off" or "transparent" to turn off.
main	Title.
labels	If TRUE, then displayed. For HCL qualitative scale, default is TRUE, otherwise FALSE.
labels_cex	Character expansion factor of labels relative to 1.
lty	Line type of the border.
output	Default to evaluate if function call at top level, so produce text and graphics output, or embedded in another function call, so do not produce that output. If set to "on", then do output. If set to "off" then do not do output.
quiet	If set to TRUE, no list of colors. Can change system default with <a href="#">style</a> function.
...	Other parameter values_

## Details

### I. HCL COLORS

Generate a palette of colors according to the parameter `pal` in the form of a character string vector of their names, and also as a color wheel if not called from another function. The default value (for all but grayscale or white color themes) of `pal` is "hues", which generates a qualitative palette of the specified number, `n`, of discrete HCL colors at the same chroma and luminance, respective default values of 60 and 50. With constant chroma and luminance the HCL color space provides a palette of colors with the same gray-scale intensities if desaturated. That means no brightness bias for viewing different colors that represent different areas, such as in a bar chart of two variables, or a pie chart. The primary qualification is that the HCL color space is not in a one-to-one correspondence with the RGB color space of computer monitors, so some HCL colors are approximated (with the default setting of the `fixup` parameter set to TRUE).

For "hues", the default, the hue values and associated colors are expressed as HEX and RGB values\_ The first 12 generated discrete colors are blue (240), brown (60), green (120), red (0), purple (275), turquoise (180), rust (30), olive (90), aqua (210), mulberry (330), emerald (150), and violet (300).

To have the generated colors be in the sequential order of hues, set `in_order` to TRUE, the default when `shape` is set to "wheel". For about up to five or six colors adjacent values are still reasonably well distinguished even if in sequential order of hue number in the hcl space.

### II. COLOR SEQUENCE

A second possibility is to generate a sequence of colors according to the value of `n` from a given start color to an ending color\_ To specify a custom range, set `pal` as the value of the first color, and then `end_pal` as the value of the last color in the color range. The colors in the sequence may or may not be of the same hue.

Or, access implicit calls Zeileis (2009) [sequential\\_hcl](#) and [diverge\\_hcl](#) functions from the `colorspace` package to access pre-defined color ranges including "grays", which is the default if the color theme is "gray" or "white". Other predefined sequences are shown in the following

table. Also can invoke the standard R color ranges of "heat", "terrain", and "rainbow". Can specify any value of hue with h. Can also provide custom values of chroma (c) and luminance (l), with either one a range of values defined as a vector of two values\_ Default values are c=100 and l=c(75, 35). That is, the color sequence is generated according to the given hue, h, with a chroma of 100 and luminance varying from 75 to the darker 45.

The predefined sequences consist of the following hues and color names, defined in 30 degree increments around the HCL color wheel. Visualize the color wheel with then discrete colors below with the lessR function `getColors`, specifically the function call `getColors(shape="wheel")`. Visualize sequential color scales for each of the colors below with the lessR function `showPalettes`.

colors	param	value
"reds"	h	0
"rusts"	h	30
"browns"	h	60
"olives"	h	90
"greens"	h	120
"emeralds"	h	150
"turquoises"	h	180
"aquas"	h	210
"blues"	h	240
"purples"	h	270
"violets"	h	300
"magentas"	h	330
"grays"	c	0

The predefined color name can be provided as the first argument of the function call, that is, the value of `pal`, or the corresponding value of `h` (or `c` for gray scale) can be specified. The specifications are equivalent. To specify a divergent color scale, provide both the value of `pal` as the beginning value and the value of `end_pal` as the last value, such that both values are one of the pre-specified color ranges. In either situation, of sequential or divergent color scales, custom values of `c` and `l` can be provided.

### III. SPECIFIED COLORS

The third possibility is to generate a color wheel from a specified set of color values. Set the value of `pal` according to the vector of these values\_ Specify the values with R color names (see the lessR function `showColors`), RGB values according to the `rgb` function or from related R color space functions such as `hcl`, or as hexadecimal codes.

### IV. OTHER INCLUDED COLOR PALETTES

The following palettes are from the `viridis` package: "viridis", "cividis", "magma", "inferno", "plasma".

Movie director Wes Anderson is known for is innovative color themes in his movies, which feature a combination of pastel colors and bold primary colors. The following palettes are from the `wesanderson` package, based the colors from his movies: "BottleRocket1", "BottleRocket2", "Rushmore1",

"Rushmore", "Royal1", "Royal2", "Zissou1", "Darjeeling1", "Darjeeling2 ", "Chevalier1", "FantasticFox1", "Moonrise1", "Moonrise2", "Moonrise3", "Cavalcanti1", "GrandBudapest1", "GrandBudapest2", "IsleofDogs1", "IsleofDogs2". The generation of the corresponding palettes are with type set to "continuous" to generalize to palettes of any length.

The palette "distinct" specifies a sequence of 20 colors manually chosen for the distinctiveness. The first five colors are from the qualitative sequence of hcl colors with  $c=90$  and  $l=50$ . To maximise color separation, the remaining 15 colors do not satisfy constance levels of  $c$  and  $l$ . Use such as for plotting with a by variable with up to 20 levels.

#### FUNCTION USAGE

Use the function on its own, in which case the color rectangle/wheel visualization is generated as are the color values\_ The vector of color values may be saved in its own R object as the output of the function call. Or, use the function to set colors for other parameter values in other function calls. See the examples.

#### Value

Colors are invisibly returned as a character string vector.

#### See Also

[hcl](#), [showColors](#)

#### Examples

```
# HCL color wheels/rectangles
#-----
# set in_order to TRUE for hues ordered by their number

# color spectrum of 12 hcl colors presented in the order
# in which they are assigned to discrete levels of a
# categorical variable
getColors()

# color spectrum of 12 hcl colors ordered by hue from 0
# by intervals of  $360/12 = 30$  degrees
getColors(in_order=TRUE)

# pastel hcl colors, set luminance to 85 from default of 50
getColors(in_order=TRUE, l=85)

# color wheel of 36 ordered hues around the wheel
getColors(n=36, shape="wheel", border="off")

# ggplot qualitative colors, here for 3 colors generated
# in order of their hue numbers across the color wheel
# starting at a hue of 15 degrees and luminance of 60
getColors(h=15, n=3, l=60, in_order=TRUE)

# HCL Qualitative Scale
# -----
```

```
# default pre-defined 12 hcl colors that were manually reordered
# so that adjacent colors achieve maximum separation
getColor()

# deep rich colors for HCL qualitative scale
getColor(c=90, l=45)

# HCL Sequential Scales
# -----
# generate hcl blue sequence with c=60 and vary l
getColor("blues", labels=FALSE)

# generate yellow hcl sequence with varying chroma
getColor("browns", c=c(20,90), l=60)

# non-linear grayscale, more concentration of colors at the beginning
getColor("black", "white", n=24, power=0.75)

# generate custom hue color sequence close to colorbrewer Blues
# library(RColorBrewer)
# getColor(brewer.pal(6, "Blues"))
# compare, vary both l and c
getColor(h=230, n=6, l=c(96,30), c=c(5,80))

# a standard R color sequence
getColor("heat")

# from Wes Anderson
getColor("Moonrise2", n=12)

# maximally distinct
getColor("distinct", n=20)

# HCL Divergent Scales
# -----
# seven colors from rust to blue
getColor("rusts", "blues", n=7)

# add a custom value of chroma, c, to make less saturated
getColor("rusts", "blues", n=7, c=45)

# Manual Specification of Colors
# -----
# individually specified colors
getColor(c("black", "blue", "red"))

# custom sequential range of colors
getColor(pal="aliceblue", end_pal="blue")
```



```

# Plots
# -----
d <- rd("Employee")

# default quantitative scale
bc(d, Dept, fill=getColors())
# or with implicit call to getColors
bc(d, Dept, fill="hues")
# or an implicit call with the blues
bc(d, Dept, fill="blues")

# even though we have a bar graph, also want the
# graph of the colors as well as the text listing of the colors
bc(d, Dept, fill=getColors("blues", output="on"))

# custom hue with different chroma levels (saturations)
BarChart(d, Dept, fill=getColors(h=230, c=c(20,60), l=60, n=5))

# custom hue with different luminance levels (brightness)
# if explicitly calling getColors need to also specify n
Histogram(Salary, fill=getColors(h=230, c=60, l=c(90,30), n=10))

# use the default qualitative viridis color scale
bc(d, Dept, fill="viridis")

```

## Description

R works by entering function names and arguments. R provides extensive help for each available function based on a function's name, but these names are not apparent to someone who has not memorized the names. To alleviate this problem, this help system suggests and briefly explains various function calls regarding a requested topic for statistical analysis. The primary call is `Help()`, which displays the main help menu in a persistent graphics window, that is, which remains until explicitly closed by the user regardless of additional graphics analyses. Each specific Help window can be called with any of the function names, or their abbreviations or related expressions. The argument can be expressed in any combination of uppercase or lowercase letters.

## Usage

```
Help(topic=NULL, width=4.5, height=4.5)
```

## Arguments

topic	Message reference, either null to specify a list of available topics or a specific argument to reference a specific help message.
width	Width of Help window.
height	Height of Help window.

**Details**

Help() displays a list of help topics, listed below.

Help("topic") generally displays the available functions relevant for the specified topic. If the name of the topic is a lessR statistical function, the abbreviated form of the name can also be invoked.

Help("lessR") calls up the link to the lessR manual and news, which includes current updates.

—

style: System level settings, such as a color theme for graphics.

data: Create a csv data file from a worksheet application.

Read: Read an external data file in csv format.

Write: Write the contents of d to a data file in csv format.

library: Many libraries of functions developed by others can be added to R.

transform: Edit and create new variables from existing variables.

—

Histogram: Histogram, box plot, dot plot and density curve..

BarChart: Bar chart or pie chart of a categorical variable.

LineChart: Run chart or time series chart.

Plot: Scatterplot for one or two variables, line chart.

—

SummaryStats: Summary statistics for one and two variables.

one.sample: Analysis of a single sample of data.

ttest: The mean difference and related statistics.

ANOVA: Compare means across two or more groups.

power: Power analysis for the t-test.

Correlation: Correlation analysis.

Regression: Regression analysis.

Logit: Logistic regression analysis.

factor.analysis: Confirmatory or exploratory factor analysis.

—

prob: Probabilities for Normal and t-distributions.

random: Random number generation.

sample: Generate random samples.

—

lessR: lessR manual and list of updates to current version

**Author(s)**

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

**See Also**

[help](#).

**Examples**

```
# list the information needed to access a specific topic
Help()

# specific help message regarding a histogram and related functions
Help(Histogram)

# other ways to call the same help message
#Help(histogram) # case insensitive
#Help(hs)
#Help(hist)
#Help(hst)
#Help(boxplot)
```

---

Histogram

*Histogram*

---

**Description**

Abbreviation: `hs`

From the standard R function `hist`, plots a frequency histogram with default colors, including background color and grid lines plus an option for a relative frequency and/or cumulative histogram, as well as summary statistics and a table that provides the bins, midpoints, counts, proportions, cumulative counts and cumulative proportions. Bins can be selected several different ways besides the default, including specifying just the bin width and/or the bin start. Also provides improved error diagnostics and feedback for the user on how to correct the problem when the bins do not contain all of the specified data.

If a set of multiple variables is provided, including an entire data frame, then each numeric variable in that set of variables is analyzed, with the option to write the resulting histograms to separate pdf files. The related `CountAll` function does the same for all variables in the set of variables, histograms for continuous variables and bar charts for categorical variables. Specifying a `by1` or `by2` variable implements Trellis graphics.

When output is assigned into an object, such as `h` in `h <- hs(Y)`, can assess the pieces of output for later analysis. A primary such analysis is `knitr` for dynamic report generation from a generated R markdown file according to the `Rmd` option in which interpretative R output is embedded in documents. See value below.

**Usage**

```
Histogram(x=NULL, data=d, filter=NULL,
          stat_x=c("count", "proportion"),
          n_cat=getOption("n_cat"), Rmd=NULL,
```

```

by1=NULL, by2=NULL,
n_row=NULL, n_col=NULL, aspect="fill",

bin_start=NULL, bin_width=NULL, bin_end=NULL, breaks="Sturges",

theme=getOption("theme"),
fill=getOption("bar_fill_ordered"),
color=getOption("bar_color_ordered"),
trans=getOption("trans_bar_fill"),

values=FALSE,
reg="snow2", cumulate=c("off", "on", "both"),

xlab=NULL, ylab=NULL, main=NULL, sub=NULL,
lab_adj=c(0,0), margin_adj=c(0,0,0,0),

rotate_x=getOption("rotate_x"), rotate_y=getOption("rotate_y"),
offset=getOption("offset"),
scale_x=NULL, scale_y=NULL,

density=FALSE, dn.hist=TRUE,
bw=NULL, type=c("general", "normal", "both"),
color_gen="gray20", color_nrm="gray20",
fill_hist=getOption("se_fill"), fill_nrm=NULL, fill_gen=NULL,
x.pt=NULL, y_axis=FALSE,
rug=FALSE, color_rug="black", size_rug=0.5,

add=NULL, x1=NULL, y1=NULL, x2=NULL, y2=NULL,

eval_df=NULL, digits_d=NULL, quiet=getOption("quiet"), do_plot=TRUE,
width=6, height=6, pdf=FALSE,
fun_call=NULL, ...)

hs(...)

```

### Arguments

<code>x</code>	Variable(s) to analyze. Can be a single numerical variable, either within a data frame or as a vector in the users workspace, or multiple variables in a data frame such as designated with the <code>c</code> function, or an entire data frame. If not specified, then defaults to all numerical variables in the specified data frame, <code>d</code> by default.
<code>data</code>	Optional data frame that contains the variable(s) of interest, default is <code>d</code> .
<code>filter</code>	A logical expression that specifies a subset of rows of the data frame to analyze.
<code>stat_x</code>	Bin and transform values of variable <code>x</code> into "counts" by default or "proportion" if specified, that is, frequencies or relative frequencies.
<code>n_cat</code>	For the analysis of multiple variables, such as a data frame, specifies the largest number of unique values of variable of a numeric data type for which the variable will be analyzed as a categorical. Default is 0.

Rmd	File name for the file of R markdown to be written, if specified. The file type is .Rmd, which automatically opens in RStudio, but it is a simple text file that can be edited with any text editor, including RStudio.
by1	A categorical variable called a conditioning variable that activates <b>Trellis graphics</b> , from the lattice package, to provide a separate scatterplot (panel) of numeric primary variables x and y for each level of the variable.
by2	A second conditioning variable to generate Trellis plots jointly conditioned on both the by1 and by2 variables, with by2 as the row variable, which yields a scatterplot (panel) for each cross-classification of the levels of numeric x and y variables.
n_row	Optional specification for the number of rows in the layout of a multi-panel display with Trellis graphics. Need not specify ncol.
n_col	Optional specification for the number of columns in the layout a multi-panel display with Trellis graphics. Need not specify n_row. If set to 1, then the strip that labels each group is moved to the left of each plot instead of the top.
aspect	Lattice parameter for the aspect ratio of the panels, defined as height divided by width. The default value is "fill" to have the panels expand to occupy as much space as possible. Set to 1 for square panels. Set to "xy" to specify a ratio calculated to "bank" to 45 degrees, that is, with the line slope approximately 45 degrees.
bin_start	Optional specified starting value of the bins.
bin_width	Optional specified bin width, which can be specified with or without a bin_start value.
bin_end	Optional specified value that is within the last bin, so the actual endpoint of the last bin may be larger than the specified value.
breaks	The method for calculating the bins, or an explicit specification of the bins, such as with the standard R <code>seq</code> function or other options provided by the <code>hist</code> function that include the default "Sturges" plus "Scott" and "FD".
theme	Color theme for this analysis. Make persistent across analyses with <code>style</code> .
fill	Fill color of the bars. Can explicitly choose "grays" or "hcl" colors, or pre-specified R color schemes "rainbow", "terrain", and "heat". Can also provide pre-defined color ranges "blues", "reds" and "greens", as well as custom colors, such as generated by <code>getColor</code> . Default is <code>bar_color</code> from the <code>lessR style</code> function.
color	Border color of the bars, can be a vector to customize the color for each bar. Default is <code>bar_color</code> from the <code>lessR style</code> function.
trans	Transparency factor of the area of each slice. Default is <code>trans_bar_fill</code> from the <code>lessR style</code> function.
values	Replaces standard R <code>labels</code> options, which has multiple definitions in R. Specifies to display the count of each bin_

reg	The color of the superimposed, regular histogram when <code>cumulate="both"</code> .
cumulate	Specify a cumulative histogram. The value of "on" displays the cumulative histogram, with default of "off". The value of "both" superimposes the regular histogram.
xlab	Label for x-axis_ Defaults to variable name unless variable labels are present, the defaults to also include the corresponding variable label. Can style with the lessR <a href="#">style</a> function
ylab	Label for y-axis_ Defaults to Frequency or Proportion. Can style with the lessR <a href="#">style</a> function.
main	Label for the title of the graph. Can set size with <code>main_cex</code> and color with <code>main_color</code> from the lessR <a href="#">style</a> function.
sub	Sub-title of graph, below <code>xlab_</code>
lab_adj	Two-element vector – x-axis label, y-axis label – adjusts the position of the axis labels in approximate inches. + values move the labels away from plot edge. Not applicable to Trellis graphics.
margin_adj	Four-element vector – top, right, bottom and left – adjusts the margins of the plotted figure in approximate inches. + values move the corresponding margin away from plot edge. Not applicable to Trellis graphics.
rotate_x	Degrees that the x-axis values are rotated, usually to accommodate longer values, typically used in conjunction with <code>offset</code> . Can set persistently with the lessR <a href="#">style</a> function.
rotate_y	Degrees that the y-axis values are rotated. Can set persistently with the lessR <a href="#">style</a> function.
offset	The amount of spacing between the axis values and the axis_ Default is 0.5. Larger values such as 1.0 are used to create space for the label when longer axis value names are rotated. Can set persistently with the lessR <a href="#">style</a> function.
scale_x	If specified, a vector of three values that define the numerical values of the x-axis: starting, ending and number of intervals, within the bounds of plot region.
scale_y	Applies to the y-axis_ See <code>scale_x</code> .
density	If TRUE, plot the smoothed <b>kernel density</b> estimate.
dn.hist	When density is TRUE, plot a histogram behind the density curve.
bw	Bandwidth of <b>kernel density</b> estimation. Initial value is "nrd0", but unless specified, then may be iterated upward to create a smoother curve.
type	Type of density curve plotted. By default, the general density is plotted, though can request the normal density and both densities.
color_gen	Color of the general density curve.
color_nrm	Color of the normal curve.
fill_hist	Fill color for the histogram behind density curve, defaults to a light gray.
fill_nrm	Fill color for the estimated normal curve, with a partially transparent blue as the default, and transparent for the gray theme.

<code>fill_gen</code>	Fill color for the estimated general density curve, with a partially transparent light red as the default, and a light transparent gray for the gray theme.
<code>x.pt</code>	Value of the point on the x-axis for which to draw a unit interval around illustrating the corresponding area under the general density curve. Only applies when requesting <code>type=general</code> .
<code>y_axis</code>	Specifies if the y-axis, the density axis, should be included.
<code>rug</code>	If TRUE, add a rug plot, a direct display of density in the form of a narrow band beneath the density curve.
<code>color_rug</code>	Color of the rug ticks.
<code>size_rug</code>	Line width of the rug ticks.
<code>add</code>	<b>Draw one or more objects</b> , text or a geometric figures, on the plot. Possible values are any text to be written, the first argument, which is "text", or, to indicate a figure, "rect" (rectangle), "line", "arrow", "v.line" (vertical line), and "h.line" (horizontal line). The value "means" is short-hand for vertical and horizontal lines at the respective means. Does not apply to Trellis graphics. Customize with parameters such as <code>add_fill</code> and <code>add_color</code> from the <a href="#">style</a> function.
<code>x1</code>	First x coordinate to be considered for each object. All coordinates vary from -1 to 1.
<code>y1</code>	First y coordinate to be considered for each object.
<code>x2</code>	Second x coordinate to be considered for each object. Only used for "rect", "line" and arrow.
<code>y2</code>	Second y coordinate to be considered for each object. Only used for "rect", "line" and arrow.
<code>eval_df</code>	Determines if to check for existing data frame and specified variables. By default is TRUE unless the shiny package is loaded then set to FALSE so that Shiny will run. Needs to be set to FALSE if using the pipe <code>%&gt;%</code> notation.
<code>digits_d</code>	Number of significant digits for each of the displayed summary statistics.
<code>quiet</code>	If set to TRUE, no text output. Can change system default with <a href="#">style</a> function.
<code>do_plot</code>	If TRUE, the default, then generate the plot.
<code>width</code>	Width of the plot window in inches, defaults to 4.5.
<code>height</code>	Height of the plot window in inches, defaults to 4.5.
<code>pdf</code>	If TRUE, graphics are to be redirected to a pdf file.
<code>fun_call</code>	Function call. Used with <code>kni tr</code> to pass the function call when obtained from the abbreviated function call <code>hs</code> .
<code>...</code>	Other parameter values for graphics as defined processed by <a href="#">hist</a> and <a href="#">par</a> for general graphics, <code>xlim</code> and <code>ylim</code> for setting the range of the x and y-axes <code>cex.main</code> for the size of the title <code>col.main</code> for the color of the title <code>cex</code> for the size of the axis value labels <code>col.lab</code> for the color of the axis labels

## Details

### OVERVIEW

Results are based on the standard R `hist` function to calculate and plot a histogram, or a multi-panel display of histograms with Trellis graphics, plus the additional provided color capabilities, a relative frequency histogram, summary statistics and outlier analysis. The `freq` option from the standard R `hist` function has no effect as it is always set to `FALSE` in each internal call to `hist`. To plot densities, use the `lessR` function `Density`.

### VARIABLES and TRELIS PLOTS

At a minimum there is one primary variable, `x`, which results in a single histogram. Trellis graphics, from Deepayan Sarkar's `lattice` package, may be implemented in which multiple panels are displayed according to the levels of one or two categorical variables, called conditioning variables. A variable specified with `by1` is a conditioning variable that results in a Trellis plot, the histogram of `x` produced at *each* level of the `by1` variable. Inclusion of a second conditioning variable, `by2`, results in a separate histogram for *each* combination of cross-classified values of both `by1` and `by2`.

### DATA

The data may either be a vector from the global environment, the user's workspace, as illustrated in the examples below, or one or more variable's in a data frame, or a complete data frame. The default input data frame is `d`. Can specify the source data frame name with the `data` option. If multiple variables are specified, only the numerical variables in the list of variables are analyzed. The variables in the data frame are referenced directly by their names, that is, no need to invoke the standard R mechanisms of the `d$name` notation, the `with` function or the `attach` function. If the name of the vector in the global environment and of a variable in the input data frame are the same, the vector is analyzed.

To obtain a histogram of each numerical variable in the `d` data frame, use `Histogram()`. Or, for a data frame with a different name, insert the name between the parentheses. To analyze a subset of the variables in a data frame, specify the list with either a `:` or the `c` function, such as `m01:m03` or `c(m01,m02,m03)`.

The `filter` parameter subsets rows (cases) of the input data frame according to a logical expression. Use the standard R operators for logical statements as described in `Logic` such as `&` for and, `|` for or and `!` for not, and use the standard R relational operators as described in `Comparison` such as `==` for logical equality `!=` for not equals, and `>` for greater than. See the Examples.

### COLORS

Individual colors in the plot can be manipulated with options such as `color_bars` for the color of the histogram bars. A color theme for all the colors can be chosen for a specific plot with the `colors` option with the `lessR` function `style`. The default color theme is `lightbronze`, but a gray scale is available with `"gray"`, and other themes are available as explained in `style`, such as `"red"` and `"green"`. Use the option `style(sub_theme="black")` for a black background and partial transparency of plotted colors.

For the color options, such as `fill`, the value of `"off"` is the same as `"transparent"`.

Set `fill` to a single color or a color range, of which there are many possibilities. For "hues" colors of the same chroma and luminance set `fill` to multiple colors all with the same saturation and brightness. Also available are the pre-specified R color schemes `"rainbow"`, `"terrain"`, and `"heat"`. Can also provide pre-defined color ranges `"blues"`, `"reds"` and `"greens"`, or generate custom colors, such as from the `lessR` function `getColors`.

### VARIABLE LABELS



If variable labels exist, then the corresponding variable label is by default listed as the label for the horizontal axis and on the text output. For more information, see [Read](#).

#### ONLY VARIABLES ARE REFERENCED

The referenced variable in a `lessR` function can only be a variable name (or list of variable names). This referenced variable must exist in either the referenced data frame, such as the default `d`, or in the user's workspace, more formally called the global environment. That is, expressions cannot be directly evaluated. For example:

```
> Histogram(rnorm(50)) # does NOT work
```

Instead, do the following:

```
> Y <- rnorm(50) # create vector Y in user workspace
> Histogram(Y)   # directly reference Y
```

#### ERROR DETECTION

A somewhat relatively common error by beginning users of the base R `hist` function may encounter is to manually specify a sequence of bins with the `seq` function that does not fully span the range of specified data values. The result is a rather cryptic error message and program termination. Here, `Histogram` detects this problem before attempting to generate the histogram with `hist`, and then informs the user of the problem with a more detailed and explanatory error message. Moreover, the entire range of bins need not be specified to customize the bins. Instead, just a bin width need be specified, `bin_width`, and/or a value that begins the first bin, `bin_start`. If a starting value is specified without a bin width, the default Sturges method provides the bin width.

#### PDF OUTPUT

To obtain pdf output, use the `pdf` option, perhaps with the optional `width` and `height` options. These files are written to the default working directory, which can be explicitly specified with the `setwd` function.

### Value

The output can optionally be saved into an R object, otherwise it simply appears in the console. Two different types of components are provided: the pieces of readable output, and a variety of statistics. The readable output are character strings such as tables amenable for display. The statistics are numerical values amenable for further analysis. The motivation of these types of output is to facilitate R markdown documents, as the name of each piece, preceded by the name of the saved object and a `$`, can be inserted into the R-Markdown document (see [examples](#)), interspersed with explanation and interpretation.

#### READABLE OUTPUT

```
out_suggest: Suggestions for other similar analyses
out_summary: Summary statistics
out_freq: Frequency distribution
out_outliers: Outlier analysis
```

#### STATISTICS

```
bin_width: Bin width
n.bins: Number of bins
breaks: Breaks of the bins
mids: Bin midpoints
```

counts: Bin counts  
prop: Bin proportion  
cumulate: Bin cumulative counts  
cprop: Bin cumulative proportion

**Author(s)**

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

**References**

Gerbing, D. W. (2014). R Data Analysis without Programming, Chapter 5, NY: Routledge.  
Sarkar, Deepayan (2008) Lattice: Multivariate Data Visualization with R, Springer. <http://lmdvr.r-forge.r-project.org/>

**See Also**

[getColor](#), [hist](#), [plot](#), [par](#), [style](#).

**Examples**

```
# get the data
d <- rd("Employee")

# make sure default style is active
style()

# -----
# different histograms
# -----

# histogram with all defaults
Histogram(Salary)
# short form
#hs(Salary)

# output saved for later analysis into object h
h <- hs(Salary)
# view full text output
h
# view just the outlier analysis
h$out_outliers
# list the names of all the components
names(h)

# histogram with no borders for the bars
Histogram(Salary, color="off")

# save the histogram to a pdf file
```

```
#Histogram(Salary, pdf=TRUE)

# just males employed more than 5 years
Histogram(Salary, filter=(Gender=="M" & Years > 5))

# histogram with red bars, black background, and black border
style(panel_fill="black", fill="red", panel_color="black")
Histogram(Salary)
# or use a lessR pre-defined sequential color palette
# with some transparency
Histogram(Salary, fill="rusts", color="brown", trans=.1)

# histogram with purple color theme, translucent gold bars
style("purple", sub_theme="black")
Histogram(Salary)
# back to default color theme
style()

# histogram with specified bin width
# can also use bin_start
Histogram(Salary, bin_width=12000)

# histogram with rotated axis values, offset more from axis
# suppress text output
style(rotate_x=45, offset=1)
Histogram(Salary, quiet=TRUE)
style()

# histogram with specified bins and grid lines displayed over the histogram
Histogram(Salary, breaks=seq(0,150000,20000), xlab="My Variable")

# histogram with bins calculated with the Scott method and values displayed
Histogram(Salary, breaks="Scott", values=TRUE, quiet=TRUE)

# histogram with the number of suggested bins, with proportions
Histogram(Salary, breaks=15, stat_x="proportion")

# histogram with non-default values for x- and y-axes
d[2,4] <- 45000
Histogram(Salary, scale_x=c(30000,130000,5), scale_y=c(0,9.5,5))

# -----
# Trellis graphics
# -----
Histogram(Salary, by1=Dept)

# -----
# cumulative histograms
# -----

# cumulative histogram with superimposed regular histogram, all defaults
Histogram(Salary, cumulate="both")
```

```

# cumulative histogram plus regular histogram
Histogram(Salary, cumulate="both", reg="mistyrose")

# density
Histogram(Salary, density=TRUE)

# -----
# histograms for data frames and multiple variables
# -----

# create data frame, d, to mimic reading data with Read function
# d contains both numeric and non-numeric data
d <- data.frame(rnorm(50), rnorm(50), rnorm(50), rep(c("A","B"),25))
names(d) <- c("X","Y","Z","C")

# although data not attached, access the variable directly by its name
Histogram(X)

# histograms for all numeric variables in data frame called d
# except for numeric variables with unique values < n_cat
# d is the default name, so does not need to be specified with data
Histogram()

# variable of interest is in a data frame which is not the default d
# access the breaks variable in the R provided warpbreaks data set
# although data not attached, access the variable directly by its name
Histogram(breaks, data=warpbreaks)

# histogram with specified options, including red axis labels
style(fill="palegreen1", panel_fill="ivory", axis_color="red")
Histogram(values=TRUE)
style() # reset

# histograms for all specified numeric variables
# use the combine or c function to specify a list of variables
Histogram(c(X,Y))

# -----
# annotations
# -----

d <- rd("Employee")

# Place a message in the top-right of the graph
# Use \n to indicate a new line
hs(Salary, add="Salaries\nin our Company", x1=100000, y1=7)

# Use style to change some parameter values
style(add_trans=.8, add_fill="gold", add_color="gold4",
      add_lwd=0.5, add_cex=1.1)

```

```
# Add a rectangle around the message centered at <100000,7>
hs(Salary, add=c("rect", "Salaries\nin our Company"),
    x1=c(82000, 100000), y1=c(7.7, 7), x2=118000, y2=6.2)
```

---

label

*Assign Variable Labels [Superseded by VariableLabels]*

---

## Description

Deprecated, replaced by [VariableLabels](#). Display a variable label for output, either text output at the console or graphics, such as a title on a graph. To return a variable label generally applies to standard R functions such that the functions can access lessR variable labels. Or, the variable name and label can be listed on the standard output. To assign a variable label, invoke the `value` option and assign the output to a specified data frame.

## Usage

```
label(x, value=NULL, data=d)
```

## Arguments

<code>x</code>	The variable for which to obtain the corresponding variable label.
<code>value</code>	If assigned, then the specified data frame is updated with this assigned label.
<code>data</code>	Data frame that contains the variable of interest. The output of the function is assigned to this data frame.

## Details

Standard R does not provide for variable labels, but lessR does. Read the labels with the [lessR Read](#) function, as explained in the corresponding documentation. Individual variable labels can also be assigned with this function. Not all variables need have a label, and the variables with their corresponding labels can be listed or assigned in any order.

The function provides two different modes. The first mode is to return the variable name and label for an existing variable label. One such use is to provide the function as an argument to an existing R function call to access a lessR variable label. For example, use the function as the argument for `main` in graphics output, where `main` is the title of the graph. This mode is triggered by not invoking the `value` option.

The second mode is to assign a variable label to an existing variable. Invoke this mode by specifying a variable label with the `value` option. The function accesses the entire specified data frame, and then modifies the specified variable label. As such, assign the output of the function to the data frame of interest, such as the default `d`. One use of this function is to add a variable label to a data frame that contains a new variable created by a transformation of the existing variables.

## Value

The specified value of `value` is returned.

**Author(s)**

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

**See Also**

[Read.](#)

**Examples**

```
# read the data and variable labels
#d <- rd("http://lessRstats.com/data/employee.xlsx")
#l <- vl("http://lessRstats.com/data/employee_lbl.xlsx")

# variable label as the title of a graph for non-lessR functions
# base R
#hist(d$Salary, xlab=label(Salary))
# ggplot2
#ggplot(d, aes(Salary)) + geom_histogram(binwidth=10000) + labs(x=label(Salary))

# assign a new label for the variable Years in d
#d <- label(Years, "Years Worked")
# verify
#label(Years)
# or view all variable labels in d
#db()

#d <- Read("Employee")
# specify a label of variable in a data frame other than d
#myd <- Subset(Gender=="M")
#myd <- label(Gender, "Only is Male", data=myd)
#db(myd)
```

---

LineChart

*Line Chart such as a Run Chart or Time-Series Chart*

---

**Description**

Abbreviation: lc

Plots a line chart, the values of the variable ordered according to their order in the data frame. Usually this ordering would be an ordering according to time, which yields a run chart. The default run chart provides the index, that is, sequential position, of each value of the variable from 1 to the last value. Optionally dates can be provided so that a time-series plot is produced.

For data of one variable exhibiting little trend, the center line is provided for the generation of a run chart, plotting the values of a variable in order of occurrence over time\_ When the center line, the median by default, is plotted, the analyses of the number and composition of the individual runs, number of consecutive values above or below the center line, is also displayed. Also, the defaults change for each of the types of plots. The intent is to rely on the default values for a

relatively sophisticated plot, particularly when compared to the default values of the standard R `plot` function called with a single variable.

If the provided object to analyze is a set of multiple variables, including an entire data frame, then each non-numeric variable in the data frame is analyzed and the results written to a pdf file in the current working directory. The name of each output pdf file that contains a bar chart and its path are specified in the output.

### Usage

```
LineChart(x, data=d, filter=NULL,
          n_cat=getOption("n_cat"), type=NULL,

          line_color=getOption("pt_color"), area=NULL,

          shape_pts=21, lab_cex=1.0, axis_cex=0.75,
          axis_text_color=getOption("axis_x_text_color"),

          rotate_x=0, rotate_y=0, offset=.5,

          xy_ticks=TRUE, line_width=1,
          xlab=NULL, ylab=NULL, main=NULL, sub=NULL, cex=NULL,

          time_start=NULL, time_by=NULL, time_reverse=FALSE,

          center_line=c("default", "mean", "median", "zero", "off"),

          show_runs=FALSE, eval_df=NULL, quiet=getOption("quiet"),
          width=6, height=6, pdf=FALSE,
          ...)

lc(...)
```

### Arguments

<code>x</code>	Variable(s) to analyze. Can be a single numerical variable, either within a data frame or as a vector in the user's workspace, or multiple variables in a data frame such as designated with the <code>c</code> function, or an entire data frame. If not specified, then defaults to all numerical variables in the specified data frame, <code>d</code> by default.
<code>data</code>	Optional data frame that contains the variable(s) of interest, default is <code>d</code> .
<code>filter</code>	A logical expression that specifies a subset of rows of the data frame to analyze.
<code>n_cat</code>	For the analysis of multiple variables, such as a data frame, specifies the largest number of unique values of variable of a numeric data type for which the variable will be analyzed as a categorical. Default is 0.
<code>type</code>	Character string that indicates the type of plot, either "p" for points, "l" for line, or "b" for both. The default is "b" for both points and lines.
<code>line_color</code>	Color of the plotted line.

area	Color of area under the plotted line segments, which by default is not applied, equivalent to a color of "transparent".
shape_pts	The standard plot character, with values defined in <code>help(points)</code> . The default value is 21, a circle with both a border and filled area, specified here as <code>color</code> and <code>fill</code> . <code>fill</code> defaults to <code>color</code> .
lab_cex	Scale magnification factor for axis labels.
axis_cex	Scale magnification factor, which by default displays the axis values to be smaller than the axis labels.
axis_text_color	Color of the font used to label the axis values_
rotate_x	Degrees that the x-axis values are rotated, usually to accommodate longer values, typically used in conjunction with <code>offset</code> .
rotate_y	Degrees that the y-axis values are rotated.
offset	The amount of spacing between the axis values and the axis_ Default is 0.5. Larger values such as 1.0 are used to create space for the label when longer axis value names are rotated.
xy_ticks	Flag that indicates if tick marks and associated values on the axes are to be displayed.
line_width	Width of the line segments_
xlab	Label for x-axis_ For two variables specified, x and y, if <code>xlab</code> not specified, then the label becomes the name of the corresponding variable. If <code>xy_ticks</code> is FALSE, then no label is displayed. If no y variable is specified, then <code>xlab</code> is set to <code>Index</code> unless <code>xlab</code> has been specified.
ylab	Label for y-axis_ If not specified, then the label becomes the name of the corresponding variable. If <code>xy_ticks</code> is FALSE, then no label displayed.
main	Label for the title of the graph. If the corresponding variable labels exist, then the title is set by default from the corresponding variable labels.
sub	Sub-title of graph, below <code>xlab_</code>
cex	Magnification factor for any displayed points, with default of <code>cex=1.0</code> .
time_start	Optional starting date for first data value. Format must be "%Y-%m-%d" or "%Y/%m/%d". If using with <code>x.reverse</code> , the first date is after the data are reverse sorted. Not needed if data are a time series with <code>ts</code> function.
time_by	Accompanies the <code>time_start</code> specification, the interval to increment the date for each sequential data value. A character string, containing one of "day", "week", "month" or "year". This string can optionally be preceded by a positive or negative integer and a space, or followed by "s", as specified in <a href="#">seq.Date</a> . Not needed if data are a time series.
time_reverse	When TRUE, reverse the ordering of the dates, particularly when the data are listed such that first row of data is the newest. Accompanies the <code>time_start</code> specification.
center_line	Plots a dashed line through the middle of a run chart. The two possible values for the line are "mean" and "median". Provides a centerline for the "median" by default when the values randomly vary about the mean. A value of "zero" specifies the center line should go through zero.



show_runs	If TRUE, display the individual runs in the run analysis.
eval_df	Determines if to check for existing data frame and specified variables. By default is TRUE unless the shiny package is loaded then set to FALSE so that Shiny will run. Needs to be set to FALSE if using the pipe %\>% notation.
quiet	If set to TRUE, no text output. Can change system default with <a href="#">style</a> function.
width	Width of the plot window in inches, defaults to 4.5.
height	Height of the plot window in inches, defaults to 4.5.
pdf	If TRUE, the pdf file is to be redirected to a pdf file.
...	Other parameters such as from <a href="#">par</a> , col.lab, sub, color_sub, color_ticks to set the color of the ticks used to label the axis values, and srt to rotate the axis value labels.

## Details

### OVERVIEW

The line chart is based on the standard R function [plot](#) when called with only a single variable.

The values on the horizontal axis of the line chart are automatically generated. The default is the index variable, the ordinal position of each data value, in which case this version of the line chart is a run chart. Or, dates on the horizontal axis can be specified from the specified starting date given by `x.start` and the accompanying increment as given by `x.by`, in which case the line chart is typically referred to as a time series chart.

If the data values randomly vary about the mean, the default is to plot the mean as the center line of the graph, otherwise the default is to ignore the center line. The default plot type for the line chart is `type="b"`, for both points and the corresponding connected line segments. The size of the points is automatically reduced according to the number of points of points plotted, and the `cex` option can override the computed default. If the area below the plotted values is specified to be filled in with color, then the default line type changes to `type="l"`.

### DATA

The data may either be a vector from the global environment, the user's workspace, as illustrated in the examples below, or one or more variable's in a data frame, or a complete data frame. The default input data frame is `d`. Can specify the source data frame name with the `data` option. If multiple variables are specified, only the numerical variables in the list of variables are analyzed. The variables in the data frame are referenced directly by their names, that is, no need to invoke the standard R mechanisms of the `d$name` notation, the [with](#) function or the [attach](#) function. If the name of the vector in the global environment and of a variable in the input data frame are the same, the vector is analyzed.

The `filter` parameter subsets rows (cases) of the input data frame according to a logical expression. Use the standard R operators for logical statements as described in [Logic](#) such as `&` for and, `|` for or and `!` for not, and use the standard R relational operators as described in [Comparison](#) such as `==` for logical equality `!=` for not equals, and `>` for greater than.

### COLORS

Individual colors in the plot can be manipulated with options such as `color`. A color theme for all the colors can be chosen for a specific plot with the `colors` option with the [lessR](#) function [style](#). The default color theme is `dodgerblue`, but a gray scale is available with `"gray"`, and other themes are available as explained in [style](#), such as `"red"` and `"green"`. Use the option `style(sub_theme="black")` for a black background and partial transparency of plotted colors.

For the color options, such as `grid_color`, the value of "off" is the same as "transparent".

#### VARIABLE LABELS

Although standard R does not provide for variable labels, `lessR` does, obtained from the [Read](#) function. If the variable labels exist, then the corresponding variable label is by default listed as the label for the horizontal axis and on the text output. For more information, see [Read](#).

#### PDF OUTPUT

To obtain pdf output, use the `pdf` option, perhaps with the optional width and height options. These files are written to the default working directory, which can be explicitly specified with the R [setwd](#) function.

#### ONLY VARIABLES ARE REFERENCED

The referenced variable in a `lessR` function can only be a variable name (or list of variable names). This referenced variable must exist in either the referenced data frame, such as the default `d`, or in the user's workspace, more formally called the global environment. That is, expressions cannot be directly evaluated. For example:

```
> LineChart(rnorm(50)) # does NOT work
```

Instead, do the following:

```
> Y <- rnorm(50) # create vector Y in user workspace
> LineChart(Y)   # directly reference Y
```

#### Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

#### See Also

[plot](#), [style](#).

#### Examples

```
# create data frame, d, to mimic reading data with Read function
# d contains both numeric and non-numeric data
d <- data.frame(rnorm(50), rnorm(50), rnorm(50), rep(c("A","B"),25))
names(d) <- c("X","Y","Z","C")

# default run chart
LineChart(Y)
# short name
lc(Y)

# save run chart to a pdf file
#LineChart(Y, pdf=TRUE)

# LineChart in gray scale, then back to default theme
style("gray")
LineChart(Y)
style()

# customize run chart with LineChart options
```

```

style(panel_fill="mintcream", color="sienna3")
LineChart(Y, line_width=2, area="slategray3", center_line="median")
style() # reset style

# customize run chart with R par parameters
# 24 is the R value for a half-triangle pointing up
lc(Y, xlab="My xaxis", ylab="My yaxis", main="My Best Title",
    cex.main=1.5, font.main=3, ylim=c(-4,4), shape_pts=24)

# generate steadily increasing values
# get a variable named A in the user workspace
A <- sort(rexp(50))
# default line chart
LineChart(A)
# line chart with border around plotted values
LineChart(A, area="off")
# time series chart, i.e., with dates, and filled area
# with option label for the x-axis
LineChart(A, time_start="2000/09/01", time_by="3 months")
# time series chart from a time series object
y.ts <- ts(A, start=c(2000, 9), frequency=4)
LineChart(y.ts)

# LineChart with built-in data set
LineChart(breaks, data=warpbreaks)

# Line charts for all numeric variables in a data frame
LineChart()

# Line charts for all specified numeric variables in a list of variables
# e.g., use the combine or c function to specify a list of variables
LineChart(c(X,Y))

```

---

## Description

Abbreviation: lr

Based directly on the standard R `glm` function with `family="binomial"`, automatically provides a logit regression analysis with graphics from a single, simple function call with many default settings, each of which can be re-specified. By default the data exists as a data frame with the default name of `d`, such as data read by the `lessR Read` function. Specify the model in the function call according to an R [formula](#), that is, the response variable followed by a tilde, followed by the list of predictor variables, each pair separated by a plus sign. The response variable is either a factor with two levels or a numeric variable with values only of 0 and 1.

Default output includes the inferential analysis of the estimated coefficients and model, sorted residuals and Cook's Distance, and sorted fitted values for existing data or new data. For a single predictor variable model, the scatterplot of the data with plotted logit function is provided.

Can also be called from the more general [model](#) function.

**Usage**

```
Logit(my_formula, data=d, filter=NULL,
      digits_d=4, text_width=120,

      brief=getOption("brief"),

      res_rows=NULL, res_sort=c("cooks", "rstudent", "dffits", "off"),
      pred=TRUE, pred_all=FALSE, prob_cut=0.5, cooks_cut=1,

      X1_new=NULL, X2_new=NULL, X3_new=NULL, X4_new=NULL,
      X5_new=NULL, X6_new=NULL,

      pdf_file=NULL, width=5, height=5, ...)

lr(...)
```

**Arguments**

<code>my_formula</code>	Standard R <a href="#">formula</a> for specifying a model. For example, for a response variable named Y and two predictor variables, X1 and X2, specify the corresponding linear model as $Y \sim X1 + X2$ .
<code>data</code>	The default name of the data frame that contains the data for analysis is d, otherwise explicitly specify.
<code>filter</code>	A logical expression that specifies a subset of rows of the data frame to analyze.
<code>digits_d</code>	For the Basic Analysis, it provides the number of decimal digits. For the rest of the output, it is a suggestion only.
<code>text_width</code>	Width of the text output at the console.
<code>brief</code>	If set to TRUE, reduced text output. Can change system default with <a href="#">style</a> function.
<code>res_rows</code>	Default is 25, which lists the first 25 rows of data sorted by the specified sort criterion. To turn this option off, specify a value of 0. To see the output for all observations, specify a value of "all".
<code>res_sort</code>	Default is "cooks", for specifying Cook's distance as the sort criterion for the display of the rows of data and associated residuals. Other values are "rstudent" for Studentized residuals, and "off" to not provide the analysis.
<code>pred</code>	Default is TRUE, which, produces confidence and prediction intervals for each row, or selected rows, of data.
<code>pred_all</code>	Default is FALSE, which produces prediction intervals only for the first, middle and last five rows of data.
<code>prob_cut</code>	Probability threshold for classifying an observation into the reference group (1) or not (0).
<code>cooks_cut</code>	Cutoff value of Cook's Distance at which observations with a larger value are flagged in red and labeled in the resulting scatterplot of Residuals and Fitted

	Values. Default value is 1.0.
X1_new	Values of the first listed predictor variable for which forecasted values and corresponding prediction intervals are calculated.
X2_new	Values of the second listed predictor variable for which forecasted values and corresponding prediction intervals are calculated.
X3_new	Values of the third listed predictor variable for which forecasted values and corresponding prediction intervals are calculated.
X4_new	Values of the fourth listed predictor variable for which forecasted values and corresponding prediction intervals are calculated.
X5_new	Values of the fifth listed predictor variable for which forecasted values and corresponding prediction intervals are calculated.
X6_new	Values of the sixth listed predictor variable for which forecasted values and corresponding prediction intervals are calculated.
pdf_file	Name of the pdf file to which graphics are redirected.
width	Width of the pdf file in inches.
height	Height of the pdf file in inches.
...	Other parameter values for R function <code>glm</code> which provides the core computations.

## Details

### OVERVIEW

The purpose of `Logit` is to combine the following function calls into one, as well as provide ancillary analyses such as graphics, organizing output into tables and sorting to assist interpretation of the output. The basic analysis successively invokes several standard R functions beginning with the standard R function for estimation of the logit model, `glm` with `family="binomial"`. The output of the analysis is stored in the object `lm.out`, available for further analysis in the R environment upon completion of the `Logit` function. By default automatically provides the analyses from the standard R functions, `summary`, `confint` and `anova`, with some of the standard output modified and enhanced. The residual analysis invokes `fitted`, `resid`, `rstudent`, and `cooks.distance` functions. The option for prediction intervals calls the standard generic R function `predict`.

The default analysis provides the model's parameter estimates and corresponding hypothesis tests and confidence intervals, goodness of fit indices, the ANOVA table, analysis of residuals and influence as well as the fitted value and standard error for each observation in the model.

### DATA

The name `d` is by default provided by the `Read` function included in this package for reading and displaying information about the data in preparation for analysis. If all the variables in the model are not in the same data frame, the analysis will not be complete. The data frame does not need to be attached, just specified by name with the `data` option if the name is not the default `d`.

The `filter` parameter subsets rows (cases) of the input data frame according to a logical expression. Use the standard R operators for logical statements as described in `Logic` such as `&` for and, `|` for

or and ! for not, and use the standard R relational operators as described in [Comparison](#) such as == for logical equality != for not equals, and > for greater than. See the Examples.

#### GRAPHICS

For models with a single predictor variable, a scatter plot of the data is produced, which also includes the fitted values. As with the density histogram plot of the residuals and the scatterplot of the fitted values and residuals, the scatterplot includes a colored background with grid lines. If more than a single predictor variable, then a scatter plot matrix is produced.

#### FORECASTS

Fitted and forecasted values are listed for all rows of data if the number of rows is less than 25 or if `pred_all=TRUE`. If only some of the rows are listed, sorted by the fitted value, the first and last four rows of data are listed. Also the 4 rows immediately around the fitted value of 0.5 are listed.

#### RESIDUAL ANALYSIS

By default the residual analysis lists the data and fitted value for each observation as well as the residual, Studentized residual, Cook's distance and dffits, with the first 20 observations listed and sorted by Cook's distance. The residual displayed is the actual difference between fitted and observed, that is, with the setting in the `residuals` of `type="response"`. The `res_sort` option provides for sorting by the Studentized residuals or not sorting at all. The `res_rows` option provides for listing these rows of data and computed statistics for any specified number of observations (rows). To turn off the analysis of residuals, specify `res_rows=0`.

#### INVOKED R OPTIONS

The `options` function is called to turn off the stars for different significance levels (`show.signif.stars=FALSE`), to turn off scientific notation for the output (`scipen=30`), and to set the width of the text output at the console to 120 characters. The later option can be re-specified with the `text_width` option. After `reg` is finished with a normal termination, the options are re-set to their values before the `reg` function began executing.

#### COLORS

The default color theme is `dodgerblue`, but a gray scale is available with `"gray"`, and other themes are available as explained in [style](#), such as `"red"` and `"green"`. Use the option `style(sub_theme="black")` for a black background and partial transparency of plotted colors.

### Value

Following the standard R function `glm`, invisibly returns an object of `class` inheriting from `"glm"` which inherits from the `class` `"lm"`. Particularly useful for comparing nested models. Assign the output of `Logit` for a model to an object. Then for a nested model. Then use the `anova` function to compare the models as shown in the examples below.

### Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

### See Also

[formula](#), [glm](#), [summary.glm](#), [anova](#), [confint](#), [fitted](#), [resid](#), [rstudent](#), [cooks.distance](#)

**Examples**

```

# Gender has values of "M" and "F"
d <- Read("Employee", quiet=TRUE)
# logit regression, rely upon default parameter value: data=d
Logit(Gender ~ Years)

# short name
lr(Gender ~ Years)

# Modify the default settings as specified
Logit(Gender ~ Years, res_row=8, res_sort="rstudent", digits_d=8, pred=FALSE)

# just for employees who have worked more than 5 years at the firm
Logit(Gender ~ Years, filter=(Years > 5))

# Multiple logistic regression model
# Provide all default analyses
Logit(Gender ~ Years + Salary)

# change the prediction probability threshold from 0.5
Logit(Gender ~ Years + Salary, prob_cut=.7)

# compare nested models
# easier and better treatment of missing data to use lessR function: Nest
full_model <- Logit(Gender ~ Years + Salary)
reduced_model <- Logit(Gender ~ Years)
anova(reduced_model, full_model)

# Save the three plots as pdf files 4 inches square, gray scale
#Logit(Gender ~ Years, pdf_file="MyModel.pdf",
#      width=4, height=4, colors="gray")

# Specify new values of the predictor variables to calculate
# forecasted values
d <- Read("Cars93")
Logit(Source ~ HP + MidPrice, X1_new=seq(100,250,50), X2_new=c(10,60,10))

```

---

Merge

---

*Merge Two Data Frames Horizontally or Vertically*


---

**Description**

Abbreviation: mrg

A horizontal merge combines data frames horizontally, that is, adds variables (columns) to an existing data frame according to a common shared ID field. Performs the horizontal merge based directly on the standard R [merge](#) function. The vertical merge is based on the [rbind](#) function in which the two data frames have the same variables but different cases (observations), so the rows build vertically, stacked on top of each other.

The advantages of this lessR function is that it provides a single function for merging data frames, adds text output to the standard R functions that provide feedback regarding properties of the merge, provides more detailed and presumably more useful error messages, and preserves any variable labels that might exist in one or both of the merged data frames.

### Usage

```
Merge(data1, data2, by=NULL, quiet=getOption("quiet"), ...)
```

```
mrg(...)
```

### Arguments

data1	The name of the first data frame from which to create the merged data frame.
data2	The name of the second data frame from which to create the merged data frame.
by	If specified, then signals a horizontal merge and the ID field by which the data frames are merged. Specify "row_names" for merging according to the row names.
quiet	If set to TRUE, no text output. Can change system default with <a href="#">style</a> function.
...	Additional arguments available in the base R <a href="#">merge</a> function such as <code>all.x=TRUE</code> for retaining all rows of the first data frame even if not matched by a row in the second data table.

### Details

Merge creates a merged data frame from two input data frames.

If `by` is specified the merge is horizontal. That is the variables in the second input data frame are presumed different from the variables in the first input data frame. The merged data frame is the combination of variables from both input data frames, with the rows aligned by the value of `by`, an ID field common to both data frames.

If `by` is not provided, then the merge is vertical. The variables are presumed the same in each input data frame. The merged data frame consists of the rows of both input data frames. The rows of the first data frame are stacked upon the rows of the second data frame.

Guidance and feedback regarding the merge are provided by default. The first five lines of each of the input data frames are listed before the merge operation, followed by the first five lines of the output data frame.

### Value

The merged data frame is returned, usually assigned the name of `d` as in the examples below. This is the default name for the data frame input into the lessR data analysis functions.

### Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)



**See Also**

[merge](#), [rbind](#).

**Examples**

```
# Horizontal
#-----
d <- Read("Employee", quiet=TRUE)
Emp1a <- Subset(1:4, columns = c("Years", "Gender", "Dept", "Salary"))
Emp1b <- Subset(1:4, columns = c("JobSat", "Plan"))
# horizontal merge
d <- Merge(Emp1a, Emp1b, by="row.names")
# suppress output to console
d <- Merge(Emp1a, Emp1b, by="row.names", quiet=TRUE)

# Vertical
#-----
d <- Read("Employee", quiet=TRUE)
Emp2a <- Subset(1:4)
Emp2b <- Subset(7:10)
# vertical merge
d <- Merge(Emp2a, Emp2b)
```

---

Model

*Regression Analysis, ANOVA or t-test*

---

**Description**

Abbreviation: `model`, `model_brief`

Automatically selects and then provides an analysis of a linear model: OLS regression, Logistic regression, ANOVA, or a t-test depending on the properties of the data. Comprehensive regression analysis with graphics from a single, simple function call with many default settings, each of which can be re-specified. By default the data exists as a data frame with the default name of `d`, such as data read by the `lessR` `rad` function. Specify the model in the function call according to an R [formula](#), that is, the response variable followed by a tilde, followed by the list of predictor variables, each pair separated by a plus sign.

**Usage**

```
Model(my_formula, data=d, brief=getOption("brief"), xlab=NULL, ...)
```

```
model_brief(..., brief=TRUE)
```

```
model(...)
```

**Arguments**

<code>my_formula</code>	Standard R <a href="#">formula</a> for specifying a model. For example, for a response variable named Y and two predictor variables, X1 and X2, specify the corresponding linear model as $Y \sim X1 + X2$ .
<code>data</code>	The default name of the data frame that contains the data for analysis is <code>d</code> , otherwise explicitly specify.
<code>brief</code>	If set to TRUE, reduced text output. Can change system default with <a href="#">style</a> function.
<code>xlab</code>	x-axis label, defaults to variable name, or, if present, variable label.
<code>...</code>	Other parameter values for R functions such as <a href="#">lm</a> which provide the core computations.

**Details****OVERVIEW**

The purpose of `Model` is to combine many standard R function calls into one, as well as provide ancillary analyses such as graphics, organizing output into tables and sorting to assist interpretation of the output, all from a single function. Currently the supported models are OLS regression, ANOVA and the t-test. For more details of each of these methods, see the `lessR` functions [Regression](#), [Logit](#), [ANOVA](#) and [ttest](#), respectively, which, in turn are based on many standard R functions.

All invocations of the `model` function are based on the standard R [formula](#).

**Author(s)**

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

**See Also**

[formula](#), [lm](#), [glm](#), [summary.lm](#), [anova](#), [confint](#), [fitted](#), [resid](#), [rstudent](#), [cooks.distance](#)

**Examples**

```
# Generate random data, place in data frame d
n <- 200
X1 <- rnorm(n)
X2 <- rnorm(n)
Y <- .7*X1 + .2*X2 + .6*rnorm(n)
Ybin <- cut(Y, breaks=2, labels=FALSE)
# instead, if read data with the Read function
# then the result is the data frame called d
d <- round(data.frame(X1, X2, Y, Ybin),2)
rm(Y); rm(Ybin); rm(X1); rm(X2)

# One-predictor regression
# Provide all default analyses including scatterplot etc.
Model(Y ~ X1)
# alternate form
model(Y ~ X1)
```

```

# Multiple regression model
# Provide all default analyses
Model(Y ~ X1 + X2)

# Logit analysis
# Y is binary, 0 or 1
d <- Recode(Ybin, old=c(1,2), new=c(0,1), quiet=TRUE)
Model(Ybin ~ X1)

# t-test
Model(breaks ~ wool, data=warpbreaks)

# ANOVA analysis
# from another data frame other than the default \code{d}
# breaks is numerical, wool and tension are categorical
Model(breaks ~ wool + tension, data=warpbreaks)

```

---

Nest

*Nest the Values of an Integer or Factor Variable*


---

## Description

Abbreviation: nt

A nested model has a subset of predictor variables from the corresponding full model. Compare a nested linear model with a full model to evaluate the effectiveness of the predictor variables deleted from the full model to define the nested model.

## Usage

```
Nest(y, nested_model, full_model, method=c("lm", "logit"),
      data=d, digits_d=NULL, ...)
```

```
nt(...)
```

## Arguments

y	Response variable.
nested_model	Predictor variables in the nested model.
full_model	Predictor variables in either the full model, or just those that added to the reduced model to derive the full model.
method	Do a least squares analysis, ls, the default, or set to logit.
data	The name of the data frame from which to create the subset, which is d by default.
digits_d	Number of decimal digits, set by default to at least 2 or the largest number of digits in the values of the response variable plus 1.
...	The specified arguments.

## Details

Use the standard R function `anova` function to compare a nested model with a corresponding full model. By default, compare models estimated with ordinary least squares from the R function `lm`, or compare models estimated with logistic regression from the R function `glm` with `family="binomial"`. For the logistic analysis, the `anova` analysis is with `test="Chisq"`.

To insure that the same data are analyzed for both models, the fit for the full model is first obtained. Then the data frame that is returned by this analysis is input into the analysis for the nested model. This guarantees that any cases with missing data values missing for the full analysis will have been deleted for the nested analysis. Otherwise rows of data could be retained for the nested analysis that were dropped for the full analysis because of missing data values for the deleted predictor variables. This method also guarantees that cases are not deleted because data was missing on variables not included in full analysis.

## Value

The output can optionally be returned and saved into an R object, otherwise it simply appears at the console. The components of this object are redesigned in `lessR` version 3.3 into (a) pieces of text that form the readable output and (b) a variety of statistics. The readable output are character strings such as tables amenable for viewing and interpretation. The statistics are numerical values amenable for further analysis, such as to be referenced in a subsequent R markdown document. The motivation of these three types of output is to facilitate R markdown documents, as the name of each piece, preceded by the name of the saved object followed by a `\$`, can be inserted into the R markdown document (see examples).

### TEXT OUTPUT

`out_models`: The specification of the two models compared

`out_anova`: Analysis of variance or, for logit, analysis of deviance

### STATISTICS

`fun_call`: Function call that generated the analysis

`anova_tested`: Term that is tested

`anova_residual`: Residual df, and either ss and ms or deviance for logit

`anova_total`: For logit, total df and deviance

Although not typically needed for analysis, if the output is assigned to an object named, for example, `n`, then the complete contents of the object can be viewed directly with the `unclass` function, here as `unclass(n)`. Invoking the `class` function on the saved object reveals a class of `out_all`. The class of each of the text pieces of output is `out`.

## Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

## See Also

`anova`, `lm`, `glm`.

**Examples**

```
d <- Read("Reading")

# compare least-squares models
# can specify all the variables in the full model
Nest(Reading, c(Absent), c(Verbal,Absent,Income))
# or, can specify just the additional variables in the full model
Nest(Reading, c(Absent), c(Verbal,Income))

# compare logistic models, save results into an object
# define the full model by adding just the variables
# not found in the reduced model
d <- Read("BodyMeas")
n <- Nest(Gender, c(Weight, Hips, Hand, Shoe),
          c(Height, Waist, Chest), method="logit")
# view the results
n
# see the names of the available output components
names(n)
```

---

PieChart

*Pie Chart*


---

**Description**

Abbreviation: pc

Plots a pie chart of a categorical variable (x). The default chart is a doughnut or ring version of a pie chart, that is, a hole in the middle of the pie. Either directly enter the corresponding numerical value (y) or have the numerical variable be the tabulated counts for the frequency of occurrence for each value of the categorical variable. Also displays the frequency table for the variable with the corresponding chi-square inferential analysis. Real numbers can also be entered directly.

**Usage**

```
PieChart(x, y=NULL, data=d, filter=NULL,

         radius=1, hole=0.65, hole_fill=getOption("panel_fill"),

         fill=NULL,
         color="lightgray",
         trans=getOption("trans_bar_fill"),

         density=NULL, angle=45,
         lty="solid", lwd=1, edges=200,

         clockwise=FALSE, init_angle=ifelse (clockwise, 90, 0),
```

```

    values=getOption("values"),
    values_color=getOption("values_color"),
  values_size=getOption("values_size"),
    values_digits=getOption("values_digits"),
    values_position=getOption("values_position"),

  main=NULL, main_cex=1.2, labels_cex=0.9, cex,

  add=NULL, x1=NULL, y1=NULL, x2=NULL, y2=NULL,

  eval_df=NULL, quiet=getOption("quiet"),
  width=6.5, height=6, pdf_file=NULL,
  ...)

pc(...)

```

### Arguments

<code>x</code>	For each level of this categorical variable, <code>x</code> , display the frequencies as slices of a pie.
<code>y</code>	Numeric variable that sets the area of each slice of the pie. If not specified, then its value is the frequency of each category of <code>x</code> , automatically tabulated.
<code>data</code>	Optional data frame that contains the variable(s) of interest, default is <code>d</code> .
<code>filter</code>	A logical expression that specifies a subset of rows of the data frame to analyze.
<code>radius</code>	The pie is drawn in a box with sides that range from -1 to 1, so the maximum value of the radius without truncating the pie is 1.
<code>hole</code>	The proportion of the radius that defines the inner hole for what is called a doughnut or hole plot. To show the full pie, set to <code>FALSE</code> or the value of <code>0</code> .
<code>hole_fill</code>	Fill color of the hole, which by default is the same color as <code>panel_fill</code> as set by the color theme or individually with the <a href="#">style</a> function.
<code>fill</code>	Specified color of each slice. Default is the discrete scale with, with fixed chroma (50) and luminance (75) for unbiased comparison across colors, for all color themes except "gray" and "white", with default gray scale. Can explicitly choose "grays" or "hues" , or pre-specified R color schemes "rainbow", "terrain", and "heat". Or, set to the name of <code>y</code> to map the values of bar fill, specified as (count) if tabulated from the data. Can also provide pre-defined color ranges "blues", "reds" and "greens", as well as custom colors, such as generated by <a href="#">getColor</a> s.
<code>color</code>	Border color of sides and the pie, can be a vector to customize the color for each slice. Default is <code>bar_color</code> from the lessR <a href="#">style</a> function.
<code>trans</code>	Transparency factor of the area of each slice. Default is <code>trans_bar_fill</code> from the lessR <a href="#">style</a> function.

density	Density of shading lines, in lines per inch. Default value is NULL, that is, no shading lines.
angle	Angle of shading lines in degrees.
lty	Type of line that borders each slice, such as "solid", the default. Can be a vector. Acceptable values are "blank", "solid", "dashed", "dotted", "dotdash", and "longdash".
lwd	Width of line that borders each slice.
edges	Approximation of a circle with a polygon drawn with the number of specified edges.
clockwise	Default value of FALSE specifies to draw the slices counter-clockwise, otherwise clockwise.
init_angle	Starting angle (in degrees) for the slices. For counter-clockwise the default value is 0 (3 o'clock), otherwise 90 (12 o'clock).
values	If not the default value of "off", adds the numerical results to the plot according to "%", "prop" or "input", that is, percentages, proportions, or the value from which the slices are plotted, such as tabulated counts if y is not specified, or the value of y if the plotted values are provided. If any other values parameter is specified, default is set to "%".
values_color	Color of the plotted text. Could be a vector to specify a unique color for each value. If fewer colors are specified than the number of categories, the colors are recycled.
values_size	Character expansion factor, the size, of the plotted text, for which the default value is 0.95.
values_digits	Number of decimal digits for which to display the values_ Default is 0, round to the nearest integer, for "%" and 2 for "prop".
values_position	Position of the plotted text. Default is inside the pie, or, if "label", as part of the label for each value outside of the pie.
main	Title of graph. Set the color with main_color with the <a href="#">style</a> function.
main_cex	Character expansion factor of title relative to 1.
labels_cex	Character expansion factor of labels relative to 1. No labels if set to 0.
cex	General character expansion factor for default values of main_cex, labels_cex, and values_size. Useful for adjustment of text for larger or smaller images.
add	<b>Draw one or more objects</b> , text or a geometric figures, on the plot. Possible values are any text to be written, the first argument, which is "text", or, to indicate a figure, "rect" (rectangle), "line", "arrow", "v.line" (vertical line), and "h.line" (horizontal line). The value "means" is short-hand for vertical and horizontal lines at the respective means. Does not apply to Trellis graphics. Customize with parameters such as fill and color from the <a href="#">style</a> function.

x1	First x coordinate to be considered for each object. All coordinates vary from -1 to 1.
y1	First y coordinate to be considered for each object.
x2	Second x coordinate to be considered for each object. Only used for "rect", "line" and arrow.
y2	Second y coordinate to be considered for each object. Only used for "rect", "line" and arrow.
eval_df	Determines if to check for existing data frame and specified variables. By default is TRUE unless the shiny package is loaded then set to FALSE so that Shiny will run. Needs to be set to FALSE if using the pipe %\>% notation.
quiet	If set to TRUE, no text output. Can change system default with <a href="#">style</a> function.
width	Width of the plot window in inches, defaults to 4.5.
height	Height of the plot window in inches, defaults to 4.5.
pdf_file	Name of the pdf file to if graphics to be redirected to a pdf file.
...	Other parameter values for graphics as defined processed by <a href="#">pie</a> and <a href="#">par</a> for general graphics, which includes radius of the pie, and color_main for the title of the graph.

## Details

### OVERVIEW

Plot a pie chart with default colors, presumably with a relatively small number of values for each variable. By default, colors are selected for the slices, background and grid lines, all of which can be customized. The basic computations of the chart are provided with the standard R functions [pie](#) and [chisq.test](#) and the lessR function [chisq.test](#). A minor modification of the original [pie](#) code provides for the hole in the middle of the pie, the default doughnut or ring chart.

### DATA

The data may either be a vector from the global environment, the user's workspace, as illustrated in the examples below, or one or more variable's in a data frame, or a complete data frame. The default input data frame is `d`. Can specify the source data frame name with the `data` option. If multiple variables are specified, only the numerical variables in the list of variables are analyzed. The variables in the data frame are referenced directly by their names, that is, no need to invoke the standard R mechanisms of the `d$name` notation, the [with](#) function or the [attach](#) function. If the name of the vector in the global environment and of a variable in the input data frame are the same, the vector is analyzed.

The `filter` parameter subsets rows (cases) of the input data frame according to a logical expression. Use the standard R operators for logical statements as described in [Logic](#) such as `&` for and, `|` for or and `!` for not, and use the standard R relational operators as described in [Comparison](#) such as `==` for logical equality `!=` for not equals, and `>` for greater than. See the Examples.

### COLORS

Set the default color of the bars by the current color theme according to `bar_fill_discrete` argument of the function [style](#), which includes the default color theme "colors" that defines a qualitative HCL color scale, or set the bar color with the `fill` parameter. These parameters reference a specified vector of color specifications, such as generated by the lessR [getColor](#) function.



Set `fill` to a single color or a color palette, of which there are many possibilities. Define a qualitative color palette with `"hues"` that provides HCL colors of the same chroma (saturation) and luminance (brightness). Also available are the pre-specified R color palettes `"rainbow"`, `"terrain"`, and `"heat"`. Pre-defined sequential and divergent color ranges are available as implicit calls to `getColor`s. The full list of pre-defined color ranges (defined in 30 degree increments around the HCL color wheel): `"reds"`, `"rusts"`, `"browns"`, `"olives"`, `"greens"`, `"emeralds"`, `"turquoises"`, `"aquas"`, `"blues"`, `"purples"`, `"violets"`, `"magentas"`, and `"grays"`.

Defines a *sequential color scale* with single value of `fill` for a pre-defined palette such as `"blues"`. Or, *manually specify colors*. For example, for a two-level by variable, could set `fill` to `c("coral3", "seagreen3")`, where the specified colors are *not* pre-defined color ranges.

For the pre-defined color scales can obtain more control over the obtained color palettes with an explicit call to `getColor`s for the argument to `fill`. Here the value of chroma (`c`) and luminance (`l`) can be explicitly manipulated in conjunction with the specification of a pre-defined color range. Or, create a custom color range for any value of hue (`h`). See `getColor`s for more information.

To change the background color, set the `"panel_fill"` argument of the `style` function. The hole of the pie defaults to that color, which, of course, can also be specified to a different `color_`

#### ANNOTATIONS

Use the `add` and related parameters to annotate the plot with text and/or geometric figures. Each object is placed according from one to four corresponding coordinates, the required coordinates to plot that object, as shown in the following table. The values of the coordinates vary from -1 to 1.

Value	Object	Required Coordinates
<code>text</code>	<code>text</code>	<code>x1, x2</code>
<code>"rect"</code>	<code>rectangle</code>	<code>x1, y1, x2, y2</code>
<code>"line"</code>	<code>line segment</code>	<code>x1, y1, x2, y2</code>
<code>"arrow"</code>	<code>arrow</code>	<code>x1, y1, x2, y2</code>

The value of `add` specifies the object. For a single object, enter a single value. Then specify the value of the needed corresponding coordinates, as specified in the above table. For multiple placements of that object, specify vectors of corresponding coordinates. To annotate multiple objects, specify multiple values for `add` as a vector. Then list the corresponding coordinates, for up to each of four coordinates, in the order of the objects listed in `add`. See the examples for illustrations.

Can also specify vectors of different properties, such as `add_color`. That is, different objects can be different colors, different transparency levels, etc.

#### STATISTICS

In addition to the pie chart, descriptive and inferential statistics are presented. First, for integer variables such as counts, the frequency table with proportions is displayed. Second, the corresponding chi-square test is also displayed. For real valued variables read from a data frame, the summary statistics such as the mean are reported.

#### PDF OUTPUT

Because `lessR` functions generate their own graphics calls, the standard graphic output functions such as `pdf` do not work with the `lessR` graphics functions. Instead, to obtain pdf output, use the

pdf\_file option, perhaps with the optional width and height options. These files are written to the default working directory, which can be explicitly specified with the R [setwd](#) function.

#### ONLY VARIABLES ARE REFERENCED

The referenced variable in a lessR function can only be a variable name. This referenced variable must exist in either the referenced data frame, d by default, or in the user's workspace, more formally called the global environment. That is, expressions cannot be directly evaluated. For example:

```
> PieChart(rnorm(10)) # does NOT work
```

Instead, do the following:

```
> Y <- rnorm(10) # create vector Y in user workspace
> PieChart(Y)    # directly reference Y
```

#### Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

#### See Also

[pie](#), [chisq.test](#).

#### Examples

```
# get the data from a file included with lessR
d <- rd("Employee")

# -----
# pie (doughnut) chart from the data for a single variable
# -----

# basic pie chart, actually a doughnut or ring chart
# with default hcl colors (except for themes "gray" and "white")
PieChart(Dept)
# short name
#pc(Dept)

# standard pie chart with no hole
pc(Dept, hole=0)

# specify a unique slice color for each of the two slices
# turn off borders
PieChart(Gender, fill=c("pink","lightblue"), lty="blank")

# just males with a salary larger than 75000 USD
PieChart(Dept, filter=(Gender=="M" & Salary > 75000))

# use getColors function to create the pie slice colors
# here as a separate function call
# need to set the correct number of colors to span the full range
mycolors <- getColors("aliceblue", end_pal="steelblue", n=5)
PieChart(Dept, fill=mycolors)
```

```

# specify the colors from a predefined color palette
# see ?getColors
PieChart(Dept, fill="blues")

# wes anderson movie theme, see getColors help for all the themes
PieChart(Dept, fill="GrandBudapest1", values="off")

# display the percentage inside each slice of the pie
# provide a unique color for each displayed value
PieChart(Dept, values="%",
          values_color=c("yellow", "pink", "blue", "purple", "brown"))

# display the counts inside each slice of the pie
# reduce size of displayed counts to 0.75
PieChart(Dept, values="input", values_size=0.75,
          values_color=getOption("window_fill"))

# add transparency and custom color for the displayed values
PieChart(Dept, trans=.6, values="%", values_color=rgb(.3,.3,.3))

# map counts of each level to the fill color of the corresponding slice
PieChart(JobSat, fill=(count))

# -----
# pie chart directly from counts
# -----

# from vector
# pie chart of one variable with three levels
# enter counts as a vector with the combine function, c
# must supply the level names and variable name
# use abbreviation pc for PieChart
City <- c(206, 94, 382)
names(City) <- c("LA", "Chicago", "NY")
pc(City, main="Employees in Each City")

# counts from data frame
x <- c("ACCT", "ADMN", "FINC", "MKTG", "SALE")
y <- c(5, 6, 4, 6, 15)
d <- data.frame(x,y)
names(d) <- c("Dept", "Count")
PieChart(Dept, Count)

# real numbers from data frame
Dept <- c("ACCT", "ADMN", "FINC", "MKTG", "SALE")
Salary <- c(86208.42, 29808.29, 42305.52, 75855.81, 65175.51)
d <- data.frame(x,y)
pc(Dept, Salary)
rm(Dept)
rm(Salary)

```

```

# -----
# annotations
# -----

d <- rd("Employee")

# Place a message in the center of the pie
# Use \n to indicate a new line
PieChart(Dept, add="Employees by\nDepartment", x1=0, y1=0)

# Use style to change some parameter values
style(add_trans=.8, add_fill="gold", add_color="gold4", add_lwd=0.5)
# Add a rectangle around the message centered at <0,0>
PieChart(Dept, add=c("rect", "Employees by\nDepartment"),
          x1=c(-.4,0), y1=c(-.2, 0), x2=.4, y2=.2)

```

---

Plot

---

*Plot One or Two Continuous and/or Categorical Variables*


---

### Description

Abbreviation:

Violin Plot only: vp, ViolinPlot

Box Plot only: bx, BoxPlot

Scatter Plot only: sp, ScatterPlot

A scatterplot displays the values of a distribution, or the relationship between the two distributions in terms of their joint values, as a set of points in an  $n$ -dimensional coordinate system, in which the coordinates of each point are the values of  $n$  variables for a single observation (row of data). From the identical syntax, from any combination of continuous or categorical variables variables  $x$  and  $y$ , `Plot(x)` or `Plot(x,y)`, where  $x$  or  $y$  can be a vector, by default generates a family of related 1- or 2-variable scatterplots, possibly enhanced, as well as related statistical analyses. A categorical variable is either non-numeric, such as an R factor, or may be defined to consist of a small number of equally spaced integer values. The maximum number of such values to define such an integer variable as categorical is set by the `n_cat` parameter, with a default value of 0, that is, by default, all variables with numerical values are defined as continuous variables.

`Plot` is a general function, which produces a wide variety of scatterplots, which, for a single variable, can be in the context of violin plots and box plots, as outlined in the following list. The parameter definitions that follow this list are grouped, with parameters that relate to the same type of plot defined in the same group.

`Plot(x,y)`:  $x$  and  $y$  continuous yields traditional scatterplot of two continuous variables

`Plot(x,y)`:  $x$  and  $y$  categorical, to solve the over-plot problem, yields a bubble (balloon) scatterplot, the size of each bubble based on the corresponding joint frequency as a replacement for the two dimensional bar chart

`Plot(x,y)`:  $x$  (or  $y$ ) categorical and the other variable continuous, yields a scatterplot with means at each level of the categorical variable

Plot(x,y): x (or y) categorical with unique (ID) values and the other variable continuous, yields a Cleveland dot plot

Plot(X,y) or Plot(x,Y): one vector variable defined by several continuous variables, paired with another single continuous variable, yields multiple scatterplots on the same graph

Plot(x): one continuous variable generates either, a violin/box/scatterplot (VBS plot), introduced here, or a run chart with run=TRUE, or x can be an R time series variable for a time series chart

Plot(x): one categorical variable yields a 1-dimensional bubble plot to solve the over-plot problem for a more compact replacement of the traditional bar chart

Plot(X): one vector of continuous variables, with no y-variable, results in a scatterplot matrix

Plot(X): one vector of categorical x-variables, with no y-variable, generalizes to a matrix of 1-dimensional bubble plots, here called the bubble plot frequency matrix, to replace a series of bar charts

Represent the influence of additional categorical variables with by1 or by2 to generate Trellis plots conditioned on one or two variables from implicit calls to functions from Deepayan Sarkar's (2009) lattice package. Use by to group multiple variables on the same plot, or on multiple panels if Trellis graphics are activated. For a third variable, which is continuous, specify size for a bubble plot. By default, the values of analysis that generate the plotted points is data, or choose other values to plot, which are statistics computed from the data such as mean.

## Usage

```
Plot(x, y=NULL, data=d, filter=NULL, enhance=FALSE,
     stat="data", n_cat=getOption("n_cat"),

     by=NULL, by1=NULL, by2=NULL,
     n_row=NULL, n_col=NULL, aspect="fill",

     theme=getOption("theme"),
     fill=NULL,
     color=NULL,
     trans=getOption("trans_pt_fill"),

     size=NULL, size_cut=NULL, shape="circle", means=TRUE,
     sort_yx=c("0", "-", "+"), segments_y=FALSE, segments_x=FALSE,
     jitter_x=0, jitter_y=0,

     ID="row.name", ID_size=0.7,
     MD_cut=0, out_cut=0, out_shape="circle", out_size=1,

     vbs_plot="vbs", vbs_size=0.9, bw=NULL, bw_iter=10,
     violin_fill=getOption("violin_fill"),
     box_fill=getOption("box_fill"),
     vbs_pt_fill="black",
     vbs_mean=FALSE, fences=FALSE,
     k=1.5, box_adj=FALSE, a=-4, b=3,

     radius=NULL, power=0.5, low_fill=NULL, hi_fill=NULL,
```

```

smooth=FALSE, smooth_points=100, smooth_size=1,
smooth_exp=0.25, smooth_bins=128,

fit="off", fit_se=0.95, ellipse=0,

bin=FALSE, bin_start=NULL, bin_width=NULL, bin_end=NULL,
breaks="Sturges", cumulate=FALSE,

run=FALSE, lwd=2, area_fill="transparent", area_origin=0,
center_line=c("default", "mean", "median", "zero", "off"),
show_runs=FALSE, stack=FALSE,

xlab=NULL, ylab=NULL, main=NULL, sub=NULL,
lab_adj=c(0,0), margin_adj=c(0,0,0,0),

rotate_x=getOption("rotate_x"), rotate_y=getOption("rotate_y"),
offset=getOption("offset"),

xy_ticks=TRUE, value_labels=NULL, label_max=20, origin_x=NULL,
legend_title=NULL, scale_x=NULL, scale_y=NULL,

add=NULL, x1=NULL, y1=NULL, x2=NULL, y2=NULL,

eval_df=NULL, digits_d=NULL, quiet=getOption("quiet"),
do_plot=TRUE, width=NULL, height=NULL, pdf_file=NULL,
fun_call=NULL, ...)

```

```

pl(...)
ScatterPlot(...)
sp(...)
BoxPlot(...)
bx(...)
ViolinPlot(...)
vp(...)

```

### Arguments

- |      |   |
|------|---|
| x    | By itself, or with y, by default, a <i>primary variable</i> , that is, plotted by its values mapped to coordinates. The <b>data values</b> can be continuous or categorical, cross-sectional or a time series. If x is sorted, with equal intervals separating the values, or is a time series, then by default plots the points sequentially, joined by line segments_ Can specify multiple x-variables or multiple y-variables as vectors, but not both. Can be in a data frame or defined in the global environment. |
| y    | An optional second <i>primary variable</i> . Variable with values to be mapped to coordinates of points in the plot on the vertical axis_ Can be continuous or categorical. Can be in a data frame or defined in the global environment.  |
| data | Optional data frame that contains one or both of x and y. Default data frame is   |

	d.
filter	A logical expression that specifies a subset of rows of the data frame to analyze.
enhance	For a two-variable scatterplot, if TRUE, automatically add the 0.95 data ellipse, labeling of outliers beyond a Mahalanobis distance of 6 from the ellipse center, the best-fitting least squares line of all the data, the best-fitting least squares line of the regular data without the outliers, and a horizontal and vertical line to represent the mean of each of the two variables.
stat	Transform data for categorical variable $x$ into a simple table of paired levels of $x$ with numerical values of $y$ . Apply specified transformation such as "count" to each of the levels of $x$ , and, for a provided numerical variable $\$y$ , transformations such as "mean", sd, etc. The resulting dot plot is analogous to a bar chart.
n_cat	Number of categories, specifies the largest number of unique, equally spaced integer values of a variable for which the variable will be analyzed as categorical instead of continuous. Default is 0. Use to specify that such variables are to be analyzed as categorical, a kind of informal R factor.
by	A categorical variable to provide a scatterplot for each level of the numeric primary variables $x$ and $y$ on the <i>same</i> plot, a <i>grouping variable</i> . For two-variable plots, applies to the panels of a <b>Trellis graphic</b> if by1 is specified.
by1	A categorical variable called a <i>conditioning variable</i> that activates Trellis graphics, provided by Deepayan Sarkar's (2007) lattice package, to provide a <i>separate</i> panel of numeric primary variables $x$ and $y$ for each level of the variable. Reorder the levels by first converting to a factor variable with <a href="#">factor</a> or <a href="#">lessR factors</a> .
by2	A second <i>conditioning variable</i> to generate Trellis plots jointly conditioned on both the by1 and by2 variables, with by2 as the row variable, which yields a scatterplot (panel) for <i>each</i> cross-classification of the levels of numeric $x$ and $y$ variables.
n_row	Optional specification for the number of rows in the layout of a multi-panel display with Trellis graphics. Specify n_col or n_row, but not both.
n_col	Optional specification for the number of columns in the layout of a multi-panel display with Trellis graphics. Specify n_col or n_row, but not both. If set to 1, then the strip that labels each group locates to the left of each plot instead of the top.
aspect	Lattice parameter for the aspect ratio of the panels, defined as height divided by width. The default value is "fill" to have the panels expand to occupy as much space as possible. Set to 1 for square panels. Set to "xy" to specify a ratio calculated to "bank" to 45 degrees, that is, with the line slope approximately 45 degrees.
theme	Color theme for this analysis. Make persistent across analyses with <a href="#">style</a> .
fill	Either fill color of the points or the area under a line chart. Can also set with the lessR function <a href="#">getColor</a> to select from a variety of color palettes. For points, default is pt_fill and for area under a line chart, violin_fill. For a line chart, set to "on" for default color_

color	Border color of the points or line_color for line plot, can be a vector to customize the color for each point or a color range such as "blues" (see <a href="#">getColor</a> s). Default is pt_color from the lessR <a href="#">style</a> function.
trans	Transparency factor of the fill color of each point. Default is trans_pt_fill from the lessR <a href="#">style</a> function.
size	When set to a constant, the scaling factor for <b>standard points</b> (not bubbles) or a line, with default of 1.0 for points and 2.0 for a line. Set to 0 to not plot the points or lines. When set to a variable, activates a bubble plot with the size of each bubble further determined by the value of radius. Applies to the standard two-variable scatterplot as well as to the scatterplot component of the integrated Violin-Box-Scatterplot (VBS) of a single continuous variable.
size_cut	If TRUE (or 1), then for a bubble plot in which the bubble sizes are defined by a size variable, show the value of the sizing variable for selected bubbles in the center of the bubbles, unless the bubble is too small. If FALSE, no value is displayed. If a number greater than 1, then display the value only for the indicated number of values, such as just the max and min for a setting of 2, the default value when bubbles represent a size variable. Color of the displayed text set by bubble_text from the <a href="#">style</a> function.
shape	The plot character(s). The default value is a circle with both an color and filled interior, specified with color and fill. Possible values are circle, square, diamond, triup (triangle up), tridown (triangle down), all uppercase and lowercase letters, all digits, and most punctuation characters. The numbers 21 through 25 as defined by the R <a href="#">points</a> function also apply. If plotting levels according to by, then list one shape for each level to be plotted.
means	If the one variable is categorical the other variable continuous, then if TRUE, by default, plot means with the scatterplot. Also applies to a 1-D scatterplot.
sort_yx	Sort the values of y by the values of x, such as for a Cleveland dot plot, that is, a numeric x-variable paired with a categorical y-variable with unique values. If a x is a vector of two variables, sort by their difference.
segments_y	For one x-variable, draw a line segment from the y-axis to each plotted point, such as for the Cleveland dot plot. For two x-variables, the line segments connect the two points.
segments_x	Draw a line segment from the x-axis for each plotted point.
jitter_x	Randomly perturbs the plotted points of a scatterplot horizontally according to an internally computed formula, or can be explicitly specified.
jitter_y	Randomly perturbs the plotted points of a scatterplot vertically according to an internally computed formula, or can be explicitly specified.
ID	Name of variable to provide the <b>labels for the selected plotted points for outlier identification</b> , row names of data frame by default. To label all the points use the add parameter described later.
ID_size	Size of the plotted labels. Modify text color of the labels with the <a href="#">style</a> function parameter ID_color.
MD_cut	Mahalanobis distance cutoff to define an outlier in a 2-variable scatterplot.



out_cut	Count or proportion of plotted points to label, in order of their distance from the scatterplot center (means), counting down from the more extreme point. For two-variable plots, assess distance from the center with Mahalanobis distance. For VBS plots of a single continuous variable, refers to outliers on each side of the plot.
out_shape	Shape of outlier points in a 2-variable scatterplot or a VBS plot. Modify fill color from the current theme with the <code>style</code> function parameters <code>out_fill</code> and <code>out2_fill</code> .
out_size	Size of outlier points in a 2-variable scatterplot or VBS plot.
vbs_plot	A character string that specifies the components of the <b>integrated Violin-Box-Scatterplot (VBS) of a continuous variable</b> . A "v" in the string indicates a violin plot, a "b" indicates a box plot with flagged outliers, and a "s" indicates a 1-variable scatterplot. Default value is "vbs". The characters can be in any order and upper- or lower-case. Generalize to Trellis plots with the <code>by1</code> and <code>by2</code> parameters, but currently only applies to horizontal displays. Modify fill and border colors from the current theme with the <code>style</code> function parameters <code>violin_fill</code> , <code>violin_color</code> , <code>box_fill</code> and <code>box_color</code> .
vbs_size	Width of the violin plot to the plot area. Make the violin (and also the accompanying box plot) larger or smaller by making the plot area and/or this value larger or smaller.
bw	Bandwidth for the smoothness of the violin plot. Higher values for smoother plots. Default is to calculate a bandwidth that provides a relative smooth density plot.
bw_iter	Number of iterations used to modify default R bandwidth to further smooth the obtained density estimate. When set, also displays the iterations and corresponding results.
violin_fill	Fill color for a <b>violin plot</b> .
box_fill	Fill color for a box plot.
vbs_pt_fill	Points in a VBS scatterplot are black by default because the background is the violin, which is based on the current theme <code>color_</code> . To use the values for <code>pt_fill</code> and <code>pt_color</code> specified by the <code>style</code> function, set to "default". Or set to any desired <code>color_</code> .
vbs_mean	Show the mean on the box plot with a strip the color of <code>out_fill</code> , which can be changed with the <code>style</code> function.
fences	If TRUE, draw the inner upper and lower fences as dotted line segments.
k	IQR multiplier for the basis of calculating the distance of the whiskers of the box plot from the box. Default is Tukey's setting of 1.5.
box_adj	Adjust the box and whiskers, and thus outlier detection, for skewness using the <code>medcouple</code> statistic as the robust measure of skewness according to Hubert and Vandervieren (2008).
a, b	Scaling factors for the adjusted box plot to set the length of the whiskers. If explicitly set, activates <code>box_adj</code> .

radius	Scaling factor of the bubbles in a <b>bubble plot</b> , which sets the radius of the largest displayed bubble in inches. To activate, either set the value of size to a third variable where the default is 0.10, or for categorical variables, either a factor or an integer variable with the number of unique values less than n_cat, the size of the bubbles represents frequency, with a default of 0.22.
power	Relative size of the scaling of the bubbles to each other. Default value of 0.5 scales the bubbles so that the area of each bubble is the value of the corresponding sizing variable. Value of 1 scales so the radius of the bubble is the value of the sizing variable, increasing the discrepancy of size between the variables.
low_fill	For a categorical variable and the resulting bubble plot, or a matrix of these plots, sets a color gradient of the fill color beginning with this color_
hi_fill	For a categorical variable and the resulting bubble plot, or a matrix of these plots, sets a color gradient of the fill color ending with this color_
smooth	<b>Smoothed density plot</b> for two numerical variables. By default, set to TRUE for 2500 or more rows of data.
smooth_points	Number of points superimposed on the density plot in the areas of the lowest density to help identify outliers, which controls how dark are the smoothed points.
smooth_size	Size of points superimposed on the density plot.
smooth_exp	Exponent of the function that maps the density scale to the color scale.
smooth_bins	Number of bins in both directions for the density estimation.
fit	The <b>best fit line</b> . Default value is "off", with options for non-linear "loess" and for linear least squares, indicated by "lm". If potential outliers are identified according to out_cut, a second (dashed) fit line is displayed calculated <i>without</i> the outliers. Modify the line color from with the <code>style</code> function parameter fit_color, and the line width with fit_lwd.
fit_se	Confidence level for the error band displayed around the line of best fit. On by default at 0.95 if a fit line is specified. Can be a vector to display multiple ranges. Set to 0 to turn off.
ellipse	Confidence level of a <b>data ellipse</b> for a scatterplot of only a single x-variable and a single y-variable according to the contours of the corresponding bivariate normal density function. Can specify the confidence level(s) for a single or vector of numeric values from 0 to 1, to plot one or more specified ellipses. For Trellis graphics, only the maximum level applies with only one ellipse per panel. Modify fill and border colors with the <code>style</code> function parameters ellipse_fill and ellipse_color.
bin	If TRUE, display the default frequency distribution for the text output of the Violin-Box-Scatter (VBS) Plot, or, if values is set to "count", a frequency polygon.
bin_start	Optional specified starting value of the bins for a <b>frequency polygon or for the text output of a Violin-Box-Scatter (VBS) Plot</b> . Also, sets bin to TRUE.

bin_width	Optional specified bin width value. Also, sets bin to TRUE.
bin_end	Optional specified value that is within the last bin, so the actual endpoint of the last bin may be larger than the specified value.
breaks	The method for calculating the bins, or an explicit specification of the bins, such as with the standard R <a href="#">seq</a> function or other options provided by the <a href="#">hist</a> function. Also, sets bin to TRUE.
cumulate	Specify a cumulative frequency polygon.
run	If set to TRUE, generate a <b>run chart</b> , i.e., line chart, in which points are plotted in the sequential order of occurrence in the data table. By default, the points are connected by line segments to form a run chart. Set by default when the x-values are sorted with equal intervals or a single variable is a time series. Customize the color of the line segments with <code>segments_color</code> with function <a href="#">style</a> .
lwd	Width of the line segments_ Set to zero to remove the line segments_
area_fill	Parameter <code>fill</code> applies to points if only points and if only a run chart or time series chart, then to area under line segments_ But <code>area_fill</code> takes precedence over <code>fill</code> for the area under the line segments, which is needed to provide both fill for points and this area. Like <code>fill</code> , the value of "on" sets the default fill color for points.
area_origin	Origin for the filled area under the time series line. Values less than this value are below the corresponding reference line, values larger are above the line.
center_line	Plots a dashed line through the middle of a run chart. The two possible values for the line are "mean" and "median". Provides a center line for the "median" by default, when the values randomly vary about the mean. A value of "zero" specifies the center line should go through zero. Currently does not apply to Trellis plots.
show_runs	If TRUE, display the individual runs in the run analysis. Also, sets run to TRUE.
stack	If TRUE, multiple time plots are stacked on each other, with area set to TRUE by default.
xlab, ylab	<b>Axis label</b> for x-axis or y-axis_ If not specified, then the label becomes the name of the corresponding variable label if it exists, or, if not, the variable name. If <code>xy_ticks</code> is FALSE, no ylab is displayed. Customize these and related parameters with parameters such as <code>lab_color</code> from the <a href="#">style</a> function.
main	Label for the title of the graph. If the corresponding variable labels exist, then the title is set by default from the corresponding variable labels.
sub	Sub-title of graph, below xlab.
lab_adj	Two-element vector – x-axis label, y-axis label – adjusts the position of the axis labels in approximate inches. + values move the labels away from plot edge. Not applicable to Trellis graphics.
margin_adj	Four-element vector – top, right, bottom and left – adjusts the margins of the plotted figure in approximate inches. + values move the corresponding margin away from plot edge. Not applicable to Trellis graphics.

rotate_x	Degrees that the axis values for the value labels on the x-axis are rotated, usually to accommodate longer values, typically used in conjunction with offset. When equal 90 the value labels are perpendicular to the x-axis and a different algorithm places the labels so that offset is not needed.
rotate_y	Degrees that the axis values for the value labels on the y-axis are rotated, usually to accommodate longer values, typically used in conjunction with offset.
offset	The amount of spacing between the axis values and the axis_ Default is 0.5. Larger values such as 1.0 are used to create space for the label when longer axis value names are rotated.
xy_ticks	Flag that indicates if tick marks and associated <b>axis values</b> on the axes are to be displayed. To rotate the axis values, use rotate_x, rotate_y, and offset from the <a href="#">style</a> function.
value_labels	Labels for the x-axis on the graph to override existing data values, including factor levels. If the variable is a factor and value_labels is not specified (is NULL), then the value_labels are set to the factor levels with each space replaced by a new line character. If x and y-axes have the same scale, they also apply to the y-axis_
label_max	Maximum size of labels for the values of a categorical variable. Not a literal maximum as preserving unique values may require a larger number of characters than specified.
origin_x	Origin of x-axis_ Starting value of x, by default the minimum value of x, except when stat is set to "count" or related where the origin is zero by default, but can be modified.
legend_title	Title of the legend for a multiple-variable x or y plot.
scale_x	If specified, a vector of three values that define the x-axis with numerical values: starting value, ending value, and number of intervals.
scale_y	If specified, a vector of three values that define the y-axis with numerical values: starting value, ending value, and number of intervals.
add	<b>Draw one or more objects</b> , text or a geometric figures, on the plot. Possible values are any text to be written, the first argument, which is "text", or, "labels" to label each point with the row name, or, "rect" (rectangle), "line", "arrow", "v_line" (vertical line), and "h_line" (horizontal line). The value "means" is short-hand for vertical and horizontal lines at the respective means. Does not apply to Trellis graphics. Customize with parameters such as add_fill and add_color from the <a href="#">style</a> function.
x1	First x-coordinate to be considered for each object, can be "mean_x". Not used for "h_line".
y1	First y-coordinate to be considered for each object, can be "mean_y". Not used for "v_line".
x2	Second x-coordinate to be considered for each object, can be "mean_x". Only used for "rect", "line" and arrow.

<code>y2</code>	Second y-coordinate to be considered for each object, can be "mean_y". Only used for "rect", "line" and arrow.
<code>eval_df</code>	Determines if to check for existing data frame and specified variables. By default is TRUE unless the shiny package is loaded then set to FALSE so that Shiny will run. Needs to be set to FALSE if using the pipe <code>%\&gt;%</code> notation.
<code>digits_d</code>	Number of significant digits for each of the displayed summary statistics.
<code>quiet</code>	If set to TRUE, no text output. Can change system default with <code>style</code> function.
<code>do_plot</code>	If TRUE, the default, then generate the plot.
<code>width</code>	Width of the plot window in inches, defaults to 5 except in RStudio to maintain an approximate square plotting area.
<code>height</code>	Height of the plot window in inches, defaults to 4.5 except for 1-D scatterplots and when in RStudio.
<code>pdf_file</code>	Indicate to direct pdf graphics to the specified name of the pdf file.
<code>fun_call</code>	Function call. Used with <code>kni tr</code> to pass the function call when obtained from the abbreviated function call <code>sp</code> .
<code>...</code>	Other parameter values for non-Trellis graphics as defined by and processed by standard R functions <code>plot</code> and <code>par</code> , including <code>xlim</code> and <code>ylim</code> for setting the range of the x and y-axes <code>cex.main</code> for the size of the title <code>col.main</code> for the color of the title <code>cex</code> for the size of the axis value labels <code>sub</code> and <code>col.sub</code> for a subtitle and its color

## Details

### VARIABLES and TRELLIS PLOTS

There is at least one primary variable, `x`, which defines the coordinate system for plotting in terms of the x-axis, the horizontal axis. Plots may also specify a second primary variable, `y`, which defines the y-axis of the coordinate system. One of these primary variables may be a vector. The simplest plot is from the specification of only one or two primary variables, each as a single variable, which generates a single scatterplot of either one or two variables, necessarily on a single plot, called a panel, defined by a single x-axis and usually a single y-axis.

For numeric primary variables, a single panel may also contain multiple plots of two types. Form the first type from subsets of observations (rows of data) based on values of a categorical variable. Specify this plot with the `by` parameter, which identifies the grouping variable to generate a scatterplot of the primary variables for each of its levels. The points for each group are plotted with a different shape and/or color. By default, the colors vary, though to maintain the color scheme, if there are only two levels of the grouping variable, the points for one level are filled with the current theme color and the points for the second level are plotted with transparent interiors.

Or, obtain multiple scatterplots on the same panel with multiple numeric x-variables, or multiple y-variables. To obtain this graph, specify one of the primary variables as a vector of multiple variables.

Trellis graphics, from Deepayan Sarkar's (2009) `lattice` package, may be implemented in which multiple panels for one numeric x-variable and one numeric y-variable are displayed according to

the levels of one or two categorical variables, called conditioning variables. A variable specified with `by` is a conditioning variable that results in a Trellis plot, the scatterplot of `x` and `y` produced at *each* level of the `by1` variable. The inclusion of a second conditioning variable, `by2`, results in a separate scatterplot panel for *each* combination of cross-classified values of both `by1` and `by2`. A grouping variable according to `by` may also be specified, which is then applied to each panel.

Control the panel dimensions and the overall size of the Trellis plot with the following parameters: `width` and `height` for the physical dimensions of the plot window, `n_row` and `n_col` for the number of rows and columns of panels, and `aspect` for the ratio of the height to the width of each panel. The plot window is the standard graphics window that displays on the screen, or it can be specified as a pdf file with the `pdf_file` parameter.

#### CATEGORICAL VARIABLES

Conceptually, there are continuous variables and categorical variables. Categorical variables have relatively few unique data values. However, categorical variables can be defined with non-numeric values, but also with numeric values, such as responses to a five-point Likert scale from Strongly Disagree to Strongly Agree, with responses coded 1 to 5. The three `by` variables – `by1`, `by2` and `by` – only apply to graphs created with numeric `x` and/or `y` variables, continuous or categorical.

The standard and most general way to define a categorical variable is as an R factor, such as created with the `lessR` `factors` function. `lessR` provides the option to define an integer variable with equally spaced values as categorical based on the value of `n_cat`, which can be set locally or globally with the `style` function. For example, for a variable with data values from 5-point Likert scale, a value of `n_cat` of 5 will define the variable as categorical. The default value is 0. To explicitly analyze the values as categorical, set `n_cat` to a value larger than 0, at least the size of the number of unique integer values. Can also annotate a graph of the values of an integer categorical variable with `value_labels` option.

A scatterplot of Likert type data is problematic because there are so few possibilities for points in the scatterplot. For example, for a scatterplot of two five-point Likert response data, there are only 26 possible paired values to plot, so most of the plotted points overlap with others. In this situation, that is, when a single variable or two variables with Likert response scales are specified, a bubble plot is automatically provided, with the size of each point relative to the joint frequency of the paired data values. To request a sunflower plot in lieu of the bubble plot, set the `shape` to "sunflower".

#### DATA

The default input data frame is `d`. Specify another name with the `data` option. Regardless of its name, the data frame need not be attached to reference the variables directly by its name, that is, no need to invoke the `d$name` notation. The referenced variables can be in the data frame and/or the user's workspace, the global environment.

The data values themselves can be plotted, or for a single variable, counts or proportions can be plotted on the `y`-axis. For a categorical `x`-variable paired with a continuous variable, means and other statistics can be plotted at each level of the `x`-variable. If `x` is continuous, it is binned first, with the standard `Histogram` binning parameters available, such as `bin_width`, to override default values. The `stat` parameter sets the values to plot, with `data` the default. By default, the connecting line segments are provided, so a frequency polygon results. Turn off the lines by setting `lwd=0`.

The `filter` parameter subsets rows (cases) of the input data frame according to a logical expression. Use the standard R operators for logical statements as described in `Logic` such as `&` for and, `|` for or and `!` for not, and use the standard R relational operators as described in `Comparison` such as `==` for logical equality `!=` for not equals, and `>` for greater than. See the Examples.

#### VALUE LABELS

The value labels for each axis can be over-riden from their values in the data to user supplied values with the `value_labels` option. This option is particularly useful for Likert-style data coded as integers. Then, for example, a 0 in the data can be mapped into a "Strongly Disagree" on the plot. These value labels apply to integer categorical variables, and also to factor variables. To enhance the readability of the labels on the graph, any blanks in a value label translate into a new line in the resulting plot. Blanks are also transformed as such for the labels of factor variables.

However, the `lessR` function `factors` allows for the easy creation of factors, one variable or a vector of variables, in a single statement, and is generally recommended as the method for providing value labels for the variables.

#### VARIABLE LABELS

Although standard R does not provide for variable labels, `lessR` can store the labels in the data frame with the data, obtained from the `Read` function or `VariableLabels`. If variable labels exist, then the corresponding variable label is by default listed as the label for the corresponding axis and on the text output.

#### ONE VARIABLE PLOT

The one variable plot of one continuous variable generates either a violin/box/scatterplot (VBS plot), or a run chart with `run=TRUE`, or `x` can be an R time series variable for a time series chart. For the box plot, for gray scale output potential outliers are plotted with squares and outliers are plotted with diamonds, otherwise shades of red are used to highlight outliers. The default definition of outliers is based on the standard boxplot rule of values more than 1.5 IQR's from the box. The definition of outliers may be adjusted (Hubert and Vandervieren, 2008), such that the whiskers are computed from the medcouple index of skewness (Brys, Hubert, & Struyf, 2004).

The plot can also be obtained as a bubble plot of frequencies for a categorical variable.

#### TWO VARIABLE PLOT

When two variables are specified to plot, by default if the values of the first variable, `x`, are unsorted, or if there are unequal intervals between adjacent values, or if there is missing data for either variable, a scatterplot is produced from a call to the standard R `plot` function. By default, sorted values with equal intervals between adjacent values of the first of the two specified variables yields a function plot if there is no missing data for either variable, that is, a call to the standard R `plot` function with `type="l"`, which connects each adjacent pair of points with a line segment.

Specifying multiple, continuous `x`-variables against a single `y` variable, or vice versa, results in multiple plots on the same graph. The color of the points of the second variable is the same as that of the first variable, but with a transparent fill. For more than two `x`-variables, multiple colors are displayed, one for each `x`-variable.

#### BUBBLE PLOT FREQUENCY MATRIX (BPFM)

Multiple categorical variables for `x` may be specified in the absence of a `y` variable. A bubble plot results that illustrates the frequency of each response for each of the variables in a common figure in which the `x`-axis contains all of the unique labels for all of the variables plotted. Each line of information, the bubbles and counts for a single variable, replaces the standard bar chart in a more compact display. Usually the most meaningful when each variable in the matrix has the same response categories, that is, levels, such as for a set of shared Likert scales. The BPFM is considerably condensed presentation of frequencies for a set of variables than are the corresponding bar charts.

#### SCATTERPLOT MATRIX

A single vector of continuous variables specified as `x`, with no `y`-variable, generates a scatterplot matrix of the specified variable. A continuous variable is defined as a numeric variable with more

than `n_cat` unique responses. To force an item with a small number of unique responses, such as from a 5-pt Likert scale, to be treated as continuous, set `n_cat` to a number lower than 5, such as `n_cat=0` in the function call.

The scatterplot matrix is displayed according to the current color theme. Specific colors such as `fill`, `color`, etc. can also be provided. The upper triangle shows the correlation coefficient, and the lower triangle each corresponding scatterplot, with, by default, the non-linear loess best fit line. The `fit` option can be used to provide the linear least squares line instead, along with the corresponding `fit_color` for the color of the fit line.

#### SIZE VARIABLE

A variable specified with `size=` is a numerical variable that activates a bubble plot in which the size of each bubble is determined by the value of the corresponding value of `size`, which can be a variable or a constant.

To explicitly vary the shapes, use `shape` and a list of shape values in the standard R form with the `c` function to combine a list of values, one specified shape for each group, as shown in the examples. To explicitly vary the colors, use `fill`, such as with R standard color names. If `fill` is specified without `shape`, then colors are varied, but not shapes. To vary both shapes and colors, specify values for both options, always with one shape or color specified for each level of the by variable.

Shapes beyond the standard list of named shapes, such as "circle", are also available as single characters. Any single letter, uppercase or lowercase, any single digit, and the characters "+", "\*" and "#" are available, as illustrated in the examples. In the use of `shape`, either use standard named shapes, or individual characters, but not both in a single specification.

#### SCATTERPLOT ELLIPSE

For a scatterplot of two numeric variables, the `ellipse=TRUE` option draws the .95 data ellipse as computed by the `ellipse` function, written by Duncan Murdoch and E. D. Chow, from the `ellipse` package. The axes are automatically lengthened to provide space for the entire ellipse that extends beyond the maximum and minimum data values. The specific level of the ellipse can be specified with a numerical value in the form of a proportion. Multiple numerical values of `ellipse` may also be specified to obtain multiple ellipses.

#### BOXPLOTS

For a single variable the preferred plot is the integrated violin/box/scatter plot or VBS plot. Only the violin or box plot can be obtained with the corresponding aliases `ViolinPlot` and `BoxPlot`, or by setting `vbs_plot` to "v" or "b". To view a box plot of a continuous variable (Y) across the levels of a categorical variable (X), either as part of the full VBS plot, or by itself, there are two possibilities:

1. `Plot(Y,X)` or `BoxPlot(Y, X)`
2. `Plot(Y, by1=X)` or `BoxPlot(Y, by1=X)`

Both styles produce the same information. What differs is the color scheme.

The first possibility places the multiple box plots on a single pane and also, for the default color scheme "colors", displays the sequence of box plots with the default qualitative color palette from the `lessR` function `getColor`s. All colors are displayed at the same level of gray-scale saturation and brightness to avoid perceptual bias. `BarChart` and `PieChart` use the same default colors as well.

The second possibility with `by1` produces the different box plots on a separate panel, that is, a Trellis chart. These box plots are displayed with a single hue, the first color, blue, in the default qualitative sequence.



### TIME CHARTS

Specifying one or more x-variables with no y-variables, and `run=TRUE` plots the x-variables in a run chart. The values of the specified x-variable are plotted on the y-axis, with `Index` on the x-axis. `Index` is the ordinal position of each data value, from 1 to the number of values.

If the specified x-variable is of type `Date`, or is a time series, a time series plot is generated for each specified variable. If a formal R time-series, univariate or multivariate, specify as the x-variable. Or, specify the x-variable of type `Date`, and then specify the y-variable as one or more time series to plot. The y-variable can be formatted as tidy data with all the values in a single column, or as wide-formatted data with the time-series variables in separate columns.

### 2-D KERNEL DENSITY

With `smooth=TRUE`, the R function `smoothScatter` is invoked according to the current color theme. Useful for very large data sets. The `smooth_points` parameter plots points from the regions of the lowest density. The `smooth_bins` parameter specifies the number of bins in both directions for the density estimation. The `smooth_exp` parameter specifies the exponent in the function that maps the density scale to the color scale to allow customization of the intensity of the plotted gradient colors. Higher values result in less color saturation, de-emphasizing points from regions of lessor density. These parameters are respectively passed directly to the `smoothScatter` `nrpoints`, `nbin` and `transformation` parameters. Grid lines are turned off, but can be displayed by setting the `grid_color` parameter.

### COLORS

A color theme for all the colors can be chosen for a specific plot with the `colors` option with the `lessR` function `style`. The default color theme is "lightbronze". A gray scale is available with "gray", and other themes are available as explained in `style`, such as "sienna" and "darkred". Use the option `style(sub_theme="black")` for a black background and partial transparency of plotted colors.

Colors can also be changed for individual aspects of a scatterplot as well with the `style` function. To provide a warmer tone by slightly enhancing red, try a background color such as `panel_fill="snow"`. Obtain a very light gray with `panel_fill="gray99"`. To darken the background gray, try `panel_fill="gray97"` or lower numbers. See the `lessR` function `showColors`, which provides an example of all available named R colors with their RGB values.

For the color options, such as `violin_color`, the value of "off" is the same as "transparent".

### ANNOTATIONS

Use the `add` and related parameters to annotate the plot with text and/or geometric figures. Each object is placed according from one to four corresponding coordinates, the required coordinates to plot that object, as shown in the following table. x-coordinates may have the value of "mean\_x" and y-coordinates may have the value of "mean\_y".

Value	Object	Required Coordinates
"\emph{text}"	text	x1, y1
"rect"	rectangle	x1, y1, x2, y2
"line"	line segment	x1, y1, x2, y2
"arrow"	arrow	x1, y1, x2, y2
"v_line"	vertical line	x1
"h_line"	horizontal line	y1

"means"	horiz, vert lines	
---------	-------------------	--

The value of `add` specifies the object. For a single object, enter a single value. Then specify the value of the needed corresponding coordinates, as specified in the above table. For multiple placements of that object, specify vectors of corresponding coordinates. To annotate multiple objects, specify multiple values for `add` as a vector. Then list the corresponding coordinates, for up to each of four coordinates, in the order of the objects listed in `add`.

Can also specify vectors of different properties, such as `add_color`. That is, different objects can be different colors, different transparency levels, etc.

#### PDF OUTPUT

To obtain pdf output, use the `pdf_file` option, perhaps with the optional `width` and `height` options. These files are written to the default working directory, which can be explicitly specified with the `setwd` function.

#### ADDITIONAL OPTIONS

Commonly used graphical parameters that are available to the standard R function `plot` are also generally available to `Plot`, such as:

**`cex.main`, `col.lab`, `font.sub`, etc.** Settings for main- and sub-title and axis annotation, see `title` and `par`.

**`main`** Title of the graph, see `title`.

**`xlim`** The limits of the plot on the x-axis, expressed as `c(x1,x2)`, where `x1` and `x2` are the limits. Note that `x1 > x2` is allowed and leads to a reversed axis\_

**`ylim`** The limits of the plot on the y-axis\_

#### ONLY VARIABLES ARE REFERENCED

A referenced variable in a `lessR` function can only be a variable name. This referenced variable must exist in either the referenced data frame, such as the default `d`, or in the user's workspace, more formally called the global environment. That is, expressions cannot be directly evaluated. For example:

```
> Plot(rnorm(50), rnorm(50)) # does NOT work
```

Instead, do the following:

```
> X <- rnorm(50) # create vector X in user workspace
> Y <- rnorm(50) # create vector Y in user workspace
> Plot(X,Y)     # directly reference X and Y
```

#### Value

The output can optionally be saved into an R object, otherwise it simply appears in the console. The output here is just for the outlier analysis of the two-variable scatterplot with continuous variables. The outlier identification must be activated for the analysis, such as from parameter `MD_cut`.

#### READABLE OUTPUT

`codeout_outlier`: Mahalanobis Distance of each outlier.

## STATISTICS

codeoutliers\_indices: Location of the outliers in the x and y vectors.

**Author(s)**

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

**References**

Brys, G., Hubert, M., & Struyf, A. (2004). A robust measure of skewness. *Journal of Computational and Graphical Statistics*, 13(4), 996-1017.

Murdoch, D, and Chow, E. D. (2013). ellipse function from the ellipse package package.

Gerbing, D. W. (2014). *R Data Analysis without Programming*, Chapter 8, NY: Routledge.

Hubert, M. and Vandervieren, E. (2008). An adjusted boxplot for skewed distributions, *Computational Statistics and Data Analysis* 52, 51865201.

Sarkar, Deepayan (2008) *Lattice: Multivariate Data Visualization with R*, Springer. <http://lmdvr-forge.r-project.org/>

**See Also**

[plot](#), [stripchart](#), [title](#), [par](#), [loess](#), [Correlation](#), [style](#).

**Examples**

```
# read the data
d <- rd("Employee", quiet=TRUE)
d <- Subset(random=.6, quiet=TRUE) # less computationally intensive

#-----
# traditional scatterplot with two numeric variables
#-----

# scatterplot with all defaults
Plot(Years, Salary)
# or use abbreviation sp in place of Plot
# or use full expression ScatterPlot in place of Plot

# maximum information, minimum input: scatterplot +
# means, outliers, ellipse, least-squares lines with and w/o outliers
Plot(Years, Salary, enhance=TRUE)

# extend x and y axes
Plot(Years, Salary, scale_x=c(-10, 35, 10), scale_y=c(0,200000,10))

# just males employed more than 5 years
Plot(Years, Salary, filter=(Gender=="M" & Years > 5))
```

```

# plot 0.95 data ellipse with the points identified that represent
# outliers defined by a Mahalanobis Distance larger than 6
# save outliers into R object out, then remove from d
d[1, "Salary"] <- 200000
out <- Plot(Years, Salary, ellipse=0.95, MD_cut=6)
d <- d[-out$outlier_indices,]

# new shape and point size, no grid or background color
# then put style back to default
style(panel_fill="powderblue", grid_color="off")
Plot(Years, Salary, size=2, shape="diamond")
style()

# translucent data ellipses without points or edges
# show the idealized joint distribution for bivariate normality
style(ellipse_color="off")
Plot(Years, Salary, size=0, ellipse=seq(.1,.9,.10))
style()

# bubble plot with size determined by the value of Pre
# display the value for the bubbles with values of min, median and max
Plot(Years, Salary, size=Pre, size_cut=3)

# variables in a data frame not the default d
# plot 0.6 and 0.9 data ellipses with partially transparent points
# change color theme to gold with black background
style("gold", sub_theme="black")
Plot(eruptions, waiting, trans=.5, ellipse=seq(.6,.9), data=faithful)

# scatterplot with two x-variables, plotted against Salary
# define a new style, then back to default
style(window_fill=rgb(247,242,230, maxColorValue=255),
      panel_fill="off", panel_color="off", pt_fill="black", trans=0,
      lab_color="black", axis_text_color="black",
      axis_y_color="off", grid_x_color="off", grid_y_color="black",
      grid_lty="dotted", grid_lwd=1)
Plot(c(Pre, Post), Salary)
style()

# increase span (smoothing) from default of .7 to 1.25
# span is a loess parameter, which generates a caution that can be
# ignored that it is not a graphical parameter -- we know that
# display confidence intervals about best-fit line at
# 0.95 confidence level
Plot(Years, Salary, fit="loess", span=1.25)

# 2-D kernel density (more useful for larger sample sizes)
Plot(Years, Salary, smooth=TRUE)

#-----
# scatterplot matrix from a vector of numeric variables

```

```

#-----

# with least squares fit line
Plot(c(Salary, Years, Pre), fit="lm")

#-----

# Trellis graphics and by for groups with two numeric variables
#-----

# Trellis plot with condition on 1-variable
# optionally re-order default alphabetical R ordering by converting
# to a factor with lessR factors (which also does multiple variables
d$Gender <- factors(Gender, levels=c("M", "F"))
Plot(Years, Salary, by1=Gender)

# all three by variables
Plot(Years, Salary, by1=Dept, by2=Gender, by=Plan)

# vary both shape and color with a least-squares fit line for each group
style(color=c("darkgreen", "brown"))
Plot(Years, Salary, by1=Gender, fit="lm", shape=c("F", "M"), size=.8)
style("gray")

# compare the men and women Salary according to Years worked
# with an ellipse for each group
Plot(Years, Salary, by=Gender, ellipse=.50)

#-----

# analysis of a single numeric variable (or vector)
#-----

# One continuous variable
# -----
# integrated Violin/Box/Scatterplot, a VBS plot
Plot(Salary)

# by variable, different colors for different values of the variable
# all on one panel
Plot(Salary, by=Dept)

# large sample size
x <- rnorm(10000)
Plot(x)

# custom colors for outliers, which might not appear in this subset data
style(out_fill="hotpink", out2_fill="purple")
Plot(Salary)

```

```

style()

# no violin plot or scatterplot, just a boxplot
Plot(Salary, vbs_plot="b")
# or, the same with the mnemonic
BoxPlot(Salary)

# two related displays of box plots for different levels of a
# categorical variable
BoxPlot(Salary, by1=Dept)

# binned values to plot counts
# -----
# bin the values of Salary to plot counts as a frequency polygon
# the counts are plotted as points instead of the data
Plot(Salary, stat="count") # bin the values

# time charts
#-----
# run chart, with default fill area
Plot(Salary, run=TRUE, area_fill="on")

# two run charts in same plot
# or could do a multivariate time series
Plot(c(Pre, Post), run=TRUE)

# Trellis graphics run chart with custom line width, no points
Plot(Salary, run=TRUE, by1=Gender, lwd=3, size=0)

# daily time series plot
# create the daily time series from R built-in data set airquality
oz.ts <- ts(airquality$Ozone, start=c(1973, 121), frequency=365)
Plot(oz.ts)

# multiple time series plotted from dates and stacked
# black background with translucent areas, then reset theme to default
style(sub_theme="black", color="steelblue2", trans=.55,
      window_fill="gray10", grid_color="gray25")
date <- seq(as.Date("2013/1/1"), as.Date("2016/1/1"), by="quarter")
x1 <- rnorm(13, 100, 15)
x2 <- rnorm(13, 100, 15)
x3 <- rnorm(13, 100, 15)
df <- data.frame(date, x1, x2, x3)
rm(date); rm(x1); rm(x2); rm(x3)
Plot(date, x1:x3, data=df)
style()

# trigger a time series with a Date variable specified first
# stock prices for three companies by month: Apple, IBM, Intel
d <- rd("StockPrice")
# only plot Apple
Plot(date, Price, filter=(Company=="Apple"))

```

```
# Trellis plots, one for each company
Plot(date, Price, by1=Company, n_col=1)
# all three plots on the same panel, three shades of blue
Plot(date, Price, by=Company, color="blues")

#-----
# analysis of a single categorical variable
#-----
d <- rd("Employee")

# default 1-D bubble plot
# frequency plot, replaces bar chart
Plot(Dept)

# abbreviated category labels
Plot(Dept, label_max=2)

# plot of frequencies for each category (level), replaces bar chart
Plot(Dept, stat="count")

#-----
# scatterplot of numeric against categorical variable
#-----

# generate a chart with the plotted mean of each level
# rotate x-axis labels and then offset from the axis
style(rotate_x=45, offset=1)
Plot(Dept, Salary)
style()

#-----
# Cleveland dot plot
#-----

# row.names on the y-axis
Plot(Salary, row_names)

# standard scatterplot
Plot(Salary, row_names, sort_yx="0", segments_y=FALSE)

# Cleveland dot plot with two x-variables
Plot(c(Pre, Post), row_names)

#-----
# annotations
#-----
```

```

# add text at the one location specified by x1 and x2
Plot(Years, Salary, add="Hi There", x1=12, y1=80000)
# add text at three different specified locations
Plot(Years, Salary, add="Hi", x1=c(12, 16, 18), y1=c(80000, 100000, 60000))

# add three different text blocks at three different specified locations
Plot(Years, Salary, add=c("Hi", "Bye", "Wow"), x1=c(12, 16, 18),
      y1=c(80000, 100000, 60000))

# add an 0.95 data ellipse and horizontal and vertical lines through the
# respective means
Plot(Years, Salary, ellipse=0.95, add=c("v_line", "h_line"),
      x1="mean_x", y1="mean_y")
# can be done also with the following short-hand
Plot(Years, Salary, ellipse=0.95, add=c("means"))

# a rectangle requires two points, four coordinates, <x1,y1> and <x2,y2>
style(add_trans=.8, add_fill="gold", add_color="gold4", add_lwd=0.5)
Plot(Years, Salary, add="rect", x1=12, y1=80000, x2=16, y2=115000)

# the first object, a rectangle, requires all four coordinates
# the vertical line at x=2 requires only an x1 coordinate, listed 2nd
Plot(Years, Salary, add=c("rect", "v_line"), x1=c(10, 2),
      y1=80000, x2=12, y2=115000)

# two different rectangles with different locations, fill colors and translucence
style(add_fill=c("gold3", "green"), add_trans=c(.8,.4))
Plot(Years, Salary, add=c("rect", "rect"),
      x1=c(10, 2), y1=c(60000, 45000), x2=c(12, 75000), y2=c(80000, 55000))

#-----
# analysis of two categorical variables (Likert data)
#-----

d <- rd("Mach4", quiet=TRUE) # Likert data, 0 to 5

# size of each plotted point (bubble) depends on its joint frequency
# triggered by default when replication of joint values and
# less than 9 unique data values for each
# n_cat=6 means treat responses as categorical for up to 6 equally-spaced
# integer values
Plot(m06, m07, n_cat=6)

# use value labels for the integer values, modify color options
LikertCats <- c("Strongly Disagree", "Disagree", "Slightly Disagree",
              "Slightly Agree", "Agree", "Strongly Agree")
style(fill="powderblue", color="blue", bubble_text="darkred")
Plot(m06, m07, value_labels=LikertCats, n_cat=6)
style() # reset theme

```



```

# proportions within each level of the other variable
Plot(m06, m07, stat="proportion", n_cat=6)

# get correlation analysis instead of cross-tab analysis
# rely upon the default value of n_cat=0 so that integer
# valued variables are analyzed as numerical
Plot(m06, m07)

#-----
# Bubble Plot Frequency Matrix
#-----
# applies to categorical variables, since Mach IV Likert items
# are 0 to 5 integer values, set n_cat to indicate the
# numeric values represent categories
Plot(c(m06,m07,m09,m10), value_labels=LikertCats, n_cat=6)

#-----
# function curve
#-----

x <- seq(10,50,by=2)
y1 <- sqrt(x)
y2 <- x**.33
# x is sorted with equal intervals so run chart by default
Plot(x, y1)

# multiple plots from variable vectors need to have the variables
# in a data frame
d <- data.frame(x, y1, y2)
# if variables are in the user workspace and in a data frame
# with the same names, the user workspace versions are used,
# which do not work with vectors of variables, so remove
rm(x); rm(y1); rm(y2)
Plot(x, c(y1, y2))

#-----
# modern art
#-----
clr <- colors() # get list of color names
color0 <- clr[sample(1:length(clr), size=1)]
clr <- clr[-(153:353)] # get rid of most of the grays

n <- sample(5:30, size=1)
x <- rnorm(n)
y <- rnorm(n)
color1 <- clr[sample(1:length(clr), size=1)]
color2 <- clr[sample(1:length(clr), size=1)]

style(window_fill=color0, color=color2)
Plot(x, y, run=TRUE, area_fill="on",
     xy_ticks=FALSE, main="Modern Art", xlab="", ylab="")

```

```
cex.main=2, col.main="lightsteelblue", n_cat=0, center_line="off")
style() # reset style to default
```

---

```
print.out
```

---

*Display a Portion of Output from a Saved List Object*

---

## Description

Displays the portions of saved results of an analysis from a `lessR` function into an object, such as for later display at the console or to be integrated into a Rmd analysis, for example from RStudio. This function is usually implicitly accessed by the user simply by entering the name of an output piece into the console or in a Rmd file, such as, such as `r$out_coefs` that results from `r` in `r <- reg(Y ~ X)`.

Now just applies to the `lessR` [Regression](#) function.

## Usage

```
## S3 method for class 'out'
print(x, ...)
```

## Arguments

<code>x</code>	The piece of output to display, a character vector or a list of character vectors.
<code>...</code>	Other parameter values_

## Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

## References

Gerbing, D. W. (2014). R Data Analysis without Programming, Chapters 9 and 10, NY: Routledge.

## See Also

[Regression](#)

## Examples

```
# read internal data set
d <- rd("Employee", quiet=TRUE)
# do the summary statistics
s <- ss.brief(Salary)
# print the piece of output, print function is implicit
s$outliers
```

---

print.out_all	<i>Display All Text Output from a Saved List Object</i>
---------------	---

---

**Description**

Displays all the results saved as an R list into an object from a lessR analysis. An example of a saved object is `r` in `r <- reg(Y ~ X)`. The results are displayed at the console or integrated into a knitr analysis, for example from RStudio. This function is usually implicitly accessed by the user simply by entering the name of the saved object at the console or in a knitr file.

**Usage**

```
## S3 method for class 'out_all'  
print(x, ...)
```

**Arguments**

<code>x</code>	The list of components to display.
<code>...</code>	Other parameter values_

**Author(s)**

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

**See Also**

[Regression](#)

**Examples**

```
# read internal data set  
d <- rd("Employee", quiet=TRUE)  
# do the summary statistics  
s <- ss_brief(Salary)  
# display all the output, print function is implicit  
s
```

---

prob_norm	<i>Compute and Plot Normal Curve Probabilities over an Interval</i>
-----------	---

---

**Description**

Calculate the probability of an interval for a normal distribution with specified mean and standard deviation, providing both the numerical probability and a plot of the interval with the corresponding normal curve.

**Usage**

```
prob_norm(lo=NULL, hi=NULL, mu=0, sigma=1, nrm_color="black",
          fill_nrm="grey91", fill_int="slategray3",
          ylab="", y_axis=FALSE, z=TRUE, axis_size=.9,
          pdf_file=NULL, width=5, height=5, ...)

prob.norm(...)
```

**Arguments**

lo	Lowest value in the interval for which to compute probability.
hi	Highest value in the interval for which to compute probability.
mu	Population mean of normal distribution.
sigma	Population standard deviation of normal distribution.
nrm_color	Color of the border of the normal curve.
fill_nrm	Fill color of the normal curve.
fill_int	Fill color of the interval for which the probability is computed.
ylab	Label for the optional vertical axis_
y_axis	If TRUE, then a vertical axis is included.
z	If TRUE, then include z-values on the horizontal-axis_ Set to FALSE if mu=0 and sigma=1.
axis_size	Magnification factor for the axis labels, the value of axis_cex.
pdf_file	Name of the pdf file to which graphics are redirected.
width	Width of the pdf file in inches.
height	Height of the pdf file in inches.
...	Other parameter values for graphics.

**Details**

Calculate the normal curve probability for the specified interval and normal curve. If there is no upper value of the interval provided, hi, then the upper tail probability is provided, that is, from the specified value until positive infinity. If there is no lower value, lo, then the lower tail probability is provided. The probability is calculated with [pnorm](#).

**Author(s)**

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

**See Also**

[pnorm](#), [plot](#).

**Examples**

```
# Mu=0, Sigma=1: Standard normal prob, values between 0 and 2
prob.norm(0,2)

# Mu=0, Sigma=1: Standard normal prob, values lower than 2
prob.norm(hi=2)

# Mu=0, Sigma=1: Standard normal prob, values larger than 2
prob.norm(lo=2)

# Mu=100, Sigma=15: Change default fill color of plotted interval
prob.norm(lo=115, hi=125, mu=100, sigma=15, fill_int="plum")
```

---

prob\_tcut

---

*Plot t-distribution Curve and Specified Cutoffs with Normal Curve*


---

**Description**

Plot a specified t-distribution against the standardized normal curve with the corresponding upper and lower tail cutoffs.

**Usage**

```
prob_tcut(df, alpha=0.05, digits_d=3, y_axis=FALSE,
          fill="aliceblue", color_tail="palevioletred4",
          nrm_color=gray(.7), color_t=gray(.08),
          pdf_file=NULL, width=5, height=5, ...)

prob.tcut(...)
```

**Arguments**

df	Degrees of freedom for t-distribution, must be 2 or larger.
alpha	Alpha to define the tail cutoff area.
digits_d	Number of decimal digits in the output.
y_axis	If FALSE, then the y axis is not displayed.
fill	Fill color for the interior of the t-distribution curve.
color_tail	Color of the tail areas of the t-distribution.
nrm_color	Color of the normal curve.
color_t	Color of the t-distribution curve.
pdf_file	Name of the pdf file to which graphics are redirected.
width	Width of the pdf file in inches.
height	Height of the pdf file in inches.
...	Other parameter values for graphics.

**Details**

Replaces a t-table by providing the corresponding t-cutoff, the critical value based on the corresponding quantile, as well as a plot that illustrates the tail probabilities. Also compare to the standardized normal curve.

**Author(s)**

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

**See Also**

[qt](#), [pnorm](#).

**Examples**

```
# t-distribution with 0.025 cutoffs for degrees of freedom of 15
prob.tcut(15)
```

---

prob\_znorm

*Plot a Normal Curve with Shaded Intervals by Standard Deviation*

---

**Description**

Display a normal curve with shading according to the z-score, the number of standard deviations from the mean.

**Usage**

```
prob_znorm(mu=0, sigma=1, color_border="gray10",
           r=.10, g=.34, b=.94, a=.20,
           xlab="", ylab="", main="",
           y_axis=FALSE, z=TRUE, axis_size=.9,
           pdf_file=NULL, width=5, height=5, ...)

prob.znorm(...)
```

**Arguments**

mu	Population mean of normal distribution.
sigma	Population standard deviation of normal distribution.
color_border	Color of the border of the normal curve.
r	Red component of fill color, from 0 to 1.
g	Green component of fill color, from 0 to 1.
b	Blue component of fill color, from 0 to 1.
a	Alpha component of fill color, that is, the transparency, from 0 to 1.

xlab	Label for the horizontal axis_
ylab	Label for the optional vertical axis_
main	Label for the graph title.
y_axis	If TRUE, then a vertical axis is included.
z	If TRUE, then include z-values on the horizontal-axis_ Set to FALSE if mu=0 and sigma=1.
axis_size	Magnification factor for the axis labels, the value of axis_cex.
pdf_file	Name of the pdf file to which graphics are redirected.
width	Width of the pdf file in inches.
height	Height of the pdf file in inches.
...	Other parameter values for graphics.

### Details

Provide a normal curve with shading of each interval defined by the number of standard deviations from the mean. The layers are written with transparency, and over-written so that the middle interval is the darkest and the most extreme intervals, beyond three standard deviations from the mean, are the lightest. Specify  $a=0$  to turn off the colors. Higher values of the alpha channel, as specified by  $a$ , yield darker colors. Specify  $a=1$  for the same solid color for all intervals.

The normal densities are calculated with `dnorm` and plotted with `plot`.

### Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

### See Also

`dnorm`, `plot`.

### Examples

```
# Mu=0, Sigma=1: Standard normal
prob.znorm()

# distribution for height of American women, mu=65.5, sigma=2.5
prob.znorm(65.5, 2.5, xlab="Height of American Women")

# do a red fill color
prob.znorm(65.5, 2.5, r=.9, xlab="Height of American Women")
```

---

Read	<i>Read Contents of a Data File with Optional Variable Labels and Feedback</i>
------	--

---

## Description

Abbreviation: `rd`, `rd_brief`, `rd_lbl`, `rd.brief` [deprecated], `Read2`

Reads the contents of the specified data file into an R data table, what R calls a data frame. By default the format of the file is detected from its filetype: comma or tab separated value text file from `.csv`, SPSS data file from `.sav`, SAS data from `.sas7bdat`, or R data file from `.rda`, and Excel file from `.xls` or `.xlsx` using Alexander Walker's [openxlsx](#) package. Specify a fixed width formatted text data file to be read with the required R `widths` option. Identify the data file by either browsing for the file on the local computer system with `Read()`, or identify the file with the first argument a character string in the form of a path name or a web URL (except for `.Rda` files which must be on the local computer system).

Any variable labels in a native SPSS or native R file are automatically included in the data file. See the `details` section below for more information. Variable labels can also be added and modified individually with the `lessR` function [label](#), and more comprehensively with the [VariableLabels](#) function.

The function provides feedback regarding the data that is read by invoking the `lessR` function [details](#). The brief form of this function invoked by default only lists the input files, the variable name table, and any variable labels.

The `lessR` function [corRead](#) reads a correlation matrix.

## Usage

```
Read(from=NULL, format=NULL, var_labels=FALSE,
     widths=NULL, stringsAsFactors=FALSE,
     missing="", n_mcut=1,
     miss_show=30, miss_zero=FALSE, miss_matrix=FALSE,
     max_lines=30, sheet=1,
     brief=TRUE, quiet=getOption("quiet"),
     fun_call=NULL, ...)

rd(...)

rd.brief(..., brief=TRUE)
rd_brief(..., brief=TRUE)
rd_lbl(..., var_labels=TRUE)

Read2(..., sep=";", dec=",")
```



**Arguments**

from	File reference, either omitted to browse for the data file, or (except for .Rda files) a full path name or web URL, included in quotes. A URL begins with <code>http://</code> .
format	Format of the data in the file, not usually specified because set by default according to the file type of the file to read: <code>.csv</code> , <code>.tsv</code> or <code>.txt</code> read as a text file, <code>.xls</code> or <code>.xlsx</code> read as an Excel file, <code>.sav</code> reads as an SPSS file, which also reads the variable labels if present, <code>.sas7bdat</code> reads as a SAS file, and <code>.rda</code> reads as a native R data file. If the data file is not identified by one of these file types, then explicitly set by setting to one of the following values: <code>"csv"</code> , <code>"tsv"</code> , <code>"Excel"</code> , <code>"R"</code> , <code>"SPSS"</code> , or <code>"SAS"</code> .
var_labels	Set TRUE if reading a csv or Excel file of variable labels into the data frame <code>l</code> in which each row consists of a variable name in the first column and the corresponding variable label in the second column, and perhaps units in the third row if using <a href="#">Regression</a> function to generate automatic markdown files of discursive text.
widths	Specifies the width of the successive columns for fixed width formatted data.
stringsAsFactors	Defaults to FALSE, so variables with at least one non-numeric data value are read as character strings instead of factors.
missing	Missing value code, which by default is literally a missing data value in the data table.
n_mcut	For the missing value analysis, list the row name and number of missing values if the number of missing exceeds or equals this cutoff.
miss_show	For the missing value analysis, the number of rows, one row per observation, that has as many or missing values as <code>n_mcut</code> .
miss_zero	For the missing value analysis, list the variable name or the row name even for values of 0, that is rows with no missing data. By default only variables and rows with missing data are listed.
miss_matrix	For the missing value analysis, if there is any missing data, list a version of the complete data table with a 0 for a non-missing value and a 1 for a missing value.
sep	Character that separates adjacent values in a text file of data.
dec	Character that serves as the decimal separator in a number.
max_lines	Maximum number of lines to list of the data and labels.
sheet	For Excel files, specifies the work sheet to read. The default is the first work sheet.
brief	If TRUE, display only variable names table plus any variable labels.
quiet	If set to TRUE, no text output. Can change the corresponding system default with <a href="#">style</a> function.
fun_call	Function call. Used with <code>Rmd</code> to pass the function call when obtained from the abbreviated function call <code>rd</code> .
...	Other parameter values define with the R read functions, such as the <code>read.table</code> function for text files, with <code>row.names</code> and <code>header</code> .

## Details

By default `Read` reads text data files which are either comma delimited, `csv`, or tab-delimited data files, native Excel files of type `.xls` or `.xlsx`, native R files with file type of `.rda`, native SAS files with file type `.sas7bdat`, and native SPSS files with file type `.sav`. Invoke the `widths` option to allow for the reading of fixed width formatted data. Calls the `lessR` function `details` to provide feedback regarding details of the data frame that was read. By default, variables defined by non-numeric variables are read as character strings. To read as factors specify `stringsAsFactors` as `FALSE`, unless all the values of a variable are non-numeric and unique, in which case the variable is classified as a character string.

### CREATE `csv` FILE

One way to create a `csv` data file is to enter the data into a text editor. A more structured method is to use a worksheet application such as MS Excel, LibreOffice Calc. Place the variable names in the first row of the worksheet. Each column of the worksheet contains the data for the corresponding variable. Each subsequent row contains the data for a specific observation, such as for a person or a company.

All numeric data in the worksheet should be displayed in the General format, so that the only non-digit character for a numeric data value is a decimal point. The General format removes all dollar signs and commas, for example, leaving only the pure number, stripped of these extra characters which R will not properly read as part of a numeric data value.

To create the `csv` file from a standard worksheet application such as Microsoft Excel or LibreOffice Calc, first convert any numeric data to general format to remove characters such as dollar signs and commas, and then under the File option, do a Save As and choose the `csv` format.

Call `help(read.table)` to view the other options that can also be implemented from `Read`.

### MECHANICS

Specify the file as with the `Read` function for reading the data into a data frame. If no arguments are passed to the function, then interactively browse for the file.

Given a `csv` data file, or tab-delimited text file, read the data into an R data frame called `d` with `Read`. Because `Read` calls the standard R function `read.csv`, which serves as a wrapper for `read.table`, the usual options that work with `read.table`, such as `row.names`, also can be passed through the call to `Read`.

### SPSS DATA

Relies upon `read.spss` from the `foreign` package. To read data in the SPSS `.sav` format. If the file has a file type of `.sav`, that is, the file specification ends in `.sav`, then the format is automatically set to `"SPSS"`. To invoke this option for a relevant data file of any file type, explicitly specify `format="SPSS"`. Any variable labels in the SPSS file are read and stored in the resulting R data table (frame). However, SPSS allows value labels for integer variables, so to preserve the variable labels in R the resulting variable is typed as a factor. To preserve the integer type, invoke the `read.spss` option use `value_labels=FALSE`.

### R DATA

Relies upon the standard R function `load`. By convention only, data files in native R format have a file type of `.rda`. To read a native R data file, if the file type is `.rda`, the format is automatically set to `"R"`. To invoke this option for a relevant data file of any file type, explicitly specify `format="R"`. Create a native R data file by saving the current data frame, usually `d`, with the `lessR` function `Write`.

### Excel DATA

Relies upon the function `read.xlsx` from Alexander Walker's `openxlsx` package. Files with a

file type of `.xlsx` are assigned a format of "Excel". The `read.xlsx` parameter `sheet` specifies the ordinal position of the worksheet in the Excel file, with a default value of 1. The `row.names` parameter can only have a value of 1. Dates stored in Excel as an Excel date type are automatically read as an R Date type.

#### lessR DATA

`lessR` has some data sets included with the package: "BodyMeas", "Cars93", "Employee", "Jackets", "Learn", "Mach4", "Reading", and "StockPrice". `Read` reads each such data set by specifying its name, such as `Read("Employee")`. No specification of format and no provided filetype, just enter the name of the data set.

#### FIXED WIDTH FORMATTED DATA

Relies upon `read.fwf`. Applies to data files in which the width of the column of data values of a variable is the same for each data value and there is no delimiter to separate adjacent data values. An example is a data file of Likert scale responses from 1 to 5 on a 50 item survey such that the data consist of 50 columns with no spaces or other delimiter to separate adjacent data values. To read this data set, invoke the `widths` option of `read.fwf`.

#### MISSING DATA

By default, `Read` provides a list of each variable and each row with the display of the number of associated missing values, indicated by the standard R missing value code `NA`. When reading the data, `Read` automatically sets any empty values as missing. Note that this is different from the R default in `read.table` in which an empty value for character string variables are treated as a regular data value. Any other valid value for any data type can be set to missing as well with the `missing` option. To mimic the standard R default for missing character values, set `missing=NA`.

To not list the variable name or row name of variables or rows without missing data, invoke the `miss_zero=FALSE` option, which can appreciably reduce the amount of output for large data sets. To view the entire data table in terms of 0's and 1's for non-missing and missing data, respectively, invoke the `miss_matrix=TRUE` option.

#### VARIABLE LABELS

Unlike standard R, `lessR` provides for variable labels, which can be provided for some or all of the variables in a data frame. Store the variable labels in a separate data frame `l`. The variable labels file that is read by `Read` consists of one row for each variable for which a variable label is provided. Each row consists of either two columns, the variable name in the first column and the associated variable label in the second column, or three columns with the third column the variable units. Use the units in conjunction for enhanced readability with the automatic markdown generated by the `Rmd` parameter for the `Regression` function. The format of the file can be `csv` or `xlsx`. The data frame `Read` constructs from this input consists of one variable, called `label`, with the variable names as row names.

The `lessR` legacy approach is to store the variable labels directly with the data in the same data frame. The problem with this approach is that any transformations of the data with any function other than `lessR` transformation functions remove the variable labels. The option for reading the variable labels with the `labels` option of `Read` statement is retained for compatibility.

Reading the data from an SPSS file, however, retains the SPSS variable labels as part of the data file. The `lessR` data analysis functions will properly process these variable labels, but any non-`lessR` data transformations will remove the labels from the data frame. To retain the labels, copy them to the `l` data frame with the `VariableLabels` function with the name of the data frame as the sole argument.

The `lessR` functions that provide analysis, such as `Histogram` for a histogram, automatically include the variable labels in their output, such as the title of a graph. Standard R functions can also use these variable labels by invoking the `lessR` function `label`, such as setting `main=label(I4)` to put the variable label for a variable named `I4` in the title of a graph.

### Value

The read data frame is returned, usually assigned the name of `d` as in the examples below. This is the default name for the data frame input into the `lessR` data analysis functions.

### Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

### References

Gerbing, D. W. (2014). *R Data Analysis without Programming*, Chapter 2, NY: Routledge.  
 Alexander Walker (2018). `openxlsx`: Read, Write and Edit XLSX Files. R package version 4.1.0.  
<https://CRAN.R-project.org/package=openxlsx>

### See Also

[read.csv](#), [read.spss](#), [read.xlsx](#), [read.fwf](#), [corRead](#), [label](#), [details](#), [VariableLabels](#).

### Examples

```
# remove the # sign before each of the following Read statements to run

# to browse for a data file on the computer system, invoke Read with
# the from argument empty
# d <- Read()
# abbreviated name
# d <- rd()
# reduced output to the console
# d <- rd.brief()

# browse for a file and then read the variable labels from
# the specified label file, here a Excel file with two columns,
# the first column of variable names and the second column the
# corresponding labels
# l <- rd.lbl("employee_lbl.xlsx")

# read a csv data file from the web
# d <- Read("http://web.pdx.edu/~gerbing/data/twogroup.csv")

# read a csv data file with -99 and XXX set to missing
# d <- Read(missing=c(-99, "XXX"))

# do not display any output
# d <- Read(quiet=TRUE)
# display full output
```

```
# d <- Read(brief=FALSE)

# read the built-in data set dataEmployee
d <- Read("Employee")

# read a data file organized by columns, with a
# 5 column ID field, 2 column Age field
# and 75 single columns of data, no spaces between columns
# name the variables with lessR function: to
# the variable names are Q01, Q02, ..., Q74, Q75
# d <- Read(widths=c(5,2,rep(1,75)), col.names=c("ID", "Age", to("Q", 75)))
```

---

Recode

*Recode the Values of an Integer or Factor Variable*


---

### Description

Abbreviation: rec

Recodes the values of one or more integer variables in a data frame. The values of the original variable may be overwritten with the recoded values, or the recoded values can be designated to be placed in a new variable, indicated by the `new.name` option. Valid values may be converted to missing, and missing values may be converted to valid values. Any existing variable labels are retained in the recoded data frame.

There is no provision to recode integer values to character strings because that task is best accomplished with the standard R `factor` function.

### Usage

```
Recode(old_vars, new_vars=NULL, old, new, data=d,
       quiet=getOption("quiet"), ...)
```

```
rec(...)
```

### Arguments

<code>old_vars</code>	One or more variables to be recoded.
<code>new_vars</code>	Name of the new variable or variables that contain the recoded values, each name in quotes. If not provided, then the values of the original variable are replaced.
<code>old</code>	The values of the variables that are to be recoded. If the value is "missing" then any existing missing values are replaced by the value specified with <code>new</code> .
<code>new</code>	The recoded values, which match one-to-one with the values in <code>old</code> . If the value is "missing" then instead any values specified in <code>old</code> are converted to missing.
<code>data</code>	The name of the data frame from which to create the subset, which is <code>d</code> by default.
<code>quiet</code>	If set to TRUE, no text output. Can change system default with <code>style</code> function.
<code>...</code>	Parameter values_

## Details

Specify the values to be recoded with the required `old` parameter, and the corresponding recoded values with the required `new` parameter. Use `new_vars` to specify the name of the variable that contains the recoded values. If `new_vars` is not present, then the values of the original variable are overwritten with the recoded values.

Not all of the existing values of the variable to be recoded need be specified. Any value not specified is unchanged in the values of the recoded variable. Unless otherwise specified, missing values are unchanged. To modify missing values, set `old="missing"` to convert missing data values to the specified value data value given in `new`. Or, set `new="missing"` to convert the one or more existing valid data values specified in `old` to missing data values.

Diagnostic checks are performed before the recode. First, it is verified that the same number of values exist in the `old` and `new` lists of values. Second, it is verified that all of the values specified to be recoded in fact exist in the original data.

If the levels of a factor were to be recoded with `Recode`, then the factor attribute would be lost as the resulting recoded variable would be character strings. Accordingly, this type of transformation is not allowed, and instead should be accomplished with the `Transform` and `factor` functions as shown in the examples.

## Value

The recoded data frame is returned, usually assigned the name of `d` as in the examples below. This is the default name for the data frame input into the `lessR` data analysis functions.

## Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

## See Also

[transform](#), [factor](#).

## Examples

```
# construct data frame
d <- read.table(text="Severity Description
1 Mild
4 Moderate
3 Moderate
2 Mild
1 Severe", header=TRUE, stringsAsFactors=FALSE)

# recode Severity into a new variable called SevereNew
d <- Recode(Severity, new_vars="SevereNew", old=1:4, new=c(10,20,30,40))

# abbreviated form, replace original with recoded
# another option, the sequence function, to generate list of values
d <- rec(Severity, old=1:4, new=seq(10,40,by=10))

# reverse score four Likert variables: m01, m02, m03, m10
```

```

d <- Read("Mach4")
d <- Recode(c(m01:m03,m10), old=0:5, new=5:0)

# convert any 1 for Plan to missing
# use Read to put data into d data frame
# write results to newdata data frame
d <- Read("Employee")
newdata <- Recode(Plan, old=1, new="missing")

# for Years and Salary convert any missing value to 99
d <- Recode(c(Years, Salary), old="missing", new=99)

# -----
# convert between factors and integers
# -----

# recode levels of a factor that should remain a factor
# with the Transform and factor functions
# using Recode destroys the factor attribute, converting to
# character strings instead, so Recode does not allow
d <- Read("Employee")
d <- Transform(
  Gender=factor(Gender, levels=c("F", "M"), labels=c("Female", "Male"))
)

# recode levels of a factor to convert to integer first by
# converting to integer with Transform and as.numeric
# here Gender has values M and F in the data
# integers start with 1 through the number of levels, can use
# Recode to change this if desired, such as to 0 and 1
d <- Transform(Gender=as.numeric(Gender))
d <- Recode(Gender, old=c(1,2), new=c(0,1))

# recode integer values to levels of a factor with value labels
# with the Transform function instead of Recode
# here Gender has values 0 and 1 in the data
d <- Read("Mach4")
d <- Transform(
  Gender=factor(Gender, levels=c(0,1), labels=c("Male","Female"))
)
# -----

```

## Description

Following a call to the `lessR` function `Regression`, in which the returned values of the function are saved into an object, allows the default plots generated by `Regression` to be accessed one at a

time\_ The specific motivation for this function is to allow custom placement of the graphs from the regression analysis from within knitr. Usually the graphics=FALSE parameter is set on the call to [Regression](#) within knitr to suppress the normal graphic output that leads to the generation of the graphs at the beginning of the knitr output.

### Usage

```
regPlot(out, type, digits_d=NULL, pred.intervals=TRUE,
        res_sort=c("cooks", "rstudent", "dffits", "off"),
        res_rows=NULL, cooks_cut=1, scatter_coef=NULL,
        pdf=FALSE, width=5, height=5, manage.gr=FALSE, ...)
```

### Arguments

out	The object returned by the lessR function <a href="#">Regression</a> .
type	Type of plot: 1 plots the scatter plot for a single predictor variable, or the scatter plot matrix for multiple predictors. If a single scatter plot, then the confidence and prediction intervals are included. 2 plots the density and histogram of residuals and 3 plots a scatter plot of the residuals with the fitted values_
digits_d	For the Basic Analysis, the number of decimal digits, set by default to at least 3 or the largest number of digits in the values of the response variable plus 1.
pred.intervals	If set to FALSE, the scatter plot for a single predictor with the response does not contain prediction and confidence intervals.
res_sort	Default is "cooks", for specifying Cook's distance as the sort criterion for the display of the rows of data and associated residuals. Other values are "rstudent" for externally Studentized residuals, "dffits" for dffits and "off" to not sort the rows of data.
res_rows	Default is 20, which lists the first 20 rows of data sorted by the specified sort criterion. To disable residuals, specify a value of 0. To see the output for all observations, specify a value of "all".
cooks_cut	Cutoff value of Cook's Distance at which observations with a larger value are flagged in red and labeled in the resulting scatterplot of Residuals and Fitted Values. Default value is 1.0.
scatter_coef	Display the correlation coefficients in the upper triangle of the scatterplot matrix.
pdf	If TRUE, then graphics are written to pdf files.
width	Width of the pdf file in inches.
height	Height of the pdf file in inches.
manage.gr	Usually leave FALSE. Refers to graphic management of the lessR system.
...	Other parameter values for R function <a href="#">lm</a> which provides the core computations.

### Details

#### OVERVIEW

The ability to separate plots is particularly useful with knitr to break up the output to intersperse comments between the plots. For Plot 1, for single predictor a scatter plot with the regression



line and confidence and prediction intervals is produced. Otherwise a scatter plot matrix of all the variables in the models is obtained.

To help assess the validity of the model, Plot 2 is of the distribution of the residuals, histogram and density plots, both general and normal. Plot 3 plots the residuals against the fitted value and also identifies the points with the largest values of Cook's distance.

### Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

### References

Gerbing, D. W. (2014). R Data Analysis without Programming, Chapters 9 and 10, NY: Routledge.

### See Also

[lm](#), [Regression](#)

### Examples

```
# read internal data set
d <- rd("Reading", quiet=TRUE)
# do regression analysis, save result into out
reg.out <- reg(Reading ~ Verbal)
# The full output already contains these plots, obtained by
# entering the name of the saved object
reg.out
# Particularly for knitr it is useful to obtain the plots
# separately from the full output
# Get the scatter plot of the data with the regression line
# and prediction and confidence intervals
regPlot(reg.out, 1)

# Can use with multiple regression for the scatter plot matrix
r <- reg(Reading ~ Verbal + Absent + Income)
regPlot(r, 1, scatter_coef=TRUE)
```

---

Regression

*Regression Analysis*

---

### Description

Abbreviation: `reg`, `reg.brief`

Provides a regression analysis with extensive output, including graphics, from a single, simple function call with many default settings, each of which can be re-specified. The computations are obtained from the R function `lm` and related R regression functions. The outputs of these functions are re-arranged and collated.

By default the data exists as a data frame with the default name of `d`, or specify explicitly with the `data` option. Specify the model in the function call as an R `formula`, that is, for a basic model, the response variable followed by a tilde, followed by the list of predictor variables, each pair separated by a plus sign, such as `reg(Y ~ X1 + X2)`.

Output is generated into distinct segments by topic, organized and displayed in sequence by default. When the output is assigned to an object, such as `r` in `r <- reg(Y ~ X)`, the full or partial output can be accessed for later analysis and/or viewing. A primary such analysis is with `knitr` for dynamic report generation, run from R directly or from within RStudio. The input instructions to `knitr` are written comments and interpretation with embedded R code, called R~Markdown. Doing a `knitr` analysis is to "knit" these comments and subsequent output together so that the R output is embedded in the resulting document – either html, pdf or Word – by default with explanation and interpretation. Generate a complete R~Markdown file with filetype (`.Rmd`) from the `Rmd` option. Simply specify the option with a file name in quotes, then run the Regression analysis to create the markdown file. Open the newly created `.Rmd` file in RStudio and click the `knit` button to create a formatted document that consists of the statistical results plus interpretative comments. See the sections `arguments`, `value` and `examples` for more information.

## Usage

```
Regression(my_formula, data=d, filter=NULL, kfold=0,
           digits_d=NULL, standardize=FALSE,

           Rmd=NULL, Rmd_browser=TRUE,
           Rmd_format=c("html", "word", "pdf", "odt", "none"),
           Rmd_data=NULL,
           results=getOption("results"), explain=getOption("explain"),
           interpret=getOption("interpret"), document=getOption("document"),
           code=getOption("code"),

           text_width=120, brief=getOption("brief"), show_R=FALSE,

           res_rows=NULL, res_sort=c("cooks", "rstudent", "dffits", "off"),
           pred_rows=NULL, pred_sort=c("predint", "off"),
           subsets=NULL, cooks_cut=1,

           scatter_coef=TRUE, graphics=TRUE, scatter_3D=FALSE,

           X1_new=NULL, X2_new=NULL, X3_new=NULL, X4_new=NULL,
           X5_new=NULL, X6_new=NULL,

           quiet=getOption("quiet"),
           pdf=FALSE, width=6.5, height=6.5, refs=FALSE,
           fun_call=NULL, ...)

reg(...)

reg.brief(..., brief=TRUE)
reg_brief(..., brief=TRUE)
```

**Arguments**

<code>my_formula</code>	Standard R <a href="#">formula</a> for specifying a model. For example, for a response variable named Y and two predictor variables, X1 and X2, specify the corresponding linear model as $Y \sim X1 + X2$ .
<code>data</code>	The default name of the data frame that contains the data for analysis is <code>d</code> , otherwise explicitly specify. If knitting and rendering the generated R~Markdown for an interpretative output as specified by the <code>Rmd</code> parameter, then this data frame must first be read by the <code>lessR</code> function <a href="#">Read</a> .
<code>filter</code>	A logical expression that specifies a subset of rows of the data frame to analyze.
<code>kfold</code>	Number of K-fold cross-validations.
<code>digits_d</code>	For the Basic Analysis, it provides the number of decimal digits, set by default to at least 2 or the largest number of digits in the values of the response variable plus 1.
<code>standardize</code>	Standardize each of the variables in the regression model before conducting the analysis.
<code>Rmd</code>	File name for the automatically generated R Markdown file, if specified. The file type is <code>.Rmd</code> , a simple text file that can be edited with any text editor, including RStudio to generate custom output.
<code>Rmd_browser</code>	If <code>html</code> format for Rmd rendering, then automatically open output in a browser.
<code>Rmd_format</code>	Format of one or more rendered R Markdown file formats, expressed in any combination of uppercase and lowercase letters. Default is <code>"html"</code> , with a browser view automatic, or <code>"word"</code> , <code>"odt"</code> , <code>"pdf"</code> (if LaTeX is available), or <code>"none"</code> . Requires <code>pandoc</code> installed, such as from RStudio.
<code>Rmd_data</code>	The default file reference of the data file when running the generated R Markdown file is the last data file as read by <a href="#">Read</a> (with the unabbreviated version of the function name). To refer to a different file to read specify the path name or web URL of the file.
<code>results</code>	By default TRUE. If set to FALSE the results are not provided in the R Markdown document, relying upon the interpretations. Can set globally with <code>style(results=FALSE)</code> .
<code>explain</code>	By default TRUE. If set to FALSE the explanations are not provided in the R Markdown document. Can set globally with <code>style(explain=FALSE)</code> .
<code>interpret</code>	By default TRUE. If set to FALSE the interpretations of the results are not provided in the R Markdown document. Can set globally with <code>style(interpret=FALSE)</code> .
<code>document</code>	By default TRUE. If set to FALSE the R documentation is not provided in the R Markdown file. Can set globally with <code>style(document=FALSE)</code> .
<code>code</code>	By default TRUE. If set to FALSE the R code that generates the results is not provided in the R Markdown file. Can set globally with <code>style(code=FALSE)</code> .
<code>text_width</code>	Width of the text output at the console.
<code>brief</code>	If set to TRUE, reduced text output. Can change system default with <a href="#">style</a> function.

show_R	Display the R instructions that yielded the lessR output, albeit without the additional formatting of the results such as combining output of different functions into a table.
res_rows	Default is 20, which lists the first 20 rows of data sorted by the specified sort criterion. To disable residuals, specify a value of 0. To see the output for all observations, specify a value of "all".
res_sort	Default is "cooks", for specifying Cook's distance as the sort criterion for the display of the rows of data and associated residuals. Other values are "rstudent" for externally Studentized residuals, "dffits" for dffits and "off" to not sort the rows of data.
pred_rows	Default is 3, which lists prediction intervals only for the first, middle and last 3 rows of data, unless there are 25 or less rows of data when all rows are displayed. To disable prediction intervals, specify a value of 0. To see the output for rows of data, specify a value of "all".
pred_sort	Default is "predint", which sorts the rows of data and associated intervals by the lower bound of each prediction interval. Turn off this sort by specifying a value of "off".
subsets	Default is to produce the analysis of the fit based on adjusted R-squared for all possible model subsets of size 10 for each number of predictors, from the leaps package. Set to FALSE to turn off. Defaults lists a maximum of the first 50 values. Specify an integer to change the maximum.
cooks_cut	Cutoff value of Cook's Distance at which observations with a larger value are flagged in red and labeled in the resulting scatterplot of Residuals and Fitted Values. Default value is 1.0.
scatter_coef	Display the correlation coefficients in the upper triangle of the scatterplot matrix.
graphics	Produce graphics. Default is TRUE. In knitr can be useful to set to FALSE so that <code>regPlot</code> can be used to place the graphics within the output file.
scatter_3D	De-activated because car package no longer linked, but if set to TRUE, directions are provided to use the car <code>scatter3d</code> function directly.
X1_new	Values of the first listed numeric predictor variable for which forecasted values and corresponding prediction intervals are calculated.
X2_new	Values of the second listed numeric predictor variable for which forecasted values and corresponding prediction intervals are calculated.
X3_new	Values of the third listed numeric predictor variable for which forecasted values and corresponding prediction intervals are calculated.
X4_new	Values of the fourth listed numeric predictor variable for which forecasted values and corresponding prediction intervals are calculated.
X5_new	Values of the fifth listed numeric predictor variable for which forecasted values and corresponding prediction intervals are calculated.
X6_new	Values of the sixth listed numeric predictor variable for which forecasted values and corresponding prediction intervals are calculated.

quiet	If set to TRUE, no text output. Can change system default with <a href="#">style</a> function.
pdf	If TRUE, then graphics are written to pdf files.
width	Width of the pdf file in inches.
height	Height of the pdf file in inches.
refs	If TRUE, then list the references for R and the packages used from which functions were used to generate the output.
fun_call	Function call. Used internally with <code>knitr</code> to pass the function call when obtained from the abbreviated function call <code>reg</code> . Not usually invoked by the user.
...	Other parameter values for R function <code>lm</code> which provides the core computations.

## Details

### OVERVIEW

The purpose of Regression is to combine the following function calls into one, as well as provide ancillary analyses such as graphics, organizing output into tables and sorting to assist interpretation of the output, as well as generate R Markdown to run through `knitr`, such as with `RStudio`, to provide extensive interpretative output.

The basic analysis successively invokes several standard R functions beginning with the standard R function for estimation of a linear model, `lm`. The output of the analysis of `lm` is stored in the object `lm.out`, available for further analysis in the R environment upon completion of the Regression function. By default `reg` automatically provides the analyses from the standard R functions, `summary`, `confint` and `anova`, with some of the standard output modified and enhanced. The correlation matrix of the model variables is obtained with `cor` function. The residual analysis invokes `fitted`, `resid`, `rstudent`, and `cooks.distance` functions. The option for prediction intervals calls the standard R function `predict`, once with the argument `interval="confidence"` and once with `interval="prediction"`. The `lessR Density` function provides the histogram and density plots for the residuals and the `ScatterPlot` function provides the scatter plots of the residuals with the fitted values and of the data for the one-predictor model. The `pairs` function provides the scatterplot matrix of all the variables in the model. Thomas Lumley's `leaps` package contains the `leaps` function that provides the analysis of the fit of all possible model subsets.

### INPUT DATA FRAME

The name `d` is by default provided by the `Read` function included in this package for reading and displaying information about the data in preparation for analysis. If all the variables in the model are not in the same data frame, the analysis will not complete. Specify the name of the data frame for analysis with the `data` option if the name is not the default `d`.

The `filter` parameter subsets rows (cases) of the input data frame according to a logical expression. Use the standard R operators for logical statements as described in [Logic](#) such as `&` for and, `|` for or and `!` for not, and use the standard R relational operators as described in [Comparison](#) such as `==` for logical equality `!=` for not equals, and `>` for greater than. See the Examples.

### TEXT OUTPUT

The output is produced in pieces by topic (see values below), automatically collated by default in the final output. But the pieces are available for later reference if the output of the function is directed toward an object, such as `r` in `r<-reg(Y~X)`. This is especially useful if the pieces are accessed within `knitr` or individual pieces are displayed at the console.

The text output is organized to provide the most relevant information while at the same time minimizing the total amount of output, particularly for analyses with large numbers of observations

(rows of data), the display of which is by default restricted to only the most interesting or representative observations in the analyses of the residuals and predicted values. Additional economy can be obtained by invoking the `brief=TRUE` option, or run `reg_brief`, which limits the analysis to just the basic analysis of the estimated coefficients and fit, and if `X1_new`, etc. are requested, the relevant rows of forecasted values: `w` .

### R MARKDOWN

An R~Markdown file ready for knitting and rendering into one of several formats can be obtained by specifying a value for `Rmd`. For the specified file name, the directory to which the file is written is displayed on the console text output, and the file type `.Rmd` is automatically appended to the specified name if it is not included in the specification.

To access the same data file for the regression analysis from running Regression from the R console, and that accomplished by knitting the generated R~Markdown, first read the data into R with the `lessR Read` function. That function stores the name of the last data file read so that it can be accessed via R as the markdown is knit and then rendered into the specified format. The default rendering is to HTML, but other formats can be specified with `Rmd_format`.

The output from `Rmd` is conceptually partitioned into five parts: results, explanations of the results, interpretations of the results, documentation of the code, and the code itself. By default all available output is generated but the flags `results`, `explain`, `interpret`, `document`, `code` can be set to `FALSE` to reduce the output. The options can be specified in a specific function all or set globally, such as with `options(explain=FALSE)`. Turning off all five flags leaves just the outline of the potential output and a bare minimum of results.

Both any existing variable labels and variable units are included in the output to the R~Markdown file. Any variable units set as a dollar, are set as USD dollars and cents in the output, displayed with a `\$`.

The default analysis provides as text output to the console the model's parameter estimates and corresponding hypothesis tests and confidence intervals, goodness of fit indices, the ANOVA table, correlation matrix of the model's variables, analysis of residuals and influence as well as the confidence and prediction intervals for each observation in the model. Also provided, for multiple regression models, collinearity analysis of the predictor variables and adjusted R-squared for the corresponding models defined by each possible subset of the predictor variables.

### DECIMAL DIGITS

The number of decimal digits displayed on the output is, by default, the maximum number of decimal digits for all the data values of the response variable. Or, this value can be explicitly specified with the `digits_d` parameter.

### GRAPHICS OUTPUT

Three default graphs are provided. When running R by itself, by default the graphs are written to separate graphics windows (which may overlap each other completely, in which case move the top graphics windows). Or, the `pdf` option may be invoked to save the graphs to a single pdf file called `regOut.pdf`. Within RStudio the graphs are successively written to the Plots window. Within `knitr` from RStudio the graphics will all appear by default at the beginning of the output. Or set to `graphics=FALSE`, and generate them individually with the accompanying function `regPlot` at the desired location within the file.

1. A histogram of the residuals includes the superimposed normal and general density plots from the `Density` function included in this `lessR` package. The overlapping density plots, which both overlap the histogram, are filled with semi-transparent colors to enhance readability.

2. A scatterplot of the residuals with the fitted values is also provided from the `ScatterPlot` function included in this package. The point corresponding to the largest value of Cook's distance, regardless of its size, is plotted in red and labeled and the corresponding value of Cook's distance specified in the subtitle of the plot. Also by default all points with a Cook's distance value larger than 1.0 are plotted in red, a value that can be specified to any arbitrary value with the `cooks_cut` option. This scatterplot also includes the `lowess` curve.

3. For models with a single predictor variable, a scatterplot of the data is produced, which also includes the regression line and corresponding confidence and prediction intervals. As with the density histogram plot of the residuals and the scatterplot of the fitted values and residuals, the scatterplot includes a colored background with grid lines. For multiple regression models, a scatterplot matrix of the variables in the model with the `lowess` best-fit line of each constituent scatterplot is produced. If the `scatter_coef` option is invoked, each scatterplot in the upper-diagonal of the correlation matrix is replaced with its correlation coefficient.

#### RESIDUAL ANALYSIS

By default the residual analysis lists the data and fitted value for each observation as well as the residual, Studentized residual, Cook's distance and `dfits`, with the first 20 observations listed and sorted by Cook's distance. The `res_sort` option provides for sorting by the Studentized residuals or not sorting at all. The `res_rows` option provides for listing these rows of data and computed statistics for any specified number of observations (rows). To turn off the analysis of residuals, specify `res_rows=0`.

#### PREDICTION INTERVALS

The output for the confidence and prediction intervals includes a table with the data and fitted value for each observation, the lower and upper bounds for the confidence interval and the prediction interval, and the width of the prediction interval. The observations are sorted by the lower bound of each prediction interval. If there are 25 or more observations then the information for only the first three, the middle three and the last three observations is displayed. To turn off the analysis of prediction intervals, specify `pred_rows=0`, which also removes the corresponding intervals from the scatterplot produced with a model with exactly one predictor variable, yielding just the scatterplot and the regression line.

The data for the default analysis of the prediction intervals is for the values of the predictor variables for each observation, that is, for each row of the data. New values of the predictor variables can be specified for the calculation of the prediction intervals by providing values for the options `X1_new` for the values of the first listed predictor variable in the model, `X2_new` for the second listed predictor variable, and so forth for up to five predictor variables, and all predictor variables are numeric. To provide these values, use functions such as `seq` for specifying a sequence of values and `c` for specifying a vector of values. For multiple regression models, all combinations of the specified new values for all of the predictor variables are analyzed.

#### RELATIONS AMONG THE VARIABLES

By default the correlation matrix of all the variables in the model is displayed, and, for multiple regression models, collinearity analysis is provided. Also provided are the first 50 models with the largest R squared adjusted from each possible model from an analysis of all possible subsets of the predictor variables. This all subsets analysis requires the `leaps` function from the `leaps` package. These contributed packages are automatically loaded if available. To turn off the all possible sets option, set `subsets=FALSE`.

#### INVOKED R OPTIONS

The `options` function is called to turn off the stars for different significance levels (`show.signif.stars=FALSE`), to turn off scientific notation for the output (`scipen=30`), and to set the width of the text output at the

console to 120 characters. The later option can be re-specified with the `text_width` option. After Regression is finished with a normal termination, the options are re-set to their values before the Regression function began executing.

#### COLOR THEME

A color theme for all the colors can be chosen for a specific plot with the `colors` option. Or, the color theme can be changed for all subsequent graphical analysis with the `lessR` function `style`. The default color theme is `lightbronze`, but a gray scale is available by removing the bronze background, such as with `style(window_fill="white")` or with `"gray"`. Other themes are available as explained in `style`.

#### VARIABLE LABELS

If variable labels exist, then the corresponding variable label is by default listed as the label for the horizontal axis and on the text output. For more information, see [Read](#).

### Value

The output can optionally be returned and saved into an R object, otherwise it simply appears at the console. The components of this object are redesigned in `lessR` version 3.3 into (a) pieces of text that form the readable output and (b) a variety of statistics. The readable output are character strings such as tables amenable for viewing and interpretation. The statistics are numerical values amenable for further analysis, such as to be referenced in a subsequent `knitr` document. The motivation of these two types of output is to facilitate `knitr` documents, as the name of each piece, preceded by the name of the saved object followed by a `\$`, can be inserted into the `knitr` document (see examples).

#### TEXT OUTPUT

`out_background`: variables in the model, rows of data and retained  
`out_estimates`: estimated coefficients, hypothesis tests and confidence intervals  
`out_fit`: fit indices; st dev of residuals; R-sq with adj and PRESS versions  
`out_anova`: analysis of variance  
`out_cor`: correlations among all variables in the model  
`out_collinear`: collinearity analysis  
`out_subsets`: R squared adjusted for all (or many) possible subsets  
`out_residuals`: residuals  
`out_predict`: analysis of residuals and influence  
`out_ref`: references if selected on the Regression function call  
`out_Rmd`: lists the name and location of the generated Rmd file  
`out_plots`: list of plots generated if more than one  
`out_suggest`: list of suggested other analyses

Separated from the rest of the text output are the major headings, which can be not included with custom collations of the output. `out_title_bck`: BACKGROUND

`out_title_basic`: BASIC ANALYSIS

`out_title_rel`: RELATIONS AMONG THE VARIABLES

`out_title_res`: ANALYSIS OF RESIDUALS AND INFLUENCE

`out_title_pred`: FORECASTING ERROR

#### STATISTICS

`call`: function call that generated the analysis



formula: model formula that specifies the model  
 n.vars: number of variables in the model  
 n.obs: number of rows of data submitted for analysis  
 n.keep: number of rows of data retained in the analysis  
 coefficients: estimated regression coefficients  
 sterr: standard errors of the estimated coefficients  
 tvalues: t-values of the estimated coefficients for null of 0  
 pvalues: p-values from the t-tests of the estimated coefficients  
 cilb: lower bound of 95% confidence interval of estimate  
 ciub: upper bound of 95% confidence interval of estimate  
 anova\_model: model df, ss, ms, F-value and p-value  
 anova\_residual: residual df, ss and ms  
 anova\_total: total df, ss and ms  
 se: standard deviation of the residuals  
 resid\_range: 95% range of normally distributed fitted residuals  
 Rsq: R-squared  
 Rsqadj: adjusted R-squared  
 PRESS: PRESS sum of squares  
 RsqPRESS: PRESS R-squared  
 m\_se: K-fold average of the standard deviation of residuals. m\_MSE: K-fold average of the MSE.  
 m\_Rsq: K-fold average of R-squared. cor: correlation matrix of all variables in the model  
 tolerances: tolerance of each predictor variable for collinearity analysis  
 VIF: variance inflation factor for each predictor variable  
 resid.max: five largest values of the residuals on which the output is sorted  
 pred\_min\_max: Rows with the smallest and largest prediction intervals  
 residuals: residuals  
 fitted: fitted values  
 cooks.distance: Cook's distance  
 model: data retained for the analysis  
 terms: terms specified for the analysis

Although not typically needed for analysis, if the regression output is assigned to an object named, for example, `r`, then the complete contents of the object can be viewed directly with the `unclass` function, here as `unclass(r)`. Invoking the `class` function on the saved object reveals a class of `out_all`. The class of each of the text pieces of output is `out`.

### Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

### References

Lumley, T., `leaps` function from the `leaps` package.

Gerbing, D. W. (2014). *R Data Analysis without Programming*, Chapters 9 and 10, NY: Routledge.

Xie, Y. (2013). *Dynamic Documents with R and knitr*, Chapman & Hall/CRC The R Series.

**See Also**

[formula](#), [lm](#), [summary.lm](#), [anova](#), [confint](#), [fitted](#), [resid](#), [rstudent](#), [cooks.distance](#), [Nest](#), [regPlot](#)

**Examples**

```
# read internal data set
d <- rd("Reading", quiet=TRUE)
# do not need all this data, so take only 30% to reduce CPU time
d <- Subset(random=.3)

# one-predictor regression
# Provide all default analyses including scatterplot etc.
# Can abbreviate Regression with reg
Regression(Reading ~ Verbal)
# Provide only the brief analysis on standardized variables
# with 3-fold cross-validations
reg_brief(Reading ~ Verbal, standardize=TRUE, kfold=3)

# Access the pieces of output, here in an object named \code{r}
r <- reg(Reading ~ Verbal + Absent + Income)
# Display all output at the console in the standard sequence
r
# list the names of all the saved components
names(r)
# Display just the estimated coefficients and their inferential analysis
r$out_estimates

# Generate an R markdown file with the option: Rmd
# Output file here will be read.Rmd, a simple text file that can
# be edited with any text editor including RStudio from which it
# can be knit to generate dynamic output to a Word document,
# pdf file or html file, as well as automatically rendered
# Here knit into an html file, but do not display
#reg(Reading ~ Verbal + Absent, Rmd="read", Rmd_browser=FALSE)

# generate interpretative R markdown file and render Word and odt
#reg(Reading ~ Verbal + Absent, Rmd="eg", Rmd_format=c("word", "odt"))

# just for incomes > 100000 and less than 5 days absent
Regression(Reading ~ Verbal, filter=(Income > 100 & Absent < 5))

# Multiple regression model
# Save the three output plots as pdf files 4 inches square
#Regression(Reading ~ Verbal + Absent + Income, pdf=TRUE,
# width=4, height=4)

# Compare nested models
# Reduced model: Reading ~ Verbal
# Full model: Reading ~ Verbal + Income + Absent
```

```
Nest(Reading, Verbal, c(Income, Absent))

# Specify new values of the predictor variables to calculate
# forecasted values and the corresponding prediction intervals
# Specify an input data frame other than d, see help(mtcars)
Regression(mpg ~ hp + wt, data=mtcars,
  X1_new=seq(50,350,50), X2_new=c(2,3))

# Indicator (dummy) variable
#d <- Read("Employee", quiet=TRUE)
#reg(Salary ~ Dept)
```

---

showColors

*Display All Named R Colors and Corresponding rgb Values*

---

## Description

For each specified color, displays the color, the name and the associated rgb definition.

## Usage

```
showColors(file="colors.pdf", color=NULL)
```

## Arguments

file	Name of pdf file that contains the list of colors with a default of colors.pdf.
color	NULL for all colors, otherwise specify a color and all colors which include that color as part of their name are displayed.

## Details

Every color name is defined in terms of a red, a green and a blue component. This function lists the rgb definitions for the specified colors, as well as the name and a display of each color. The output should be routed to an external pdf file for storage. The directory and file name of the output file are displayed.

## Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

## Examples

```
# all colors
#showColors()

# all colors with 'blue' in their name
#showColors(file="theblues.pdf", color="blue")
```

---

showPalettes	<i>Display Color Palettes</i>
--------------	-------------------------------

---

**Description**

For each specified set of palettes display each in the set.

**Usage**

```
showPalettes(palette="hcl", n=12, border="transparent", file=NULL)
```

**Arguments**

palette	Name of the palette.
n	Number of colors per palette with a default of 12.
border	Border between intervals. By default is off.
file	Name of pdf file that contains the list of colors with a default of the name of the palette. Default is name of palette with a .pdf filetype.

**Details**

Available palettes are "hcl" for sequential palettes for each of 12 hues across the hcl color wheel in 30 degree intervals plus the qualitative scale of different hues and grayscale, "viridis", and "wesanderson".

**Author(s)**

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

**Examples**

```
# all hcl palettes based on each hue from 30 degrees of the color wheel,  
# including "colors" and "grays"  
# default is 12 colors per palette  
#showPalettes()  
  
# viridis palate, simulate continuity  
#showPalettes("viridis", n=500, border="off")
```

**Description**

Show a sequence of confidence intervals, all calculated from repeated samples of simulated data from the same normal population, and show which intervals contain the true population mean.

**Usage**

```
simCImean(ns, n, mu=0, sigma=1, cl=0.95,
          ylim_bound=NULL, show_data=FALSE, show_title=TRUE,
          miss_only=FALSE, color_hit="gray40", color_miss="red",
          grid="grey90", pause=FALSE,
          main=NULL, pdf_file=NULL, width=5, height=5, ...)
```

**Arguments**

ns	Number of samples, that is, repetitions of the experiment.
n	Size of each sample.
mu	Population mean.
sigma	Population standard deviation.
cl	Confidence level.
ylim_bound	Specify the maximum deviation of the mean in either direction for the extent of the vertical axis_
show_data	Plot the data for each sample as well as the confidence interval.
show_title	Place a title on the graph that contains the parameter values_
miss_only	For the text output, only display information for samples that missed the mean.
color_hit	Color of the confidence intervals that contains the mean.
color_miss	Color of the confidence intervals that miss the mean.
grid	Color of the grid lines.
pause	Build the graph and the text output confidence interval by confidence interval.
main	Title of graph.
pdf_file	Name of the pdf file to which graphics are redirected.
width	Width of the pdf file in inches.
height	Height of the pdf file in inches.
...	Other parameter values, possibly invalid.

**Details**

Simulate random normal data and display the resulting confidence intervals.

**Author(s)**

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

**Examples**

```
# 25 confidence intervals with a sample size each of 100
# mu=0, sigma=1, that is, sample from the standard normal
simCImean(25, 100)

# 25 confidence intervals with a sample size each of 100
# mu=100, sigma=15
# pause after each interval and show the data
simCImean(25, 100, mu=100, sigma=15, show_data=TRUE)
```

---

 simCLT

---

*Pedagogical Simulation for the Central Limit Theorem*


---

**Description**

Show the distribution of sample means and relevant summary statistics, such as the 95% range of variation. Provide a plot of both the specified population and the corresponding distribution of sample means.

**Usage**

```
simCLT(ns, n, p1=0, p2=1,
       type=c("normal", "uniform", "lognormal", "antinormal"),
       fill="lightsteelblue3", n_display=2, digits_d=3,
       subtitle=TRUE, pop=TRUE,
       main=NULL, pdf=FALSE, width=5, height=5, ...)
```

**Arguments**

ns	Number of samples, that is, repetitions of the experiment.
n	Size of each sample.
p1	First parameter value for the population distribution, the mean, minimum or meanlog for the normal, uniform and lognormal populations, respectively. Must be 0, the minimum, for the anti-normal distribution.
p2	Second parameter value for the population distribution, the standard deviation, maximum or sdlog for the normal, uniform and lognormal populations, respectively. Is the maximum for the anti-normal, usually left at the default value of 1.
type	The general population distribution.
fill	Fill color of the graphs.
n_display	Number of samples for which to display the sample mean and data values_

digits_d	Number of decimal digits to display on the output.
subtitle	If TRUE, then display the specific parameter values of the population or sample, depending on the graph.
pop	If TRUE, then display the graph of the population from which the data are sampled.
main	Title of graph.
pdf	Indicator as to if the graphic files should be saved as pdf files instead of directed to the standard graphics windows.
width	Width of the pdf file in inches.
height	Height of the pdf file in inches.
...	Other parameter values for R function <code>lm</code> which provides the core computations.

### Details

Provide a plot of both the specified population and the corresponding distribution of sample means. Include descriptive statistics including the 95% range of sampling variation in raw units and standard errors for comparison to the normal distribution. Also provide a few samples of the data and corresponding means.

Four different populations are provided: normal, uniform, lognormal for a skewed distribution, and what is called the anti-normal, the combining of two side-by-side triangular distributions so that most of the values are in the extremes and fewer values are close to the middle.

For the lognormal distribution, increase the skew by increasing the value of `p2`, which is the population standard deviation.

The anti-normal distribution requires the `triangle` package. No population mean and standard deviation are provided for the anti-normal distribution, so the 95% range of sampling variable of the sample mean in terms of standard errors is not provided. \*\* Not activated until the `triangle` package is updated. \*\*

If the two plots, of the population and sample distributions respectively, are written to pdf files, according to `pdf=TRUE`, they are named `SimPopulation.pdf` and `SimSample.pdf`. Their names and the directory to which they are written are provided as part the console output.

### Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

### Examples

```
# plot of the standardized normal
# and corresponding sampling distribution with 10000 samples
# each of size 2
simCLT(ns=1000, n=2)

# plot of the uniform dist from 0 to 4
# and corresponding sampling distribution with 10000 samples
# each of size 2
simCLT(ns=1000, n=2, p1=0, p2=4, type="uniform", bin_width=0.01)
```

```
# save the population and sample distributions to pdf files
# simCLT(100, 10, pdf=TRUE)
```

---

 simFlips

*Pedagogical Binomial Simulation, Coin flips*


---

### Description

Simulate a sequence of coin flips.

### Usage

```
simFlips(n, prob=.5, show_title=TRUE,
         show_flips=TRUE, grid="grey90", pause=FALSE,
         main=NULL, pdf_file=NULL, width=5, height=5, ...)
```

### Arguments

n	Size of each sample, that is, the number of trials or flips.
prob	Probability of a success on any one trial.
show_title	Place a title on the graph that contains the parameter values_
show_flips	Plot the outcome of each flips.
grid	Color of the grid lines.
pause	Build the graph and the text output confidence interval by confidence interval.
main	Title of graph.
pdf_file	Name of the pdf file to which graphics are redirected.
width	Width of the pdf file in inches.
height	Height of the pdf file in inches.
...	Other parameter values, possibly invalid.

### Details

Generate and plot successive values of a Head or a Tail using standard R [rbinom](#) function.

### Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

### Examples

```
# 10 flips of a fair coin
simFlips(10, .5)
```



---

 simMeans

*Pedagogical Simulation of Sample Means over Repeated Samples*


---

### Description

Show a sequence of sample means and data, all simulated from the same normal population. Useful for developing an intuition for developing an informal confidence interval, that is, specifying a likely range of values that contain the true population mean, but without a formal probability.

### Usage

```
simMeans(ns, n, mu=0, sigma=1, ylim_bound=NULL,
         show_title=TRUE, show_data=TRUE, max_data=10,
         grid="grey90", pause=FALSE,
         sort=NULL, set_mu=FALSE, digits_d=2,
         main=NULL, pdf_file=NULL, width=5, height=5, ...)
```

### Arguments

ns	Number of samples, that is, repetitions of the experiment.
n	Size of each sample.
mu	Population mean.
sigma	Population standard deviation.
ylim_bound	Specify the maximum deviation of the mean in either direction for the extent of the vertical axis_
show_title	Place a title on the graph that contains the parameter values_
show_data	Show the data values on the text output.
max_data	Maximum number of data values per sample on the text output.
grid	Color of the grid lines.
pause	Build the graph and the text output sample by sample.
sort	Sort the output by the means in ascending order. By default is TRUE unless se.mu or pause is TRUE
set_mu	Have the program randomly set mu and sigma, usually to guess the correct value.
digits_d	Sort the output by the means in ascending order.
main	Title of graph.
pdf_file	Name of the pdf file to which graphics are redirected.
width	Width of the pdf file in inches.
height	Height of the pdf file in inches.
...	Other parameter values, possibly invalid.

**Details**

Simulate random normal data and display the resulting sample means, both as text output and graphic output.

If `pause=TRUE`, then the true population values are not revealed as the simulation progresses. These values are saved in the user's workspace and can be revealed by entering their names at the user prompt, `mu` and `sigma`.

**Author(s)**

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

**Examples**

```
# 8 samples, each with a sample size of 10
# mu=0, sigma=1, that is, sample from the standard normal
simMeans(8, 10)

# 25 sample means with a sample size each of 100
# mu=100, sigma=15
# pause after each interval and show the data
simMeans(25, 100, mu=100, sigma=15, show_data=FALSE)
```

---

Sort

---

*Sort the Rows of a Data Frame*


---

**Description**

Abbreviation: `srt`

Sorts the values of a data frame according to the values of one or more variables contained in the data frame, or the row names. Variable types include numeric and factor variables. Factors are sorted by the ordering of their values, which, by default is alphabetical. Sorting by row names is also possible.

**Usage**

```
Sort(by, direction=NULL, data=d, quiet=getOption("quiet"), ...)
```

```
srt(...)
```

**Arguments**

<code>by</code>	One or more variables to be sorted, or just the character string <code>row.names</code> or <code>random</code> .
<code>direction</code>	Default is ascending for all variables listed in <code>by</code> . Or, specify a list of "+" for ascending and "-" for descending, one for each variable to be sorted.
<code>data</code>	The name of the data frame from which to create the subset, which is <code>d</code> by default.

quiet            If set to TRUE, no text output. Can change system default with [style](#) function.  
 ...             Parameter values\_

### Details

`Sort` sorts the rows of a data frame and lists the first five rows of the sorted data frame. Specify the values upon which to base the sort with the required by parameter. If not all sorted variables are sorted in ascending order, then also specify a sequence of "+" for ascending and "-" for descending, respectively, one for each variable to be sorted. If `row.names` or `random` is specified, then no other variables can be specified.

A list of consecutive variables can be specified using the colon notation, such as `Years:Salary` To specify a list of multiple variables, or "+" and "-" signs, or sets of variables, separate each set of variables or each sign by a comma, then invoke the R combine or `c` function. For example, if three variables are to be sorted, the first two ascending and the last descending, then specify, `direction=c("+", "+", "-")`.

`Sort` is based on the standard R function `order`, though the `Sort` function allows for the sorting of factors, whereas `order` does not.

### Value

The sorted data frame is returned, usually assigned the name of `d` as in the examples below. This is the default name for the data frame input into the `lessR` data analysis functions.

### Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

### See Also

[order](#).

### Examples

```
# construct data frame
d <- read.table(text="Severity Description
1 Mild
4 Moderate
3 Moderate
2 Mild
1 Severe", header=TRUE)

# sort the data frame called d according to Severity
#   in ascending order
d <- Sort(Severity)

# abbreviated form, replace original with sorted
d <- srt(Severity)

# sort Description in descending order, sort Severity within
#   each level of Description in ascending order
```

```

d <- Sort(c(Description, Severity), direction=c("-", "+"))

# data in a different data frame than d
data(dataEmployee)
d <- Sort(Gender, data=dataEmployee)

# sort by row names in ascending order
d <- Read("Employee")
d <- Sort(row.names)

# randomly re-shuffle the rows of data
d <- Read("Employee")
d <- Sort(random)

```

---

style

*Set the Default Color Theme and Other System Settings*


---

## Description

Deprecated Names: set, theme

The color and style attributes of each plot can be set as a general theme, or individually set from the following list of attributes. For convenience, groups of these attributes are specified to define color themes, plus style sub-themes that apply to any theme, with default values: theme="lightbronze" and sub\_theme="default". To reset to the default theme: style().

## Usage

```

style(
  theme=c("colors", "lightbronze", "dodgerblue", "darkred", "gray",
    "gold", "darkgreen", "blue", "red", "rose", "green", "purple",
    "sienna", "brown", "orange", "white"),
  sub_theme=c("default", "black", "wsj"),
  set=NULL, get=FALSE, reset=TRUE,

  window_fill=getOption("window_fill"),
  panel_fill=getOption("panel_fill"),
  panel_color=getOption("panel_color"),
  panel_lwd=getOption("panel_lwd"),
  panel_lty=getOption("panel_lty"),

  fill=NULL,
  bar_fill=getOption("bar_fill"),
  bar_fill_discrete=getOption("bar_fill_discrete"),
  bar_fill_ordered=getOption("bar_fill_ordered"),
  trans=NULL,
  trans_bar_fill=getOption("trans_bar_fill"),
  color=NULL,
  bar_color=getOption("bar_color"),

```

```
bar_color_ordered=getOption("bar_color_ordered"),
bar_color_discrete=getOption("bar_color_discrete"),

values=getOption("values"),
values_color=getOption("values_color"),
values_size=getOption("values_size"),
values_digits=getOption("values_digits"),
values_position=getOption("values_position"),

pt_fill=getOption("pt_fill"),
trans_pt_fill=getOption("trans_pt_fill"),
pt_color=getOption("pt_color"),
se_fill=getOption("se_fill"),
ellipse_fill=getOption("ellipse_fill"),
ellipse_color=getOption("ellipse_color"),
ellipse_lwd=getOption("ellipse_lwd"),
fit_color=getOption("fit_color"),
fit_lwd=getOption("fit_lwd"),
bubble_text_color=getOption("bubble_text_color"),
segment_color=getOption("segment_color"),
ID_color=getOption("ID_color"),
out_fill=getOption("out_fill"),
out_color=getOption("out_color"),
out2_fill=getOption("out2_fill"),
out2_color=getOption("out2_color"),

violin_fill=getOption("violin_fill"),
violin_color=getOption("violin_color"),
box_fill=getOption("box_fill"),
box_color=getOption("box_color"),

axis_color=getOption("axis_color"),
axis_x_color=getOption("axis_x_color"),
axis_y_color=getOption("axis_y_color"),
axis_lwd=getOption("axis_lwd"),
axis_x_lwd=getOption("axis_x_lwd"),
axis_y_lwd=getOption("axis_y_lwd"),
axis_lty=getOption("axis_lty"),
axis_x_lty=getOption("axis_x_lty"),
axis_y_lty=getOption("axis_y_lty"),
axis_cex=getOption("axis_cex"),
axis_x_cex=getOption("axis_x_cex"),
axis_y_cex=getOption("axis_y_cex"),
axis_text_color=getOption("axis_text_color"),
axis_x_text_color=getOption("axis_x_text_color"),
axis_y_text_color=getOption("axis_y_text_color"),
rotate_x=getOption("rotate_x"),
rotate_y=getOption("rotate_y"),
```

```

offset=getOption("offset"),

lab_color=getOption("lab_color"),
lab_x_color=getOption("lab_x_color"),
lab_y_color=getOption("lab_y_color"),
lab_cex=getOption("lab_cex"),
lab_x_cex=getOption("lab_x_cex"),
lab_y_cex=getOption("lab_y_cex"),
main_color=getOption("main_color"),
main_cex=getOption("main_cex"),

grid_color=getOption("grid_color"),
grid_x_color=getOption("grid_x_color"),
grid_y_color=getOption("grid_y_color"),
grid_lwd=getOption("grid_lwd"),
grid_x_lwd=getOption("grid_x_lwd"),
grid_y_lwd=getOption("grid_y_lwd"),
grid_lty=getOption("grid_lty"),
grid_x_lty=getOption("grid_x_lty"),
grid_y_lty=getOption("grid_y_lty"),

strip_fill=getOption("strip_fill"),
strip_color=getOption("strip_color"),
strip_text_color=getOption("strip_text_color"),

add_fill=getOption("add_fill"),
add_trans=getOption("add_trans"),
add_color=getOption("add_color"),
add_cex=getOption("add_cex"),
add_lwd=getOption("add_lwd"),
add_lty=getOption("add_lty"),

n_cat=getOption("n_cat"), suggest=getOption("suggest"),
quiet=getOption("quiet"), brief=getOption("brief"),

results=getOption("results"), explain=getOption("explain"),
interpret=getOption("interpret"), document=getOption("document"),
code=getOption("code"),

width=120, show=FALSE, ...)

set(...)

```

### Arguments

theme	The specified color scheme. If specified, re-sets all style attributes to the values consistent with that theme.
sub_theme	Further modification of the main themes.

set	A list of parameter values, a theme, that was previously saved, and now is read back to become the current set of parameter values_ See the examples.
get	Save the current list of parameter values, a theme, into an R object.
reset	Change one or more settings or the entire theme.
window_fill	Fill color of the entire device window.
panel_fill	Color of the plot background.
panel_color	Color of border around the plot background, the box, that encloses the plot, with a default of "black".
panel_lwd	Line width of the box around the plot.
panel_lty	Line type of the box around the plot. Acceptable values are "blank", "solid", "dashed", "dotted", "dotdash", and "longdash".
fill	Color of a filled region – bars, points and bubbles – depending on the object plotted. Can explicitly choose "grays" or "hues" , or pre-specified R color schemes "rainbow", "terrain", and "heat". Can also provide pre-defined color ranges "blues", "reds" and "greens", as well as custom colors, such as generated by <a href="#">getColor</a> s
bar_fill	Color of a filled bar, bubble or box.
bar_fill_discrete	Color of a filled bar chart bar or pie chart slice.
bar_fill_ordered	Color of a filled histogram bar.
trans	Transparency of a filled bar, rectangular region, or points from 0 (none) to 1 (complete).
trans_bar_fill	The transparency of a filled bar or rectangular region, such as a histogram bar or the box in a box plot. Value from 0 to 1, opaque to transparent.
color	Color of a line segment such as the border of bar or point. Can explicitly choose "grays" or "hues", or pre-specified R color schemes "rainbow", "terrain", and "heat". Can also provide pre-defined color ranges "blues", "reds" and "greens", as well as custom colors, such as generated by <a href="#">getColor</a> s
bar_color	Color of the border of a filled region such as a histogram bar.
bar_color_discrete	Color of the border of a filled region for values on a qualitative scale.
bar_color_ordered	Color of the border of a filled region for values on a quantitative scale, such as a histogram bar.
values	If not the default value of "off", adds the numerical results to the plot according to "%", "prop" or "input", that is, percentages, proportions, or the value from which the slices are plotted, such as tabulated counts if y is not specified, or the value of y if the plotted values are provided. If any other values parameter is specified, default is set to "%".

values_color	Color of the plotted text. Could be a vector to specify a unique color for each value. If fewer colors are specified than the number of categories, the colors are recycled.
values_size	Character expansion factor, the size, of the plotted text, for which the default value is 0.95.
values_digits	Number of decimal digits for which to display the values_ Default is 0, round to the nearest integer, for "%" and 2 for "prop".
values_position	Position of the plotted text. Default is inside the pie, or, if "label", as part of the label for each value outside of the pie.
pt_fill	Color of a filled plotted point.
trans_pt_fill	The transparency of the inner region of a plotted point. Value from 0 to 1, opaque to transparent.
pt_color	Color of a line or outline of a filled region, such as the border of a plotted point.
se_fill	Color of the fill for the standard error plot about a fit line in a scatter plot.
ellipse_fill	Color of the fill for an ellipse in a scatter plot.
ellipse_color	Color of the border for an ellipse in a scatter plot.
ellipse_lwd	Line width of the border for an ellipse in a scatter plot.
fit_color	Color of the fit line in a scatter plot.
fit_lwd	Width of fit line. By default is 2 for Windows and 1.5 for Mac.
bubble_text_color	Color of the displayed text regarding the size of a bubble, either a tabulated frequency for categorical variables, or the value of a third variable according to size.
segment_color	Color of connecting line segments when there are also plotted points, such as in a frequency polygon. Default color is color.
ID_color	Color of the text to display the ID labels.
out_fill	For a scatterplot, color of the border of potential outliers, which, for the unadjusted boxplot, are default values 1.5 IQR's beyond the lower or upper quartile.
out_color	For a scatterplot, color of potential outliers.
out2_fill	For a scatterplot, color of extreme outliers, which, for the unadjusted boxplot, are default values 3 IQR's beyond the lower or upper quartile.
out2_color	For a scatterplot, color of the border of extreme outliers.
violin_fill	Fill color for a <b>violin plot</b> .
violin_color	Border color for the violin in a violin plot.
box_fill	Fill color for a box plot.
box_color	Border color of a box in a box plot.
axis_color	Color of the axes.



<code>axis_x_color</code>	Color of the x-axis_
<code>axis_y_color</code>	Color of the y-axis_
<code>axis_lwd</code>	Line width of axes.
<code>axis_x_lwd</code>	Line width of horizontal axis_
<code>axis_y_lwd</code>	Line width of vertical axis_
<code>axis_lty</code>	Line type of axes, either "solid", "dashed", "dotted", "dotdash", "longdash", "twodash", or "blank".
<code>axis_x_lty</code>	Line type of horizontal axis_
<code>axis_y_lty</code>	Line type of vertical axis_
<code>axis_cex</code>	Scale magnification factor, which by defaults displays the axis values to be smaller than the axis labels. Provides the functionality of, and can be replaced by, the standard R <code>cex.axis</code> .
<code>axis_x_cex</code>	Scale magnification factor for the x-axis_
<code>axis_y_cex</code>	Scale magnification factor for the y-axis_
<code>axis_text_color</code>	Color of the font used to label the axis values_
<code>axis_x_text_color</code>	Color of the font used to label the x-axis values_
<code>axis_y_text_color</code>	Color of the font used to label the y-axis values_
<code>rotate_x</code>	Degrees that the x-axis values are rotated, usually to accommodate longer values, typically used in conjunction with <code>offset</code> .
<code>rotate_y</code>	Degrees that the y-axis values are rotated.
<code>offset</code>	The spacing between the axis values and the axis_ Default is 0.5. Larger values such as 1.0 are used to create space for the label when longer axis value names are rotated.
<code>lab_color</code>	Color of the axis labels.
<code>lab_x_color</code>	Color of the axis labels on the horizontal axis_
<code>lab_y_color</code>	Color of the axis labels on the vertical axis_
<code>lab_cex</code>	Size of labels for x and y axes.
<code>lab_x_cex</code>	Size of labels for x.
<code>lab_y_cex</code>	Size of labels for y.
<code>main_color</code>	Color of the title.
<code>main_cex</code>	Size of the title font.
<code>grid_color</code>	Color of the grid lines.
<code>grid_x_color</code>	Color of the grid lines for the x-axis_
<code>grid_y_color</code>	Color of the grid lines for the y-axis_
<code>grid_lwd</code>	Width of grid lines.

<code>grid_x_lwd</code>	Width of vertical grid lines, inherits from <code>grid_lwd</code> .
<code>grid_y_lwd</code>	Width of horizontal grid lines, inherits from <code>grid_lwd</code> .
<code>grid_lty</code>	Line type for grid lines: "solid", "dashed", "dotted", "dotdash", "longdash", or "twodash", or "blank".
<code>grid_x_lty</code>	Line-type of vertical grid lines, inherits from <code>grid_lty</code> .
<code>grid_y_lty</code>	Line-type of horizontal grid lines, inherits from <code>grid_lty</code> .
<code>strip_fill</code>	Fill color for the <b>strip that labels each panel</b> in a Trellis plot.
<code>strip_color</code>	Border color for the strip that labels each panel in a Trellis plot.
<code>strip_text_color</code>	Color of the label in each strip of a Trellis plot.
<code>add_fill</code>	Interior fill color of added object. Can explicitly choose "grays" or "hues", or pre-specified R color schemes "rainbow", "terrain", and "heat". Can also provide pre-defined color ranges "blues", "reds" and "greens", as well as custom colors, such as generated by <a href="#">getColor</a> s
<code>add_trans</code>	Transparency level of color or fill, which ever is applicable from 0 (opaque) to 1 (transparent).
<code>add_color</code>	Color of borders and lines of added object.
<code>add_cex</code>	Text expansion factor, relative to 1. As with the following properties, can be a vector for multiple placement or objects.
<code>add_lwd</code>	Line width of added object.
<code>add_lty</code>	Line type of added object. See <code>panel_lty</code> for types.
<code>n_cat</code>	Number of categories that specifies the largest number of unique equally-spaced values of variable of a numeric data type for which the variable will be analyzed as categorical. Applies to <a href="#">ScatterPlot</a> and <a href="#">SummaryStats</a> , and also to the functions such as <a href="#">Histogram</a> when processing multiple graphs.
<code>suggest</code>	If TRUE, then provide suggestions for alternative analyses.
<code>quiet</code>	If TRUE then some functions suppress console output.
<code>brief</code>	If set to TRUE, reduced text output.
<code>results</code>	For the R markdown file generated by the Rmd option, show the results.
<code>explain</code>	For the R markdown file generated by the Rmd option, explain the results.
<code>interpret</code>	For the R markdown file generated by the Rmd option, interpret the results.
<code>document</code>	For the R markdown file generated by the Rmd option, documents the code that generated the results.
<code>code</code>	For the R markdown file generated by the Rmd option, shows the code that generated the results.
<code>width</code>	Maximum width of each line displayed at the console, just accesses the standard R options function for width.
<code>show</code>	Option for showing all settings.
<code>...</code>	Parameter values_

## Details

### OVERVIEW

Sets the default color palette via the R `options` statement, as well as the transparency of plotted bars and points and other non-color characteristics such as the color of the grid lines. For convenience, groups of attributes are organized into themes and sub-themes. When the theme is specified, *all* options are reset to their default values. All other modifications, with individual parameters or grouped parameters as a sub-theme, are cumulative. For example, one sub-theme can be followed by another, as well as the specifications of individual attributes. Calling the function with no arguments sets to the default style.

Available themes:

```
"lightbronze" [default]
"dodgerblue" [default lessR 3.6.0 and earlier]
"darkred"
"gray"
"gold"
"darkgreen"
"blue"
"red"
"rose"
"green"
"purple"
"sienna"
"brown"
"orange"
"white"
```

The "gray" color theme is based on the colors used in Hadley Wickham's `ggplot2` package. The "lightbronze" theme, especially with the `wsj` sub-theme, is based on Jeffrey Arnold's `wsj` theme from his `ggthemes` package.

### SUB-THEMES

"black": Black background of the entire device window with translucent fill colors from the current theme. "wsj": Similar to the `wsj` theme from the `ggthemes` package, especially with the theme of "lightbronze". The y-axis is removed with though the value labels retained, the vertical grid is removed, and the horizontal grid is dotted and thicker than the default.

## Value

The current settings can optionally be saved into an R object, and then read back at a later time with the `set` function.

## Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

## References

Arnold, Jeffrey B., (2017), ggthemes: Extra Themes, Scales and Geoms for 'ggplot2'. R package version 3.4.0. <https://CRAN.R-project.org/package=ggthemes>

Wickham, Hadley, (2009), ggplot2: Elegant Graphics for Data Analysis, 2nd edition, Springer.

## See Also

[options.](#)

## Examples

```
# some data
d <- rd("Employee", quiet=TRUE)

# gold colors embedded in a black background
style("gold", sub_theme="black")
Plot(Years, Salary, size=0, ellipse=seq(.1,.9,.1))

# three ways to do gray scale
style(window_fill="white")
# 1. gray scale with a light gray background
style("gray")
# 2. gray scale with a dark, almost black, background
style("gray", sub_theme="black")
# 3. mostly black and white
style("white")

# reset style to the default "colors"
style()

# set bar fill to qualitative hcl colors
# here also turn off bar borders and set to a mild transparency
Histogram(Salary, fill="greens", color="off")
# same as
# style(bar_fill_ordered="greens", bar_color="off")
# Histogram(Salary)

# set bar fill to 6 blue colors
# for continuous band explicitly call getColors and specify n
# to obtain the full spectrum, such as for analysis of Likert
# scale responses with six possible responses per item
style(bar_fill=getColors("blues", n=6))

# adjust Trellis strip to a dark background
style(strip_fill="gray60", strip_color="gray20",
      strip_text_color=rgb(247,242,230, maxColorValue=255))
Plot(Years, Salary, by1=Gender)

# define a custom style beyond just colors
style(panel_fill="off", panel_color="off",
```

```

        window_fill=rgb(247,242,230, maxColorValue=255),
        pt_fill="black", trans=0,
        lab_color="black", axis_text_color="black",
        axis_y_color="off",
        grid_x_color="off", grid_y_color="black", grid_lty="dotted", grid_lwd=1)
hs(Salary)

# save the current theme settings into an R object without changes
# unless set to FALSE, get is always TRUE, for all calls to style
mystyle <- style(get=TRUE)
# ... bunch of changes
# then recall older settings to current theme setting
style(set=mystyle)

# create a gray-scale with a sub-theme of wsj
# save, and then at a later session read back in
grayWSJ <- style("gray", sub_theme="wsj")
# Write("grayWSJ", data=grayWSJ, format="R")
# ...
#mystyle <- Read("grayWSJ.rda") # read grayWSJ.rda
#style(set=mystyle)

# all numeric variables with 8 or less unique values and equally spaced
# intervals are analyzed as categorical variables
style(n_cat=8)

```

---

Subset

---

*Subset the Values of One or More Variables*


---

## Description

Abbreviation: subs

Based directly on the standard R [subset](#) function to only include or exclude specified rows or data, and for specified columns of data. Output provides feedback and guidance regarding the specified subset operations. Rows of data may be randomly extracted, and also with the code provided to generate a hold out validation sample created. The hold out sample is created from the original data frame, usually named `d`, so the subset data frame must be directed to a data frame with a new name or the data re-read to construct the holdout sample. Any existing variable labels are retained in the subset data frame.

## Usage

```
Subset(filter, columns, data=d, holdout=FALSE,
        random=0, quiet=getOption("quiet"), ...)
```

```
subs(...)
```

**Arguments**

filter	Specify the rows, i.e., observations, to be included or deleted, such as with a logical expression or by direct specification of the numbers of the corresponding rows of data.
columns	Specify the columns, i.e., variables, to be included or deleted.
data	The name of the data frame from which to create the subset, which is d by default.
holdout	Create a hold out sample for validation if rows is a proportion or an integer to indicate random extraction of rows of data.
random	If an integer or proportion, specifies number of rows to data to randomly extract.
quiet	If set to TRUE, no text output. Can change system default with <a href="#">style</a> function.
...	The list of variables, each of the form, <code>variable = equation</code> . Each variable can be the name of an existing variable in the data frame or a newly created variable.

**Details**

Subset creates a subset data frame based on one or more rows of data and one or more variables in the input data frame, and lists the first five rows of the revised data frame. Guidance and feedback regarding the subsets are provided by default. The first five lines of the input data frame are listed before the subset operation, followed by the first five lines of the output data frame.

The argument `filter` can be a logical expression based on values of the variables, or it can be an integer or proportion to indicate random extraction of rows. An integer specifies the number of rows to retain, and a proportion specifies the corresponding proportion, which is then rounded to an integer. If `holdout=TRUE`, then the code to create a hold out data frame with a subsequent Subset analysis is also created. Copy and run this code on the original data frame to create the hold out sample.

To indicate retaining an observation, specify at least one variable name and the value of the variable for which to retain the corresponding observations, using two equal signs to indicate the logical equality. If no rows are specified, all rows are retained. Use the base R [row.names](#) function to identify rows by their row names, as illustrated in the examples below.

To indicate retaining a variable, specify at least one variable name. To specify multiple variables, separate adjacent variables by a comma, and enclose the list within the standard R combine function, `c`. A single variable may be replaced by a range of consecutive variables indicated by a colon, which separates the first and last variables of the range. To delete a variable or variables, put a minus sign, `-`, in front of the `c`.

**Value**

The subset of the data frame is returned, usually assigned the name of `d` as in the examples below. This is the default name for the data frame input into the `lessR` data analysis functions.

**Author(s)**

David W. Gerbing (Portland State University; <[gerbing@pdx.edu](mailto:gerbing@pdx.edu)>)

**See Also**

[subset, factor.](#)

**Examples**

```
# construct data frame
d <- read.table(text="Severity Description
1 Mild
4 Moderate
3 Moderate
2 Mild
1 Severe", header=TRUE)

# only include those with a value of Moderate for Description
d <- Subset(filter=Description=="Moderate")
# use abbreviation and do not need the filter= for the first argument
d <- subs(Description=="Moderate")

# locate, that is, display only, the 2nd and 4th rows of data
Subset(row.names(d=="2" | row.names(d=="4"))

# retain only the first and fourth rows of data, store in myd
myd <- Subset(c(1,4))

# delete only the first and fourth rows of data, store in myd
myd <- Subset(-c(1,4))

# built-in data table warpbreaks has several levels of wool
# and breaks plus continuous measure tension
# retain only the A level of wool and the L level of tension,
# and the one variable breaks
d <- Subset(wool=="A" & tension=="L", columns=breaks, data=warpbreaks)

# delete Years and Salary
d <- Read("Employee", quiet=TRUE)
d <- Subset(columns=-c(Years, Salary))

# locate, display only, a specified row by its row.name
d <- Read("Employee", quiet=TRUE)
Subset(row.names(d=="Fulton, Scott")

# randomly extract 60% of the data
# generate code to create the hold out sample of the rest
d <- Read("Employee", quiet=TRUE)
mysubset <- Subset(random=.6, holdout=TRUE)
```

**Description**

Abbreviation: `ss`, `ss.brief`

Descriptive or summary statistics for a numeric variable or a factor, one at a time or for all numeric and factor variables in the data frame. For a single variable, there is also an option for summary statistics at each level of a second, usually categorical variable or factor, with a relatively few number of levels. For a numeric variable, output includes the sample mean, standard deviation, skewness, kurtosis, minimum, 1st quartile, median, third quartile and maximum, as well as the number of non-missing and missing values. For a categorical variable, the output includes the table of counts for each value of a factor, the total sample size, and the corresponding proportions.

If the provided object to analyze is a set of multiple variables, including an entire data frame, then each non-numeric variable in the data frame is analyzed and the results written to a pdf file in the current working directory. The name of each output pdf file that contains a bar chart and its path are specified in the output.

When output is assigned into an object, such as `s` in `s <- ss(Y)`, the pieces of output can be accessed for later analysis. A primary such analysis is `knitr` for dynamic report generation in which R output embedded in documents See value below.

**Usage**

```
SummaryStats(x=NULL, by=NULL, data=d, n_cat=getOption("n_cat"),
             digits_d=NULL, brief=getOption("brief"), label_max=20, ...)
```

```
ss.brief(..., brief=TRUE)
```

```
ss_brief(..., brief=TRUE)
```

```
ss(...)
```

**Arguments**

<code>x</code>	Variable(s) to analyze. Can be a single variable, either within a data frame or as a vector in the user's workspace, or multiple variables in a data frame such as designated with the <code>c</code> function, or an entire data frame. If not specified, then defaults to all variables in the specified data frame, <code>d</code> by default.
<code>by</code>	Applies to an analysis of a numeric variable, which is then analyzed at each level of the <code>by</code> variable. The variable is coerced to a factor.
<code>data</code>	Optional data frame that contains the variable of interest, default is <code>d</code> .
<code>n_cat</code>	Specifies the largest number of unique values of variable of a numeric data type for which the variable will be analyzed as a categorical. Default is off, set to 0.
<code>digits_d</code>	Specifies the number of decimal digits to display in the output.
<code>brief</code>	If set to TRUE, reduced text output. Can change system default with <code>style</code> function.
<code>label_max</code>	Maximum size of labels for the values of a variable. Not a literal maximum as preserving unique values may require a larger number of characters than specified.
<code>...</code>	Further arguments to be passed to or from methods.



## Details

### OVERVIEW

The `by` option specifies a categorical variable or factor, with a relatively few number of values called levels. The variable of interest is analyzed at each level of the factor.

The `digits_d` parameter specifies the number of decimal digits in the output. It must follow the formula specification when used with the formula version. By default the number of decimal digits displayed for the analysis of a variable is one more than the largest number of decimal digits in the data for that variable.

Reported outliers are based on the boxplot criterion. The determination of an outlier is based on the length of the box, which corresponds, but may not equal exactly, the interquartile range. A value is reported as an outlier if it is more than 1.5 box lengths away from the box.

Skewness is computed with the usual adjusted Fisher-Pearson standardized moment skewness coefficient, the version found in many commercial packages.

The `lessR` function [Read](#) reads the data from an external csv file into the data frame called `d`. To describe all of the variables in a data frame, invoke `SummaryStats(d)`, or just `SummaryStats()`, which then defaults to the former.

In the analysis of a categorical variable, if there are more than 10 levels then an abbreviated analysis is performed, only reporting the values and the associated frequencies. If all the values are unique, then the user is prompted with a note that perhaps this is actually an ID field which should be specified using the `row.names` option when reading the data.

### DATA

If the variable is in a data frame, the input data frame has the assumed name of `d`. If this data frame is named something different, then specify the name with the `data` option. Regardless of its name, the data frame need not be attached to reference the variable directly by its name, that is, no need to invoke the `d$name` notation.

To analyze each variable in the `d` data frame, use `SummaryStats()`. Or, for a data frame with a different name, insert the name between the parentheses. To analyze a subset of the variables in a data frame, specify the list with either a `:` or the `c` function, such as `m01:m03` or `c(m01,m02,m03)`.

### VARIABLE LABELS

If variable labels exist, then the corresponding variable label is by default listed as the label for the horizontal axis and on the text output. For more information, see [Read](#).

### ONLY VARIABLES ARE REFERENCED

The referenced variable in a `lessR` function can only be a variable name. This referenced variable must exist in either the referenced data frame, such as the default `d`, or in the user's workspace, more formally called the global environment. That is, expressions cannot be directly evaluated. For example:

```
> SummaryStats(rnorm(50)) # does NOT work
```

Instead, do the following:

```
> Y <- rnorm(50) # create vector Y in user workspace
> SummaryStats(Y) # directly reference Y
```

## Value

The output can optionally be saved into an R object, otherwise it simply appears in the console. Re-designed in `lessR` version 3.3 to provide two different types of components: the pieces of readable

output in character format, and a variety of statistics. The readable output are character strings such as tables amenable for reading. The statistics are numerical values amenable for further analysis. A primary motivation of these two types of output is to facilitate knitr documents, as the name of each piece can be inserted into the knitr document.

If the analysis is of a single numeric variable, the full analysis returns the following statistics: n, miss, mean, sd, skew, kurtosis, min, quartile1, median, quartile3, max, IQR. The brief analysis returns the corresponding subset of the summary statistics. If the analysis is conditioned on a by variable, then nothing is returned except the text output. The pieces of readable output are out\_stats and out\_outliers.

If the analysis is of a single categorical variable, a list is invisibly returned with two tables, the frequencies and the proportions, respectively named freq and prop. The pieces of readable output are out\_title and out\_stats.

If two categorical variables are analyzed, then for the full analysis four tables are returned as readable output, but no numerical statistics. The pieces are out\_title, out\_freq, out\_prop, out\_colsum, out\_rowsum.

Although not typically needed, if the output is assigned to an object named, for example, s, as in `s <- ss(Y)`, then the contents of the object can be viewed directly with the `unclass` function, here as `unclass(s)`.

### Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

### See Also

[summary](#), [formula](#), [boxplot](#).

### Examples

```
# -----
# one or two numeric or categorical variables
# -----

# create data frame, d, to mimic reading data with rad function
# d contains both numeric and non-numeric data
# X has two character values, Y is numeric
n <- 15
X <- sample(c("Group1","Group2"), size=n, replace=TRUE)
Y <- round(rnorm(n=n, mean=50, sd=10),3)
d <- data.frame(X,Y)
rm(X); rm(Y)

# Analyze the values of numerical Y
# Calculate n, mean, sd, skew, kurtosis, min, max, quartiles
SummaryStats(Y)
# short name
ss(Y)
# output saved for later analysis
s <- ss(Y)
```

```
# view full text output
s
# view just the outlier analysis
s$out_outliers
# list the names of all the components
names(s)

# Analyze the values of categorical X
# Calculate frequencies and proportions, totals, chi-square
SummaryStats(X)

# Only a subset of available summary statistics
ss_brief(Y)
ss_brief(X, label_max=3)

# Reference the summary stats in the object: stats
stats <- ss(Y)
my.mean <- stats$mean

# Get the summary statistics for Y at each level of X
# Specify 2 decimal digits for each statistic displayed
SummaryStats(Y, by=X, digits_d=2)

# -----
# data frame
# -----

# Analyze all variables in data frame d at once
# Any variables with a numeric data type and 4 or less
# unique values will be analyzed as a categorical variable
SummaryStats()

# Analyze all variables in data frame d at once
# Any variables with a numeric data type and 7 or less
# unique values will be analyzed as a categorical variable
SummaryStats(n_cat=7)

# analyze just a subset of a data frame
d <- Read("Employee", quiet=TRUE)
SummaryStats(c(Salary, Years))

# -----
# data frame different from default d
# -----

# variables in a data frame which is not the default d
# access the breaks variable in the R provided warpbreaks data set
# although data not attached, access the variable directly by its name
data(warpbreaks)
SummaryStats(breaks, by=wool, data=warpbreaks)
```

```

# Analyze all variables in data frame warpbreaks at once
SummaryStats(warpbreaks)

# -----
# can enter many types of data
# -----

# generate and enter integer data
X1 <- sample(1:4, size=100, replace=TRUE)
X2 <- sample(1:4, size=100, replace=TRUE)
SummaryStats(X1)
SummaryStats(X1,X2)

# generate and enter type double data
X1 <- sample(c(1,2,3,4), size=100, replace=TRUE)
X2 <- sample(c(1,2,3,4), size=100, replace=TRUE)
SummaryStats(X1)
SummaryStats(X1, by=X2)

# generate and enter character string data
# that is, without first converting to a factor
Travel <- sample(c("Bike", "Bus", "Car", "Motorcycle"), size=25, replace=TRUE)
SummaryStats(Travel)

```

---

to *Create a Sequence of Numbered Variable Names with a Common Prefix and Width*

---

## Description

Generates sequentially numbered variable names, all starting with the same prefix, usually in conjunction with reading data values into R. The advantage over the standard R function `paste0` is that it maintains equal widths of the names, such as m08 instead of m8 if some values are m10 or larger up to m99.

## Usage

```
to(prefix, until, from=1, same.size=TRUE)
```

## Arguments

prefix	Character string that begins each variable name.
until	Last name in the sequence, the one with the last number.
from	First name in the sequence, the one with the initial number.
same.size	If TRUE, pads the beginning of each number for the variable name with leading zeros so that all names are of the same width.

## Details

Some data sets, particularly those from surveys, have sequentially numbered variable names, each beginning with the same prefix, such as the first later of the name of a set of related attitude items. This function generates the string of such variable names, generally intended for use in a read statement for reading the data and then naming the variables, or for a subsequent assignment of the names with a `names`. Relies upon the R `paste` function.

## Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

## See Also

[paste](#).

## Examples

```
# generate: "m01" "m02" "m03" "m04" "m05" "m06" "m07" "m08" "m09" "m10"
to("m", 10)

# generate: "m1" "m2" "m3" "m4" "m5" "m6" "m7" "m8" "m9" "m10"
to("m",10, same.size=FALSE)
# equivalent to standard R function
paste0("m", 1:10)

# generate a 10 x 10 data frame
d <- data.frame(matrix(rnorm(100), nrow=10))
# name the variables in the data frame
names(d) <- to("m", 10)
```

---

Transform

*Transform the Values of an Integer or Factor Variable*

---

## Description

Abbreviation: `trans`

A wrapper for the base R `transform` function that defaults to the `d` data frame and provides output regarding the specified transformation(s).

## Usage

```
Transform(data=d, quiet=getOption("quiet"), ...)

trans(...)
```

**Arguments**

<code>data</code>	The name of the data frame from which to create the subset, which is <code>d</code> by default.
<code>quiet</code>	If set to <code>TRUE</code> , no text output. Can change system default with <a href="#">style</a> function.
<code>...</code>	The list of transformations, each of the form, <code>variable = equation</code> . Each <code>variable</code> can be the name of an existing variable in the data frame or a newly created variable.

**Details**

The first five rows of the data frame are listed before the transformation, and the first five values of the transformed variables are listed after the transformation. The default input data frame is `d`.

Guidance and feedback regarding the transformations are provided by default. The first five lines of the input data frame are listed before the transformation, then the specified transformations are listed, followed by the first five lines of the transformed data frame.

Multiple transformations can be defined with a single statement. Note that a newly created transformed variable cannot then be used to define another transformed variable in the same `Transform` statement. Instead, the transformed variable that depends on an earlier created transformed variable must be defined in its own `Transform` statement.

**Value**

The transformed data frame is returned, usually assigned the name of `d` as in the examples below. This is the default name for the data frame input into the `lessR` data analysis functions.

**Author(s)**

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

**See Also**

[transform](#), [factor](#).

**Examples**

```
# construct data frame
d <- read.table(text="Status Severity
1 Mild
4 Moderate
3 Moderate
2 Mild
1 Severe", header=TRUE)

# replace Status with a transformed version
d <- Transform(Status=Status-1)

# abbreviated form
d <- trans(StatusNew=Status-1)
```

```

# replace Status with a transformed version
# leave input d unmodified
# save transformed data frame to the created data frame called newdata
newdata <- Transform(Status=Status-1)

# construct data frame
# recode Status into a factor
d <- Transform(Status=factor(Status, labels=c("OK","Hurts","Painful","Yikes")))

# read lessR data set dataEmployee into data frame d
d <- Read("Employee")
# multiple transformations in one statement
# Months is a new variable
# Salary is a new version of the old Salary
# JobSat was read as non-numeric, so as a factor, but is also ordinal
# Plan was read as numeric values 0,1,2, now converted to a factor
d <- Transform(
  Months=Years*12,
  Salary=Salary/1000,
  Plan=factor(Plan,
    levels=c(0,1,2), labels=c("GoodHealth", "YellowCross", "BestCare"))
)
# new variable Months now exists
# if relevant, supply a corresponding variable label
# d <- label(Months, "Months Employed in the Company")
# confirm
db()

# -----
# transformations with factors
# -----

# transform a nominal variable to ordinal, re-order the categories
d <- Transform(JobSat=
  factor(JobSat, levels=c("low", "med", "high"), ordered=TRUE))

# recode levels of a factor that should remain a factor
# with the Transform and factor functions
# using Recode destroys the factor attribute, converting to
# character strings instead, so Recode does not allow
d <- Read("Employee")
d <- Transform(
  Gender=factor(Gender, levels=c("F", "M"), labels=c("Female", "Male"))
)

# recode levels of a factor to convert to integer first by
# converting to integer with Transform and as.numeric
# here Gender has values M and F in the data
# integers start with 1 through the number of levels, can use
# Recode to change this if desired, such as to 0 and 1
# Gender is now a factor to illustrate
d <- Transform(Gender=as.numeric(Gender))

```

```
d <- Recode(Gender, old=c(1,2), new=c(0,1))

# recode integer values to levels of a factor with value labels
# with the Transform function instead of Recode
# here Gender has values 0 and 1 in the data
d <- Read("Mach4")
d <- Transform(
  Gender=factor(Gender, levels=c(0,1), labels=c("Male","Female"))
)
# -----
```

---

tttest

*Generic Method for t-test and Standardized Mean Difference with Enhanced Graphics*


---

### Description

Abbreviation: tt, tt\_brief, tt.brief [deprecated]

Provides enhanced output from the standard `t.test` function applied to the analysis of the mean of a single variable, or the independent groups analysis of the mean difference, from either data or summary statistics. Includes the analysis of a dependent-groups analysis from the data. The data can be in the form of a data frame or separate vectors of data, one for each group. This output includes the basic descriptive statistics, analysis of assumptions and the hypothesis test and confidence interval. For two groups the output also includes the analysis for both with and without the assumption of homogeneous variances, the pooled or within-group standard deviation, and the standardized mean difference or Cohen's *d* and its confidence interval.

The output from data for two groups introduces the ODDSMD plot, which displays the Overlapping Density Distributions of the two groups as well as the means, mean difference and Standardized Mean Difference. The plot also includes the results of the descriptive and inferential analyses. For the dependent-groups analysis, a scatter plot of the two groups of data also is produced, which includes the diagonal line through the scatter plot that represents equality, and a line segment for each point in the scatter plot which is the vertical distance from the point to the diagonal line to display the amount of change.

Can also be called from the more general `model` function.

### Usage

```
tttest(x=NULL, y=NULL, data=d, filter=NULL, paired=FALSE,

      n=NULL, m=NULL, s=NULL, mu=NULL,
      n1=NULL, n2=NULL, m1=NULL, m2=NULL, s1=NULL, s2=NULL,

      Ynm="Y", Xnm="X", X1nm="Group1", X2nm="Group2", xlab=NULL,

      brief=getOption("brief"), digits_d=NULL, conf_level=0.95,
      alternative=c("two_sided", "less", "greater"),
      mmd=NULL, msmd=NULL, Edesired=NULL,
```



```
show_title=TRUE, bw1="bcv", bw2="bcv",
graph=TRUE, line_chart=FALSE,
width=5, height=5, pdf_file=NULL, ...)
```

```
tt.brief(...)
tt_brief(...)
```

```
tt(...)
```

### Arguments

x	A <a href="#">formula</a> of the form $Y \sim X$ , where Y is the numeric response variable compared across the two groups, and X is a grouping variable with two levels that define the corresponding groups, or, if the data are submitted in the form of two vectors, the responses for the first group.
y	If x is not a formula, the responses for the second group, otherwise NULL.
data	Data frame that contains the variable of interest, default is d.
filter	A logical expression that specifies a subset of rows of the data frame to analyze.
paired	Set to TRUE for a dependent-samples t-test with two data vectors or variables from a data frame, with the difference computed from subtracting the first vector from the second.
n	Sample size for one group.
m	Sample size for one group.
s	Sample size for one group.
mu	Hypothesized mean for one group. If not present, then confidence interval only.
n1	Sample size for first of two groups.
n2	Sample size for second of two groups.
m1	Sample mean for first of two groups.
m2	Sample mean for second of two groups.
s1	Sample standard deviation for first of two groups.
s2	Sample standard deviation for second of two groups.
Ynm	Name of response variable.
Xnm	Name of predictor variable, the grouping variable or factor with exactly two levels.
X1nm	Value of grouping variable, the level that defines the first group.
X2nm	Value of grouping variable, the level that defines the second group.
xlab	x-axis label, defaults to variable name, or, if present, variable label.
brief	If set to TRUE, reduced text output. Can change system default with <a href="#">style</a> function.
digits_d	Number of decimal places for which to display numeric values_ Suggestion only.

<code>conf_level</code>	Confidence level of the interval, expressed as a proportion.
<code>alternative</code>	Default is "two_sided". Other values are "less" and "greater".
<code>mmd</code>	Minimum Mean Difference of practical importance, the difference of the response variable between two group means. The concept is optional, and only one of <code>mmd</code> and <code>msmd</code> is provided.
<code>msmd</code>	For the Standardized Mean Difference, Cohen's <i>d</i> , the Minimum value of practical importance. The concept is optional, and only one of <code>mmd</code> and <code>msmd</code> is provided.
<code>Edesired</code>	The desired margin of error for the needed sample size calculation for a 95% confidence interval, based on Kupper and Hafner (1989).
<code>show_title</code>	Show the title on the graph of the density functions for two groups.
<code>bw1</code>	Bandwidth for the computation of the densities for the first group.
<code>bw2</code>	Bandwidth for the computation of the densities for the second group.
<code>graph</code>	If TRUE, then display the graph of the overlapping density distributions.
<code>line_chart</code>	Plot the run chart for the response variable for each group in the analysis.
<code>pdf_file</code>	Name of the pdf file to which the density graph is redirected. Also specifies to save the line charts with pre-assigned names if they are computed.
<code>width</code>	Width of the pdf file in inches.
<code>height</code>	Height of the pdf file in inches.
<code>...</code>	Further arguments to be passed to or from methods.

## Details

### OVERVIEW

If `n` or `n1` are set to numeric values, then the analysis proceeds from the summary statistics, the sample size and mean and standard deviation of each group. Missing data are counted and then removed for further analysis of the non-missing data values. Otherwise the analysis proceeds from data, which can be in a data frame, by default named `d`, with a grouping variable and response variable, or in two data vectors, one for each group.

Following the format and syntax of the standard `t.test` function, to specify the two-group test with a formula, `formula`, the data must include a variable that has exactly two values, a grouping variable or factor generically referred to as `X`, and a numerical response variable, generically referred to as `Y`. The formula is of the form `Y ~ X`, with the names `Y` and `X` replaced by the actual variable names specific to a particular analysis. The formula method automatically retrieves the names of the variables and data values for display on the resulting output.

The values of the response variable `Y` can be organized into two vectors, the values of `Y` for each group in its corresponding vector. When submitting data in this form, the output is enhanced if the actual names of the variables referred to generically as `X` and `Y`, as well as the names of the levels of the factor `X`, are explicitly provided.

For the output, when computed from the data the two groups are automatically arranged so that the group with the larger mean is listed as the first group. The result is that the resulting mean difference, as well as the standardized mean difference, is always non-negative.

The inferential analysis in the full version provides both homogeneity of variance and the Welch test which does not assume homogeneity of variance. Only a two-sided test is provided. The null hypothesis is a population mean difference of 0.

If computed from the data, the bandwidth parameter controls the smoothness of the estimated density curve. To obtain a smoother curve, increase the bandwidth from the default value.

#### DATA

If the input data frame is named something different than `d`, then specify the name with the `data` option. Regardless of its name, the data frame need not be attached to reference the variable directly by its name without having to invoke the `d$name` notation.

#### PRACTICAL IMPORTANCE

The practical importance of the size of the mean difference is addressed when one of two parameter values are supplied, the minimum mean difference of practical importance, `mmd`, or the corresponding standardized version, `msmd`. The remaining value is calculated and both values are added to the graph and the console output.

#### DECIMAL DIGITS

The number of decimal digits is determined by default from the largest number of decimal digits of the entered descriptive statistics. The number of decimal digits is then set at that value, plus one more with a minimum of two decimal digits by default. Or, override the default with the `digits_d` parameter.

#### VARIABLE LABELS

If variable labels exist, then the corresponding variable label is by default listed as the label for the horizontal axis and on the text output. For more information, see [Read](#).

#### PDF OUTPUT

To obtain pdf output, use the `pdf_file` option, perhaps with the optional `width` and `height` options. These files are written to the default working directory, which can be explicitly specified with the `Rsetwd` function.

### Value

Returned value is `NULL` except for a two-group analysis from a formula. Then the values for the response variable of the two groups are separated and returned invisibly as a list for further analysis as indicated in the examples below. The first group of data values is the group with the largest sample mean.

<code>value1</code>	Value of the grouping variable for the first group.
<code>group1</code>	Data values for the first group.
<code>value2</code>	Value of the grouping variable for the second group.
<code>group2</code>	Data values for the second group.

### Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

### References

- Gerbing, D. W. (2014). R Data Analysis without Programming, Chapter 8, NY: Routledge.  
 Kupper and Hafner (1989). The American Statistician, 43(2):101-105.

**See Also**

[t.test](#), [density](#), [plot.density](#), [ttestPower](#), [formula](#).

**Examples**

```
# -----
# tt for two groups, from a formula
# -----

d <- Read("Employee", quiet=TRUE)

# analyze data with formula version
# variable names and levels of X are automatically obtained from data
# although data frame not attached, reference variable names directly
ttest(Salary ~ Gender)

# short form
tt(Salary ~ Gender)

# brief version of results
tt_brief(Salary ~ Gender)

# return the vectors group1 and group2 into the object t.out
# separate the data values for the two groups and analyze separately
Y <- rnorm(100)
ttest(Y)
t.out <- ttest(Salary ~ Gender)
Histogram(group1, data=t.out)
Histogram(group2, data=t.out)

# compare to standard R function t.test
t.test(d$Salary ~ d$Gender, var.equal=TRUE)

# consider the practical importance of the difference
ttest(Salary ~ Gender, msmd=.5)

# obtain the line chart of the response variable for each group
ttest(Salary ~ Gender, line_chart=TRUE)

# variable of interest is in a data frame which is not the default d
# access the data frame in the lessR dat.twogroup data set
# although data not attached, access the variables directly by their name
data(dataLearn)
ttest(Score ~ StudyType, data=dataLearn)

# -----
# tt for a single group, from data
# -----

# confidence interval only, from data
```

```

ttest(Salary)

# confidence interval and hypothesis test, from data
ttest(Salary, mu=52000)

# just with employees with salaries less than $100,000
ttest(Salary, mu=52000, filter=(Salary < 100000))

# -----
# tt for two groups from data stored in two vectors
# -----

# create two separate vectors of response variable Y
# the vectors exist are not in a data frame
# their lengths need not be equal
Y1 <- round(rnorm(n=10, mean=50, sd=10),2)
Y2 <- round(rnorm(n=10, mean=60, sd=10),2)

# analyze the two vectors directly
# usually explicitly specify variable names and levels of X
# to enhance the readability of the output
ttest(Y1, Y2, Ynm="MyY", Xnm="MyX", X1nm="Group1", X2nm="Group2")

# dependent groups t-test from vectors in global environment
ttest(Y1, Y2, paired=TRUE)

# dependent groups t-test from variables in data frame d
d <- data.frame(Y1,Y2)
rm(Y1); rm(Y2)
ttest(Y1, Y2, paired=TRUE)
# independent groups t-test from variables (vectors) in a data frame
ttest(Y1, Y2)

# -----
# tt from summary statistics
# -----

# one group: sample size, mean and sd
# optional variable name added
tt(n=34, m=8.92, s=1.67, Ynm="Time")

# confidence interval and hypothesis test, from descriptive stats
# get rid of the data frame, analysis should still proceed
rm(d)
tt_brief(n=34, m=8.92, s=1.67, mu=9, conf_level=0.90)

# two groups: sample size, mean and sd for each group
# specify the briefer form of the output
tt_brief(n1=19, m1=9.57, s1=1.45, n2=15, m2=8.09, s2=1.59)

```

---

ttestPower

---

*Compute a Power Curve for a One or Two Group t-test*


---

## Description

Abbreviation: ttp

From one or two sample sizes, and either the within-cell (pooled) standard deviation, or one or two separate group standard deviations, generate and calibrate a power curve for either the one-sample t-test or the independent-groups t-test, as well as ancillary statistics. Uses the standard R function `power.t.test` to calculate power and then the `ScatterPlot` function in this package to automatically display the annotated power curve with colors.

For both the one and two-group t-tests, power is calculated from a single sample size and single standard deviation. For the two-sample test, the within-group standard deviation is automatically calculated from the two separate group standard deviations if not provided directly. Similarly, the harmonic mean of two separate sample sizes is calculated if two separate sample sizes are provided.

## Usage

```
ttestPower(n=NULL, s=NULL, n1=NULL, n2=NULL, s1=NULL, s2=NULL,
           mmd=NULL, msmd=NULL, mdp=.8, mu=NULL,
           pdf_file=NULL, width=5, height=5, ...)
```

```
ttp(...)
```

## Arguments

n	Sample size for each of the two groups.
s	Within-group, or pooled, standard deviation.
n1	Sample size for Group 1.
n2	Sample size for Group 2.
s1	Sample standard deviation for Group 1.
s2	Sample standard deviation for Group 2.
mmd	Minimum Mean Difference of practical importance, the difference of the response variable between two group means. The concept is optional, and only one of mmd and msmd is provided.
msmd	For the Standardized Mean Difference, Cohen's d, the Minimum value of practical importance. The concept is optional, and only one of mmd and msmd is provided.
mdp	Minimum Desired Power, the smallest value of power considered to provide sufficient power. Default is 0.8. If changed to 0 then the concept is dropped from the analysis.
mu	Hypothesized mean, of which a provided value triggers a one-sample analysis.
pdf_file	Name of the pdf file to which graphics are redirected.

width	Width of the pdf file in inches.
height	Height of the pdf file in inches.
...	Other parameter values, such as lwd and lab_cex from <a href="#">plot</a> and col.line and col.bg from <a href="#">ScatterPlot</a> .

## Details

This function relies upon the standard [power.t.test](#) function to calibrate and then calculate the power curve according to the relevant non-central t-distribution. The [Plot](#) function from this package, which in turn relies upon the standard [plot](#) function, plots the power curve. As such, parameters in [Plot](#) for controlling the different colors and other aspects of the display are also available, as are many of the more basic parameters in the usual [plot](#) function.

Also plotted, if provided, is the minimal meaningful difference, `mmd`, as well as the minimal desired power, `mdp`, provided by default. Relevant calculations regarding these values are also displayed at the console. One or both concepts can be deleted from the analysis. Not providing a value `mmd` implies that the concept will not be considered, and similarly for setting `mdp` to 0.

Invoke the function with the either the within-group (pooled) standard deviation, `s`, or the two separate group standard deviations, `s1` and `s2`, from which `s` is computed. If the separate standard deviations are provided, then also provide the sample sizes, either as a single value of `n` or as two separate sample sizes, `n1` and `n2`. If separate sample sizes `n1` and `n2` are entered, their harmonic mean serves as the value of `n`.

For power analysis of the two-sample t-test, the null hypothesis is a zero population mean difference. For a one-sample test, the null hypothesis is specified, and it is this non-null specification of  $\mu$  that triggers the one-sample analysis. Only non-directional or two-tailed tests are analyzed.

The effect size that achieves a power of 0.8 is displayed. If a minimal meaningful difference, `mmd`, is provided, then the associated power is also displayed, as well as the needed sample size to achieve a power of 0.8.

If the function is called with no parameter values, that is, as `ttp()`, then the values of `n1`, `n2` and `sw` must already exist before the function call. If they do, these values are used in the power computations.

## Author(s)

David W. Gerbing (Portland State University; <[gerbing@pdx.edu](mailto:gerbing@pdx.edu)>)

## See Also

[Plot](#), [plot](#), [power.t.test](#).

## Examples

```
# default power curve and colors
ttestPower(n=20, s=5)
# short name
ttp(n=20, s=5)

# default power curve and colors
# plus optional smallest meaningful effect to enhance the analysis
```

```
ttestPower(n=20, s=5, mmd=2)

# power curve from both group standard deviations and sample sizes
# also provide the minimum standardized mean difference of
# practical importance to obtain corresponding power
ttestPower(n1=14, n2=27, s1=4, s2=6, msmd=.5)

# power curve for one sample t-test, triggered by non-null mu
ttestPower(n=20, s=5, mu=30, mmd=2)
```

---

values

---

*List the Values of a Variable*


---

### Description

List the values of a variable from the global environment or a data frame.

### Usage

```
values(x, data=d, ...)
```

### Arguments

x	Variable for which to construct the histogram and density plots.
data	Data frame that contains the variable of interest, default is d.
...	Other parameter values for as defined processed by <a href="#">print</a> , including digits.

### Details

Provided for listing the values of a variable in an unattached data frame. All `lessR` functions that access data for analysis from a data frame, such as the default `d` provided by the [Read](#) function that reads the data frame from an external data file, do not require the data frame to be attached. Attaching a data frame can lead to some confusing issues, but one negative of not attaching is that simply listing the name of a variable within the data frame leads to an 'object not found' error. The `values` function provides access to that variable within a data frame just as is true for any other `lessR` function that accesses data.

The function displays the values of the specified variable with the standard R [print](#) function, so parameter values for [print](#) can also be passed to `values`.

### Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

### See Also

[print](#)



**Examples**

```
# generate 10 random normal data values
Y <- rnorm(10)
d <- data.frame(Y)
rm(Y)

# list the values of Y
values(Y)

# variable of interest is in a data frame which is not the default d
# access the breaks variable in the R provided warpbreaks data set
# although data not attached, access the variable directly by its name
data(warpbreaks)
values(breaks, data=warpbreaks)
```

---

VariableLabels

*Create or Display Variable Labels*


---

**Description**

Assign and/or display variable labels stored in the data frame `l`. Variable labels enhance output of analyses either as text output at the console or as graphics, such as an axis label on a graph. The variable labels can be assigned individually, or for some or all variables.

NOTE: Mostly deprecated. Can just set `var_labels=TRUE` on for a call to [Read](#) to read a file of variable labels, and assign the output to `l`. Still needed to pull labels out of data frame from an SPSS read, or to read units to generate Rmd files from [Regression](#).

**Usage**

```
VariableLabels(x, value=NULL, quiet=getOption("quiet"))
```

**Arguments**

<code>x</code>	The file reference or character string variable (see examples) from which to obtain the variable labels, or a variable name for which to assign or obtain the corresponding variable label in conjunction with the <code>value</code> parameter. Can also be a data frame from which to extract any existing variable labels.
<code>value</code>	The variable label assigned to a specific variable, otherwise NULL.
<code>quiet</code>	If set to TRUE, no text output. Can change system default with <a href="#">style</a> function.
<code>vl...</code>	

**Details**

Unlike standard R, `lessR` provides for variable labels, here stored in the data frame `l`. To read the labels from an external file, specify a file reference as the first argument of the function call. Or create a character string of variable names and labels and specify the character string as the first argument to the function call. To assign an individual variable label with this function specify the

variable name as the first argument followed by the label in quotes. Not all variables need have a label, and the variables with their corresponding labels can be listed or assigned in any order. If the `l` data frame is created or modified, the output of the function must be assigned to `l`, as shown in the following examples.

When all or some of the labels are read, either from the console or an external csv or Excel file, each line of the file contains the variable name and then the associated variable label. The file types of `.csv` and `.xlsx` in the file reference listed in the first position of the function call are what trigger the interpretation of the argument as a file reference.

For a file that contains only labels, each row of the file, including the first row, consists of the variable name, a comma if a csv file, and then the label. For the csv form of the file, this is the standard csv format such as obtained with the `csv` option from a standard worksheet application such as Microsoft Excel or LibreOffice Calc. Not all variables in the data frame that contains the data, usually `d`, need have a label, and the variables with their corresponding labels can be listed in any order. An example of this file follows for four variables, I1 through I4, and their associated labels.

I2,This instructor presents material in a clear and organized manner.

I4,Overall, this instructor was highly effective in this class.

I1,This instructor has command of the subject.

I3,This instructor relates course materials to real world situations.

If there is a comma in the variable label, then the label needs to be enclosed in quotes.

The `lessR` functions that provide analysis, such as [Histogram](#) for a histogram, automatically include the variable labels in their output, such as the title of a graph. Standard R functions can also use these variable labels by invoking the `lessR` function `label`, such as setting `main=label(I4)` to put the variable label for a variable named I4 in the title of a graph.

Variable units may also be added to the third column of a variable label file. These are used for generating a better natural language text in the generation of R~Markdown files with the `Rmd` option on supporting functions such as [Regression](#). For currency (USD), indicate with unit: dollar. a

### Value

The data frame with the variable labels is returned.

### Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

### See Also

[Read](#).

### Examples

```
# read file and then variable labels from csv files
# l <- Read("http://lessRstats.com/data/employee.csv")
# l <- VariableLabels("http://lessRstats.com/data/employee_lbl.csv")
```

```
# construct and read variable labels from console
lbl <- "
Years, Years of Company Employment
Gender, Male or Female
Dept, Department Employed
Salary, Annual Salary (USD)
JobSat, JobSat with Work Environment
Plan, 1=GoodHealth 2=YellowCross 3=BestCare
"
l <- VariableLabels(lbl)
l

# add/modify a single variable label
l <- VariableLabels(Salary, "Annual Salaries in USD")
l

# list the contents of a single variable label
VariableLabels(Salary)

# display all variable labels
VariableLabels()
```

---

Write

*Write the Contents of a Data Frame to an External File*

---

## Description

Abbreviation: `wrt`, `wrt_r`, `wrt_x`

Writes the contents of the specified data frame, such as with the default `d`, to the current working directory as either the default csv data file, an Excel data table, or a native R data file of the specified data frame. If the write is for a csv file, then any variable labels are written to a second csv file with `"_lbl"` appended to the file name. Any variable labels and variable units are automatically included in a native R data file.

## Usage

```
Write(to=NULL, data=d, format=c("csv", "R", "Excel"), rowNames=NULL,
      ExcelTable=FALSE, ExcelColWidth=TRUE,
      quiet=getOption("quiet"), ...)
```

```
wrt(...)
```

```
wrt_r(..., format="R")
```

```
wrt_x(..., format="Excel")
```

**Arguments**

to	Name of the output file as a character string, that is, with quotes. If not included in the name, the file type is automatically added to the name, either <code>.csv</code> or <code>.rda</code> , depending of the value of <code>format</code> .
data	Data frame to be written as an object, that is, no quotes.
format	Format of file to be written with <code>.csv</code> as the default.
rowNames	Format of file to be written with <code>.csv</code> as the default. Set to <code>TRUE</code> by default unless writing to Excel or csv file and row names are just the integers from 1 to the number of rows.
ExcelTable	If <code>TRUE</code> , write the Excel file as an Excel table.
ExcelColWidth	On by default but calculation of column widths for large files takes more time, so option to turn off.
quiet	If set to <code>TRUE</code> , no text output. Can change system default with <code>style</code> function.
...	Other parameter values for csv files consistent with the usual <code>write.table</code> , including <code>na=""</code> to write missing data to a csv file as blanks instead of NA.

**Details**

Can specify the file name without the file type, which `Write` adds automatically, `.csv` for a comma separated values data file and `.rda` for a native R data file. The default file name is the name of the data frame to be written. The name of the file that is written, as well as the name of the working directory into which the file was written, are displayed at the console.

An Excel file is written using functions from Alexander Walker's `openxlsx` package.

`Write` is designed to work in conjunction with the function `Read` from this package, which reads a csv, fixed width format, or native SPSS or R data files into the data frame `d`. `Write` relies upon the R functions `write.csv` and `save`.

When writing the data frame in native R format, the specified name of the resulting `.rda` file is distinct from the name of the data frame as stored within R.

**Author(s)**

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

**See Also**

[Read](#), [write.csv](#), [save](#).

**Examples**

```
# create data frame called d
n <- 12
X <- sample(c("Group1", "Group2"), size=n, replace=TRUE)
Y <- rnorm(n=n, mean=50, sd=10)
d <- data.frame(X, Y)

# write the current contents of default data frame d to GoodData.csv
```

```
# Write("GoodData")
# short name
# write the default data frame d to the R data file d.rda
# wrt_r()

# write the data as an Excel data table in an Excel file
# Write("GoodData", format="Excel")
# with abbreviation
# wrt_x("GoodData")

# access the R data frame warpbreaks
# data(warpbreaks)
# write the file warpbreaks.rda
# wrt_r(data=warpbreaks)
```

---

xAnd

*Text Processing: Insert and Into a List*

---

## Description

Inserts the word and into a vector of words, each a separate character string. Primarily for internal use in text processing of knitr output. Not usually referenced by the user.

## Usage

```
xAnd(x)
```

## Arguments

x                    The set of character strings for which to insert and.

## Details

Input is a vector of character strings, output is a single character string with and inserted if needed.

## Author(s)

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

## Examples

```
xAnd(c("sky", "land", "mountains"))
```

---

`xNum`*Text Processing: Convert a Number to a Word*

---

**Description**

Converts a number to a word. Primarily for internal use in text processing of knitr output. Not usually referenced by the user.

**Usage**`xNum(x)`**Arguments**

`x` The integer to convert.

**Details**

Input is an integer, or coerced to integer after rounding. For integers from 0 to 12, output is the single English word. For values larger than 12, or negative, the integer is just converted to character format.

**Author(s)**

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

**Examples**`xNum(5)`

---

`xP`*Text Processing: Print Formatted Numbers*

---

**Description**

Prints numbers nicely formatted, with optional units. Primarily for internal use in text processing of knitr output. Not usually referenced by the user.

**Usage**`xP(x, d=NULL, unit=NULL, semi=FALSE)`

**Arguments**

x	The variable.
d	The digits.
unit	Unit of measurement for the variable.
semi	Add a semicolon before the unit to add some horizontal spacing in math mode.

**Details**

Input is numeric, output is formatted text. A special unit is "\$", which is added to the front of the number instead of as a trailing descriptor.

**Author(s)**

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

**Examples**

```
xP(12345678.9, d=2, unit="$")
xP(12345678.9, d=2, unit="lbs")
```

---

xRow	<i>Text Processing: Add the Word Row to Case Labels that Could be Numeric</i>
------	---

---

**Description**

For a vector of row names, if the names can be represented as integers the word Row is added to the beginning of each name in the vector. Primarily for internal use in text processing of knitr output. Not usually referenced by the user.

**Usage**

```
xRow(x)
```

**Arguments**

x	Vector with names for each value.
---	-----------------------------------

**Details**

Input is a vector of values, output is vector of associated row labels, perhaps with the added word Row.

**Author(s)**

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

**Examples**

```
# The word Row gets added
v <- c(2, 4, 6)
names(v) <- c("1", "2", "3")
xRow(v)

# The word Row does not get added
v <- c(2, 4, 6)
names(v) <- c("Bill", "Tulane", "Hanna")
xRow(v)
```

---

xU

*Text Processing: Capitalize First Letter of a Word*

---

**Description**

Capitalize the first letter of a word. Primarily for internal use in text processing of knitr output. Not usually referenced by the user.

**Usage**

```
xU(x)
```

**Arguments**

x                    The character string (word) for which to capitalize the first letter.

**Details**

Input is a single word. Output is the word with its first letter capitalized.

**Author(s)**

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

**Examples**

```
xU("the")
```



---

xW *Text Processing: Wrap Words to Create New Lines From a Specified Line*

---

**Description**

Split a larger line into multiple lines by wrapping words with inserted line feeds. Primarily for internal use in text processing of `kni tr` output. Not usually referenced by the user.

**Usage**

```
xW(x, w=90, indent=5)
```

**Arguments**

x	The character string to split into separate lines.
w	Maximum width of each line.
indent	Amount of spaces to indent lines after the first line.

**Details**

Input is a sentence. Output is the sentence word wrapped into multiple lines, each line up to the maximum width.

**Author(s)**

David W. Gerbing (Portland State University; <gerbing@pdx.edu>)

**Examples**

```
xW("The quick brown fox jumped over the lazy dog's back.", w=30)
```

# Index

- \*Topic **bar chart**
  - BarChart, 7
  - CountAll, 43
- \*Topic **binomial process**
  - simFlips, 152
- \*Topic **central limit theorem**
  - simCLT, 150
- \*Topic **color**
  - BarChart, 7
  - Density, 51
  - getColors, 59
  - Histogram, 67
  - PieChart, 93
  - Plot, 100
  - showColors, 147
  - showPalettes, 148
- \*Topic **confidence interval**
  - simCImean, 149
  - simMeans, 153
- \*Topic **correlation**
  - corCFA, 21
  - corEFA, 28
  - corProp, 30
  - corRead, 32
  - corReflect, 33
  - corReorder, 38
  - corScree, 41
- \*Topic **csv**
  - Correlation, 35
  - details, 56
  - label, 77
  - Read, 128
  - style, 156
  - VariableLabels, 185
  - Write, 187
- \*Topic **datasets**
  - dataBodyMeas, 44
  - dataCars93, 44
  - dataEmployee, 45
  - dataEmployee\_lbl, 46
  - dataJackets, 47
  - dataLearn, 47
  - dataMach4, 48
  - dataMach4\_lbl, 48
  - dataReading, 49
  - dataStockPrice, 50
- \*Topic **density**
  - Density, 51
- \*Topic **descriptive**
  - CountAll, 43
- \*Topic **factor analysis**
  - corCFA, 21
  - corEFA, 28
- \*Topic **grouping variable**
  - Plot, 100
- \*Topic **hcl**
  - getColors, 59
- \*Topic **help**
  - Help, 65
- \*Topic **histogram**
  - CountAll, 43
  - Density, 51
  - Histogram, 67
- \*Topic **labels**
  - label, 77
  - VariableLabels, 185
- \*Topic **line chart**
  - LineChart, 78
- \*Topic **logit**
  - Logit, 83
- \*Topic **merge**
  - Merge, 87
- \*Topic **names**
  - to, 172
- \*Topic **nested models**
  - Nest, 91
- \*Topic **pie chart**
  - PieChart, 93

- \*Topic **plot**
    - LineChart, 78
    - Plot, 100
  - \*Topic **power**
    - ttestPower, 182
  - \*Topic **print.out\_all**
    - print.out\_all, 123
  - \*Topic **print.out**
    - print.out, 122
  - \*Topic **print**
    - values, 184
  - \*Topic **probability**
    - prob\_norm, 123
    - prob\_tcut, 125
    - prob\_znorm, 126
  - \*Topic **proportionality**
    - corProp, 30
  - \*Topic **read**
    - details, 56
    - Read, 128
  - \*Topic **recode**
    - Recode, 133
  - \*Topic **regPlot**
    - regPlot, 135
  - \*Topic **regression**
    - ANOVA, 3
    - Logit, 83
    - Model, 89
    - Regression, 137
  - \*Topic **run chart**
    - LineChart, 78
  - \*Topic **scree**
    - corScree, 41
  - \*Topic **sets**
    - style, 156
  - \*Topic **smd**
    - ttest, 176
  - \*Topic **sort**
    - Sort, 154
  - \*Topic **subset**
    - Subset, 165
  - \*Topic **summary**
    - SummaryStats, 167
  - \*Topic **t-cutoff**
    - prob\_tcut, 125
  - \*Topic **t-distribution**
    - prob\_tcut, 125
  - \*Topic **t.test**
    - ttest, 176
    - ttestPower, 182
  - \*Topic **time series chart**
    - LineChart, 78
  - \*Topic **transform**
    - Transform, 173
  - \*Topic **values**
    - values, 184
  - \*Topic **write**
    - Correlation, 35
    - Write, 187
- 
- abbreviate, 14
  - ANOVA, 3, 90
  - anova, 85, 86, 90, 92, 141, 146
  - aov, 3–6
  - attach, 54, 72, 81, 96
  - av (ANOVA), 3
  - av\_brief (ANOVA), 3
  
  - BarChart, 7, 43, 112
  - barplot, 9, 12, 17
  - bc (BarChart), 7
  - BoxPlot, 112
  - BoxPlot (Plot), 100
  - boxplot, 170
  - bx (Plot), 100
  
  - c, 8, 13, 24, 34, 39, 51, 68, 72, 79, 112, 143, 155, 166, 168, 169
  - ca (CountAll), 43
  - cfa (corCFA), 21
  - chisq.test, 12, 96, 98
  - class, 6, 29, 86, 92, 145
  - Comparison, 5, 13, 54, 72, 81, 86, 96, 110, 141
  - confint, 85, 86, 90, 141, 146
  - cooks.distance, 85, 86, 90, 141, 146
  - cor, 33, 36, 141
  - cor.test, 36, 37
  - corCFA, 21, 28, 33, 37
  - corEFA, 28, 37, 41
  - corProp, 30
  - corRead, 24, 32, 128, 132
  - corReflect, 33
  - Correlation, 22, 24, 26, 29–31, 33, 34, 35, 40, 42, 115
  - corReorder, 38
  - corScree, 41
  - CountAll, 43, 67

- cov, [36, 37](#)
- cr (Correlation), [35](#)
- cr\_brief (Correlation), [35](#)
- dataBodyMeas, [44](#)
- dataCars93, [44](#)
- dataEmployee, [45](#)
- dataEmployee\_lbl, [46](#)
- dataJackets, [47](#)
- dataLearn, [47](#)
- dataMach4, [48](#)
- dataMach4\_lbl, [48, 48](#)
- dataReading, [49](#)
- dataStockPrice, [50](#)
- db (details), [56](#)
- Density, [51, 72, 141, 142](#)
- density, [53, 55, 180](#)
- details, [56, 128, 130, 132](#)
- diverge\_hcl, [61](#)
- dn (Density), [51](#)
- dnorm, [53, 55, 127](#)
- efa (corEFA), [28](#)
- factanal, [28, 29, 37, 41](#)
- factor, [103, 133, 134, 167, 174](#)
- factors, [58, 103, 110, 111](#)
- fitted, [85, 86, 90, 141, 146](#)
- formula, [4, 83, 84, 86, 89, 90, 138, 139, 146, 170, 177, 178, 180](#)
- getColor, [9, 14, 17, 59, 62, 69, 72, 74, 94, 96, 97, 103, 104, 112, 159, 162](#)
- glm, [83, 85, 86, 90, 92](#)
- hcl, [63](#)
- hclust, [40](#)
- Help, [65](#)
- help, [67](#)
- hist, [53, 55, 67, 69, 71–74, 107](#)
- Histogram, [43, 53, 57, 67, 110, 132, 162, 186](#)
- hs (Histogram), [67](#)
- interaction.plot, [5, 6](#)
- label, [57, 77, 128, 132, 186](#)
- lattice, [109](#)
- lc (LineChart), [78](#)
- legend, [10, 12, 14, 17](#)
- LineChart, [78](#)
- lm, [4, 90, 92, 136, 137, 141, 146, 151](#)
- loess, [115](#)
- Logic, [5, 13, 54, 72, 81, 85, 96, 110, 141](#)
- Logit, [83, 90](#)
- lowess, [143](#)
- lr (Logit), [83](#)
- Merge, [87](#)
- merge, [87–89](#)
- Model, [89](#)
- model, [83, 176](#)
- model (Model), [89](#)
- model\_brief (Model), [89](#)
- mrg (Merge), [87](#)
- names, [173](#)
- Nest, [91, 146](#)
- nt (Nest), [91](#)
- openxlsx, [128, 188](#)
- options, [86, 143, 163, 164](#)
- order, [155](#)
- par, [12, 71, 74, 81, 96, 109, 114, 115](#)
- paste, [173](#)
- paste0, [172](#)
- pc (PieChart), [93](#)
- pdf, [42, 97](#)
- pie, [96, 98](#)
- PieChart, [93, 112](#)
- pl (Plot), [100](#)
- Plot, [100, 114, 183](#)
- plot, [53, 55, 74, 79, 81, 82, 109, 111, 114, 115, 124, 127, 183](#)
- plot.density, [180](#)
- pnorm, [124, 126](#)
- points, [104](#)
- power.t.test, [183](#)
- predict, [85, 141](#)
- print, [184](#)
- print.out, [122](#)
- print.out\_all, [123](#)
- prob.norm (prob\_norm), [123](#)
- prob.tcut (prob\_tcut), [125](#)
- prob.znorm (prob\_znorm), [126](#)
- prob\_norm, [123](#)
- prob\_tcut, [125](#)
- prob\_znorm, [126](#)
- prop (corProp), [30](#)

- qt, [126](#)
- rbind, [87, 89](#)
- rbinom, [152](#)
- rd (Read), [128](#)
- rd.cor (corRead), [32](#)
- rd\_brief (Read), [128](#)
- rd\_lbl (Read), [128](#)
- Read, [24, 43, 54, 58, 73, 77, 78, 82, 85, 111, 128, 130, 139, 141, 142, 144, 169, 179, 184–186, 188](#)
- read.csv, [132](#)
- read.fwf, [132](#)
- read.spss, [130, 132](#)
- read.table, [33, 57](#)
- read.xlsx, [130, 132](#)
- Read2 (Read), [128](#)
- rec (Recode), [133](#)
- Recode, [34, 133](#)
- reflect (corReflect), [33](#)
- reg (Regression), [137](#)
- reg\_brief (Regression), [137](#)
- regPlot, [4, 135, 140, 142, 146](#)
- Regression, [90, 122, 123, 129, 131, 135–137, 137, 185, 186](#)
- reord (corReorder), [38](#)
- resid, [85, 86, 90, 141, 146](#)
- residuals, [86](#)
- rgb, [55](#)
- row.names, [166](#)
- rstudent, [85, 86, 90, 141, 146](#)
- save, [188](#)
- scales (corCFA), [21](#)
- ScatterPlot, [141, 143, 162, 182, 183](#)
- ScatterPlot (Plot), [100](#)
- scree (corScree), [41](#)
- seq, [69, 107, 143](#)
- seq.Date, [80](#)
- sequential\_hcl, [61](#)
- set (style), [156](#)
- setwd, [16, 42, 54, 73, 82, 98, 114, 179](#)
- shapiro.test, [55](#)
- showColors, [62, 63, 113, 147](#)
- showPalettes, [62, 148](#)
- simCImean, [149](#)
- simCLT, [150](#)
- simFlips, [152](#)
- simMeans, [153](#)
- smoothScatter, [113](#)
- Sort, [154](#)
- sp (Plot), [100](#)
- srt (Sort), [154](#)
- ss (SummaryStats), [167](#)
- ss\_brief (SummaryStats), [167](#)
- stripchart, [115](#)
- style, [4, 9–12, 14, 15, 25, 52–54, 61, 69–72, 74, 81, 82, 84, 86, 88, 90, 94–97, 103–110, 113, 115, 129, 133, 139, 141, 144, 155, 156, 166, 168, 174, 177, 185, 188](#)
- subs (Subset), [165](#)
- Subset, [165](#)
- subset, [165, 167](#)
- summary, [85, 141, 170](#)
- summary.glm, [86](#)
- summary.lm, [90, 146](#)
- SummaryStats, [43, 162, 167](#)
- t.test, [176, 178, 180](#)
- table, [17](#)
- title, [114, 115](#)
- to, [33, 172](#)
- trans (Transform), [173](#)
- Transform, [173](#)
- transform, [134, 173, 174](#)
- ts, [80](#)
- tt (ttest), [176](#)
- tt\_brief (ttest), [176](#)
- ttest, [90, 176](#)
- ttestPower, [180, 182](#)
- ttp (ttestPower), [182](#)
- TukeyHSD, [4, 6](#)
- unclass, [6, 29, 55, 92, 145, 170](#)
- values, [184](#)
- VariableLabels, [77, 111, 128, 131, 132, 185](#)
- ViolinPlot, [112](#)
- ViolinPlot (Plot), [100](#)
- vl (VariableLabels), [185](#)
- vp (Plot), [100](#)
- with, [54, 72, 81, 96](#)
- Write, [130, 187](#)
- write.csv, [188](#)
- write.table, [188](#)
- wrt (Write), [187](#)

wrt\_r (Write), [187](#)

wrt\_x (Write), [187](#)

xAnd, [189](#)

xNum, [190](#)

xP, [190](#)

xRow, [191](#)

xU, [192](#)

xW, [193](#)