

# Package ‘patternize’

November 23, 2018

**Title** Quantification of Color Pattern Variation

**Version** 0.0.2

**Maintainer** Steven Van Belleghem <vanbelleghemsteven@hotmail.com>

**Description** Quantification of variation in organismal color patterns as obtained from image data. Patternize defines homology between pattern positions across images either through fixed landmarks or image registration. Pattern identification is performed by categorizing the distribution of colors using RGB thresholds or image segmentation.

**BugReports** <https://github.com/StevenVB12/patternize/issues>

**URL** <https://github.com/StevenVB12/patternize>

**Depends** R (>= 3.5.0)

**Imports** raster, sp, rgdal, abind, Morpho, dplyr, imager, magrittr, purrr, vegan, RNiftyReg

**License** GPL-3

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 6.1.0

**NeedsCompilation** no

**Author** Steven Van Belleghem [aut, cre]

**Repository** CRAN

**Date/Publication** 2018-11-23 10:50:03 UTC

## R topics documented:

colorChecker . . . . .	2
createTarget . . . . .	3
extdata . . . . .	4
imageList . . . . .	5
kImage . . . . .	5
lanArray . . . . .	6

landmarkArray . . . . .	7
landmarkList . . . . .	7
makeList . . . . .	8
maskOutline . . . . .	8
patArea . . . . .	10
patLanK . . . . .	11
patLanRGB . . . . .	13
patLanW . . . . .	14
patPCA . . . . .	16
patRDA . . . . .	19
patRegK . . . . .	21
patRegRGB . . . . .	22
patRegW . . . . .	24
patternize . . . . .	25
plotHeat . . . . .	28
rasterList_lanK . . . . .	30
rasterList_lanRGB . . . . .	31
rasterList_regK . . . . .	32
rasterList_regRGB . . . . .	32
redRes . . . . .	33
sampleLandmarks . . . . .	33
sampleRGB . . . . .	34
sumRaster . . . . .	35
<b>Index</b>	<b>36</b>

---

colorChecker	<i>Calibrate images using ColorChecker.</i>
--------------	---

---

## Description

Calibrate images using ColorChecker.

## Usage

```
colorChecker(IDlist, prepath = NULL, extension = NULL,
             patchSize = 0.6)
```

## Arguments

IDlist	List of sample IDs.
prepath	Prepath (default = NULL).
extension	Extension (default = NULL).
patchSize	Proportion of ColorChecker patch that will be used for observed RGB values (default = NULL).

**Value**

Calibrated image(s) ('filename\_calibrated.jpg')

---

createTarget	<i>Create a target image (RasterStack) from a polygon.</i>
--------------	--

---

**Description**

Create a target image (RasterStack) from a polygon.

**Usage**

```
createTarget(outline, image, res = 300, colorFill = "black",
             colorBG = "white", sigma = 10, plot = FALSE)
```

**Arguments**

outline	xy coordinates that define outline.
image	Image imported as RasterStack used in the analysis. This is used to extract the extent and dimensions for the raster layers.
res	Resolution for RasterStack (default = 300).
colorFill	Color for the fill of the polygon (default = 'black').
colorBG	Color for the background (default = 'white').
sigma	Size of sigma for Gaussian blurring (default = 10).
plot	Whether to plot the created target image (default = FALSE).

**Value**

RasterStack

**Examples**

```
## Not run:
outline_BC0077 <- read.table(paste(system.file("extdata", package = 'patternize'),
'/BC0077_outline.txt', sep=''), header = FALSE)

data(imageList)

target <- createTarget(outline_BC0077, imageList[[1]], plot = TRUE)

## End(Not run)
```

---

extdata

*External patternize data*

---

### **Description**

Raw image, landmark and cartoon data of *Heliconius erato* hydara wings.

### **Format**

Raw JPG images, landmark and cartoon data.

**BC0077.JPG** jpeg image

**BC0071.JPG** jpeg image

**BC0050.JPG** jpeg image

**BC0049.JPG** jpeg image

**BC0004.JPG** jpeg image

**BC0077\_landmarks\_LFW.Txt** xy landmark coordinates

**BC0071\_landmarks\_LFW.Txt** xy landmark coordinates

**BC0050\_landmarks\_LFW.Txt** xy landmark coordinates

**BC0049\_landmarks\_LFW.Txt** xy landmark coordinates

**BC0004\_landmarks\_LFW.Txt** xy landmark coordinates

**BC0077\_outline.txt** xy outline coordinates

**BC0077\_vein1.txt** xy vein coordinates

**BC0077\_vein2.txt** xy vein coordinates

**BC0077\_vein3.txt** xy vein coordinates

**BC0077\_vein4.txt** xy vein coordinates

**BC0077\_vein5.txt** xy vein coordinates

**BC0077\_vein6.txt** xy vein coordinates

**BC0077\_vein7.txt** xy vein coordinates

**BC0077\_vein8.txt** xy vein coordinates

**BC0077\_vein9.txt** xy vein coordinates

**BC0077\_vein10.txt** xy vein coordinates

**BC0077\_vein11.txt** xy vein coordinates

---

imageList	<i>imageList</i>
-----------	------------------

---

**Description**

List of RasterStacks as returned by makeList.

**Usage**

```
imageList
```

**Format**

A list of 5 RasterStack objects of Heliconius erato hy dara dorsal forewings.

**Examples**

```
## Not run:
data(imageList)
summary(imageList)

## End(Not run)
```

---

kImage	<a href="#">kmeans</a> clustering of image imported as a RasterStack. This function is used by patLanK and patRegK.
--------	---

---

**Description**

[kmeans](#) clustering of image imported as a RasterStack. This function is used by patLanK and patRegK.

**Usage**

```
kImage(image, k = 5, startCenter = NULL)
```

**Arguments**

image	Image imported as a RasterStack for k-means clustering.
k	Integer for number of k-means clusters (default = 3).
startCenter	A matrix of cluster centres to start k-means clustering from (default = NULL).

**Value**

List including the k-means clustered RasterStack returned as an array and object of class "kmeans".

## Examples

```
image <- raster::stack(system.file("extdata", "BC0077.jpg", package = "patternize"))
out <- kImage(image, 6)
```

---

lanArray	<i>Build landmark array for <a href="#">Morpho</a>.</i>
----------	---

---

## Description

Build landmark array for [Morpho](#).

## Usage

```
lanArray(sampleList, adjustCoords = FALSE, imageList = NULL)
```

## Arguments

sampleList	List of landmark matrices as returned by <a href="#">makeList</a> .
adjustCoords	Adjust landmark coordinates in case they are reversed compared to pixel coordinates (default = FALSE).
imageList	List of RasterStacks as returned by <a href="#">makeList</a> should be given when adjustCoords = TRUE.

## Value

X x Y x n array, where X and Y define the coordinates of the landmark points and n is the sample size.

## Examples

```
IDlist <- c('BC0077', 'BC0071', 'BC0050', 'BC0049', 'BC0004')

prepath <- system.file("extdata", package = 'patternize')
extension <- '_landmarks_LFW.txt'

landmarkList <- makeList(IDlist, 'landmark', prepath, extension)

landmarkArray <- lanArray(landmarkList)
```

---

landmarkArray	<i>landmarkArray</i>
---------------	----------------------

---

**Description**

Array of landmarks as returned by `lanArray` and used by `link[Morpho]{procsym}`.

**Usage**

```
landmarkArray
```

**Format**

An array of landmarks for 5 *Heliconius erato* *hydrara* dorsal forewings.

**Examples**

```
## Not run:  
data(landmarkArray)  
summary(landmarkArray)  
  
## End(Not run)
```

---

landmarkList	<i>landmarkList</i>
--------------	---------------------

---

**Description**

List of landmarks as returned by `makeList`.

**Usage**

```
landmarkList
```

**Format**

A list of landmarks for 5 *Heliconius erato* *hydrara* dorsal forewings.

**Examples**

```
## Not run:  
data(landmarkList)  
summary(landmarkList)  
  
## End(Not run)
```

---

makeList	<i>Build list of landmarks or RasterStacks from images using filepath and file extension.</i>
----------	---

---

### Description

Build list of landmarks or RasterStacks from images using filepath and file extension.

### Usage

```
makeList(IDlist, type, prepath = NULL, extension = NULL)
```

### Arguments

IDlist	List of sample IDs.
type	'landmark' or 'image' depending on what type of list to make.
prepath	Prepath (default = NULL).
extension	Extension (default = NULL).

### Value

Landmark or RasterStack list.

### Examples

```
IDlist <- c('BC0077', 'BC0071', 'BC0050', 'BC0049', 'BC0004')

prepath <- system.file("extdata", package = 'patternize')
extension <- '_landmarks_LFW.txt'

landmarkList <- makeList(IDlist, 'landmark', prepath, extension)

extension <- '.jpg'
imageList <- makeList(IDlist, 'image', prepath, extension)
```

---

maskOutline	<i>Intersects a RasterStack with an outline. Everything outside of the outline will be removed from the raster.</i>
-------------	---

---

### Description

Intersects a RasterStack with an outline. Everything outside of the outline will be removed from the raster.



**Usage**

```
maskOutline(RasterStack, outline, refShape, landList = NULL,
  adjustCoords = FALSE, cartoonID = NULL, IDlist = NULL,
  crop = c(0, 0, 0, 0), flipRaster = NULL, flipOutline = NULL,
  imageList = NULL, maskColor = 0)
```

**Arguments**

RasterStack	RasterStack to be masked.
outline	xy coordinates that define outline.
refShape	This can be 'target' in case the reference shape is a single sample (for registration analysis) or 'mean' if the images were transformed to a mean shape (only for meanshape when using landmark transformation)
landList	Landmark list to be given when type = 'mean'.
adjustCoords	Adjust landmark coordinates in case they are reversed compared to pixel coordinates (default = FALSE).
cartoonID	ID of the sample for which the cartoon was drawn. Only has to be given when refShape is 'mean'.
IDlist	List of sample IDs should be specified when refShape is 'mean'.
crop	Vector c(xmin, xmax, ymin, ymax) that specifies the pixel coordinates to crop the original image used in landmark or registration analysis.
flipRaster	Whether to flip raster along xy axis (in case there is an inconsistency between raster and outline coordinates).
flipOutline	Whether to flip plot along x, y or xy axis.
imageList	List of image as obtained from <a href="#">makeList</a> should be given if one wants to flip the outline or adjust landmark coordinates.
maskColor	Color the masked area gets. Set to 0 for black (default) or 255 for white.

**Examples**

```
## Not run:
data(imageList)
outline_BC0077 <- read.table(paste(system.file("extdata", package = 'patternize'),
  '/BC0077_outline.txt', sep=''), header = FALSE)

masked <- maskOutline(imageList[[1]], outline_BC0077, refShape = 'target', flipOutline = 'y')

## End(Not run)
```

---

patArea	<i>This function calculates the area in which the color pattern is expressed in each sample as the relative proportion using the provided outline of the considered trait or structure.</i>
---------	---

---

### Description

This function calculates the area in which the color pattern is expressed in each sample as the relative proportion using the provided outline of the considered trait or structure.

### Usage

```
patArea(rList, IDlist, refShape, type, outline = NULL, landList = NULL,
        adjustCoords = FALSE, cartoonID = NULL, crop = c(0, 0, 0, 0),
        flipRaster = NULL, flipOutline = NULL, imageList = NULL)
```

### Arguments

rList	List of RasterLayers as obtained from the main patternize functions.
IDlist	List of sample IDs.
refShape	This can be 'target' in case the reference shape is a single sample (for registration analysis) or 'mean' if the images were transformed to a mean shape using landmark transformation.
type	Type of rasterlist; 'RGB' or 'k' (result from RGB or k-means analysis, respectively).
outline	xy coordinates that define outline.
landList	Landmark list as returned by <a href="#">makeList</a> .
adjustCoords	Adjust landmark coordinates in case they are reversed compared to pixel coordinates (default = FALSE).
cartoonID	ID of the sample for which the cartoon was drawn.
crop	Vector c(xmin, xmax, ymin, ymax) that specifies the pixel coordinates to crop the original image used in landmark or registration analysis.
flipRaster	Whether to flip raster along xy axis (in case there is an inconsistency between raster and outline coordinates).
flipOutline	Whether to flip plot along x, y or xy axis.
imageList	List of images as obtained from <a href="#">makeList</a> should be given if one wants to flip the outline or adjust landmark coordinates.

### Value

Table or list of tables with sample IDs and relative area of color pattern or kmeans cluster.

**Examples**

```

data(rasterList_lanRGB)
#data(rasterList_regRGB)
#data(rasterList_lanK)
#data(rasterList_regK)

data(imageList)

IDlist <- c('BC0077', 'BC0071', 'BC0050', 'BC0049', 'BC0004')

outline_BC0077 <- read.table(paste(system.file("extdata", package = 'patternize'),
'/BC0077_outline.txt', sep=''), header = FALSE)

prepath <- system.file("extdata", package = 'patternize')
extension <- '_landmarks_LFW.txt'

landmarkList <- makeList(IDlist, 'landmark', prepath, extension)

area_lanRGB <- patArea(rasterList_lanRGB, IDlist, refShape = 'mean', type = 'RGB',
outline = outline_BC0077, landList = landmarkList, adjustCoords = TRUE,
imageList = imageList, cartoonID = 'BC0077')

## Not run:
area_regRGB <- patArea(rasterList_regRGB, IDlist, refShape = 'target', type = 'RGB',
outline = outline_BC0077, crop = c(100,400,40,250), adjustCoords = TRUE,
imageList = imageList, cartoonID = 'BC0077', flipRaster = 'xy')

arealist_lanK <- patArea(rasterList_lanK, IDlist, refShape = 'mean', type = 'k',
outline = outline_BC0077, landList = landmarkList, adjustCoords = TRUE,
imageList = imageList, cartoonID = 'BC0077')

arealist_regK <- patArea(rasterList_regK, IDlist, refShape = 'target', type = 'k',
outline = outline_BC0077, crop = c(100,400,40,250), adjustCoords = TRUE,
imageList = imageList, cartoonID = 'BC0077', flipRaster = 'xy')

## End(Not run)

```

---

patLanK

*Aligns images usings transformations obtained from fixed landmarks  
and extracts colors using k-means clustering.*

---

**Description**

Aligns images usings transformations obtained from fixed landmarks and extracts colors using k-means clustering.

**Usage**

```
patLanK(sampleList, landList, k = 3, resampleFactor = NULL,
        crop = FALSE, cropOffset = c(0, 0, 0, 0), res = 300,
        transformRef = "meanshape", transformType = "tps",
        removebgK = NULL, adjustCoords = FALSE, plot = FALSE,
        focal = FALSE, sigma = 3)
```

**Arguments**

sampleList	List of RasterStack objects.
landList	Landmark list as returned by <a href="#">makeList</a> .
k	Integere for defining number of k-means clusters (default = 3).
resampleFactor	Integer for downsampling used by <a href="#">redRes</a> .
crop	Whether to use the landmarks range to crop the image. This can significantly speed up the analysis (default = FALSE).
cropOffset	Vector c(xmin, xmax, ymin, ymax) that specifies the number of pixels you want the cropping to be offset from the landmarks (in case the landmarks do not surround the entire color pattern). The values specified should present the percentage of the maximum landmark value along the x and y axis.
res	Resolution for color pattern raster (default = 300). This should be reduced if the number of pixels in the image is lower than th raster.
transformRef	ID of reference sample for shape to which color patterns will be transformed to. Can be 'meanshape' for transforming to mean shape of Procrustes analysis.
transformType	Transformation type as used by <a href="#">computeTransform</a> (default = 'tps').
removebgK	Integer indicating the range RGB threshold to remove from image (e.g. 100 removes pixels with average RGB > 100; default = NULL) for k-means analysis. This works only to remove a white background.
adjustCoords	Adjust landmark coordinates in case they are reversed compared to pixel coordinates (default = FALSE).
plot	Whether to plot transformed color patterns while processing (default = FALSE).
focal	Whether to perform Gaussian blurring (default = FALSE).
sigma	Size of sigma for Gaussian blurring (default = 3).

**Value**

List of summed raster for each k-means cluster objects.

**Examples**

```
## Not run:
IDlist <- c('BC0077', 'BC0071', 'BC0050', 'BC0049', 'BC0004')
prepath <- system.file("extdata", package = 'patternize')
extension <- '_landmarks_LFW.txt'
landmarkList <- makeList(IDlist, 'landmark', prepath, extension)
```

```

extension <- '.jpg'
imageList <- makeList(IDlist, 'image', prepath, extension)
# Note that this example only aligns two images with the target,
# remove [1:2] to run a full examples.
rasterList_lanK <- patLanK(imageList[1:2], landmarkList[1:2], k = 4, crop = TRUE,
res = 100, removebgK = 100, adjustCoords = TRUE, plot = TRUE)

## End(Not run)

```

---

patLanRGB

*Aligns images usings transformations obtained from fixed landmarks and extracts colors using a predefined RGB values and cutoff value.*

---

### Description

Aligns images usings transformations obtained from fixed landmarks and extracts colors using a predefined RGB values and cutoff value.

### Usage

```

patLanRGB(sampleList, landList, RGB, resampleFactor = NULL,
colOffset = 0.1, crop = FALSE, cropOffset = c(0, 0, 0, 0),
res = 300, transformRef = "meanshape", transformType = "tps",
adjustCoords = FALSE, plot = NULL, focal = FALSE, sigma = 3,
iterations = 0)

```

### Arguments

sampleList	List of RasterStack objects.
landList	Landmark list as returned by <a href="#">makeList</a> .
RGB	RGB values for color pattern extraction specified as vector.
resampleFactor	Integer for downsampling used by <a href="#">redRes</a> .
colOffset	Color offset for color pattern extraction (default = 0.10).
crop	Whether to use the landmarks range to crop the image. This can speed up the analysis (default = FALSE).
cropOffset	Vector c(xmin, xmax, ymin, ymax) that specifies the number of pixels you want the cropping to be offset from the landmarks (in case the landmarks do not surround the entire color pattern). The values specified should present the percentage of the maximum landmark value along the x and y axis.
res	Resolution for color pattern raster (default = 300). This should be reduced if the number of pixels in the image is lower than th raster.
transformRef	ID of reference sample for shape to which color patterns will be transformed to. Can be 'meanshape' for transforming to mean shape of Procrustes analysis.
transformType	Transformation type as used by <a href="#">computeTransform</a> (default = 'tps').

adjustCoords	Adjust landmark coordinates in case they are reversed compared to pixel coordinates (default = FALSE).
plot	Whether to plot transformed color patterns while processing (default = NULL). Transformed color patterns can be plot on top of each other ('stack') or next to the original image for each sample ('compare').
focal	Whether to perform Gaussian blurring (default = FALSE).
sigma	Size of sigma for Gaussian blurring (default = 3).
iterations	Number of iterations for recalculating average color.

**Value**

List of raster objects.

**Examples**

```
## Not run:
IDlist <- c('BC0077','BC0071','BC0050','BC0049','BC0004')
prepath <- system.file("extdata", package = 'patternize')
extension <- '_landmarks_LFW.txt'

landmarkList <- makeList(IDlist, 'landmark', prepath, extension)

extension <- '.jpg'
imageList <- makeList(IDlist, 'image', prepath, extension)

RGB <- c(114,17,0)
rasterList_lanRGB <- patLanRGB(imageList, landmarkList, RGB,
  colOffset = 0.15, crop = TRUE, res = 100, adjustCoords = TRUE, plot = 'stack')

## End(Not run)
```

---

patLanW

*Extracts color pattern from landmark transformed image using watershed segmentation. This function works interactively by allowing to pick a starting pixel within each pattern element from which the watershed will extract the pattern. This function works best for patterns with sharp boundaries.*

---

**Description**

Extracts color pattern from landmark transformed image using watershed segmentation. This function works interactively by allowing to pick a starting pixel within each pattern element from which the watershed will extract the pattern. This function works best for patterns with sharp boundaries.

**Usage**

```
patLanW(sampleList, landList, IDlist = NULL, adjustCoords = FALSE,
        transformRef = "meanshape", resampleFactor = NULL,
        transformType = "tps", maskOutline = NULL, cartoonID = NULL,
        correct = FALSE, blur = TRUE, sigma = 3, bucketfill = TRUE,
        cleanP = NULL, splitC = NULL, plotTransformed = FALSE,
        plotCorrect = FALSE, plotEdges = FALSE, plotPriority = FALSE,
        plotWS = FALSE, plotBF = FALSE, plotFinal = FALSE)
```

**Arguments**

sampleList	List of RasterStack objects.
landList	Landmark list as returned by <a href="#">makeList</a> .
IDlist	List of sample IDs should be specified when masking outline and transformRef is 'meanshape'.
adjustCoords	Adjust landmark coordinates in case they are reversed compared to pixel coordinates (default = FALSE).
transformRef	ID of reference sample for shape to which color patterns will be transformed to. Can be 'meanshape' for transforming to mean shape of Procrustes analysis.
resampleFactor	Integer for downsampling image used by <a href="#">redRes</a> .
transformType	Transformation type as used by <a href="#">computeTransform</a> (default = 'tps').
maskOutline	When outline is specified, everything outside of the outline will be masked for the color extraction (default = NULL).
cartoonID	ID of the sample for which the cartoon was drawn and will be used for masking (should be set when transformRef = 'meanShape').
correct	Correct image illumination using a linear model (default = FALSE).
blur	Blur image for priority map extraction (default = TRUE).
sigma	Size of sigma for Gaussian blurring (default = 5).
bucketfill	Use a bucket fill on the background to fill holes (default = TRUE).
cleanP	Integer to remove spurious areas with width smaller than cleanP (default = NULL).
splitC	Integer to split selected patterns into connected components and remove ones with areas smaller than splitC (default = NULL).
plotTransformed	Plot transformed image (default = FALSE).
plotCorrect	Plot corrected image, corrected for illumination using a linear model (default = FALSE).
plotEdges	Plot image gradient (default = FALSE).
plotPriority	Plot priority map (default = FALSE).
plotWS	Plot watershed result (default = FALSE).
plotBF	Plot bucketfill (default = FALSE).
plotFinal	Plot extracted patterns (default = FALSE).

**Value**

List of raster objects.

**Examples**

```
## Not run:
IDlist <- c('BC0077','BC0071','BC0050','BC0049','BC0004')
prepath <- system.file("extdata", package = 'patternize')
extension <- '_landmarks_LFW.txt'

landmarkList <- makeList(IDlist, 'landmark', prepath, extension)

extension <- '.jpg'
imageList <- makeList(IDlist, 'image', prepath, extension)

outline_BC0077 <- read.table(paste(system.file("extdata", package = 'patternize'),
'/BC0077_outline.txt', sep=''), header = FALSE)

rasterList_W <- patLanW(imageList, landmarkList, IDlist, transformRef = 'meanshape',
adjustCoords = TRUE, plotTransformed = FALSE, correct = TRUE, plotCorrect = FALSE, blur = FALSE,
sigma = 2, bucketfill = FALSE, cleanP = 0, splitC = 10, plotPriority = TRUE, plotWS = TRUE,
plotBF = TRUE, plotFinal = TRUE, maskOutline = outline_BC0077, cartoonID = 'BC0077')

## End(Not run)
```

---

patPCA

*This function transforms the individual color pattern rasters as obtained by the main patternize functions to a dataframe of 0 and 1 values that can be used for Principal Component Analysis ([prcomp](#)). This function also allows to plot the analysis including a visualization of the shape changes along the axis. Pixel values are predicted by multiplying the rotation matrix (eigenvectors) with a vector that has the same length as the number of rows in the rotation matrix and in which all values are set to zero except for the PC value for which we want to predict the pixel values.*

---

**Description**

This function transforms the individual color pattern rasters as obtained by the main patternize functions to a dataframe of 0 and 1 values that can be used for Principal Component Analysis ([prcomp](#)). This function also allows to plot the analysis including a visualization of the shape changes along the axis. Pixel values are predicted by multiplying the rotation matrix (eigenvectors) with a vector that has the same length as the number of rows in the rotation matrix and in which all values are set to zero except for the PC value for which we want to predict the pixel values.



**Usage**

```
patPCA(rList, popList, collist, symbolList = NULL, rListPredict = NULL,
      popListPredict = NULL, collistPredict = NULL,
      symbolListPredict = NULL, plot = FALSE, plotType = "points",
      plotChanges = FALSE, PCx = 1, PCy = 2, plotCartoon = FALSE,
      refShape = NULL, outline = NULL, lines = NULL, landList = NULL,
      adjustCoords = FALSE, crop = c(0, 0, 0, 0), flipRaster = NULL,
      flipOutline = NULL, imageList = NULL, cartoonID = NULL,
      colpalette = NULL, normalized = NULL, cartoonOrder = "above",
      lineOrder = "above", cartoonCol = "gray", cartoonFill = NULL,
      plotLandmarks = FALSE, landCol = "black", xlim = c(-1, 1),
      legendTitle = "Predicted", xlab = "", ylab = "", main = "")
```

**Arguments**

rList	List of raster objects.
popList	List of vectors including sampleIDs for each population.
collist	List of colors for each population.
symbolList	List with graphical plotting symbols (default = NULL).
rListPredict	List of raster objects to predict into PCA space (default = NULL).
popListPredict	List of vectors including sampleIDs for each set of predict samples (default = NULL). Note to that this also has to be a list if only one population is included.
collistPredict	List of colors for each set of predict samples (default = NULL).
symbolListPredict	List with graphical plotting symbols for predict sets (default = NULL).
plot	Whether to plot the PCA analysis (default = FALSE).
plotType	Plot 'points' or sample 'labels' (default = 'points')
plotChanges	Whether to include plots of the changes along the PC axis (default = FALSE).
PCx	PC axis to be presented for x-axis (default PC1).
PCy	PC axis to be presented for y-axis (default PC2).
plotCartoon	Whether to plot a cartoon. This cartoon should be drawn on one of the samples used in the analysis.
refShape	This can be 'target' in case the reference shape is a single sample (for registration analysis) or 'mean' if the images were transformed to a mean shape (only for meanshape when using landmark transformation)
outline	xy coordinates that define outline.
lines	list of files with xy coordinates of line objects to be added to cartoon.
landList	Landmark landmarkList.
adjustCoords	Adjust landmark coordinates.
crop	Vector c(xmin, xmax, ymin, ymax) that specifies the pixel coordinates to crop the original image used in landmark or registration analysis.
flipRaster	Whether to flip raster along xy axis (in case there is an inconsistency between raster and outline coordinates).

flipOutline	Whether to flip plot along x, y or xy axis.
imageList	List of image should be given if one wants to flip the outline or adjust landmark coordinates.
cartoonID	ID of the sample for which the cartoon was drawn.
colpalette	Vector of colors for color palette (default = c("white","lightblue","blue","green","yellow","red"))
normalized	Set this to true in case the summed rasters are already divided by the sample number.
cartoonOrder	Whether to plot the cartoon outline 'above' or 'under' the pattern raster (default = 'above'). Set to 'under' for filled outlines.
lineOrder	Whether to plot the cartoon lines 'above' or 'under' the pattern raster (default = 'above').
cartoonCol	Outline and line color for cartoon (default = 'gray').
cartoonFill	Fill color for outline of cartoon (default = NULL).
plotLandmarks	Whether to plot the landmarks from the target image or mean shape landmarks (default = FALSE).
landCol	Color for plotting landmarks (default = 'black').
zlim	z-axis limit (default = c(0,1))
legendTitle	Title of the raster legend (default = 'Proportion')
xlab	Optional x-axis label.
ylab	Optional y-axis label.
main	Optional main title.

### Value

If plot = TRUE: List including a [1] dataframe of the binary raster values that can be used for principle component analysis, [2] a dataframe of sample IDs and specified population colors and [3] prcomp results. If plot = FALSE: prcomp result.

### See Also

[prcomp](#)

### Examples

```
data(rasterList_lanRGB)

pop1 <- c('BC0077', 'BC0071')
pop2 <- c('BC0050', 'BC0049', 'BC0004')
popList <- list(pop1, pop2)
colList <- c("red", "blue")

pcaOut <- patPCA(rasterList_lanRGB, popList, colList, plot = TRUE)
```

---

patRDA	<i>This function transforms the individual color pattern rasters as obtained by the main patternize functions to a dataframe of 0 and 1 values that can be used for constrained Redundancy Analysis (RDA) (<a href="#">rda</a>). This function also allows to plot the analysis including a visualization of the shape changes along the axis.</i>
--------	--

---

### Description

This function transforms the individual color pattern rasters as obtained by the main patternize functions to a dataframe of 0 and 1 values that can be used for constrained Redundancy Analysis (RDA) ([rda](#)). This function also allows to plot the analysis including a visualization of the shape changes along the axis.

### Usage

```
patRDA(rList, popList, collist, symbolList = NULL, rListPredict = NULL,
       popListPredict = NULL, collistPredict = NULL,
       symbolListPredict = NULL, plot = FALSE, plotType = "points",
       plotChanges = FALSE, PCx = 1, PCy = 2, plotCartoon = FALSE,
       refShape = NULL, outline = NULL, lines = NULL, landList = NULL,
       adjustCoords = FALSE, crop = c(0, 0, 0, 0), flipRaster = NULL,
       flipOutline = NULL, imageList = NULL, cartoonID = NULL,
       colpalette = NULL, normalized = NULL, cartoonOrder = "above",
       lineOrder = "above", cartoonCol = "gray", cartoonFill = NULL,
       plotLandmarks = FALSE, landCol = "black", zlim = c(-1, 1),
       legendTitle = "Predicted", xlab = "", ylab = "", main = "")
```

### Arguments

rList	List of raster objects.
popList	List of vectors including sampleIDs for each population.
collist	List of colors for each population.
symbolList	List with graphical plotting symbols (default = NULL).
rListPredict	List of raster objects to predict into DFA space (default = NULL).
popListPredict	List of vectors including sampleIDs for each set of predict samples (default = NULL). Note to that this also has to be a list if only one population is included.
collistPredict	List of colors for each set of predict samples (default = NULL).
symbolListPredict	List with graphical plotting symbols for predict sets (default = NULL).
plot	Whether to plot the PCA analysis (default = FALSE).
plotType	Plot 'points' or sample 'labels' (default = 'points')
plotChanges	Whether to include plots of the changes along the PC axis (default = FALSE).
PCx	PC axis to be presented for x-axis (default PC1).

PCy	PC axis to be presented for y-axis (default PC2).
plotCartoon	Whether to plot a cartoon. This cartoon should be drawn on one of the samples used in the analysis.
refShape	This can be 'target' in case the reference shape is a single sample (for registration analysis) or 'mean' if the images were transformed to a mean shape (only for meanshape when using landmark transformation)
outline	xy coordinates that define outline.
lines	list of files with xy coordinates of line objects to be added to cartoon.
landList	Landmark landmarkList.
adjustCoords	Adjust landmark coordinates.
crop	Vector c(xmin, xmax, ymin, ymax) that specifies the pixel coordinates to crop the original image used in landmark or registration analysis.
flipRaster	Whether to flip raster along xy axis (in case there is an inconsistency between raster and outline coordinates).
flipOutline	Whether to flip plot along x, y or xy axis.
imageList	List of image should be given if one wants to flip the outline or adjust landmark coordinates.
cartoonID	ID of the sample for which the cartoon was drawn.
colpalette	Vector of colors for color palette (default = c("white", "lightblue", "blue", "green", "yellow", "red"))
normalized	Set this to true in case the summed rasters are already divided by the sample number.
cartoonOrder	Whether to plot the cartoon outline 'above' or 'under' the pattern raster (default = 'above'). Set to 'under' for filled outlines.
lineOrder	Whether to plot the cartoon lines 'above' or 'under' the pattern raster (default = 'above').
cartoonCol	Outline and line color for cartoon (default = 'gray').
cartoonFill	Fill color for outline of cartoon (default = NULL).
plotLandmarks	Whether to plot the landmarks from the target image or mean shape landmarks (default = FALSE).
landCol	Color for plotting landmarks (default = 'black').
zlim	z-axis limit (default = c(0,1))
legendTitle	Title of the raster legend (default = 'Proportion')
xlab	Optional x-axis label.
ylab	Optional y-axis label.
main	Optional main title.

### Value

If plot = TRUE: List including a [1] dataframe of the binary raster values that can be used for discriminant function analysis, [2] a dataframe of sample IDs and specified population colors and [3] lda results. if rListPredict not empty: [4] class prediction of samples. If plot = FALSE: lda result only.

**See Also**[lda](#)**Examples**

```

data(rasterList_lanRGB)

pop1 <- c('BC0077', 'BC0071')
pop2 <- c('BC0050', 'BC0049', 'BC0004')
popList <- list(pop1, pop2)
collist <- c("red", "blue")

pcaOut <- patRDA(rasterList_lanRGB, popList, collist, plot = TRUE)

```

patRegK

*Aligns images using [niftyreg](#) utilities for automated image registration and extracts colors using k-means clustering.*

**Description**

Aligns images using [niftyreg](#) utilities for automated image registration and extracts colors using k-means clustering.

**Usage**

```

patRegK(sampleList, target, k = 3, resampleFactor = NULL,
        useBlockPercentage = 75, crop = c(0, 0, 0, 0), removebgR = NULL,
        removebgK = NULL, maskOutline = NULL, maskColor = 0,
        plot = FALSE, focal = FALSE, sigma = 3)

```

**Arguments**

sampleList	List of RasterStack objects.
target	Image imported as RasterStack used as target for registration.
k	Integere for defining number of k-means clusters (default = 3).
resampleFactor	Integer for downsampling used by <a href="#">redRes</a> (default = NULL).
useBlockPercentage	Block percentage as used in <a href="#">niftyreg</a> (default = 75).
crop	Vector c(xmin, xmax, ymin, ymax) that specifies the pixel coordinates to crop the original image.
removebgR	Integer indicating the range RGB treshold to remove from image (e.g. 100 removes pixels with average RGB > 100; default = NULL) for registration analysis. This works only to remove a white background.

removebgK	Integer indicating the range RGB threshold to remove from image (e.g. 100 removes pixels with average RGB > 100; default = NULL) for k-means analysis. This works only to remove a white background.
maskOutline	When outline is specified, everything outside of the outline will be masked for the color extraction (default = NULL).
maskColor	Color the masked area gets. Set to 0 for black (default) or 255 for white.
plot	Whether to plot k-means clustered image while processing (default = FALSE).
focal	Whether to perform Gaussian blurring (default = FALSE).
sigma	Size of sigma for Gaussian blurring (default = 3).

**Value**

List of rasters for each k-means cluster objects.

**Examples**

```
IDlist <- c('BC0077','BC0071','BC0050','BC0049','BC0004')
prepath <- system.file("extdata", package = 'patternize')
extension <- '.jpg'

imageList <- makeList(IDlist, 'image', prepath, extension)

target <- imageList[[1]]

## Not run:
rasterList_regK <- patRegK(imageList[3], target, k = 5,
crop = c(100,400,40,250), removebgR = 100, plot = TRUE)

## End(Not run)
```

---

patRegRGB	<i>Aligns images using <a href="#">niftyreg</a> utilities for automated image registration and extracts colors using a predefined RGB values and cutoff value.</i>
-----------	--

---

**Description**

Aligns images using [niftyreg](#) utilities for automated image registration and extracts colors using a predefined RGB values and cutoff value.

**Usage**

```
patRegRGB(sampleList, target, RGB, resampleFactor = NULL,
useBlockPercentage = 75, colOffset = 0.1, crop = c(0, 0, 0, 0),
removebgR = NULL, maskOutline = NULL, plot = FALSE,
focal = FALSE, sigma = 3, iterations = 0)
```

**Arguments**

sampleList	List of RasterStack objects.
target	Image imported as RasterStack used as target for registration.
RGB	Values for color pattern extraction specified as RGB vector.
resampleFactor	Integer for downsampling used by <code>redRes</code> (default = NULL).
useBlockPercentage	Block percentage as used in <code>niftyreg</code> (default = 75).
colOffset	Color offset for color pattern extraction (default = 0.10).
crop	Vector c(xmin, xmax, ymin, ymax) that specifies the pixel coordinates to crop the original image.
removebgR	Integer indicating the range RGB threshold to remove from image (e.g. 100 removes pixels with average RGB > 100; default = NULL) for registration analysis. This works only to remove a white background.
maskOutline	When outline is specified, everything outside of the outline will be masked for the color extraction (default = NULL).
plot	Whether to plot transformed color patterns while processing (default = FALSE). Transformed color patterns can be plot on top of each other ('stack') or next to the original image for each sample ('compare').
focal	Whether to perform Gaussian blurring (default = FALSE).
sigma	Size of sigma for Gaussian blurring (default = 3).
iterations	Number of iterations for recalculating average color (default = 0). If set, the RGB value for pattern extraction will be iteratively recalculated to be the average of the extracted area. This may improve extraction of distinct color pattern, but fail for more gradually distributed (in color space) patterns.

**Value**

List of raster objects.

**Examples**

```
IDlist <- c('BC0077','BC0071','BC0050','BC0049','BC0004')
prepath <- system.file("extdata", package = 'patternize')
extension <- '.jpg'

imageList <- makeList(IDlist, 'image', prepath, extension)

target <- imageList[[1]]

RGB <- c(114,17,0)

# Note that this example only aligns one image with the target,
# remove [2] to run a full examples.
rasterList_regRGB <- patRegRGB(imageList[2], target, RGB,
colOffset= 0.15, crop = c(100,400,40,250), removebgR = 100, plot = 'stack')
```

---

patRegW	<i>Aligns images using <a href="#">niftyreg</a> utilities for automated image registration and extracts color pattern using watershed segmentation. This function works interactively by allowing to pick a starting pixel within each pattern element from which the watershed will extract the pattern. This function works best for patterns with sharp boundaries.</i>
---------	--

---

## Description

Aligns images using [niftyreg](#) utilities for automated image registration and extracts color pattern using watershed segmentation. This function works interactively by allowing to pick a starting pixel within each pattern element from which the watershed will extract the pattern. This function works best for patterns with sharp boundaries.

## Usage

```
patRegW(sampleList, target, resampleFactor = NULL,
        useBlockPercentage = 75, crop = c(0, 0, 0, 0), removebgR = NULL,
        maskOutline = NULL, cartoonID = NULL, correct = FALSE,
        blur = TRUE, sigma = 3, bucketfill = TRUE, cleanP = NULL,
        splitC = NULL, plotTransformed = FALSE, plotCorrect = FALSE,
        plotEdges = FALSE, plotPriority = FALSE, plotWS = FALSE,
        plotBF = FALSE, plotFinal = FALSE)
```

## Arguments

sampleList	List of RasterStack objects.
target	Image imported as RasterStack used as target for registration.
resampleFactor	Integer for downsampling image used by <a href="#">redRes</a> .
useBlockPercentage	Block percentage as used in <a href="#">niftyreg</a> (default = 75).
crop	Vector c(xmin, xmax, ymin, ymax) that specifies the pixel coordinates to crop the original image.
removebgR	Integer indicating the range RGB threshold to remove from image (e.g. 100 removes pixels with average RGB > 100; default = NULL) for registration analysis. This works only to remove a white background.
maskOutline	When outline is specified, everything outside of the outline will be masked for the color extraction (default = NULL).
cartoonID	ID of the sample for which the cartoon was drawn and will be used for masking.
correct	Correct image illumination using a linear model (default = FALSE).
blur	Blur image for priority map extraction (default = TRUE).
sigma	Size of sigma for Gaussian blurring (default = 5).
bucketfill	Use a bucket fill on the background to fill holes (default = TRUE).



cleanP	Integer to remove spurious areas with width smaller than cleanP (default = NULL).
splitC	Integer to split selected patterns into connected components and remove ones with areas smaller than splitC (default = NULL).
plotTransformed	Plot transformed image (default = FALSE).
plotCorrect	Plot corrected image, corrected for illumination using a linear model (default = FALSE).
plotEdges	Plot image gradient (default = FALSE).
plotPriority	Plot priority map (default = FALSE).
plotWS	Plot watershed result (default = FALSE).
plotBF	Plot bucketfill (default = FALSE).
plotFinal	Plot extracted patterns (default = FALSE).

**Value**

List of raster objects.

**Examples**

```
## Not run:
IDlist <- c('BC0077', 'BC0071', 'BC0050', 'BC0049', 'BC0004')
prepath <- system.file("extdata", package = 'patternize')
extension <- '.jpg'

imageList <- makeList(IDlist, 'image', prepath, extension)

target <- imageList[[1]]

outline_BC0077 <- read.table(paste(system.file("extdata", package = 'patternize'),
  '/BC0077_outline.txt', sep=''), header = FALSE)

rasterList_regW <- patRegW(imageList, target, plotTransformed = FALSE, cartoonID = 'BC0077',
  correct = TRUE, plotCorrect = FALSE, blur = FALSE, sigma = 2,
  bucketfill = FALSE, cleanP = 0, splitC = 10, plotPriority = TRUE,
  plotWS = FALSE, plotBF = FALSE, plotFinal = TRUE, removebgR = 100,
  maskOutline = outline_BC0077)

## End(Not run)
```

## Description

Quantifying variation in color patterns to study and compare the consistency of their expression necessitates the homologous alignment and color-based segmentation of images. Patternize is an R package that quantifies variation in color patterns as obtained from image data. Patternize defines homology between pattern positions across specimens either through fixed landmarks or image registration. Pattern identification is performed by categorizing the distribution of colors using either an RGB threshold or an unsupervised image segmentation. The quantification of the color patterns can be visualized as heat maps and compared between sets of samples.

## patternize main functions

The package has six main functions depending on how you want the alignment of the iamges and the color extraction to be performed.

`patLanRGB`

Aligns images by transformations obtained from fixed landmarks and extracts colors using a predefined RGB values and cutoff value.

`patLanK`

Aligns images by transformations obtained from fixed landmarks and extracts colors using k-means clustering.

`patLanW`

Aligns images by transformations obtained from fixed landmarks and extracts color patterns by watershed segmentation using `imager` utilities.

`patRegRGB`

Aligns images using `niftyreg` utilities for automated image registration and extracts colors using a predefined RGB values and cutoff value.

`patRegK`

Aligns images using `niftyreg` utilities for automated image registration and extracts colors using k-means clustering.

`patRegW`

Aligns images using `niftyreg` utilities for automated image registration and extracts color patterns by watershed segmentation using `imager` utilities.

## patternize preprocessing functions

The input for the main patternize functions are RasterStack objects and when landmark transformation is used, landmark arrays.

`makeList`

This function returns a list of RasterStacks or a list of landmarks depending on the input provided.

`sampleLandmarks`

Sample landmarks in an image.

`lanArray`

This function creates a landmark array as used by `procSym` in the package Morpho.

**patternize postprocessing functions**

sumRaster

This function sums the individual color pattern rasters as obtained by the main patternize functions.

plotHeat

Plots the color pattern heatmaps from sumRaster output.

patPCA

This function transforms the individual color pattern rasters as obtained by the main patternize functions to a dataframe of 0 and 1 values that can be used for Principal Component Analysis ([prcomp](#)). This function also allows to plot the analysis including a visualization of the shape changes along the axis.

patRDA

This function transforms the individual color pattern rasters as obtained by the main patternize functions to a dataframe of 0 and 1 values that can be used for constrained Redundancy Analysis ([rda](#)). This function also allows to plot the analysis including a visualization of the shape changes along the axis.

patArea

This function calculates the area in which the color pattern is expressed in each sample as the relative proportion using the provided outline of the considered trait or structure.

**patternize miscellaneous functions**

redRes

Reduces the resolution of the RasterStack objects to speed up analysis.

kImage

Performs k-means clustering of images.

sampleRGB

Interactive function to sample RGB value from pixel or area in an image.

createTarget

Creates an artificial target images using a provided outline that can be used for image registration (experimental).

maskOutline

Intersects a RasterStack with an outline. Everything outside of the outline will be removed from the raster.

colorChecker

Calibrate images using ColorChecker.

**Author(s)**

Steven M. Van Belleghem

**See Also**

[raster](#), [stack](#), [procSym](#), [computeTransform](#), [niftyreg imager](#)

Jon Clayden, Marc Modat, Benoit Presles, Thanasis Anthopoulos and Pankaj Daga (2017). *RNiftyReg: Image Registration Using the 'NiftyReg' Library*. R package version 2.5.0. <https://CRAN.R-project.org/package=RNiftyReg>

Stefan Schlager (2016). *Morpho: Calculations and Visualisations Related to Geometric Morphometrics*. R package version 2.4.1.1. <https://github.com/zarquon42b/Morpho>

Simon Barthelmé (2017). *imager: Image processing library based on 'CImg'*. R package version 0.40.2. <https://CRAN.R-project.org/package=imager>

---

plotHeat *Plots the color pattern heatmaps from sumRaster output.*

---

## Description

Plots the color pattern heatmaps from sumRaster output.

## Usage

```
plotHeat(summedRaster, IDlist, colpalette = NULL, plotCartoon = FALSE,
  refShape = NULL, outline = NULL, lines = NULL, landList = NULL,
  adjustCoords = FALSE, cartoonID = NULL, normalized = FALSE,
  crop = c(0, 0, 0, 0), flipRaster = NULL, flipOutline = NULL,
  imageList = NULL, cartoonOrder = "above", lineOrder = "above",
  cartoonCol = "gray", cartoonFill = NULL, plotLandmarks = FALSE,
  landCol = "black", zlim = c(0, 1), legendTitle = "Proportion",
  xlab = "", ylab = "", main = "", plotPCA = FALSE)
```

## Arguments

summedRaster	Summed raster or summedRasterList.
IDlist	List of sample IDs.
colpalette	Vector of colors for color palette (default = c("white", "lightblue", "blue", "green", "yellow", "red"))
plotCartoon	Whether to plot a cartoon. This cartoon should be drawn on one of the samples used in the analysis.
refShape	This can be 'target' in case the reference shape is a single sample (for registration analysis) or 'mean' if the images were transformed to a mean shape (only for meanshape when using landmark transformation)
outline	xy coordinates that define outline.
lines	list of files with xy coordinates of line objects to be added to cartoon.
landList	Landmark landmarkList.
adjustCoords	Adjust landmark coordinates.

cartoonID	ID of the sample for which the cartoon was drawn.
normalized	Set this to true in case the summed rasters are already divided by the sample number.
crop	Vector c(xmin, xmax, ymin, ymax) that specifies the pixel coordinates to crop the original image used in landmark or registration analysis.
flipRaster	Whether to flip raster along xy axis (in case there is an inconsistency between raster and outline coordinates).
flipOutline	Whether to flip plot along x, y or xy axis.
imageList	List of images should be given if one wants to flip the outline or adjust landmark coordinates.
cartoonOrder	Whether to plot the cartoon outline 'above' or 'under' the pattern raster (default = 'above'). Set to 'under' for filled outlines.
lineOrder	Whether to plot the cartoon lines 'above' or 'under' the pattern raster (default = 'above').
cartoonCol	Outline and line color for cartoon (default = 'gray').
cartoonFill	Fill color for outline of cartoon (default = NULL).
plotLandmarks	Whether to plot the landmarks from the target image or mean shape landmarks (default = FALSE).
landCol	Color for plotting landmarks (default = 'black').
zlim	z-axis limit (default = c(0,1))
legendTitle	Title of the raster legend (default = 'Proportion')
xlab	Optional x-axis label.
ylab	Optional y-axis label.
main	Optional main title.
plotPCA	Set as TRUE when visualizing shape changes along PCA axis in <code>\codepatPCA</code> .

## Examples

```

data(rasterList_lanRGB)
IDlist <- c('BC0077', 'BC0071', 'BC0050', 'BC0049', 'BC0004')
outline_BC0077 <- read.table(paste(system.file("extdata", package = 'patternize'),
  '/BC0077_outline.txt', sep=''), header = FALSE)
lines_BC0077 <- list.files(path=paste(system.file("extdata", package = 'patternize')),
  pattern='vein', full.names = TRUE)

summedRaster_regRGB <- sumRaster(rasterList_regRGB, IDlist, type = 'RGB')
data(imageList)

plotHeat(summedRaster_regRGB, IDlist, plotCartoon = TRUE, refShape = 'target',
  outline = outline_BC0077, lines = lines_BC0077, crop = c(100,400,40,250),
  flipRaster = 'xy', imageList = imageList, cartoonOrder = 'under',
  cartoonFill = 'black', main = 'registration_example')

## Not run:
data(rasterList_lanK)

```

```

IDlist <- c('BC0077','BC0071','BC0050','BC0049','BC0004')
summedRasterList <- sumRaster(rasterList_lanK, IDlist, type = 'k')
plotHeat(summedRasterList, IDlist)

summedRasterList_regK <- sumRaster(rasterList_regK, IDlist, type = 'k')
plotHeat(summedRasterList_regK, IDlist, plotCartoon = TRUE, refShape = 'target',
outline = outline_BC0077, lines = lines_BC0077, crop = c(100,400,40,250),
flipRaster = 'y', imageList = imageList, cartoonOrder = 'under',
cartoonFill = 'black', main = 'kmeans_example')

plotHeat(summedRasterList_regK[[1]], IDlist, plotCartoon = TRUE, refShape = 'target',
outline = outline_BC0077, lines = lines_BC0077, crop = c(100,400,40,250),
flipRaster = 'y', imageList = imageList, cartoonOrder = 'under',
cartoonFill = 'black', main = 'kmeans_example')

prepath <- system.file("extdata", package = 'patternize')
extension <- '_landmarks_LFW.txt'
landmarkList <- makeList(IDlist, 'landmark', prepath, extension)

summedRaster_lanRGB <- sumRaster(rasterList_lanRGB, IDlist, type = 'RGB')

plotHeat(summedRaster_lanRGB, IDlist, plotCartoon = TRUE, refShape = 'mean',
outline = outline_BC0077, lines = lines_BC0077, landList = landmarkList,
adjustCoords = TRUE, imageList = imageList, cartoonID = 'BC0077',
cartoonOrder = 'under', cartoonFill= 'black', main = 'Landmark_example')

summedRaster_lanK <- sumRaster(rasterList_lanK, IDlist, type = 'k')

plotHeat(summedRaster_lanK, IDlist, plotCartoon = TRUE, refShape = 'mean',
outline = outline_BC0077, lines = lines_BC0077, landList = landmarkList,
adjustCoords = TRUE, imageList = imageList, cartoonID = 'BC0077',
cartoonOrder = 'under', cartoonFill= 'black', main = 'Landmark_example')

plotHeat(summedRaster_lanK[[2]], IDlist, plotCartoon = TRUE, refShape = 'mean',
outline = outline_BC0077, lines = lines_BC0077, landList = landmarkList,
adjustCoords = TRUE, imageList = imageList, cartoonID = 'BC0077',
cartoonOrder = 'under', cartoonFill= 'black', main = 'Landmark_example')

## End(Not run)

```

---

rasterList\_lanK

*rasterList\_lanK*


---

## Description

List of RasterLayers as returned by patLanK.

**Usage**

```
rasterList_lanK
```

**Format**

A list of RasterLayers including the red color pattern extracted from 5 *Heliconius erato* hy dara dorsal forewings using patLanK.

**Examples**

```
## Not run:  
data(rasterList_lanK)  
summary(rasterList_lanL)  
  
## End(Not run)
```

---

*rasterList\_lanRGB*      *rasterList\_lanRGB*

---

**Description**

List of RasterLayers as returned by patLanRGB.

**Usage**

```
rasterList_lanRGB
```

**Format**

A list of RasterLayers including the red color pattern extracted from 5 *Heliconius erato* hy dara dorsal forewings using patLanRGB.

**Examples**

```
## Not run:  
data(rasterList_lanRGB)  
summary(rasterList_lanRGB)  
  
## End(Not run)
```

---

rasterList_regK	<i>rasterList_regK</i>
-----------------	------------------------

---

**Description**

List of RasterLayers as returned by patRegK.

**Usage**

```
rasterList_regK
```

**Format**

A list of RasterLayers including the red color pattern extracted from 5 *Heliconius erato* hydara dorsal forewings using patRegK.

**Examples**

```
## Not run:  
data(rasterList_regK)  
summary(rasterList_regK)  
  
## End(Not run)
```

---

rasterList_regRGB	<i>rasterList_regRGB</i>
-------------------	--------------------------

---

**Description**

List of RasterLayers as returned by patRegRGB.

**Usage**

```
rasterList_regRGB
```

**Format**

A list of RasterLayers including the red color pattern extracted from 5 *Heliconius erato* hydara dorsal forewings using patRegRGB.

**Examples**

```
## Not run:  
data(rasterList_regRGB)  
summary(rasterList_regRGB)  
  
## End(Not run)
```



---

redRes	<i>Reduce the resolution of an image imported as a RasterStack by downsampling.</i>
--------	---

---

**Description**

Reduce the resolution of an image imported as a RasterStack by downsampling.

**Usage**

```
redRes(image, resampleFactor)
```

**Arguments**

image            RasterStack for downsampling.  
resampleFactor   Integer for downsampling.

**Value**

Downsampled RasterStack

**Examples**

```
image <- raster::stack(system.file("extdata", "BC0077.jpg", package = "patternize"))
image_reduced <- redRes(image, 5)
```

---

sampleLandmarks	<i>Sample landmarks in an image.</i>
-----------------	--------------------------------------

---

**Description**

Sample landmarks in an image.

**Usage**

```
sampleLandmarks(sampleList, resampleFactor = NULL, crop = c(0, 0, 0, 0))
```

**Arguments**

sampleList        RasterStack or list of RasterStack objects as obtained by [makeList](#).  
resampleFactor   Integer for downsampling the image(s) used by [redRes](#).  
crop                Vector c(xmin, xmax, ymin, ymax) that specifies the pixel coordinates to crop the original image.

**Value**

landmark matrix or landmark list

**Examples**

```
## Not run:
IDlist <- c('BC0077', 'BC0071')
prepath <- system.file("extdata", package = 'patternize')
extension <- '.jpg'
imageList <- makeList(IDlist, 'image', prepath, extension)

landmarkList <- sampleLandmarks(imageList)

## End(Not run)
```

---

sampleRGB	<i>Interactive function to sample RGB value from pixel or square area in an image.</i>
-----------	--

---

**Description**

Interactive function to sample RGB value from pixel or square area in an image.

**Usage**

```
sampleRGB(image, resampleFactor = NULL, crop = c(0, 0, 0, 0),
  type = "point")
```

**Arguments**

image	Image imported as a RasterStack.
resampleFactor	Integer for downsampling used by <a href="#">redRes</a> .
crop	Vector c(xmin, xmax, ymin, ymax) that specifies the pixel coordinates to crop the original image.
type	Set 'point' to extract RGB from a single point or 'area' to extract from a square area defined by setting two points (default = 'point').

**Value**

RGB vector

**Examples**

```
image <- raster::stack(system.file("extdata", "BC0077.jpg", package = "patternize"))
RGB <- sampleRGB(image, resampleFactor = 1)
```

---

sumRaster	<i>This function sums the individual color pattern RasterLayes as obtained by the main patternize functions.</i>
-----------	--

---

**Description**

This function sums the individual color pattern RasterLayes as obtained by the main patternize functions.

**Usage**

```
sumRaster(rList, IDlist, type)
```

**Arguments**

rList	List of RasterLayers or list of RasterLayers for each k-means cluster.
IDlist	List of sample IDs.
type	Type of rasterlist; 'RGB' or 'k' (result from RGB or k-means analysis, respectively).

**Examples**

```
data(rasterList_lanRGB)
IDlist <- c('BC0077','BC0071','BC0050','BC0049','BC0004')
summedRaster <- sumRaster(rasterList_lanRGB, IDlist, type = 'RGB')

data(rasterList_lanK)
IDlist <- c('BC0077','BC0071','BC0050','BC0049','BC0004')
summedRasterList <- sumRaster(rasterList_lanK, IDlist, type = 'k')
```

# Index

## \*Topic **datasets**

- imageList, [5](#)
  - landmarkArray, [7](#)
  - landmarkList, [7](#)
  - rasterList\_lanK, [30](#)
  - rasterList\_lanRGB, [31](#)
  - rasterList\_regK, [32](#)
  - rasterList\_regRGB, [32](#)
- colorChecker, [2](#)
- computeTransform, [12](#), [13](#), [15](#), [27](#)
- createTarget, [3](#)
- extdata, [4](#)
- imageList, [5](#)
- imager, [26](#), [27](#)
- kImage, [5](#)
- kmeans, [5](#)
- lanArray, [6](#)
- landmarkArray, [7](#)
- landmarkList, [7](#)
- lda, [21](#)
- makeList, [6](#), [8](#), [9](#), [10](#), [12](#), [13](#), [15](#), [33](#)
- maskOutline, [8](#)
- Morpho, [6](#)
- niftyreg, [21–24](#), [26](#), [27](#)
- patArea, [10](#)
- patLanK, [11](#)
- patLanRGB, [13](#)
- patLanW, [14](#)
- patPCA, [16](#), [29](#)
- patRDA, [19](#)
- patRegK, [21](#)
- patRegRGB, [22](#)
- patRegW, [24](#)
- patternize, [25](#)
- patternize-package (patternize), [25](#)
- plotHeat, [28](#)
- prcomp, [16](#), [18](#), [27](#)
- procSym, [26](#), [27](#)
- raster, [27](#)
- rasterList\_lanK, [30](#)
- rasterList\_lanRGB, [31](#)
- rasterList\_regK, [32](#)
- rasterList\_regRGB, [32](#)
- rda, [19](#), [27](#)
- redRes, [12](#), [13](#), [15](#), [21](#), [23](#), [24](#), [33](#), [33](#), [34](#)
- sampleLandmarks, [33](#)
- sampleRGB, [34](#)
- stack, [27](#)
- sumRaster, [35](#)