

Package ‘CCAMLRGIS’

March 23, 2020

Type Package

Title Antarctic Spatial Data Manipulation

Version 3.0.3

Date 2020-03-23

Description Loads and creates spatial data, including layers and tools that are relevant to the activities of the Commission for the Conservation of Antarctic Marine Living Resources. Provides two categories of functions: load functions and create functions. Load functions are used to import existing spatial layers from the online CCAMLR GIS such as the ASD boundaries. Create functions are used to create layers from user data such as polygons and grids.

Depends R (>= 3.6), sp, dplyr, raster

License GPL-3

URL <https://github.com/ccamlr/CCAMLRGIS>

Encoding UTF-8

LazyData true

Imports methods, rgdal, rgeos, geosphere, graphics, grDevices,
magrittr

RoxygenNote 7.1.0

Suggests knitr, rmarkdown

VignetteBuilder knitr

NeedsCompilation no

Author Stephane Thanassekos [aut, cre],
Keith Reid [aut],
Lucy Robinson [aut],
Michael D. Sumner [ctb],
Roger Bivand [ctb]

Maintainer Stephane Thanassekos <stephane.thanassekos@ccamlr.org>

Repository CRAN

Date/Publication 2020-03-23 05:20:02 UTC

R topics documented:

add_col	2
add_Cscale	4
add_labels	6
add_RefGrid	8
assign_areas	9
CCAMLRGIS	11
CCAMLRp	12
Clip2Coast	12
Coast	13
create_Lines	14
create_Points	16
create_PolyGrids	17
create_Polys	19
create_Stations	21
Depth_cols	23
Depth_cols2	24
Depth_cuts	25
Depth_cuts2	25
get_depths	26
GridData	27
Labels	28
LineData	29
load_ASDs	29
load_Coastline	30
load_EEZs	31
load_MAs	32
load_MPAs	32
load_RBs	33
load_RefAreas	34
load_SSMUs	35
load_SSRUs	36
PointData	36
PolyData	37
seabed_area	38
SmallBathy	39
Index	40

 add_col

Add colors

Description

Given an input variable, generates either a continuous color gradient or color classes. To be used in conjunction with [add_Cscale](#).

Usage

```
add_col(var, cuts = 100, cols = c("green", "yellow", "red"))
```

Arguments

var	numeric vector of the variable to be colorized. Either all values (in which case all values will be assigned to a color) or only two values (in which case these are considered to be the range of values).
cuts	numeric, controls color classes. Either one value (in which case cuts equally spaced color classes are generated) or a vector (in which cases irregular color classes are generated e.g. <code>c(-10, 0, 100, 2000)</code>).
cols	character vector of colors (see R standard color names here). cols are interpolated along cuts. Color codes as such generated, for example, by rgb may also be used.

Value

list containing the colors for the variable var (given as \$varcol in the output) as well as the single cols and cuts, to be used as inputs in [add_Cscale](#).

See Also

[add_Cscale](#), [create_PolyGrids](#), [R colors](#).

Examples

```
#Example 1: add color to points

MyPoints=create_Points(PointData)
MyCols=add_col(MyPoints$Nfishes) #With default cols and cuts
plot(MyPoints,pch=21,bg=MyCols$varcol,cex=2)

MyCols=add_col(MyPoints$Nfishes,cols=c('blue','red')) #With custom colors - here from blue to red
plot(MyPoints,pch=21,bg=MyCols$varcol,cex=2)

MyCols=add_col(MyPoints$Nfishes,cols=c('blue','red'),cuts=3) #With custom colors and fewer classes
plot(MyPoints,pch=21,bg=MyCols$varcol,cex=2)

#Example 2: add color to a grid, using custom cuts and colors, and adding a color scale (add_Cscale)

#Step 1: Generate your grid
MyGrid=create_PolyGrids(GridData,dlon=2,dlat=1)

#Step 2: Inspect your grid data (e.g. sum of Catch) to determine whether irregular cuts are required
hist(MyGrid$Catch_sum,100)
#In this case (heterogeneously distributed data) irregular cuts would be preferable

#Step 3: Generate colors according to the desired classes (cuts)
Gridcol=add_col(MyGrid$Catch_sum,cuts=c(0,50,100,500,2000,3500),cols=c('yellow','purple'))
```

```
#Step 4: Plot result and add color scale
Mypar=par(mai=c(0,0,0,2)) #Figure margins as c(bottom, left, top, right)
plot(MyGrid,col=Gridcol$varcol) #Use the colors generated by add_col
#Add color scale using cuts and cols generated by add_col
add_Cscale(title='Sum of Catch (t)',cuts=Gridcol$cuts,cols=Gridcol$cols,width=33)
par(Mypar)
```

add_Cscale

Add a color scale

Description

Adds a color scale to plots. Default behavior set for bathymetry. May also be used to place a [legend](#).

Usage

```
add_Cscale(
  pos = "1/1",
  title = "Depth (m)",
  width = 18,
  height = 70,
  cuts = Depth_cuts,
  cols = Depth_cols,
  minVal = NA,
  maxVal = NA,
  fontsize = 1,
  offset = 100,
  lwd = 1,
  mode = "Cscale"
)
```

Arguments

pos	character, indicating the vertical position of the color scale (which is always on the right side of plots). if pos="1/1", the color scale will be centered. if pos="1/2", the color scale will in the top half of the plotting regions. if pos="2/2", the color scale will in the bottom half of the plotting regions.
title	character, title of the color scale.
width	width of the color scale box, expressed in % of the width of the plotting region.
height	height of the color scale box, expressed in % of the height of the plotting region.
cuts	numeric vector of color classes. May be generated via add_col .
cols	character vector of color names. May be generated via add_col .

minVal	If desired, the color scale may be generated starting from the value minVal. See examples.
maxVal	If desired, the color scale may be generated up to the value maxVal. See examples.
fontsize	Size of the text in the color scale.
offset	Controls the horizontal position of the color scale. Increase to distance from the plotting region.
lwd	thickness of lines.
mode	if 'Cscale', the default, the function builds a color scale. if 'Legend', the function gives you the location of a legend , arguments pos, offset and height may be used for adjustments. See examples.

See Also

[SmallBathy](#), [Depth_cuts](#), [Depth_cols](#), [add_col](#), [Depth_cuts2](#), [Depth_cols2](#), [R colors](#), [legend](#).

Examples

```
#Example 1: simple bathymetry plot with color scale
Mypar=par(mai=c(0,0,0,1)) #plot margins as c(bottom, left, top, right)
plot(SmallBathy, breaks=Depth_cuts, col=Depth_cols, legend=FALSE, axes=FALSE, box=FALSE)
add_Cscale(height=95)
par(Mypar)

#' #Example 2: simple bathymetry plot with Fishable Depth range highlight and color scale
Mypar=par(mai=c(0,0,0,1)) #plot margins as c(bottom, left, top, right)
plot(SmallBathy, breaks=Depth_cuts2, col=Depth_cols2, legend=FALSE, axes=FALSE, box=FALSE)
add_Cscale(height=95, cuts=Depth_cuts2, cols=Depth_cols2)
par(Mypar)

#Example 3: Show only values greater than 'minVal'
Mypar=par(mai=c(0,0,0,1)) #plot margins as c(bottom, left, top, right),
plot(SmallBathy, breaks=Depth_cuts, col=Depth_cols, legend=FALSE, axes=FALSE, box=FALSE)
add_Cscale(minVal=-3200)
par(Mypar)

#Example 4: Show only values between 'minVal' and 'maxVal'
Mypar=par(mai=c(0,0,0,1)) #plot margins as c(bottom, left, top, right)
plot(SmallBathy, breaks=Depth_cuts, col=Depth_cols, legend=FALSE, axes=FALSE, box=FALSE)
add_Cscale(minVal=-3200, maxVal=-400)
par(Mypar)

#Example 5: Adding two color scales

#Bathymetry
Mypar=par(mai=c(0,0,0,1)) #plot margins as c(bottom, left, top, right)

plot(SmallBathy, breaks=Depth_cuts, col=Depth_cols, legend=FALSE, axes=FALSE, box=FALSE)
add_Cscale(pos='1/2', height=45, maxVal=-1, minVal=-4000, fontsize=0.8)
```

```

#Some gridded data
MyGrid=create_PolyGrids(GridData,dlon=2,dlat=1)
Gridcol=add_col(MyGrid$Catch_sum,cuts=10)
plot(MyGrid,col=Gridcol$varcol,add=TRUE)
#Add color scale using cuts and cols generated by add_col, note the use of 'round'
add_Cscale(pos='2/2',height=45,title='Catch (t)',
           cuts=round(Gridcol$cuts,1),cols=Gridcol$cols,fontsize=0.8)
par(Mypar)

#Example 6: Adding a color scale and a legend

#Create some point data
MyPoints=create_Points(PointData)

#Crop the bathymetry to match the extent of MyPoints (extended extent)
BathyCr=raster::crop(SmallBathy,raster::extend(raster::extent(MyPoints),100000))
MyPar=par(mai=c(0,0,0,1)) #plot margins as c(bottom, left, top, right)
plot(BathyCr,breaks=Depth_cuts,col=Depth_cols,legend=FALSE,axes=FALSE,box=FALSE)
add_Cscale(pos='1/2',height=45,maxVal=-1,minVal=-4000,fontsize=0.8)

#Plot points with different symbols and colors (see ?points)
Psymbols=c(21,22,23,24)
Pcolors=c('red','green','blue','yellow')
plot(MyPoints[MyPoints$name=='one',],pch=Psymbols[1],bg=Pcolors[1],add=TRUE)
plot(MyPoints[MyPoints$name=='two',],pch=Psymbols[2],bg=Pcolors[2],add=TRUE)
plot(MyPoints[MyPoints$name=='three',],pch=Psymbols[3],bg=Pcolors[3],add=TRUE)
plot(MyPoints[MyPoints$name=='four',],pch=Psymbols[4],bg=Pcolors[4],add=TRUE)

#Add legend with position determined by add_Cscale
Loc=add_Cscale(pos='2/2',height=45,mode='Legend')
legend(Loc,legend=c('one','two','three','four'),title='Vessel',pch=Psymbols,pt.bg=Pcolors,xpd=TRUE)
par(Mypar)

```

add_labels

Add labels

Description

Adds labels to plots. Three modes are available: In 'auto' mode, labels are placed at the centres of polygon parts of spatial objects loaded via the `load_` functions. Internally used in conjunction with [Labels](#). In 'manual' mode, users may click on their plot to position labels. An editable label table is generated to allow fine-tuning of labels appearance, and may be saved for external use. To edit the label table, double-click inside one of its cells, edit the value, then close the table. In 'input' mode, a label table that was generated in 'manual' mode is re-used.

Usage

```

add_labels(
  mode = NULL,

```

```

    layer = NULL,
    fontsize = 1,
    fonttype = 1,
    angle = 0,
    col = "black",
    LabelTable = NULL
)

```

Arguments

mode	either 'auto', 'manual' or 'input'. See Description above.
layer	in 'auto' mode, single or vector of characters, may only be one, some or all of: c("ASDs", "SSRUs", "RBs", "SSMUs", "MAs", "RefAreas", "MPAs", "EEZs").
fontsize	in 'auto' mode, size of the text.
fonttype	in 'auto' mode, type of the text (1 to 4), where 1 corresponds to plain text, 2 to bold face, 3 to italic and 4 to bold italic.
angle	in 'auto' mode, rotation of the text in degrees.
col	in 'auto' mode, color of the text.
LabelTable	in 'input' mode, a label table that was generated in 'manual' mode.

Value

Adds labels to plot. To save a label table generated in 'manual' mode, use: `MyLabelTable=add_labels(mode='auto')`. To re-use that label table, use: `add_labels(mode='input',LabelTable=MyLabelTable)`.

See Also

[Labels](#), [load_ASDs](#), [load_SSRUs](#), [load_RBs](#), [load_SSMUs](#), [load_MAs](#), [load_EEZs](#), [load_RefAreas](#), [load_MPAs](#), [R colors](#).

Examples

```

#Example 1: 'auto' mode
#label ASDs in bold and red
ASDs=load_ASDs()
plot(ASDs)
add_labels(mode='auto',layer='ASDs',fontsize=1,fonttype=2,col='red')
#add MPAs and EEZs and their labels in large, green and vertical text
MPAs=load_MPAs()
EEZs=load_EEZs()
plot(MPAs,add=TRUE,border='green')
plot(EEZs,add=TRUE,border='green')
add_labels(mode='auto',layer=c('EEZs','MPAs'),fontsize=2,col='green',angle=90)

#Example 2: 'manual' mode (you will have to do it yourself)
plot(SmallBathy)

```

```

ASDs=load_ASDs()
plot(ASDs,add=TRUE)
MyLabels=add_labels(mode='manual')

#Example 3: Re-use the label table generated in Example 2
plot(SmallBathy)
plot(ASDs,add=TRUE)
add_labels(mode='input',LabelTable=MyLabels)

```

add_RefGrid

Add a Reference grid

Description

Add a Latitude/Longitude reference grid to maps.

Usage

```

add_RefGrid(
  bb,
  ResLat = 1,
  ResLon = 2,
  LabLon = NA,
  lwd = 1,
  fontsize = 1,
  offset = NA
)

```

Arguments

bb	bounding box of the first plotted object. for example, bb=bbox(SmallBathy) or bb=bbox(MyPolys).
ResLat	Latitude resolution in decimal degrees.
ResLon	Longitude resolution in decimal degrees.
LabLon	Longitude at which Latitude labels should appear. if set, the resulting Reference grid will be circumpolar.
lwd	Line thickness of the Reference grid.
fontsize	Font size of the Reference grid's labels.
offset	offset of the Reference grid's labels (distance to plot border).

See Also[SmallBathy](#)**Examples**

```
#Example 1: Circumpolar grid with Latitude labels at Longitude 0

Mypar=par(mai=c(1,1.5,0.5,0)) #Figure margins as c(bottom, left, top, right)
par(Mypar)
plot(SmallBathy,breaks=Depth_cuts, col=Depth_cols, legend=FALSE,axes=FALSE,box=FALSE)
add_RefGrid(bb=bbox(SmallBathy),ResLat=10,ResLon=20,LabLon = 0)

#Example 2: Local grid around created polygons

MyPolys=create_Polys(PolyData,Densify=TRUE)
BathyC=raster::crop(SmallBathy,MyPolys) #crop the bathymetry to match the extent of MyPolys
Mypar=par(mai=c(0.5,0.5,0.5,0.5)) #Figure margins as c(bottom, left, top, right)
par(Mypar)
plot(BathyC,breaks=Depth_cuts, col=Depth_cols, legend=FALSE,axes=FALSE,box=FALSE)
add_RefGrid(bb=bbox(BathyC),ResLat=2,ResLon=6)
plot(MyPolys,add=TRUE,col='orange',border='brown',lwd=2)
```

assign_areas

*Assign Areas***Description**

Given a set of polygons and a set of point locations (given in decimal degrees), finds in which polygon those locations fall. Finds, for example, in which ASD the given fishing locations occurred.

Usage

```
assign_areas(
  Input,
  Polys,
  AreaNameFormat = "GAR_Long_Label",
  Buffer = 0,
  NamesOut = NULL
)
```

Arguments

Input dataframe containing - at the minimum - Latitudes and Longitudes to be assigned to polygons.

The columns in the Input must be in the following order: Latitude, Longitude, Variable 1, Variable 2, ... Variable x.

Polys	character vector of spatial objects names (e.g., Polys=c('ASDs', 'RBs')). Must be matching the names of the pre-loaded spatial objects (loaded via e.g., ASDs=load_ASDs())
AreaNameFormat	dependent on the polygons loaded. For the Secretariat's spatial objects loaded via 'load_' functions, we have the following: 'GAR_Name' e.g., 'Subarea 88.2' 'GAR_Short_Label' e.g., '882' 'GAR_Long_Label' (default) e.g., '88.2' Several values may be entered if desired (if several Polys are used), e.g. c('GAR_Short_Label', 'GAR_Na in which case AreaNameFormat must be given in the same order as Polys.
Buffer	distance in nautical miles to be added around the Polys of interest. Can be specified for each of the spatial objects named in Polys (e.g., Buffer=c(2,5)). Useful to determine whether locations are within Buffer nautical miles of a polygon.
NamesOut	names of the resulting area columns in the output dataframe, with order matching that of Polys (e.g., NamesOut=c('Recapture_ASD', 'Recapture_RB')). If not provided will be set as equal to Polys.

Value

dataframe with the same structure as the Input, with additional columns corresponding to the Polys used and named after NamesOut.

See Also

[load_ASDs](#), [load_SSRUs](#), [load_RBs](#), [load_SSMUs](#), [load_MAs](#), [load_RefAreas](#), [load_MPs](#), [load_EEZs](#).

Examples

```
#Generate a dataframe
MyData=data.frame(Lat=runif(100,min=-65,max=-50),
                  Lon=runif(100,min=20,max=40))

#Assign ASDs and SSRUs to these locations (first load ASDs and SSRUs)
ASDs=load_ASDs()
SSRUs=load_SSRUs()

MyData=assign_areas(MyData,Polys=c('ASDs','SSRUs'),NamesOut=c('MyASDs','MySSRUs'))

#View(MyData)
table(MyData$MyASDs) #count of locations per ASD
table(MyData$MySSRUs) #count of locations per SSRU
```

CCAMLRGIS

Loads and creates spatial data, including layers and tools that are relevant to CCAMLR activities.

Description

This package provides two broad categories of functions: load functions and create functions.

Load functions

Load functions are used to import CCAMLR geo-referenced layers and include:

- [load_ASDs](#)
- [load_SSRUs](#)
- [load_RBs](#)
- [load_SSMUs](#)
- [load_MAs](#)
- [load_Coastline](#)
- [load_RefAreas](#)
- [load_MPAs](#)
- [load_EEZs](#)

Create functions

Create functions are used to create geo-referenced layers from user-generated data and include:

- [create_Points](#)
- [create_Lines](#)
- [create_Polys](#)
- [create_PolyGrids](#)
- [create_Stations](#)

Vignette

To learn more about CCAMLRGIS, start with the vignette: `browseVignettes(package = "CCAMLRGIS")`

See Also

The CCAMLRGIS package relies on several other package which users may want to familiarize themselves with, namely [sp](#), [raster](#), [rgeos](#) and [rgdal](#).

CCAMLRp

CCAMLRGIS Projection

Description

The CCAMLRGIS package uses the [Lambert azimuthal equal-area projection](http://gis.ccamlr.org/). Source: <http://gis.ccamlr.org/>

Usage

```
data(CCAMLRp)
```

Format

Character string

Value

```
"+proj=laea +lat_0=-90 +lon_0=0 +x_0=0 +y_0=0 +datum=WGS84 +units=m +no_defs +ellps=WGS84 +towgs84=0,0,0"
```

Clip2Coast

Clip Polygons to the Antarctic coastline

Description

Clip Polygons to the [Coast](#) (removes polygon parts that fall on land) and computes the area of the resulting polygon. Uses a SpatialPolygon as input which may be user-generated or created via buffered points (see [create_Points](#)), buffered lines (see [create_Lines](#)) or polygons (see [create_Polys](#)).

Usage

```
Clip2Coast(Input)
```

Arguments

Input Polygon(s) to be clipped.

Value

SpatialPolygon carrying the same data as the Input.

See Also

[Coast](#), [create_Points](#), [create_Lines](#), [create_Polys](#), [create_PolyGrids](#).

Examples

#Example 1: Use Clip2Coast on a pre-generated polygon

```
MyPolys=create_Polys(PolyData,Densify=TRUE,Buffer=c(10,-15,120))
plot(MyPolys,col='red')
plot(Coast[Coast$ID=='All',],col='grey',add=TRUE)
MyPolysClipped=Clip2Coast(MyPolys)
plot(MyPolysClipped,col='blue',add=TRUE)
#View(MyPolysClipped)
```

#Example 2: Use Clip2Coast while creating a polygon, with Clip=TRUE in create_Polys().

```
MyPolysBefore=create_Polys(PolyData,Buffer=c(10,-15,120))
MyPolysAfter=create_Polys(PolyData,Buffer=c(10,-15,120),Clip=TRUE)
plot(MyPolysBefore,col='green')
plot(Coast[Coast$ID=='All',],add=TRUE)
plot(MyPolysAfter,col='red',add=TRUE)
```

Coast

Coast

Description

Coastline polygons generated from [load_Coastline](#) and sub-sampled to only contain data that falls within the CCAMLR boundaries. This spatial object may be subsetted to plot the coastline for selected ASDs or EEZs. Source: <http://gis.ccamlr.org/>

Usage

```
data(Coast)
```

Format

SpatialPolygonsDataFrame

See Also

[Clip2Coast](#).

Examples

```
#Complete coastline:
plot(Coast[Coast$ID=='All',],col='grey')

#ASD 48.1 coastline:
plot(Coast[Coast$ID=='48.1',],col='grey')
```

 create_Lines

Create Lines

Description

Create Lines to display, for example, fishing line locations or tagging data.

Usage

```
create_Lines(
  Input,
  OutputFormat = "ROBJECT",
  OutputName = NULL,
  Buffer = 0,
  Densify = FALSE,
  Clip = FALSE,
  SeparateBuf = TRUE
)
```

Arguments

Input	<p>the name of the Input data as a .csv file or an R dataframe. If a .csv file is used as input, this file must be in your working directory and its name given in quotes e.g. "DataFile.csv".</p> <p>The columns in the Input must be in the following order:</p> <p>Line name, Latitude, Longitude.</p> <p>If a given line is made of more than two points, the locations of points must be given in order, from one end of the line to the other.</p>
OutputFormat	<p>can be an R object or an ESRI Shapefile. if OutputFormat is specified as "ROBJECT" (the default), a spatial object is created in your R environment. if OutputFormat is specified as "SHAPEFILE", an ESRI Shapefile is exported in your working directory.</p>
OutputName	<p>if OutputFormat is specified as "SHAPEFILE", the name of the output shapefile in quotes (e.g. "MyLines") must be provided.</p>
Buffer	<p>Distance in nautical miles by which to expand the lines. Can be specified for each line (as a numeric vector).</p>
Densify	<p>If set to TRUE, additional points between points of equal latitude are added prior to projection (see examples).</p>
Clip	<p>if set to TRUE, polygon parts (from buffered lines) that fall on land are removed (see Clip2Coast).</p>
SeparateBuf	<p>If set to FALSE when adding a Buffer, all spatial objects are merged, resulting in a single spatial object.</p>

Value

Spatial object in your environment or ESRI shapefile in your working directory. Data within the resulting spatial object contains the data provided in the Input plus additional "LengthKm" and "LengthNm" columns which corresponds to the lines lengths, in kilometers and nautical miles respectively.

To see the data contained in your spatial object, type: View(MyLines@data).

See Also

[create_Points](#), [create_Polys](#), [create_PolyGrids](#), [create_Stations](#), [add_RefGrid](#).

Examples

#If your data contains line end locations in separate columns, you may reformat it as follows:

```
#Example data:
MyData=data.frame(
  Line=c(1,2),
  Lat_Start=c(-60,-65),
  Lon_Start=c(-10,5),
  Lat_End=c(-61,-66),
  Lon_End=c(-2,2)
)

#Reformat to us as input as:
Input=data.frame(
  Line=c(MyData$Line,MyData$Line),
  Lat=c(MyData$Lat_Start,MyData$Lat_End),
  Lon=c(MyData$Lon_Start,MyData$Lon_End)
)

#Create lines and plot them
plot(create_Lines(Input))
```

#Example 1: Simple and non-densified lines

```
MyLines=create_Lines(LineData)
plot(MyLines,lwd=2,col=rainbow(length(MyLines)))
```

#Example 2: Simple and densified lines (note the curvature of the purple line)

```
MyLines=create_Lines(LineData,Densify=TRUE)
plot(MyLines,lwd=2,col=rainbow(length(MyLines)))
```

#Example 3: Densified, buffered and clipped lines

```
MyLines=create_Lines(LineData,Densify=TRUE,Buffer=c(10,40,50,80,100),Clip=TRUE)
```

```

plot(MyLines,lwd=2,col=rainbow(length(MyLines)))
plot(Coast[Coast$ID=='All',],col='grey',add=TRUE)

#Example 4: Buffered and grouped lines
MyLines=create_Lines(LineData,Densify=TRUE,Buffer=30,SeparateBuf=FALSE)
plot(MyLines,lwd=2,border='blue')

```

create_Points

Create Points

Description

Create Points to display point locations. Buffering points may be used to produce bubble charts.

Usage

```

create_Points(
  Input,
  OutputFormat = "OBJECT",
  OutputName = NULL,
  Buffer = 0,
  Clip = FALSE,
  SeparateBuf = TRUE
)

```

Arguments

Input	the name of the Input data as a .csv file or an R dataframe. If a .csv file is used as input, this file must be in your working directory and its name given in quotes e.g. "DataFile.csv". The columns in the Input must be in the following order: Latitude, Longitude, Variable 1, Variable 2, ... Variable x
OutputFormat	can be an R object or an ESRI Shapefile. if OutputFormat is specified as "OBJECT" (the default), a spatial object is created in your R environment. if OutputFormat is specified as "SHAPEFILE", an ESRI Shapefile is exported in your working directory.
OutputName	if OutputFormat is specified as "SHAPEFILE", the name of the output shapefile in quotes (e.g. "MyPoints") must be provided.
Buffer	Radius in nautical miles by which to expand the points. Can be specified for each point (as a numeric vector).
Clip	if set to TRUE, polygon parts (from buffered points) that fall on land are removed (see Clip2Coast).
SeparateBuf	If set to FALSE when adding a Buffer, all spatial objects are merged, resulting in a single spatial object.

Value

Spatial object in your environment or ESRI shapefile in your working directory. Data within the resulting spatial object contains the data provided in the Input plus additional "x" and "y" columns which corresponds to the projected points locations and may be used to label points (see examples).

To see the data contained in your spatial object, type: `View(MyPoints@data)`.

See Also

[create_Lines](#), [create_Polys](#), [create_PolyGrids](#), [create_Stations](#), [add_RefGrid](#).

Examples

```
#Example 1: Simple points with labels
```

```
MyPoints=create_Points(PointData)
plot(MyPoints)
text(MyPoints$x,MyPoints$y,MyPoints$name,adj=c(0.5,-0.5),xpd=TRUE)
```

```
#Example 2: Simple points with labels, highlighting one group of points with the same name
```

```
MyPoints=create_Points(PointData)
plot(MyPoints)
text(MyPoints$x,MyPoints$y,MyPoints$name,adj=c(0.5,-0.5),xpd=TRUE)
plot(MyPoints[MyPoints$name=='four',],bg='red',pch=21,cex=1.5,add=TRUE)
```

```
#Example 3: Buffered points with radius proportional to catch
```

```
MyPoints=create_Points(PointData,Buffer=0.5*PointData$Catch)
plot(MyPoints,col='green')
text(MyPoints$x,MyPoints$y,MyPoints$name,adj=c(0.5,0.5),xpd=TRUE)
```

```
#Example 4: Buffered points with radius proportional to catch and clipped to the Coast
```

```
MyPoints=create_Points(PointData,Buffer=2*PointData$Catch,Clip=TRUE)
plot(MyPoints,col='cyan')
plot(Coast[Coast$ID=='All',],add=TRUE,col='grey')
```

Description

Create a polygon grid to spatially aggregate data in cells of chosen size. Cell size may be specified in degrees or as a desired area in square kilometers (in which case cells are of equal area).

Usage

```
create_PolyGrids(
  Input,
  OutputFormat = "ROBJECT",
  OutputName = NULL,
  dlon = NA,
  dlat = NA,
  Area = NA,
  cuts = 100,
  cols = c("green", "yellow", "red")
)
```

Arguments

Input	the name of the Input data as a .csv file or an R dataframe. If a .csv file is used as input, this file must be in your working directory and its name given in quotes e.g. "DataFile.csv". The columns in the Input must be in the following order: Latitude, Longitude, Variable 1, Variable 2 ... Variable x.
OutputFormat	can be an R object or an ESRI Shapefile. if OutputFormat is specified as "ROBJECT" (the default), a SpatialPolygonDataFrame is created in your R environment. if OutputFormat is specified as "SHAPEFILE", an ESRI Shapefile is exported in your working directory.
OutputName	if OutputFormat is specified as "SHAPEFILE", the name of the output shapefile in quotes (e.g. "MyGrid") must be provided.
dlon	width of the grid cells in decimal degrees of longitude.
dlat	height of the grid cells in decimal degrees of latitude.
Area	area, in square kilometers, of the grid cells.
cuts	Number of desired color classes.
cols	Desired colors. If more that one color is provided, a linear color gradient is generated.

Value

Spatial object in your environment or ESRI shapefile in your working directory. Data within the resulting spatial object contains the data provided in the Input after aggregation within cells. For each Variable, the minimum, maximum, mean, sum, count, standard deviation, and, median of values in each cell is returned.

To see the data contained in your spatial object, type: `View(MyGrid@data)`.

In addition, colors are generated for each aggregated values according to the chosen cuts (numerical classes) and cols (colors). To generate a custom color scale, refer to [add_col](#) and [add_Cscale](#).

See Also

[create_Points](#), [create_Lines](#), [create_Polys](#), [create_Stations](#), [add_RefGrid](#), [add_col](#), [add_Cscale](#).

Examples

```
#Example 1: Simple grid, using automatic colors

MyGrid=create_PolyGrids(GridData,dlon=2,dlat=1)
#View(MyGrid@data)
plot(MyGrid,col=MyGrid$Col_Catch_sum)

#Example 2: Equal area grid, using automatic colors

MyGrid=create_PolyGrids(GridData,Area=10000)
plot(MyGrid,col=MyGrid$Col_Catch_sum)

#Example 3: Equal area grid, using custom cuts and colors

#MyGrid=create_PolyGrids(GridData,Area=10000,cuts=c(0,50,100,500,2000,3500),cols=c('blue','red'))
plot(MyGrid,col=MyGrid$Col_Catch_sum)

#Example 4: Equal area grid, using custom cuts and colors, and adding a color scale (add_Cscale)

#Step 1: Generate your grid
MyGrid=create_PolyGrids(GridData,Area=10000)

#Step 2: Inspect your gridded data (e.g. sum of Catch) to
#determine whether irregular cuts are required
hist(MyGrid$Catch_sum,100)
#In this case (heterogeneously distributed data) irregular cuts would be preferable

#Step 3: Generate colors according to the desired classes (cuts)
Gridcol=add_col(MyGrid$Catch_sum,cuts=c(0,50,100,500,2000,3500),cols=c('yellow','purple'))

#Step 4: Plot result and add color scale
Mypar=par(mai=c(0,0,0,2)) #Figure margins as c(bottom, left, top, right)
plot(MyGrid,col=Gridcol$varcol) #Use the colors generated by add_col
#Add color scale using cuts and cols generated by add_col
add_Cscale(title='Sum of Catch (t)',cuts=Gridcol$cuts,cols=Gridcol$cols,width=24)
par(Mypar)
```

Description

Create Polygons such as proposed Research Blocks or Marine Protected Areas.

Usage

```
create_Polys(
  Input,
  OutputFormat = "ROBJECT",
  OutputName = NULL,
  Buffer = 0,
  Densify = TRUE,
  Clip = FALSE,
  SeparateBuf = TRUE
)
```

Arguments

Input	the name of the Input data as a .csv file or an R dataframe. If a .csv file is used as input, this file must be in your working directory and its name given in quotes e.g. "DataFile.csv". The columns in the Input must be in the following order: Polygon name, Latitude, Longitude. Latitudes and Longitudes must be given clockwise.
OutputFormat	can be an R object or an ESRI Shapefile. if OutputFormat is specified as "ROBJECT" (the default), a SpatialPolygonDataFrame is created in your R environment. if OutputFormat is specified as "SHAPEFILE", an ESRI Shapefile is exported in your working directory.
OutputName	if OutputFormat is specified as "SHAPEFILE", the name of the output shapefile in quotes (e.g. "MyPolygons") must be provided.
Buffer	Distance in nautical miles by which to expand the polygons. Can be specified for each polygon (as a numeric vector).
Densify	If set to TRUE, additional points between points of equal latitude are added prior to projection (see examples).
Clip	if set to TRUE, polygon parts that fall on land are removed (see Clip2Coast).
SeparateBuf	If set to FALSE when adding a Buffer, all spatial objects are merged, resulting in a single spatial object.

Value

Spatial object in your environment or ESRI shapefile in your working directory. Data within the resulting spatial object contains the data provided in the Input plus and additional "AreaKm2" column which corresponds to the areas, in square kilometers, of your polygons. Also, columns "Labx" and "Laby" may be used to add labels to polygons.

To see the data contained in your spatial object, type: View(MyPolygons@data).

See Also

[create_Points](#), [create_Lines](#), [create_PolyGrids](#), [create_Stations](#), [add_RefGrid](#).

Examples

```
#Example 1: Simple and non-densified polygons

MyPolys=create_Polys(PolyData,Densify=FALSE)
plot(MyPolys,col='blue')
text(MyPolys$Labx,MyPolys$Laby,MyPolys$ID,col='white')

#Example 2: Simple and densified polygons (note the curvature of iso-latitude lines)

MyPolys=create_Polys(PolyData)
plot(MyPolys,col='red')
text(MyPolys$Labx,MyPolys$Laby,MyPolys$ID,col='white')

#Example 3: Buffered and clipped polygons

MyPolysBefore=create_Polys(PolyData,Buffer=c(10,-15,120))
MyPolysAfter=create_Polys(PolyData,Buffer=c(10,-15,120),Clip=TRUE)
plot(MyPolysBefore,col='green')
plot(Coast[Coast$ID=='All',],add=TRUE)
plot(MyPolysAfter,col='red',add=TRUE)
text(MyPolysAfter$Labx,MyPolysAfter$Laby,MyPolysAfter$ID,col='white')

#Example 4: Buffered and grouped polygons
MyPolys=create_Polys(PolyData,Buffer=80,SeparateBuf=FALSE)
plot(MyPolys,border='blue',lwd=3)
```

create_Stations

Create Stations

Description

Create random point locations inside a polygon and within bathymetry strata constraints. A distance constraint between stations may also be used if desired.

Usage

```
create_Stations(  
  Poly,
```

```

    Bathy,
    Depths,
    N = NA,
    Nauto = NA,
    dist = NA,
    Buf = 1000,
    ShowProgress = FALSE
  )

```

Arguments

Poly	single polygon inside which stations will be generated. May be created using create_Polys .
Bathy	bathymetry raster with the appropriate projection , such as this one .
Depths	vector of depths. For example, if the depth strata required are 600 to 1000 and 1000 to 2000, <code>Depths=c(-600, -1000, -2000)</code> .
N	vector of number of stations required in each depth strata, therefore <code>length(N)</code> must equal <code>length(Depths)-1</code> .
Nauto	instead of specifying N, a number of stations proportional to the areas of the depth strata may be created. Nauto is the maximum number of stations required in any depth stratum.
dist	if desired, a distance constraint in nautical miles may be applied. For example, if <code>dist=2</code> , stations will be at least 2 nautical miles apart.
Buf	distance in meters from isobaths. Useful to avoid stations falling on strata boundaries.
ShowProgress	if set to TRUE, a progress bar is shown (<code>create_Stations</code> may take a while).

Value

Spatial object in your environment. Data within the resulting object contains the strata and stations locations in both projected space ("x" and "y") and degrees of Latitude/Longitude.

To see the data contained in your spatial object, type: `View(MyStations@data)`.

See Also

[create_Polys](#), [SmallBathy](#), [add_RefGrid](#).

Examples

```

#First, create a polygon within which stations will be created

MyPolys=create_Polys(PolyData,Densify=TRUE)
plot(MyPolys)
text(MyPolys$Labx,MyPolys$Laby,MyPolys$ID)
#Subsample MyPolys to only keep the polygon with ID 'one'

```

```

MyPoly=MyPolys[MyPolys$ID=='one',]
plot(MyPoly,col='green',add=TRUE)

#Second (optional), crop your bathymetry raster to match the extent of your polygon

BathyCropped=raster::crop(SmallBathy,MyPoly)

#Example 1: Set numbers of stations, no distance constraint

MyStations=create_Stations(MyPoly,BathyCropped,Depths=c(-550,-1000,-1500,-2000),N=c(20,15,10))
Mypar=par(mai=c(0,0,0,2)) #Figure margins as c(bottom, left, top, right)
plot(BathyCropped,breaks=Depth_cuts, col=Depth_cols, legend=FALSE,axes=FALSE,box=FALSE)
add_Cscale(offset = 50,height = 90,fontsize = 0.8,width=25)
plot(MyPoly,add=TRUE,border='red',lwd=2)
raster::contour(BathyCropped,levels=c(-550,-1000,-1500,-2000),add=TRUE)
plot(MyStations,add=TRUE,col='orange')
par(Mypar)

#Example 2: Set numbers of stations, with distance constraint

MyStations=create_Stations(MyPoly,BathyCropped,
                           Depths=c(-550,-1000,-1500,-2000),N=c(20,15,10),dist=10)
Mypar=par(mai=c(0,0,0,2)) #Figure margins as c(bottom, left, top, right)
plot(BathyCropped,breaks=Depth_cuts, col=Depth_cols, legend=FALSE,axes=FALSE,box=FALSE)
add_Cscale(offset = 50,height = 90,fontsize = 0.8,width=25)
plot(MyPoly,add=TRUE,border='red',lwd=2)
raster::contour(BathyCropped,levels=c(-550,-1000,-1500,-2000),add=TRUE)
plot(MyStations[MyStations$Stratum=='550-1000',],pch=21,bg='yellow',add=TRUE)
plot(MyStations[MyStations$Stratum=='1000-1500',],pch=21,bg='orange',add=TRUE)
plot(MyStations[MyStations$Stratum=='1500-2000',],pch=21,bg='red',add=TRUE)
par(Mypar)

#Example 3: Automatic numbers of stations, with distance constraint

MyStations=create_Stations(MyPoly,BathyCropped,Depths=c(-550,-1000,-1500,-2000),Nauto=30,dist=10)
Mypar=par(mai=c(0,0,0,2)) #Figure margins as c(bottom, left, top, right)
plot(BathyCropped,breaks=Depth_cuts, col=Depth_cols, legend=FALSE,axes=FALSE,box=FALSE)
add_Cscale(offset = 50,height = 90,fontsize = 0.8,width=25)
plot(MyPoly,add=TRUE,border='red',lwd=2)
raster::contour(BathyCropped,levels=c(-550,-1000,-1500,-2000),add=TRUE)
plot(MyStations[MyStations$Stratum=='550-1000',],pch=21,bg='yellow',add=TRUE)
plot(MyStations[MyStations$Stratum=='1000-1500',],pch=21,bg='orange',add=TRUE)
plot(MyStations[MyStations$Stratum=='1500-2000',],pch=21,bg='red',add=TRUE)
par(Mypar)

```

Description

Set of standard colors to plot bathymetry, to be used in conjunction with [Depth_cuts](#).

Usage

```
data(Depth_cols)
```

Format

Character vector

See Also

[Depth_cols2](#), [add_col](#), [add_Cscale](#), [SmallBathy](#).

Examples

```
plot(SmallBathy,breaks=Depth_cuts,col=Depth_cols,axes=FALSE,box=FALSE)
```

Depth_cols2

Bathymetry colors with Fishable Depth range

Description

Set of colors to plot bathymetry and highlight Fishable Depth range, to be used in conjunction with [Depth_cuts2](#).

Usage

```
data(Depth_cols2)
```

Format

Character vector

See Also

[Depth_cols](#), [add_col](#), [add_Cscale](#), [SmallBathy](#).

Examples

```
plot(SmallBathy,breaks=Depth_cuts2,col=Depth_cols2,axes=FALSE,box=FALSE)
```

Depth_cuts	<i>Bathymetry depth classes</i>
------------	---------------------------------

Description

Set of depth classes to plot bathymetry, to be used in conjunction with [Depth_cols](#).

Usage

```
data(Depth_cuts)
```

Format

Numeric vector

See Also

[Depth_cuts2](#), [add_col](#), [add_Cscale](#), [SmallBathy](#).

Examples

```
plot(SmallBathy,breaks=Depth_cuts,col=Depth_cols,axes=FALSE,box=FALSE)
```

Depth_cuts2	<i>Bathymetry depth classes with Fishable Depth range</i>
-------------	---

Description

Set of depth classes to plot bathymetry and highlight Fishable Depth range, to be used in conjunction with [Depth_cols2](#).

Usage

```
data(Depth_cuts2)
```

Format

Numeric vector

See Also

[Depth_cuts](#), [add_col](#), [add_Cscale](#), [SmallBathy](#).

Examples

```
plot(SmallBathy,breaks=Depth_cuts2,col=Depth_cols2,axes=FALSE,box=FALSE)
```

get_depths

*Get depths of locations from bathymetry raster***Description**

Given a bathymetry raster and an input dataframe of point locations (given in decimal degrees), computes the depths at these locations using bilinear interpolation (using [extract](#)). Optionally can also compute the horizontal distance of locations to chosen isobaths.

Usage

```
get_depths(
  Input,
  Bathy,
  d = 10000,
  Isobaths = NA,
  IsoLocs = FALSE,
  ShowProgress = FALSE
)
```

Arguments

Input	dataframe with, at least, Latitudes and Longitudes. The columns in the Input must be in the following order: Latitude, Longitude, Variable 1, Variable 2, ... Variable x
Bathy	bathymetry raster with the appropriate projection , such as this one . It is recommended to use a raster of higher resolution than SmallBathy .
d	distance in meters, used to group locations by distance and speed up computations (by cutting the bathymetry raster into small pieces matching the extent of grouped locations). Lower values make computations faster but at the risk of not finding distances to isobaths (when desired).
Isobaths	Depths to which the horizontal distances to locations are computed, if required.
IsoLocs	If TRUE, the locations on the Isobaths that are closest to the locations given in the Input are added to the exported dataframe.
ShowProgress	if set to TRUE, a progress bar is shown (get_depths may take a while).

Value

dataframe with the same structure as the Input with additional columns, where 'x' and 'y' are the projected locations, 'd' is the depth, 'D_iso', 'X_iso' and 'Y_iso' are the horizontal distances and closest point location on 'Isobaths'. All units are in meters.

See Also

[SmallBathy](#), [create_Points](#), [create_Stations](#), [extract](#).

Examples

```
#Generate a dataframe
MyData=data.frame(Lat=PointData$Lat,
Lon=PointData$Lon,
Catch=PointData$Catch)

#Example 1: get depths of locations
MyDataD=get_depths(MyData,SmallBathy)
#View(MyDataD)
plot(MyDataD$d,MyDataD$Catch,xlab='Depth',ylab='Catch',pch=21,bg='blue') #Plot of catch vs depth

#Example 2: get depths of locations and distance to isobath -3000m

MyDataD=get_depths(MyData,SmallBathy,Isobaths=-3000,IsoLocs=TRUE,d=200000,ShowProgress=TRUE)
plot(MyDataD$x,MyDataD$y,pch=21,bg='green')
contour(SmallBathy,levels=-3000,add=TRUE,col='blue',maxpixels=1000000)
segments(x0=MyDataD$x,
         y0=MyDataD$y,
         x1=MyDataD$x_3000,
         y1=MyDataD$y_3000,col='red')
```

GridData

Example dataset for create_PolyGrids

Description

To be used in conjunction with [create_PolyGrids](#).

Usage

```
data(GridData)
```

Format

DataFrame

See Also

[create_PolyGrids](#).

Examples

```
#View(GridData)

MyGrid=create_PolyGrids(Input=GridData,dlon=2,dlat=1)
plot(MyGrid,col=MyGrid$Col_Catch_sum)
```

Labels

Polygon labels

Description

Labels for the layers obtained via 'load_' functions. Positions correspond to the centroids of polygon parts. Can be used in conjunction with [add_labels](#).

Usage

```
data(Labels)
```

Format

```
dataframe
```

See Also

[add_labels](#), [load_ASDs](#), [load_SSRUs](#), [load_RBs](#), [load_SSMUs](#), [load_MAs](#), [load_EEZs](#), [load_RefAreas](#), [load_MPsAs](#).

Examples

```
#View(Labels)

ASDs=load_ASDs()
plot(ASDs)
add_labels(mode='auto',layer='ASDs',fontsize=1,fonttype=2)
```

LineData	<i>Example dataset for create_Lines</i>
----------	---

Description

To be used in conjunction with [create_Lines](#).

Usage

```
data(LineData)
```

Format

DataFrame

See Also

[create_Lines](#).

Examples

```
#View(LineData)

MyLines=create_Lines(LineData)
plot(MyLines,lwd=2)
```

load_ASDs	<i>Load CCAMLR statistical Areas, Subareas and Divisions</i>
-----------	--

Description

Download the up-to-date spatial layer from the [online CCAMLRGIS](#) and load it to your environment. The layer's Metadata is accessible by clicking on the red 'i' in the list of layers available on the [online CCAMLRGIS](#). See examples for offline use.

Usage

```
load_ASDs()
```

See Also

[load_SSRUs](#), [load_RBs](#), [load_SSMUs](#), [load_MAs](#), [load_Coastline](#), [load_RefAreas](#), [load_MPAs](#), [load_EEZs](#).

Examples

```
#When online:
ASDs=load_ASDs()
plot(ASDs)

#If going offline in the future: load and save as RData when online,
# then reload RData when offline:
ASDs=load_ASDs()
EEZs=load_EEZs()
save(list=c('ASDs','EEZs'), file = file.path(tempdir(), "CCAMLRlayers.RData"))
rm(ASDs,EEZs)
load(file.path(tempdir(), "CCAMLRlayers.RData"))
```

load_Coastline	<i>load the full CCAMLR Coastline</i>
----------------	---------------------------------------

Description

Download the up-to-date spatial layer from the [online CCAMLRGIS](#) and load it to your environment. The layer's Metadata is accessible by clicking on the red 'i' in the list of layers available on the [online CCAMLRGIS](#). See examples for offline use. Note that this coastline expands further north than [Coast](#).

Usage

```
load_Coastline()
```

See Also

[load_ASDs](#), [load_SSRUs](#), [load_RBs](#), [load_SSMUs](#), [load_MAs](#), [load_RefAreas](#), [load_MPAs](#), [load_EEZs](#).

Examples

```
#When online:
Coastline=load_Coastline()
plot(Coastline)

#If going offline in the future: load and save as RData when online,
# then reload RData when offline:
Coastline=load_Coastline()
EEZs=load_EEZs()
```

```
save(list=c('Coastline','EEZs'), file = file.path(tempdir(), "CCAMLRLayers.RData"))
rm(Coastline,EEZs)
load(file.path(tempdir(), "CCAMLRLayers.RData"))
```

load_EEZs

Load Exclusive Economic Zones

Description

Download the up-to-date spatial layer from the [online CCAMLRGIS](#) and load it to your environment. The layer's Metadata is accessible by clicking on the red 'i' in the list of layers available on the [online CCAMLRGIS](#). See examples for offline use.

Usage

```
load_EEZs()
```

See Also

[load_ASDs](#), [load_SSRUs](#), [load_RBs](#), [load_SSMUs](#), [load_MAs](#), [load_Coastline](#), [load_RefAreas](#), [load_MPAs](#).

Examples

```
#When online:
EEZs=load_EEZs()
plot(EEZs)

#If going offline in the future: load and save as RData when online,
# then reload RData when offline:
MPAs=load_MPAs()
EEZs=load_EEZs()
save(list=c('MPAs','EEZs'), file = file.path(tempdir(), "CCAMLRLayers.RData"))
rm(MPAs,EEZs)
load(file.path(tempdir(), "CCAMLRLayers.RData"))
```

load_MAs

Load CCAMLR Management Areas

Description

Download the up-to-date spatial layer from the [online CCAMLRGIS](#) and load it to your environment. The layer's Metadata is accessible by clicking on the red 'i' in the list of layers available on the [online CCAMLRGIS](#). See examples for offline use.

Usage

```
load_MAs()
```

See Also

[load_ASDs](#), [load_SSRUs](#), [load_RBs](#), [load_SSMUs](#), [load_Coastline](#), [load_RefAreas](#), [load_MPAs](#), [load_EEZs](#).

Examples

```
#When online:
MAs=load_MAs()
plot(MAs)

#If going offline in the future: load and save as RData when online,
# then reload RData when offline:
MAs=load_MAs()
EEZs=load_EEZs()
save(list=c('MAs','EEZs'), file = file.path(tempdir(), "CCAMLRlayers.RData"))
rm(MAs,EEZs)
load(file.path(tempdir(), "CCAMLRlayers.RData"))
```

load_MPAs

load CCAMLR Marine Protected Areas

Description

Download the up-to-date spatial layer from the [online CCAMLRGIS](#) and load it to your environment. The layer's Metadata is accessible by clicking on the red 'i' in the list of layers available on the [online CCAMLRGIS](#). See examples for offline use.

Usage

```
load_MPAs()
```

See Also

[load_ASDs](#), [load_SSRUs](#), [load_RBs](#), [load_SSMUs](#), [load_MAs](#), [load_Coastline](#), [load_RefAreas](#), [load_EEZs](#).

Examples

```
#When online:
MPAs=load_MPAs()
plot(MPAs)

#If going offline in the future: load and save as RData when online,
# then reload RData when offline:
MPAs=load_MPAs()
EEZs=load_EEZs()
save(list=c('MPAs','EEZs'), file = file.path(tempdir(), "CCAMLRlayers.RData"))
rm(MPAs,EEZs)
load(file.path(tempdir(), "CCAMLRlayers.RData"))
```

load_RBs

Load CCAMLR Research Blocks

Description

Download the up-to-date spatial layer from the [online CCAMLRGIS](#) and load it to your environment. The layer's Metadata is accessible by clicking on the red 'i' in the list of layers available on the [online CCAMLRGIS](#). See examples for offline use.

Usage

```
load_RBs()
```

See Also

[load_ASDs](#), [load_SSRUs](#), [load_SSMUs](#), [load_MAs](#), [load_Coastline](#), [load_RefAreas](#), [load_MPAs](#), [load_EEZs](#).

Examples

```
#When online:
RBs=load_RBs()
plot(RBs)

#If going offline in the future: load and save as RData when online,
# then reload RData when offline:
RBs=load_RBs()
EEZs=load_EEZs()
save(list=c('RBs','EEZs'), file = file.path(tempdir(), "CCAMLRlayers.RData"))
rm(RBs,EEZs)
load(file.path(tempdir(), "CCAMLRlayers.RData"))
```

load_RefAreas

Load CCAMLR Reference Areas

Description

Download the up-to-date spatial layer from the [online CCAMLRGIS](#) and load it to your environment. The layer's Metadata is accessible by clicking on the red 'i' in the list of layers available on the [online CCAMLRGIS](#). See examples for offline use.

Usage

```
load_RefAreas()
```

See Also

[load_ASDs](#), [load_SSRUs](#), [load_RBs](#), [load_SSMUs](#), [load_MAs](#), [load_Coastline](#), [load_MPAs](#), [load_EEZs](#).

Examples

```
#When online:
RefAreas=load_RefAreas()
plot(RefAreas)

#If going offline in the future: load and save as RData when online,
# then reload RData when offline:
RefAreas=load_RefAreas()
EEZs=load_EEZs()
```

```
save(list=c('RefAreas','EEZs'), file = file.path(tempdir(), "CCAMLRLayers.RData"))
rm(RefAreas,EEZs)
load(file.path(tempdir(), "CCAMLRLayers.RData"))
```

load_SSMUs

Load CCAMLR Small Scale Management Units

Description

Download the up-to-date spatial layer from the [online CCAMLRGIS](#) and load it to your environment. The layer's Metadata is accessible by clicking on the red 'i' in the list of layers available on the [online CCAMLRGIS](#). See examples for offline use.

Usage

```
load_SSMUs()
```

See Also

[load_ASDs](#), [load_SSRUs](#), [load_RBs](#), [load_MAs](#), [load_Coastline](#), [load_RefAreas](#), [load_MPAs](#), [load_EEZs](#).

Examples

```
#When online:
SSMUs=load_SSMUs()
plot(SSMUs)

#If going offline in the future: load and save as RData when online,
# then reload RData when offline:
SSMUs=load_SSMUs()
EEZs=load_EEZs()
save(list=c('SSMUs','EEZs'), file = file.path(tempdir(), "CCAMLRLayers.RData"))
rm(SSMUs,EEZs)
load(file.path(tempdir(), "CCAMLRLayers.RData"))
```

load_SSRUs	<i>load CCAMLR Small Scale Research Units</i>
------------	---

Description

Download the up-to-date spatial layer from the [online CCAMLRGIS](#) and load it to your environment. The layer's Metadata is accessible by clicking on the red 'i' in the list of layers available on the [online CCAMLRGIS](#). See examples for offline use.

Usage

```
load_SSRUs()
```

See Also

[load_ASDs](#), [load_RBs](#), [load_SSMUs](#), [load_MAs](#), [load_Coastline](#), [load_RefAreas](#), [load_MPAs](#), [load_EEZs](#).

Examples

```
#When online:
SSRUs=load_SSRUs()
plot(SSRUs)

#If going offline in the future: load and save as RData when online,
# then reload RData when offline:
SSRUs=load_SSRUs()
EEZs=load_EEZs()
save(list=c('SSRUs','EEZs'), file = file.path(tempdir(), "CCAMLRlayers.RData"))
rm(SSRUs,EEZs)
load(file.path(tempdir(), "CCAMLRlayers.RData"))
```

PointData	<i>Example dataset for create_Points</i>
-----------	--

Description

To be used in conjunction with [create_Points](#).

Usage

```
data(PointData)
```

Format

DataFrame

See Also

[create_Points.](#)

Examples

```
#View(PointData)

MyPoints=create_Points(PointData)
plot(MyPoints)
text(MyPoints$x,MyPoints$y,MyPoints$name,adj=c(0.5,-0.5),xpd=TRUE)
plot(MyPoints[MyPoints$name=='four',],bg='red',pch=21,cex=1.5,add=TRUE)
```

PolyData

Example dataset for create_Polys

Description

To be used in conjunction with [create_Polys.](#)

Usage

```
data(PolyData)
```

Format

DataFrame

See Also

[create_Polys.](#)

Examples

```
#View(PolyData)

MyPolys=create_Polys(PolyData,Densify=TRUE)
plot(MyPolys,col='green',add=TRUE)
text(MyPolys$Labx,MyPolys$Laby,MyPolys$ID)
plot(MyPolys[MyPolys$ID=='three',],border='red',lwd=3,add=TRUE)
```

seabed_area	<i>Calculate planimetric seabed area</i>
-------------	--

Description

Calculate planimetric seabed area within polygons and depth strata in square kilometers.

Usage

```
seabed_area(Bathy, Polys, depth_classes = c(-600, -1800))
```

Arguments

Bathy	bathymetry raster with the appropriate projection , such as this one . It is recommended to use a raster of higher resolution than SmallBathy .
Polys	polygon(s) within which the areas of depth strata are computed.
depth_classes	numeric vector of strata depths. for example, <code>depth_classes=c(-600,-1000,-2000)</code> . If the values <code>-600,-1800</code> are given within <code>depth_classes</code> , the computed area will be labelled as 'Fishable_area'.

Value

dataframe with the name of polygons in the first column and the area for each strata in the following columns. Note that polygon names are taken from the first column in the data of the input `SpatialPolygonDataframe`.

See Also

[SmallBathy](#), [create_Polys](#), [load_RBs](#).

Examples

```
#Example 1: Compute fishable area in Research Blocks using the SmallBathy (not recommended)

RBs=load_RBs()
RBs@data[,1]=RBs$GAR_Short_Label #Take the 'GAR_Short_Label' as polygon names
FishDepth=seabed_area(SmallBathy,RBs)
#View(FishDepth)

#Example 2: Compute various strata areas within user-generated polygons

MyPolys=create_Polys(PolyData,Densify=TRUE)
FishDepth=seabed_area(SmallBathy,MyPolys,depth_classes=c(0,-200,-600,-1800,-3000,-5000))
#View(FishDepth)
```

SmallBathy

Small bathymetry dataset

Description

Bathymetry dataset derived from the [GEBCO 2019](#) dataset. Subsampled using raster's [resample](#) function, using the nearest neighbor method and a 10,000m resolution. Projected using the CCAMLR standard projection ([CCAMLRp](#)). To highlight the Fishable Depth range, use [Depth_cols2](#) and [Depth_cuts2](#). **To be only used for large scale illustrative purposes.** Please refer to the package's vignette (`browseVignettes("CCAMLRGIS")`; see Section 1) to produce a higher resolution raster, suitable for analyses.

Usage

```
data(SmallBathy)
```

Format

raster

See Also

[add_col](#), [add_Cscale](#), [Depth_cols](#), [Depth_cuts](#), [Depth_cols2](#), [Depth_cuts2](#), [get_depths](#), [create_Stations](#).

Examples

```
plot(SmallBathy,breaks=Depth_cuts,col=Depth_cols,axes=FALSE,box=FALSE)
```

Index

`add_col`, 2, 4, 5, 18, 19, 24, 25, 39
`add_Cscale`, 2, 3, 4, 18, 19, 24, 25, 39
`add_labels`, 6, 28
`add_RefGrid`, 8, 15, 17, 19, 21, 22
`assign_areas`, 9

`CCAMLRGIS`, 11
`CCAMLRp`, 12, 39
`Clip2Coast`, 12, 13, 14, 16, 20
`Coast`, 12, 13, 30
`create_Lines`, 11, 12, 14, 17, 19, 21, 29
`create_Points`, 11, 12, 15, 16, 19, 21, 26, 36, 37
`create_PolyGrids`, 3, 11, 12, 15, 17, 17, 21, 27
`create_Polys`, 11, 12, 15, 17, 19, 19, 22, 37, 38
`create_Stations`, 11, 15, 17, 19, 21, 21, 26, 39

`Depth_cols`, 5, 23, 24, 25, 39
`Depth_cols2`, 5, 24, 24, 25, 39
`Depth_cuts`, 5, 24, 25, 25, 39
`Depth_cuts2`, 5, 24, 25, 25, 39

`extract`, 26

`get_depths`, 26, 39
`GridData`, 27

`Labels`, 6, 7, 28
`legend`, 4, 5
`LineData`, 29
`load_ASDs`, 7, 10, 11, 28, 29, 30–36
`load_Coastline`, 11, 13, 29, 30, 31–36
`load_EEZs`, 7, 10, 11, 28–30, 31, 32–36
`load_MAs`, 7, 10, 11, 28–31, 32, 33–36
`load_MPAs`, 7, 10, 11, 28–32, 32, 33–36
`load_RBs`, 7, 10, 11, 28–33, 33, 34–36, 38
`load_RefAreas`, 7, 10, 11, 28–33, 34, 35, 36
`load_SSMUs`, 7, 10, 11, 28–34, 35, 36
`load_SSRUs`, 7, 10, 11, 28–35, 36

`PointData`, 36
`PolyData`, 37
`projection`, 22, 26, 38

`resample`, 39
`rgb`, 3

`seabed_area`, 38
`SmallBathy`, 5, 9, 22, 24–26, 38, 39

`this one`, 22, 26, 38