

Package ‘SDLfilter’

May 4, 2020

Type Package

Title Filtering and Assessing Sample Size of Tracking Data

Version 2.0.0

Date 2020-05-04

Author Takahiro Shimada

Maintainer Takahiro Shimada <taka.shimada@gmail.com>

Description Functions to filter GPS and/or Argos locations, as well as assessing sample sizes for the analysis of animal distributions. The filters remove temporal and spatial duplicates, fixes located at a given height from estimated high tide line, and locations with high error as described in Shimada et al. (2012) <doi:10.3354/meps09747> and Shimada et al. (2016) <doi:10.1007/s00227-015-2771-0>. Sample sizes for the analysis of animal distributions can be assessed by the conventional area-based approach or the alternative probability-based approach as described in Shimada et al. (in prep).

Depends R (>= 3.5.0), ggplot2

Imports plotKML, sp, raster, trip, data.table, gridExtra, ggsn, stats, maps, pracma, plyr, ggmap, lubridate, dplyr

License GPL-2 | file LICENSE

URL <https://github.com/TakahiroShimada/SDLfilter>

BugReports <https://github.com/TakahiroShimada/SDLfilter/issues>

LazyData true

Encoding UTF-8

RoxygenNote 7.1.0

NeedsCompilation no

Repository CRAN

Date/Publication 2020-05-04 13:40:06 UTC

R topics documented:

asymptote	2
Australia	4
bathymodel	4
boot_area	5
boot_overlap	6
curtis	8
ddfilter	8
ddfilter_loop	10
ddfilter_speed	12
depthfilter	13
distfilter	16
dupfilter	17
dupfilter_exact	19
dupfilter_qi	20
dupfilter_space	21
dupfilter_time	22
kml_track	23
map_track	24
percent_vol	27
SandyStrait	27
tidalplane	28
tidedata	28
track_param	29
turtle	30
turtle2	31
vmax	31
vmaxlp	32
Index	34

asymptote	<i>Horizontal asymptotes of rational functions</i>
-----------	--

Description

Function to find horizontal asymptotes of a rational function.

Usage

```
asymptote(
  data = NULL,
  x = NULL,
  y = NULL,
  d1 = 1,
  d2 = 1,
  threshold = 0.95,
```

```
    proportional = TRUE  
  )
```

Arguments

<code>data</code>	An output object from <code>boot_overlap</code> or <code>boot_area</code> .
<code>x, y</code>	Numeric vectors of independent (<code>x</code>) and dependent (<code>y</code>) variables. These parameters will be ignored if <code>data</code> is supplied.
<code>d1, d2</code>	Maximal degrees of numerator (<code>d1</code>) and denominator (<code>d2</code>) of a rational function.
<code>threshold</code>	Threshold value for considering an asymptote. Once the <code>y</code> value reaches the threshold, it is considered that an asymptote is reached.
<code>proportional</code>	If TRUE (default), a threshold is calculated as <i>estimated asymptote</i> * <i>threshold</i> . If FALSE, the value specified in <i>threshold</i> is used in the analysis.

Details

This function fits a rational function to the input data. When an output object from `boot_overlap` or `boot_area` is supplied, a rational function is fit to the means of the bootstrap results (e.g. mean overlap probability) as a function of `x` (e.g. sample size). It then estimates horizontal asymptotes and identifies the sample size when an asymptote is considered.

Value

A list containing a data frame (rational function fit associated with `x` values), an estimated horizontal asymptote, and the minimum sample size if an asymptote is reached.

Author(s)

Takahiro Shimada

References

Press, W. H., S. A. Teukolsky, W. T. Vetterling, and B. P. Flannery (2007). *Numerical Recipes: The Art of Numerical Computing*. Third Edition, Cambridge University Press, New York.

Shimada et al., (in prep)

See Also

[boot_overlap](#), [boot_area](#)

Australia

A map of Australia

Description

This map layer outlines the coast of Australia.

Usage

Australia

Format

A data.frame

bathymodel

Bathymetry model for Sandy Strait, Australia

Description

A high resolution bathymetry model (100 m) for the Sandy Strait region developed by Beaman, R.J. (2010).

Usage

bathymodel

Format

A RasterLayer

Source

<https://www.deepreef.org/>

References

Beaman, R.J. (2010) Project 3DGBR: A high-resolution depth model for the Great Barrier Reef and Coral Sea. *Marine and Tropical Sciences Research Facility (MTSRF) Project 2.5i.1a Final Report*, MTSRF, Cairns, Australia, pp. 13 plus Appendix 1.

Description

Function to calculate collective areas (merged x% Utilisation Distributions or UD_s) of n individuals by bootstrapping.

Usage

```
boot_area(  
  data,  
  cell.size = NA,  
  R = 1000,  
  percent = 50,  
  quantiles = c(0.25, 0.5, 0.75)  
)
```

Arguments

data	A matrix or list of RasterLayer objects. Each row of the matrix or each RasterLayer object contains a utilisation distribution (or other statistics that sums to 1 - e.g. proportion of time spent). The grid size and geographical extent must be consistent across each row of the matrix or each RasterLayer object. The function assumes that each column of the matrix is associated with a unique geographical location or that each RasterLayer has exactly the same geographical extent and resolution.
cell.size	A numeric value specifying the grid cell size of the input data in metres.
R	An integer specifying the number of iterations.
percent	An integer specifying the percent volume of each UD to be considered in the analysis.
quantiles	A vector or a number to specify the quantiles to be calculated in the summary of the results.

Details

This function calculates collective areas (e.g. 50% UD_s) of 1 to n individuals by bootstrapping.

Value

A list containing two data frames - raw results and summary (mean, sd, sem and quantiles at each sample size).

Author(s)

Takahiro Shimada

References

Shimada et al. (in prep)

Examples

```
## Not run:

#1 Utilisation distributions of flatback turtles.
data(curtis)

#2 Calculate collective areas from 1000 random permutation
area <- boot_area(curtis, R = 1000, percent = 50)

#3 Find the minimum sample size required to estimate the general distribution.
a <- asymptote(area)

#4 Plot the mean collective area and rational function fit relative to the sample sizes.
ggplot(data = area$summary)+
  geom_point(aes(x = N, y = mu/1e+6), alpha = 0.5) +
  geom_path(data = a$results, aes(x = x, y = ys/1e+6)) +
  labs(x = "N", y = expression(Area~(km^2)))

## End(Not run)
```

boot_overlap

Bootstrap overlaps between Utilisation Distributions (UDs)

Description

Function to calculate overlaps between UD's relative to sample size by bootstrapping.

Usage

```
boot_overlap(
  data,
  R = 1000,
  method = "PHR",
  percent = 100,
  quantiles = c(0.25, 0.5, 0.75)
)
```

Arguments

data A matrix or list of RasterLayer objects. Each row of the matrix or each RasterLayer object contains a utilisation distribution (or other statistics that sums to 1 - e.g. proportion of time spent). **The grid size and geographical extent must be consistent across each row of the matrix or each RasterLayer object.** The

	function assumes that each column of the matrix is associated with a unique geographical location or that each RasterLayer has exactly the same geographical extent and resolution.
R	An integer specifying the number of iterations.
method	The overlap quantification method. "HR" is for the proportion of an individual's home range overlapped by the known habitats of other individuals. "PHR" is for the probability of an individual to be within the known habitats of other individuals. "VI", "BA" and "UDOI" quantify overlap between UD's using the full probabilistic properties as described in Fieberg and Kochanny (2005). For the latter three options, the function calculates overlaps between each additional UD and a collective UD. To generate a collective UD, each UD is overlaid and averaged at each grid cell so the probability density of the collective UD sums up to 1 (Shimada et al. in prep).
percent	An integer specifying the percent volume of each UD to be considered in the analysis.
quantiles	A vector or a number to specify the quantiles to be calculated in the summary of the results.

Details

This function calculates and bootstraps overlap between UD's based on the areas ("HR"), areas of collective UD's and the probability distribution of each individual ("PHR"), or the probability distribution of an individual and an averaged probability distribution of collective individuals ("VI", "BA", "UDOI").

Value

A list containing two data frames - raw results and summary (mean, sd, sem and quantiles at each sample size).

Author(s)

Takahiro Shimada

References

Fieberg J & Kochanny CO (2005) Quantifying home-range overlap: The importance of the utilization distribution. *The Journal of Wildlife Management*, 69(4), 1346–1359. doi: 10.2193/0022-541x(2005)69[1346:Qhotio]2.0.Co;2

Shimada et al. in prep

Examples

```
## Not run:

#1 Utilisation uistributions of flatback turtles.
data( curtis )

#2 Calculate overlap probability from 1000 random permutation.
```

```

overlap <- boot_overlap(curtis, R = 1000, method = "PHR")

#3 Find the minimum sample size required to estimate the general distribution.
a <- asymptote(overlap)

#4 Plot the mean probability and rational function fit relative to the sample sizes.
ggplot(data = overlap$summary)+
  geom_point(aes(x = N, y = mu), alpha = 0.5) +
  geom_path(data = a$results, aes(x = x, y = ys)) +
  geom_vline(xintercept = a$min.n, linetype = 2) +
  labs(x = "N", y = "Overlap probability")

## End(Not run)

```

curtis

Flatback turtle utilisation distributions

Description

Inter-nesting utilisation distributions of 29 flatback turtles (*Natator depressus*) that nested in Curtis Island, Australia. As a demonstration, the resolution of the UDs is reduced to 1km grid instead of 50m as used in Shimada et al (in prep).

Usage

```
curtis
```

Format

A list of 29 RasterLayer objects

Source

Shimada T et al, (in prep)

ddfilter

Filter locations using a data driven filter

Description

Function to remove locations by a data driven filter as described in Shimada et al. (2012).

Usage

```
ddfilter(sdata, vmax = 8.9, vmaxlp = 1.8, qi = 4, ia = 90, method = 1)
```


Arguments

<code>sdata</code>	A data frame containing columns with the following headers: "id", "DateTime", "lat", "lon", "qi". The function filters the input data by the unique "id". "DateTime" is date & time in class <code>POSIXct</code> . "lat" and "lon" are the latitude and longitude of each location in decimal degrees. "qi" is the numerical quality index associated with each location fix where a greater number indicates a higher accuracy (e.g. number of GPS satellites used for estimation).
<code>vmax</code>	A numeric value specifying a threshold of speed from a previous and/or to a subsequent fix. Default is 8.9km/h. If this value is unknown, it can be estimated from <code>sdata</code> using the function <code>vmax</code> .
<code>vmaxlp</code>	A numeric value specifying a threshold of speed, which is used to evaluate the locations of loop trips. Default is 1.8 km/h. If this value is unknown, it can be estimated from <code>sdata</code> using the function <code>vmaxlp</code> .
<code>qi</code>	An integer specifying a threshold of quality index, which is used to evaluate the locations of loop trips. Default is 4.
<code>ia</code>	An integer specifying a threshold of inner angle, which is used to evaluate the locations of loop trips. Default is 90 degrees.
<code>method</code>	An integer specifying how locations should be filtered with <code>vmax</code> . A location is removed if the speed from a previous and(1)/or(2) to a subsequent location exceeds <code>vmax</code> . Default is 1 (both way).

Details

Locations are removed if the speed from a previous and/or to a subsequent location exceeds `vmax`, or if all of the following criteria apply: the associated quality index is less than or equal to `qi`, the inner angle is less than or equal to `ia` and the speed either from a previous or to a subsequent location exceeds `vmaxlp`. If `vmax` and `vmaxlp` are unknown, they can be estimated using the functions `vmax` and `vmaxlp` respectively.

Value

The input data is returned without locations identified by this filter. The following columns are added: "pTime", "sTime", "pDist", "sDist", "pSpeed", "sSpeed", "inAng". "pTime" and "sTime" are hours from a previous and to a subsequent fix respectively. "pDist" and "sDist" are straight distances in kilometres from a previous and to a subsequent fix respectively. "pSpeed" and "sSpeed" are linear speed from a previous and to a subsequent fix respectively. "inAng" is the degree between the bearings of lines joining successive location points.

Author(s)

Takahiro Shimada

References

Shimada T, Jones R, Limpus C, Hamann M (2012) Improving data retention and home range estimates by data-driven screening. *Marine Ecology Progress Series* 457:171-180 doi:[10.3354/meps09747](https://doi.org/10.3354/meps09747)

See Also

[ddfilter_speed](#), [ddfilter_loop](#), [vmax](#), [vmaxlp](#)

Examples

```
##### Load data sets
## Fastloc GPS data obtained from a green turtle
data(turtle)

## A Map for the example site
data(Australia)
data(SandyStrait)

##### Filter temporal and/or spatial duplicates
turtle.dup <- dupfilter(turtle, step.time=5/60, step.dist=0.001)

##### ddfilter
## Using the built-in function to estimate the threshold speeds
V <- vmax(turtle.dup)
VLP <- vmaxlp(turtle.dup)
turtle.dd <- ddfilter(turtle.dup, vmax=V, vmaxlp=VLP)

## Or using user specified threshold speeds
turtle.dd <- ddfilter(turtle.dup, vmax=9.9, qi=4, ia=90, vmaxlp=2.0)

##### Plot data removed or retained by ddfilter
## Entire area
p1<-map_track(turtle.dup, bmap=Australia, point.size = 2, line.size = 0.5, axes.lab.size = 0,
              sb.distance=200, multiplot = FALSE, point.bg = "red",
              title.size=15, title="Entire area")[[1]] +
  geom_point(aes(x=lon, y=lat), data=turtle.dd, size=2, fill="yellow", shape=21)+
  geom_point(aes(x=x, y=y), data=data.frame(x=c(154, 154), y=c(-22, -22.5)),
            size=3, fill=c("yellow", "red"), shape=21) +
  annotate("text", x=c(154.3, 154.3), y=c(-22, -22.5), label=c("Retained", "Removed"),
         colour="black", size=4, hjust = 0)

## Zoomed in
p2<-map_track(turtle.dup, bmap=SandyStrait, xlim=c(152.7, 153.2), ylim=c(-25.75, -25.24)),
              axes.lab.size = 0, sb.distance=10, point.size = 2, point.bg = "red", line.size = 0.5,
              multiplot = FALSE, title.size=15, title="Zoomed in")[[1]] +
  geom_path(aes(x=lon, y=lat), data=turtle.dd, size=0.5, colour="black", linetype=1) +
  geom_point(aes(x=lon, y=lat), data=turtle.dd, size=2, colour="black", shape=21, fill="yellow")

gridExtra::marrangeGrob(list(p1, p2), nrow=1, ncol=2)
```

Description

A partial component of `ddfilter`, although works as a stand-alone function. This function removes locations by speed, inner angle, and quality index as described in Shimada et al. (2012).

Usage

```
ddfilter_loop(sdata, qi = 4, ia = 90, vmaxlp = 1.8)
```

Arguments

<code>sdata</code>	A data frame containing columns with the following headers: "id", "DateTime", "lat", "lon", "qi". The function filters the input data by the unique "id". "DateTime" is date & time in class <code>POSIXct</code> . "lat" and "lon" are the latitude and longitude of each location in decimal degrees. "qi" is the numerical quality index associated with each location fix where a greater number indicates a higher accuracy (e.g. number of GPS satellites used for estimation).
<code>qi</code>	An integer specifying a threshold of quality index, which is used to evaluate the locations of loop trips. Default is 4.
<code>ia</code>	An integer specifying a threshold of inner angle, which is used to evaluate the locations of loop trips. Default is 90 degrees.
<code>vmaxlp</code>	A numeric value specifying a threshold of speed, which is used to evaluate the locations of loop trips. Default is 1.8 km/h. If this value is unknown, it can be estimated from <code>sdata</code> using the function <code>vmaxlp</code> .

Details

This function removes locations if all of the following criteria apply: the number of source satellites are less than or equal to `qi`, the inner angle is less than and equal to `ia` and the speed either from a previous or to a subsequent location exceeds `vmaxlp`. If `vmaxlp` is unknown, it can be estimated using the function `vmaxlp`.

Value

The input data is returned without locations identified by this filter. The following columns are added: "pTime", "sTime", "pDist", "sDist", "pSpeed", "sSpeed", "inAng". "pTime" and "sTime" are hours from a previous and to a subsequent fix respectively. "pDist" and "sDist" are straight distances in kilometres from a previous and to a subsequent fix respectively. "pSpeed" and "sSpeed" are linear speed from a previous and to a subsequent fix respectively. "inAng" is the degree between the bearings of lines joining successive location points.

Author(s)

Takahiro Shimada

References

Shimada T, Jones R, Limpus C, Hamann M (2012) Improving data retention and home range estimates by data-driven screening. *Marine Ecology Progress Series* 457:171-180 doi:[10.3354/meps09747](https://doi.org/10.3354/meps09747)

See Also

[ddfilter](#), [ddfilter_speed](#), [vmaxlp](#)

ddfilter_speed	<i>Filter locations by speed</i>
----------------	----------------------------------

Description

A partial component of [ddfilter](#), although works as a stand-alone function. This function removes locations by a given threshold speed as described in Shimada et al. (2012).

Usage

```
ddfilter_speed(sdata, vmax = 8.9, method = 1)
```

Arguments

sdata	A data frame containing columns with the following headers: "id", "DateTime", "lat", "lon", "qi". The function filters the input data by the unique "id". "DateTime" is date & time in class POSIXct . "lat" and "lon" are the latitude and longitude of each location in decimal degrees. "qi" is the numerical quality index associated with each location fix where a greater number indicates a higher accuracy (e.g. number of GPS satellites used for estimation).
vmax	A numeric value specifying a threshold of speed from a previous and/or to a subsequent fix. Default is 8.9km/h. If this value is unknown, it can be estimated from <i>sdata</i> using the function vmax .
method	An integer specifying how locations should be filtered with <i>vmax</i> . A location is removed if the speed from a previous and(1)/or(2) to a subsequent location exceeds <i>vmax</i> . Default is 1 (both way).

Details

This function removes locations if the speed from a previous and/or to a subsequent location exceeds a given threshold speed. If *vmax* is unknown, it can be estimated using the function [vmax](#).

Value

The input data is returned without locations identified by this filter. The following columns are added: "pTime", "sTime", "pDist", "sDist", "pSpeed", "sSpeed". "pTime" and "sTime" are hours from a previous and to a subsequent fix respectively. "pDist" and "sDist" are straight distances in kilometres from a previous and to a subsequent fix respectively. "pSpeed" and "sSpeed" are linear speed from a previous and to a subsequent fix respectively.

Author(s)

Takahiro Shimada

References

Shimada T, Jones R, Limpus C, Hamann M (2012) Improving data retention and home range estimates by data-driven screening. *Marine Ecology Progress Series* 457:171-180 doi:[10.3354/meps09747](https://doi.org/10.3354/meps09747)

See Also

[ddfilter](#), [ddfilter_loop](#), [vmax](#), [track_param](#)

depthfilter

Filter locations by water depth

Description

Function to filter locations according to bathymetry and tide.

Usage

```
depthfilter(  
  sdata,  
  bathymetry,  
  extract = "bilinear",  
  qi = 4,  
  tide,  
  tidal.plane,  
  type = "HT",  
  height = 0,  
  filter = TRUE  
)
```

Arguments

sdata	A data frame containing columns with the following headers: "id", "DateTime", "lat", "lon", "qi". The function filters the input data by the unique "id". "DateTime" is date & time in class <code>POSIXct</code> . "lat" and "lon" are the latitude and longitude of each location in decimal degrees. "qi" is the numerical quality index associated with each location fix where a greater number indicates a higher accuracy (e.g. number of GPS satellites used for estimation).
bathymetry	A <code>RasterLayer</code> object containing bathymetric data in metres. Negative and positive values indicate below and above the water respectively. Geographic coordinate system is WGS84.
extract	Method to extract cell values from the raster layer as inherited from the <code>extract</code> function of the raster package. Default is bilinear.
qi	An integer specifying a threshold of quality index. <code>depthfilter</code> does not filter a location that is associated with a quality index higher than this threshold. Default is 4.

tide	A data frame containing columns with the following headers: "tideDT", "reading", "standard.port". "tideDT" is date & time in class <code>POSIXct</code> at each observation. "reading" is the observed tidal height in metres. "standard.port" is the identifier of each tidal station.
tidal.plane	A data frame containing columns with the following headers: "standard.port", "secondary.port", "lat", "lon", "timeDiff", "datumDiff". "standard.port" is the identifier for a tidal observation station. "secondary.port" is the identifier for a station at which tide is only predicted using tidal records observed at the related standard port. "lat" and "lon" are the latitude and longitude of each secondary port in decimal degrees. "timeDiff" is the time difference between standard port and its associated secondary port. "datumDiff" is the baseline difference in metres if bathymetry and tidal observations/predictions uses different datum (e.g. LAT and MSL).
type	The type of water depth considered in the filtering process. "exp" is for the water depth experienced by the animal at the time. This option may be applicable to species that remain in water at all times (e.g. dugongs, dolphins, etc). "HT" is for the water depth at the nearest high tide (default). This option is useful for animals that use inter-tidal zones at high tide and may remain there even after the tide drops (e.g. some sea turtles).
height	A numerical value to adjust the water depth an animal is likely to use. Default is 0 m. This parameter is useful if the minimum water depth used by the animal is known. For example, a dugong is unlikely to use water shallower than its body height (e.g. ~0.5 m) so it may be sensible to consider the fix is an error if the estimated water depth is shallower than its body height. A negative value indicates below the water surface. For the dugong example, to remove locations for which the water depth was <0.5 m, it should be specified as; height = -0.5. By supplying the body height to this argument, all the locations recorded shallower than its body will be removed.
filter	Default is TRUE. If FALSE, the function does not filter locations but it still returns estimates of the water depth experienced by the animal at each location.

Details

The function examines each location according to the water depth experienced by the animal or the water depth at the nearest high tide. The function looks for the closest match between each fix and tidal observations or predictions in temporal and spatial scales. When *filter* is disabled, the function does not filter locations but returns the estimated water depth of each location with the tide effect considered (bathymetry + tide).

Value

When *filter* option is enabled, this function filters the input data and returns with two additional columns; "depth.exp", "depth.HT". "depth.exp" is the estimated water depth at each location at the time of location fixing. "depth.HT" is the estimated water depth at the nearest high tide at each location.

Note

The input data must not contain temporal or spatial duplicates.

Author(s)

Takahiro Shimada

References

Shimada T, Limpus C, Jones R, Hazel J, Groom R, Hamann M (2016) Sea turtles return home after intentional displacement from coastal foraging areas. *Marine Biology* 163:1-14 doi:[10.1007/s00227-015-2771-0](https://doi.org/10.1007/s00227-015-2771-0)

Beaman, R.J. (2010) Project 3DGBR: A high-resolution depth model for the Great Barrier Reef and Coral Sea. *Marine and Tropical Sciences Research Facility (MTRSF) Project 2.5i.1a Final Report*, MTRSF, Cairns, Australia, pp. 13 plus Appendix 1.

See Also

[dupfilter](#), [ddfilter](#)

Examples

```
#### Load data sets
## Fastloc GPS data obtained from a green turtle
data(turtle)

## Bathymetry model developed by Beaman (2010)
data(bathymodel)

## A tidal plane for the example site
data(tidalplane)

## Tidal observations and predictions for the example site
data(tidedata)

## Maps for the example site
data(SandyStrait)

#### Remove temporal and/or spatial duplicates
turtle.dup <- dupfilter(turtle)

#### Remove biologically unrealistic fixes
turtle.dd <- ddfilter(turtle.dup, vmax=9.9, qi=4, ia=90, vmaxlp=2.0)

#### Apply depthfilter
turtle.dep <- depthfilter(sdata=turtle.dd,
                        bathymetry=bathymodel,
                        tide=tidedata,
                        tidal.plane=tidalplane)
```

```
#### Plot data removed or retained by depthfilter
map_track(turtle.dd, bgmap=SandyStrait, point.bg = "red", point.size = 2, line.size = 0.5,
          axes.lab.size = 0, title.size=0, sb.distance=10, multiplot = FALSE)[[1]] +
geom_point(aes(x=lon, y=lat), data=turtle.dep, size=2, fill="yellow", shape=21)+
geom_point(aes(x=x, y=y), data=data.frame(x=c(152.68, 152.68), y=c(-25.3, -25.34)),
          size=3, fill=c("yellow", "red"), shape=21) +
annotate("text", x=c(152.7, 152.7), y=c(-25.3, -25.34), label=c("Retained", "Removed"),
        colour="black", size=4, hjust = 0)
```

distfilter

Filter locations by distance

Description

This function removes locations that are located beyond a specified distance.

Usage

```
distfilter(sdata, max.dist = 100, method = 1)
```

Arguments

sdata	A data frame containing columns with the following headers: "id", "DateTime", "lat", "lon". The function filters the input data by the unique "id". "DateTime" is date & time in class <code>POSIXct</code> . "lat" and "lon" are the latitude and longitude of each location in decimal degrees.
max.dist	A numeric value specifying a threshold of distance between successive locations. Default is 100 km.
method	An integer specifying how locations should be filtered with <i>max.dist</i> . A location is removed if the distance from a previous and(1)/or(2) to a subsequent location exceeds <i>max.dist</i> . Default is 1 (both way).

Details

This function removes locations if the distance from a previous and/or to a subsequent location exceeds *max.dist*.

Value

The input data is returned without locations identified by this filter. The following columns are added: "pDist", "sDist". "pDist" and "sDist" are straight distances in kilometres from a previous and to a subsequent fix respectively.

Author(s)

Takahiro Shimada

Examples

```
##### Load data sets
## Fastloc GPS data obtained from a green turtle
data(turtle)

## A Map for the example site
data(Australia)
data(SandyStrait)

##### Filter temporal and/or spatial duplicates
turtle.dup <- dupfilter(turtle, step.time=5/60, step.dist=0.001)

##### distfilter
turtle.dist <- distfilter(turtle.dup)

##### Plot data removed or retained by ddfilter
## Entire area
p1 <- map_track(turtle.dup, bgmap=Australia, point.size = 2, line.size = 0.5, axes.lab.size = 0,
               sb.distance=200, multiplot = FALSE, point.bg = "red",
               title.size=15, title="Entire area")[[1]] +
  geom_point(aes(x=lon, y=lat), data=turtle.dist, size=2, fill="yellow", shape=21)+
  geom_point(aes(x=x, y=y), data=data.frame(x=c(154, 154), y=c(-22, -22.5)),
            size=3, fill=c("yellow", "red"), shape=21) +
  annotate("text", x=c(154.3, 154.3), y=c(-22, -22.5), label=c("Retained", "Removed"),
         colour="black", size=4, hjust = 0)

## Zoomed in
p2 <- map_track(turtle.dup, bgmap=SandyStrait, xlim=c(152.7, 153.2), ylim=c(-25.75, -25.24)),
       axes.lab.size = 0, sb.distance=10, point.size = 2, point.bg = "red", line.size = 0.5,
       multiplot = FALSE, title.size=15, title="Zoomed in")[[1]] +
  geom_path(aes(x=lon, y=lat), data=turtle.dist, size=0.5, colour="black", linetype=1) +
  geom_point(aes(x=lon, y=lat), data=turtle.dist, size=2, colour="black", shape=21, fill="yellow")

gridExtra::marrangeGrob(list(p1, p2), nrow=1, ncol=2)
```

dupfilter

Filter temporal and/or spatial duplicates

Description

Function to filter temporal and spatial duplicates in tracking data and retain only a single fix per time and location.

Usage

```
dupfilter(sdata, step.time = 0, step.dist = 0, conditional = FALSE)
```

Arguments

sdata	A data frame containing columns with the following headers: "id", "DateTime", "lat", "lon", "qi". The function filters the input data by the unique "id". "DateTime" is date & time in class <code>POSIXct</code> . "lat" and "lon" are the latitude and longitude of each location in decimal degrees. "qi" is the numerical quality index associated with each location fix where a greater number indicates a higher accuracy (e.g. the number of GPS satellites involved in estimation).
step.time	Consecutive locations less than or equal to <i>step.time</i> apart are considered temporal duplicates. Default is 0 hours.
step.dist	Consecutive locations less than or equal to <i>step.dist</i> apart are considered spatial duplicates. Default is 0 kilometres.
conditional	If TRUE, spatial duplicates are filtered only if they are less than or equal to <i>step.time</i> apart. Default is FALSE.

Details

This function filters temporal and spatial duplicates in tracking data. It first filters temporally and spatially exact locations. It then looks for temporal duplicates and retains a fix with the highest quality index. When temporal or spatial duplicates are associated with the same quality index, the function retains a location that is nearest from a previous and to a subsequent location.

Value

The input data frame is returned containing only a single fix (latitude/longitude pair) per time and location.

Author(s)

Takahiro Shimada

References

Shimada T, Limpus C, Jones R, Hazel J, Groom R, Hamann M (2016) Sea turtles return home after intentional displacement from coastal foraging areas. *Marine Biology* 163:1-14 doi:[10.1007/s00227-015-2771-0](https://doi.org/10.1007/s00227-015-2771-0)

See Also

[dupfilter_exact](#), [dupfilter_qi](#), [dupfilter_time](#), [dupfilter_space](#), [track_param](#)

Examples

```
#### Load data sets
## Fastloc GPS data obtained from a green turtle
data(turtle)

#### Apply dupfilter
turtle.dup <- dupfilter(turtle)
```

dupfilter_exact	<i>Filter temporally and spatially exact duplicates</i>
-----------------	---

Description

Function to filter temporally and spatially exact locations in tracking data.

Usage

```
dupfilter_exact(sdata)
```

Arguments

sdata	A data frame containing columns with the following headers: "id", "DateTime", "lat", "lon", "qi". The function filters the input data by the unique "id". "DateTime" is date & time in class <code>POSIXct</code> . "lat" and "lon" are the latitude and longitude of each location in decimal degrees. "qi" is the numerical quality index associated with each location fix where a greater number indicates a higher accuracy (e.g. the number of GPS satellites involved in estimation).
-------	--

Details

This is a partial component of `dupfilter`, although works as a stand-alone function. It looks for temporally and spatially exact locations and retains only a single fix (latitude/longitude pair) per time and location.

Value

The input data frame is returned with temporally and spatially exact duplicates removed.

Author(s)

Takahiro Shimada

References

Shimada T, Limpus C, Jones R, Hazel J, Groom R, Hamann M (2016) Sea turtles return home after intentional displacement from coastal foraging areas. *Marine Biology* 163:1-14 doi:[10.1007/s00227-015-2771-0](https://doi.org/10.1007/s00227-015-2771-0)

See Also

[dupfilter](#), [dupfilter_qi](#), [dupfilter_time](#), [dupfilter_space](#), [track_param](#)

dupfilter_qi	<i>Filter temporal duplicates by quality index</i>
--------------	--

Description

Function to filter temporal duplicates in tracking data by quality index.

Usage

```
dupfilter_qi(sdata = sdata, step.time = 0)
```

Arguments

sdata	A data frame containing columns with the following headers: "id", "DateTime", "qi". The function filters the input data by the unique "id". "DateTime" is date & time in class <code>POSIXct</code> . "qi" is the numerical quality index associated with each location fix where a greater number indicates a higher accuracy (e.g. the number of GPS satellites involved in estimation).
step.time	Consecutive locations less than or equal to <i>step.time</i> apart are considered temporal duplicates. Default is 0 hours.

Details

This function is a partial component of `dupfilter`, although works as a stand-alone function. It looks for temporal duplicates and retains a fix with the highest quality index.

Value

The input data frame is returned with temporal duplicates removed by the quality index.

Author(s)

Takahiro Shimada

References

Shimada T, Limpus C, Jones R, Hazel J, Groom R, Hamann M (2016) Sea turtles return home after intentional displacement from coastal foraging areas. *Marine Biology* 163:1-14 doi:[10.1007/s00227-015-2771-0](https://doi.org/10.1007/s00227-015-2771-0)

See Also

[dupfilter](#), [dupfilter_exact](#), [dupfilter_time](#), [dupfilter_space](#), [track_param](#)

dupfilter_space	<i>Filter spatial duplicates</i>
-----------------	----------------------------------

Description

Function to filter spatial duplicates in tracking data.

Usage

```
dupfilter_space(sdata, step.time = 0, step.dist = 0, conditional = FALSE)
```

Arguments

sdata	A data frame containing columns with the following headers: "id", "DateTime", "lat", "lon", "qi". The function filters the input data by the unique "id". "DateTime" is date & time in class <code>POSIXct</code> . "lat" and "lon" are the latitude and longitude of each location in decimal degrees. "qi" is the numerical quality index associated with each location fix where a greater number indicates a higher accuracy (e.g. the number of GPS satellites involved in estimation).
step.time	Consecutive locations less than or equal to <i>step.time</i> apart are considered temporal duplicates. Default is 0 hours.
step.dist	Consecutive locations less than or equal to <i>step.dist</i> apart are considered spatial duplicates. Default is 0 kilometres.
conditional	If TRUE, spatial duplicates are filtered only if they are less than or equal to <i>step.time</i> apart. Default is FALSE.

Details

This function is a partial component of `dupfilter`, although works as a stand-alone function. First it identifies spatial duplicates by searching for consecutive fixes that were located within *step.dist*. For each group of spatial duplicates, the function then retains a single fix that is nearest from a previous and to a subsequent location.

Value

The input data frame is returned with spatial duplicates removed.

Note

A minimum of two locations per id is required.

Author(s)

Takahiro Shimada

References

Shimada T, Limpus C, Jones R, Hazel J, Groom R, Hamann M (2016) Sea turtles return home after intentional displacement from coastal foraging areas. *Marine Biology* 163:1-14 doi:[10.1007/s00227-015-2771-0](https://doi.org/10.1007/s00227-015-2771-0)

See Also

[dupfilter](#), [dupfilter_exact](#), [dupfilter_time](#), [dupfilter_qi](#), [track_param](#)

dupfilter_time	<i>Filter temporal duplicates</i>
----------------	-----------------------------------

Description

Function to filter temporal duplicates that are associated with the same quality index.

Usage

```
dupfilter_time(sdata, step.time = 0)
```

Arguments

sdata	A data frame containing columns with the following headers: "id", "DateTime", "lat", "lon", "qi". The function filters the input data by the unique "id". "DateTime" is date & time in class POSIXct . "lat" and "lon" are the latitude and longitude of each location in decimal degrees. "qi" is the numerical quality index associated with each location fix where a greater number indicates a higher accuracy (e.g. the number of GPS satellites involved in estimation).
step.time	Consecutive locations less than or equal to <i>step.time</i> apart are considered temporal duplicates. Default is 0 hours.

Details

This is a partial component of [dupfilter](#), although works as a stand-alone function. First it identifies temporal duplicates by searching for consecutive locations that were obtained within *step.time*. For each group of temporal duplicates, the function then retains a single fix that is nearest from a previous and to a subsequent location.

Value

The input data frame is returned with temporal duplicates removed.

Author(s)

Takahiro Shimada

References

Shimada T, Limpus C, Jones R, Hazel J, Groom R, Hamann M (2016) Sea turtles return home after intentional displacement from coastal foraging areas. *Marine Biology* 163:1-14 doi:[10.1007/s00227-015-2771-0](https://doi.org/10.1007/s00227-015-2771-0)

See Also

[dupfilter](#), [dupfilter_exact](#), [dupfilter_qi](#), [dupfilter_space](#), [track_param](#)

kml_track

Generate KML from locations

Description

Function to generate a kml file from tracking data. This is a wrapper of [plotKML](#) and [kml](#), specifically designed to generate a kml file from tracking data.

Usage

```
kml_track(sdata, sdata.CRS = "WGS", output = "open", type = "point", ...)
```

Arguments

sdata	A data frame containing location data of one individual, with the following column headers: "id", "DateTime", "lat", "lon". "id" is the identifier of the individual. "DateTime" is date & time in class POSIXct . "lat" and "lon" are the latitude and longitude of each location in decimal degrees.
sdata.CRS	Coordinate reference system (CRS) for the input location data. If the input data is not in WGS, the specific CRS needs to be supplied as a PROJ.4 notation or EPSG code. (e.g. "+proj=utm +zone=37 +datum=WGS84 +units=m +no_defs" or "EPSG:32637")
output	A string specifying whether to 'open' or 'save' the output. The output will be saved in the current working directory.
type	Type of the output. 'point' or 'line'.
...	Optional arguments passed to plotKML and kml .

Value

A kml file

Author(s)

Takahiro Shimada

See Also

[map_track](#)

Examples

```
#### Fastloc GPS data obtained from a green turtle
data(turtle)

## Not run:
#### See the data on Google earth
## points with time stamps
kml_track(turtle, output = 'open', type = 'point',
points_names = turtle$DateTime, colour_scale = 'yellow')

## lines
kml_track(turtle, output = 'open', type = 'line', colour = 'red')

#### Save the location points to the current working directory
shape <- "http://maps.google.com/mapfiles/kml/pal2/icon26.png"
kml_track(turtle, output = 'save', type = 'point', shape = shape, colour = 'yellow')

## End(Not run)
```

map_track

Plot location data on a map

Description

Function to plot tracking data on a map or a satellite image.

Usage

```
map_track(
  sdata,
  xlim = NULL,
  ylim = NULL,
  margin = 10,
  bgmap = NULL,
  google.key = NULL,
  map.bg = "grey",
  map.col = "black",
  zoom = NULL,
  point.bg = "yellow",
  point.col = "black",
  point.symbol = 21,
  point.size = 1,
  line.col = "lightgrey",
  line.type = 1,
  line.size = 0.5,
  sb.distance = NULL,
  sb.lwd = 1,
```



```

    sb.line.col = "black",
    sb.text.size = 4,
    sb.text.col = "black",
    sb.space = 3,
    title = "id",
    title.size = 11,
    axes.text.size = 11,
    axes.lab.size = 11,
    multiplot = TRUE,
    nrow = 1,
    ncol = 1
)

```

Arguments

sdata	A data frame containing columns with the following headers: "id", "DateTime", "lat", "lon". The function creates a map for each unique "id". "DateTime" is date & time in class <code>POSIXct</code> . "lat" and "lon" are the latitude and longitude of each location in decimal degrees.
xlim, ylim	Limits for x and y axes. If not specified, the values are determined as the maximum range of the input data plus an additional margin (see <i>margin</i>).
margin	Set the amount of spaces added around the periphery of the plot. The value is scaled to the plot. The smaller value increases the margin.
bgmap	A data frame of a background map data, containing the following headers: "long", "lat", "group". If not specified, the <code>world</code> map is used. Google Maps ("terrain", "satellite", "roadmap", "hybrid") can also be queried.
google.key	If Google Maps are queried, a valid API key (a string) needs to be specified here. See register_google for details.
map.bg	Background colour of the map. This argument is ignored when any Google Maps is selected.
map.col	Outline colour of the map. This argument is ignored when any Google Maps is selected.
zoom	Map zoom for Google Maps. Default (NULL) to estimate the zoom from each data set. For other options, see get_map for details.
point.bg	The colour to fill in a symbol.
point.col	The colour for the outline of a symbol.
point.symbol	An integer or a string to specify the symbol type. See shape for details.
point.size	An integer to specify the size of the symbol.
line.col	The colour of the line that connects consecutive points.
line.type	The type of the line that connects consecutive points. See linetype for details.
line.size	An integer to specify the thickness (width) of the line that connects consecutive points.
sb.distance	An integer to specify the length of the scale bar. If not specified, approximately a quarter of the plotting range will be used.

sb.lwd	An integer to specify the thickness (width) of the scale bar.
sb.line.col	The colour of the scale bar.
sb.text.size	An integer to specify the text size for the scale bar.
sb.text.col	The colour of the text for the scale bar.
sb.space	Set the amount of space between the scale bar and the text. The value is scaled to the plot. The smaller value increases the space.
title	The main title for each plot. If not specified, the "id" will be used.
title.size	An integer to specify the size of the title.
axes.text.size	An integer to specify the size of the axes characters.
axes.lab.size	An integer to specify the size of the axes labels.
multiplot	Logical. If TRUE (default), multiple plots are displayed on the same page.
nrow	An integer to specify the number of rows in the multiple plot page.
ncol	An integer to specify the number of columns in the multiple plot page.

Value

An `arrangelist` is returned when `multiplot` is TRUE. Otherwise a list is returned.

Author(s)

Takahiro Shimada

See Also

[kml_track](#), [dupfilter](#), [ddfiler](#), [vmax](#), [vmaxlp](#)

Examples

```
#### Load data sets
## Fastloc GPS data obtained from two green turtles
data(turtle)
data(turtle2)
turtles<-rbind(turtle, turtle2)

#### Filter temporal and/or spatial duplicates
turtle.dup <- dupfilter(turtles, step.time=5/60, step.dist=0.001)

#### ddfilter
V <- vmax(turtle.dup)
VLP <- vmaxlp(turtle.dup)
turtle.dd <- ddfilter(turtle.dup, vmax=V, vmaxlp=VLP)

#### Plot filtered data for each animal
## using the low-resolution world map
map_track(turtle.dd, point.size = 2, line.size = 0.5, axes.lab.size = 0, ncol=2, nrow=1)
```

```
## Not run:
## using the high-resolution google satellite images
map_track(turtle.dd, bgmap = "satellite", google.key = "key", ncol=2)

## End(Not run)
```

percent_vol	<i>UD percent volume</i>
-------------	--------------------------

Description

Function to calculate a percent volume on a utilisation distribution (UD)

Usage

```
percent_vol(x, percent = 100)
```

Arguments

x	A vector containing the probability density.
percent	An integer specifying the percent volume of a UD to be considered.

Details

This function calculates a percent volume on a UD. The probability beyond the specified range will be assigned with a zero value.

Value

A vector containing the specified percent volume.

Author(s)

Takahiro Shimada

SandyStrait	<i>A map of Sandy Strait, Australia</i>
-------------	---

Description

This map layer outlines the coast around Sandy Strait, Australia.

Usage

```
SandyStrait
```

Format

A data.frame

tidalplane	<i>Tidal plane table for Sandy Strait, Australia</i>
------------	--

Description

A semidiurnal tidal plane table containing the height of the mean tidal planes and the average time differences of tide at different locations within Sandy Strait.

Usage

tidalplane

Format

A data frame with 2 rows and 6 variables:

standard.port identifier for a tidal observation station.

secondary.port identifier for a station at which tide is only predicted using the tidal records observed at the related standard port.

lat latitude in decimal degrees.

lon longitude in decimal degrees.

timeDiff time difference between standard port and its associated secondary port.

datumDiff baseline difference in metres between the bathymetry model and tidal observations/predictions, if each data uses different datum (e.g. LAT and MSL).

Source

The State of Queensland (Department of Transport and Main Roads), Tidal planes.

tidedata	<i>Tidal data for Sandy Strait, Australia</i>
----------	---

Description

A dataset containing tidal observations recorded at Bundaberg, Australia

Usage

tidedata

Format

A data frame with 26351 rows and 3 variables:

timeDT date & time in class `POSIXct` for each observed tidal height.

reading observed tidal height in metres.

standard.port identifier of the tidal station.

Source

The State of Queensland (Department of Transport and Main Roads), Tidal data.

track_param	<i>Calculate parameters between locations</i>
-------------	---

Description

Calculate time, distance, speed, and inner angle between successive locations

Usage

```
track_param(
  sdata,
  param = c("time", "distance", "speed", "angle", "mean speed", "mean angle"),
  days = 2
)
```

Arguments

sdata	A data frame containing columns with the following headers: "id", "DateTime", "lat", "lon". The function calculates each movement parameter by the unique "id". "DateTime" is date & time in class <code>POSIXct</code> . "lat" and "lon" are the latitude and longitude of each location in decimal degrees.
param	A string or vector specifying movement parameters to be calculated. Options are 'time', 'distance', 'speed', 'angle', 'mean speed' and 'mean angle'. See <i>details</i> .
days	A numeric value specifying the number of days to calculate mean speeds and angles. This argument is only used when 'mean speed' and/or 'mean angle' are selected in <i>param</i> .

Details

This function calculates various parameters of tracks. time (h), distance (km), speed (km/h) and inner angle (degrees) are calculated from each pair of successive locations. mean speed (km/h) and angle (degrees) are calculated from locations over a specified number of days.

Value

The input data is returned with new columns containing the requested parameters. "pTime" and "sTime" are hours from a previous and to a subsequent fix respectively. "pDist" and "sDist" are straight distances in kilometres from a previous and to a subsequent fix respectively. "pSpeed" and "sSpeed" are linear speed (km/h) from a previous and to a subsequent fix respectively. "inAng" is the degree between the bearings of lines joining successive location points. "meanSpeed" and "meanAngle" are the mean speed and degree over a specified number of days.

Author(s)

Takahiro Shimada

Examples

```
#### Load turtle tracking data
data(turtle)

#### Filter temporal and/or spatial duplicates
turtle.dup <- dupfilter(turtle, step.time=5/60, step.dist=0.001)

#### ddfilter
turtle.dd <- ddfilter(turtle.dup, vmax=9.9, qi=4, ia=90, vmaxlp=2.0)

#### Mean speed over 2 days
mean.speed <- track_param(turtle.dd, param = c('speed', 'mean speed'), days=2)

#### Plot data
ggplot(data = mean.speed, aes(x=lon, y=lat)) +
  geom_path(colour = 'grey') +
  geom_point(aes(colour=meanSpeed))
```

turtle

Green turtle tracking data

Description

A dataset containing Fastloc GPS locations of a green turtle tracked in Sandy Strait, Australia.

Usage

```
turtle
```

Format

A data frame with 429 rows and 5 variables:

id identifier for each animal.

DateTime date & time in class [POSIXct](#).

lat latitude in decimal degrees.

lon longitude in decimal degrees.

qi numerical quality index associated with each location fix where a greater number indicates a higher accuracy (e.g. number of GPS satellites used for estimation).

Source

Shimada T, Jones R, Limpus C, Groom R, Hamann M (2016) Long-term and seasonal patterns of sea turtle home ranges in warm coastal foraging habitats: Implications for conservation. *Marine Ecology Progress Series* 562:163-179. doi:[10.3354/meps11972](https://doi.org/10.3354/meps11972)

turtle2	<i>Green turtle tracking data 2</i>
---------	-------------------------------------

Description

A dataset containing Fastloc GPS locations of a green turtle tracked in Moreton Bay, Australia.

Usage

```
turtle2
```

Format

A data frame with 276 rows and 5 variables:

id identifier for each animal.

DateTime date & time in class `POSIXct`.

lat latitude in decimal degrees.

lon longitude in decimal degrees.

qi numerical quality index associated with each location fix where a greater number indicates a higher accuracy (e.g. number of GPS satellites used for estimation).

Source

Shimada T, Jones R, Limpus C, Groom R, Hamann M (2016) Long-term and seasonal patterns of sea turtle home ranges in warm coastal foraging habitats: Implications for conservation. *Marine Ecology Progress Series* 562:163-179. doi:[10.3354/meps11972](https://doi.org/10.3354/meps11972)

vmax	<i>Estimate maximum linear speed</i>
------	--------------------------------------

Description

Function to estimate the maximum linear speed between two consecutive locations.

Usage

```
vmax(sdata, qi = 5, prob = 0.99, ...)
```

Arguments

sdata	A data frame containing columns with the following headers: "id", "DateTime", "lat", "lon", "qi". "id" is the unique representing an individual. "DateTime" is date & time in class <code>POSIXct</code> . "lat" and "lon" are the latitude and longitude of each location in decimal degrees. "qi" is the numerical quality index associated with each location fix where a greater number indicates a higher accuracy (e.g. the number of GPS satellites involved in estimation).
qi	An integer specifying the lowest quality index of a location that is qualified to be used in the estimation. Default is 5 (e.g. 5 GPS satellite or more).
prob	A numeric value to specify a sample quantile. Default is 0.99.
...	Extra arguments passed to <code>dupfilter</code> .

Details

The function first calculates the linear speed between each pair of two consecutive locations. It then discards extreme values, based on the specified quantile, to exclude potential outliers from the estimation process. The maximum value in the retained dataset (i.e. without outliers) represents the maximum linear speed at which an animal would travel between two consecutive locations.

Value

Maximum linear speed (vmax) estimated from the input data. The unit is km/h.

Author(s)

Takahiro Shimada

References

Shimada T, Jones R, Limpus C, Hamann M (2012) Improving data retention and home range estimates by data-driven screening. *Marine Ecology Progress Series* 457:171-180 doi:[10.3354/meps09747](https://doi.org/10.3354/meps09747)

See Also

[ddfiter](#), [ddfiter_speed](#), [track_param](#), [dupfilter](#)

vmaxlp

Estimate maximum one-way linear speed of a loop trip

Description

Function to estimate the maximum one-way linear speed of a loop trip as described in Shimada et al. (2012).

Usage

```
vmaxlp(sdata, qi = 4, prob = 0.99, ...)
```


Arguments

sdata	A data frame containing columns with the following headers: "id", "DateTime", "lat", "lon", "qi". "id" is the unique representing an individual. "DateTime" is date & time in class <code>POSIXct</code> . "lat" and "lon" are the recorded latitude and longitude in decimal degrees. "qi" is the numerical quality index associated with each location fix where a greater number indicates a higher accuracy (e.g. the number of GPS satellites involved in estimation).
qi	An integer specifying the minimum quality index associated with a location used for the estimation. Default is 4 (e.g. 4 GPS satellite or more).
prob	A numeric value to specify a sample quantile. Default is 0.99.
...	Extra arguments passed to <code>dupfilter</code> .

Details

The function first detects a "loop trip". Loop trip behaviour is represented by spatial departure and return involving more than 3 consecutive locations (Shimada et al 2012). The function calculates the net (i.e. straight-line) distance between the departure and turning point as well as the turning point and return location of a loop trip. It then calculates the one-way travelling speed to or from each turning point for each loop trip. The function discards extreme values, based on the specified quantile, to exclude potential outliers from the estimation process. The maximum value in the retained dataset (i.e. without outliers) represents the maximum one-way linear speed at which an animal would travel during a loop trip.

Value

Maximum one-way linear speed of a loop trip (`vmaxlp`) estimated from the input data. The unit km/h.

Note

The input data must not contain temporal or spatial duplicates. A minimum of 8 locations are required.

Author(s)

Takahiro Shimada

References

Shimada T, Jones R, Limpus C, Hamann M (2012) Improving data retention and home range estimates by data-driven screening. *Marine Ecology Progress Series* 457:171-180 doi:[10.3354/meps09747](https://doi.org/10.3354/meps09747)

See Also

[ddfiter](#), [ddfiter_loop](#), [track_param](#), [dupfilter](#)

Index

*Topic **datasets**

- Australia, 4
 - bathymodel, 4
 - curtis, 8
 - SandyStrait, 27
 - tidalplane, 28
 - tidedata, 28
 - turtle, 30
 - turtle2, 31
- asymptote, 2
- Australia, 4
- bathymodel, 4
- boot_area, 3, 5
- boot_overlap, 3, 6
- curtis, 8
- ddfiler, 8, 11–13, 15, 26, 32, 33
- ddfiler_loop, 10, 10, 13, 33
- ddfiler_speed, 10, 12, 12, 32
- depthfilter, 13
- distfilter, 16
- dupfilter, 15, 17, 19–23, 26, 32, 33
- dupfilter_exact, 18, 19, 20, 22, 23
- dupfilter_qi, 18, 19, 20, 22, 23
- dupfilter_space, 18–20, 21, 23
- dupfilter_time, 18–20, 22, 22
- extract, 13
- get_map, 25
- kml, 23
- kml_track, 23, 26
- linetype, 25
- map_track, 23, 24
- percent_vol, 27
- plotKML, 23
- POSIXct, 9, 11–14, 16, 18–23, 25, 28–33
- register_google, 25
- SandyStrait, 27
- shape, 25
- tidalplane, 28
- tidedata, 28
- track_param, 13, 18–20, 22, 23, 29, 32, 33
- turtle, 30
- turtle2, 31
- vmax, 9, 10, 12, 13, 26, 31
- vmaxlp, 9–12, 26, 32
- world, 25