

Package ‘pubmed.mineR’

July 23, 2019

Type Package

Title Text Mining of PubMed Abstracts

Version 1.0.16

Date 2019-07-23

Author Jyoti Rani, S.Ramachandran, Ab Rauf Shah

Maintainer S. Ramachandran <ramuigib@gmail.com>

Description

Text mining of PubMed Abstracts (text and XML) from <<http://www.ncbi.nlm.nih.gov/pubmed>>.

Depends R (>= 2.10), methods

Imports RCurl, XML, boot, R2HTML

Collate 'Abstracts-class.R' 'HGNC-class.R' 'Yearwise.R' 'Genewise.R'
'combineabs.R' 'gene_atomization.R' 'Find_conclusion.R'
'getabs.R' 'getabsT.R' 'gethgnc.R' 'ready.R' 'readabs.R'
'removeabs.R' 'searchabsL.R' 'searchabsT.R' 'sendabs.R'
'subabs.R' 'cleanabs.R' 'word_atomizations.R' 'SentenceToken.R'
'contextSearch.R' 'uniprotfun.R' 'local_uniprotfun.R'
'tdm_for_lsa.R' 'printabs.R' 'pubtator_function.R'
'cos_sim_calc.R' 'cos_sim_calc_boot.R' 'wordcluster.R'
'whichcluster.R' 'wordclusterview.R' 'find_intro_conc_html.R'
'cluster_words.R' 'get_original_term.R' 'get_original_term2.R'
'input_for_find_intro_conc_html.R' 'xmlreadabs.R'
'xmlword_atomizations.R' 'xmlgene_atomizations.R'
'pubtator_result_list_to_table.R' 'genes_BWI.R' 'BWI.R'
'currentabs_fn.R' 'previousabs_fn.R' 'altnamesfun.R'
'subsetabs.R' 'prevsymbol_fn.R' 'alias_fn.R' 'get_NMids.R'
'get_PMCIDS.R' 'get_PMCtable.R' 'get_Sequences.R'
'Give_Sentences_PMC.R' 'head_abbrev.R' 'names_fn.R'
'official_fn.R' 'pmids_to_abstracts.R' 'get_gene_sentences.R'
'Give_Sentences.R' 'get_MedlinePlus.R' 'co_occurrence_fn.R'
'space_quasher.R' 'readabsnew.R' 'word_associations.R'
'get_DOIs.R'

License GPL-3

LazyLoad yes

LazyData yes

NeedsCompilation no

Repository CRAN

Date/Publication 2019-07-23 07:40:02 UTC

R topics documented:

Abstracts-class	2
alias_fn	3
altnamesfun	4
BWI	5
cleanabs	6
cleanabs-methods	6
cluster_words	7
combineabs	7
combineabs-methods	8
common_words_new	9
contextSearch	9
contextSearch-methods	10
cos_sim_calc	10
cos_sim_calc_boot	11
co_occurrence_fn	12
currentabs_fn	13
Find_conclusion	14
find_intro_conc_html	14
genes_BWI	15
GeneToEntrez	16
Genewise	17
Genewise-methods	18
gene_atomization	18
getabs	19
getabs-methods	20
getabsT	20
getabsT-methods	21
get_DOIs	21
get_gene_sentences	22
get_MedlinePlus	22
get_NMids	23
get_original_term	24
get_original_term2	25
get_PMCIDS	25
get_PMCTable	26
get_Sequences	27
Give_Sentences	27
Give_Sentences_PMC	28
head_abbrev	29
HGNC-class	29

HGNC2UniprotID	30
HGNCdata	31
input_for_find_intro_conc_html	32
local_uniprotfun	33
names_fn	33
official_fn	34
pmids_to_abstracts	35
previousabs_fn	36
prevsymbol_fn	37
printabs	38
pubtator_function	38
pubtator_result_list_to_table	39
readabs	40
readabsnew	41
ready	41
removeabs	42
removeabs-methods	43
searchabsL	43
searchabsL-methods	44
searchabsT	44
searchabsT-methods	46
sendabs	46
sendabs-methods	47
SentenceToken	47
space_quasher	48
subabs	48
subabs-methods	49
subsetabs	50
subsetabs-methods	50
tdm_for_lsa	51
uniprotfun	51
whichcluster	52
wordscluster	53
wordsclusterview	54
word_associations	55
word_atomizations	56
xmlgene_atomizations	57
xmlreadabs	57
xmlword_atomizations	58
Yearwise	59
Yearwise-methods	60

Abstracts-class *Class "Abstracts" Abstract Class*

Description

S4 Class with three slots Journal, Abstract, PMID to store abstracts from PubMed

Objects from the Class

Objects can be created by calls of the form `new("Abstracts", ...)`.

Slots

Journal: Object of class "character" to store Journals of the abstracts from PubMed

Abstract: Object of class "character" to store Abstracts from the PubMed

PMID: Object of class "numeric" to store PMIDs of abstracts from PubMed

Methods

No methods defined with class "Abstracts" in the signature.

Author(s)

S.Ramachandran, Ab Rauf Shah

See Also

searchabsL getabs contextSearch Genewise Yearwise combineabs subabs subsetabs
readabs

Examples

```
showClass("Abstracts")
```

alias_fn *To extract sentences containing Alias of the Human Genes from Pubmed abstracts.*

Description

alias_fn This function returns the sentences containing alias of gene and the user given terms from the Abstracts using HGNC gee data table. In this sense this function is a 2 Dimensional search.

Usage

```
alias_fn(genes, data, abs, filename, terms)
```

Arguments

genes	genes a table containing genes (official symbol,first column) with its frequency of occurrence (second column)could be an output of gene_atomization function and subsequently subsetting the table using for example the code genes_table = subset(t2diababs_genes, select = c("Gene_symbol","Freq")). Alternatively, a custome gene table can be supplied with two columns, the first one being the column for Gene symbols and the second one being the Frequency of occurrence. If Frequency of occurrence is not available then a dummy value of 1 can be set.
data	data is HGNC data table with all 49 features (columns) available from the web site https://www.genenames.org/
abs	abs an S4 object of class Abstracts.
filename	filename specifies the name of output file. Please note that the term alias will be suffixed to the given filename.
terms	terms query term(s) to be search in the abstracts, could be a vector of terms.

Value

An output file containing sentences with aliases of genes.For convenience both the official symbol and the corresponding alias are written in the output. The PMID of the corresponding Abstract containing the extracted sentence also appears just before the sentence. Note that multiple sentences from different abstracts are clubbed together under one gene alias that appears in those sentences.

Author(s)

S.Ramachandran

See Also

prevsymbol_fn

Examples

```
## Not run: alias_fn(genes,data,myabs,"nephro_",c("diabetic nephropathy","kidney disease"))
## genes output of gene_atomization()
```

altnamesfun

To Get Alternative names of Genes

Description

This function is used to retrieve the Alternative names of genes from UniProt using HGNC gene symbol.

Usage

```
altnamesfun(m)
```

Arguments

`m` is a character vector of HGNC official gene symbols.

Value

It returns a list of alternative names of given Gene symbols.

Author(s)

S.Ramachandran

References

UniProt Consortium. "The universal protein resource (UniProt)." Nucleic acids research 36.suppl 1 (2008): D190-D195. <http://www.uniprot.org/>

See Also

```
uniprotfun, ~~~
```

Examples

```
## Not run: test = altnamesfun(c("ADIPOQ", "BDNF"))
## here "ADIPOQ" is the HGNC gene symbol for which alternative name(s) is required.
```

BWI

To obtain the Buzz Word Index of terms from the Abstracts.

Description

This function is used to obtain the Buzz word index value for the terms.

Usage

```
BWI(current, previous, n, N)
```

Arguments

`current` current an S4 object containing the Abstracts for the current year we require the BWI an output from `currentabs_fn()`

`previous` previous an S4 object containing the Abstracts for years previous to current year of study an output from `previousabs_fn()`.

`n` n is a character term for which Buzz Word Index is to be calculated.

`N` N is a character value specifying the theme from the large corpus.

Value

It returns a list containing BWI value for the given word.

Author(s)

S.Ramachandran

References

Jensen, Lars Juhl, Jasmin Saric, and Peer Bork. "Literature mining for the biologist: from information retrieval to biological discovery." *Nature reviews genetics* 7.2 (2006): 119-129.

See Also

genes_BWI

Examples

```
## Not run: result = BWI(mycurrentabs, mypreviousabs, "insulin", "inflammation")
## BWI for the term "insulin" and the theme is inflammation.
## Note that in the previous, years are starting one before the current year 2015;
## current is an S4 object containing the output from currentabs_fn()
## previous is an S4 object containing the output from previousabs_fn().
## 'n' and 'N' are query terms whose BWI is sought and the theme respectively
```

cleanabs

To clean the result of searchabsL

Description

It will remove the 'NONE' abstracts from the result of searchabsL.

Usage

```
cleanabs(object)
```

Arguments

object an S4 object of class Abstracts.

Value

an S4 object of class Abstracts.

Author(s)

Jyoti Rani

See Also

searchabsL

Examples

```
## Not run: test1 = searchabsL(abs, include=c("term1", "term2"));
test2 = cleanabs(test1)
## End(Not run)
## here 'abs' is an S4 object of class Abstracts
## 'term1', 'term2' are the searchterms
## test1 is an S4 object containing abstracts for given terms
## and test2 is an S4 object of class Abstracts containing clean abstracts of searchabsL
```

cleanabs-methods *Methods for Function cleanabs*

Description

To clean 'NONE' part of searchabsL output.

Methods

signature(object = "Abstracts") From an S4 object of class 'Abstracts' the cleanabs function is able to clean the output of searchabsL by removing the 'NONE' part of resultant abstracts.

cluster_words *To Find the highest frequency of words within clusters*

Description

Function for finding the word (term) of highest frequency within clusters.

Usage

```
cluster_words(wordscluster, n)
```

Arguments

wordscluster an R object containing the output of wordscluster()
n a numeric vector containing cluster numbers

Value

a list containing cluster and its highest frequency word

Author(s)

S. Ramachandran

See Also

wordscluster

Examples

```
## Not run: test = cluster_words(wordscluster, 5)
## wordscluster is an R object of wordscluster
## 5 is number of cluster
## End(Not run)
```

combineabs

To combine the abstracts

Description

combineabs will automatically combine two abstracts of two objects.

Usage

```
combineabs(object1, object2)
```

Arguments

object1	An S4 object of class Abstracts
object2	An S4 object of class Abstracts

Details

Two objects of class 'Abstracts' are combined to return non-redundant combined abstracts. It can be used sequentially to combine many objects of class 'Abstracts'. It will also write the number of combined abstracts into a text file named "data_out.txt"

Value

An R object containing the combined abstracts, and a text file named "data_out.txt" containing the number of abstracts combined together

Author(s)

S.Ramachandran, Jyoti Rani

Examples

```
## Not run: res1 = combineabs(x,y)
## here 'x', 'y' are the S4 objects of class 'Abstracts'.
```

combineabs-methods Abstracts *Method to Combine Abstracts*

Description

combineabs method to combine the abstracts. object1 and object2 are from Abstracts class.

Methods

signature(object1 = "Abstracts") An S4 object of class "Abstracts"

signature(object2 = "Abstracts") An S4 object of class "Abstracts"

common_words_new *R Data containing words which frequently in text*

Description

This dataset is used to remove common words from the abstracts. This step is used for size reduction for further data mining.

Usage

```
data(common_words_new)
```

Format

The format is: chr "common_words_new"

Details

The dataset containing common words used to remove them from the text for size reduction.

References

https://en.wikipedia.org/wiki/Most_common_words_in_English

Examples

```
data(common_words_new)
```

contextSearch	<i>For Context Search</i>
---------------	---------------------------

Description

contextSearch is a method to extract the sentences containing a given query term

Usage

```
contextSearch(object, y)
```

Arguments

object	An S4 object of Class Abstracts containing text abstracts
y	a character vector of term(s)

Details

It takes object of class Abstracts and query term(s) as arguments and returns a text and latex file of the sentences containing query term. The latex file can be further converted into PDF by using the system command in R i.e. `system("pdflatex filename.tex")`. pdflatex is a shell command in Linux to convert the latex file into PDF. In the pdf file the terms are written in bold face type to enable ease of reading

Value

contextSearch() will write two files one is a text file named "companion.txt", and other is a Latex file. If the single term is given in query then file name comes with the term name. If multiple terms are used then the file name will be "combined.tex"

Author(s)

Dr.S.Ramachandran, Jyoti Rani

Examples

```
## Not run: contextSearch(x, "diabetes")  
## here 'x' is S4 object of class 'Abstracts', and query term is 'diabetes'.
```

contextSearch-methods

Method for Context Search

Description

contextSearch will search the sentence for the given term(s).

Methods

signature(object = "Abstracts") The object from where it will search should be an S4 object of class Abstracts

cos_sim_calc

To calculate the cosine similarity between terms.

Description

cos_sim_calc calculates the cosine measure of similarity between pairs of terms from a corpus.

Usage

```
cos_sim_calc(nummatrix)
```

Arguments

nummatrix A numerical matrix for e.g. a Term Document matrix (output from tdm_for_lsa)

Details

The term document matrix is taken as input and cosine measures of similarity between all pairs of terms are calculated.

Value

A tab delimited text file containing the similarity values between all pairs of terms.

Note

This file can be input to cytoscape directly.

Author(s)

S. Ramachandran

References

https://en.wikipedia.org/wiki/Cosine_similarity

See Also

tdm_for_lsa

Examples

```
## Not run: x = cos_sim_calc(nummatrix)
## here nummatrix is the 'Term Document Matrix' generated from tdm_for_lsa()
```

cos_sim_calc_boot *Cosine Similarity Calculation by Boot Strapping*

Description

cos_sim_calc_boot allows boot strap analysis. This function should be used as argument for 'statistic' in the boot function of 'boot' package.

Usage

```
cos_sim_calc_boot(data, indices)
```

Arguments

data	Term Document Matrix generated from tdm_for_lsa function of this package. In this matrix, rows are terms and columns are abstracts.
indices	index of matrix.

Details

while calling this function we need to transpose the input tdm and can also set the number of replicates. boot package is required to call this function.

Value

It will return a matrix containing the cosine similarity of pairs of terms in the abstracts. This object is in same format as returned by the 'boot' function of 'boot' package.

Author(s)

Dr.S.Ramachandran

See Also

tdm_for_lsa

Examples

```
## Not run: test_boot = boot(data = t(nummatrix), statistic = cos_sim_calc_boot, R = 2)
## here 'nummatrix' is a Term Document Matrix, boot inbuilt function of boot package,
## R is number of replicates here it is 2. User can extend this number.
```

co_occurrence_fn *Extracts sentences with co-occurrence of two sets of terms*

Description

co_occurrence_fn will automatically extract sentences with co-occurrence of two sets of terms.

Usage

```
co_occurrence_fn(terms1, abs, filename, terms2)
```

Arguments

terms1	a character vector of terms.
abs	an S4 object of class Abstracts
filename	a single character, filename
terms2	a character vector of terms.

Details

Sentences with co-occurrence of two terms will be extracted along with the corresponding PMIDs. The data will be written in a text file with the user given filename and the word co_occurrence will be suffixed to it.

Value

A text file.

Author(s)

S.Ramachandran

Examples

```
## Not run: co_occurrence_fn("resistance",myabs,"resistance_genetic",c("genes","genetic"))
##
```

currentabs_fn	<i>To Retrieve the Abstracts for year.</i>
---------------	--

Description

This function is used to extract the abstracts for year we want to study. Its output is used as input in other functions like BWI() and genes_BWI()

Usage

```
currentabs_fn(yr_to_include, theme, parentabs)
```

Arguments

yr_to_include	yr_to_include is the year for which we want to extract the Abstracts.
theme	theme is a character value specifying the themes for the Abstracts.
parentabs	parentabs an S4 object containing the Abstracts.

Value

It returns an S4 object containing the abstracts of the given year.

Author(s)

S.Ramachandran

See Also

previousabs_fn

Examples

```
## Not run: test = currentabs_fn("2015", "atherosclerosis", diabetesabs)
## here "2015" is the year for which, we wish to extract the abstracts on theme"Atherosclerosis"
## from the large corpus of diabetes i.e. diabetesabs.
```

Find_conclusion *To find the conclusion from the abstract(s).*

Description

This function is designed for the user convenience, so that user can get the conclusion from the abstract(s) without reading the whole abstract(s).

Usage

```
Find_conclusion(y)
```

Arguments

y An S4 object of class 'Abstract'.

Value

A list containing conclusions of given abstract(s)

Author(s)

S.Ramachandran, Jyoti Rani

Examples

```
## Not run: res1 = Find_conclusion(y)
## here 'y' is an S4 object of class Abstract.
```

find_intro_conc_html

To find the introduction and conclusion from the abstracts.

Description

it helps to fetch the introduction and conclusion part from the abstracts.

Usage

```
find_intro_conc_html(y, themes, all)
```

Arguments

y and S4 object of class Abstracts
themes a character vector containing terms to be search in the abstracts
all is logical, if true, will include title and author otherwise only abstracts will be considered.

Details

`find_intro_conc_html` provides an HTML file containing space separated introduction and conclusion part from the abstracts of given query term as well as gives a link directly to PubMed for the resulting PMID.

Value

an HTML file.

Author(s)

S.Ramachandran, Jyoti Rani

See Also

`input_for_find_intro_conc_html`

Examples

```
## Not run: test = find_intro_conc_html(abs, "diet", all=FALSE)
## here 'abs' is an S4 object of class Abstracts
## and 'diet' is a term to be search from the abstracts
## this function works for small size of corpus, say about 30-40 abstracts
```

genes_BWI

Function to obtain the Buzz Word Index of Genes from the abstracts.

Description

This function provides the Buzz word index for each gene. The theme is the context in which the gene is studied for e.g. atherosclerosis. Using this function user can identify abstracts with emphasis on a given gene.

Usage

```
genes_BWI(currentabs, previousabs, theme, genes)
```

Arguments

<code>currentabs</code>	<code>currentabs</code> an S4 object containing the Abstracts for the year we want to study. Output from <code>currentabs_fn()</code>
<code>previousabs</code>	<code>previousabs</code> an S4 object containing the Abstracts for years previous than our year of study. Output from <code>previousabs_fn()</code> .
<code>theme</code>	<code>theme</code> a character value to categorize our search. For e.g. 'Atherosclerosis' from 'diabetes' Abstracts.
<code>genes</code>	<code>genes</code> list of genes.

Value

It returns a dataframe containig Genes with their corresponding BWI values.

Author(s)

S.Ramachandran

See Also

BWI

Examples

```
## Not run: test = genes_BWI(currentabs, previousabs, theme, genes)
## currentabs is an S4 object contaning the Abstracts for the year we want to study.
## previousabs is an S4 object contaning the Abstracts for the years previous
## than our query year for e.g. before 2015
## theme is a character value specifying the search.
## genes is a character vector of gene symbols.
```

GeneToEntrez	<i>Data containing Entrez Ids</i>
--------------	-----------------------------------

Description

This dataset is used in `DAVID_info` function of the package, and it contains the Entrez Ids for the respective genes and these Entrez Ids will be used to get information about human genes.

Usage

```
data(GeneToEntrez)
```

Format

The format is: chr "GeneToEntrez"

Examples

```
data(GeneToEntrez)
```

Genewise

To Search the number of abstracts for Genes

Description

Genewise reports the number of abstracts for given gene(s) name(s)

Usage

```
Genewise(object, gene)
```

Arguments

object	An S4 object of class Abstracts
gene	a character input of gene name(HGNC approved symbol)

Details

This function will report the number of abstracts containing the query gene term(s) [HGNC approved symbols], and the result is saved in a text file "dataout.txt". Genewise() will report numbers of abstracts only. The abstracts themselves for corresponding gene names can be obtained using searchabsL() and searchabsT.

Value

Genewise will return an R object containing the abstracts for given gene, and a text file named "dataout.txt" containing the number of abstracts

Author(s)

S. Ramachandran, Jyoti Rani

Examples

```
## Not run: Genewise(x, "TLR4")  
## here 'x' contains the S4 object of Abstracts.
```

Genewise-methods *method to find the abstracts for the given gene.*

Description

Genewise The method Genewise will automatically report the numbers of abstracts for a given gene. It will write the result in the text file named "dataout.txt"

Methods

signature(object = "Abstracts") This method will search in an S4 object, containing abstracts. It will write a text file named "dataout.txt", containing the number of abstracts for the query gene terms

gene_atomization *To Extract Genes from the Abstracts*

Description

gene_atomization will automatically fetch the genes (HGNC approved Symbol) from the text and report their frequencies. presently only HGNC approved symbols are used.

Usage

```
gene_atomization(m)
```

Arguments

m An S4 object of class Abstracts

Details

The function writes a text file with file name "data_table.txt". The function gene_atomization() is used to obtain the name of genes along with their frequencies of occurrence.

Value

A tab delimited table containing gene name and their frequencies of occurrence.

Author(s)

S.Ramachandran, Jyoti Rani

Examples

```
## Not run: gene_atomization(myabs)
## here myabs is an S4 object of class 'Abstracts' containing the abstracts
## uses older version of HGNC data (https://www.genenames.org/) by default.
## users may also use other functions such as official_fn and related
## family of functions for deeper data mining.
```

getabs

To get Abstracts for a given term.

Description

getabs will automatically fetch the abstracts containing the query term. A base function of the package pubmed.mineR.

Usage

```
getabs(object, x, y)
```

Arguments

object	An S4 object of class Abstracts
x	A character string for the term
y	logical, if TRUE, search will be case sensitive

Details

getabs() is used to find and extract the abstracts for any given term, from the large a large corpus of abstracts. It uses regexpr based search strategy.

Value

An S4 object of class 'Abstracts', containing the result abstracts for the given term.

Author(s)

Dr.S.Ramachandran

Examples

```
## Not run: getabs(x, "term")
## x is an S4 obeject of class abstracts containing the abstracts.
```

getabs-methods	getabs <i>To Get abstracts for a term</i>
----------------	---

Description

getabs will search for the abstracts of a given term. It is case sensitive.

Methods

`signature(object = "Abstracts")` This method takes three arguments, first 'object' containing data to be search, 'x', the term to be search, 'y' is logical if set "YES" will consider the case of text.

getabsT	<i>To get Abstracts for a given term.</i>
---------	---

Description

getabsT will automatically fetch the abstracts containing the query term.

Usage

```
getabsT(object, x, y)
```

Arguments

object	An S4 object of class Abstracts
x	A character string for the term
y	is logical, if set TRUE, search will be case sensitive.

Details

getabsT() is similar to getabs(), but it performs more specific search.

Value

An object of class 'Abstracts', containing the resulted abstracts for term.

Author(s)

S.Ramachandran

Examples

```
## Not run: getabsT(diabdata, "term")
```

getabsT-methods *To Get Abstracts*

Description

getabsT will automatically return the abstracts of a term from the data.

Methods

signature(object = "Abstracts") getabsT will search for the abstracts of a term in the data, and will automatically write the number of abstracts into a text file named "dataout.txt".

get_DOIs *function for extracting Digital Object Identifier (DOIs) of papers*

Description

get_DOIs is used to extract DOIs of papers.

Usage

```
get_DOIs(abs)
```

Arguments

abs An S4 object of class Abstracts

Details

get_DOIs allow users to get DOIs for individual papers.

Value

It returns a list object containing DOIs. This is useful for further extraction of papers

Author(s)

S.Ramachandran

Examples

```
## Not run: test = get_DOIs(vitiligoabs)
##
```

get_gene_sentences *To extract the sentences for genes from the corpus.*

Description

get_gene_sentences is used to extract the exact sentence in which query gene is discussed.

Usage

```
get_gene_sentences(genes, abs, filename)
```

Arguments

genes	genes a character vector containing the gene symbols.
abs	abs an S4 object of class Abstracts
filename	filename specifies the output file name.

Value

an output file containing the sentences for given gene.

Author(s)

S.Ramachandran

Examples

```
## Not run: get_gene_sentences("RBP4", abstracts, "RBP4_sentence.txt")
```

get_MedlinePlus *To Get MedLinePlus Summary*

Description

This function is to get the summary from MedLinePlus.

Usage

```
get_MedlinePlus(x)
```

Arguments

x	x is a character input of terms: for examples 'malaria', 'pneumonia', 'chronic diseases'
---	--

Value

It returns a HTML file with name result_Medline_plus.html to be opened with any browser

Author(s)

S.Ramachandran

References

www.medlineplus.gov, Conuel T. Finding answers in a beauty shop. NIH MedlinePlus: the magazine [Internet]. 2012 Fall [cited 2013 Feb 9]; 7(3):24-26. Available from: <https://medlineplus.gov/magazine/issues/fall12/article26.html>

Examples

```
## Not run: get_MedlinePlus("malaria")
```

get_NMids *To extract NM ids from NCBI.*

Description

get_NMids is to fetch the NM ids from the NCBI for corresponding gene/s to further fetch the sequence of that gene/s.

Usage

```
get_NMids(x)
```

Arguments

x x an R object containing Locus IDs for genes from NCBI2R package.

Value

It returns a list object containing corresponding NM id from NCBI.

Author(s)

S.Ramachandran

References

<http://www.ncbi.nlm.nih.gov/gene>

See Also

get_Sequences

Examples

```
## Not run: getNMids("5950")
## 5950 is Locus id of RBP4 gene.
```

get_original_term *To get the original terms from the corpus. deprecated*

Description

get_original_term is used to get the exact term as it is present in corpus. This function is not recommended anymore.

Usage

```
get_original_term(m, n)
```

Arguments

m an S4 object of class Abstracts containing the corpus.
n a list object output from the function cluster_words

Value

a list object containing the terms.

Author(s)

S.Ramachandran, Jyoti Rani

See Also

wordscluster

Examples

```
## Not run: test = get_original_term(abs, words)
## here abs is an S4 object of class Abstracts
## words is the output object of cluster_words()
```

get_original_term2 *To get the original terms from the corpus.*

Description

get_original_term2 is used to get the exact term as it is present in corpus. It takes one term at a time. For multiple terms we can use lapply.

Usage

```
get_original_term2(x, y)
```

Arguments

x	x is a character value specifying the query term.
y	y is an S4 object containing abstracts.

Value

It returns a list object containing accurate term.

Author(s)

Jyoti Rani, S.Ramachandran.

See Also

get_original_term

Examples

```
## Not run: test = get_original_term("hbalc", diababs)
## here it will return accurate formation of hbalc i.e. HbA1c from diababs.
```

get_PMCIDS *To extract the PMC Ids of the abstracts.*

Description

get_PMCIDS is used to fetch the PMC Ids of the abstracts from the corpus.

Usage

```
get_PMCIDS(abs)
```

Arguments

abs absan S4 object of class Abtracts.

Value

It returns a list containing PMC Ids.

Author(s)

S.Ramachandran

Examples

```
## Not run: get_PMCIDS(abstracts)
```

get_PMCTable *To fetch the given PMC article tables. Deprecated*

Description

get_PMCTable is used to extract the full text article by giving query PMC Id. Deprecated.

Usage

```
get_PMCTable(url)
```

Arguments

url url is url of query PMC Id.

Value

It will return a full text article.

Author(s)

S.Ramachandran

References

<http://www.ncbi.nlm.nih.gov/pmc/>

See Also

get_PMCIDS

Examples

```
## Not run: get_PMCTable("http://www.ncbi.nlm.nih.gov/pmc/?term=4039032")
```

get_Sequences *To extract the Gene sequence from the NCBI.*

Description

get_Sequences is used to fetch the sequences of genes using NM ids.

Usage

```
get_Sequences(x, filename)
```

Arguments

x NM Id of the sequence.
filename filename specifies the name of output file.

Value

It will return a text file containing sequence.

Author(s)

S.Ramachandran

See Also

get_NMids, ~~~

Examples

```
## Not run: get_Sequences("NM_012238.4", "SIRT1")
```

Give_Sentences *To extract sentences from the Abstracts*

Description

Give_Sentences will help to extract the sentence containing query term/s from the large corpus.

Usage

```
Give_Sentences(m, abs)
```

Arguments

m m a character term.
abs abs an S4 object of class Abstracts.

Value

It will return a list object containing sentences

Author(s)

S.Ramachandran

See Also

Give_Sentences_PMC

Examples

```
## Not run: Give_Sentences("diabetes", Abstracts)
```

Give_Sentences_PMC *To fetch the sentence from the PMC full text article*

Description

Give_Sentences_PMC is used to extract the sentences from the full text article of given PMC id/s.

Usage

```
Give_Sentences_PMC(PMCID, term)
```

Arguments

PMCID	PMCID represents the PMC Id from where we want to extract the sentence.
term	term represents the term contained in a sentence.

Value

It will return a list object containing the sentences for query term from the given article.

Author(s)

S.Ramachandran

Examples

```
## Not run: Give_Sentences_PMC(PMC4039032, "atherosclerosis")
```

head_abbrev	<i>To extract the abbreviated term.</i>
-------------	---

Description

head_abbrev is used to find expansion for which abbreviation is used. It will help to find the falsely matching abbreviations from the abstracts.

Usage

```
head_abbrev(limits, term, pmid, abs)
```

Arguments

limits	limits specifies the limit up to which expansion should be displayed. Default is 50
term	term is the query term (abbreviation)
pmid	pmid describes the PMID
abs	absan S4 object of class Abstracts.

Value

It will return a list.

Author(s)

S.Ramachandran

Examples

```
## Not run: head_abbrev(50, "AR", "16893912", myabs)
```

HGNC-class	<i>HGNC Class for package.</i>
------------	--------------------------------

Description

"HGNC"

Objects from the Class

Objects can be created by calls of the form `new("HGNC", ...)`.

Slots

HGNCID: Object of class "character"
ApprovedSymbol: Object of class "character"
ApprovedName: Object of class "character"
Status: Object of class "character"
PreviousSymbols: Object of class "character"
Aliases: Object of class "character"
Chromosome: Object of class "character"
AccessionNumbers: Object of class "character"
RefSeqIDs: Object of class "character"

Author(s)

Dr.S.Ramachandran, Ab Rauf Shah

See Also

Abstracts

Examples

```
showClass("HGNC")
```

HGNC2UniprotID *R Data containing HGNC2UniprotID data mapping.*

Description

This dataset contains HGNC2UniprotID from Uniprot and is used in uniprotfn() function of this package, to get the information of a gene from the Uniprot.

Usage

```
data(HGNC2UniprotID)
```

Format

The format is: chr "HGNC2UniprotID"

Details

The dataset contains HGNC2UniprotID

References

UniProt Consortium. "The universal protein resource (UniProt)." Nucleic acids research 36.suppl 1 (2008): D190-D195. <http://www.uniprot.org/>

Examples

```
data (HGNC2UniprotID)
```

HGNCdata

R Data containing HGNC data.

Description

This dataset contains data from Human Gene Nomenclature Committee i.e HGNC ID, HGNC approved symbol, approved name, gene synonyms, chromosome no., accession numbers and RefSeq ids.

Usage

```
data (HGNCdata)
```

Format

The format is: chr "HGNCdata"

Details

The dataset contains HGNCdata

References

Povey, Sue, et al. "The HUGO gene nomenclature committee (HGNC)." Human genetics 109.6 (2001): 678-680. <http://www.genenames.org/>

Examples

```
data (HGNCdata)
```

```
input_for_find_intro_conc_html
    fetch the abstracts using E-utilities.
```

Description

it helps in searching and fetching the abstracts from E-utilities using PMIDs.

Usage

```
input_for_find_intro_conc_html(y, all)
```

Arguments

y	an S4 object of class Abstracts
all	is logical if true, will include title and author also.

Details

it takes an S4 object as input and uses its PMIDs to fetch the abstracts from E-utilities. The output will be used as input for find_intro_conc_html as it contains neat data i.e. abstracts only.

Value

a list containing abstracts and PMID

Author(s)

S.Ramachandran, Jyoti Rani

References

[literature/http://eutils.ncbi.nlm.nih.gov/](http://eutils.ncbi.nlm.nih.gov/literature/)

See Also

find_intro_conc_html

Examples

```
## Not run: test=input_for_find_intro_conc_html(abs)
## here 'abs' is an S4 object of class Abstracts.
```

local_uniprotfun *To Get Information from Uniprot.*

Description

It is an auxiliary function for altnamesfun.

Usage

```
local_uniprotfun(y)
```

Arguments

y y a character value containing HGNC Gene symbol

Value

It writes an output file named "x.txt" which will be used as input in altnamesfun().

Author(s)

S.Ramachandran, Jyoti Rani

See Also

```
uniprotfun
```

Examples

```
## Not run: local_uniprotfun("TLR4")
## here it will generate an output file named "x.txt" containing
## result for TLR4.
```

names_fn *To extract the sentences in asbtracts containing gene names from HGNC.*

Description

names_fn matches the gene symbols to gene names and extract from HGNC.

Usage

```
names_fn(genes, data, abs, filename, terms)
```

Arguments

genes	genes is output of gene_atomization or a table containing HGNC gene symbols in first column with its frequency in second column.
data	data is HGNC data table with all 49 features (columns) available from the web site https://www.genenames.org/
abs	abs an S4 object of class Abstracts.
filename	filename specifies the name of output file.
terms	terms second query term to be searched in the same sentence (co-occurrence) of abstracts.

Value

It returns an output file containing genes with their corresponding gene names and sentences with co-occurrences if any.

Author(s)

S.Ramachandran

Examples

```
## Not run:
names_fn(genes, data, diabetes_abs, "names", c("diabetic nephropathy", "DN"))

## End(Not run)
## genes output of gene_atomization()
```

official_fn	<i>To extract the sentences containing official gene symbol from abstracts.</i>
-------------	---

Description

official_fn is used to fetch the sentences containing official gene symbol from HGNC.

Usage

```
official_fn(genes, abs, filename, terms)
```

Arguments

genes	genes is output of gene_atomization, or a table containing HGNC gene symbols in first column with its frequency in second column.
abs	abs an S4 object of class Abstracts.
filename	filename specifies the name of output file.
terms	terms second query term to be searched in the same sentence (co-occurrence) of abstracts.

Value

It will return a text file containing corresponding official gene symbol.

Author(s)

S.Ramachandran

Examples

```
## Not run:
official_fn(genes, diabetes_abs, "genes", c("diabetic nephropathy", "DN"))

## End(Not run)
## genes output of gene_atomization()
```

pmids_to_abstracts *To Find and match the PMIDs to the abstracts.*

Description

pmids_to_abstracts is used to extract the abstract/s of query PMID/s.

Usage

```
pmids_to_abstracts(x, abs)
```

Arguments

x	x a numeric vector containing PMIDs
abs	abs an S4 object of class Abstracts.

Value

It will return an S4 object of class abstracts containing abstracts for query PMIDs.

Author(s)

S.Ramachandran

Examples

```
## Not run: pmids_to_abstracts(26878666, abs)
```

previousabs_fn *To Retrieve the Abstracts from the large corpus for given years.*

Description

This function is used to extract the abstracts from the large corpus excluding the years and under a given theme. Its output is used in other functions like BWI and genes_BWI

Usage

```
previousabs_fn(yrs_to_exclude, theme, parentabs)
```

Arguments

`yrs_to_exclude` `yrs_to_exclude` is abstracts for the list of years we want to exclude from the corpus

`theme` `theme` is a character value specifying the themes for the Abstracts.

`parentabs` `parentabs` an S4 object containing the Abstracts.

Value

It returns an S4 object containing the abstracts of the given year.

Author(s)

S.Ramachandran

See Also

`currentabs_fn`

Examples

```
## Not run: test = previousabs_fn(as.character(2015:2010), "atherosclerosis", diabetesabs
## here we will get the abstracts before 2010 for 'atherosclerosis'
## from the large corpus diabetesabs.
```

prevsymbol_fn *To extract the sentences containing Previous symbols of HGNC genes.*

Description

prevsymbol_fn will return the sentences containing previous symbols of the genes from the abstracts using HGNC data.

Usage

```
prevsymbol_fn(genes, data, abs, filename, terms)
```

Arguments

genes	genes is output of gene_atomization, or a table containing HGNC gene symbols in first column with its frequency in second column.
data	data is HGNC data table with all 49 features (columns) available from the web site https://www.genenames.org/
abs	abs an S4 object of class Abstracts.
filename	filename specify the name of output file
terms	terms second query term to be searched in the same sentence (co-occurrence) of abstracts.

Value

It returns a text file containing gene symbol with corresponding previous symbols.

Author(s)

S.Ramachandran

See Also

names_fn, official_fn

Examples

```
## Not run:
prevsymbol_fn(genes, data, diabetes_abs, "prevsym", c("diabetic nephropathy", "DN"))
## End (Not run)
```

`printabs` *To print the total number of abstracts in an S4 object of class Abstracts, its start and end*

Description

It gives overview of the abstracts in an S4 object of class Abstracts.

Usage

```
printabs(object)
```

Arguments

`object` An S4 object of class Abstracts.

Value

prints the total number of abstracts in an S4 object with additional information.

Author(s)

S.Ramachandran

Examples

```
## Not run: printabs(myabs)
## here myabs is an S4 object of class Abstracts.
```

`pubtator_function` *function for text annotation using PubTator*

Description

`pubtator_function` is used to extract specific information from an abstract like Gene, chemical, and diseases etc.

Usage

```
pubtator_function(x)
```

Arguments

`x` numeric value PMID.

Details

pubtator_function allow users to get information about 'Gene', 'Chemical' and 'Disease' for given PMID. It uses online tool PubTator on R platform. It also removes redundancy from the output. It takes one PMID at once, for multiple PMIDs user can use lapply() function.

Value

It returns a list object containing Gene, Chemical, Disease and PMID. The corresponding concept id numbers are joined by a '>' character. This is useful for further data mining

Author(s)

S.Ramachandran, Jyoti Rani

References

Wei CH et. al., PubTator: a Web-based text mining tool for assisting Biocuration, Nucleic acids research, 2013, 41 (W1): W518-W522. doi: 10.1093/nar/gkt44

Wei CH et. al., Accelerating literature curation with text-mining tools: a case study of using PubTator to curate genes in PubMed abstracts, Database (Oxford), bas041, 2012

Wei CH et. al., PubTator: A PubMed-like interactive curation system for document triage and literature curation, in Proceedings of BioCreative 2012 workshop, Washington DC, USA, 145-150, 2012

Examples

```
## Not run: test = pubtator_function(17922911)
## here pubtator_function() will extract the information from this given pmid.
```

pubtator_result_list_to_table

Function to Convert Pubtator result from list into Table

Description

This function is used to collect the outputs of pubtator_function() after using lapply over multiple PMIDs. This function enables to convert it into table for easy reading and further analysis.

Usage

```
pubtator_result_list_to_table(x)
```

Arguments

x here x is list output of pubtator_function().

Value

It returns table for pubtator_function output.

Author(s)

S.Ramachandran, Jyoti Rani

See Also

pubtator_function

Examples

```
## Not run: test = pubtator_result_list_to_table(x)
##here x is the output of pubtator_function
```

readabs

To read Abstracts

Description

readabs will automatically read the abstracts from the pubmed file.

Usage

```
readabs(x)
```

Arguments

x Text file of PubMed abstracts. (Abstracts downloaded from PubMed)

Details

The saved file from a general pubmed search as text file is read via readabs().

Value

An S4 object of class "Abstracts", and a text file with tab delimited headers Journal, Abstract, PMID written with file name "newabs.txt".

Author(s)

S.Ramachandran

Examples

```
## Not run: readabs("pubmed_result.txt")
##here pubmed_result.txt is the text file of abstracts saved from PubMed.
```

readabsnew	<i>To read Abstracts</i>
------------	--------------------------

Description

readabsnew will automatically read the abstracts from the pubmed text file.

Usage

```
readabsnew(x)
```

Arguments

x Text file of PubMed abstracts. (Abstracts downloaded from PubMed)

Details

The saved file from a general pubmed search as text file is read via readabsnew().

Value

An S4 object of class "Abstracts" and a text file with tab delimited headers Journal, Abstract, PMID written with file name "newabs.txt".

Author(s)

S.Ramachandran

Examples

```
## Not run: readabsnew("pubmed_result.txt")
##here pubmed_result.txt is the text file of abstracts saved from PubMed.
```

ready	<i>To Initiate the Classes.</i>
-------	---------------------------------

Description

ready will initiate the classes necessary for other functions.

Usage

```
ready()
```

Details

This function is necessary to initiate the classes which are needed for the implementation of other functions.

Value

classes

Author(s)

S. Ramachandran

Examples

```
## Not run: ready()
```

removeabs

To remove abstracts for the query term.

Description

removeabs will remove the abstracts from a corpus for a given term.

Usage

```
removeabs(object, x, y)
```

Arguments

object	An S4 object of class Abstracts
x	A character value
y	is logical, if set 'TRUE' search will be case specific

Details

removeabs() finds the abstracts for the given term and remove them from the large set of abstracts. A text file of file name "dataout.txt" will be written containing the number of abstracts removed.

Value

An S4 object of class Abstracts and a text file named "dataout.txt"

Author(s)

S.Ramachandran, Jyoti Rani

Examples

```
## Not run: removeabs(myabs, "atherosclerosis", TRUE)
```

```
removeabs-methods  removeabs To remove abstracts of a term from the data.
```

Description

`removeabs` This function will search for the abstracts containing the given term to remove them from the data.

Methods

`signature(object = "Abstracts")` This method depicts its function, it will remove the abstracts from the data, and the number of abstracts removed will be written the text file named "dataout.txt"

```
searchabsL          To Search the abstracts of term(s) in a combination mode.
```

Description

`searchabsL` will search for abstracts for the given term(s). Multiple combinations are allowed.

Usage

```
searchabsL(object, yr, include, restrict, exclude)
```

Arguments

<code>object</code>	An S4 object of class Abstracts
<code>yr</code>	character vector specifies the year of search
<code>include</code>	character vector specifies the terms contained in the abstracts.
<code>restrict</code>	character vector specifies the term contained in the abstracts for which search should be restricted.
<code>exclude</code>	character vector specifies the terms contained in the abstracts for excluding these abstracts from the search results.

Details

In the arguments except for the object all other arguments have "NONE" as default. To export or write the result of `searchabsL()` we use `sendabs()` function.

Value

An object of class Abstracts satisfying the term combinations, In addition a text file named "out.txt" reporting the number of abstracts for given query term combinations.

Author(s)

S.Ramachandran

See Also

searchabsT

Examples

```
## Not run: searchabsL(myabs, include="term")
searchabsL(myabs, yr="2013")
searchabsL(myabs, restrict="term")
searchabsL(myabs, exclude="term")
searchabsL(myabs, include="term", exclude="term2")
## End(Not run)
## Here myabs is the object of class Abstracts containing data,
## "term" is the query term to be search.
```

searchabsL-methods *Searching Abstracts*

Description

searchabsL will automatically search the abstracts from the data for the given terms or their combination of several terms.

Methods

signature(object = "Abstracts") searchabsL will search the abstracts for the given term or combinations of several terms. In this method the argument "include" uses the boolean operator 'OR' and is liberal whereas the 'restrict' and 'exclude' use the boolean operator 'AND' to specify additional filters. If the restriction to individual terms are desired then they can be individually searched and then the multiple abstracts can be combined using combineasb() function.

searchabsT *To Search Abstracts*

Description

searchabsT It is similar to searchabsL() but performs more specific search. It performs case sensitive search.

Usage

```
searchabsT(object, yr, include, restrict, exclude)
```

Arguments

object	An S4 object of class Abstracts
yr	character vector specifies the year(s) of search.
include	character vector specifies the term(s) for which abstracts to be searched.
restrict	character vector specifies the term(s) contained in the abstracts for which search should be restricted.
exclude	character vector specifies the term(s) contained in the abstracts for excluding these abstracts from our search results.

Details

In the arguments except the object all arguments have "NONE" as default. Use sendabs() function to write the results in a tab delimited text file.

Value

An object of class Abstracts meeting the term and the term combinations. A text file reporting the number of abstracts for the query terms and their combinations is also written with the filename "out.txt".

Author(s)

Dr.S.Ramachandran

See Also

searchabsL

Examples

```
## Not run: searchabsT(myabs, yr="2013")
searchabsT(myabs, include="term")
searchabsT(myabs, restrict="term")
searchabsT(myabs, exclude="term")
searchabsT(myabs, yr="2013", include="term")
## End(Not run)
## Here myabs is an S4 object of class Abstracts containing the abstracts to search,
## "term" is the query term to be search.
```

searchabsT-methods searchabsT *Searching abstracts*

Description

searchabsT will perform a specific search for the given term.

Methods

signature(object = "Abstracts") It is similar to the searchabsL method, but it is more specific than searchabsL, it is case sensitive, however searchabsL is not.

sendabs *To send abstracts*

Description

sendabs will send the abstracts into a tab delimited text file with the fields Journal, Abstract, and PMID.

Usage

```
sendabs(object, x)
```

Arguments

object	An S4 object of class 'Abstracts'
x	"filename.txt" to write the abstracts

Details

A general writing function for object of class 'Abstracts'

Value

A tab delimited text file with headers Journal, Abstract, PMID.

Author(s)

S.Ramachandran, Jyoti Rani

Examples

```
## Not run: sendabs(myabs, "myabs.txt")  
## here myabs is the S4 object of class 'Abstracts' and  
## 'abs.txt' is the file where abstracts will be written.
```

sendabs-methods *To send the Data into a File*

Description

sendabs will write the data of an object of class 'Abstracts' into a tab delimited text file with header Journal, Abstract, and PMID

Methods

signature(object = "Abstracts") sendabs will send the data into a text file. It writes a tab delimited text file for PubMed abstracts containing Journal, Abstract, and PMID.

SentenceToken *To Tokenize the sentences*

Description

SentenceToken will tokenize abstracts into individual sentences.

Usage

```
SentenceToken(x)
```

Arguments

x is a character string; could be an output from paste

Details

This function is necessary for extracting sentences from abstracts, used by contextSearch function. The tokenization principle follows the overall strategy as described in contextSearch

Value

A character vector of sentences

Author(s)

S.Ramachandran

Examples

```
## Not run: SentenceToken(x)
```

space_quasher *Removes extra spaces between words.*

Description

space_quasher will automatically remove extra spaces between words. Therefore only one space between any pair of words will be left

Usage

```
space_quasher(x)
```

Arguments

x x is a text with single or multiple sentences given within double quotes.

Details

The extra spaces between words in sentences is quashed to one via space_quasher().

Value

Sentences(s) in which extra spaces between any pair of words are quashed to one.

Author(s)

S.Ramachandran

Examples

```
## Not run: space_quasher("I am            a ghostbuster. I have the tools        required to    hunt g  
##here pubmed_result.txt is the text file of abstracts saved from PubMed.
```

subabs *To find sub-abstracts*

Description

subabs will automatically extract the sub-abstracts from large set of abstracts.

Usage

```
subabs(object, start, end)
```

Arguments

object	An S4 object of class Abstracts
start	integer, specifies starting limit of the range to perform search
end	integer, specifies end limit of the range to perform search

Details

From a large number of asbstracts wish to extract a subset of abstracts into a separate object.

Value

An R object of class 'Abstracts' containing the extracted abstracts meeting a given range.

Author(s)

Jyoti Rani, S.Ramachandran

Examples

```
## Not run: subabs(myabs,1,5)
## Here 'myabs' is an S4 object of class 'Abstracts',
## 1 and 5 are the start and end respectively.
```

subabs-methods *Getting subabstracts*

Description

subabs subabs will extract the sub abstracts corresponding to a given range, from the whole data.

Methods

signature(object = "Abstracts") From an S4 object of class 'Abstracts' the subabs function is able to extract the abstracts corresponding to a given range.

`subsetabs`*To make subsets of large corpus.*

Description

It is used to divide the large corpus into a given range.

Usage

```
subsetabs(object, indices)
```

Arguments

`object` `object` is an S4 object containing Abstracts.
`indices` `indices` a numeric range (e.g. 1:10, c(1,5,7,9,10)).

Value

It returns an S4 object of extracted Abstracts.

Author(s)

S. Ramachandran.

Examples

```
## Not run: test = subsetabs(diabetesabs, 1:50)
## here we want to extract the Abstracts ranges from 1 to 50
## from the large corpus of diabetes.
```

`subsetabs-methods`*To make subset of Abstracts.*

Description

`subsetabs` is used to subset of Abstracts from the large corpus. Its output is used in other functions like `currentabs_fn` and `previousabs_fn`

Methods

`signature(object = "Abstracts")` `subsetabs` will divide the large corpus into subset.

tdm_for_lsa	<i>create Term Document Matrix for lsa analysis</i>
-------------	---

Description

lsa package take "Term Document Matrix" as input, so it is needed to create a 'tdm' for Abstracts and `tdm_for_lsa` do the same as it find out the frequency of given term in each abstract and each abstract is considered as separate document. It prepares term document matrix of terms in the 'abstracts' corpus

Usage

```
tdm_for_lsa(object, y)
```

Arguments

<code>object</code>	An S4 object of class 'Abstracts'
<code>y</code>	a character vector specifying the terms

Value

a Term Document Matrix (Numerical matrix) containing the raw frequencies of given terms in each abstract.

Author(s)

Jyoti Rani

Examples

```
## Not run: y = c("insulin", "inflammation", "obesity")
tdm_for_lsa(myabs, y)
## End(Not run)
```

uniprotfun	<i>To get information about gene from the UniProt.</i>
------------	--

Description

`uniprotfun` will access the UniProt data for a given gene as per HGNC approved gene symbols

Usage

```
uniprotfun(y)
```

Arguments

`y` a HGNC approved gene symbol as character

Details

This function retrieves data from the UniProt. At present uniprotfun() works with only HGNC approved gene symbols.

Value

A text file written with filename as the 'query' name suffixed with .txt

Author(s)

S.Ramachandran

Examples

```
## Not run: uniprotfun("SIRT1")
```

`whichcluster` *To fetch the cluster for words*

Description

`whichcluster` is used to get the cluster in which a given word (term) occurs.

Usage

```
whichcluster(clusterobject, y)
```

Arguments

`clusterobject` an R object containing the clusters of words output by `wordscluster` function.

`y` a character string of query terms.

Value

a list containing the number of cluster under which given term occurs.

Author(s)

S.Ramachandran

See Also

`wordscluster`

Examples

```
## Not run: test<-whichcluster(x, "diabetes")
## here x is an R object output form wordcluster function.
## and "diabetes" is the term for which cluster number is to be searched.
## End(Not run)
```

wordcluster *To cluster the words*

Description

wordcluster is used to cluster the words, using the levenshtein distance concept, which are coming together in combination with either 'prefixes' or 'suffixes' or other compound words. The first word, usually of lowest length, could be 'stemmed' word in many cases drastically so, is considered as representative for that cluster.

Usage

```
wordcluster(lower, upper)
```

Arguments

lower	lower limit for characters in word. Default = 5.
upper	upper limit of characters in word. Default = 30

Details

This function is usefull for dampening the 'explotion' of words output from word_atomizations. This step enables easy examination of the terms.

Value

a list object of words clustered together and a text filenameed "resulttable.txt" with the columns cluster number, cluster size and representatives of clusters.

Note

The function may run faster when the lower limits are reduced but 'risks' producing plenty of 'decoy' situations. Their frequencies are very rare. Decoy situations: Some 'words' with part identity to other smaller words will runaway with smaller words. This event creates an unfavorable situation whereby the generated 'clusters' of words become difficult to interpret. This situation can be minimized by increasing the lower limit of word length, however at the cost of lowering computational speed. An example is: the word hypercholesterolemia runsaway with the smaller word 'lester' which could be another name. In this instance increasing the lower limit will be more usefull. Words longer than 30 characters are usually names of chemical compunds in IUPAC system of nomenclature.

Author(s)

S.Ramachandran, Jyoti Rani

See Also

whichcluster word_atomizations

Examples

```
## Not run:
test=wordscluster(5, 10)
## here it will start making cluster of words of length with minimum of 5 characters
## and maximum of 10 characters.

## End(Not run)
```

wordsclusterview *To view the words in cluster*

Description

wordsclusterview is used to view the words comes in cluster formed by wordscluster function.

Usage

```
wordsclusterview(words_cluster, all)
```

Arguments

words_cluster	an R object containing output of wordscluster
all	is logical and default is FALSE, if set to TRUE includes those with one member word.

Details

The first 5 words and 5 words near the median and 5 words at the tail end are shown for clusters with more than 15 members. In case of cluster size less than 15, all the words are written in output.

Value

It returns a text file named word_cluster_view.txt

Author(s)

S.Ramachandran, Jyoti Rani

See Also

wordscluster

Examples

```
## Not run: test= wordsclusterview(cluster)
# here cluster is output from wordscluster
## End(Not run)
```

word_associations *Extracts the words associated (to the left and to the right) with a given word*

Description

word_associations will automatically extract associated words for a given word, namely the words immediately to the left and to the right. The given word is usually in the middle except for those cases, where the given word occurs either at the start or the end of the sentence.

Usage

```
word_associations(term, abs)
```

Arguments

term	is a single word
abs	an S4 object of class Abstracts

Details

Certain words are qualified by authors in various ways. For example, physical therapy, gene therapy etc. This function is useful in extracting these qualified words in the form of available associated words. Useful for preparing terms to be given in co_occurrence_fn (). There could be other uses also.

Value

comp1	A list of all the word pairs in a given set of abstracts.
-------	---

Author(s)

S. Ramachandran

References

Rani J, Shah AB, Ramachandran S. pubmed.mineR: an R package with text-mining algorithms to analyse PubMed abstracts. J Biosci. 2015 Oct;40(4):671-82. PubMed PMID: 26564970.

See Also

Give_Sentences

Examples

```
## Not run: word_associations("therapy",myabs
##
```

word_atomizations *Atomization of words*

Description

word_atomizations will automatically break the whole text into words and rank them according to their frequency of occurrence.

Usage

```
word_atomizations(m)
```

Arguments

m An S4 object of class Abstracts

Details

word_atomizations() will break down the whole text into words after removing the extra white space, punctuation marks and very common english words.

Value

A text file containing words with their frequencies

Author(s)

S. Ramachandran, Jyoti Sharma

Examples

```
## Not run: word_atomizations(myabs)
## here myabs is the object containing abstracts.
```

`xmlgene_atomizations`*Gene atomization of xml abstracts.*

Description

`xmlgene_atomizations` is used to fetch the list of genes from the xml abstracts

Usage

```
xmlgene_atomizations(m)
```

Arguments

`m` an S4 object of class Abstracts, output from `xmlreadabs`.

Value

a list containing genes from the text with their frequency of occurrence.

Author(s)

S.Ramachandran, Jyoti Sharma

See Also

`xmlreadabs`

Examples

```
## Not run: test = xmlgene_atomizations(xmlabs)
## xmlabs is an S4 object of class Abstracts i.e. output of xmlreadabs
```

`xmlreadabs`*To read the abstracts from the PubMed saved in XML format.*

Description

`xmlreadabs` is modified form of `readabs` as it reads the abstracts downloaded/saved in XML format from PubMed. This is helpful to give clean and better result after preprocessing i.e. `word_atomizations`, `wordscluster` etc.

Usage

```
xmlreadabs(file)
```

Arguments

file an XML file saved from PubMed.

Value

an S4 object of class Abstracts containing journals, abstracts and PMID.

Author(s)

S.Ramachandran

See Also

readabs

Examples

```
## Not run: xmlabs = xmlreadabs("pubmed_result.xml")
## here "pubmed_result.xml" is an xml format file downloaded from PubMed.
```

xmlword_atomizations

Word atomizations of abstracts from xml format.

Description

xmlword_atomizations is used to process the abstracts from PubMed in XML format.

Usage

```
xmlword_atomizations(m)
```

Arguments

m an S4 object of class Abstracts resulted from xmlreadabs.

Value

a list containing words from the text with their frequencies.

Note

xmlword_atomizations cannot work on output of readabs.

Author(s)

S. Ramachandran

See Also

xmlreadabs

Examples

```
## Not run: test = xmlword_atomizations(xmlabs)
## here xmlabs is an S4 object i.e. output of xmlreadabs
```

Yearwise

To Search abstracts Year wise

Description

Yearwise reports the no. of abstracts in a year.

Usage

```
Yearwise(object, year)
```

Arguments

object	An S4 object of class Abstracts.
year	a character vector specifies the year.

Details

Yearwise() is useful to find the no. of abstracts for the given year.

Value

A text file containing the no. of abstracts for given Year(s)

Author(s)

Dr.S.Ramachandran

Examples

```
## Not run: Yearwise(myabs, "2011") or
Yearwise(myabs, c("2011", "2013", "2009"))
## End(Not run)
## Here myabs is the object containing PubMed abstracts.
```

Yearwise-methods Yearwise *Year wise extraction of Abstracts*

Description

Yearwise will report the abstracts for given year(s).

Methods

signature(object = "Abstracts") This method "Yearwise" is written to fetch the abstracts yearly.