

Package ‘geoSpectral’

February 20, 2020

Type Package

Title Classes and Methods for Working with Spectral Data with
Space-Time Attributes

Version 0.17.5

Date 2020-02-17

Depends R (>= 2.10.0)

Imports methods, dplyr, spacetime, xts, maps, rgdal, leaflet, rbokeh,
plotly, sp, stats

Author Servet Ahmet Cizmeli [aut, cre]
(<<https://orcid.org/0000-0001-6694-9305>>)

Maintainer Servet Ahmet Cizmeli <ahmet@pranageo.com>

URL <https://github.com/PranaGeo/geoSpectral>

BugReports <https://github.com/PranaGeo/geoSpectral/issues>

Description Provides S4 classes and data import, preprocessing, graphing,
manipulation and export methods for geo-Spectral datasets (datasets with space/time/spectral
dimensions). These type of data are frequently collected within earth observation projects
(remote sensing, spectroscopy, bio-optical oceanography, mining, agricultural, atmospheric,
environmental or similar branch of science).

License GPL

LazyLoad yes

Collate geoSpectral.R SpcHeader-Class.R SpcHeader-Methods.R
Spectra-Class.R Spectra-Methods.R SpcList-Class.R
SpcList-Methods.R Spectra-ImportFuns.R

RoxygenNote 7.0.2

Suggests testthat, xlsx, geoSpectral

NeedsCompilation no

Repository CRAN

Date/Publication 2020-02-20 14:20:02 UTC

R topics documented:

| | |
|--|----|
| Arith,Spectra,Spectra-method | 3 |
| dim,Spectra-method | 4 |
| geoSpectral | 5 |
| head,Spectra-method | 5 |
| names,SpcList-method | 6 |
| names,Spectra-method | 7 |
| ncol,Spectra-method | 7 |
| nrow,Spectra-method | 8 |
| rep,Spectra-method | 8 |
| show,SpcHeader-method | 9 |
| show,SpcList-method | 10 |
| show,Spectra-method | 10 |
| sort,SpcList-method | 11 |
| sort,Spectra-method | 12 |
| spc.bbox2lines | 12 |
| spc.cname.construct | 13 |
| spc.colMeans | 14 |
| spc.colnames | 14 |
| spc.data2header | 15 |
| spc.data2header,list-method | 16 |
| spc.example_spectra | 17 |
| spc.export.text | 18 |
| spc.export.xlsx | 19 |
| spc.getheader | 20 |
| spc.getheader,list-method | 21 |
| spc.getinvalid.idx | 22 |
| spc.getselected.idx | 22 |
| spc.getwavelengths | 23 |
| spc.header.infos | 24 |
| spc.header2data | 24 |
| spc.interp.spectral | 25 |
| spc.invalid.detect | 26 |
| spc.lapply | 27 |
| spc.lines | 27 |
| spc.make.stindex | 28 |
| spc.makeSpcList | 29 |
| spc.plot | 30 |
| spc.plot.depth | 31 |
| spc.plot.depth.overlay | 32 |
| spc.plot.depth.plotly | 33 |
| spc.plot.grid | 34 |
| spc.plot.map.leaflet | 35 |
| spc.plot.map.plotly | 36 |
| spc.plot.map.rbokeh | 36 |
| spc.plot.overlay | 37 |
| spc.plot.plotly | 39 |

| | |
|---------------------------------------|----|
| spc.plot.time | 40 |
| spc.plot.time.plotly | 41 |
| spc.rbind | 42 |
| spc.rbind,STIDF-method | 42 |
| spc.Read_ASD | 43 |
| spc.Read_NOMAD_v2 | 44 |
| spc.select | 44 |
| spc.setheader<- | 45 |
| spc.setheader<-,list-method | 46 |
| spc.setinvalid.idx<- | 46 |
| spc.setselected.idx<- | 47 |
| spc.setwavelengths<- | 48 |
| spc.STI.stdistance | 48 |
| spc.timeMatch | 49 |
| spc.updateheader | 50 |
| SpcHeader-class | 51 |
| SpcHeaderAdd | 51 |
| SpcHeaderList-class | 52 |
| SpcList | 52 |
| SpcList-class | 53 |
| Spectra | 53 |
| Spectra-class | 55 |
| Spectra-coerce | 55 |
| subset,SpcList-method | 56 |
| subset,Spectra-method | 57 |
| \$.SpcList-method | 58 |
| \$.Spectra-method | 59 |

Index**61**

Arith,Spectra,Spectra-method

Apply arithmetic operations on and between Spectra objects.

Description

Methods defining Arithmetic and Math operations between two Spectra objects e1 and e2 or one Spectra object e1 and a numeric value.

Usage

```
## S4 method for signature 'Spectra,Spectra'
Arith(e1, e2)
```

```
## S4 method for signature 'Spectra,numeric'
Arith(e1, e2)
```

```
## S4 method for signature 'Spectra'
Math(x)
```

Arguments

| | |
|----|-------------------------|
| e1 | spectra object |
| e2 | spectra object or other |
| x | spectra object |

Details

These methods allow performing arithmetic operations involving Spectra objects.

See Also

[Arith](#)

`dim,Spectra-method` *Dimensions of a Spectra object.*

Description

Gives number of dimension of a Spectra object

Usage

```
## S4 method for signature 'Spectra'  
dim(x)
```

Arguments

| | |
|---|------------------|
| x | A Spectra object |
|---|------------------|

Value

Returns a numeric vector containing `nrow` and `ncol` of the Spectra object.

Examples

```
sp<-spc.example_spectra()  
dim(sp)
```

geoSpectral

Classes and Methods for Working with Spectral Data with Space-Time Attributes

Description

Provides S4 classes and data import, preprocessing, graphing, manipulation and export methods for geo-Spectral datasets (datasets with space/time/spectral dimensions). These type of data are frequently collected within earth observation projects (remote sensing, spectroscopy, bio-optical oceanography, mining, agricultural, atmospheric, environmental or similar branch of science).

Details

This package provides the following S4 classes:

- `Spectra` (stores spatial/temporal/spectral aspects of data)
- `SpcHeader` (stores metadata in an R list object)
- `SpcList` (makes a collection of `Spectra` objects in an R list)

as well as basic data access and manipulation methods for importing, accessing and subsetting, converting into R objects, analyzing, plotting, and exporting to other scientific data formats. Have a look at the constructor function by typing `?Spectra` to get started.

Author(s)

Servet Ahmet Cizmeli <ahmet@pranageo.com>

See Also

See also the packages `spacetime`, `rgdal`, `sp`, `xts`

`head, Spectra-method` *Return the first or last part of a Spectra object*

Description

Return the first or last parts of a `Spectra` object

Usage

```
## S4 method for signature 'Spectra'  
head(x, ...)
```

Arguments

`x` a `Spectra` object
`...` arguments to be passed to or from other methods

Value

Returns a matrix (Spectra data)

Examples

```
x <- spc.example_spectra()
head(x)
```

names,SpcList-method *names of SpcList object*

Description

Retrieve names of a SpcList object

Usage

```
## S4 method for signature 'SpcList'
names(x)
```

Arguments

x A SpcList object

Value

Returns the coulmn names of an object of class SpcList as a charecter vector.

Examples

```
sp <- spc.example_spectra()
BL = spc.makeSpcList(sp,"CAST")
names(BL)
```

names, Spectra-method *The Names of a Spectra object*

Description

Retrieve the names of Spectra object

Usage

```
## S4 method for signature 'Spectra'  
names(x)
```

Arguments

x a Spectra object

Examples

```
x <- spc.example_spectra()  
names(x)
```

ncol, Spectra-method *The Number of Columns of a Spectra object*

Description

nrow and ncol return the number of rows or columns of a Spectra object

Usage

```
## S4 method for signature 'Spectra'  
ncol(x)
```

Arguments

x A Spectra object

Examples

```
x <- spc.example_spectra()  
ncol(x) #501  
nrow(x) #26
```

nrow,Spectra-method *The Number of rows of a Spectra object*

Description

nrow and ncol return the number of rows or columns present in a Spectra object

Usage

```
## S4 method for signature 'Spectra'
nrow(x)
```

Arguments

x a Spectra object

Examples

```
x <- spc.example_spectra()
ncol(x) #501
nrow(x) #26
```

rep,Spectra-method *Replicate rows of Spectra object*

Description

Operators

Usage

```
## S4 method for signature 'Spectra'
rep(x, times, ...)
```

Arguments

x A Spectra object whose rows are to be replicated.

times A integer vector giving the (non-negative) number of times to repeat each row. See help of [rep](#).

... further arguments to be passed to or from other methods. See help of [rep](#).

Details

Replicates rows of x, making times copies of each row. Replicates Spectra, data, sp, time, endTime, InvalidIdx slots. Resets the SelectedIdx slot.

Value

A Spectra object

Examples

```
sp=spc.example_spectra()
dim(sp)
sp2 = rep(sp, 5)
dim(sp2)
```

show, SpcHeader-method *Show a SpcHeader object*

Description

Display a SpcHeader object

Usage

```
## S4 method for signature 'SpcHeader'
show(object)
```

Arguments

object of class SpcHeader

See Also

[show](#)

Examples

```
x=spc.example_spectra()
show(x@header)
```

show, SpcList-method *Show a SpcList object*

Description

Display a SpcList object

Usage

```
## S4 method for signature 'SpcList'  
show(object)
```

Arguments

object a SpcList object

Value

show returns an invisible NULL

Examples

```
x <- spc.example_spectra()  
BL = spc.makeSpcList(x, "CAST")  
show(BL)
```

show, Spectra-method *Show a Spectra object*

Description

Display a Spectra object

Usage

```
## S4 method for signature 'Spectra'  
show(object)
```

Arguments

object a Spectra object

Value

show returns an invisible NULL

Examples

```
x <- spc.example_spectra()
show(x)
```

sort,SpcList-method *Sort a SpcList object*

Description

Applies the sort() method for Spectra class to every element of a SpcList object. All the Spectra objects within the SpcList object gets sorted according to the specified criteria.

Usage

```
## S4 method for signature 'SpcList'
sort(x, decreasing = FALSE, na.last = NA, which.col, ...)
```

Arguments

| | |
|------------|---|
| x | A SpcList object |
| decreasing | Logical. If TRUE, then the rows are sorted in decreasing order. Passed on to the sort.idx() function from the base package. Default is FALSE. |
| na.last | for controlling the treatment of NAs. Passed on to the sort.idx() function from the base package. Default is NA. |
| which.col | A character, defining the name of the column to be used in the sorting |
| ... | arguments to be passed to or from methods. See help of sort . |

Examples

```
sp <- spc.example_spectra()
#Create an SpcList object (one separate Spectra object for each unique STATION)
spL <- spc.makeSpcList(sp,"STATION")
#Sort all Spectra objects with respect to their rows using the CAST column
spL.s <- sort(spL,which.col="CAST",decreasing=TRUE)
lapply(spL.s, function(x) as.character(x[["CAST"]]))
```

sort, Spectra-method *Sort a Spectra object*

Description

Sort a Spectra object with respect to its rows with respect to values of one given column (specified by which.col). Sorting with respect to multiple columns is not implemented yet.

Usage

```
## S4 method for signature 'Spectra'
sort(x, decreasing = FALSE, na.last = NA, which.col, ...)
```

Arguments

| | |
|------------|---|
| x | A Spectra object |
| decreasing | Logical. If TRUE, then the rows are sorted in decreasing order. Passed on to the sort.idx() function from the base package. Default is FALSE. |
| na.last | for controlling the treatment of NAs. Passed on to the sort.idx() function from the base package. Default is NA. |
| which.col | A character, defining the name of the column to be used in the sorting |
| ... | arguments to be passed to or from methods. See help of sort . |

Examples

```
sp <- spc.example_spectra()
sp2 <- sort(sp, which.col="Offset")
sp2$Offset
sp2 <- sort(sp, which.col="CAST", decreasing=TRUE)
sp2$CAST
```

spc.bbox2lines *Constructs a rectangle with a Spectra object*

Description

Constructs a rectangle of sp::Lines using the bounding box of a Spectra object.

Usage

```

spc.bbox2lines(object)

## S4 method for signature 'Spatial'
spc.bbox2lines(object)

## S4 method for signature 'STI'
spc.bbox2lines(object)

## S4 method for signature 'Spectra'
spc.bbox2lines(object)

```

Arguments

object spectra object t

Examples

```

sp=spc.example_spectra()
spc.bbox2lines(sp)

```

spc.cname.construct *Generating column names for a Spectra object*

Description

Function for a Spectra object that generates column names made of a combination of @shortName and @Wavelength slots. If value is omitted, the @ShortName slot is used.

Usage

```

spc.cname.construct(object, value)

## S4 method for signature 'Spectra'
spc.cname.construct(object, value)

```

Arguments

object A variable of class Spectra
value A character object

Value

vector of characters

Examples

```
sp <- spc.example_spectra()
spc.cname.construct(sp)
spc.cname.construct(sp, "Newvar")
```

spc.colMeans *Computes the mean along the rows of a Spectra object*

Description

Computes the mean along the rows of a Spectra object. The method finds the measurement closest in time to the mean time and keeps the spatial/time attributes as well as Ancillary data table (@data) associated to that measurement as that of the mean spectra

Usage

```
spc.colMeans(object)

## S4 method for signature 'Spectra'
spc.colMeans(object)
```

Arguments

object a Spectra object

Examples

```
sp=spc.example_spectra()
spc.colMeans(sp)
```

spc.colnames *Column names of Spectra object*

Description

Set or retrieve column names of a Spectra object

Usage

```
spc.colnames(x)

## S4 method for signature 'Spectra'
spc.colnames(x)

spc.colnames(x) <- value

## S4 replacement method for signature 'Spectra'
spc.colnames(x) <- value
```

Arguments

x A Spectra object
 value character vector containing new column names to be assigned

Value

spc.colnames() returns the column names of an object of class Spectra as a character vector.
 spc.colnames()<- returns a Spectra object.

See Also

[spc.cname.construct](#)

Examples

```
x <- spc.example_spectra()
head(spc.colnames(x))
# or
spc.colnames(x) <- spc.cname.construct(x)
spc.colnames(x)
```

spc.data2header *Populate fields of header slot using data from data slot*

Description

Populates a field of @header with a column data from @data slot.

Usage

```
spc.data2header(object, dataname, headerfield, compress, ...)
```

S4 method for signature 'Spectra'

```
spc.data2header(object, dataname, headerfield, compress = FALSE, ...)
```

Arguments

object A Spectra object.
 dataname A character object specifying the name of @data column to be used.
 headerfield A character object specifying the name of the @header field to be changed
 compress logical. Whether or not to compress data put into the header. See the description section.
 ... arguments to be passed to or from other methods

Details

This function extracts data from a column of the @data slot (specified by dataname) and creates a new @header field with it. If a header field is not provided, the name of the new header field will be the same as dataname.

The name of the new header field can be overwritten by providing header field. If all the incoming data rows (dataname) are the same, information put into the header can be compressed by selecting compress=TRUE (default is FALSE). This would take only the first element from the @data column.

Value

object of class Spectra

Examples

```
sp=spc.example_spectra()
sp=spc.data2header(sp,"CAST")
sp@header
sp=spc.data2header(sp,"CAST","ProjectCast")
sp@header
sp$CAST=rep(33, nrow(sp))
sp=spc.data2header(sp,"CAST","ProjectCast", compress=TRUE)
sp@header
```

spc.data2header,list-method

Populate fields of header slot using data from data slot

Description

Populates a field of @header with a column data from @data slot.

Usage

```
## S4 method for signature 'list'
spc.data2header(object, dataname, headerfield, compress = TRUE, ...)
```

Arguments

| | |
|-------------|--|
| object | Spclist object |
| dataname | A character object specifying the name of @data column to be used |
| headerfield | A character object specifying the name of the @header field to be changed |
| compress | TRUE or FALSE |
| ... | arguments to be passed to or from methods. See help of spc.data2header . |

Details

This function extracts data from a column of the @data slot (specified by dataname) and creates a new @header field with it. If headerfield is not provided, the name of the new header field will be the same as dataname. The name of the new header field can be overwritten by providing headerfield. If all the incoming data rows (dataname) are the same, information put into the header can be compressed by selecting compress=TRUE (default is FALSE). This would take only the first element from the @data column.

Value

object of class SpcList

Examples

```
sp=spc.example_spectra()
BL=spc.makeSpcList(sp,"CAST")
BL[[1]]@header
BL[[1]]=spc.data2header(BL[[1]],"CAST","ProjectCast")
BL[[1]]@header
BL[[1]]$CAST=rep(33, nrow( BL[[1]]))
BL[[1]]=spc.data2header(BL[[1]],"CAST","ProjectCast", compress=TRUE)
BL[[1]]@header
```

spc.example_spectra *Create example of Spectral object*

Description

Example of Spectral object is created by the function

Usage

```
spc.example_spectra()
```

Examples

```
sp = spc.example_spectra()
class(sp)
show(sp)
```

spc.export.text *Exporting into text format*

Description

Save the Spectra and SpcHeader objects on disk in text format and read back in.

Usage

```
spc.export.text(  
  input,  
  filename,  
  sep = ";",  
  append = FALSE,  
  writeheader = TRUE,  
  ...  
)  
  
## S4 method for signature 'Spectra'  
spc.export.text(  
  input,  
  filename,  
  sep = ";",  
  append = FALSE,  
  writeheader = TRUE,  
  ...  
)  
  
## S4 method for signature 'SpcHeader'  
spc.export.text(  
  input,  
  filename,  
  sep = ";",  
  append = FALSE,  
  writeheader = TRUE,  
  ...  
)  
  
spc.import.text(filename, sep = ";", ...)
```

Arguments

| | |
|----------|---|
| input | A Spectra object |
| filename | Name of the output text file |
| sep | character. the field separator string |
| append | logical. Only relevant if file is a character string. Default is TRUE |

writeheader either a logical value indicating whether the header names are to be written
 ... arguments to be passed to or from other methods

See Also

[spc.import.text](#)

Examples

```
x=spc.example_spectra()
fn <- tempfile()
spc.export.text(x,filename=fn)
aa=spc.import.text(fn)
dev.new()
spc.plot(aa)

#Export the SpcHeader object
fn2 <- tempfile()
spc.export.text(x@header, filename=fn2)
hdr=spc.import.text(fn2)
class(hdr)
```

spc.export.xlsx *Exports a Spectra object into Excel format.*

Description

Exports a Spectra object into Excel format.

Usage

```
spc.export.xlsx(
  input,
  filename,
  sheetName,
  writeheader = TRUE,
  append = F,
  sep = ";",
  ...
)

## S4 method for signature 'Spectra'
spc.export.xlsx(
  input,
  filename,
  sheetName,
  writeheader = TRUE,
```

```

    append = F,
    sep = ";",
    ...
)

```

Arguments

| | |
|-------------|--|
| input | A Spectra object |
| filename | Name of the output xlsx file |
| sheetName | The Spectra object to be output. |
| writeheader | A boolean, indicating whether or not the metadata (contents of the slot header) is to be included in the excel file. Default : TRUE |
| append | A boolean, indicating whether or not to append the contents of the Spectra object into the existing file. Default : FALSE (overwrites the existing Excel file if it exists.) |
| sep | Not used. |
| ... | Not used. |

Details

spc.export.xlsx() calls functions from package xlsx to write the contents of a Spectra object into an Excel file. For this function to work, make sure the package xlsx is installed.

Value

None. Simply creates an Excel file on disk.

Examples

```

## Not run:
sp=spc.example_spectra()
if("xlsx" %in% installed.packages())
  spc.export.xlsx(sp,"test.xlsx")

## End(Not run)

```

spc.getheader

Extract a field of the @header slot of a Spectra object

Description

Extracts the value of a field in the header slot of Spectra object

Usage

```
spc.getheader(object,name)

## S4 method for signature 'Spectra'
spc.getheader(object, name)
```

Arguments

| | |
|--------|-------------------------------------|
| object | A Spectra object |
| name | of the header field to be extracted |

See Also

[spc.setheader<-](#)

Examples

```
sp=spc.example_spectra()
sp@header
spc.getheader(sp,"Latitude")
```

spc.getheader,list-method

Extract a field of the @header slot of a SpcList object

Description

Extracts the value of a field in the header slot of SpcList object

Usage

```
## S4 method for signature 'list'
spc.getheader(object, name)
```

Arguments

| | |
|--------|-------------------------------------|
| object | A SpcList object |
| name | of the header field to be extracted |

Examples

```
sp=spc.example_spectra()
BL = spc.makeSpcList(sp,"CAST")
BL[[1]]@header
spc.getheader(BL,"CAST")
```

spc.getinvalid.idx *Get index of Spectra rows marked as invalid*

Description

Extract the row indexes stored as invalid

Usage

```
spc.getinvalid.idx(object)

## S4 method for signature 'Spectra'
spc.getinvalid.idx(object)
```

Arguments

object A Spectra object

Value

Logical vector

Examples

```
sp= spc.example_spectra()
spc.getinvalid.idx(sp) #No invalid rows
```

spc.getselected.idx *Extract index inside of a Spectra object*

Description

Extracts index of rows marked as selected

Usage

```
spc.getselected.idx(object)

## S4 method for signature 'Spectra'
spc.getselected.idx(object)
```

Arguments

object A Spectra object

Value

Spectra object

See Also

[spc.setselected.idx<-](#)

Examples

```
x <- spc.example_spectra()
idx=rep(FALSE,nrow(x));
idx[1:5]=TRUE
spc.setselected.idx(x)<-idx
spc.getselected.idx(x)
```

| | |
|--------------------|---|
| spc.getwavelengths | <i>Extract wave lengths of a Spectra object</i> |
|--------------------|---|

Description

Get wave lengths inside of a Spectra object

Usage

```
spc.getwavelengths(object)

## S4 method for signature 'Spectra'
spc.getwavelengths(object)
```

Arguments

object A Spectra object

Value

numeric vector of wave lengths

See Also

[spc.setwavelengths<-](#)

Examples

```
x <- spc.example_spectra()
spc.getwavelengths(x)
```

spc.header.infos *Getting as input the Spectra header*

Description

This internal function takes as input the Spectral header as a list and converts its elements to numbers (when possible) evals its elements in case the text contains some R code

Usage

```
spc.header.infos(header)
```

Arguments

header A Spectra header

Examples

```
sp=spc.example_spectra()
spc.header.infos(sp$header)
```

spc.header2data *Copy header data into the @data slot*

Description

Get the header metadata and place it inside the @data slot

Usage

```
spc.header2data(object, headerfield, dataname, compress, ...)

## S4 method for signature 'Spectra'
spc.header2data(object, headerfield, dataname, compress = TRUE, ...)

## S4 method for signature 'list'
spc.header2data(object, headerfield, dataname, compress = TRUE, ...)

## S4 method for signature 'Spclist'
spc.header2data(object, headerfield, dataname, compress = TRUE, ...)
```


Arguments

| | |
|-------------|---|
| object | A Spectra object |
| headerfield | character. Field name of the header to be copied. |
| dataname | character. Column name of @data slot to copy the incoming data. |
| compress | logical. Whether or not to compress data put into the header. See help of spc.data2header . |
| ... | arguments to be passed to or from other methods |

Details

If header element has length >1, its type is checked. If it is "character", its elements will be pasted using `paste(...,collapse="|")`. If it is another type, only the first element will be taken. For list and SpcList objects, the same procedure is repeated for all elements of the list containing Spectra objects. If dataname is missing, then it will be taken equal to headerfield.

Value

object of class Spectra or SpcList

Examples

```
sp <- spc.example_spectra()
sp <- spc.updateheader(sp,"Zone", "ZoneA")
sp <- spc.header2data(sp, "Zone")
sp$Zone
```

spc.interp.spectral *Interpolate spectral values*

Description

Estimate spectral data at a new set of wavelengths through interpolation using `approx()`.

Usage

```
spc.interp.spectral(source1,target_lbd,show.plot, ...)
```

S4 method for signature 'Spectra'

```
spc.interp.spectral(source1, target_lbd, show.plot = FALSE)
```

Arguments

| | |
|------------|---|
| source1 | A Spectra object |
| target_lbd | numeric vector giving desired wavelengths |
| show.plot | logical TRUE if a graphical representation is required |
| ... | further arguments to pass on to <code>approx()</code> . |

Examples

```

sp=spc.example_spectra()
lbd = as.numeric(c(412,440,490,555,670))
sp2 = spc.interp.spectral(sp[,lbd],c(430,450,500))
spc.plot.overlay(SpcList(list(sp,sp2)))

#Quick Plot only the first row
spc.interp.spectral(sp[,lbd],c(430,450,500),show.plot=TRUE)

```

spc.invalid.detect *Determinate invalid rows of a Spectra object*

Description

Determine invalid rows (records) of a Spectra SpcList object

Usage

```

spc.invalid.detect(source1)

## S4 method for signature 'Spectra'
spc.invalid.detect(source1)

## S4 method for signature 'list'
spc.invalid.detect(source1)

```

Arguments

source1 A Spectra object

Value

logical. TRUE for invalid rows

Examples

```

sp=spc.example_spectra()
nrow(sp)
invalid=spc.invalid.detect(sp)
show(invalid); length(invalid)

BL = spc.makeSpcList(sp,"CAST")
invalid=spc.invalid.detect(BL)
show(invalid)

```

| | |
|------------|--|
| spc.lapply | <i>Apply a function over a Spclist</i> |
|------------|--|

Description

lapply returns a list of the same length as X, each element of which is the result of applying FUN to the corresponding element of X.

Usage

```
spc.lapply(X, FUN, ...)  
  
## S4 method for signature 'Spclist'  
spc.lapply(X, FUN, ...)
```

Arguments

| | |
|-----|--|
| X | A Spclist object . |
| FUN | function to be applied to each element of X. |
| ... | optional arguments to FUN. |

Value

list or Spclist object.

Examples

```
sp=spc.example_spectra()  
BL=spc.makeSpclist(sp,"CAST")  
#Counts rows (returns a list object)  
spc.lapply(BL,function(x) {nrow(x)})  
#Perform arithmetic operations on all Spectra elements. Returns a Spclist object.  
spc.lapply(BL,function(x) {x^2+1})
```

| | |
|-----------|--|
| spc.lines | <i>Add spectra to an existing plot</i> |
|-----------|--|

Description

Adds spectra to an existing plot created by spc.plot() using lines()

Usage

```

spc.lines(x,...)

## S4 method for signature 'Spectra'
spc.lines(x, ...)
```

Arguments

x An object of class Spectra
... Additional input arguments to be passed to lines()

See Also

[spc.plot](#)

Examples

```

sp = spc.example_spectra()
spc.plot(sp[2,])
spc.lines(sp[3,],col="red")
```

spc.make.stindex

Create a spatio-temporal index based on a list of Spectra objects

Description

Given a list of Spectra objects, this function creates a STIDF object summarizing the spatial and temporal variability of the input dataset. Upon request, it also includes data columns.

Usage

```

spc.make.stindex(
  input,
  what2include = "",
  rowSimplify = "none",
  includeTIME = FALSE,
  includeLATLON = FALSE
)
```

Arguments

input An object of class spectra
what2include A character variable giving the data columns to be included in the output
rowSimplify Either of "none", "spc.colMeans", "firstRow" or "lastRow". Default is "none"
includeTIME Logical. Whether or not to include TIME data in the output STIDF object.
 Default is FALSE.

includeLATLON Logical. Whether or not to include LAT&LON data in the output STIDF object. Default is FALSE.

Details

This function accepts a list of Spectra objects and outputs one STIDF object summarizing spatial and temporal variation of the input dataset.

If rowSimplify="none", length of the output object will be equal to the sum of all rows of all elements of the input list object.

If rowSimplify="spc.colMeans", length of the output object will be equal to the number of rows of the input list object. This option returns the measurement nearest to the average time of each element of the input list.

firstRow and lastRow : length of the output object equals the number of rows of the input list object. These two options return the first and last measurements of the input list element

Value

An object of class STIDF. Each row of the output object has a space and time characteristics depending of the input argument rowSimplify.

See Also

[spc.makeSpclist](#)

Examples

```
sp = spc.example_spectra()
BL = spc.makeSpclist(sp,"STATION")
stidx = spc.make.stindex(BL)
dim(stidx)
stidx = spc.make.stindex(BL, what2include = "CAST")
head(stidx@data)
stidx = spc.make.stindex(BL, rowSimplify="spc.colMeans")
dim(stidx)
```

spc.makeSpclist

Conversion from Spectra to Spclist

Description

Conversion from Spectra to Spclist using a data field

Usage

```
spc.makeSpclist(myobj, name)
```

Arguments

myobj a Spectra object
 name name of station of a Spectra object

Examples

```
sp <- spc.example_spectra()
BL = spc.makeSpList(sp,"CAST")
show(BL)
```

 spc.plot

Plotting Spectra object

Description

Generating plot of the intensity of a measurement inside a Spectra object with respect to the wavelength.

Usage

```
spc.plot(x, Y, maxSp, lab_cex,xlab,ylab,type,pch,lwd,cex,...)
```

```
## S4 method for signature 'Spectra'
spc.plot(
  x,
  Y,
  maxSp,
  lab_cex,
  xlab,
  ylab,
  type = "l",
  pch = 19,
  lwd = 2,
  cex = 0.3,
  ...
)
```

Arguments

x and Y a Spectra data
 Y fskjldsk
 maxSp maximum number of Spectra to plot
 lab_cex vector of character expansion sizes, used cyclically
 xlab title for x axis, as in plot().

| | |
|------|---|
| ylab | title for y axis, as in plot(). |
| type | character string (length 1 vector) or vector of 1-character strings indicating the type of plot for each column of y. See help of <code>matplot()</code> or <code>plot()</code> . |
| pch | character string or vector of 1-characters or integers for plotting characters. See help of <code>par</code> . |
| lwd | vector of line widths. See help of <code>par</code> . |
| cex | A numerical value giving the amount by which plotting text and symbols should be magnified relative to the default. See help of <code>par</code> . |
| ... | any further arguments to be passed to <code>matplot</code> |

See Also

[spc.lines](#), [par](#)

Examples

```
x <- spc.example_spectra()
spc.plot(x)
```

spc.plot.depth *Plotting Spectra object*

Description

Generating plot of the contents of a Spectra object with respect to depth

Usage

```
spc.plot.depth(object, ...)

## S4 method for signature 'Spectra'
spc.plot.depth(
  object,
  X,
  maxSp = 10,
  lab_cex,
  title,
  add = FALSE,
  xlab = NULL,
  ylab = NULL,
  ylim = NULL,
  xlim = NULL,
  lwd = 2,
  ...
)
```

Arguments

| | |
|------------|--|
| object | a Spectra data. |
| ... | any further arguments of plot |
| X | character. Column names of the a Spectra object to be plotted. |
| maxSp | numeric. Maximum number of Spectra to plot. |
| lab_cex | vector of character expansion sizes, used cyclically. |
| title | a character string, title for plot |
| add | logical. If TRUE, plots are added to current one, |
| xlab, ylab | titles for x and y axes, as in plot. |
| ylim, xlim | ranges of x and y axes, as in plot. |
| lwd | numeric vector of line widths |

See Also

[spc.plot](#)

Examples

```
x <- spc.example_spectra()
spc.plot.depth(x)
```

spc.plot.depth.overlay

Plotting SpcList object

Description

Generating plot of the contents of a SpcList object overlay with respect to depth

Usage

```
spc.plot.depth.overlay(object, X, lab_cex, ...)
```

```
## S4 method for signature 'SpcList'
spc.plot.depth.overlay(object, X, lab_cex, ...)
```

Arguments

| | |
|---------|--|
| object | a SpcList data |
| X | column name or index |
| lab_cex | vector of character expansion sizes, used cyclically |
| ... | any further arguments of plot |

Examples

```
sp <- spc.example_spectra()
BL = spc.makeSpclist(sp, "CAST")
spc.plot.depth.overlay(BL, "anap_555")
```

spc.plot.depth.plotly *Display a Spectra object*

Description

Plot a Spectra object with respect to depth

Usage

```
spc.plot.depth.plotly(
  sp,
  column,
  plot.max = 10,
  showlegend = FALSE,
  hoverinfo = "name",
  title = sp@LongName
)

## S4 method for signature 'Spectra'
spc.plot.depth.plotly(
  sp,
  column,
  plot.max = 10,
  showlegend = FALSE,
  hoverinfo = "name",
  title = sp@LongName
)
```

Arguments

| | |
|------------|---|
| sp | A Spectra object |
| column | Number or name , default value is 10 if a number or name has not been entered |
| plot.max | numeric value for a maximum number of data in plot |
| showlegend | logical, to display legend or not, default is FALSE |
| hoverinfo | a character, info about Spectra object to be used in hover box |
| title | a character string, title for plot |

Examples

```

sp = spc.example_spectra()
BL = spc.makeSpclist(sp,"CAST")
p1<-spc.plot.depth.plotly(BL[[5]])
#p1<-layout(p1,title=paste("CAST =", BL[[5]]$CAST[1]))
p2<-spc.plot.depth.plotly(BL[[4]])
#p2<-plotly::layout(p2,title=paste("CAST =", BL[[4]]$CAST[1]))
p <- plotly::subplot(p1, p2, margin = 0.05, shareY=TRUE,shareX=TRUE,titleX=TRUE,titleY=TRUE)
p <- plotly::layout(p, showlegend = TRUE,
  annotations = list(
    list(x = 0.2 , y = 1.05, text = BL[[5]]$CAST[1], showarrow = FALSE, xref='paper', yref='paper'),
    list(x = 0.8 , y = 1.05, text = BL[[4]]$CAST[1], showarrow = FALSE, xref='paper', yref='paper'))
p

```

spc.plot.grid

Plotting Spclist object in a grid

Description

Generating plot of the contents of a Spclist object in a grid

Usage

```
spc.plot.grid(x,FUN, nrow, ncol, mar,oma, lab_cex, ...)
```

```

## S4 method for signature 'Spclist'
spc.plot.grid(
  x,
  FUN,
  nrow,
  ncol,
  mar = c(4, 4.5, 1, 0.5),
  oma = c(0, 0, 0, 0),
  lab_cex,
  ...
)

```

Arguments

| | |
|------|---|
| x | a Spclist data |
| FUN | a character string giving the name of the plotting function to be used. Can be either of "spc.plot" |
| nrow | number of rows for the grid to be produced |
| ncol | number of columns for the grid to be produced |
| mar | A numeric vector of length 4, which sets the margin sizes in the following order: bottom, left, top, and right. The default is c(4,4.5,1,0.5) |

| | |
|---------|--|
| oma | oma the "outer margin area" around a figure or figures. The usage of mar and oma is shown when plotting a single figure, |
| lab_cex | vector of character expansion sizes, used cyclically |
| ... | any further arguments of plot |

Examples

```
sp <- spc.example_spectra()
BL = spc.makeSpclist(sp,"CAST")
spc.plot.grid(BL,"spc.plot",3,2)
```

spc.plot.map.leaflet *Display a Spectra object*

Description

Create a point map with leaflet engine using Spectra rows

Usage

```
spc.plot.map.leaflet(
  sp,
  hover_field = "row",
  color = "#FF0000",
  opacity = 1,
  weight = 5
)

## S4 method for signature 'Spectra'
spc.plot.map.leaflet(
  sp,
  hover_field = "row",
  color = "#FF0000",
  opacity = 1,
  weight = 5
)
```

Arguments

| | |
|-------------|---|
| sp | Spectra object |
| hover_field | A character or vector of strings giving column names of Spectra object. This information will be displayed when hovering over the glyph |
| color | Determine color of points |
| opacity | The opacity transparency of the glyph between 0 (transparent) and 1 (opaque) |
| weight | Stroke width in pixels |

Examples

```
sp=spc.example_spectra()
spc.plot.map.leaflet(sp)
```

spc.plot.map.plotly *Display a Spectra object*

Description

Create a point map with plotly engine using Spectra rows

Usage

```
spc.plot.map.plotly(sp, hover_field = "row", color = "#FF0000", opacity = 1)

## S4 method for signature 'Spectra'
spc.plot.map.plotly(sp, hover_field = "row", color = "#FF0000", opacity = 1)
```

Arguments

| | |
|-------------|--|
| sp | A Spectra object |
| hover_field | A character, column names of sp object to be used in hover box |
| color | Determine color of points |
| opacity | The opacity transparency of the glyph between 0 (transparent) and 1 (opaque) |

Examples

```
sp <- spc.example_spectra()
spc.plot.map.plotly(sp)
```

spc.plot.map.rbokeh *Display a Spectra object*

Description

Create a point map with rbokeh engine using Spectra rows

Usage

```

spc.plot.map.rbokeh(
  sp,
  glyph = 2,
  color = "#FF0000",
  legend = NULL,
  hover = "row",
  opacity = 1
)

## S4 method for signature 'Spectra'
spc.plot.map.rbokeh(
  sp,
  glyph = 2,
  color = "#FF0000",
  legend = NULL,
  hover = "row",
  opacity = 1
)

```

Arguments

| | |
|---------|--|
| sp | Spectra object |
| glyph | Value(s) or field name of the glyph to use point_types |
| color | Determine color of points |
| legend | not implemented yet |
| hover | String or vector of strings giving column names of Spectra object. This information will be displayed when hovering over the glyph |
| opacity | The opacity transparency of the glyph between 0 (transparent) and 1 (opaque) |

Examples

```

## Not run:
sp=spc.example_spectra()
spc.plot.map.rbokeh(sp, hover = "Snap")
spc.plot.map.rbokeh(sp)

## End(Not run)

```

Description

This function overlays spectra plots of several Spectra objects inside a SpcList object. The first element of the input SpcList object is plotted with spc.plot() while remaining elements are overlaid with spc.lines().

Usage

```
spc.plot.overlay(object,lab_cex,leg_idx, type, lty,lwd, col, ...)

## S4 method for signature 'SpcList'
spc.plot.overlay(
  object,
  lab_cex = 1,
  leg_idx = TRUE,
  type = "l",
  lty = 1,
  lwd = 1,
  col,
  ...
)
```

Arguments

| | |
|---------|---|
| object | A SpcList data |
| lab_cex | vector of character expansion sizes, used cyclically |
| leg_idx | logical If it is of length 1, it determines whether or not to display the legend. If length(leg_idx) is bigger than 1, then its lengths has to equal length(object). Default is TRUE. |
| type | character string (length 1 vector) or vector of 1-character strings indicating the type of plot for each column of y, |
| lty | vector of line types. See par(). |
| lwd | numeric. Vector of line widths. See par(). |
| col | A specification for the default plotting color. See par(). |
| ... | any further arguments to the plotting function matplot() or spc.plot() |

Examples

```
sp <- spc.example_spectra()
BL = spc.makeSpcList(sp,"CAST")
spc.plot.overlay(BL)
spc.plot.overlay(BL, xlim=c(400,500),ylim=c(0,0.2),lwd=2)
spc.plot.overlay(BL, col=c("red"), leg_idx=FALSE, lty=2)
spc.plot.overlay(BL, col=c("red","blue","green","yellow","cyan","black"))
```

spc.plot.plotly *Plot a Spectra object data*

Description

Plot a Spectra object with plotly engine

Usage

```
spc.plot.plotly(  
  sp,  
  plot.max = 10,  
  showlegend = FALSE,  
  legend_field = "row",  
  hoverinfo = "title",  
  title = sp@LongName  
)  
  
## S4 method for signature 'Spectra'  
spc.plot.plotly(  
  sp,  
  plot.max = 10,  
  showlegend = FALSE,  
  legend_field = "row",  
  hoverinfo = "title",  
  title = sp@LongName  
)
```

Arguments

| | |
|--------------|--|
| sp | A Spectra object |
| plot.max | numeric value for a maximum number of data in plot. Default is 10. |
| showlegend | logical, to display legend or not, default is FALSE |
| legend_field | character. Gives the name of the column to be used in the legend. |
| hoverinfo | a character, info about Spectra object to be used in hover box. |
| title | a character string, title for plot. |

Examples

```
sp = spc.example_spectra()  
spc.plot.plotly(sp)  
spc.plot.plotly(sp, legend_field = "Spectra")  
spc.plot.plotly(sp, legend_field = "CAST")  
spc.plot.plotly(sp, legend_field = "NISKIN")  
spc.plot.plotly(sp, legend_field = "STATION")  
spc.plot.plotly(sp, legend_field = "anap_440")
```

spc.plot.time *Plotting Spectra object*

Description

Generating plot of the contents of a Spectra object with respect to time. If xdata is 'time', data is plotted with respect to the 'TIME' column. If xdata is 'observations', data is plotted with respect to an integer index equal to 1:nrow(object).

Usage

```
spc.plot.time(object, ...)  
  
## S4 method for signature 'Spectra'  
spc.plot.time(object, Y, maxSp = 50, xdata = "time", lab_cex, lwd = 2, ...)
```

Arguments

| | |
|---------|---|
| object | A Spectra object. |
| ... | any further arguments of plot |
| Y | character. Name of the columns of the Spectra object to be plotted. |
| maxSp | numeric. Maximum number of Spectra to plot. |
| xdata | character. Type of time-series data. Can be 'time' or 'observations'. |
| lab_cex | vector of character expansion sizes, used cyclically. |
| lwd | vector of line widths |

See Also

[spc.plot.depth](#)

Examples

```
x <- spc.example_spectra()  
spc.plot.time(x)
```

spc.plot.time.plotly *Plot a Spectra object data with respect to time*

Description

Plot a Spectra object with respect to time

Usage

```
spc.plot.time.plotly(  
  sp,  
  column,  
  plot.max = 10,  
  showlegend = FALSE,  
  hoverinfo = "name",  
  title = sp@LongName  
)  
  
## S4 method for signature 'Spectra'  
spc.plot.time.plotly(  
  sp,  
  column,  
  plot.max = 10,  
  showlegend = FALSE,  
  hoverinfo = "name",  
  title = sp@LongName  
)
```

Arguments

| | |
|------------|---|
| sp | A Spectra object |
| column | Number or name , default value is 10 if a number or name has not been entered |
| plot.max | numeric value for a maximum number of data in plot |
| showlegend | logical, to display legend or not, default is FALSE |
| hoverinfo | a character, info about Spectra object to be used in hover box |
| title | a character string, title for plot |

Examples

```
## Not run:  
sp = spc.example_spectra()  
spc.plot.time.plotly(sp)  
spc.plot.time.plotly(sp, plot.max = 3)  
spc.plot.time.plotly(sp, c("anap_450", "anap_550", "anap_650"))  
  
## End(Not run)
```

`spc.rbind`*Combine Spectra Objects by Rows*

Description

Take a Spectra objects and combine by rows

Usage

```
spc.rbind(...)  
  
## S4 method for signature 'Spectra'  
spc.rbind(..., compressHeader = TRUE)
```

Arguments

```
...           Spectra object  
compressHeader Compress the header (make multiple all-equal header elements as ONE, default  
              value is TRUE)
```

Value

Spectra object

Examples

```
x <- spc.example_spectra()  
nrow(x) #[1] 26  
x2=spc.rbind(x,x)  
nrow(x2) #[1] 52
```

`spc.rbind,STIDF-method`*Combine STIDF objects by Rows*

Description

Take a STIDF objects and combine by rows

Usage

```
## S4 method for signature 'STIDF'  
spc.rbind(...)
```

Arguments

... STIDF object

Examples

```
x <- spc.example_spectra()
nrow(x) #[1] 26
x2 <- spc.rbind(as(x, "STIDF"),as(x, "STIDF"))
nrow(x2) #[1] 52
```

| | |
|--------------|--|
| spc.Read_ASD | <i>Read the ASD Spectra from text file</i> |
|--------------|--|

Description

Imports ASD spectra from text files prepared by the software provided by ASD inc. This function imports only one spectra per file.

Usage

```
spc.Read_ASD(filename)
```

Arguments

filename A string name of the input text file containing the raw ASD data.

Value

Returns an object of class Spectra.

Examples

```
filename = file.path(system.file(package = "geoSpectral"),"test_data", "106.064.txt")
L = spc.Read_ASD(filename)
class(L)
spc.plot.plotly(L)
```

```
spc.Read_NOMAD_v2      Read the NOMAD v2 bio-optical database
```

Description

Imports the NOMAD v2 database of the SeaBASS project. More information about this dataset can be found at <https://seabass.gsfc.nasa.gov/wiki/NOMAD>

Usage

```
spc.Read_NOMAD_v2(skip.all.na.rows = TRUE)
```

Arguments

```
skip.all.na.rows
                logical whether or not eliminate records where all channels are NAs
```

Value

Returns an object of class `data.frame`.

Examples

```
nomad = spc.Read_NOMAD_v2()
class(nomad[[1]])
spc.plot.plotly(nomad[[4]], plot.max=15)
```

```
spc.select      Selecting rows of a Spectra object with the mouse
```

Description

This function allows the selection of Spectra rows that is drawn with `spc.plot` or `spc.lines`. Selected lines will be colored red. Pressing the escape button will end the selection process and return selection results.

Usage

```
spc.select(object)

## S4 method for signature 'Spectra'
spc.select(object)
```

Arguments

```
object      A Spectra object
```

Value

logical Row indexes, TRUE for selected data rows.

See Also

[spc.plot](#) [spc.lines](#)

Examples

```
sp <- spc.example_spectra()
spc.plot(sp)
spc.setselected.idx(sp)<-spc.select(sp)
```

spc.setheader<- *Set a field of the @header slot of a Spectra object*

Description

Function sets or changes the value of a field in the header slot of Spectra object

Usage

```
spc.setheader(object) <- value

## S4 replacement method for signature 'Spectra'
spc.setheader(object) <- value
```

Arguments

| | |
|--------|---------------------------|
| object | A Spectra object |
| value | Object of class SpcHeader |

See Also

[spc.getheader](#)

Examples

```
sp=spc.example_spectra()
a=new("SpcHeader") # create new SpcHeader class
a$Longitude=123
spc.setheader(sp) <- a
sp@header
```

```
spc.setheader<-,list-method
```

Set a field of the @header slot of a SpcList object

Description

Function sets or changes the value of a field in the header slot of SpcList object.

Usage

```
## S4 replacement method for signature 'list'
spc.setheader(object) <- value
```

Arguments

| | |
|--------|--------------------------|
| object | A SpcList object. |
| value | Object of class SpcList. |

Examples

```
sp=spc.example_spectra()
BL=spc.makeSpcList(sp,"CAST")
a=new("SpcHeader") # create new SpcHeader class
a$Longitude=123
spc.setheader(BL[[1]]) <- a
h=spc.getheader(BL[[1]])
h
```

```
spc.setinvalid.idx<- Set rows of Spectra as invalid
```

Description

Stores the row indexes to be stored as invalid.

Usage

```
spc.setinvalid.idx(object) <- value

## S4 replacement method for signature 'Spectra'
spc.setinvalid.idx(object) <- value
```

Arguments

| | |
|--------|------------------|
| object | A Spectra object |
| value | Logical vector |

See Also[spc.setselected.idx<-](#)**Examples**

```
sp = spc.example_spectra()
spc.getinvalid.idx(sp) #No invalid rows
vld = rep(TRUE,26)
vld[1:5]<-FALSE
spc.setinvalid.idx(sp)<-vld #Mark the first 5 rows as invalid
spc.getinvalid.idx(sp)
```

`spc.setselected.idx<-` *Set index to a Spectra object*

Description

Set or change selected row index of a Spectra object

Usage

```
spc.setselected.idx(object) <- value

## S4 replacement method for signature 'Spectra'
spc.setselected.idx(object) <- value
```

Arguments

| | |
|---------------------|----------------------------|
| <code>object</code> | A Spectra object |
| <code>value</code> | index for a Spectra object |

Value

A Spectra object

See Also[spc.getselected.idx](#)**Examples**

```
x <- spc.example_spectra()
idx=rep(FALSE,nrow(x));
idx[1:5]=TRUE
spc.setselected.idx(x)<-idx
spc.plot(x)
```

spc.setwavelengths<- *Setting wavelengths in a Spectra object*

Description

Function to change or set wavelengths inside of a Spectra object

Usage

```
spc.setwavelengths(object) <- value

## S4 replacement method for signature 'Spectra'
spc.setwavelengths(object) <- value
```

Arguments

| | |
|--------|------------------|
| object | A Spectra object |
| value | Numeric |

See Also

[spc.getwavelengths](#)

Examples

```
x <- spc.example_spectra()
show(x)
spc.setwavelengths(x) <- 300:800
show(x)
```

spc.STI.stdistance *Report the space and time distance of each row of an STI-inherited object*

Description

Function that reports the space and time distance of each row of the STI-inherited object searched to the corresponding row of the STI-inherited object master

Usage

```
spc.STI.stdistance(master, searched, report = F)
```


Arguments

- master An STI-inherited object
- searched An STI-inherited object
- report Logical. Default value is FALSE

Details

Reports the space and time distance of each row of the STI-inherited object searched to the corresponding row of the STI-inherited object master.

Value

Outputs a data.frame, with two columns : time2master ("difftime", in seconds) and distance2master ("numeric", in meters)

| | |
|---------------|---------------------------------|
| spc.timeMatch | <i>Match two time sequences</i> |
|---------------|---------------------------------|

Description

Match two time sequences for a Spectra object, where each can be intervals or instances.

Usage

```
spc.timeMatch(master, searched, returnList, method, limits, report)
```

Arguments

- master ordered sequence of variable of class Spectra
- searched A variable of class Spectrawhich is searched
- returnList Boolean; should a list be returned with all matches (TRUE), or a vector with single matches (FALSE)?
- method Method used in time-based matching. See the details section.
- limits the interval limits
- report return character string which has information about searching results, default is False

Details

spc.timeMatch is similar to spacetime::timeMatch(), only adding some more matching methods. When method is "over", the same technique used by spacetime::timeMatch() is used. Useful when matched timestamps of both master and searched are exactly equal. When method is "nearest", the nearest measurement will be found, matching only one data for ALL elements of master. When method is "within", measurements that are within the interval limits=c(upper,lower) (in seconds) will be found.

Examples

```
#Read the Nomad database inside a SpcList object.
dat = SpcList(spc.Read_NOMAD_v2())

#Different list elements contain different parameters
names(dat)

#We would like to find elements of Es that match time-wise rows of Kd.
nrow(dat$kd); nrow(dat$es)

#Use spc.timeMatch() to get row indexes of Es that would match those of Kd time-wise
t_idx=spc.timeMatch((dat$kd), (dat$es))
#Verification
all(time(dat$es)[t_idx]==time(dat$kd))
```

| | |
|------------------|---|
| spc.updateheader | <i>Update a field of the @header slot of a Spectra object</i> |
|------------------|---|

Description

Updates or changes the value of a field in the header slot of Spectra object

Usage

```
spc.updateheader(object,Name,value,...)

## S4 method for signature 'Spectra'
spc.updateheader(object, Name, value, ...)

## S4 method for signature 'list'
spc.updateheader(object, Name, value)
```

Arguments

| | |
|--------|---|
| object | A Spectra object |
| Name | of the header field to be updated |
| value | to update header with |
| ... | arguments to be passed to or from other methods |

Examples

```
sp=spc.example_spectra()
sp@header
sp <- spc.updateheader(sp,"Station", 11)
sp@header
```

```
#SpcList example
sp=spc.example_spectra()
BL=spc.makeSpcList(sp,"CAST")
BL[[1]]@header
BL[[1]] <- spc.updateheader(BL[[1]],"Station", 11)
BL[[1]]@header
```

| | |
|-----------------|--|
| SpcHeader-class | <i>SpcHeader class for header object storing metadata.</i> |
|-----------------|--|

Description

Definition for SpcHeader. This class is required for the @header slot of Spectra object. This class directly inherits R lists, so there is no additional slots.

Examples

```
new("SpcHeader")
```

| | |
|--------------|--|
| SpcHeaderAdd | <i>Set a field of the @header slot of a SpcHeader class object</i> |
|--------------|--|

Description

Function add the value of a field in the header slot of SpcHeader class object

Usage

```
SpcHeaderAdd (object,Name,Value,...)
```

```
## S4 method for signature 'SpcHeader'
SpcHeaderAdd(object, Name, Value)
```

Arguments

| | |
|--------|---|
| object | of class SpcHeader |
| Name | a character variable |
| Value | a numeric variable |
| ... | arguments to be passed to or from other methods |

Examples

```
sp=spc.example_spectra()
sp@header
sp@ShortName
sp@header=SpcHeaderAdd(sp@header , sp@ShortName, 10)
sp@header
```

Spclist-class Spclist *class*.

Description

Definition for Spclist. This class provides a collection of multiple Spclist objects inside a list.

Examples

```
h1 = new("Spclist")
h2 = new("Spclist")
as(list(h1, h2), "Spclist")
new("Spclist")
```

Spclist *Constructor function for the Spclist class.*

Description

With this function, it is easy to create a Spclist object given an list containing multiple Spectra objects.

Usage

```
Spclist(x)
```

Arguments

x a list object

Examples

```
sp=spc.example_spectra()
#Create an Spclist object using two Spectra objects
as(list(sp,sp^2), "Spclist")
#the above is the same as
Spclist(list(sp,sp^2))
```

| | |
|---------------|---------------------------------|
| Spclist-class | <i>Spclist class definition</i> |
|---------------|---------------------------------|

Description

Definition for Spclist, a class to store multiple Spectra objects inside a list-like object. See the help of the constructor function [Spclist](#).

Slots

.Data list, Inherited R list object

by character, Determines the header field in the Spectra objects within the Spclist that describes how they are different one from the other.

| | |
|---------|--|
| Spectra | <i>Constructor function for the class Spectra.</i> |
|---------|--|

Description

Spectra Creates an instance of class Spectra.

Usage

```
Spectra(inDF, Spectra, Wavelengths, Units, space, time, endTime, header, ...)
```

Arguments

| | |
|-------------|--|
| inDF | a long-format data.frame containing LAT,LON and TIME columns as well as Ancillary data. See stConstruct for more information on long DF format. |
| Spectra | matrix containing spectral data. Channels are in columns, observations are in rows. If Spectra is missing, the first length(Wavelengths) columns of inDF will be taken as spectral data. |
| Wavelengths | numeric vector containing wavelengths of spectral channels. |
| Units | character defining the units of the wavelengths. |
| space | a character or integer holding the column index in inDF where the spatial coordinates are (if length(space)==2) or where the ID of the spatial location is (if (length(space)==1). If space is not provided, inDF columns are searched to match one of the following : LAT,lat,latitude,LATITUDE,LON,LONG,lon,long,longitude,LONGITUDE. If LAT & LON are not found, they set the dummy value of 1. |
| time | character or integer indicating the column in inDF containing POSIXct TIME data values. if time is missing, it is set the dummy integer sequential vector of 1:nrow(Spectra). |

| | |
|---------|--|
| endTime | character or integer indicating the column in inDF containing POSIXct END-TIME data values. If the temporal measurements are performed over an interval, time and endTime contain the time for the start and end of intervals respectively. If the temporal measurements are performed over a time-instance, then endTime==TIME. If endTime is not provided, inDF columns are searched to match ENDTIME. If none found, then it is assumed that data are time-instance measurements. For more information, see the documentation of spacetime . |
| header | SpcHeader object containing metadata |
| ... | other input arguments to be passed to the new() function |

Details

This constructor function uses The function Spectra() calls spacetime::stConstruct() that is the constructor of the STIDF class using an input data.frame object of long-table format.

length{@Wavelengths}==ncol{@Spectra}. The default @WavelengthsUnit is nm^-1.

Value

Returns an object of class Spectra.

Examples

```

fnm = file.path(base::system.file(package = "geoSpectral"),
"test_data", "particulate_absorption.csv.gz")
fnm=gsub("\\\\", "/", fnm)
abs = read.table(fnm, sep=",", header=TRUE)
abs$STATION=factor(abs$STATION)
abs[1:2,1:17] #Display only the first 2 rows and first 17 columns if the data frame
lbd = as.numeric(gsub("X", "", colnames(abs)[14:514]))
Units="1/m"
colnames(abs)= gsub("X", paste("anap", "_", sep=""), colnames(abs))
colnames(abs)= gsub("PRES", "DEPTH", colnames(abs))
abs = abs[,c(14:514,1:13)] #Rearrange so that Spectra columns come first
tz<-strsplit(as.character(abs$TIME), " ")[[1]][[3]] #Extract the timezone
abs$TIME = as.POSIXct(as.character(abs$TIME), tz=tz) #Compute the time

#Space and time columns are automatically found in the column names of inDF
myS<-Spectra(abs, Wavelengths=lbd, Units=Units, ShortName="a_nap")

#Space and time columns are explicitly chosen from inDF columns
myS<-Spectra(abs, Wavelengths=lbd, space=c("LONG", "LAT"), time="TIME",
Units=Units, ShortName="a_nap")

```

| | |
|---------------|---------------------------------|
| Spectra-class | <i>Spectra class definition</i> |
|---------------|---------------------------------|

Description

Spectra class is the main class provided by the package `geoSpectRal`. It allows storage of spectral or non-spectra data with space and time attributes.

Slots

`ShortName` character, A short name for the parameter described in the spectra object.

`LongName` character, A long name for the parameter described in the spectra object.

`Spectra` matrix, n by m matrix, describing n rows of spectral data (or time) in m channels (columns).

`data` data.frame n by t data frame, describing n rows of ancillary data of t variables. This slot is inherited from `STIDF` class.

`Wavelengths` numeric vector, length of m. Wavelength data.

`WavelengthsUnit` character, Units of the `@Wavelength` slot

`header` `SpcHeader`, Header object. See `SpcHeader`-class.

`Units` character, Units of spectral data.

`UnitsAnc` character, Units of each column of the `@data` slot holding ancillary data.

`ShortNameAnc` character, A short name for each column of the `@data` slot holding ancillary data.

`LongNameAnc` character, A long name for each column of the `@data` slot holding ancillary data.

`InvalidIdx` logical, length of m. Row index for measurements marked by the user as invalid.

`SelectedIdx` logical, length of m. Row index for measurements marked by the user as selected.

`ClassVersion` numeric, Version of the class.

| | |
|----------------|--|
| Spectra-coerce | <i>Conversion between Spectra and data.frame objects</i> |
|----------------|--|

Description

Converting `Spectra` object to `data.frame` is straightforward while the conversion in the opposite direction requires a set of attributes to be present in the source `data.frame` object. These attributes are generally created during the conversion of a `Spectra` object into `data.frame`, they can also be manually set if they are non-existent (see the example below).

Arguments

| | |
|-------------------|------------------------------------|
| <code>from</code> | The input object |
| <code>to</code> | Name of the class of output object |

Examples

```
#Convert a Spectra object to data.frame
sp <- spc.example_spectra()
df <- as(sp, "data.frame")
class(df); dim(df)
attributes(df)

#Convert the data.frame back to Spectra
sp2 <- as(df, "Spectra")

#Convert a bare data.frame to Spectra with minimal attributes
df2 <- data.frame(ch1=c(1,2,3,4), ch2=c(5,6,7,8), TIME=Sys.time()+1:4, LAT=1:4, LON=5:8)
attr(df2, "Units") <- "m-1"
attr(df2, "Wavelengths") <- c(500, 600)
attr(df2, "ShortName") <- "abs"
as(df2, "Spectra")
```

subset,Spclist-method *Subsetting for a spclist and Spectra classes*

Description

Subsetting can be achieved using the implementation of the R function `subset()` for Spectra and Spclist classes. It is possible to perform a row-wise selection. The argument "select" is not implemented yet. Use "[]".

Usage

```
## S4 method for signature 'Spclist'
subset(x, subset, select, drop = FALSE, ...)
```

Arguments

| | |
|--------|--|
| x | A Spectra object. |
| subset | logical expression indicating elements or rows to keep: missing values are taken as false. |
| select | expression, indicating columns to select from the Spectra object. |
| drop | passed on to [indexing operator. Default is FALSE . |
| ... | arguments to be passed to or from other methods. |

Examples

```
fnm = file.path(system.file(package = "geoSpectral"), "test_data","particulate_absorption.csv.gz")
abs = read.table(fnm,sep="," ,header=TRUE)
abs$STATION=factor(abs$STATION)
abs[1:2,1:17] #Display only the first 2 rows and first 17 columns if the data frame
lbd = as.numeric(gsub("X","",colnames(abs)[14:514]))
```



```

Units="1/m"
colnames(abs)= gsub("X",paste("anap","_",sep=""), colnames(abs))
colnames(abs)= gsub("PRES","DEPTH", colnames(abs))
abs = abs[,c(14:514,1:13)]
tz<-strsplit(as.character(abs$TIME)," ")[[1]][[3]] #Extract the timezone
abs$TIME = as.POSIXct(as.character(abs$TIME),tz=tz)
myS<-Spectra(abs,Wavelengths=lbd,Units=Units,ShortName="a_nap")
myS
head(spc.getwavelengths(myS))
spc.setwavelengths(myS) <- 300:800
myS[1:10]
myS[, "anap_400"]
myS[,c("anap_400","anap_500")]
myS[1:10,30:50] #Selection of channels by column index
lbd = as.numeric(c(412,440,490,555,670))
myS[1:10,lbd] #Selection of channels by wavelength
myS[1:10,"415::450"]
myS$CAST #Returns Ancillary data
myS$anap_400 #Returns spectra as numeric vector
head(myS[["anap_400"]]) #Returns spectra as numeric vector
head(myS[[c("Snap","Offset")]]) #Returns data.frame
#Subsetting rows with respect to the value of Ancillary data
subset(myS,DEPTH<=30)
#Subsetting rows with respect to the value of Spectral data
subset(myS,anap_440<=0.01)
#Selecting Ancillary data columns, leaving Spectral columns intact
subset(myS,subset=DEPTH<=30,select="CAST")

```

subset,Spectra-method *Subsetting for a Spectra and spcList classes*

Description

Subsetting can be achieved using the implementation of the R function `subset()` for Spectra and SpcList classes. It is possible to perform a row-wise selection.

Usage

```
## S4 method for signature 'Spectra'
subset(x, subset, select, drop = FALSE, ...)
```

Arguments

| | |
|---------------------|--|
| <code>x</code> | A Spectra object |
| <code>subset</code> | logical expression indicating elements or rows to keep: missing values are taken as false. |
| <code>select</code> | Condition selected |
| <code>drop</code> | passed on to [indexing operator. Default is FALSE |
| <code>...</code> | arguments to be passed to or from other methods. |

Examples

```

fnm = file.path(system.file(package = "geoSpectral"), "test_data", "particulate_absorption.csv.gz")
abs = read.table(fnm, sep=",", header=TRUE)
abs$STATION=factor(abs$STATION)
abs[1:2,1:17] #Display only the first 2 rows and first 17 columns if the data frame
lbd = as.numeric(gsub("X","", colnames(abs)[14:514]))
Units="1/m"
colnames(abs)= gsub("X",paste("anap","_",sep=""), colnames(abs))
colnames(abs)= gsub("PRES","DEPTH", colnames(abs))
abs = abs[,c(14:514,1:13)]
tz<-strsplit(as.character(abs$TIME)," ")[[1]][[3]] #Extract the timezone
abs$TIME = as.POSIXct(as.character(abs$TIME),tz=tz)
myS<-Spectra(abs,Wavelengths=lbd,Units=Units,ShortName="a_nap")
myS
head(spc.getwavelengths(myS))
spc.setwavelengths(myS) <- 300:800
myS[1:10]
myS[, "anap_400"]
myS[,c("anap_400","anap_500")]
myS[1:10,30:50] #Selection of channels by column index
lbd = as.numeric(c(412,440,490,555,670))
myS[1:10,lbd] #Selection of channels by wavelength
myS[1:10,"415:450"]
myS$CAST #Returns Ancillary data
myS$anap_400 #Returns spectra as numeric vector
head(myS[["anap_400"]]) #Returns spectra as numeric vector
head(myS[[c("Snap","Offset")]]) #Returns data.frame
#Subsetting rows with respect to the value of Ancillary data
subset(myS,DEPTH<=30)
#Subsetting rows with respect to the value of Spectral data
subset(myS,anap_440<=0.01)
#Selecting Ancillary data columns, leaving Spectral columns intact
subset(myS,subset=DEPTH<=30,select="CAST")

```

\$,Spclist-method

Extract or replace parts of a SpcList object

Description

Operators acting on Spectra objects to extract or replace parts

Usage

```

## S4 method for signature 'SpcList'
x$name

```

Arguments

| | |
|------|---|
| x | A Spectra object from which to extract element(s) or in which to replace element(s) |
| name | A character (column name) |

Examples

```

sp<-spc.example_spectra()
BL = spc.makeSpList(sp,"STATION")

#Extract station 394 (returns Spectra object)
BL$`394`

BL@by="CRUISE"
BL[[1]]$CRUISE="Cruise1"
BL[[2]]$CRUISE="Cruise2"
BL[[3]]$CRUISE="Cruise3"
BL[[4]]$CRUISE="Cruise4"
names(BL)
BL$Cruise4

```

\$,Spectra-method *Extract or replace parts of a Spectra object*

Description

Operators acting on Spectra objects to extract parts

Operators acting on Spectra object and Spectra lists to extract or replace parts.

Usage

```

## S4 method for signature 'Spectra'
x$name

## S4 replacement method for signature 'Spectra'
x$name <- value

## S4 method for signature 'Spectra'
x[i, j]

## S4 method for signature 'Spectra,character,missing'
x[[i, j]]

## S4 replacement method for signature 'Spectra,character,missing'
x[[i, j]] <- value

```

Arguments

| | |
|-------|--|
| x | A Spectra object from which to extract element(s) or in which to replace element(s) |
| name | A character (column name) or a numeric (column index) variable |
| value | A vector or matrix or data.frame. Values to be replaced with matched Spectra column. |
| i | A numeric (row index) variable |
| j | A character (column name) or a numeric (column index) variable |

Details

These operators are generic. You can write methods to handle indexing of specific classes of objects

Examples

```

sp<-spc.example_spectra()
# spc.colnames() is used to extract column names
head(spc.colnames(sp))
head(sp$anap_300)
sp[, "anap_345"]
sp[, "anap_345"] #returns Spectra object with only one channel (column)
sp[1:3, "anap_345"] #returns Spectra object with first 3 rows and only one channel (column)
# spc.colnames() is used to extract column names
head(spc.colnames(sp))
head(sp$anap_300)
sp[, "anap_345"]
sp=spc.example_spectra()
sp #501 spectral channels in columns and 26 observations in rows
sp[1] #returns Spectra object, 501 spectral channels in columns and 1 observations in rows
names(sp)
sp[["CAST"]] #returns the CAST data column
sp[[4]] #returns the CAST data column
sp[["CAST"]]=12 #Modify the CAST column
sp[["CAST"]] #returns the CAST data column

```

Index

[, Spectra-method (\$, Spectra-method), 59
[[, Spectra, character, missing-method
(\$, Spectra-method), 59
[[<- , Spectra, character, missing-method
(\$, Spectra-method), 59
\$, SpcList-method, 58
\$, Spectra (\$, Spectra-method), 59
\$, Spectra-method, 59
\$<- , Spectra (\$, Spectra-method), 59
\$<- , Spectra-method (\$, Spectra-method),
59

Arith, 4
Arith, Spectra, numeric-method
(Arith, Spectra, Spectra-method),
3
Arith, Spectra, Spectra-method, 3
as, Spectra (Spectra-coerce), 55

dim, Spectra-method, 4

geoSpectral, 5

head, Spectra-method, 5

Math, Spectra-method
(Arith, Spectra, Spectra-method),
3

names, SpcList-method, 6
names, Spectra-method, 7
ncol, Spectra-method, 7
nrow, Spectra-method, 8

par, 31
point_types, 37

rep, 8
rep, Spectra-method, 8

show, 9
show, SpcHeader-method, 9
show, SpcList-method, 10
show, Spectra-method, 10
sort, 11, 12
sort, SpcList-method, 11
sort, Spectra-method, 12
spc.bbox2lines, 12
spc.bbox2lines, Spatial-method
(spc.bbox2lines), 12
spc.bbox2lines, Spectra-method
(spc.bbox2lines), 12
spc.bbox2lines, STI-method
(spc.bbox2lines), 12
spc.cname.construct, 13, 15
spc.cname.construct, Spectra-method
(spc.cname.construct), 13
spc.colMeans, 14
spc.colMeans, Spectra-method
(spc.colMeans), 14
spc.colnames, 14
spc.colnames, Spectra-method
(spc.colnames), 14
spc.colnames<- (spc.colnames), 14
spc.colnames<- , Spectra-method
(spc.colnames), 14
spc.data2header, 15, 16, 25
spc.data2header, list-method, 16
spc.data2header, Spectra-method
(spc.data2header), 15
spc.example_spectra, 17
spc.export.text, 18
spc.export.text, SpcHeader-method
(spc.export.text), 18
spc.export.text, Spectra-method
(spc.export.text), 18
spc.export.xlsx, 19
spc.export.xlsx, Spectra-method
(spc.export.xlsx), 19
spc.getheader, 20, 45

- spc.getheader, list-method, 21
- spc.getheader, Spectra-method (spc.getheader), 20
- spc.getinvalid.idx, 22
- spc.getinvalid.idx, Spectra-method (spc.getinvalid.idx), 22
- spc.getselected.idx, 22, 47
- spc.getselected.idx, Spectra-method (spc.getselected.idx), 22
- spc.getwavelengths, 23, 48
- spc.getwavelengths, Spectra-method (spc.getwavelengths), 23
- spc.header.infos, 24
- spc.header2data, 24
- spc.header2data, list-method (spc.header2data), 24
- spc.header2data, SpcList-method (spc.header2data), 24
- spc.header2data, Spectra-method (spc.header2data), 24
- spc.import.text, 19
- spc.import.text (spc.export.text), 18
- spc.interp.spectral, 25
- spc.interp.spectral, Spectra-method (spc.interp.spectral), 25
- spc.invalid.detect, 26
- spc.invalid.detect, list-method (spc.invalid.detect), 26
- spc.invalid.detect, Spectra-method (spc.invalid.detect), 26
- spc.lapply, 27
- spc.lapply, SpcList-method (spc.lapply), 27
- spc.lines, 27, 31, 45
- spc.lines, Spectra-method (spc.lines), 27
- spc.make.stindex, 28
- spc.makeSpcList, 29, 29
- spc.plot, 28, 30, 32, 45
- spc.plot, Spectra-method (spc.plot), 30
- spc.plot.depth, 31, 40
- spc.plot.depth, Spectra-method (spc.plot.depth), 31
- spc.plot.depth.overlay, 32
- spc.plot.depth.overlay, SpcList-method (spc.plot.depth.overlay), 32
- spc.plot.depth.plotly, 33
- spc.plot.depth.plotly, Spectra-method (spc.plot.depth.plotly), 33
- spc.plot.grid, 34
- spc.plot.grid, SpcList-method (spc.plot.grid), 34
- spc.plot.map.leaflet, 35
- spc.plot.map.leaflet, Spectra-method (spc.plot.map.leaflet), 35
- spc.plot.map.plotly, 36
- spc.plot.map.plotly, Spectra-method (spc.plot.map.plotly), 36
- spc.plot.map.rbokeh, 36
- spc.plot.map.rbokeh, Spectra-method (spc.plot.map.rbokeh), 36
- spc.plot.overlay, 37
- spc.plot.overlay, SpcList-method (spc.plot.overlay), 37
- spc.plot.plotly, 39
- spc.plot.plotly, Spectra-method (spc.plot.plotly), 39
- spc.plot.time, 40
- spc.plot.time, Spectra-method (spc.plot.time), 40
- spc.plot.time.plotly, 41
- spc.plot.time.plotly, Spectra-method (spc.plot.time.plotly), 41
- spc.rbind, 42
- spc.rbind, Spectra-method (spc.rbind), 42
- spc.rbind, STIDF-method, 42
- spc.Read_ASD, 43
- spc.Read_NOMAD_v2, 44
- spc.select, 44
- spc.select, Spectra-method (spc.select), 44
- spc.setheader<-, 45
- spc.setheader<-, list-method, 46
- spc.setheader<-, Spectra-method (spc.setheader<-), 45
- spc.setinvalid.idx<-, 46
- spc.setinvalid.idx<-, Spectra-method (spc.setinvalid.idx<-), 46
- spc.setselected.idx<-, 47
- spc.setselected.idx<-, Spectra-method (spc.setselected.idx<-), 47
- spc.setwavelengths<-, 48
- spc.setwavelengths<-, Spectra-method (spc.setwavelengths<-), 48
- spc.STI.stdistance, 48
- spc.timeMatch, 49
- spc.updateheader, 50

`spc.updateheader`, list-method
 (`spc.updateheader`), [50](#)
`spc.updateheader`, Spectra-method
 (`spc.updateheader`), [50](#)
SpHeader-class, [51](#)
SpHeaderAdd, [51](#)
SpHeaderAdd, SpHeader-method
 (`SpHeaderAdd`), [51](#)
SpHeaderList-class, [52](#)
SpList, [52](#), [53](#)
SpList-class, [53](#)
Spectra, [53](#)
Spectra-class, [55](#)
Spectra-coerce, [55](#)
stConstruct, [53](#)
subset, SpList-method, [56](#)
subset, Spectra-method, [57](#)