

Package ‘hyperoverlap’

September 4, 2020

Title Overlap Detection in n-Dimensional Space

Version 1.0

Description

Uses support vector machines to identify a perfectly separating hyperplane (linear or curvilinear) between two entities in high-dimensional space. If this plane exists, the entities do not overlap. Applications include overlap detection in morphological, resource or environmental dimensions. More details can be found in: Brown et al. (2020) <doi:10.1111/2041-210X.13363> .

Depends R (>= 3.4.0)

Imports e1071, matlib, ggplot2, rgl, misc3d, methods, stats, MASS, graphics

License GPL-3

Encoding UTF-8

LazyData true

Suggests knitr, rmarkdown, plotrix, rlang

VignetteBuilder knitr

RoxygenNote 7.1.1

NeedsCompilation no

Author Matilda Brown [aut, cre] (<<https://orcid.org/0000-0003-2536-8365>>),
Greg Jordan [aut]

Maintainer Matilda Brown <matilda.brown@utas.edu.au>

Repository CRAN

Date/Publication 2020-09-04 07:42:08 UTC

R topics documented:

hyperoverlap	2
hyperoverlap-class	2
hyperoverlap_detect	3
hyperoverlap_lda	4
hyperoverlap_pairs_plot	5
hyperoverlap_plot	5
hyperoverlap_set	6

Index**8**

hyperoverlap	<i>Hyperoverlap: Detection and Visualisation of Overlap in n-Dimensional Space</i>
--------------	--

Description

Uses support vector machines to identify a perfectly separating hyperplane (linear or curvilinear) between two entities in high-dimensional space. If this plane exists, the entities do not overlap. Applications include overlap detection in morphological, resource or environmental dimensions.

Details

More details available in Brown et al. (2020) <doi:10.1111/2041-210X.13363> and vignette.

Author(s)

Matilda Brown <matilda.brown@utas.edu.au>

hyperoverlap-class	<i>Storage class for the description of hyperoverlaps</i>
--------------------	---

Description

Storage class for the description of hyperoverlaps

Slots

entity1 A length-one character vector
entity2 A length-one character vector
dimensions A length n character vector containing the variables used to define the space
occurrences A matrix containing the labelled input data
shape shape of the decision boundary; either "linear" or "curvilinear"
polynomial.order a length-one numeric vector showing the polynomial order of the most accurate kernel function. "0" if linear kernel.
result a length-one character vector, either "overlap" or "non-overlap"
accuracy a 2x2 table with the true (y) and predicted (pred) labels
number.of.points.misclassified a length-one numeric vector
model svm model used to plot decision boundary

hyperoverlap_detect *Overlap detection in n-dimensional space using support vector machines (SVMs)*

Description

Given a matrix containing the ecological data (x) and labels (y) for two entities, a support vector machine is trained and the predicted label of each point is evaluated. If every point has been classified correctly, the entities can be separated and they do not overlap.

Usage

```
hyperoverlap_detect(x, y, kernel = "polynomial", kernel.degree = 3, cost = 500,
  stoppage.threshold = 0.4, verbose = TRUE, set = FALSE)
```

Arguments

x	A matrix or data.frame containing the variables of interest for both entities.
y	A vector of labels.
kernel	Character. Either "linear" or "polynomial" (default = "polynomial").
kernel.degree	Parameter needed for kernel = polynomial (default = 3).
cost	Specifies the SVM margin 'hardness'. Default value is 50, but can be increased for improved accuracy (although this increases runtimes and memory usage).
stoppage.threshold	Numeric. If the number of points misclassified using a linear hyperplane exceeds this proportion of the number of observations, non-linear separation is not attempted. Must be between 0 and 1 (default = 0.2).
verbose	Logical. If TRUE, prints diagnostic messages.
set	Logical. Is this function being called as part of hyperoverlap_set()? Should not need to be changed.

Details

Input data should be preprocessed so that all variables are comparable (e.g. same order of magnitude). Polynomial kernels allow curvilinear decision boundaries to be found between entities (see <https://www.cs.cmu.edu/~ggordon/SVMs/new-svms-and-kernels.pdf>). Smaller values of kernel.degree permit less complex decision boundaries; biological significance is likely to be lost at values > 5.

Value

A `hyperoverlap-class` object

Examples

```
data = iris[which(iris$Species!="versicolor"),]
x = hyperoverlap_detect(data[,1:3],data$Species, kernel="linear")
```

hyperoverlap_lda	<i>Hyperoverlap visualisation using linear discriminant analysis (LDA)</i>
------------------	--

Description

Hyperoverlap visualisation using linear discriminant analysis (LDA)

Usage

```
hyperoverlap_lda(x, return.plot=TRUE, visualise3d=FALSE, showlegend=TRUE)
```

Arguments

x	An hyperoverlap-class object.
return.plot	Logical. If TRUE, data are plotted using <code>plot()</code> .
visualise3d	Logical. If FALSE, data are projected onto two axes (LDA1, residualPCA1). If TRUE, data are projected onto three axes (LDA1, residualPCA1, residualPCA2)
showlegend	Logical. Used for 3D plots.

Details

This function provides a way to visualise overlap (or non-overlap) between classes of high dimensional data. For inspection, it is useful to use the base graphics package (implemented by `return.plot=TRUE`). The transformed coordinates of each point are also returned as a dataframe, which can be plotted with user-defined parameters.

Value

Returns a dataframe with columns "Entity", "LDA1", "residualPCA1", "residualPCA2" (if `visualise3d = TRUE`)

See Also

[hyperoverlap_detect](#)

Examples

```
#using iris dataset reduced to two species
data = iris[which(iris$Species!="versicolor"),]
x = hyperoverlap_detect(data[1:4], data$Species)
hyperoverlap_lda(x)
```

`hyperoverlap_pairs_plot`*Overlap heatmap plotting for analysis of multiple entities*

Description

This function plots a matrix of overlap.

Usage

```
hyperoverlap_pairs_plot(x, cols = pal)
```

Arguments

<code>x</code>	A matrix of the form produced by produced by <code>hyperoverlap_set()</code> (see Details).
<code>cols</code>	A vector of colours (default: <code>c("red", "blue")</code>).

Details

Input matrix must contain columns named "entity1", "entity2" and "result"

Value

A ggplot object

Examples

```
hyperoverlap.iris.set = hyperoverlap_set(iris[1:3],iris$Species, kernel="linear")
hyperoverlap_pairs_plot(hyperoverlap.iris.set)
```

`hyperoverlap_plot`*Overlap plotting for low-dimensional spaces*

Description

Plot the optimal separating hyperplane found by `hyperoverlap_detect()` in 3D .

Usage

```
hyperoverlap_plot(x)
```

Arguments

<code>x</code>	An <code>hyperoverlap-class</code> object.
----------------	--

See Also

[hyperoverlap_detect](#), [hyperoverlap_lda](#)

Examples

```
data = iris[which(iris$Species!="versicolor"),]
x = hyperoverlap_detect(data[,1:3],data$Species, kernel="linear")
hyperoverlap_plot(x)
```

hyperoverlap_set	<i>Pairwise overlap detection in n-dimensional space of multiple entities using support vector machines (SVMs)</i>
------------------	--

Description

This function is a wrapper for [hyperoverlap_detect](#) for pairwise overlap detection between multiple entities.

Usage

```
hyperoverlap_set(x, y, kernel = "polynomial",kernel.degree = 3, cost = 1000,
stoppage.threshold = 0.2, write.to.file = FALSE,
path = NULL,
sample.dimensionality.omit = "FALSE")
```

Arguments

x	A matrix or data.frame containing the variables of interest for both entities.
y	A vector of labels.
kernel	Character. Either "linear" or "polynomial" (default = "polynomial").
kernel.degree	Parameter needed for kernel = polynomial (default = 3).
cost	Specifies the SVM margin 'hardness'. Default value is 1000, but can be increased for improved accuracy (although this increases runtimes and memory usage).
stoppage.threshold	Numeric. If the number of points misclassified using a linear hyperplane exceeds this proportion of the number of observations, non-linear separation is not attempted. Must be between 0 and 1 (default = 0.2).
write.to.file	Logical. If TRUE, each hyperoverlap-class object is saved as a .rds file.
path	Character. Path to write .rds files to. Ignored if write.to.file=FALSE
sample.dimensionality.omit	Logical. If TRUE, omits any entity pairs with a combined sample size less than n+1, where n is the number of dimensions (see details).

Details

In n dimensions, any set of points up to $n+1$ points can be separated using a linear hyperplane. This may produce an artefactual non-overlap result. The `sample.dimensionality.omit` parameter gives two options for dealing with these pairs when they form part of a larger analysis. If `sample.dimensionality.omit = "TRUE"`, this pair is removed from the analysis (result = NA). If `sample.dimensionality.omit = "FALSE"`, the pair is included, but a warning is printed.

Value

A long-form matrix with the following columns: `entity1`, `entity2`, `shape`, `polynomial.order` (if `kernel="polynomial"`), `result`, `number.of.points.misclassified`.

If specified, individual `Hyperoverlap-class` objects are written to file.

Examples

```
data(iris)
hyperoverlap.iris.set = hyperoverlap_set(iris[1:3],iris$Species, kernel="linear")
```

Index

hyperoverlap, [2](#)
hyperoverlap-class, [2](#)
hyperoverlap_detect, [3](#), [4](#), [6](#)
hyperoverlap_lda, [4](#), [6](#)
hyperoverlap_pairs_plot, [5](#)
hyperoverlap_plot, [5](#)
hyperoverlap_set, [6](#)