

# Package ‘sen2r’

January 7, 2021

**Type** Package

**Title** Find, Download and Process Sentinel-2 Data

**Version** 1.4.0

**Description** Functions to download Sentinel-2 optical images and perform preliminary processing operations. 'sen2r' provides the instruments required to easily perform (and eventually automate) the steps necessary to build a complete Sentinel-2 processing chain.

A Graphical User Interface to facilitate data processing is also provided.

For additional documentation refer to the following article:

Ranghetti et al. (2020) <doi:10.1016/j.cageo.2020.104473>.

**License** GPL-3

**Encoding** UTF-8

**URL** <http://sen2r.ranghetti.info>, <https://github.com/ranghetti/sen2r>

**BugReports** <https://github.com/ranghetti/sen2r/issues>

**Depends** R (>= 3.5.0)

**Imports** methods, sf (>= 0.9.2), stars (>= 0.4.1), data.table, raster, rgdal, XML, jsonlite, geojsonio, foreach, parallel, doParallel, httr, RcppTOML

**Suggests** leaflet, leafpm, mapedit, shiny, shinyFiles, shinydashboard, shinyjs, shinyWidgets, spelling, geojsonlint, httpptest, knitr, markdown, rmarkdown, sys, tools, units, testthat (>= 2.1.0)

**SystemRequirements** GDAL (>= 2.1.2), PROJ (>= 4.9.1), GEOS (>= 3.4.2), Cairo, Curl, NetCDF, jq, Protocol Buffers, V8, OpenSSL, Libxml2.

**VignetteBuilder** knitr

**RoxygenNote** 7.1.1

**Language** en-GB

**NeedsCompilation** no

**Author** Luigi Ranghetti [aut, cre] (<<https://orcid.org/0000-0001-6207-5188>>),  
Lorenzo Busetto [aut] (<<https://orcid.org/0000-0001-9634-6038>>)

**Maintainer** Luigi Ranghetti <luigi@ranghetti.info>

**Repository** CRAN

**Date/Publication** 2021-01-07 18:10:02 UTC

## R topics documented:

abs2rel . . . . .	3
add_rgb_image . . . . .	5
add_tile_suffix . . . . .	5
build_example_param_file . . . . .	7
calcindex_raster . . . . .	8
check_gdal . . . . .	9
check_gui_deps . . . . .	10
check_param_list . . . . .	11
check_sen2r_deps . . . . .	12
compute_s2_paths . . . . .	13
comsub . . . . .	18
create_indices_db . . . . .	19
create_s2_dop . . . . .	20
dontuse . . . . .	21
expand_path . . . . .	21
expect_equal_crs . . . . .	22
fix_envi_format . . . . .	23
gdalUtil . . . . .	24
gdalwarp_grid . . . . .	26
gdal_abs2rel . . . . .	27
gdal_warp . . . . .	29
gipp_init . . . . .	32
give_write_permission . . . . .	34
init_python . . . . .	35
install_aria2 . . . . .	35
install_sen2cor . . . . .	36
list_indices . . . . .	37
load_binpaths . . . . .	38
load_extent_bbox . . . . .	39
mountpoint . . . . .	40
nn . . . . .	41
normalize_path . . . . .	42
path_check . . . . .	43
print_message . . . . .	43
projpar . . . . .	45
raster2rgb . . . . .	46
raster_metadata . . . . .	47
read_gipp . . . . .	48
read_scihub_login . . . . .	50
s2_calcindices . . . . .	52
s2_defNA . . . . .	54

s2_dop . . . . .	55
s2_download . . . . .	56
s2_gui . . . . .	58
s2_list . . . . .	59
s2_mask . . . . .	61
s2_merge . . . . .	65
s2_order . . . . .	67
s2_rgb . . . . .	69
s2_thumbnails . . . . .	72
s2_tiles . . . . .	73
s2_translate . . . . .	74
safelist-class . . . . .	77
safe_getMetadata . . . . .	78
safe_is_online . . . . .	82
safe_shortname . . . . .	83
sen2cor . . . . .	85
sen2r . . . . .	88
sen2r_getElements . . . . .	97
sen2r_process_report . . . . .	98
smooth_mask . . . . .	100
stack2rgb . . . . .	101
start_trace . . . . .	103
str_pad2 . . . . .	104
st_as_text_2 . . . . .	105
st_crs2 . . . . .	106
suppress_warnings . . . . .	108
tiles_intersects . . . . .	109
write_ignorelist . . . . .	110
<b>Index</b>	<b>112</b>

---

abs2rel	<i>Convert a path to a relative path</i>
---------	--

---

### Description

The function convert an absolute path to a relative path in respect to a reference. The longest common parent directory is taken as reference. Symbolic links are converted to original paths before performing the operation.

### Usage

```
abs2rel(path, ref_path, mustWork = NA)
```

**Arguments**

path	The path to be converted (if it is not absolute, the current working directory is considered as its parent, and a warning is shown).
ref_path	The reference path to be compared to path to obtain the relative directory. <i>Important</i> : the path is considered as a directory also if it is the path of a file!
mustWork	(optional) logical: if TRUE an error is given if path or ref_path do not exist; if NA (default) then a warning; if FALSE nothing is shown.

**Value**

The relative path

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2017) <luigi.ranghetti@gmail.com>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

**Examples**

```
# the reference path
(ref_path <- system.file(package="sen2r"))
# a path with a common parent with ref_path
(in_path_1 <- system.file(package="gdalUtils"))
# a path included in ref_path
(in_path_2 <- system.file("R/abs2rel.R", package="sen2r"))
# a path external to ref_path (in Linux)
(in_path_3 <- system.file(package="base"))
# an unexisting path
(in_path_4 <- gsub("sen2r","r2sen",ref_path))

abs2rel(in_path_1, ref_path)

abs2rel(in_path_2, ref_path)

suppressWarnings(abs2rel(in_path_3, ref_path))

suppressWarnings(abs2rel(in_path_4, ref_path, mustWork=FALSE))

suppressWarnings(abs2rel(ref_path, ref_path))
```

---

add_rgb_image	<i>Add RGB product</i>
---------------	------------------------

---

**Description**

Modal dialog to define an RGB image.

**Usage**

```
add_rgb_image(s2_bands)
```

**Arguments**

s2_bands	2-length list (one for TOA, one for BOA), each element being a list of S2 bands, as defined in <a href="#">s2_gui</a> .
----------	---

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

---

add_tile_suffix	<i>Add/remove suffixes for split tiles</i>
-----------------	--

---

**Description**

add\_tile\_suffix() adds specific suffixes to tile IDs in order to distinguish tiled filenames referring to different original SAFE products.

remove\_tile\_suffix() removes existing suffixes from tile IDs.

extract\_tile\_suffix() extracts suffixes from input paths.

**Usage**

```
add_tile_suffix(paths, suffix)
```

```
remove_tile_suffix(paths)
```

```
extract_tile_suffix(paths)
```

**Arguments**

paths	Paths of the input tiled products
suffix	Character (1-length): if provided, the specified suffix is appended to the tile ID of each path; if not provided (default), a sequential suffix is appended only to the tile ID of the duplicated paths.

**Details**

In some sporadic cases, a tiled Sentinel-2 image is split in two SAFE products (see e.g. products [S2A\\_MSIL1C\\_20200408T101021\\_N0209\\_R022\\_T32TNL\\_20200408T153254](#) and [S2A\\_MSIL1C\\_20200408T101021\\_N0209\\_R022\\_T32TNL\\_20200408T153254](#)). This split, probably a consequence of the division of the whole orbit image, creates ambiguity in the association among SAFE images and sen2r products, since the sen2r naming convention is not sufficient to manage them as separate products. So, in the definition of the filenames of intermediate tiled products (output of `s2_translate()`) it is necessary to add a suffix to be able to manage them separately and then merge them in `s2_merge()`. A lowercase letter ("a" and "b", but potentially "a" to "z") is used. Functions `add_tile_suffix()` and `remove_tile_suffix()` are used in the `sen2r()` main code as a workaround.

**Value**

The input paths with/without the tile suffix.

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2020) <[luigi@ranghetti.info](mailto:luigi@ranghetti.info)>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

**Examples**

```
safe_names <- c(
  "S2A_MSIL2A_20200408T101021_N0214_R022_T32TNK_20200408T175711.SAFE",
  "S2A_MSIL2A_20200408T101021_N0214_R022_T32TNL_20200408T175711.SAFE",
  "S2A_MSIL2A_20200408T101021_N0214_R022_T32TNL_20200408T161405.SAFE"
)
prod_names <- safe_shortcode(safe_names, ext = ".tif", allow_duplicated = TRUE)
( prod_names_univoc <- sen2r::add_tile_suffix(prod_names) )
( prod_names_custom <- sen2r::add_tile_suffix(prod_names, "a") )
sen2r::remove_tile_suffix(prod_names_univoc)
```

---

`build_example_param_file`*Build an example JSON parameter file*

---

### Description

Function used to write JSON parameter file. A function is provided instead than a json file to ensure directories to match the user folder tree.

### Usage

```
build_example_param_file(  
  json_path = tempfile(fileext = "_sen2r_params.json"),  
  overwrite = TRUE  
)
```

### Arguments

<code>json_path</code>	Path of the output file. Default is to save it on a temporary file, whose path is returned.
<code>overwrite</code>	Logical value: should existing output file be overwritten? (default: TRUE)

### Value

The path of the created file.

### Note

License: GPL 3.0

### Author(s)

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

### References

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

### Examples

```
build_example_param_file()
```

---

calcindex\_raster      *Compute index using raster or stars features*

---

### Description

Internal functions used to compute spectral indices and thumbnails through raster or stars features.

### Usage

```
calcindex_raster(
  x,
  sel_formula,
  out_file,
  NAflag = -32768,
  sel_format = "GTiff",
  compress = "LZW",
  datatype = "Int32",
  bigtiff = FALSE,
  overwrite = FALSE,
  minrows = NULL
)
```

```
calcindex_stars(
  x,
  sel_formula,
  out_file,
  NAflag = -32768,
  sel_format = "GTiff",
  compress = "LZW",
  datatype = "Int16",
  bigtiff = FALSE,
  overwrite = FALSE
)
```

### Arguments

x	Input file path, or RasterLayer (in calcindex_raster()) or stars (in calcindex_stars()).
sel_formula	Formula used to compute output raster (specific formats are used - documentation will be improved).
out_file	Output file path.
NAflag	(optional)
sel_format	(optional) Format of the output file (in a format recognised by GDAL). Default "GTiff".
compress	(optional) In the case a GTiff format is present, the compression indicated with this parameter is used.



datatype	(optional) Numeric datatype of the output rasters (see <code>s2_calcindices()</code> ).
bigtiff	(optional) Logical: if TRUE, the creation of a BigTIFF is forced (default is FALSE). This option is used only in the case a GTiff format was chosen.
overwrite	Logical value: should existing output files be overwritten? (default: FALSE)
minrows	(optional) parameter passed to <code>blockSize()</code> .

**Value**

NULL (the function is called for its side effects)

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2020) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

---

check\_gdal

*Check GDAL installation*

---

**Description**

The function checks that GDAL is installed and updated to the minimum required version (2.1.2).

**Usage**

```
check_gdal(abort = TRUE, gdal_path = NULL, force = FALSE, full_scan = FALSE)
```

**Arguments**

abort	Logical parameter: if TRUE (default), the function aborts in case no GDAL installation is found; if FALSE, a warning is shown and FALSE is returned.
gdal_path	(optional) Character: the path in which GDAL must be searched in. If NULL (default), search is performed in the whole file system.
force	(optional) Logical: if TRUE, install even if it is already installed (default is FALSE). Notice that, defining <code>gdal_path</code> , GDAL is searched again even if "force" = FALSE in case the existing installation is not in <code>gdal_path</code> .

`full_scan` (optional) Logical: in Linux and MacOS, if `gdal_path` was not manually defined, GDAL is searched within the system path in case this argument is left to default value FALSE; instead, if TRUE, a full search is performed. In Windows, if the default OSGeo directory `C:\OSGeo4W64` exists, GDAL is searched there, instead in the main directory `C:\`; setting `full_scan` to TRUE, is always searched in the whole `C:\`. This argument takes no effect if `gdal_path` was defined, since, in that case, a full search is always performed in `gdal_path`.

### Value

Logical (invisible): TRUE in case the installation is ok, FALSE if GDAL is missing and `abort=FALSE` (otherwise, the function stops).

### Note

License: GPL 3.0

### Author(s)

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

### References

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

### Examples

```
check_gdal()
```

---

<code>check_gui_deps</code>	<i>Check GUI dependencies</i>
-----------------------------	-------------------------------

---

### Description

Check if suggested dependencies required to run the `sen2r` GUI are present.

### Usage

```
check_gui_deps(abort = TRUE)
```

### Arguments

`abort` Logical parameter: if TRUE (default), the function aborts in case some packages need to be installed; if FALSE, a warning is shown.

**Details**

Packages required to run the GUI (shiny- and leaflet-related packages), which were sen2r dependencies until version 1.3.4, are now suggested dependencies. sen2r can be used without them with the exception of the GUI.

**Value**

Logical (invisible): TRUE if all the required packages are installed, FALSE (if abort = FALSE) or an error if some is missing.

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2020) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

**Examples**

```
check_gui_deps()
```

---

check_param_list	<i>Check a parameter list</i>
------------------	-------------------------------

---

**Description**

Check that the parameter list (or JSON parameter file) is in the correct format, and then specified values are coherent with parameters.

**Usage**

```
check_param_list(pm, type = "string", check_paths = FALSE, correct = TRUE)
```

**Arguments**

pm	List of parameters or path of a JSON parameter file.
type	Type of the output (see <a href="#">print_message</a> for details).
check_paths	Logical: if TRUE, the function checks required output paths to be provided; if FALSE (default) these checks are skipped.
correct	Logical: if TRUE (default), the function corrects some incoherences (e.g. timewindow of length 1 is transformed in length 2) and returns the corrected list as output; if false, only checking is performed, and the output is NULL if no errors occur.

**Value**

In case of errors, depending on type argument, output can be a vector of errors (if type = "string"), the first error occurred (if type = "error") or a set of warnings (if type = "warning"). If no errors occur, output is the corrected parameter list if correct = TRUE or NULL otherwise.

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

---

check\_sen2r\_deps

*Check package dependencies*

---

**Description**

The function allows to graphically check that all the optional runtime dependencies are installed.

**Usage**

```
check_sen2r_deps()
```

## Details

This package needs some external dependencies in order to run specific actions:

- Sen2Cor for atmospheric correction;
- GDAL for cloud mask smoothing and buffering;
- aria2 to download SAFE images with an alternative downloader.

This function opens a GUI which allows to check that these dependencies are installed. This check is highly suggested before using the library for the first time, in order to avoid errors.

## Value

NULL (the function is called for its side effects)

## Note

License: GPL 3.0

## Author(s)

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

## References

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

## Examples

```
if (interactive()) {  
  check_sen2r_deps()  
}
```

---

compute\_s2\_paths

*Compute names of S2 file to be generated*

---

## Description

compute\_s2\_paths is an internal function (to be used within `sen2r()`) which computes the names of the required output image files (see details). The function was split from `sen2r()` because this code is called twice (and to shorten the main function).

`list_sen2r_paths` is a wrapper of `sen2r()`, which runs `sen2r()` until `compute_s2_paths()` is called, returning the same list. It is a simple way to call `compute_s2_paths()` with the same arguments if `sen2r()`.

**Usage**

```
compute_s2_paths(  
  pm,  
  s2_list_l1c,  
  s2_list_l2a,  
  tmpdir,  
  list_prods,  
  force_tiles = FALSE,  
  check_tmp = TRUE,  
  ignorelist  
)  
  
list_sen2r_paths(  
  param_list = NULL,  
  gui = NA,  
  preprocess = TRUE,  
  s2_levels = c("l1c", "l2a"),  
  sel_sensor = c("s2a", "s2b"),  
  online = TRUE,  
  apihub = NA,  
  downloader = "builtin",  
  overwrite_safe = FALSE,  
  rm_safe = "no",  
  step_atmcorr = "auto",  
  max_cloud_safe = 100,  
  timewindow = NA,  
  timeperiod = "full",  
  extent = NA,  
  extent_name = "sen2r",  
  s2tiles_selected = NA,  
  s2orbits_selected = NA,  
  list_prods = c("BOA"),  
  list_rgb = NA,  
  list_indices = NA,  
  index_source = "BOA",  
  rgb_ranges = NA,  
  mask_type = NA,  
  max_mask = 100,  
  mask_smooth = 0,  
  mask_buffer = 0,  
  clip_on_extent = TRUE,  
  extent_as_mask = FALSE,  
  reference_path = NA,  
  res = NA,  
  res_s2 = "10m",  
  unit = "Meter",  
  proj = NA,  
  resampling = "near",
```

```

    resampling_scl = "near",
    outformat = "GTiff",
    rgb_outformat = "GTiff",
    index_datatype = "Int16",
    compression = "DEFLATE",
    rgb_compression = "90",
    overwrite = FALSE,
    path_l1c = NA,
    path_l2a = NA,
    path_tiles = NA,
    path_merged = NA,
    path_out = NA,
    path_rgb = NA,
    path_indices = NA,
    path_subdirs = TRUE,
    thumbnails = TRUE,
    parallel = TRUE,
    processing_order = "by_step",
    use_python = TRUE,
    tmpdir = NA,
    rmtmp = TRUE,
    log = NA
)

```

### Arguments

pm	List of input parameters.
s2_list_l1c	Names and paths of input SAFE level-1C products.
s2_list_l2a	Names and paths of input SAFE level-2A products.
tmpdir	Path of the temporary directory.
list_prods	Character vector with the values of the products to be processed (accepted values: "TOA", "BOA", "SCL", "TCI", "AOT", "WVP", "CLD", "SNW").
force_tiles	(optional) Logical: passed to <code>safe_shortcode()</code> (default: FALSE).
check_tmp	(optional) Logical: if TRUE (default), temporary files are also searched when <code>exi</code> names are computed; if FALSE, only non temporary files are searched.
ignorelist	List of output files to be ignored (generated by <code>read_ignorelist()</code> ).
param_list	sen2r argument (refer to <code>sen2r()</code> documentation).
gui	sen2r argument (refer to <code>sen2r()</code> documentation).
preprocess	sen2r argument (refer to <code>sen2r()</code> documentation).
s2_levels	sen2r argument (refer to <code>sen2r()</code> documentation).
sel_sensor	sen2r argument (refer to <code>sen2r()</code> documentation).
online	sen2r argument (refer to <code>sen2r()</code> documentation).
apihub	sen2r argument (refer to <code>sen2r()</code> documentation).
downloader	sen2r argument (refer to <code>sen2r()</code> documentation).

overwrite\_safe sen2r argument (refer to sen2r() documentation).  
 rm\_safe sen2r argument (refer to sen2r() documentation).  
 step\_atmcorr sen2r argument (refer to sen2r() documentation).  
 max\_cloud\_safe sen2r argument (refer to sen2r() documentation).  
 timewindow sen2r argument (refer to sen2r() documentation).  
 timeperiod sen2r argument (refer to sen2r() documentation).  
 extent sen2r argument (refer to sen2r() documentation).  
 extent\_name sen2r argument (refer to sen2r() documentation).  
 s2tiles\_selected sen2r argument (refer to sen2r() documentation).  
 s2orbits\_selected sen2r argument (refer to sen2r() documentation).  
 list\_rgb sen2r argument (refer to sen2r() documentation).  
 list\_indices sen2r argument (refer to sen2r() documentation).  
 index\_source sen2r argument (refer to sen2r() documentation).  
 rgb\_ranges sen2r argument (refer to sen2r() documentation).  
 mask\_type sen2r argument (refer to sen2r() documentation).  
 max\_mask sen2r argument (refer to sen2r() documentation).  
 mask\_smooth sen2r argument (refer to sen2r() documentation).  
 mask\_buffer sen2r argument (refer to sen2r() documentation).  
 clip\_on\_extent sen2r argument (refer to sen2r() documentation).  
 extent\_as\_mask sen2r argument (refer to sen2r() documentation).  
 reference\_path sen2r argument (refer to sen2r() documentation).  
 res sen2r argument (refer to sen2r() documentation).  
 res\_s2 sen2r argument (refer to sen2r() documentation).  
 unit sen2r argument (refer to sen2r() documentation).  
 proj sen2r argument (refer to sen2r() documentation).  
 resampling sen2r argument (refer to sen2r() documentation).  
 resampling\_scl sen2r argument (refer to sen2r() documentation).  
 outformat sen2r argument (refer to sen2r() documentation).  
 rgb\_outformat sen2r argument (refer to sen2r() documentation).  
 index\_datatype sen2r argument (refer to sen2r() documentation).  
 compression sen2r argument (refer to sen2r() documentation).  
 rgb\_compression sen2r argument (refer to sen2r() documentation).  
 overwrite sen2r argument (refer to sen2r() documentation).  
 path\_l1c sen2r argument (refer to sen2r() documentation).  
 path\_l2a sen2r argument (refer to sen2r() documentation).



path_tiles	sen2r argument (refer to sen2r() documentation).
path_merged	sen2r argument (refer to sen2r() documentation).
path_out	sen2r argument (refer to sen2r() documentation).
path_rgb	sen2r argument (refer to sen2r() documentation).
path_indices	sen2r argument (refer to sen2r() documentation).
path_subdirs	sen2r argument (refer to sen2r() documentation).
thumbnails	sen2r argument (refer to sen2r() documentation).
parallel	sen2r argument (refer to sen2r() documentation).
processing_order	sen2r argument (refer to sen2r() documentation).
use_python	sen2r argument (refer to sen2r() documentation).
rmtmp	sen2r argument (refer to sen2r() documentation).
log	sen2r argument (refer to sen2r() documentation).

### Details

compute\_s2\_paths is structured in the following way:

1. Retrieve the file names expected to be present at the end of the processing chain (element `exp`) and already existing (`exi`);
2. Compute the file names expected to be created (elements `req` and `new`, see below) (this operation is done in reverse order).

Meaning of the elements `exi`, `exp`, `req` and `new` (here and for all the script), which are defined for each processing step:

- `exi`: full names of the files already existing before launching the processing chain;
- `exp`: full names of the files expected to be present at the end of the processing chain (already existing or not);
- `req`: names of the files required by the step;
- `new`: names of the required files not existing yet (expected to be created).

With `overwrite=TRUE`, all these vectors are equal because all is overwritten.

### Value

A nested list:

- first elements are `exi`, `exp`, `req` and `new`;
- second elements deal with the processing step: `tiles`, `merged`, `warped`, `warped_nomsk`, `rgb`, `masked` and `indices`;
- third elements are related to output products.

### Note

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

---

comsub

*Find the longest common starting substring or directory*

---

**Description**

The function search for the longest common prefix between multiple strings.

**Usage**

```
comsub(data, sep = "")
```

**Arguments**

data	A vector of strings
sep	A character which is used to separate elements; default ("") is used to compare single characters; other useful alternatives are "/" (or "\\\" in Windows) to find the longest common directory, or " " to compare words instead of characters.

**Value**

A character with the longest common initial substring

**Note**

Modified from a suggestion taken from [stackoverflow](#).

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

### Examples

```
strings <- c("/home/user/git/sen2r",
            "/home/user/git_data/sen2r/ex/vrt/01_translate/")

comsub(strings)

comsub(strings, sep="/")
```

---

create\_indices\_db      *Create the indices database*

---

### Description

The internal function checks if indices.json (the database of spectral indices) already exists; if not, it downloads source files and creates it. Since this function depends on xsltproc executable (available only for Linux), this function can be used only from Linux. It is not necessary, since a indices.json file is present in the package.

### Usage

```
create_indices_db(xslt_path = NA, json_path = NA, force = FALSE)
```

### Arguments

xslt_path	(optional) The path where to install xsltml, an external xsltproc script used to convert MathML index formulas to LaTeX (default: a subdirectory of the package).
json_path	(optional) The path of the output JSON file. <i>Warning:</i> to create a file which will be usable by the package, this option must be left to NA (default location is within the package installation). Edit this only to create the file in another place for external use.
force	(optional) Logical: if FALSE (default), the db is created only if missing or not updated; if TRUE, it is created in any case.

### Value

NULL (the function is called for its side effects)

### Note

License: GPL 3.0

### Author(s)

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

## References

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

---

create_s2_dop	<i>Create the database of S2 orbits and doy of passage</i>
---------------	--

---

## Description

The internal function build a database with the base DOY of passage across each Sentinel-2A orbit (which is used in function s2\_dop).

## Usage

```
create_s2_dop(json_path = NA, force = FALSE)
```

## Arguments

json_path	(optional) The path of the output JSON file. <i>Warning</i> : to create a file which will be usable by the package, this option must be left to NA (default location is within the package installation). Edit this only to create the file in another place for external use.
force	(optional) Logical: if FALSE (default), the db is created only if missing or not updated; if TRUE, it is created in any case.

## Value

The path of the json file

## Note

License: GPL 3.0

## Author(s)

Luigi Ranghetti, PhD (2019) <[luigi@ranghetti.info](mailto:luigi@ranghetti.info)>

## References

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

---

dontuse	<i>Don't use</i>
---------	------------------

---

**Description**

Don't use this function.

**Usage**

```
dontuse()
```

**Details**

This function simply call an `rgdal` function, so to be able to include package `rgdal` among imported dependencies. This is necessary since using `raster` without having `rgdal` installed causes troublings in R 4.

---

<code>expand_path</code>	<i>Expand a path with a parent directory</i>
--------------------------	--

---

**Description**

Accessory function which checks if a path is absolute or relative; if relative, use a specified parent directory instead than the working directory to expand it. Useful for functions which accept more than one path as arguments, in which one of them contains the absolute position, and the others do not.

**Usage**

```
expand_path(path, parent = getwd(), silent = TRUE, normalize = TRUE)
```

**Arguments**

<code>path</code>	The path name (character) to check ad eventually expand.
<code>parent</code>	The parent directory (character) to use if path is relative (default value: the working directory).
<code>silent</code>	Logical value: if TRUE (default), no message are shown; if FALSE, a message inform if parent were applied or not; if NA, a warning is returned if path is expanded, nothing if it is already an absolute path.
<code>normalize</code>	Logical value: if TRUE (default), the path is normalised ( <code>normalizePath()</code> is applied); if FALSE it is simply appended.

**Value**

The path eventually expanded.

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

---

expect_equal_crs	<i>Compare two non-null CRS</i>
------------------	---------------------------------

---

**Description**

Internal function: convenience function to compare two non-null CRS in tests without using EPSG (so usable with rgdal >= 1.5).

**Usage**

```
expect_equal_crs(crs1, crs2)
```

**Arguments**

crs1	CRS 1 to compare
crs2	CRS 2 to compare

**Value**

testthat::expect\_equal() output.

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2020) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

---

fix_envi_format	<i>Fix ENVI outputs</i>
-----------------	-------------------------

---

## Description

Internal function which changes some elements of output ENVI files:

- file extension is set to .dat if .envi (in case of files created by writeRaster) is found, and the header is edited properly,
- and band names are set in the header file (in particular, SR band names include wavelengths and names like NIR, SWIR; other products shows the product name as band name);
- SCL headers include information about class names and colours.

## Usage

```
fix_envi_format(infile)
```

## Arguments

infile	A vector of input filenames, in the sen2r naming convention ( <a href="#">safe_shortcode</a> ) and ENVI format.
--------	---

## Value

NULL (the function is called for its side effects)

## Note

License: GPL 3.0

## Author(s)

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

## References

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

gdalUtil

*Interface to GDAL Python-based utilities***Description**

This accessory function interfaces with GDAL utilities (sen2r must be interfaced with a runtime GDAL environment, see `check_gdal()`). Python-based utilities are always called from a runtime GDAL; C-based ones are called using `sf::gdal_utils()`.

**Usage**

```
gdalUtil(
    util = "info",
    source,
    destination = character(0),
    options = character(0),
    quiet = FALSE,
    formula = character(0),
    processing = character(0),
    colorfilename = character(0)
)
```

**Arguments**

<code>util</code>	Character: one among "info", "translate", "warp", "demprocessing", "buildvrt" (C-based), "calc" and "fillnodata" (Python-based). Other utilities were not implemented, since they are not used by sen2r.
<code>source</code>	path of input layer(s); for calc this can be more than one.
<code>destination</code>	Path of the output layer.
<code>options</code>	Character vector with GDAL options.
<code>quiet</code>	Logical: if TRUE, suppress printing of output for info (this argument is ignored in case package sys is not installed).
<code>formula</code>	(for <code>util = "calc"</code> ) Calculation in <code>gdalnumeric</code> syntax using +, -, /, *, or any numpy array functions (i.e. <code>log10()</code> ).
<code>processing</code>	Character: processing options for <code>util = "demprocessing"</code> .
<code>colorfilename</code>	Character: name of colour file for <code>util = "demprocessing"</code> (mandatory if <code>processing="color-relief"</code> ).

**Value**

A logical (invisible) indicating success (i.e., TRUE); in case of failure, an error is raised and FALSE is returned (in case of Python-based utilities).

**Note**

License: GPL 3.0



**Author(s)**

Luigi Ranghetti, PhD (2020) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

**Examples**

```
# Define product names
exemplename <- system.file(
  "extdata/out/S2A2A_20190723_022_Barbellino_BOA_10.tif",
  package = "sen2r"
)

## gdalinfo
out0 <- gdalUtil("info", exemplename, quiet = TRUE)
message(out0)

## gdal_translate
outname1 <- tempfile(fileext = ".tif")
gdalUtil(
  "translate",
  exemplename, outname1,
  options = c("-tr", "2", "2", "-r", "cubicspline", "-co", "COMPRESS=DEFLATE")
)
oldpar <- par(mfrow = c(1,2), mar = rep(0,4))
image(stars::read_stars(exemplename), rgb = c(11,8,4), useRaster = TRUE)
image(stars::read_stars(outname1), rgb = c(11,8,4), useRaster = TRUE)

## gdalwarp
outname2 <- tempfile(fileext = ".tif")
gdalUtil(
  "warp",
  exemplename, outname2,
  options = c("-t_srs", "EPSG:32633", "-co", "COMPRESS=DEFLATE")
)
oldpar <- par(mfrow = c(1,2), mar = rep(0,4))
image(stars::read_stars(exemplename), rgb = c(11,8,4), useRaster = TRUE)
image(stars::read_stars(outname2), rgb = c(11,8,4), useRaster = TRUE)

## gdal_calc
outname3 <- tempfile(fileext = ".tif")
ndvirefname <- system.file(
  "extdata/out/S2A2A_20190723_022_Barbellino_NDVI_10.tif",
  package = "sen2r"
)
gdalUtil(
  "calc",
```

```

rep(exemplename,2), outname3,
formula = "10000*(A.astype(float)-B)/(A+B)",
options = c("--A_band", "8", "--B_band", "4", "--type", "Int16")
)
oldpar <- par(mfrow = c(1,2), mar = rep(0,4))
image(stars::read_stars(ndvirefname), useRaster = TRUE)
image(stars::read_stars(outname3), useRaster = TRUE)

```

---

gdalwarp\_grid

---

*Warp a raster file aligning it on the grid of another file*


---

## Description

The function applies `gdalwarp` to build rasters with the same projection, resolution and grid alignment of another raster. If not specified, the output format of each file is the same of the corresponding source file.

## Usage

```

gdalwarp_grid(
  srcfiles,
  dstfiles,
  ref,
  of = NULL,
  r = NULL,
  dstnodata = NA,
  tmpdir = tempdir()
)

```

## Arguments

<code>srcfiles</code>	A vector of input file paths (managed by GDAL).
<code>dstfiles</code>	A vector of input file paths.
<code>ref</code>	Path of the raster taken as reference.
<code>of</code>	The output format (use the short format name). Default is the format of every input filename.
<code>r</code>	<code>Resampling_method("near" "bilinear" "cubic" "cubicspline" "lanczos" "average" "mode" "ma</code>
<code>dstnodata</code>	(optional) Set nodata values for output bands (parameter passed to <code>gdalUtil()</code> ).
<code>tmpdir</code>	(optional) Path where intermediate files (.prj) will be created. Default is a temporary directory.

## Value

NULL (the function is called for its side effects)

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

**Examples**

```
# Define file names
ex_sel <- system.file(
  "extdata/out/S2A2A_20190723_022_Barbellino_BOA_10.tif",
  package = "sen2r"
)
ex_ref <- system.file(
  "extdata/out/S2A2A_20190723_022_Barbellino_SCL_10.tif",
  package = "sen2r"
)
ex_out <- tempfile(fileext = "_BOA_out.tif")

# Run function
sen2r::gdalwarp_grid(ex_sel, ex_out, ref = ex_ref)

# Show output
oldpar <- par(mfrow = c(1,3), mar = rep(0,4))
image(stars::read_stars(ex_sel), rgb = 4:2, maxColorValue = 3500, useRaster = TRUE)
par(mar = rep(2/3,4))
image(stars::read_stars(ex_ref), useRaster = TRUE)
par(mar = rep(0,4))
image(stars::read_stars(ex_out), rgb = 4:2, maxColorValue = 3500, useRaster = TRUE)
par(oldpar)
```

---

gdal\_abs2rel

*Convert absolute from/to relative paths in a virtual file*

---

**Description**

The two functions read the content of a GDAL virtual file (VRT) and check the presence of paths to linked files.

`gdal_abs2rel` scans the presence of absolute paths: when an absolute path has a common parent directory with the path in which the VRT is, this is replaced with a relative. This is useful when VRT are on a remote driver, which can be mounted to several points.

`gdal_rel2abs` checks the presence of relative paths, and replace them with the corresponding absolute path (symbolic links are followed). This is useful to grant that VRT can be moved (if the files they link to are not moved).

### Usage

```
gdal_abs2rel(in_vrt, out_vrt = NA)
```

```
gdal_rel2abs(in_vrt, out_vrt = NA)
```

### Arguments

<code>in_vrt</code>	The path of the VRT to be read.
<code>out_vrt</code>	(optional) The path of the output VRT file (default is to overwrite <code>in_vrt</code> ).

### Value

NULL (the function is called for its side effects)

### Note

License: GPL 3.0

### Author(s)

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

### References

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

### Examples

```
# Load a VRT containing a relative path
ex_vrt <- system.file(
  "extdata/out/S2A2A_20190723_022_Barbellino_RGB432B_10.vrt",
  package = "sen2r"
)
abs_vrt <- tempfile(fileext = "_abs.vrt")
rel_vrt <- tempfile(fileext = "_rel.vrt")
gdal_rel2abs(ex_vrt, abs_vrt)
gdal_abs2rel(ex_vrt, rel_vrt)

# Show differences
ex_vrt_content <- readLines(ex_vrt)
```

```

abs_vrt_content <- readLines(abs_vrt)
rel_vrt_content <- readLines(rel_vrt)
ex_vrt_content[ex_vrt_content != abs_vrt_content] # Original line
abs_vrt_content[ex_vrt_content != abs_vrt_content] # Modified line
rel_vrt_content[ex_vrt_content != rel_vrt_content] # No edits

```

---

gdal\_warp

*Clip, reproject and warp raster files*


---

## Description

The function applies gdalwarp to clip, reproject and/or warp raster files. If not specified, the output format of each file is the same of the corresponding source file.

## Usage

```

gdal_warp(
  srcfiles,
  dstfiles,
  of = NULL,
  co = NULL,
  ref = NULL,
  mask = NULL,
  tr = NULL,
  t_srs = NULL,
  r = NULL,
  dstnodata = NULL,
  overwrite = FALSE,
  tmpdir = NA,
  rmtmp = TRUE
)

```

## Arguments

srcfiles	A vector of input file paths (managed by GDAL).
dstfiles	A vector of corresponding output file paths.
of	The output format (use the short format name). Default is the format of every input filename.
co	Character. Passes a creation option to the output format driver. Multiple -co options may be listed. See format specific documentation for legal creation options for each format.
ref	Path of the raster taken as reference: if provided, parameters regarding the output grid (alignment, resolution and extent) are taken from this raster. To set differently some of these values, specify also other values of mask and/or tr. t_srs parameter value is always ignored when ref is provided.

mask	Spatial path or object from which to take the extent of output files. If it is a polygon, this is used as masking layer; otherwise, only the bounding box is considered. If both ref and mask are provided, this parameter will overlay the extent of the reference raster. In order to take only the grid from res and not to clip on its extent, set mask=NA. Notice that the output projection is never taken from mask.
tr	Numeric. (c(xres,yres)). set output file resolution (in target georeferenced units). If bot ref and tr are provided, tr is rounded in order to match the exact extent.
t_srs	Target spatial reference set (character). The coordinate systems that can be passed are anything supported by <code>st_crs2</code> .
r	Resampling_method ("near" "bilinear" "cubic" "cubicspline" "lanczos" "average" "mode" "ma
dstnodata	Set nodata values for output bands (different values can be supplied for each band). If more than one value is supplied all values should be quoted to keep them together as a single operating system argument. New files will be initialized to this value and if possible the nodata value will be recorded in the output file. Use a value of NA to ensure that nodata is not defined. A vector with the same length of srcfiles can be supplied, in order to specify different nodata values for each input file. If this argument is not used then nodata values will be copied from the source datasets. At the moment it is not possible to set different values for different srcfiles (use multiple calls of the functions).
overwrite	Logical value: should existing output files be overwritten? (default: FALSE)
tmpdir	(optional) Path where intermediate files (maskfile) will be created. Default is a temporary directory. If tmpdir is a non-empty folder, a random subdirectory will be used.
rmtmp	(optional) Logical: should temporary files be removed? (Default: TRUE)

**Value**

NULL (the function is called for its side effects)

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

**Examples**

```

#' # Define file names
ex_sel <- system.file(
  "extdata/out/S2A2A_20190723_022_Barbellino_RGB432B_10.tif",
  package = "sen2r"
)
ex_ref <- system.file(
  "extdata/out/S2A2A_20190723_022_Barbellino_SCL_10.tif",
  package = "sen2r"
)
crop_poly <- system.file("extdata/vector/dam.geojson", package = "sen2r")
crop_line <- sf::st_cast(sf::read_sf(crop_poly), "LINESTRING")

# Simple clip
test1 <- tempfile(fileext = "_test1.tif")
gdal_warp(ex_sel, test1, mask = crop_line)

# Clip and mask
test2 <- tempfile(fileext = "_test2.tif")
gdal_warp(ex_sel, test2, mask = crop_poly)

# Show output
crop_bbox <- sf::st_as_sfc(sf::st_bbox(crop_line))
oldpar <- par(mfrow = c(1,3), mar = rep(0,4))
image(stars::read_stars(ex_sel), rgb = 1:3, useRaster = TRUE)
plot(crop_line, add = TRUE, col = "blue", lwd = 2)
plot(crop_bbox, add = TRUE, border = "red", lwd = 2)
image(stars::read_stars(test1), rgb = 1:3, useRaster = TRUE)
plot(crop_bbox, add = TRUE, border = "red", lwd = 2)
image(stars::read_stars(test2), rgb = 1:3, useRaster = TRUE)
plot(crop_line, add = TRUE, col = "blue", lwd = 2)

# Warp on a reference raster
test3 <- tempfile(fileext = "_test3.tif")
gdal_warp(ex_sel, test3, ref = ex_ref)

# Show output
par(mfrow = c(1,3))
par(mar = rep(0,4)); image(stars::read_stars(ex_sel), rgb = 1:3, useRaster = TRUE)
par(mar = rep(2/3,4)); image(stars::read_stars(ex_ref), useRaster = TRUE)
par(mar = rep(0,4)); image(stars::read_stars(test3), rgb = 1:3, useRaster = TRUE)

# Reproject all the input file
test4 <- tempfile(fileext = "_test4.tif")
gdal_warp(ex_sel, test4, t_srs = 32631)

# Reproject and clip on a bounding box
test5 <- tempfile(fileext = "_test5.tif")
gdal_warp(ex_sel, test5, t_srs = "EPSG:32631", mask = stars::read_stars(test1))

# Reproject and clip on polygon (masking outside)

```

```

test6 <- tempfile(fileext = "_test6.tif")
gdal_warp(ex_sel, test6, t_srs = "31N", mask = crop_poly)

# Show output
crop_line_31N <- sf::st_transform(crop_line, 32631)
test1_bbox <- sf::st_as_sfc(sf::st_bbox(stars::read_stars(test1)))
test1_bbox_31N <- sf::st_transform(test1_bbox, 32631)
par(mfrow = c(1,4), mar = rep(0,4))
image(stars::read_stars(ex_sel), rgb = 1:3, useRaster = TRUE)
plot(crop_line, add = TRUE, col = "blue", lwd = 2)
plot(test1_bbox, add = TRUE, border = "red", lwd = 2)
image(stars::read_stars(test4), rgb = 1:3, useRaster = TRUE)
image(stars::read_stars(test5), rgb = 1:3, useRaster = TRUE)
plot(test1_bbox_31N, add = TRUE, border = "red", lwd = 2)
image(stars::read_stars(test6), rgb = 1:3, useRaster = TRUE)
plot(crop_line_31N, add = TRUE, col = "blue", lwd = 2)

# Use a reference raster with a different projection
test7 <- tempfile(fileext = "_test7.tif")
gdal_warp(ex_sel, test7, ref = test6)

# Use a reference raster with a different projection
# and specify a different bounding box
test8 <- tempfile(fileext = "_test8.tif")
gdal_warp(ex_sel, test8, mask = stars::read_stars(test1), ref = test6)

# Use a reference raster with a different projection and a mask
test9 <- tempfile(fileext = "_test9.tif")
gdal_warp(ex_sel, test9, mask = crop_poly, ref = test6)

# Show output
par(mfrow = c(1,4), mar = rep(0,4))
image(stars::read_stars(ex_sel), rgb = 1:3, useRaster = TRUE)
plot(crop_line, add = TRUE, col = "blue", lwd = 2)
image(stars::read_stars(test7), rgb = 1:3, useRaster = TRUE)
plot(crop_line_31N, add = TRUE, col = "blue", lwd = 2)
image(stars::read_stars(test8), rgb = 1:3, useRaster = TRUE)
plot(test1_bbox_31N, add = TRUE, border = "red", lwd = 2)
image(stars::read_stars(test9), rgb = 1:3, useRaster = TRUE)
plot(crop_line_31N, add = TRUE, col = "blue", lwd = 2)

par(oldpar)

```

---

gipp\_init

*Copy L2A\_GIPP.xml in sen2r*


---

### Description

Internal function to copy L2A\_GIPP.xml from default Sen2Cor directory to sen2r. After that, user will allow editing Sen2Cor options in sen2r without affecting standalone Sen2Cor behaviour.



**Usage**

```
gipp_init(gipp_sen2r_path = NA, force = FALSE, dem_warning = FALSE)
```

**Arguments**

gipp_sen2r_path	Character path of the output GIPP XML file. By default it is equal to NA (meaning the default sen2r GIPP path).
force	Logical: if TRUE, the file is copied in any case; if FALSE (default), only if it does not yet exist.
dem_warning	TEMPORARY ARGUMENT Logical: if TRUE, a warning about the fact that DEM_Directory XML parameter was not overwritten is shown (default is FALSE). This argument will be removed when use_dem = TRUE will become the default.

**Value**

TRUE if the file was copied, FALSE elsewhere (invisible output)

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2020) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

**Examples**

```
## Not run:  
gipp_init()  
  
## End(Not run)
```

---

give\_write\_permission *Give permission to write settings on disk*

---

### Description

In interactive mode, ask users for permission to create a .sen2r settings directory, in which to store files required by the packages. The function can be used also in non-interactive mode by setting `agree = TRUE`. The function has no effect if the directory already exists.

### Usage

```
give_write_permission(agree = NA)
```

### Arguments

agree	Logical: if TRUE, allow creating the hidden directory; if FALSE, do not allow it; if NA (default), the permission is asked to the user in interactive mode (in non-interactive mode, the permission is denied).
-------	---

### Value

Logical: if TRUE, R was authorised saving in the directory; if FALSE, it was not and a temporary directory is being used.

### Note

License: GPL 3.0

### Author(s)

Lorenzo Busetto, PhD (2019)

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

### References

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

---

init_python	<i>Initialise python</i>
-------------	--------------------------

---

**Description**

Internal function to set the environmental variables required to run Python-based GDAL utilities on Windows.

**Usage**

```
init_python()
```

**Value**

NULL (the function is called for its side effects)

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2020) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

---

install_aria2	<i>Download and install aria2.</i>
---------------	------------------------------------

---

**Description**

This function download and install standalone version of [aria2](#) for Windows.

**Usage**

```
install_aria2(aria2_dir, force = FALSE)
```

**Arguments**

aria2_dir	Path where aria2 executable will be installed.
force	(optional) Logical: if TRUE, install even if it is already installed (default is FALSE).

**Value**

The path of aria2

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

**Examples**

```
## Not run:
# Run only on Windows
install_aria2(aria2_dir = tempdir())
# ( use a non-temporary folder path instead of tempdir() )

## End(Not run)
```

---

install_sen2cor	<i>Download and install (or link) Sen2Cor</i>
-----------------	---

---

**Description**

`install_sen2cor()` downloads and installs a standalone version of **Sen2Cor**.  
`link_sen2cor()` links an existing standalone version of **Sen2Cor** to sen2r.

**Usage**

```
install_sen2cor(sen2cor_dir = NA, version = "2.5.5", force = FALSE)

link_sen2cor(sen2cor_dir)
```

**Arguments**

sen2cor_dir	Path where sen2cor will be installed or searched (by default it is a subdirectory "sen2cor" of the default sen2r directory).
version	(optional) Character: Sen2Cor version (one among '2.5.5' - default - and '2.8.0').
force	(optional) Logical: if TRUE, installs sen2cor even if it is already found in sen2cor_dir (default is FALSE).

**Value**

NULL (the function is called for its side effects)

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

**Examples**

```
## Not run:
install_sen2cor(sen2cor_dir = tempdir())
# ( use a non-temporary folder path instead of tempdir() )

## End(Not run)
```

---

list\_indices

*List spectral indices*

---

**Description**

Return a table with attributes of the spectral indices computable with the package.

**Usage**

```
list_indices(values, pattern = "", all = FALSE)
```

**Arguments**

values            A vector of attributes which will be returned, being one or more within the followings:

- n\_index: internal index identifiers;
- name: index name;
- longname: index description;
- link: URL to the index description page;
- s2\_formula: expression containing the formula to compute the index;
- s2\_formula\_mathml: MathML version of the formula;
- checked: logical (TRUE for verified indices);

- a, b, x: parameter values (NA for non required parameters).
- pattern      A regular expression on index names.
- all           Logical: if TRUE, all the indices retrieved from **IDB** are returned; if FALSE (default), only indices checked by the authors are returned.

**Value**

A data.frame with the required information. The table contains also the following attributes:

- creation\_date: timestamp of the creation date of the indices archive;
- pkg\_version: version of the sen2r package used to create the indices archive.

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

**Examples**

```
# Show index names
list_indices(c("name", "longname"))

# Return the MSAVI2 formula
list_indices("s2_formula", "^MSAVI2$")

# Return all index names (including unchecked)
list_indices("name", all = TRUE)
```

---

load\_binpaths

*Load the paths of external executables*

---

**Description**

Internal function to load the paths of executables from the JSON where they are saved when installed.

**Usage**

```
load_binpaths(bins = NULL)
```

**Arguments**

`bins` Character vector with one or more of the following values: "gdal", "sen2cor", "aria2", "python". If an executable corresponding to the passed bins value is not found in the JSON, it is checked (when possible).

**Value**

The list of the paths

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

**Examples**

```
# Load only existing paths
binpaths <- load_binpaths()
binpaths

## Not run:
# Load paths, forcing to check GDAL and sen2cor
binpaths <- load_binpaths(c("gdal", "sen2cor"))
binpaths

## End(Not run)
```

---

load\_extent\_bbox      *Insert an extent*

---

**Description**

Internal functions and modal dialogs to specify an extent in the GUI.

**Usage**

```
load_extent_bbox()
load_extent_vectfile()
load_extent_draw(extent_ns_name)
```

**Arguments**

extent\_ns\_name Name of the namespace to be used

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

---

mountpoint

*Return the mountpoint of the input directory (if it is mounted)*

---

**Description**

The function checks if the input directory is a subdirectory of a mountpoint of a certain protocol. At the moment, it works only on unix operating systems.

**Usage**

```
mountpoint(path, protocol = NA)
```

**Arguments**

path The path to be checked

protocol (optional) Vector of protocol types. If NA (default), all the protocols are considered.

**Value**

The path of the parent mountpoint for mounted directories; if the input directory is not mounted, NULL is returned. NULL is returned also if the operating system is not unix (together with a warning message). An attribute "protocol" contains the protocol of the mountpoint.



**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

---

nn	<i>Replace NULL with character()</i>
----	--------------------------------------

---

**Description**

Internal function: return character(0) instead of NULL. This is sometimes needed not to return error when applying some functions.

**Usage**

nn(x)

**Arguments**

x                      Input variable

**Value**

character(0) if x==NULL, x elsewhere

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

## Examples

```
tryCatch(basename(NULL), error = print) # error
basename(character()) # ok
basename(sen2r:::nn(NULL)) # ok
```

---

normalize_path	<i>Express file paths in canonical Form depending on the operating system</i>
----------------	---

---

## Description

Accessory function wrapper for `normalizePath()` in Linux and `shortPathName(normalizePath())` in Windows.

## Usage

```
normalize_path(path, ...)
```

## Arguments

path	character vector of file paths
...	additional parameters passed to <code>normalizePath</code> (i.e. <code>mustWork</code> ).

## Value

The paths normalized.

## Note

License: GPL 3.0

## Author(s)

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

## References

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

---

path_check	<i>Check a path</i>
------------	---------------------

---

**Description**

Accessory functions to check that a directory exists and the user have write permissions on it (to be used in a Shiny context)

**Usage**

```
path_check(path, mustbe_empty = FALSE, mustbe_writable = TRUE)
```

**Arguments**

path	string full path to a folder
mustbe_empty	logical if TRUE, accept only empty directories
mustbe_writable	logical if TRUE, accept only directories with write permissions

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

Lorenzo Busetto, PhD (2019)

---

print_message	<i>Print a message</i>
---------------	------------------------

---

**Description**

A common interface for printing messages of several types.

**Usage**

```
print_message(  
  ...,  
  type,  
  sep = "",  
  date = FALSE,  
  date_format = "",  
  width = 0.9 * getOption("width"),  
  indent = TRUE,  
  exdent = TRUE,  
  prefix = "",  
  initial = prefix  
)
```

**Arguments**

...	R objects which are concatenated.
type	Type of the output .Accepted values: <ul style="list-style-type: none"> <li>• 'message' for a diagnostic message;</li> <li>• 'string' for a character output;</li> <li>• 'cat' for the output of cat () function;</li> <li>• 'error' and 'warning' for an error or warning message.</li> </ul> Intentionally, no default value is defined.
sep	(optional) character used to separate input values (default is nothing).
date	Logical value: set TRUE to place the date before the message and after the prefix (this is useful for logs or time consuming operations); default is FALSE.
date_format	Format of the date (see strftime ()) for the definition of the format). The default format is '%Y-%m-%d %H:%M:%S'.
width	Positive integer: target column for wrapping lines in the output (set to Inf for no wrapping).
indent	Non-negative integer: indentation of the first line in a paragraph It can be also a logical: in this case, if TRUE (default) the value is optimised in order to align first line with the followings.
exdent	Non-negative integer: indentation of subsequent lines in paragraphs. It can be also a logical: in this case, if TRUE (default) the value is optimised in order to align lines with the first line.
prefix	Character: prefix for each line except the first.
initial	Character: prefix for the first line.

**Details**

Several functions print messages in different formats (message, error, warning, cat, R output) and with different syntaxes (concatenating parameters or accepting a single argument, appending a new line, etc.). This accessory function provides a common interface for different types: several arguments are accepted and concatenated with the sep argument; the format is defined with the format argument; a date is optionally placed before the message.

**Value**

Message (in the defined format).

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2020) <luigi@ranghetti.info>

## References

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

---

projpar

*Return a parameter used in a WKT projection*

---

## Description

Return the value of a parameter (the name or the unit) present in the WKT of the given CRS.

## Usage

```
projpar(x, par, abort = FALSE)
```

```
projname(x, abort = FALSE)
```

## Arguments

x	The CRS to be named (any <code>st_crs2</code> input is accepted).
par	Character corresponding to the parameter name (it can be one among "name" and "unit" - case insensitive).
abort	logical: if TRUE, the function aborts in case an invalid CRS is passed; if FALSE (default), the function returns NA, and a warning is shown.

## Value

A character with the content of the parameter, and an attribute `crs` with the input projection checked using `sf::st_crs()`.

## Note

The old function, which was searching for a generic parameter parsing the WKT, was deprecated: now `projpar()` only accepts `par = "name"` and `par = "unit"`, and `projname()` is an alias for `projpar(..., par = "name")`.

License: GPL 3.0

## Author(s)

Luigi Ranghetti, PhD (2020) <[luigi@ranghetti.info](mailto:luigi@ranghetti.info)>

## References

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

## Examples

```
projpar(4326, "name")
projpar(4326, "unit")

projname(4326)
```

---

raster2rgb

*Produce an RGB image from a singleband raster file.*

---

## Description

Internal function to create JPEG or PNG images from a singleband raster file. This function is used by [s2\\_thumbnails](#), and it will be exported when it would be more generalised.

## Usage

```
raster2rgb(
  in_rast,
  out_file = NULL,
  palette = "generic_ndsi_2",
  minval = -1,
  maxval = 1,
  bigtiff = FALSE,
  tmpdir = NA
)
```

## Arguments

<code>in_rast</code>	Path of the input multiband raster.
<code>out_file</code>	(optional) Path of the output RGB JPEG image; if NULL (default), a Raster-Layer will be returned.
<code>palette</code>	Path of the palette file to be used (cpt or txt), or character value of a builtin palette ("SCL", "NDVI", the default "generic_ndsi" or "generic_ndsi_2").
<code>minval</code>	(to be implemented) the value corresponding to the minimum value of the palette (for now, only -1 is used). A quantile will be also accepted.
<code>maxval</code>	(to be implemented) the value corresponding to the maximum value of the palette (for now, only 1 is used). A quantile will be also accepted.
<code>bigtiff</code>	(optional) Logical: if TRUE, the creation of a BigTIFF is forced (default is FALSE). This option is used only in the case a GTiff format was chosen.
<code>tmpdir</code>	(optional) Path where intermediate files (VRT) will be created. Default is a temporary directory. If tmpdir is a non-empty folder, a random subdirectory will be used.

**Value**

The path of the output image; alternatively, the output image as RasterLayer (if out\_rast = NULL).

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

---

raster_metadata	<i>Get metadata from raster paths</i>
-----------------	---------------------------------------

---

**Description**

This accessory function extract some useful metadata from a vector of raster paths.

**Usage**

```
raster_metadata(raster_paths, meta = "all", format = "data.table")
```

**Arguments**

raster_paths	A vector of raster paths.
meta	Vector with the desired metadata: one or more values among 'res', 'size', 'bbox', 'proj', 'unit', 'outformat', 'type'. Alternatively meta = 'all' (default) allows to return all metadata.
format	One between data.table (default), data.frame and list.

**Value**

A data.table, data.frame or list of the output metadata.

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

## References

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

## Examples

```
# Define product names
exemplenames <- c(
  system.file("tif/L7_ETMs.tif", package="stars"),
  system.file("extdata/out/S2A2A_20190723_022_Barbellino_BOA_10.tif",
    package = "sen2r")
)

# Return metadata as data.table
raster_metadata(exemplenames)

# Return some metadata as data.table
raster_metadata(exemplenames, c("res", "size", "bbox", "outformat"))

# Return some metadata as list
raster_metadata(exemplenames, c("res", "size", "bbox", "proj"), format = "list")

# Output with an invalid raster
exemplenames <- c(
  exemplenames,
  system.file("extdata/settings/gdal_formats.json", package="sen2r")
)
raster_metadata(exemplenames, c("bbox", "proj"))
```

---

read\_gipp

*Manage GIPP parameters for Sen2Cor*

---

## Description

`read_gipp()` reads Ground Image Processing Parameters (GIPP) from the default sen2r GIPP path or from an XML file.

`set_gipp()` modifies values of a list of GIPP in an XML file (or creates a new XML file with the desired GIPP).

## Usage

```
read_gipp(gipp_names, gipp_path = NA)
```

```
set_gipp(gipp = list(), gipp_path = NA, use_dem = NA)
```



**Arguments**

<code>gipp_names</code>	Character vector with the names of the parameters to be read.
<code>gipp_path</code>	Character path of the GIPP XML file to be read ( <code>read_gipp()</code> ) or written ( <code>set_gipp()</code> ). In <code>read_gipp()</code> , if NA (default), the default sen2r GIPP path is read; in <code>set_gipp()</code> , setting this argument is mandatory (see details).
<code>gipp</code>	(optional) Ground Image Processing Parameters (GIPP) (see <code>sen2cor()</code> for further details). Elements whose name is missing in the XML file are skipped.
<code>use_dem</code>	Logical, determining if a DEM should be set for being used for topographic correction in the XML specified with argument <code>gipp_path</code> (see <code>sen2cor()</code> for further details).

**Details**

In `set_gipp()`, editing /resetting the default sen2r GIPP XML file was disabled to grant code reproducibility among different machines (an error is returned if `gipp_path` is not set). Users who want to do that (being aware of the risk doing that) must explicitly define the argument `gipp_path` as the path of the default GIPP file, which is `file.path(dirname(attr(load_binpaths(), "path")), "sen2r_L2A_GIPP.xml")`.

**Value**

`read_gipp()` returns a named list of GIPP with the required parameters (values not found in the XML are skipped).

`set_gipp()` returns NULL (the function is called for its side effects).

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2020) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

**Examples**

```
# Read default values
read_gipp(c("dem_directory", "dem_reference"))
# Set the use of a topographic correction
set_gipp(use_dem = TRUE, gipp_path = gipp_temp <- tempfile())
# Read the parameters in the created temporary files
read_gipp(c("DEM_Directory", "DEM_Reference"), gipp_path = gipp_temp)
# Set not to use a topographic correction
set_gipp(use_dem = FALSE, gipp_path = gipp_temp <- tempfile())
```

```
# This is equivalent to:
# set_gipp(
#   list(DEM_Directory = NA, DEM_Reference = NA),
#   gipp_path = gipp_temp <- tempfile()
# )
# Read again the parameters in the created temporary files
read_gipp(c("DEM_Directory", "DEM_Reference"), gipp_path = gipp_temp)
```

---

read\_scihub\_login      *Import / export / check SciHub username and password*

---

### Description

Read the SciHub login information (`read_scihub_login()`), save new username and password (`write_scihub_login()`) or check their validity (`check_scihub_login()`). Login information is stored in a file `apihub.txt` inside the ".sen2r" subfolder of the home directory. This functions allow to read or write this file, and to edit them from inside the GUI.

### Usage

```
read_scihub_login(apihub_path = NA)

check_scihub_login(username, password)

check_scihub_connection()

write_scihub_login(
  username,
  password,
  apihub_path = NA,
  check = TRUE,
  append = FALSE
)
```

### Arguments

<code>apihub_path</code>	Path of the file in which login information is saved. If NA (default) it is automatically read from the package default location.
<code>username</code>	SciHub username.
<code>password</code>	SciHub password.
<code>check</code>	Logical: if TRUE (default), new credentials are checked before writing them on <code>apihub_path</code> (if they are invalid, an error is provided); if FALSE, they are directly written.
<code>append</code>	Logical: if TRUE, new credentials are added to the ones existing within <code>apihub_path</code> ; if FALSE (default), <code>apihub_path</code> is replaced with the new ones.

## Details

Notice that new/recently updated SciHub credentials are recognised by API Hub with a delay of about one week (see <https://scihub.copernicus.eu/twiki/do/view/SciHubWebPortal/APIHubDescription> for details).

For this reason, newly created credentials can not immediately be used by `sen2r`, and password edits on old credentials are not immediately recognised.

## Value

`read_scihub_login` returns a matrix of credentials, in which username is in the first column, password in the second.

`check_scihub_login` returns TRUE if credentials are valid, FALSE elsewhere.

`check_scihub_connection` returns TRUE if internet connection is available and SciHub is accessible, FALSE otherwise.

`write_scihub_login` returns NULL.

## Note

License: GPL 3.0

## Author(s)

Luigi Ranghetti, PhD (2019) <[luigi@ranghetti.info](mailto:luigi@ranghetti.info)>

Lorenzo Busetto, PhD (2019)

## References

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

## Examples

```
check_scihub_login("user", "user")
write_scihub_login("user", "user")
read_scihub_login()
check_scihub_connection()
```

---

s2\_calcindices                      *Compute maps of spectral indices*

---

### Description

Create maps of a set of spectral indices. Since `gdal_calc.py` is used to perform computations, output files are physical rasters (no output VRT is allowed).

### Usage

```
s2_calcindices(
  infiles,
  indices,
  outdir = ".",
  parameters = NULL,
  source = c("TOA", "BOA"),
  format = NA,
  subdirs = NA,
  tmpdir = NA,
  compress = "DEFLATE",
  bigtiff = FALSE,
  dataType = "Int16",
  scaleFactor = NA,
  proc_mode = "raster",
  parallel = FALSE,
  overwrite = FALSE,
  .log_message = NA,
  .log_output = NA
)
```

### Arguments

infiles	A vector of input filenames. Input files are paths of BOA (or TOA) products already converted from SAFE format to a format managed by GDAL (use <a href="#">s2_translate</a> to do it); their names must be in the sen2r naming convention ( <a href="#">safe_shortname</a> ).
indices	Character vector with the names of the required indices. Values should be included in names corresponding to the Abbreviations of the following indices: <b>IDB</b> .
outdir	(optional) Full name of the output directory where the files should be created (default: current directory). <code>outdir</code> can be an existing or non-existing directory (in the second case, its parent directory must exist). If it is a relative path, it is expanded from the common parent directory of <code>infiles</code> .
parameters	(optional) Values of index parameters. This variable must be a named list, in which each element is a list of parameters, i.e.: <code>parameters = list("SAVI" = list("a" = 0.5))</code> Values can be both numeric values or band names (e.g. "band_1"). If not specified, parameters are set to default values.

source	(optional) Vector with the products from which computing the indices. It can be "BOA", "TOA" or both (default). If both values are provided, indices are computed from the available products ("TOA" if TOA is available, BOA if BOA is available); in the case both are available, two files are produced (they can be distinguished from the level component - S2x1C or S2x2A - in the filename).
format	(optional) Format of the output file (in a format recognised by GDAL). Default is the same format of input images (or "GTiff" in case of VRT input images).
subdirs	(optional) Logical: if TRUE, different indices are placed in separated outfile subdirectories; if FALSE, they are placed in outfile directory; if NA (default), subdirectories are created only if more than a single spectral index is required.
tmpdir	(optional) Path where intermediate files (GTiff) will be created in case format is "VRT".
compress	(optional) In the case a GTiff format is present, the compression indicated with this parameter is used.
bigtiff	(optional) Logical: if TRUE, the creation of a BigTIFF is forced (default is FALSE). This option is used only in the case a GTiff format was chosen.
dataType	(optional) Numeric datatype of the output rasters. if "Float32" or "Float64" is chosen, numeric values are not rescaled; if "Int16" (default) or "UInt16", values are multiplied by scaleFactor argument; if "Byte", values are shifted by 100, multiplied by 100 and truncated at 200 (so that range -1 to 1 is coerced to 0-200), and nodata value is assigned to 255.
scaleFactor	(optional) Scale factor for output values when an integer datatype is chosen (default values are 10000 for "Int16" and "UInt16", 1E9 for "Int32" and "UInt32"). Notice that, using "UInt16" and "UInt32" types, negative values will be truncated to 0.
proc_mode	(optional) Character: if "gdal_calc", gdal_calc routines are used to compute indices; if "raster" (default) or "stars", R functions are instead used (using respectively raster or stars routines). <b>Notes:</b> <ol style="list-style-type: none"> <li>1. default value ("raster") is the only fully supported mode. "gdal_calc" can be used only if a runtime GDAL environment can be properly configured (no assistance is provided in case of GDAL-related problems). "raster" mode is experimental.</li> <li>2. There is a difference in which the two modes manage values out of ranges (e.g. -32768 to 32767 in Int16 and 0 to 255 in Byte): "raster" and "stars" modes set these values to NA, "gdal_calc" mode clip them to the minimum/maximum values;</li> </ol>
parallel	(optional) Logical: if TRUE, the function is run using parallel processing, to speed-up the computation for large rasters. The number of cores is automatically determined; specifying it is also possible (e.g. parallel = 4). If FALSE (default), single core processing is used. Multiprocess masking computation is always performed in singlecore mode
overwrite	Logical value: should existing output files be overwritten? (default: FALSE)
.log_message	(optional) Internal parameter (it is used when the function is called by sen2r()).
.log_output	(optional) Internal parameter (it is used when the function is called by sen2r()).

**Value**

A vector with the names of the created products.

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2020) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

**Examples**

```
# Define file names
ex_in <- system.file(
  "extdata/out/S2A2A_20190723_022_Barbellino_B0A_10.tif",
  package = "sen2r"
)

# Run function
ex_out <- s2_calcindices(
  infiles = ex_in,
  indices = "EVI",
  outdir = tempdir(),
  dataType = "Float32"
)
ex_out

# Show output
oldpar <- par(mfrow = c(1,2), mar = rep(0,4))
image(stars::read_stars(ex_in), rgb = 4:2, maxColorValue = 3500, useRaster = TRUE)
par(mar = rep(2/3,4))
image(stars::read_stars(ex_out), useRaster = TRUE)
par(oldpar)
```

---

s2\_defNA

*Set NA value of a specific product type*

---

**Description**

Internal function to determine the NA value to be used for each product type (except for spectral indices, whose NA value is managed by [s2\\_calcindices](#)).

**Usage**

```
s2_defNA(prod_types)
```

**Arguments**

prod\_types      Character vector of the input product types

**Value**

Numeric NA values (NA not to set any NA value), corresponding to prod\_types.

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**Examples**

```
sen2r:::s2_defNA("BOA")
sen2r:::s2_defNA(c("BOA", "BOA", "SCL", "TCI"))
```

---

s2\_dop

*Return the Dates Of Passage over some orbits*


---

**Description**

The function allows to know which Sentinel-2 passages should pass over certain orbits during a defined time interval. Dates are intended to be in UTC time. Notice that this is the expected calendar: some unexpected events (e.g. technical problems, or early working phases during first stages of acquisition) could cause the data unavailability even if an acquisition was expected. Notice also that some orbits (030, 073 and 116) acquire across UTC midnight: in this cases, the date is assumed to be the one of the acquisition after midnight (which corresponds to the date in local time).

**Usage**

```
s2_dop(s2_orbits = 1:143, timewindow = "10 days", mission = c("2A", "2B"))
```

**Arguments**

s2\_orbits      A vector of Sentinel-2 orbits (as integer numbers or 3-length character). Default is all the 143 orbits.

timewindow    Temporal window for querying: Date object of length 1 (single day) or 2 (time window). Is it possible to pass also integer (or difftime) values, which are interpreted as the next n days (if positive) or the past n days (if negative). Also strings which can be interpreted as time ranges are accepted (see examples). Default is the next 10 days (one cycle).

mission        (optional) Vector with the desired Sentinel-2 missions ("2A", "2B" or both). Default is both.

**Value**

A data table with the dates (column "date"), the missions (column "mission") and the orbits (column "orbit"). An empty data table with the same structure is returned if no passages were found with the passed settings.

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

**Examples**

```
# All the passages in a cycle of 10 days over all the orbits
s2_dop()

# The passages in the current month over two orbits
s2_dop(c("022", "065"), "this month")

# The dates in which Sentinel-2A will pass in next six weeks over one orbit
s2_dop("022", "6 weeks", mission = "2A")$date

# The date in which Sentinel-2A would be passed in the last 10 days over one orbit
s2_dop("022", "-10 days", mission = "2A")$date

# All the orbits covered today
s2_dop(timewindow = Sys.Date(), mission = "2B")$orbit

# The passages in a fixed time window for one orbit
s2_dop(65, as.Date(c("2018-08-01", "2018-08-31")))

# A research with no passages found
s2_dop(22, "2018-08-16", mission = "2A")
```

---

s2\_download

*Download S2 products.*

---

**Description**

The function downloads S2 products. Input filenames must be elements obtained with [s2\\_list](#) function (each element must be a URL, and the name the product name).



**Usage**

```
s2_download(  
  s2_prodlst = NULL,  
  downloader = "builtin",  
  apihub = NA,  
  service = NA,  
  tile = NULL,  
  outdir = ".",  
  order_lta = TRUE,  
  overwrite = FALSE  
)
```

**Arguments**

s2_prodlst	Named character: list of the products to be downloaded, in the format <code>safelist</code> (see <code>safelist</code> ). Alternatively, it can be the path of a JSON file exported by <code>s2_order</code> .
downloader	Executable to use to download products (default: "builtin"). Alternatives are "builtin" or "aria2" (this requires aria2c to be installed).
apihub	Path of the <code>apihub.txt</code> file containing credentials of SciHub account. If NA (default), the default location inside the package will be used.
service	Character: it can be "dhus" or "apihub", in which cases the required service is forced instead that the one present in the URLs passed through argument <code>s2_prodlst</code> . If NA (default), the service present in the URLs is maintained.
tile	Deprecated argument
outdir	(optional) Full name of the existing output directory where the files should be created (default: current directory).
order_lta	Logical: if TRUE (default), products which are not available for direct download are ordered from the Long Term Archive; if FALSE, they are simply skipped.
overwrite	Logical value: should existing output archives be overwritten? (default: FALSE)

**Value**

Vector character with the list of the output products (being downloaded or already existing).

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2020) <luigi@ranghetti.info>

Lorenzo Busetto, PhD (2019)

## References

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

## Examples

```
## Not run:
single_s2 <- paste0("https://scihub.copernicus.eu/apihub/odata/v1/",
  "Products(\'c7142722-42bf-4f93-b8c5-59fd1792c430\')/$value")
names(single_s2) <- "S2A_MSIL1C_20170613T101031_N0205_R022_T32TQQ_20170613T101608.SAFE"
# (this is equivalent to:
# single_s2 <- example_s2_list[1]
# where example_s2_list is the output of the example of the
# s2_list() function)

# Download the whole product
s2_download(single_s2, outdir=tempdir())

#' # Download the whole product - using aria2
s2_download(single_s2, outdir=tempdir(), downloader = "aria2")

# Download more products, ordering the ones stored in the Long Term Archive
pos <- sf::st_sfc(sf::st_point(c(-57.8815,-51.6954)), crs = 4326)
time_window <- as.Date(c("2018-02-21", "2018-03-20"))
list_safe <- s2_list(spatial_extent = pos, time_interval = time_window)
s2_download(list_safe, outdir=tempdir())

## End(Not run)
```

---

s2\_gui

*Launch the GUI for Sentinel-2 products*

---

## Description

Launch the GUI to set parameters for the processing chain of Sentinel-2 products.

## Usage

```
s2_gui(param_list = NULL, thunderforest_api = NA)
```

## Arguments

`param_list` List of parameters for initialising the GUI values (if empty, default values are used).

`thunderforest_api` Character value with the API for thunderforest layers (now not used).

**Value**

A list of parameters.

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

---

s2\_list

*Retrieve list of available S2 products.*


---

**Description**

The function retrieves the list of available Sentinel-2 products satisfying given search criteria.

**Usage**

```
s2_list(
  spatial_extent = NULL,
  tile = NULL,
  orbit = NULL,
  time_interval = c(Sys.Date() - 10, Sys.Date()),
  time_period = "full",
  level = "auto",
  server = "scihub",
  apihub = NA,
  service = "apihub",
  max_cloud = 100,
  availability = "ignore",
  output_type = "deprecated"
)
```

**Arguments**

**spatial\_extent** A valid spatial object object of class sf, sfc or sfg  
**tile** string array Sentinel-2 Tiles to be considered string (5-length character)  
**orbit** string array Sentinel-2 orbit numbers to be considered

time_interval	Dates to be considered, as a temporal vector (class <code>POSIXct</code> or <code>Date</code> , or string in YYYY-mm-dd format) of length 1 (specific day) or 2 (time interval).
time_period	(optional) Character: <ul style="list-style-type: none"> <li>• "full" (default) means that all the images included in the time window are considered;</li> <li>• "seasonal" means that only the single seasonal periods in the window are used (i.e., with a time window from 2015-06-01 to 2017-08-31, the periods 2015-06-01 to 2015-08-31, 2016-06-01 to 2016-08-31 and 2017-06-01 to 2017-08-31 are considered).</li> </ul>
level	Character vector with one of the following: - "auto" (default): check if level-2A is available on SciHub: if so, list it; if not, list the corresponding level-1C product - "L1C": list available level-1C products - "L2A": list available level-2A products
server	The servers where archives are searched. Currently, only "sci-hub" is supported (Google Cloud will be implemented in future). In case of multiple values, they are used in order of priority. If <code>availability = "check"</code> , products on LTA are always left as last choice.
apihub	Path of the <code>apihub.txt</code> file containing credentials of SciHub account. If NA (default), the default location inside the package will be used.
service	Character: it can be "dhus" or "apihub" (default), in which cases the required service is forced instead that the one present in the URLs passed through argument <code>s2_prodlst</code> .
max_cloud	Integer number (0-100) containing the maximum cloud level of the tiles to be listed (default: no filter).
availability	Character argument, determining which products have to be returned: <ul style="list-style-type: none"> <li>• "online" : only archive names already available for download are returned;</li> <li>• "lta": only archive names stored in the <b>Long Term Archive</b> are returned;</li> <li>• "check": all archive names are returned, checking if they are available or not for download (see "Value" to know how to distinguish each other);</li> <li>• "ignore" (default): all archive names are returned, without doing the check (running the function is faster).</li> </ul>
output_type	Deprecated (use <code>as.data.table</code> to obtain a <code>data.table</code> ).

### Value

An object of class `safelist`. The attribute `online` contains logical values: in case `availability != "ignore"`, values are TRUE / FALSE for products available for download / stored in the Long Term Archive; otherwise, values are set to NA.

### Note

License: GPL 3.0

**Author(s)**

Lorenzo Busetto, PhD (2019) - Inspired by function `getSentinel1_query` of package `getSpatialData` by J. Schwalb-Willmann

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

**Examples**

```
pos <- sf::st_sfc(sf::st_point(c(9.85,45.81)), crs = 4326)
time_window <- as.Date(c("2016-05-01", "2017-07-30"))

# Full-period list
example_s2_list <- s2_list(
  spatial_extent = pos,
  tile = "32TNR",
  time_interval = time_window,
  orbit = "065"
)
print(example_s2_list)
# Print the dates of the retrieved products
safe_getMetadata(example_s2_list, "sensing_datetime")

# Seasonal-period list
example_s2_list <- s2_list(
  spatial_extent = pos,
  tile = "32TNR",
  time_interval = time_window,
  time_period = "seasonal"
)
print(example_s2_list)
# Print the dates of the retrieved products
safe_getMetadata(example_s2_list, "sensing_datetime")
```

---

s2\_mask

*Apply cloud masks*


---

**Description**

`s2_mask` Applies a cloud mask to a Sentinel-2 product. Since `raster` functions are used to perform computations, output files are physical rasters (no output VRT is allowed).

`s2_perc_masked` computes the percentage of cloud-masked surface. The function is similar to `s2_mask`, but it returns percentages instead of masked rasters.

**Usage**

```

s2_mask(
  infiles,
  maskfiles,
  mask_type,
  smooth = 0,
  buffer = 0,
  max_mask = 100,
  outdir = "./masked",
  tmpdir = NA,
  rmtmp = TRUE,
  save_binary_mask = FALSE,
  format = NA,
  subdirs = NA,
  compress = "DEFLATE",
  bigtiff = FALSE,
  parallel = FALSE,
  overwrite = FALSE,
  .log_message = NA,
  .log_output = NA
)

s2_perc_masked(
  infiles,
  maskfiles,
  mask_type = "cloud_medium_proba",
  tmpdir = NA,
  rmtmp = TRUE,
  parallel = FALSE
)

```

**Arguments**

infiles	A vector of input filenames. Input files are paths of products already converted from SAFE format to a format managed by GDAL (use <a href="#">s2_translate</a> to do it); their names must be in the sen2r naming convention ( <a href="#">safe_shortcode</a> ).
maskfiles	A vector of filenames from which to take the information about cloud coverage (for now, only SCL products have been implemented). It is not necessary that maskfiles elements strictly match infiles ones. Input files are paths of products already converted from SAFE format to a format managed by GDAL (use <a href="#">s2_translate</a> to do it); their names must be in the sen2r naming convention ( <a href="#">safe_shortcode</a> ).
mask_type	Character vector which determines the type of mask to be applied. Accepted values are: <ul style="list-style-type: none"> <li>"nomask": do not mask any pixel;</li> <li>"nodata": mask pixels checked as "No data" or "Saturated or defective" in the SCL product (all pixels with values are maintained);</li> </ul>

	<ul style="list-style-type: none"> <li>• "cloud_high_proba": mask pixels checked as "No data", "Saturated or defective" or "Cloud (high probability)" in the SCL product;</li> <li>• "cloud_medium_proba": mask pixels checked as "No data", "Saturated or defective" or "Cloud (high or medium probability)" in the SCL product;</li> <li>• "cloud_and_shadow": mask pixels checked as "No data", "Saturated or defective", "Cloud (high or medium probability)" or "Cloud shadow" in the SCL product;</li> <li>• "clear_sky": mask pixels checked as "No data", "Saturated or defective", "Cloud (high or medium probability)", "Cloud shadow", "Unclassified" or "Thin cirrus" in the SCL product (only pixels classified as clear-sky surface - so "Dark area", "Vegetation", "Bare soil", "Water" or "Snow" - are maintained);</li> <li>• "land": mask pixels checked as "No data", "Saturated or defective", "Cloud (high or medium probability)", "Cloud shadow", "Dark area", "Unclassified", "Thin cirrus", "Water" or "Snow" in the SCL product (only pixels classified as land surface - so "Vegetation" or "Bare soil" - are maintained);</li> <li>• a string in the following form: "scl_n_m_n", where n, m and n are one or more SCL class numbers. E.g. string "scl_0_8_9_11" can be used to mask classes 0 ("No data"), 8-9 ("Cloud (high or medium probability)") and 11 ("Snow").</li> </ul>
smooth	(optional) Numerical (positive): the size (in the unit of inmask, typically metres) to be used as radius for the smoothing (the higher it is, the more smooth the output mask will result). Default is 0 (no smoothing is applied).
buffer	(optional) Numerical (positive or negative): the size of the buffer (in the unit of inmask, typically metres) to be applied to the masked area after smoothing it (positive to enlarge, negative to reduce). Default is 0 (no buffer).
max_mask	(optional) Numeric value (range 0 to 100), which represents the maximum percentage of allowed masked surface (by clouds or any other type of mask chosen with argument mask_type) for producing outputs. Images with a percentage of masked surface greater than max_mask% are not processed (the list of expected output files which have not been generated is returned as an attribute, named skipped). Default value is 100 (images are always produced). Notice that the percentage is computed on non-NA values (if input images had previously been clipped and masked using a polygon, the percentage is computed on the surface included in the masking polygons).
outdir	(optional) Full name of the output directory where the files should be created (default: "masked" subdir of current directory). outdir can not be an existing or non-existing directory (in the second case, its parent directory must exist). If it is a relative path, it is expanded from the common parent directory of infiles.
tmpdir	(optional) Path where intermediate files (VRT) will be created. Default is a temporary directory. If tmpdir is a non-empty folder, a random subdirectory will be used.
rmtmp	(optional) Logical: should temporary files be removed? (Default: TRUE). This parameter takes effect only if the output files are not VRT (in this case temporary files cannot be deleted, because rasters of source bands are included within them).

save_binary_mask	(optional) Logical: should binary masks be exported? Binary mask are intermediate rasters used to apply the cloud mask: pixel values can be 1 (no cloud mask), 0 (cloud mask) or NA (original NA value, i.e. because input rasters had been clipped on the extent polygons). If FALSE (default) they are not exported; if TRUE, they are exported as MSK prod type (so saved within outdir, in a subdirectory called "MSK" if subdirs = TRUE). Notice that the presence of "MSK" products is not checked before running sen2r(), as done for the other products; this means that missing products which are not required to apply cloud masks will not be produced.
format	(optional) Format of the output file (in a format recognised by GDAL). Default is the same format of input images (or "GTiff" in case of VRT input images).
subdirs	(optional) Logical: if TRUE, different indices are placed in separated outfile subdirectories; if FALSE, they are placed in outfile directory; if NA (default), subdirectories are created only if more than a single product is required.
compress	(optional) In the case a GTiff format is present, the compression indicated with this parameter is used.
bigtiff	(optional) Logical: if TRUE, the creation of a BigTIFF is forced (default is FALSE). This option is used only in the case a GTiff format was chosen.
parallel	(optional) Logical: if TRUE, masking is conducted using parallel processing, to speed-up the computation for large rasters. The number of cores is automatically determined; specifying it is also possible (e.g. parallel = 4). If FALSE (default), single core processing is used. Multiprocess masking computation is always performed in singlecore mode if format != "VRT" (because in this case there is no gain in using multicore processing).
overwrite	(optional) Logical value: should existing output files be overwritten? (default: FALSE)
.log_message	(optional) Internal parameter (it is used when the function is called by sen2r()).
.log_output	(optional) Internal parameter (it is used when the function is called by sen2r()).

### Value

[s2\\_mask](#) returns a vector with the names of the created products. An attribute "toomasked" contains the paths of the outputs which were not created cause to the high percentage of cloud coverage.

[s2\\_perc\\_masked](#) returns a names vector with the percentages of masked surfaces.

### Note

License: GPL 3.0

### Author(s)

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>



## References

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

## Examples

```
# Define file names
ex_in <- system.file(
  "extdata/out/S2A2A_20190723_022_Barbellino_RGB432B_10.tif",
  package = "sen2r"
)
ex_mask <- system.file(
  "extdata/out/S2A2A_20190723_022_Barbellino_SCL_10.tif",
  package = "sen2r"
)

# Run function
ex_out <- s2_mask(
  infiles = ex_in,
  maskfiles = ex_mask,
  mask_type = "land",
  outdir = tempdir()
)
ex_out

# Show output
oldpar <- par(mfrow = c(1,3))
par(mar = rep(0,4))
image(stars::read_stars(ex_in), rgb = 1:3, useRaster = TRUE)
par(mar = rep(2/3,4))
image(stars::read_stars(ex_mask), useRaster = TRUE)
par(mar = rep(0,4))
image(stars::read_stars(ex_out), rgb = 1:3, useRaster = TRUE)
par(oldpar)
```

---

s2\_merge

---

*Merge S2 tiles with the same date and orbit*


---

## Description

The function merge the input Sentinel-2 files with the same date, orbit number, product type and file format. Outputs are a set of products in the same format of corresponding input files.

**Usage**

```
s2_merge(
  infiles,
  outdir = ".",
  subdirs = NA,
  tmpdir = NA,
  rmtmp = TRUE,
  format = NA,
  compress = "DEFLATE",
  bigtiff = FALSE,
  vrt_rel_paths = NA,
  out_crs = NA,
  parallel = FALSE,
  overwrite = FALSE,
  .log_message = NA,
  .log_output = NA
)
```

**Arguments**

<code>infiles</code>	A vector of input filenames. Input files are paths of products already converted from SAFE format to a format managed by GDAL (use <code>s2_translate</code> to do it); their names must be in the sen2r naming convention ( <code>safe_shortname</code> ).
<code>outdir</code>	(optional) Full name of the output directory where the files should be created (default: current directory). <code>outdir</code> can bot be an existing or non-existing directory (in the second case, its parent directory must exists). If it is a relative path, it is expanded from the common parent directory of <code>infiles</code> .
<code>subdirs</code>	(optional) Logical: if TRUE, different output products are placed in separated outfile subdirectories; if FALSE, they are placed in outfile directory; if NA (default), subdirectories are created only if <code>infiles</code> relate to more than a single product.
<code>tmpdir</code>	(optional) Path where intermediate files (VRT) will be created. Default is a temporary directory. If <code>tmpdir</code> is a non-empty folder, a random subdirectory will be used.
<code>rmtmp</code>	(optional) Logical: should temporary files be removed? (Default: TRUE). This parameter takes effect only if the output files are not VRT (in this case temporary files cannot be deleted, because rasters of source bands are included within them).
<code>format</code>	(optional) Format of the output file (in a format recognised by GDAL). Default is to maintain each input format.
<code>compress</code>	(optional) In the case a GTiff format is present, the compression indicated with this parameter is used.
<code>bigtiff</code>	(optional) Logical: if TRUE, the creation of a BigTIFF is forced (default is FALSE). This option is used only in the case a GTiff format was chosen.
<code>vrt_rel_paths</code>	(optional) Logical: if TRUE (default on Linux), the paths present in the VRT output file are relative to the VRT position; if FALSE (default on Windows), they are absolute. This takes effect only with <code>format = "VRT"</code> .

out_crs	(optional) output CRS, in any format accepted by <code>st_crs2</code> (default: the CRS of the first input file). The tiles with CRS different from out_crs will be reprojected (and a warning returned).
parallel	(optional) Logical: if TRUE, the function is run using parallel processing, to speed-up the computation for large rasters. The number of cores is automatically determined; specifying it is also possible (e.g. parallel = 4). If FALSE (default), single core processing is used.
overwrite	Logical value: should existing output files be overwritten? (default: FALSE)
.log_message	(optional) Internal parameter (it is used when the function is called by <code>sen2r()</code> ).
.log_output	(optional) Internal parameter (it is used when the function is called by <code>sen2r()</code> ).

**Value**

A vector with the names of the merged products (just created or already existing).

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

---

s2_order	<i>Order S2 products.</i>
----------	---------------------------

---

**Description**

The function orders S2 products from [Long Term Archive](#).

**Usage**

```
s2_order(
  s2_prodlst = NULL,
  export_prodlst = TRUE,
  delay = 0.5,
  apihub = NA,
  service = NA,
  reorder = TRUE
)
```

## Arguments

s2_prodlst	Named character: list of the products to be ordered, in the format safelist (see <a href="#">safelist</a> ). Alternatively, it can be the path of a JSON file exported by a previous execution of <a href="#">s2_order</a> , in case the user wants, for any reason, to resubmit the order.
export_prodlst	Logical or character: if TRUE (default), the list of ordered products is saved in a JSON text file, so to be easily retrievable at a later stage with <a href="#">safe_is_online</a> or <a href="#">s2_download</a> ; if FALSE, no output files are generated. It is also possible to pass the path of an existing folder in which the JSON file will be saved (otherwise, a default path is used).
delay	Numeric: time frame (in seconds) to leave between two consecutive orders. Default is 0.5 seconds: use a higher value if you encountered errors (i.e. not all the products were correctly ordered).
apihub	Path of the apihub.txt file containing credentials of SciHub account. If NA (default), the default location inside the package will be used.
service	Character: it can be "dhus" or "apihub", in which cases the required service is forced instead that the one present in the URLs passed through argument s2_prodlst. If NA (default), the service present in the URLs is maintained.
reorder	Logical: If TRUE, and a json file exported by s2_order is passed as argument to the function, try to order again also the "available" and "ordered" S2 datasets. Otherwise, only order the "notordered" ones.

## Value

A named vector, containing the subset of s2\_prodlst elements which were ordered. Moreover, the vector includes the following attributes:

- "available" with the elements of s2\_prodlst which were already available for download,
- "notordered" with the elements of s2\_prodlst which were not ordered for any reasons,
- "path" (only if argument export\_prodlst is not FALSE) with the path of the json file in which the list of the products (ordered, available and not ordered) was saved (if export\_prodlst = TRUE).

## Note

License: GPL 3.0

## Author(s)

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

Lorenzo Busetto, PhD (2020)

## References

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

## Examples

```
# Generate the lists of products
pos <- sf::st_sfc(sf::st_point(c(-57.8815,-51.6954)), crs = 4326)
time_window <- as.Date(c("2018-02-21", "2018-03-20"))
list_safe <- s2_list(spatial_extent = pos, time_interval = time_window)
print(list_safe)
# (at the time the documentation was written, this list was containing 5
# archives already available online and 2 stored in the Long Term Archive)

# Order the products
ordered_prods <- s2_order(list_safe)

# Check in a second time if the product was made available
(order_path <- attr(ordered_prods, "path"))
safe_is_online(order_path)
```

---

s2\_rgb

*Create RGB images from S2 reflectance products.*

---

## Description

Function to create RGB images from Sentinel-2 reflectances.

## Usage

```
s2_rgb(  
  infiles,  
  prod_type = NA,  
  rgb_bands = 4:2,  
  scaleRange = NA,  
  outdir = NA,  
  subdirs = NA,  
  format = NA,  
  compress = "DEFLATE",  
  bigtiff = FALSE,  
  tmpdir = NA,  
  rmtmp = TRUE,  
  proc_mode = "raster",  
  parallel = TRUE,  
  overwrite = FALSE,  
  .log_message = NA,  
  .log_output = NA  
)
```

**Arguments**

infile	A vector of input filenames. Input files are paths of products already converted from SAFE format to a format managed by GDAL (use <a href="#">s2_translate</a> to do it); their names must be in the sen2r naming convention ( <a href="#">safe_shortcode</a> ).
prod_type	(optional) Output product (see <a href="#">safe_shortcode</a> for the list of accepted products). If not provided, it is retrieved from the file name.
rgb_bands	(optional) 3-length integer vector, which the number of the bands to be used respectively for red, green and blue. Default is 4:2 (true colours). It is also possible to pass a list of 3-length integer vectors in order to create multiple RGB types for each input file. Notice that this is the <b>actual number name of the bands</b> : so, to use i.e. BOA band 11 (1610nm) use the number 11, even if band 11 is the 10th band of a BOA product (because band 10 is missing).
scaleRange	(optional) Range of valid values. It can be a 2-length integer vector (min-max for all the 3 bands) or a 6-length vector or 3x2 matrix (min red, min green, min blue, max red, max green, max blue). Default is to use c(0,2500) for bands 1-5; c(0,7500) bands 6-12.
outdir	(optional) Full name of the existing output directory where the files should be created. Default is the same directory of input reflectance files.
subdirs	(optional) Logical: if TRUE, different indices are placed in separated outfile subdirectories; if FALSE, they are placed in outfile directory; if NA (default), subdirectories are created only if more than a single spectral index is required.
format	(optional) Format of the output file (in a format recognised by GDAL). Default is the same format of input images (or "GTiff" in case of VRT input images).
compress	(optional) In the case a GTiff format is present, the compression indicated with this parameter is used.
bigtiff	(optional) Logical: if TRUE, the creation of a BigTIFF is forced (default is FALSE). This option is used only in the case a GTiff format was chosen.
tmpdir	(optional) Path where intermediate files (VRT) will be created. Default is a temporary directory. If tmpdir is a non-empty folder, a random subdirectory will be used.
rmtmp	(optional) Logical: should temporary files be removed? (Default: TRUE)
proc_mode	(optional) Character: if "gdal_calc", gdal_calc routines are used to compute indices; if "raster" or "stars", R functions are instead used (using respectively raster or stars routines). <b>Note</b> : default value ("raster") is the only fully supported mode. "gdal_calc" can be used only if a runtime GDAL environment can be properly configured (no assistance is provided in case of GDAL-related problems). "raster" mode is experimental. See <a href="#">s2_calcindices()</a> for further details.
parallel	(optional) Logical: if TRUE, the function is run using parallel processing, to speed-up the computation for large rasters. The number of cores is automatically determined; specifying it is also possible (e.g. parallel = 4). If FALSE (default), single core processing is used.
overwrite	(optional) Logical value: should existing thumbnails be overwritten? (default: TRUE)

- .log\_message (optional) Internal parameter (it is used when the function is called by `sen2r()`).
- .log\_output (optional) Internal parameter (it is used when the function is called by `sen2r()`).

### Value

A vector with the names of the created images.

### Note

License: GPL 3.0

### Author(s)

Luigi Ranghetti, PhD (2019) <[luigi@ranghetti.info](mailto:luigi@ranghetti.info)>

### References

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

### Examples

```
# Define file names
ex_in <- system.file(
  "extdata/out/S2A2A_20190723_022_Barbellino_B0A_10.tif",
  package = "sen2r"
)

# Run function
ex_out <- s2_rgb(
  infiles = ex_in,
  rgb_bands = list(c(11,8,4),c(9,5,4)),
  scaleRange = list(c(0,7500), matrix(c(rep(0,3),8500,6000,4000),ncol=2)),
  outdir = tempdir(),
  compress = 50
)
ex_out

# Show output
oldpar <- par(mfrow = c(1,3), mar = rep(0,4))
image(stars::read_stars(ex_in), rgb = 4:2, maxColorValue = 3500, useRaster = TRUE)
image(stars::read_stars(ex_out[1]), rgb = 1:3, useRaster = TRUE)
image(stars::read_stars(ex_out[2]), rgb = 1:3, useRaster = TRUE)
par(oldpar)
```

---

s2\_thumbnails                      *Create thumbnails for S2 products.*

---

### Description

Function to create thumbnail images for Sentinel-2 products. BOA and TOA multiband images are rendered as false colour JPEG images; SCL maps are rendered as 8-bit PNG; other singleband images (like spectral indices) are rendered as JPEG images with a standard colour palette. Output images are georeferenced.

### Usage

```
s2_thumbnails(
  infiles,
  prod_type = NA,
  rgb_type = "SwirNirR",
  dim = 1024,
  scaleRange = NA,
  outdir = NA,
  tmpdir = NA,
  rmtmp = TRUE,
  proc_mode = "raster",
  overwrite = FALSE
)
```

### Arguments

infiles	A vector of input filenames. Input files are paths of products already converted from SAFE format to a format managed by GDAL (use <a href="#">s2_translate</a> to do it); their names must be in the sen2r naming convention ( <a href="#">safe_shortcode</a> ).
prod_type	(optional) Output product (see <a href="#">safe_shortcode</a> for the list of accepted products). If not provided, it is retrieved from the file name.
rgb_type	(optional) For BOA and TOA products, this value determine the type of false colours to be used for the thumbnails: <ul style="list-style-type: none"> <li>• "SwirNirR" (default) for SWIR-NIR-Red;</li> <li>• "NirRG" for NIR-Red-Green;</li> <li>• "RGB" for true colours;</li> </ul>
dim	Integer value, with the maximum greater dimension in pixels (width or height) of the output images (default: 1024 px). If this is lower than the corresponding dimension of the maps, maps are rescaled before producing the thumbnails; otherwise the original dimensions are maintained. To keep the original size in any case, set dim = Inf.
scaleRange	(optional) Range of valid values. If not specified (default), it is automatically retrieved from the product type. Default ranges for BOA and TOA products are 0 to 8000 (rgb_type = "SwirNirR"), 0 to 7500 ("NirRG") and 0 to 2500



	("RGB"). For spectral indices, default range is -1 to 1 for Float products, -10000 to 10000 for Int and 0 to 200 for Byte; for "Zscore" products, default range is -3 to 3 for Float and -3000 to 3000 for Int. It can be useful i.e. to stretch BOA "dark" products.
outdir	(optional) Full name of the existing output directory where the files should be created. Default is a subdirectory (named "thumbnails") of the parent directory of each input file.
tmpdir	(optional) Path where intermediate files (VRT) will be created. Default is a temporary directory. If tmpdir is a non-empty folder, a random subdirectory will be used.
rmtmp	(optional) Logical: should temporary files be removed? (Default: TRUE)
proc_mode	(optional) Character: if "gdal_calc", gdal_calc routines are used to compute indices; if "raster" or "stars", R functions are instead used (using respectively raster or stars routines). <b>Note:</b> default value ("raster") is the only fully supported mode. "gdal_calc" can be used only if a runtime GDAL environment can be properly configured (no assistance is provided in case of GDAL-related problems). "raster" mode is experimental. See s2_calcindices() for further details.
overwrite	(optional) Logical value: should existing thumbnails be overwritten? (default: TRUE)

**Value**

A vector with the names of the created images.

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

---

s2\_tiles

*Load Sentinel-2 tiles*


---

**Description**

Load the vector object of the Sentinel-2 tiles. When the function is run for the first time, it downloads the vector file from the sen2r GitHub repository and it saves it on disk.

**Usage**

```
s2_tiles()
```

**Value**

An sf spatial object containing the extent of the tiles.

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

**Examples**

```
# Retrieve all the tiles
s2tiles <- s2_tiles()

# Extract a subset of all the tiles
htr::GET(
  "https://github.com/ranghetti/sen2r/raw/master/utils/vector/ch_bound.rds",
  htr::write_disk(ch_path <- tempfile())
)
ch <- readRDS(ch_path)
s2tiles_ch <- s2tiles[suppressMessages(sf::st_intersects(ch, s2tiles))[[1]],]
s2_coords <- sf::st_coordinates(suppressWarnings(sf::st_centroid(s2tiles_ch)))

# Show the tiles
plot(s2tiles_ch$geometry, border = "blue")
plot(ch, border = "red", add = TRUE)
text(s2_coords[,1], s2_coords[,2], s2tiles_ch$tile_id, col = "blue", cex = .75)

# Use function tiles_intersects() to exclude unuseful tiles.
```

---

s2\_translate

---

*Convert from SAFE format*


---

**Description**

The function build a virtual raster from a Sentinel2 SAFE product, eventually translating it in another spatial format. For now, only L1C and L2a with long name (< 2016/12/06) are recognised. Output vrt is at 10m resolution.

**Usage**

```
s2_translate(
  infile,
  outdir = ".",
  subdirs = NA,
  tmpdir = NA,
  rmtmp = TRUE,
  prod_type = NULL,
  tiles = NA,
  res = "10m",
  format = "VRT",
  compress = "DEFLATE",
  bigtiff = FALSE,
  vrt_rel_paths = NA,
  utmzone = "",
  overwrite = FALSE
)
```

**Arguments**

<code>infile</code>	Full path of the input SAFE folder (alternatively, full path of the xml file of the product with metadata).
<code>outdir</code>	(optional) Full name of the output directory where the files should be created (default: current directory). <code>outdir</code> can not be an existing or non-existing directory (in the second case, its parent directory must exist). If it is a relative path, it is expanded from the directory of <code>infile</code> .
<code>subdirs</code>	(optional) Logical: if TRUE, different output products are placed in separated <code>outdir</code> subdirectories; if FALSE, they are placed in <code>outdir</code> directory; if NA (default), subdirectories are created only if <code>prod_type</code> has length > 1.
<code>tmpdir</code>	(optional) Path where intermediate files (VRT) will be created. Default is a temporary directory. If <code>tmpdir</code> is a non-empty folder, a random subdirectory will be used.
<code>rmtmp</code>	(optional) Logical: should temporary files be removed? (Default: TRUE). This parameter takes effect only if the output files are not VRT (in this case temporary files cannot be deleted, because rasters of source bands are included within them).
<code>prod_type</code>	(optional) Vector of types to be produced as outputs (see <a href="#">safe_shortcode</a> for the list of accepted values). Default is reflectance ("TOA" for level 1C, "BOA" for level 2A).
<code>tiles</code>	(optional) Character vector with the desired output tile IDs (id specified IDs are not present in the input SAFE product, they are not produced). Default (NA) is to process all the found tiles.
<code>res</code>	(optional) Spatial resolution (one between '10m', '20m' or '60m'); default is '10m'. Notice that, choosing '10m' or '20m', bands with lower resolution will be rescaled to <code>res</code> . Band 08 is used with <code>res = '10m'</code> , band 08A with <code>res = '20m'</code> and <code>res = '60m'</code> .

format	(optional) Format of the output file (in a format recognised by GDAL). Default value is "VRT" (Virtual Raster).
compress	(optional) In the case a GTiff format is chosen, the compression indicated with this parameter is used.
bigtiff	(optional) Logical: if TRUE, the creation of a BigTIFF is forced (default is FALSE). This option is used only in the case a GTiff format was chosen.
vrt_rel_paths	(optional) Logical: if TRUE (default on Linux), the paths present in the VRT output file are relative to the VRT position; if FALSE (default on Windows), they are absolute. This takes effect only with format = "VRT".
utmzone	(optional) UTM zone of output products (default: the first one retrieved from input granules), being a 3-length character (e.g. "32N"). Note that this function does not perform reprojections: if no granules refer to the specified UTM zone, no output is created.
overwrite	Logical value: should existing output files be overwritten? (default: FALSE)

**Value**

A vector with the names of the created output files (just created or already existing).

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

**Examples**

```
## Not run:
s2_l1c_example <- file.path(
  "/existing/path",
  "S2A_MSIL1C_20170603T101031_N0205_R022_T32TQQ_20170603T101026.SAFE")
s2_l1c_example <- file.path(
  "/existing/path",
  "S2A_MSIL2A_20170603T101031_N0205_R022_T32TQQ_20170603T101026.SAFE")

# Create a single TOA GeoTIFF in the same directory
s2_translate(s2_l1c_example, format="GTiff")

# Create a single BOA VRT with a custom name
s2_translate(
  s2_l2a_example,
```

```

    "/new/path/example_sentinel2_sr.vrt",
    vrt_rel_paths = TRUE
  )

# Create three products (ENVI) in the same directory at 60m resolution
s2_translate(
  s2_example,
  format = "ENVI",
  prod_type = c("BOA", "TCI", "SCL"),
  res = "60m",
  subdirs = TRUE
)

## End(Not run)

```

---

safelist-class

*Format for SAFE archive lists*


---

## Description

safelist is a format thought to manage lists of SAFE Sentinel.2 archives. It is a named character in which names are SAFE codes (e.g. S2A\_MSIL2A\_20170507T102031\_N0205\_R065\_T32TNR\_20170507T102319.SAFE), and values are URLs used to retrieve them from ESA API Hub (e.g. [https://scihub.copernicus.eu/apihub/odata/v1/Products\('a4db7b-4ba8-9b09-53027ab0d7ab'\)/\\$value](https://scihub.copernicus.eu/apihub/odata/v1/Products('a4db7b-4ba8-9b09-53027ab0d7ab')/$value)). Some attributes may be included, basically information retrieved by function `s2_list` containing product metadata. Moreover, the attribute `online` (retrieved by function `safe_is_online`) may contain logical values (TRUE for products available for download, FALSE for products stored in the Long Term Archive).

The class can be generated as an output of function `s2_list`, or converting named characters (with the same structures), data.frames or data.tables (including the columns name and url) using `as` (see examples). Objects of class `safelist` can be converted to named character, data.frames or data.tables (see examples). The conversion to data.frame / data.table is useful for reading hidden attributes.

## Note

License: GPL 3.0

## Author(s)

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

## References

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

## Examples

```
pos <- sf::st_sfc(sf::st_point(c(9.85,45.81)), crs = 4326)
time_window <- as.Date(c("2017-05-01", "2017-05-31"))

## Create an object of class safelist
list_safe <- s2_list(spatial_extent = pos, time_interval = time_window)
list_safe
class(list_safe)
attr(list_safe, "sensing_datetime") # extract an hidden attribute from a safelist

## Convert to other classes
(s2_char <- as.character(list_safe)) # convert to a simple named character
(s2_df <- as.data.frame(list_safe)) # convert to a data.frame
library(data.table)
(s2_dt <- as.data.table(list_safe)) # convert to a data.table
library(sf)
(s2_sf <- st_as_sf(list_safe)) # convert to sf

## Convert from other classes
as(s2_char, "safelist") # this causes the loss of hidden attributes
as(s2_df, "safelist") # this (and followings) maintain attributes as columns
as(s2_dt, "safelist")
as(s2_sf, "safelist")
```

---

safe\_getMetadata

*Get information from S2 file name or metadata*

---

## Description

The function `safe_getMetadata()` scans a Sentinel2 product (main path or granule xml file) to retrieve information about the product.

The accessory function `rm_invalid_safe()` remove a SAFE archive in the case it is not recognised by `safe_getMetadata()`.

The accessory function `safe_isvalid()` scan the SAFE name to understand if it is a valid SAFE.

## Usage

```
safe_getMetadata(
  s2,
  info = "all",
  format = "default",
  simplify = TRUE,
  abort = TRUE,
  allow_oldnames = FALSE
)
```

```

rm_invalid_safe(s2, req_res = c("10m", "20m", "60m"), allow_oldnames = FALSE)

safe_isvalid(
  s2,
  allow_oldnames = FALSE,
  check_file = TRUE,
  req_res = c("10m", "20m", "60m")
)

```

## Arguments

- s2** Sentinel-2 products, which can be:
- a list of products in the format safelist (see [safelist](#));
  - a vector of SAFE paths;
  - a vector of paths of xml product files with metadata. If the product does not exist locally, the function can run only with option info = "nameinfo" (see below).
- info** (optional) A character vector with the list of the metadata which should be provided. Accepted values are:
- "all" (default): all the retrievable metadata are provided;
  - "fileinfo": only the metadata obtained by scanning the file name and product structure (without opening it with GDAL) are provided.
  - "nameinfo": only the metadata obtained by scanning the file name are provided (it is faster and there is no need to have downloaded yet the file).
  - a vector of single specific information (one or more from the followings):
    - "name" (SAFE name - this is always returned);
    - "validname" (TRUE or FALSE);
    - "exists" (TRUE or FALSE);
    - "prod\_type" ('singlegranule' or 'product');
    - "version" ('old' or 'compact');
    - "tiles" (vector with the tiles ID available in the product);
    - "utm" (vector with the UTM zones used in the product);
    - "xml\_main" (name of the main XML file with metadata);
    - "xml\_granules" (names of the XML with granule metadata);
    - "level" ('1C' or '2A');
    - "creation\_datetime", "id\_tile", "mission", "centre", "file\_class", "id\_orbit", "orbit\_number", "sensing\_datetime", "id\_baseline": metadata specific of the product type and version (they are returned only if obtainable for the specified input);
    - "clouds", "direction", "orbit\_n", "preview\_url", "proc\_baseline", "level", "sensing\_datetime", "nodata\_value", "saturated\_value": information retrieved from the metadata stored in the XML file;
    - "res": resolutions with all the output products available;
    - "jp2list" (data.frame with the list of the JP2 band files - asking for this info will cause format to be coerced to "list").

Notice that the required info are returned only if available; i.e., if some info requiring existing files are asked by the user, but input SAFE do not exist, only info retrievable by the SAFE name are returned.

format	Output format, being one of the followings: <ul style="list-style-type: none"> <li>• "data.table" and "data.frame": a table with one row per s2 input and one column per required info;</li> <li>• "list": a list (one element per s2 input) in which each element is a list of the required info;</li> <li>• "vector": a list (one element per info) in which each element is a named vector (with s2 length and names) with the required info;</li> <li>• "default" (default): "vector" if info is of length 1; "data.table" otherwise.</li> </ul>
simplify	Logical parameter, which applies in case s2 is of length 1: in this case, if TRUE (default) and format is "list" or "vector", a single info list or vector is returned; if FALSE, a list of length 1 (containing the list or vector of the required s2 product) is returned.
abort	Logical parameter: if TRUE (default), the function aborts in case some inputs are not recognised, or if some files do not exist (in case some info elements require the files to be present); if FALSE, a warning is shown.
allow_oldnames	Logical parameter: if TRUE, old (long) name products are managed (metadata are returned, and they are considered valid; if FALSE (default), they are considered as non-supported files. Note that, from sen2r version 1.1.0, oldname products are no more supported within processing chains, so this function is deprecated and no more supported; moreover, it will be removed in next releases.
req_res	Character: vector of variable length (0 to 3) containing the names of the spatial resolution to be checked (one or more among "10m", "20m" and "60m"). In case of level 2A-products, the existence of the JP2 files with the required resolutions necessary for sen2r processing chains (spectral bands and SCL) is checked, determining the result of the check. Default is c("10m", "20m", "60m"), since Sen2Cor by default produces all of these resolutions. NULL can be used not to scan for JP2 content. In case of level-1C products, in which each layer band is available in a specific resolution, any of the previous values causes all JP2 layers to be checked, while NULL causes no scan to be performed (as in the case of L2A). In safe_isvalid(), this argument is ignored if check_file = FALSE.
check_file	Logical: if TRUE (default), the content of the provided paths is checked; if FALSE, only the validity of SAFE names is tested.

## Value

safe\_getMetadata() returns a data.table, a data.frame or a list (depending on argument format) with the output metadata;

rm\_invalid\_safe() returns a named vector (with the length of s2) with TRUE if the s2 product was removed, FALSE elsewhere.

safe\_isvalid() returns a named vector (with the length of s2) with TRUE if the product is a valid SAFE, FALSE if not.



**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

**Examples**

```
# Define product name
s2_exemplenames <- c(
  "S2A_MSIL1C_20190723T101031_N0208_R022_T32TNS_20190723T121220.SAFE",
  "S2A_MSIL1C_20190723T101031_N0208_R022_T32TNR_20190723T121220.SAFE"
)

# Return the information retrievable from the file names (files are not scanned)
safe_getMetadata(s2_exemplenames, info="nameinfo")

# Return some specific information without scanning files
safe_getMetadata(s2_exemplenames, info=c("level", "id_tile"))

# Return a single information without scanning files
# (in this case, the default output is a vector instead than a data.table)
safe_getMetadata(s2_exemplenames, info="level")

# Check if the products are valid existing SAFE archives
safe_isvalid(s2_exemplenames)

# Check if the product names are valid SAFE names
safe_isvalid(s2_exemplenames, check_file = FALSE)
safe_isvalid("invalid_safe_name.SAFE", check_file = FALSE)

## Not run:
# Download a sample SAFE archive (this can take a while)
s2_exampleurl <- c(
  "S2A_MSIL1C_20190723T101031_N0208_R022_T32TNS_20190723T121220.SAFE" =
  paste0("https://scihub.copernicus.eu/apihub/odata/v1/",
    "Products('19bbde60-992b-423d-8dea-a5e0ac7715fc')/$value")
)
s2_download(s2_exampleurl, outdir=tempdir())
s2_examplepath <- file.path(tempdir(), names(s2_exampleurl))

# Return all the available information
safe_getMetadata(s2_examplepath)

# Return some specific information
```

```

safe_getMetadata(s2_examplepath, info=c("clouds", "direction"))

# Return a single information
safe_getMetadata(s2_examplepath, info="nodata_value")

# Check if the downloaded SAFE is valid
safe_isvalid(s2_examplepath)

# Delete it if it is not recognised
rm_invalid_safe(s2_examplepath)

## End(Not run)

```

---

safe_is_online	<i>Check if SAFE is available for download</i>
----------------	--

---

## Description

The function checks if the required SAFE archives are available for download, or if they have to be ordered from the Long Term Archive.

## Usage

```
safe_is_online(s2_prodlis = NULL, apihub = NA, verbose = TRUE)
```

## Arguments

s2_prodlis	Named character: list of the products to be checked, in the format safelist (see <a href="#">safelist</a> ). Alternatively, it can be the path of a JSON file exported by <a href="#">s2_order</a> .
apihub	Path of the "apihub.txt" file containing credentials of SciHub account. If NA (default), the default location inside the package will be used.
verbose	Logical: if TRUE, provide processing messages summarising how many of the SAFE archives in s2_prodlis are available online.

## Value

A logical vector of the same length and names of the SAFE products passed with s2\_prodlis, in which each element is TRUE if the corresponding SAFE archive is available for download, FALSE if it is not or NA in case of errors with the SAFE url.

## Note

License: GPL 3.0

## Author(s)

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>  
 Lorenzo Busetto, PhD (2020)

## References

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

## Examples

```
# Generate the lists of products
pos <- sf::st_sfc(sf::st_point(c(-57.8815,-51.6954)), crs = 4326)
time_window <- as.Date(c("2018-02-21", "2018-03-20"))
list_safe <- s2_list(spatial_extent = pos, time_interval = time_window)
# (at the time the documentation was written, this list was containing 5
# archives already available online and 2 stored in the Long Term Archive)

# Check for availability
safe_is_online(list_safe)
```

---

safe_shortname	<i>Rename products using a shorten convention</i>
----------------	---

---

## Description

This function renames a Sentinel-2 product in order to obtain shorten names. See the details for the structure of the adopted schema (named "sen2r naming convention"). The function applies only to compact product names (not to single granule names), since it is thought to be applied to entire products. Old long names are no more supported.

## Usage

```
safe_shortname(  
  prod_name,  
  prod_type = NULL,  
  ext = NULL,  
  res = "10m",  
  tiles = NULL,  
  force_tiles = NULL,  
  full.name = TRUE,  
  allow_duplicated = FALSE,  
  set.seed = NULL,  
  multiple_names = NULL,  
  abort = FALSE  
)
```

## Arguments

prod_name	Input Sentinel-2 product name (it is not required that the file exists).
prod_type	(optional) Output product (default: TOA for L1C, BOA for L2A); see the details for the list of accepted products.
ext	(optional) Extension of the output filename (default: none).
res	(optional) Spatial resolution (one between '10m', '20m' or '60m'); default is '10m'. Notice that, choosing '10m' or '20m', bands with lower resolution will be rescaled to res. Band 08 is used with res = '10m', band 08A with res = '20m' and res = '60m'.
tiles	Deprecated (no more used).
force_tiles	Deprecated (no more used).
full.name	Logical value: if TRUE (default), all the input path is maintained (if existing); if FALSE, only basename is returned.
allow_duplicated	Logical value: if TRUE, duplicated values are maintained; if FALSE (default), in case of duplicated value a suffix is added to the tile ID (see <code>add_tile_suffix()</code> ).
set.seed	Deprecated (no more used).
multiple_names	Deprecated (no more used).
abort	Logical parameter: if TRUE, the function aborts in case prod_type is not recognised; if FALSE (default), a warning is shown.

## Details

**ESA Sentinel-2 naming convention** is particularly long-winded. So, the convention here adopted, named "sen2r naming convention", follows this schema:

S2m11\_yyyymmdd\_rrr\_ttttt\_ppp\_rr.fff

where:

- S2m11 (length: 5) shows the mission ID (S2A or S2B) and the product level (1C or 2A);
- yyyymmdd (length: 8) is the sensing date (e.g. 20170603 for 2017-06-03); the hour is skipped, since a single sensor can not pass two times in a day on the same tile);
- rrr (length: 3) is the relative orbit number (e.g. 022);
- ttttt (length: 5) is the tile number (e.g. 32TQQ);
- ppp (length: 3) is the output product, being one of these: *for level 1C*:
  - TOA: 13-bands Top-Of-Atmosphere Reflectance; *for level 2A*:
  - BOA: 13-bands Bottom-Of-Atmosphere Reflectance;
  - TCI: True Colour Image (3-band RGB 8-bit image);
  - AOT: Aerosol Optical Thickness;
  - WVP: Water Vapour;
  - SCL: Scene Classification Map;
  - CLD: Quality Indicators for cloud probabilities;
  - SNW: Quality Indicators for snow probabilities;
  - VIS: TODO Visibility (used for AOT);
- rr (length: 2) is the original minimum spatial resolution in metres (10, 20 or 60);
- fff (length: variable, generally 3) is the file extension.

**Value**

Output product name

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

**Examples**

```
safe_shortname("S2A_MSIL1C_20170603T101031_N0205_R022_T32TQQ_20170603T101026.SAFE", ext="tif")
```

---

sen2cor

*Correct L1C products using Sen2Cor*

---

**Description**

The function uses Sen2Cor to manually correct L1C products. Standalone version of **sen2cor** (version 2.8.0 or 2.5.5) is used.

**Usage**

```
sen2cor(  
  l1c_proclist = NULL,  
  l1c_dir = NULL,  
  outdir = NULL,  
  proc_dir = NA,  
  tmpdir = NA,  
  rmtmp = TRUE,  
  gipp = NULL,  
  use_dem = NA,  
  tiles = NULL,  
  parallel = FALSE,  
  timeout = 0,  
  kill_errored = FALSE,  
  overwrite = FALSE,  
  .log_message = NA,  
  .log_output = NA  
)
```

## Arguments

l1c_prodlst	List of L1C product names to be corrected. They can be both product names with full/relative path or only names of SAFE products (in this case, also l1c_dir argument must be provided). SAFE products must be unzipped. Note that, at this stage, all products must be in the same directory (this will be fixed).
l1c_dir	Full or relative path of input L1C products. If NULL (default), l1c_prodlst must already be a vector of full paths.
outdir	Directory where output L2A products will be placed. If NULL (default), each product is left in the parent directory of l1c_prodlst.
proc_dir	(optional) Directory where processing is applied. If NA (default), processing is done in l1c_dir and output L2A product is then moved to outdir, unless l1c_dir is a subdirectory of a SAMBA mountpoint under Linux: in this case, L1C input products are copied in a temporary directory (specified with argument tmpdir), processing is done there and then L2A is moved to outdir. This is required under Linux systems when l1c_dir is a subdirectory of a unit mounted with SAMBA, otherwise Sen2Cor would produce empty L2A products.
tmpdir	(optional) Path where processing is performed if a temporary working directory is required (see argument proc_dir). Be sure tmpdir not to be a SAMBA mountpoint under Linux. Default is a temporary directory. If tmpdir is a non-empty folder, a random subdirectory will be used.
rmtmp	(optional) Logical: should temporary files be removed? (Default: TRUE)
gipp	(optional) Ground Image Processing Parameters (GIPP) to be passed to Sen2Cor. It is possible to specify both the path of an existing XML file or a list of parameters in the form parameter_name = "value", where parameter_name is the name of the parameter as specified in the XML file (case insensitive), and "value" is the character value which the user wants to set (notice that, in the case the user wants to specify the value NONE, both "NONE" and NA can be used, but not NULL, which has the effect to maintain the value specified in the XML file).  For details about the GIPP parameters, refer to the Sen2Cor documentation (v. 2.5.5 or 2.8.0: see the "Schemas of the GIPP file" at the end of each page). <i>Note</i> : this argument takes effect only in the current execution of sen2cor() function.
use_dem	(optional) Logical: if TRUE, Sen2Cor is set to use a Digital Elevation Model for topographic correction (reflecting what is done for Level-2A SAFE images provided by ESA Hub); if FALSE, it is set not to perform topographic correction (reflecting the current default Sen2Cor behaviour); if NA (default), the option set in the XML GIPP configuration file used by sen2r (stored in the default sen2r settings directory) is respected; in case the user never edited it, the current default setting is not to perform topographic correction.

### Notes:

1. if TRUE, the path used to read or store DEM files and the online source used to download missing DEM tiles are respectively the DEM\_Directory and DEM\_Reference parameters set in the default sen2r GIPP XML file (the user can read them with the function read\_gipp(c("DEM\_Directory", "DEM\_Reference"))). In case one or both these parameters were set to "NONE", a subdirectory

"srtm90" of the default sen2r directory is used as DEM directory, and/or the **CGIAR SRTM 90m** is set as online source. To set another directory or reference, use argument `gipp` in the form `gipp = list(DEM_Directory = tempdir(), DEM_Reference = "another_reference", ...)` (replacing `tempdir()` with the desired path and specifying the online resource).

2. Currently the default value is NA in order to grant backward compatibility. In a future release of sen2r, the default value will be set to TRUE, so to grant homogeneity between Level-2A products downloaded from ESA Hub and generated using Sen2Cor.

<code>tiles</code>	Vector of Sentinel-2 Tile strings (5-length character) to be processed (default: process all the tiles found in the input L1C products).
<code>parallel</code>	(optional) Logical: if TRUE, Sen2Cor instances are launched in parallel using multiple cores; if FALSE (default), they are launched in series on a single core. The number of cores is automatically determined; specifying it is also possible (e.g. <code>parallel = 4</code> ).
<code>timeout</code>	Integer value: number of minutes after which killing Sen2Cor if it is still running (default, 0, means that this is never done). This can be useful in case Sen2Cor produced an error without exiting from Python (leaving a standing process running).
<code>kill_errored</code>	Logical: experimental feature allowing killing dead Sen2Cor processes, so leaving <code>sen2cor()</code> continuing processing on the remaining products. Set to TRUE to activate it (default is FALSE). This experimental feature is available only on Unix systems, and requires package "tools" to be installed. This option is not compatible with <code>timeout</code> (in case both are set, <code>kill_errored</code> will be ignored).
<code>overwrite</code>	Logical value: should existing output L2A products be overwritten? (default: FALSE)
<code>.log_message</code>	(optional) Internal parameter (it is used when the function is called by <code>sen2r()</code> ).
<code>.log_output</code>	(optional) Internal parameter (it is used when the function is called by <code>sen2r()</code> ).

### Value

Vector character with the list of the output products (being corrected or already existing).

### Note

License: GPL 3.0

### Author(s)

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

### References

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

## Examples

```
## Not run:
# Download an L1C SAFE product
example_s2_list <- s2_list(
  spatial_extent = st_sfc(st_point(c(12.0, 44.8)), crs=st_crs(4326)),
  tile = "32TQQ",
  time_interval = as.Date(c("2017-05-01", "2017-07-30"))
)
s2_download(example_s2_list, outdir = tempdir())

# Correct it applying a topographic correction
sen2cor(
  names(example_s2_list)[1],
  l1c_dir = tempdir(),
  outdir = tempdir(),
  use_dem = TRUE
)

## End(Not run)
```

---

 sen2r

---

*Find, download and preprocess Sentinel-2 images*


---

## Description

The function is a wrapper to perform the entire processing chain to find, download and pre-process Sentinel-2 data. Input is a set of parameters that can be passed with a list or file (parameter `param_list`) or singularly (see the descriptions of all the other parameters).

## Usage

```
sen2r(
  param_list = NULL,
  gui = NA,
  preprocess = TRUE,
  s2_levels = "l2a",
  sel_sensor = c("s2a", "s2b"),
  online = TRUE,
  order_lta = TRUE,
  apihub = NA,
  downloader = "builtin",
  overwrite_safe = FALSE,
  rm_safe = "no",
  step_atmcorr = "auto",
  sen2cor_use_dem = NA,
  sen2cor_gipp = NA,
  max_cloud_safe = 100,
  timewindow = NA,
```



```
timeperiod = "full",
extent = NA,
extent_name = "sen2r",
s2tiles_selected = NA,
s2orbits_selected = NA,
list_prods = NA,
list_rgb = NA,
list_indices = NA,
index_source = "BOA",
rgb_ranges = NA,
mask_type = NA,
max_mask = 100,
mask_smooth = 0,
mask_buffer = 0,
clip_on_extent = TRUE,
extent_as_mask = FALSE,
reference_path = NA,
res = NA,
res_s2 = "10m",
unit = "Meter",
proj = NA,
resampling = "near",
resampling_scl = "near",
outformat = "GTiff",
rgb_outformat = "GTiff",
index_datatype = "Int16",
compression = "DEFLATE",
rgb_compression = "90",
overwrite = FALSE,
path_l1c = NA,
path_l2a = NA,
path_tiles = NA,
path_merged = NA,
path_out = NA,
path_rgb = NA,
path_indices = NA,
path_subdirs = TRUE,
thumbnails = TRUE,
parallel = FALSE,
processing_order = "by_groups",
use_python = NA,
tmpdir = NA,
rmtmp = TRUE,
log = NA
)
```

## Arguments

param_list	(optional) List of input parameters: it can be both an R list or the path of a JSON file. If some parameters are passed both as elements of param_list and as function arguments, the values passed as function arguments are considered. If some parameters are missing in param_list and are not provided as arguments, default values will be used. Use the function s2_gui() to create a complete list of parameters. If param_list is NULL (default), values given with the parameters below (or default values for parameters not provided) are used.
gui	(optional) Logical: if TRUE, function s2_gui() is launched before starting to process in order to set or load parameters; if FALSE, the function uses parameters passed with param_list or with other function arguments. Default is FALSE if param_list is not NULL, TRUE elsewhere.
preprocess	(optional) Logical: TRUE (default) to perform also preprocessing steps, FALSE not to (do only find, download and atmospheric correction).
s2_levels	(optional) Character vector of length 1 or 2, with Sentinel-2 levels required for processing steps or as output. This parameter is used only if preprocess = FALSE (otherwise, the required levels are derived from list_prods). Accepted values: "11c" and "12a"; default: "12a".
sel_sensor	(optional) Character vector of length 1 or 2, with Sentinel-2 sensors to be used. Accepted values: "s2a" and "s2b"; default: c("s2a","s2b").
online	(optional) Logical: TRUE (default) to search for available products on SciHub (and download if needed); FALSE to work only with already downloaded SAFE products.
order_lta	(optional) Logical: TRUE (default) to order products from the Long Term Archive if unavailable for direct download; FALSE to simply skip them (this option has effect only in online mode).
apihub	Path of the text file containing credentials of SciHub account. If NA (default), the default location inside the package will be used.
downloader	(optional) Character value corresponding to the executable which should be used to download SAFE products. It could be one among "builtin" (default) and "aria2". If aria2 is not installed, built-in method will be used instead.
overwrite_safe	(optional) Logical: TRUE to overwrite existing products with products found online or manually corrected, FALSE (default) to skip download and atmospheric correction for products already existing.
rm_safe	(optional) Character: should SAFE products be deleted after preprocessing? "yes" (or "all") means to delete all SAFE; "no" (default) not to delete; "11c" to delete only Level-1C products.
step_atmcorr	(optional) Character vector to determine how to obtain Level-2A SAFE products: <ul style="list-style-type: none"> <li>• "auto" (default) means that L2A is first searched on SciHub: if found, it is downloaded, if not, the corresponding Level-1C is downloaded and sen2cor is used to produce L2A;</li> <li>• "scihub" means that Sen2Cor is always used from L1C products downloaded from SciHub;</li> </ul>

- "12a" means that they are downloaded if available on SciHub, otherwise they are skipped (sen2cor is never used).

sen2cor_use_dem	(optional) Logical, determining if a DEM should be used for topographic correction by Sen2Cor (see the documentation of <a href="#">sen2cor()</a> - argument use_dem for further details). Currently the default value is NA in order to grant backward compatibility: in this case, the option set in the XML GIPP configuration file used by sen2r (stored in the default sen2r settings directory) is respected. <i>Note:</i> in a future release of sen2r, the default value will be set to TRUE, so to grant homogeneity between Level-2A products downloaded from ESA Hub and generated using Sen2Cor.
sen2cor_gipp	(optional) Ground Image Processing Parameters (GIPP) to be passed to Sen2Cor (see the documentation of <a href="#">sen2cor()</a> - argument gipp - for details about the usage of this argument). Default value (NA) corresponds to an empty list of parameters.
max_cloud_safe	(optional) Integer number (0-100) containing the maximum cloud level of each SAFE to be considered (default: no filter). It is used to limit the research of SAFE products to "good" images, so it is applied only to non-existing archives (existing SAFE are always used). In this sense, this parameter is different from max_mask, which can be used to set a maximum cloud coverage over output extents. Notice also that this value is used to filter on the basis of the metadata "Cloud cover percentage" associated to each SAFE, so it is not based on the cloud mask defined with the processing options.
timewindow	(optional) Temporal window for querying: Date object of length 1 (single day) or 2 (time window). Default is NA, meaning that no filters are used if online = FALSE, and all found images are processed; if online = TRUE, last 90 days are processed. Is it possible to pass also integer (or difftime) values, which are interpreted as the last n days.
timeperiod	(optional) Character: <ul style="list-style-type: none"> <li>• "full" (default) means that all the images included in the time window are considered;</li> <li>• "seasonal" means that only the single seasonal periods in the window are used (i.e., with a time window from 2015-06-01 to 2017-08-31, the periods 2015-06-01 to 2015-08-31, 2016-06-01 to 2016-08-31 and 2017-06-01 to 2017-08-31 are considered).</li> </ul>
extent	(optional) Spatial extent on which to clip products (it can be both the path of a vector file or a geoJSON). Default is NA for offline mode (meaning no extent: all found tiles are entirely used); in online mode, a sample extent is used as default.
extent_name	(optional) Name of the area set as extent, to be used in the output file names. Default is "sen2r". The name is an alphanumeric string which cannot contain points nor underscores, and that cannot be a five-length string with the same structure of a tile ID (two numeric and three uppercase character values).
s2tiles_selected	(optional) Character vector with the Sentinel-2 tiles to be considered (default is NA, meaning all the tiles).

s2orbits_selected	(optional) Character vector with the Sentinel-2 orbits to be considered (still to be implemented; for now, all the accepted values are listed).
list_prods	(optional) Character vector with the values of the products to be processed (accepted values: "TOA", "BOA", "SCL", "TCI"). Default is no one (NA).
list_rgb	(optional) Character vector with the values of the RGB images to be produced. Images are in the form RGBrgbx, where: <ul style="list-style-type: none"> <li>• x is B (if source is BOA) or T (if source is TOA);</li> <li>• r g and b are the the number of the bands to be used respectively for red, green and blue, in hexadecimal format. Notice that this is the <b>actual number name of the bands</b>: so, to use i.e. BOA band 11 (1610nm) use the value "b", even if band 11 is the 10th band of a BOA product (because band 10 is missing). (e.g., RGB432B, RGB843B) Default is no one (NA).</li> </ul>
list_indices	(optional) Character vector with the values of the spectral indices to be computed. Default is no one (NA).
index_source	(optional) Character value: if "BOA" (default), indices are computed from BOA values; if "TOA", non corrected reflectances are instead used (be careful to use this setting!).
rgb_ranges	(optional) Range of valid values to be used for RGB products. Values must be provided in the same scale used within SAFE and BOA/TOA products (0-10000, corresponding to reflectances * 10000). It can be a 2-length integer vector (min-max for all the 3 bands) or a 6-length vector or 3x2 matrix (min red, min green, min blue, max red, max green, max blue). Default is to use c(0,2500) for bands 2, 3 and 4; c(0,7500) for other bands. In case list_rgb is a vector of length > 1, rgb_ranges must be a list of the same length (otherwise, the same range values will be used for all the RGB products).
mask_type	(optional) Character value which determines the categories in the Surface Classification Map to be masked (see s2_mask() for the accepted values). Default (NA) is not to mask.
max_mask	(optional) Numeric value (range 0 to 100), which represents the maximum percentage of allowed masked surface (by clouds or any other type of mask chosen with argument mask_type) for producing outputs. Images with a percentage of masked surface greater than max_mask% are not processed (the list of expected output files which have not been generated is returned as an attribute, named "skipped"). Default value is 100 (all products are produced). This parameter is different from max_cloud_safe, because: <ol style="list-style-type: none"> <li>1. it is computed over the selected extent;</li> <li>2. it is computed starting from the cloud mask defined as above. Notice that the percentage is computed on non-NA values (if input images had previously been clipped and masked using a polygon, the percentage is computed on the surface included in the masking polygons).</li> </ol>
mask_smooth	(optional) Numeric positive value: the smoothing radius (expressed in unit of measure of the output projection, typically metres) to be applied to the cloud mask by function s2_mask().

mask_buffer	(optional) Numeric value: the buffering radius (expressed in unit of measure of the output projection, typically metres) to be applied to the cloud mask by function <code>s2_mask()</code> . Default value (0) means that no buffer is applied; a positive value causes an enlargement of the masked area; a negative value cause a reduction.
clip_on_extent	(optional) Logical: if TRUE (default), output products and indices are clipped to the selected extent (and resampled/reprojected); if FALSE, the geometry and extension of the tiles is maintained.
extent_as_mask	(optional) Logical: if TRUE, pixel values outside the extent polygon are set to NA; if FALSE (default), all the values within the bounding box are maintained.
reference_path	(optional) Path of the raster file to be used as a reference grid. If NA (default), no reference is used.
res	(optional) Numeric vector of length 2 with the x-y resolution for output products. Default (NA) means that the resolution is kept as native.
res_s2	(optional) Character value corresponding to the native Sentinel-2 resolution to be used. Accepted values are "10m" (default), "20m" and "60m".
unit	(optional) Character value corresponding to the unit of measure with which to interpret the resolution (for now, only "Meter" - the default value - is supported).
proj	(optional) Character string with the proj4string of the output resolution. default value (NA) means not to reproject.
resampling	(optional) Resampling method (one of the values supported by <code>gdal_translate</code> : "near" (default), "bilinear", "cubic", "cubicspline", "lanczos", "average" or "mode").
resampling_scl	(optional) Resampling method for categorical products (for now, only SCL): one among "near" (default) and "mode".
outformat	(optional) Format of the output file (in a format recognised by GDAL). Default is "GTiff". Value "BigTIFF" can be used to generate a GeoTIFF with the option BigTIFF
rgb_outformat	(optional) Format of the output RGB products (in a format recognised by GDAL). Default is "GTiff".
index_datatype	(optional) Numeric datatype of the output spectral indices (see <code>s2_calcindices()</code> ).
compression	(optional) In the case GTiff is chosen as output format, the compression indicated with this parameter is used (default is "DEFLATE").
rgb_compression	(optional) In the case GTiff is chosen as output format for RGB products, the compression indicated with this parameter is used (default is "DEFLATE"). In the cases GTiff or JPEG are chosen as output format for RGB products, this parameter can also be a 1-100 integer value, which is interpreted as the compression level for a JPEG compression.
overwrite	(optional) Logical value: should existing output files be overwritten? (default: FALSE).
path_11c	(optional) Path of the directory in which Level-1C SAFE products are searched and/or downloaded. If not provided (default), a temporary directory is used.

path_12a	(optional) Path of the directory in which Level-2A SAFE products are searched, downloaded and/or generated. If not provided (default), a temporary directory is used.
path_tiles	(optional) Path of the directory in which Sentinel-2 tiles (as generated by <code>s2_translate()</code> ) are searched and/or generated. If not provided (default), a temporary directory is used, and files are generated as virtual rasters; otherwise, they are generated in the format specified with <code>outformat</code> parameter.
path_merged	(optional) Path of the directory in which Sentinel-2 tiles merged by orbit (as generated by <code>s2_merge()</code> ) are searched and/or generated. If not provided (default), a temporary directory is used, and files are generated as virtual rasters; otherwise, they are generated in the format specified with <code>outformat</code> parameter.
path_out	(optional) Path of the directory in which Sentinel-2 output products are searched and/or generated. If not provided (default), a temporary directory is used.
path_rgb	(optional) Path of the directory in RGB products are searched and/or generated. If not provided (default), <code>path_out</code> is used.
path_indices	(optional) Path of the directory in which files of spectral indices are searched and/or generated. If not provided (default), <code>path_out</code> is used.
path_subdirs	(optional) Logical: if TRUE (default), a directory for each output product or spectral index is generated within <code>path_tiles</code> , <code>path_merged</code> , <code>path_out</code> and <code>path_indices</code> ; if FALSE, products are put directly within them.
thumbnails	(optional) Logical: if TRUE (default), a thumbnail is added for each product created. Thumbnails are JPEG or PNG georeferenced small images (width or height of 1024 pixels) with default colour palettes (for more details, see the help window in the GUI). They are placed in a subdirectory of the products names "thumbnails". If FALSE, they are not created.
parallel	(optional) Logical or integer: setting to TRUE, the processing is executed using multiple cores in order to speed up the execution. Parallelisation is performed on groups of dates. The number of cores is automatically determined; specifying it is also possible (e.g. <code>parallel = 4</code> ). If FALSE (default), the processing chain is forced to run with a single core (this can be useful if multiple <code>sen2r()</code> instances are run in parallel).
processing_order	(optional) Character string: order used to execute the processing chain (this affects the speed of computation and the usage of system resources). Values can be one of the followings: <ul style="list-style-type: none"> <li>• "4" or "by_groups" (default): it provides a good compromise between processing speed and disk usage. Processing is done as follows: <ol style="list-style-type: none"> <li>1. the list of required SAFE and output product names is computed;</li> <li>2. the required dates are grouped in <math>g</math> groups, where <math>g</math> is the number of dates divided by the number of CPU;</li> <li>3. groups are then processed sequentially; for each group: <ul style="list-style-type: none"> <li>– the required SAFE archives are downloaded;</li> <li>– Sen2Cor is applied in parallel using one core per L1C SAFE archive;</li> <li>– the remaining processing operations are executed using parallel R sessions (one core for each date).</li> </ul> </li> </ol> </li> </ul>

- "2" or "by\_date": this allows minimising the requirements of disk usage (in particular if SAFE archives are deleted after processing). It is similar to the default execution, but each group is composed by a single date: so the disk space occupied by SAFE archives and temporary files is lower, but it is generally slower than the default one because parallel computation over dates for products' generation is not possible.
- "3" or "mixed": this allows maximising CPU usage and processing speed. The cycle on groups is ignored, and all the required SAFE are first of all downloaded and/or produced, and then dates are processed in parallel. This mode is faster than the default mode, but it requires all SAFE archives to be downloaded and processed before performing subsequent steps, thus increasing disk space requirements.
- "1" or "by\_step": this is the legacy mode, in which the cycle on groups is ignored as well as the parallel computation over dates. All SAFE archives are first downloaded/processed, then the processing steps are performed sequentially. This mode is similar to the previous one in terms of disk usage but it is slightly slower; its advantage are the lower RAM requirements.

use_python	Deprecated argument
tmpdir	(optional) Path where intermediate files will be created. Default is a temporary directory (unless outformat = "VRT": in this case, default is a subdirectory named ".vrt" within path_out).
rmtmp	(optional) Logical: should temporary files be removed? (Default: TRUE). rmtmp is forced to FALSE if outformat = "VRT".
log	(optional) Character string with the path where the package messages will be redirected. Default (NA) is not to redirect (use standard output). A two-length character with two paths (which can also coincide) can be used to redirect also the output: in this case, the first path is the path for messages, the second one for the output.

### Value

A vector with the paths of the files which were created (excluded the temporary files); NULL otherwise. The vector includes some attributes:

- cloudcovered with the list of images not created due to the higher percentage of cloud covered pixels;
- missing with the list of images not created due to other reasons;
- procpath with the path of a json parameter file, created after each sen2r() run, containing the parameters used in the execution of the function;
- ltapath with the path of a json file containing the list of the SAFE Sentinel-2 archives eventually ordered in Long Term Archive.
- status with a data.frame summarising the status of the processing (see sen2r\_process\_report()).

### Note

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2020) <luigi@ranghetti.info>

Lorenzo Busetto, PhD (2020)

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

**Examples**

```
# Open an interactive section
if (interactive()) {
  sen2r()
}

# Launch a processing from a saved JSON file (here we use an internal function
# to create a testing json file - this is not intended to be used by final users)
json_path <- build_example_param_file()

out_paths_2 <- sen2r(json_path)
# Notice that passing the path of a JSON file results in launching
# a session without opening the gui, unless gui = TRUE is passed.

# Launch a processing using function arguments
safe_dir <- file.path(dirname(attr(load_binpaths(), "path")), "safe")
out_dir_3 <- tempfile(pattern = "Barbellino_")
out_paths_3 <- sen2r(
  gui = FALSE,
  step_atmcorr = "l2a",
  extent = system.file("extdata/vector/barbellino.geojson", package = "sen2r"),
  extent_name = "Barbellino",
  timewindow = as.Date("2020-08-01"),
  list_prods = c("TOA", "BOA", "SCL"),
  list_indices = c("NDVI", "MSAVI2"),
  list_rgb = c("RGB432T", "RGB432B", "RGB843B"),
  mask_type = "cloud_medium_proba",
  max_mask = 80,
  path_l1c = safe_dir,
  path_l2a = safe_dir,
  path_out = out_dir_3
)

# Launch a processing based on a JSON file, but changing some parameters
# (e.g., the same processing on a different extent)
out_dir_4 <- tempfile(pattern = "Scalve_")
out_paths_4 <- sen2r(
  param_list = json_path,
  extent = system.file("extdata/vector/scalve.kml", package = "sen2r"),
```



```

    extent_name = "Scalve",
    path_out = out_dir_4
)

# Show outputs (loading thumbnails)

# Generate thumbnails names
thumb_3 <- file.path(dirname(out_paths_3), "thumbnails", gsub("tif$", "jpg", basename(out_paths_3)))
thumb_3[grep("SCL", thumb_3)] <-
  gsub("jpg$", "png", thumb_3[grep("SCL", thumb_3)])
thumb_4 <- file.path(dirname(out_paths_4), "thumbnails", gsub("tif$", "jpg", basename(out_paths_4)))
thumb_4[grep("SCL", thumb_4)] <-
  gsub("jpg$", "png", thumb_4[grep("SCL", thumb_4)])

oldpar <- par(mfrow = c(1,2), mar = rep(0,4))
image(stars::read_stars(thumb_3[grep("BOA", thumb_3)]), rgb = 1:3, useRaster = TRUE)
image(stars::read_stars(thumb_3[grep("SCL", thumb_3)]), rgb = 1:3, useRaster = TRUE)

par(mfrow = c(1,2), mar = rep(0,4))
image(stars::read_stars(thumb_3[grep("MSAVI2", thumb_3)]), rgb = 1:3, useRaster = TRUE)
image(stars::read_stars(thumb_3[grep("NDVI", thumb_3)]), rgb = 1:3, useRaster = TRUE)

par(mfrow = c(1,2), mar = rep(0,4))
image(stars::read_stars(thumb_3[grep("RGB432B", thumb_3)]), rgb = 1:3, useRaster = TRUE)
image(stars::read_stars(thumb_3[grep("RGB843B", thumb_3)]), rgb = 1:3, useRaster = TRUE)

par(mfrow = c(1,2), mar = rep(0,4))
image(stars::read_stars(thumb_4[grep("BOA", thumb_4)]), rgb = 1:3, useRaster = TRUE)
image(stars::read_stars(thumb_4[grep("SCL", thumb_4)]), rgb = 1:3, useRaster = TRUE)

par(mfrow = c(1,2), mar = rep(0,4))
image(stars::read_stars(thumb_4[grep("MSAVI2", thumb_4)]), rgb = 1:3, useRaster = TRUE)
image(stars::read_stars(thumb_4[grep("NDVI", thumb_4)]), rgb = 1:3, useRaster = TRUE)

par(mfrow = c(1,2), mar = rep(0,4))
image(stars::read_stars(thumb_4[grep("RGB432B", thumb_4)]), rgb = 1:3, useRaster = TRUE)
image(stars::read_stars(thumb_4[grep("RGB843B", thumb_4)]), rgb = 1:3, useRaster = TRUE)

par(oldpar)

```

---

sen2r\_getElements

*Get information from S2 short name*


---

## Description

This accessory function extracts metadata included in the name of a Sentinel-2 product which follows the sen2r naming convention (see [safe\\_shortcode](#)).

**Usage**

```
sen2r_getElements(s2_names, format = "data.table", abort = TRUE)
```

**Arguments**

s2_names	A vector of Sentinel-2 product names in the sen2r naming convention.
format	One between data.table (default), data.frame and list.
abort	Logical parameter: if TRUE (default), the function aborts in case any of s2_names is not recognised; if FALSE, a warning is shown, and a list with only the element "type"='unrecognised' is returned.

**Value**

A data.table, data.frame or list of the output metadata.

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

**Examples**

```
# Define product name
fs2nc_exemplename <-
  "/path/of/the/product/S2A1C_20170603_022_32TQQ_TOA_20.tif"

# Return metadata
sen2r_getElements(fs2nc_exemplename)
```

---

sen2r\_process\_report *Summarise processing report*

---

**Description**

Internal function used to summarise results of sen2r execution at the end of a processing..

**Usage**

```
sen2r_process_report(
  s2_list_ordered,
  s2names = NULL,
  pm = NULL,
  ignorelist = list(),
  s2_list_cloudcovered = NA,
  s2_list_failed = NA,
  download_only = FALSE,
  s2_downloaded = NA,
  s2_skipped = NA,
  s2_corrected = NA
)
```

**Arguments**

s2_list_ordered	List containing the lists of ordered/notordered LTA S2 images.
s2names	Output of <a href="#">compute_s2_paths()</a> .
pm	List containing sen2r processing parameters.
ignorelist	Internal parameter.
s2_list_cloudcovered	Internal parameter.
s2_list_failed	Internal parameter.
download_only	Logical: if TRUE, it indicates that the processing to be summarised only involved download (pm\$preprocess = FALSE).
s2_downloaded	Internal parameter.
s2_skipped	Internal parameter.
s2_corrected	Internal parameter.

**Value**

A data.frame summarising the report, and containing the following columns:

- time: date/time of report creation;
- n\_req\_tot\_dates: number of dates to be processed based on the query;
- n\_ondisk\_dates: number of dates for which all expected products are already on disk;
- n\_proc\_dates: number of date for which some products were computed in the current run;
- n\_complete\_out: number of dates for which processing is "complete", and all products were created;
- n\_failed\_dates: number of dates for which processing is "complete", but some products were not created for unexpected reasons;
- n\_cloudy\_dates: number of dates for which processing is "complete", but some products were not created because cloudiness in the spatial extent was above max\_mask;

- `n_notonline_dates`: number of date for which processing is "incomplete", because not all require images are online;
- `n_ordered_imgs`: number of images correctly ordered from LTA;
- `n_notordered_imgs`: number of images for which LTA order failed;
- `n_downloaded`: number of images downloaded during current run;
- `n_skipped`: number of required images not downloaded because already on disk (note: this does not include images that would be needed to process a date for which all products are already on disk);
- `n_corrected`: number of images atmospherically corrected using `sen2cor`;
- `completed`: logical, indicating if processing can be considered "complete" (it is set to TRUE in case `n_notonline_dates = 0`).

### Note

License: GPL 3.0

### Author(s)

Lorenzo Busetto, PhD (2020)

### References

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

---

smooth\_mask

*Buffer cloud masks*

---

### Description

Internal function (used by `s2_mask`) which smooths and buffers a 0-1 mask image in order to reduce the roughness of the mask obtained from SCL classification (which is done pixel by pixel). See details.

### Usage

```
smooth_mask(  
  inmask,  
  tmpdir = tempdir(),  
  radius = 250,  
  buffer = 250,  
  namask = NULL,  
  bigtiff = FALSE  
)
```

**Arguments**

inmask	The path of the input 0-1 mask (where 0 represents the area to be masked, 1 the clean surface).
tmpdir	(optional) Path where intermediate files (VRT) will be created. Default is a temporary directory.
radius	(optional) Numerical (positive): the size (in the unit of inmask, typically metres) to be used as radius for the smoothing (the higher it is, the more smooth the output mask will result).
buffer	(optional) Numerical (positive or negative): the size of the buffer (in the unit of inmask, typically metres) to be applied to the masked area after smoothing it (positive to enlarge, negative to reduce).
namask	(optional) The path of an input 0-1 mask where 0 represents the area of the original file with NA values (which should not be smoothed / buffered). Default (NULL) means that no NA values are present.
bigtiff	(optional) Logical: if TRUE, the creation of a BigTIFF is forced (default is FALSE).

**Value**

The path of the smoothed mask.

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

---

stack2rgb

*Produce an RGB image from a multiband raster file.*

---

**Description**

Internal function to create JPEG images from a multiband raster file. This function is used by [s2\\_thumbnails](#), and it will be exported when it would be more generalised.

**Usage**

```

stack2rgb(
  in_rast,
  out_file = NULL,
  bands = 1:3,
  minval = 0,
  maxval = 10000,
  format = "JPEG",
  compress = "90",
  bigtiff = FALSE,
  proc_mode = "raster",
  tmpdir = NA
)

```

**Arguments**

<code>in_rast</code>	Input raster (as Raster* or stars object).
<code>out_file</code>	(optional) Path of the output RGB JPEG image; if NULL (default), a RasterBrick will be returned.
<code>bands</code>	(optional) 3-length integer argument, with the position of the three bands to be used respectively for red, green and blue.
<code>minval</code>	(optional) the value corresponding to black (default: 0). Also a 3-length vector is accepted (min values for red, green and blue respectively).
<code>maxval</code>	(optional) the value corresponding to white (default: 10000). Also a 3-length vector is accepted (max values for red, green and blue respectively).
<code>format</code>	(optional) Format of the output file (in a format recognised by GDAL). Default is JPEG.
<code>compress</code>	(optional) In the case a GTiff format is present, the compression indicated with this parameter is used. In the case a JPEG format is present, the compression indicates the quality (integer, 0-100). In the case a GTiff format is present and an integer 0-100 number is provided, this is interpreted as the quality level of a JPEG compression.
<code>bigtiff</code>	(optional) Logical: if TRUE, the creation of a BigTIFF is forced (default is FALSE). This option is used only in the case a GTiff format was chosen.
<code>proc_mode</code>	(optional) Character: if "gdal_calc", gdal_calc routines are used to compute indices; if "raster" (default) or "stars", R functions are instead used (using respectively raster or stars routines). <b>Note:</b> default value ("raster") is the only fully supported mode. "gdal_calc" can be used only if a runtime GDAL environment can be properly configured (no assistance is provided in case of GDAL-related problems). "raster" mode is experimental. See <code>s2_calcindices()</code> for further details.
<code>tmpdir</code>	(optional) Path where intermediate files will be created. Default is a temporary directory. If tmpdir is a non-empty folder, a random subdirectory will be used.

**Value**

The path of the output image; alternatively, the output image as RasterBrick (if `out_rast = NULL`).

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

---

start\_trace

*Trace functions which create files*

---

**Description**

Some functions create output files during their execution; some of them are slow, so the probability that something goes wrong during their execution is not null, with the consequence that output files are incomplete, or that undesired temporary files are left on the filesystem.

This functions is though to manage these situations.

[trace\\_function](#) runs a function and checks if errors occur during its execution; in this case, the files created by it are deleted (only if the timestamp of the files is subsequent to the time of execution of the function). If the code interrupts before the function ends, the paths of the files intended to be created by the function are saved within the package, so that they can be easily deleted in a second time; to do it, simply run [clean\\_traces](#).

Other intermediate functions are used internally: [start\\_trace](#) saves the paths of the files intended to be created within a text file; [end\\_trace](#) deletes this text file (it is used by [trace\\_function](#) when a function stops without errors); [clean\\_trace](#) deletes this text file and the intended output files (it is used by [trace\\_function](#) when a function stops with errors).

**Usage**

```
start_trace(trace_files, trace_funname)
```

```
end_trace(tracename)
```

```
clean_trace(tracename)
```

```
trace_function(trace_fun, trace_files, trace_funname = NA, ...)
```

```
clean_traces(trace_funname = NA)
```

**Arguments**

trace_files	Vector of the files intended to be created by fun (for now, providing it is mandatory). Also temporary files can be indicated here.
trace_funname	The name of the function to be run (in <a href="#">start_trace</a> ) or to be cleaned (in <a href="#">clean_traces</a> ; if NA, all the traces are cleaned).
tracename	The path of the text file containing the log information generated by <a href="#">start_trace</a> .
trace_fun	The function to be run.
...	Arguments of the function fun

**Value**

NULL (the function is called for its side effects)

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

---

str\_pad2

*Pad a string.*

---

**Description**

Vectorised over string, width and pad. This is an internal function doing the same thing of `str_pad()` function in package `stringr` (except for parameters 'width' and 'length' which must be of length 1), but without depending on package `stringi`.

**Usage**

```
str_pad2(string, width, side = c("left", "right", "both"), pad = " ")
```

**Arguments**

string	A character vector.
width	Minimum width of padded strings.
side	Side on which padding character is added (left, right or both).
pad	Single padding character (default is a space).



**Value**

A character vector.

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

**Examples**

```
rbind(
  str_pad2("hadley", 30, "left"),
  str_pad2("hadley", 30, "right"),
  str_pad2("hadley", 30, "both")
)

# All arguments are vectorised except side
str_pad2(c("a", "abc", "abcdef"), 10)

# Longer strings are returned unchanged
str_pad2("hadley", 3)
```

---

st\_as\_text\_2

*Return WKT or WKT2 basing on the installed rgdal version*

---

**Description**

This is a convenience temporary function which returns the WKT representation of a CRS, using `sf::st_as_text()` in case `PROJ < 3`, `rgdal::CRS()` otherwise. This has the advantage to perform precise transformations with `PROJ >= 3`, and to avoid conversion errors (see [here](#)). This function will be deleted whenever `sf` will manage WKT2.

**Usage**

```
st_as_text_2(x, pretty = FALSE)
```

**Arguments**

x	object of class sf, sfc or crs
pretty	logical; if TRUE, print human-readable well-known-text representation of a coordinate reference system

**Value**

Well-known Text representation of simple feature geometry or coordinate reference system

**Author(s)**

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

**Examples**

```
sen2r:::st_as_text_2(sf::st_crs(32632))
```

---

st_crs2	<i>Retrieve coordinate reference system from sf or sfc object</i>
---------	---

---

**Description**

This function is a wrapper for `sf::st_crs`, unless treating numeric character strings as integers, and accepting also UTM timezones, paths of spatial files and paths of text files containing WKT like .prj (see details).

**Usage**

```
st_crs2(x, ...)
```

**Arguments**

x	numeric, character, or object of class sf or sfc, being: <ul style="list-style-type: none"> <li>• EPSG code: numeric (e.g. 32632) or character (in the form "32632" or "EPSG:32632");</li> <li>• UTM zone: numeric (e.g. 32, interpreted as 32 North) or character (e.g. "32" or "32N" for zone 32 North, "32S" for 32 South);</li> <li>• WKT test: passed as character string or as path of a text file containing it (e.g. the path of a .prj file);</li> <li>• PROJ.4 string, passed as character (e.g. "+proj=utm +zone=32 +datum=WGS84 +units=m +no_defs" (<b>NOTE</b>: this representation is deprecated with PROJ &gt;= 6 – see <a href="http://rgdal.r-forge.r-project.org/articles/PROJ6_GDAL3.html">http://rgdal.r-forge.r-project.org/articles/PROJ6_GDAL3.html</a> – so a warning is returned using it, unless the string contains only the epsg code – e.g. "+init=epsg:32632", in which case the EPSG code is taken);</li> <li>• path of a spatial file (managed by <code>sf::st_read</code> or <code>stars::read_stars</code>), passed as character string of length 1;</li> <li>• spatial file of class sf or sfc.</li> </ul>
...	other parameters passed to <code>sf::st_crs</code> .

**Details**

See [sf::st\\_crs](#) for details.

**Value**

An object of class `crs` of length 2.

**Note**

License: GPL 3.0

**Author(s)**

Luigi Ranghetti, PhD (2019) <[luigi@ranghetti.info](mailto:luigi@ranghetti.info)>

**References**

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

**Examples**

```
## CRS from EPSG
st_crs2(32609)
st_crs2("EPSG:32609")

## CRS from UTM zone
st_crs2(9)
st_crs2("09")
st_crs2("9N")
st_crs2("09S")

## CRS from WKT (string or path)
(wkt_32n <- sf::st_as_text(sf::st_crs(32609)))
st_crs2(wkt_32n)
writeLines(wkt_32n, wkt_32n_path <- tempfile())
st_crs2(wkt_32n_path)

## CRS from spatial file path
raster_path <- system.file(
  "extdata/out/S2A2A_20190723_022_Barbellino_B0A_10.tif",
  package="sen2r"
)
vector_path <- system.file(
  "extdata/vector/barbellino.geojson",
  package="sen2r"
)
st_crs2(raster_path)
st_crs2(vector_path)
```

```
## CRS from spatial files
st_crs2(stars::read_stars(raster_path))
st_crs2(sf::read_sf(vector_path))

## CRS from PROJ.4 string
# (avoid using this with PROJ >= 6!)
st_crs2("+init=epsg:32609") # this makes use of the EPSG code
st_crs2("+proj=utm +zone=9 +datum=WGS84 +units=m +no_defs")
st_crs2(raster::raster(raster_path)) # st_crs(raster) uses the PROJ.4 as input
```

---

suppress_warnings	<i>Selective suppress warnings</i>
-------------------	------------------------------------

---

## Description

Suppress warnings matching particular regular expressions.

## Usage

```
suppress_warnings(.expr, .f)
```

## Arguments

.expr	Code to evaluate
.f	A regular expression (which will be passed to <code>grep1()</code> ).

## Details

See <https://stackoverflow.com/questions/16517795/selective-suppresswarnings-that-filters-by-regular-expression>

## Value

The warning message as character string, invisibly.

---

tiles_intersects	Select the tiles intersecting the extent
------------------	--

---

### Description

Function which returns the tile IDs of the Sentinel-2 tiles which overlap a provided extent.

### Usage

```
tiles_intersects(extent, all = FALSE, out_format = "id", .s2tiles = NULL)
```

### Arguments

extent	sf object with the spatial extent.
all	logical: if TRUE, all the tiles overlapping the extent are provided; if FALSE (default), unnecessary tiles are skipped. Unnecessary tiles are tiles which overlaps the extent for an area already covered by another tile. In case the extent is all included in an overlapping area, only one of the two candidate tiles is returned (the first in alphabetical order).
out_format	character: if "sf", the spatial object of the overlapping tiles is returned; if "id" (default), a character vector with the tile IDs.
.s2tiles	output of <code>s2_tiles()</code> function (it is possible to pass it in order to speed up the execution; otherwise leave to NULL and it will be generated within the function).

### Value

the tiles intersecting the extent (see argument out\_format).

### Note

License: GPL 3.0

### Author(s)

Luigi Ranghetti, PhD (2019) <luigi@ranghetti.info>

### References

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

**Examples**

```

ex_extent <- sf::st_read(
  system.file("extdata/vector/scalve.kml", package = "sen2r"),
  quiet = TRUE
)
ex_extent <- ex_extent[1,]

# Tile ID of the required S2 tile
tiles_intersects(ex_extent)

# Tile ID of all the overlapping S2 tiles
tiles_intersects(ex_extent, all = TRUE)

# Spatial object with the required tile
sel_tiles <- tiles_intersects(ex_extent, out_format = "sf")
plot(sf::st_geometry(sel_tiles)); plot(sf::st_geometry(ex_extent), add=TRUE, col="yellow")

# Spatial object with the overlapping S2 tiles
sel_tiles <- tiles_intersects(ex_extent, all = TRUE, out_format = "sf")
plot(sf::st_geometry(sel_tiles)); plot(sf::st_geometry(ex_extent), add=TRUE, col="yellow")

```

---

write_ignorelist	<i>Read / write the ignore list</i>
------------------	-------------------------------------

---

**Description**

Internal functions to read or write the file containing information about images not to process (because cloud covered or because, for any reason, they were not produced during previous processing runs).

**Usage**

```

write_ignorelist(
  pm,
  names_cloudcovered = NULL,
  dates_cloudcovered = NULL,
  names_missing = NULL,
  param_list = NULL
)

read_ignorelist(pm, param_list = NULL)

path_ignorelist(pm)

clean_ignorelist(pm, param_list = NULL)

```

## Arguments

<code>pm</code>	parameter list (passed by <code>sen2r()</code> ).
<code>names_cloudcovered</code>	paths of cloud covered images (passed by <code>sen2r()</code> ).
<code>dates_cloudcovered</code>	dates of cloud covered images (passed by <code>sen2r()</code> ) (this is used only if <code>names_cloudcovered</code> is not specified).
<code>names_missing</code>	paths of non produced images (passed by <code>sen2r()</code> ).
<code>param_list</code>	path of the parameter file (passed by <code>sen2r()</code> ).

## Details

Sometimes not all the output files are correctly created: the main reason is the cloud coverage higher than the maximum allowed value (argument `max_mask`), but also some other unexpected reasons could happen, i.e. because of old name SAFE products which do not include all the tiles. To prevent to try to create these files every time the function is called with the same parameter file, the TOML file `".ignorelist.txt"` is created in the directory where output files (or indices, or RGB images) are saved. With `sen2r <= 1.3.3`, a different strategy was used: if `param_list` is a path, these lists were saved in two hidden files (one per file not created because of cloud coverage, one other for all the other reasons). To try it again, delete the files/files or set `overwrite = TRUE` in `sen2r()`.

## Value

`write_ignorelist()` returns the path of the written TOML file (invisibly).

`read_ignorelist()` returns a list with two vectors:

- `dates_cloudcovered` (dates of cloud covered files);
- `names_missing` (base names of files to be ignored).

`path_ignorelist()` returns the path in which the TOML file should be written (basing on processing parameters).

`clean_ignorelist()` returns NULL (it is called for its side effects).

## Note

License: GPL 3.0

## Author(s)

Luigi Ranghetti, PhD (2020) <[luigi@ranghetti.info](mailto:luigi@ranghetti.info)>

## References

L. Ranghetti, M. Boschetti, F. Nutini, L. Busetto (2020). "sen2r": An R toolbox for automatically downloading and preprocessing Sentinel-2 satellite data. *Computers & Geosciences*, 139, 104473. doi: [10.1016/j.cageo.2020.104473](https://doi.org/10.1016/j.cageo.2020.104473), URL: <http://sen2r.ranghetti.info/>.

# Index

abs2rel, 3  
add\_rgb\_image, 5  
add\_tile\_suffix, 5  
as, 77  
  
build\_example\_param\_file, 7  
  
calcindex\_raster, 8  
calcindex\_stars (calcindex\_raster), 8  
check\_gdal, 9  
check\_gui\_deps, 10  
check\_param\_list, 11  
check\_scihub\_connection  
    (read\_scihub\_login), 50  
check\_scihub\_login (read\_scihub\_login),  
    50  
check\_sen2r\_deps, 12  
clean\_ignorelist (write\_ignorelist), 110  
clean\_trace, 103  
clean\_trace (start\_trace), 103  
clean\_traces, 103, 104  
clean\_traces (start\_trace), 103  
compute\_s2\_paths, 13  
compute\_s2\_paths(), 99  
comsub, 18  
create\_indices\_db, 19  
create\_s2\_dop, 20  
crs, 107  
  
Date, 60  
dontuse, 21  
  
end\_trace, 103  
end\_trace (start\_trace), 103  
expand\_path, 21  
expect\_equal\_crs, 22  
extract\_tile\_suffix (add\_tile\_suffix), 5  
  
fix\_envi\_format, 23  
gdal\_abs2rel, 27, 28  
gdal\_rel2abs, 28  
gdal\_rel2abs (gdal\_abs2rel), 27  
gdal\_warp, 29  
gdalUtil, 24  
gdalwarp\_grid, 26  
gipp\_init, 32  
give\_write\_permission, 34  
  
init\_python, 35  
install\_aria2, 35  
install\_sen2cor, 36  
install\_sen2cor(), 36  
  
link\_sen2cor (install\_sen2cor), 36  
list\_indices, 37  
list\_sen2r\_paths (compute\_s2\_paths), 13  
load\_binpaths, 38  
load\_extent\_bbox, 39  
load\_extent\_draw (load\_extent\_bbox), 39  
load\_extent\_vectfile  
    (load\_extent\_bbox), 39  
  
mountpoint, 40  
  
nn, 41  
normalize\_path, 42  
normalizePath, 42  
  
path\_check, 43  
path\_ignorelist (write\_ignorelist), 110  
POSIXct, 60  
print\_message, 12, 43  
projname (projpar), 45  
projpar, 45  
projpar(), 45  
  
raster, 61  
raster2rgb, 46  
raster\_metadata, 47  
read\_gipp, 48  
read\_gipp(), 48, 49



- read\_ignorelist (write\_ignorelist), 110
- read\_scihub\_login, 50
- remove\_tile\_suffix (add\_tile\_suffix), 5
- rm\_invalid\_safe (safe\_getMetadata), 78
  
- s2\_calcindices, 52, 54
- s2\_defNA, 54
- s2\_dop, 55
- s2\_download, 56, 68
- s2\_gui, 5, 58
- s2\_list, 56, 59, 77
- s2\_mask, 61, 61, 64, 100
- s2\_merge, 65
- s2\_order, 57, 67, 68, 82
- s2\_perc\_masked, 61, 64
- s2\_perc\_masked (s2\_mask), 61
- s2\_rgb, 69
- s2\_thumbnails, 46, 72, 101
- s2\_tiles, 73
- s2\_tiles(), 109
- s2\_translate, 52, 62, 66, 70, 72, 74
- safe\_getMetadata, 78
- safe\_is\_online, 68, 77, 82
- safe\_isvalid (safe\_getMetadata), 78
- safe\_shortcode, 23, 52, 62, 66, 70, 72, 75, 83, 97
- safelist, 57, 60, 68, 79, 82
- safelist (safelist-class), 77
- safelist-class, 77
- sen2cor, 85
- sen2cor(), 49, 91
- sen2r, 88
- sen2r(), 13
- sen2r\_getElements, 97
- sen2r\_process\_report, 98
- set\_gipp (read\_gipp), 48
- set\_gipp(), 48, 49
- sf, 106
- sf::st\_crs, 106, 107
- sf::st\_crs(), 45
- sf::st\_read, 106
- sfc, 106
- smooth\_mask, 100
- st\_as\_text\_2, 105
- st\_crs2, 30, 45, 67, 106
- stack2rgb, 101
- stars::read\_stars, 106
- start\_trace, 103, 103, 104
- str\_pad2, 104
  
- suppress\_warnings, 108
  
- tiles\_intersects, 109
- trace\_function, 103
- trace\_function (start\_trace), 103
  
- write\_ignorelist, 110
- write\_scihub\_login (read\_scihub\_login), 50