

Package ‘idiogramFISH’

February 6, 2021

Title Shiny App. Idiograms with Marks and Karyotype Indices

Version 2.0.0

Date 2021-02-03

Description Plot idiograms of karyotypes, plasmids, circular chr. having a set of data.frames for chromosome data and optionally mark data. Two styles of chromosomes can be used: without or with visible chromatids (when not circular). Supports micrometers, cM and Mb or any unit. Two styles of centromeres are available: triangular and rounded; and six styles of marks: square (squareLeft), dots, cM (cMLeft), cenStyle, upArrow, downArrow; its legend (label) can be drawn inline or to the right of karyotypes. Idiograms can also be plotted in concentric circles. It is possible to calculate chromosome indices by Levan et al. (1964) <doi:10.1111/j.1601-5223.1964.tb01953.x>, karyotype indices of Watanabe et al. (1999) <doi:10.1007/PL00013869> and Romero-Zarco (1986) <doi:10.2307/1221906> and classify chromosomes by morphology Guerra (1986) and Levan et al. (1964).

Depends R (>= 3.0)

Imports crayon, dplyr, tidyr

License GPL (>= 2)

Encoding UTF-8

LazyData true

Suggests plyr, rentrez, ggplot2, ggpubr, ggtree, phytools, treeio, rmdformats, knitr, kableExtra, rvcheck, badger, rmarkdown, RCurl, shiny, shinydashboard

VignetteBuilder plyr, rmdformats, knitr, kableExtra, rmarkdown, RCurl, rvcheck, badger, rentrez

SystemRequirements pandoc (>= 2.0)

URL <https://ferroao.gitlab.io/manualidiogramfish/>,
<https://ferroao.gitlab.io/idiogramFISH>

BugReports <https://gitlab.com/ferroao/idiogramFISH/-/issues>

RoxygenNote 7.1.1

NeedsCompilation no

Author Fernando Roa [aut, cre],
Mariana PC Telles [ctb]

Maintainer Fernando Roa <froao@unal.edu.co>

Repository CRAN

Date/Publication 2021-02-06 07:20:02 UTC

R topics documented:

armRatioCI	2
asymmetry	3
chrbasicdataHolo	5
chrbasicdatamono	6
citrusSize	7
dfMarkStyle	10
genBankReadIF	11
make.uniqueIF	12
makedfMarkColorMycolors	13
mapGGChr	13
markdataholo	14
markposDFs	15
namesToColumns	17
perMark	18
plotIdiograms	19
posCalc	32
robert	34
runBoard	35
Index	36

armRatioCI	<i>FUNCTIONS armRatioCI and swapChrRegionDfSizeAndMarks.</i>
------------	--

Description

armRatioCI: reads a data.frame and produces AR (radius), CI, Guerra and Levan classifications.

swapChrRegionDfSizeAndMarks: reads data.frames to swap arms

Usage

```
armRatioCI(dfChrSize)
```

```
swapChrRegionDfSizeAndMarks(dfChrSize, dfMarkPos, chrNamesToSwap)
```

Arguments

dfChrSize name of data.frame with columns: shortArmSize, longArmSize
dfMarkPos name of data.frame of marks
chrNamesToSwap name of chr. names to swap arms

Value

data.frame (armRatioCI)
list of data.frames (swapChrRegionDfSizeAndMarks)

References

LEVAN A, FREDGA K, SANDBERG AA (1964) NOMENCLATURE FOR CENTROMERIC POSITION ON CHROMOSOMES. Hereditas 52:201–220.

Guerra. 1986. Reviewing the chromosome nomenclature of Levan et al. Braz. Jour. Gen. Vol IX, 4, 741-743

See Also

[chrbasicdatamono](#)

Examples

```
armRatioCI(dfOfChrSize)
armRatioCI(bigdfOfChrSize)

swapChrRegionDfSizeAndMarks(dfOfChrSize,dfOfMarks,"1")
```

asymmetry

FUNCTIONS asymmetry and asymmetryA2.

Description

asymmetry: calculates karyotype asymmetry A and A2.

asymmetryA2: calculates karyotype asymmetry A2

This functions read a data.frame with columns: shortArmSize and longArmSize

If several species present, use column OTU.

It returns a list with the A and A2 indices

$$A = \frac{\sum_{i=1}^n \frac{longArm_i - shortArm_i}{CL_i}}{n}$$

A: Watanabe et al. (1999) asymmetry of karyotype ranging from 0 (symmetric) to 1 (asymmetric)

$$A_2 = \frac{sCL}{xCL}$$

(s = std dev, CL = chr. length, x = mean) (Romero-Zarco 1986)

related to:

$$CV_{CL} = A_2 * 100$$

(CV = coeff. var.) (Paszko 2006)

Usage

```
asymmetry(dfChrSize)
```

```
asymmetryA2(dfChrSize)
```

Arguments

```
dfChrSize      name of data.frame
```

Value

list

References

Watanabe K, Yahara T, Denda T, Kosuge K. 1999. Chromosomal evolution in the genus *Brachyscome* (Asteraceae, Astereae): Statistical tests regarding correlation between changes in karyotype and habit using phylogenetic information. *Journal of Plant Research* 112: 145-161. 10.1007/PL00013869

A2: Romero-Zarco. 1986. A New Method for Estimating Karyotype Asymmetry. *Taxon* Vol. 35, No. 3 pp. 526-530

Paszko B. 2006. A critical review and a new proposal of karyotype asymmetry indices. *Plant Syst Evol* 258:39-48.

See Also

[chrbasicdatamono](#)

[chrbasicdatamono](#)

[chrbasicdataHolo](#)

Examples

```
asymmetry(dfOfChrSize)
myAlist<-asymmetry(bigdfOfChrSize)
as.data.frame(myAlist)
asymmetryA2(dfOfChrSize)
as.data.frame(asymmetryA2(bigdfOfChrSize))
asymmetryA2(dfChrSizeHolo)
as.data.frame(asymmetryA2(bigdfChrSizeHolo))
```

chrbasicdataHolo *Chr. basic data Holo.*

Description

dfChrSizeHolo: Example data for holocentrics for 1 species

bigdfChrSizeHolo: Example data for holocentrics for several species, OTU

parentalAndHybHoloChrSize: Example data for holocentrics for several species, OTU

bigdfOfChrSize3Mb: Example data in Mb without chr. arms for three species, OTU

Usage

dfChrSizeHolo

bigdfChrSizeHolo

parentalAndHybHoloChrSize

bigdfOfChrSize3Mb

Format

data.frame with columns:

OTU grouping OTU (species), optional if only one OTU

chrName name of chromosome

chrSize size of chromosome, micrometers or Mb

group chromosome group, optional

chrNameUp optional name over kar.

Mbp optional name to show size in Mbp, use only when chrSize is not in Mbp

An object of class data.frame with 12 rows and 3 columns.

An object of class data.frame with 13 rows and 3 columns.

An object of class data.frame with 14 rows and 3 columns.

See Also

[asymmetryA2](#)

[plotIdiograms](#)

[markdataholo](#)

chrbasicdatamono *Chr. basic data Monocen.*

Description

dfOfChrSize: Example data for monocentrics

bigdfOfChrSize: Example data for monocentrics for several species, OTU

humChr: Data for human karyotype, measured from Adler (1994)

allChrSizeSample: Example data for monocentrics for several species, OTU

parentalAndHybChrSize: Example data for monocentrics for GISH

traspadf: Example data for Tradescantia (Rhoeo) spathacea (Golczyk et al. 2005)

Usage

dfOfChrSize

bigdfOfChrSize

humChr

allChrSizeSample

parentalAndHybChrSize

traspadf

Format

data.frame with columns:

OTU OTU, species, optional if only one OTU (species)

chrName name of chromosome

shortArmSize size of short arm, micrometers

longArmSize size of long arm, micrometers

group chr group, optional

chrNameUp optional name over kar.

Mbp optional name to show size in Mbp, use only when shortArmSize is not in Mbp

An object of class data.frame with 50 rows and 4 columns.

An object of class data.frame with 24 rows and 4 columns.

An object of class data.frame with 75 rows and 4 columns.

An object of class data.frame with 13 rows and 4 columns.

An object of class data.frame with 12 rows and 4 columns.

Source

<http://www.pathology.washington.edu/research/cytopages/idiograms/human/>

References

Adler 1994. Idiogram Album. <http://www.pathology.washington.edu/research/cytopages/idiograms/human/>

Golczyk H, Hasterok R, Joachimiak AJ (2005) FISH-aimed karyotyping and characterization of Renner complexes in permanent heterozygote *Rhoeo spathacea*. *Genome* 48:145–153.

See Also

[plotIdiograms](#)

[armRatioCI](#)

[asymmetry](#)

[markposDFs](#)

`citrusSize`

FUNCTIONS: citrusSize, citrusMarkPos, markOverCMA

Description

Helper function to create data.frames with chr. size and mark size data for Citrus based on categories in Carvalho et al. (2005)

Special behaviour while plotting: normally you will get chr. names as: B_1, B_2, etc. to remove `_*`, use `chrIdPatternRem='_.*'` in `plotIdiograms`. However, for FL+ and FL0, this conversion is automatic. So, in plot you will never see FL0_1, FL0_2, for example.

Usage

```
citrusSize(  
  A = 0,  
  B = 0,  
  C = 0,  
  D = 0,  
  E = 0,  
  F = 0,  
  FL = 0,  
  FL0 = 0,  
  G = 0,  
  shortArm = 1.2,  
  longArm = 1.7,  
  shortArmFL = 1.3,  
  longArmFL = 1.8,  
  OTU = "OTU 1"
```

```

)

citrusMarkPos(
  chrSizeDf,
  mSizePter = 0.25,
  mSizeQter = 0.35,
  mSizePprox = 0.35,
  mOther = 0.25,
  markName = "CMA"
)

markOverCMA(
  citrusMarkPosDF,
  chrType = "B",
  chrName,
  chrRegion = "p",
  markName = "45S",
  shrinkMark = TRUE
)

```

Arguments

A	number of A to calculate (citrusSize)
B	number of B to calculate (citrusSize)
C	number of C to calculate (citrusSize)
D	number of D to calculate (citrusSize)
E	number of E to calculate (citrusSize)
F	number of F to calculate (citrusSize)
FL	number of FL+ to calculate (citrusSize)
FL0	number of FL0 to calculate (citrusSize)
G	number of G to calculate (citrusSize)
shortArm	for A to G (not FL) (citrusSize)
longArm	for A to G (not FL) (citrusSize)
shortArmFL	for FL (citrusSize)
longArmFL	for FL (citrusSize)
OTU	name of species (citrusSize)
chrSizeDf	data.frame created with citrusSize function (citrusMarkPos)
mSizePter	numeric, default size for P(short) ter (terminal) bands. 0.25 (default) (citrusMarkPos)
mSizeQter	numeric, default size for Q(long) ter (terminal) bands. 0.35 (default) (citrusMarkPos)
mSizePprox	numeric, default size for P prox (proximal) bands. 0.35 (default) (citrusMarkPos)

mOther numeric, default size for other bands. 0.25 (default) (citrusMarkPos)

markName character, default name of mark "CMA", or "45S", respectively. (citrusMarkPos,markOverCMA)

citrusMarkPosDF

 data.frame, with CMA marks (markOverCMA)

chrType character, defaults to "B", chr. type to duplicate mark (markOverCMA)

chrName character, defaults to "B", chr. name(s) to duplicate mark (markOverCMA)

chrRegion character, arm, defaults to "p". for mark duplication (markOverCMA)

shrinkMark boolean, shrink new mark to be created (markOverCMA)

Value

data.frame
 data.frame
 data.frame

References

Carvalho, R., Soares Filho, W. S., Brasileiro-Vidal, A. C., & Guerra, M. (2005). The relationships among lemons, limes and citron: A chromosomal comparison. *Cytogenetic and Genome Research*, 109(1–3), 276–282. <https://doi.org/10.1159/000082410>

Examples

```
citrusSizeDF <- citrusSize(B=1,D=11,F=4,FL0=2,OTU="C. jambhiri")
suppressMessages(
plotIdiograms(citrusSizeDF,
  indexIdTextSize=.4,# font size
  rulerNumberSize=.4,# font size
  rulerTitleSize=.4, # font size
  rulerPos =-.5,    # ruler pos.
  xPosRulerTitle =1.5,    # ruler title pos.
  orderChr="original"# order of chr. as in d.f.
)
)
citrusSizeDF2 <- citrusSize(B=2,D=10,F=4,FL0=1,
FL=1,          # equivalent to FL+
OTU="C. limettioides")

suppressMessages(
plotIdiograms(citrusSizeDF2,    # FL^NA error corrected in 1.15.4
  indexIdTextSize=.4,# font size
  rulerNumberSize=.4,# font size
  rulerTitleSize=.4, # font size
  rulerPos =-.5,    # ruler pos.
  xPosRulerTitle =1.5,    # ruler title pos.
  orderChr="original"# order of chr. as in d.f.
)
)
```

```

)

citrusMarkPosDF <- citrusMarkPos(citrusSizeDF)
suppressMessages(
plotIdiograms(dfChrSize= citrusSizeDF,      # chr. size data.frame
              dfMarkPos= citrusMarkPosDF, # mark position data.frame (inc. cen.)
              ruler=FALSE,                # remove
              chrIndex=FALSE,             # remove
              morpho=FALSE,               # remove
              karIndex=FALSE,             # remove
              indexIdTextSize=.4,         # font size
              xlimRightMod=4,             # xlim mod.
              orderChr="original",        # order chr. as in d.f.
              chrColor="blue",           # chr. color
              legendHeight=3              # legend item height
              )
)

citrusMarkPosDF45S<-markOverCMA(citrusMarkPosDF, chrType="B", chrRegion="p", markName="45S")
suppressMessages(
plotIdiograms(dfChrSize= citrusSizeDF, # chr. size data.frame
              dfMarkPos= citrusMarkPosDF45S, # mark position data.frame (inc. cen.)
              ruler=FALSE,                # remove ruler
              chrIndex=FALSE,             # remove index
              morpho=FALSE,               # remove morphol.
              karIndex=FALSE,             # remove
              indexIdTextSize=.4,         # font size chr.
              xlimRightMod=4,             # modify xlim
              orderChr="original",        # as in d.f.
              chrColor="blue",           # chr. color
              legendHeight=5,            # height of legend item
              colorBorderMark="black",    # mark border color
              OTUfont=3                   # italics
              )
)

```

dfMarkStyle

Mark characteristics

Description

style column does not apply to cen. marks, only color.

dfMarkColor: Example General data for marks NOT position

humMarkColor: human bands' characteristics, from Adler (1994)

mydfMaColor: mark characteristics used in vignette of phylogeny

Usage

dfMarkColor

humMarkColor

mydfMaColor

Format

dfMarkColor a data.frame with columns:

markName name of mark

markColor use R colors

style character, use square or dots, optional

protruding numeric, modifies aspect of cM/cMLeft marks, see parameter protruding in [plotIdiograms](#), optional

An object of class data.frame with 395 rows and 3 columns.

An object of class data.frame with 6 rows and 3 columns.

Source

<http://www.pathology.washington.edu/research/cytopages/idiograms/human/>

References

Adler 1994. Idiogram Album. URL: <http://www.pathology.washington.edu/research/cytopages/idiograms/human/>

See Also

[plotIdiograms](#)

[markposDFs](#)

[markdataholo](#)

genBankReadIF

FUNCTION genBankReadIF

Description

genBankReadIF: creates a list of data.frames from a genbank format file or a rentrez object

Requires tidy

Usage

genBankReadIF(filename.gb)

Arguments

filename.gb name of file to read, downloaded from genBank, or, object from `rentrez::entrez_fetch(db="nuccore", id="theID", rettype="gbwithparts", retmode="text")`

Value

list

make.uniqueIF *FUNCTION make.uniqueIF*

Description

make.uniqueIF: produces unique strings from duplicated

Usage

```
make.uniqueIF(string, sep = "_", letter = FALSE)
```

Arguments

string name of char. vector
sep separator
letter boolean, use numbers when FALSE

Value

character vector

Examples

```
make.uniqueIF(c(1,1,2,2))
```

 makedfMarkColorMycolors

FUNCTION to make a data.frame of Marks' characteristics

Description

This function reads character vector with marks names, a character vector of prohibited colors and a custom list of colors to be associated with the mark names

It returns a data.frame with color and style for each mark

Usage

```
makedfMarkColorMycolors(
  markNames,
  mycolors,
  colorstoremove = NULL,
  defaultStyleMark = "square"
)
```

Arguments

markNames names of marks

mycolors character vector of names of colors

colorstoremove character vector of colors to remove from mycolors. Default NULL

defaultStyleMark
 character vector with default style "square". Other options: "squareLeft",
 "cM" "cMLeft", "dots", "upArrow", "downArrow", "cenStyle"

Value

data.frame

 mapGGChr

FUNCTIONS mapGGChr and mapGGChrMark (for ggplot)

Description

Currently works for holocentrics when only one OTU. See vignette.

mapGGChr: reads a data.frame and produces coordinates for ggplot of chr.

mapGGChrMark: reads data.frames and produces data.frames for ggplot of chr. and marks

Usage

```
mapGGChr(dfChrSize, chrSpacing = 0.5, squareness = 4, n = 50)
```

```
mapGGChrMark(dfChrSize, dfMarkPos, chrSpacing = 0.5, squareness = 4, n = 50)
```

Arguments

dfChrSize	character, name of data.frame with columns: chrSize
chrSpacing	numeric, 1 -chrSpacing will be the width of chr.
squareness	numeric, squareness
n	numeric, vertices number for rounded portions
dfMarkPos	(mapGGChrMark) name of data.frame of marks

Value

list

list

markdataholo

Mark Positional data - Holocen.

Description

When several OTUs, some can be monocen. and others holocen. Marks distance for monocen. are measured from cen. and for holocen. from top or bottom depending on param origin. See vignettes.

bigdfMarkPosHolo: Example data for mark position of holocentrics with column OTU

dfMarkPosHolo: Example data for mark position of holocentrics

dfAlloParentMarksHolo: Example data for mark position of GISH

bigdfOfMarks3Mb: Example data for mark position in Mb

Usage

```
bigdfMarkPosHolo
```

```
dfMarkPosHolo
```

```
dfAlloParentMarksHolo
```

```
bigdfOfMarks3Mb
```

Format

data.frame with columns:

OTU OTU, species, optional

chrName name of chromosome

markName name of mark

markPos position from bottom or top (see parameter origin in plotIdiograms)

markSize size of mark in micrometers or Mb

An object of class data.frame with 6 rows and 4 columns.

An object of class data.frame with 13 rows and 4 columns.

An object of class data.frame with 12 rows and 5 columns.

See Also

[markposDFs](#)

[plotIdiograms](#)

[chrbasicdataHolo](#)

markposDFs

Mark Positional data - monocentric

Description

When several OTUs, some can be monocen. and others holocen. Marks distance for monocen. are measured from cen. and for holocen. from top or bottom depending on param origin. See vignettes.

bigdfOfMarks: Example data for mark position with column OTU

dfOfMarks: Example data for marks' position

dfOfMarks2: Marks' position including cen. marks

humMarkPos: human karyotype bands' (marks) positions, measured from Adler (1994)

allMarksSample: Example data for marks' position

dfAlloParentMarks: Example data for mark position of GISH of monocen.

traspaMarks: T. spathacea (Rhoeo) marks' positions, from Golczyk et al. (2005)

Usage

bigdfOfMarks
dfOfMarks
dfOfMarks2
humMarkPos
allMarksSample
dfAlloParentMarks
traspaMarks

Format

bigdfOfMarks a data.frame with columns:

OTU OTU, species, mandatory if in dfChrSize

chrName name of chromosome

markName name of mark

chrRegion use p for short arm, q for long arm, and cen for centromeric

markDistCen distance of mark to centromere (not for cen)

markSize size of mark (not for cen)

An object of class data.frame with 4 rows and 5 columns.

An object of class data.frame with 6 rows and 5 columns.

An object of class data.frame with 395 rows and 5 columns.

An object of class data.frame with 43 rows and 6 columns.

An object of class data.frame with 15 rows and 4 columns.

An object of class data.frame with 18 rows and 7 columns.

Source

[Washington U](#)

References

Adler 1994. Idiogram Album. URL: [Washington U](#).

Golczyk H, Hasterok R, Joachimiak AJ (2005) FISH-aimed karyotyping and characterization of Renner complexes in permanent heterozygote *Rhoeo spathacea*. *Genome* 48:145–153.

See Also

[markdataholo](#)
[plotIdiograms](#)
[chrbasicdatamono](#)
[dfMarkColor](#)

namesToColumns *FUNCTION that modifies marks' names into columns*

Description

Reads a data.frame with marks' of styles downArrow, upArrow, cM, cMLeft positions. It separates names in columns, avoiding overlap when multiple close names

Exceptionally this function requires the column style in the data.frame of marks' positions.

Returns a data.frame

Usage

```
namesToColumns(
  marksDf,
  dfChrSize,
  markType = c("downArrow", "upArrow", "cMLeft", "cM"),
  amountofSpaces = 13,
  colNumber = 2,
  protruding = 0.5,
  protrudingInt = 0.5,
  circularPlot = TRUE,
  rotation = 0.5,
  defaultStyleMark = "square",
  orderChr = "size",
  halfModDown = NA,
  halfModUp = NA,
  rotatMod = 0
)
```

Arguments

marksDf	data.frame with columns: markName, style, markPos
dfChrSize	data.frame, size of chr. Same of plot.
markType	character, use c("downArrow", "upArrow", "cM", "cMLeft") or a subset
amountofSpaces	numeric, number of spaces for each column
colNumber	numeric, number of columns
protruding	numeric, same as plot, minimal protruding for arrow marks, equivalent to cM protruding

protrudingInt	numeric, spacing of columns in terms of width of chr. percent 1 = 100%. Defaults to 0.5
circularPlot	boolean, use TRUE for circular plots. Use FALSE otherwise
rotation	numeric, same as plot, anti-clockwise rotation, defaults to 0.5 which rotates chr. from top to -90 degrees. ($-0.5 * \pi$)
defaultStyleMark	character, if some data in column style missing fill with this one. Defaults to "square"
orderChr	character, replaces orderBySize -deprecated when "size", sorts chromosomes by total length from the largest to the smallest. "original": preserves d.f. order. "name": sorts alphabetically; "group": sorts by group name
halfModDown	numeric, for circ. plots, when plotting several chromosomes in a circular plot, using a small value 0.05 corrects for alignment problems of downArrows, cMLeft labels. Defaults to NA
halfModUp	numeric, for circ. plots, when plotting several chromosomes in a circular plot, using a small value 0.05 corrects for alignment problems of upArrows, cM labels. Defaults to NA
rotatMod	numeric, for circ. plots, when rotation $\neq 0$ (diff.), corrects alignment of labels. Defaults to 0

Value

data.frame

perMark *FUNCTION perMark*

Description

calculates fraction (%) of chromosome for each mark

Usage

```
perMark(dfMarkPos, listOfdfChromSize)
```

Arguments

dfMarkPos data.frame of marks' position
listOfdfChromSize list data.frames of chr. sizes. Require col. chrSize for all. Use armRatioCI

Value

list

Examples

```
# Beginning with two data.frames with column OTU
dfOfChrSize$OTU<-1
dfOfMarks2$OTU<-1

# add column chrSize if missing
dfOfChrSizeWithChrSize <- armRatioCI(dfOfChrSize)

#data.frame of chr. size to list
listOfdfChr<-idiogramFISH::dfToListColumn(dfOfChrSizeWithChrSize)

perMark(dfOfMarks2,listOfdfChr)
```

plotIdiograms	<i>FUNCTION to plot idiograms of karyotypes with and without centromere</i>
---------------	---

Description

This function reads a data.frame passed to dfChrSize with columns: chrName (mono/holo) and shortArmSize and longArmSize for monocentrics or a column chrSize for holocentrics and produces a plot of idiograms. If more than one species, a column named OTU is needed.

Optionally, it reads another data.frame passed to dfMarkPos with the position of marks (sites). Examples: [markposDFs](#). Another data.frame for mark characteristics can be used [dfMarkColor](#) or a character vector passed to mycolors

Usage

```
plotIdiograms(
  dfChrSize,
  defaultFontFamily,
  revOTUs = FALSE,
  karHeight = 2,
  karHeiSpace = 2.5,
  karSepar = TRUE,
  amoSepar = 10,
  addMissingOTUAfter = NA,
  addMissingOTUBefore = NA,
  missOTUspacings = 0,
  moveKarHor,
  moveAllKarValueHor,
  moveAllKarValueY,
  karAnchorLeft,
  karAnchorRight,
  anchor,
  anchorLineLty = 1,
```

```
anchorText = "",
anchorTextMParental,
anchorTextMoveX = 0.5,
anchorTextMoveY = 1,
anchorTextMoveParenX = 0,
anchorTextMoveParenY = 0,
anchorVsizeF = 0.5,
pchAnchor = 23,
moveAnchorV = 0,
moveAnchorH = 0,
mkhValue = 0.5,
n = 50,
notes,
leftNotes,
leftNotesUp,
notesTextSize = 0.4,
notesLeft,
notesPosX = 0.5,
notesPosY = 0,
leftNotesPosX = 0.5,
leftNotesPosY = 0,
leftNotesUpPosY = 0,
leftNoteFont = 1,
leftNoteFontUp = 1,
noteFont = 1,
parseTypes = TRUE,
parseStr2lang = FALSE,
propWidth = FALSE,
MbThreshold = 10000,
threshold = 35,
MbUnit = "Mb",
yTitle = "μm",
specialyTitle = "cM",
specialOTUNames = "",
addOTUName = TRUE,
OTUTextSize = 1,
OTUfont,
OTUfamily,
OTUasNote = FALSE,
OTUasLeftNote = FALSE,
orderChr = "size",
chrId = "original",
classMbName = "Pm.",
classcMName = "L.G.",
classChrName = "Chr.",
classChrNameUp = "Type",
classGroupName = "",
chrNameUp = FALSE,
```

```
chrIdPatternRem,  
indexIdTextSize = 1,  
distTextChr = 1,  
groupUp = FALSE,  
groupName = TRUE,  
groupSepar = 0.5,  
chromatids = TRUE,  
arrowsBothChrt = TRUE,  
holocenNotAsChromatids = FALSE,  
exHoloFrArrToSide = FALSE,  
xModifier,  
xModMonoHoloRate,  
chrWidth = 0.5,  
chrSpacing = 0.5,  
specialChrWidth = 0.3,  
specialChrSpacing = 0.7,  
chrColor = "gray",  
chrBorderColor,  
centromereSize = NA,  
cenColor,  
fixCenBorder = NULL,  
gishCenBorder,  
hideCenLines = 1.75,  
roundedCen = TRUE,  
squareness = 4,  
lwd.chr = 0.5,  
lwd.cM,  
lwd.marks,  
dfMarkPos,  
dfCenMarks,  
defaultStyleMark = "square",  
markDistType = "beg",  
protruding = 0.2,  
origin = "b",  
efZero = 1e-05,  
cMBeginCenter = FALSE,  
arrowhead = 0.3,  
shrinkArrow = 0.3333,  
arrowheadWidthShrink = 0.1,  
arrowsToSide = TRUE,  
useOneDot = FALSE,  
dotsAsOval = FALSE,  
dfMarkColor,  
mycolors,  
borderOfWhiteMarks = TRUE,  
colorBorderMark,  
lwd.mimicCen,  
defCenStyleCol,
```

```
pattern = "",
legend = "aside",
remSimiMarkLeg = FALSE,
bannedMarkName,
bannedMarkNameAside = FALSE,
forbiddenMark,
legendWidth = 1.7,
legendHeight = NA,
markLabelSize = 1,
markLabelSpacer = 1,
legendYcoord = 0,
markNewLine = NA,
mylheight = 0.7,
chrSize = FALSE,
nsmall = 1,
chrSizeMbp = FALSE,
markPer = "",
showMarkPos = FALSE,
bToRemove = "",
perAsFraction = FALSE,
chrIndex = "both",
morpho = "both",
nameChrIndexPos = 2,
karIndex = TRUE,
karIndexPos = 0.5,
ruler = TRUE,
useMinorTicks = FALSE,
miniTickFactor = 10,
rulerPos = 0,
ruler.tck = -0.02,
rulerNumberPos = 0.5,
rulerNumberSize = 1,
rulerInterval,
rulerIntervalcM,
rulerIntervalMb,
ceilingFactor = 0,
xPosRulerTitle = 2.6,
yPosRulerTitle = 0,
rulerTitleSize = 1,
xlimLeftMod = 1,
xlimRightMod = 2,
ylimBotMod = 0.2,
ylimTopMod = 0.2,
callPlot = TRUE,
asp = 1,
circularPlot = FALSE,
verticalPlot = TRUE,
karSpaceHor = 0,
```

```

shrinkFactor = 0.9,
separFactor = 1.5,
labelSpacing = 0.7,
labelOutwards = FALSE,
chrLabelSpacing = 0.5,
radius = 0.5,
rotation = 0.5,
circleCenter = 1,
circleCenterY = 1,
OTUlabelSpacing = 0.3,
OTUsrt = 0,
OTUplacing = "first",
OTUlabelSpacerx = 0,
OTUlabelSpacery = 0,
OTUcentered = TRUE,
OTUjustif = 0,
OTUlegendHeight = NA,
roundness,
...
)

```

Arguments

dfChrSize	mandatory data.frame, with columns: OTU (optional), chrName (mandatory), shortArmSize, longArmSize for monocen. or chrSize for holocen.
defaultFontFamily	character. use this as the font family. No default value.
revOTUs	boolean, The order of species is the one in the main data.frame, use TRUE to reverse
karHeight	numeric, vertical size of karyotypes. See also karHeiSpace. Defaults to 2
karHeiSpace	numeric, vertical size of karyotypes including spacing. Proportional to karHeight, if overlap, increase. Default value 2.5
karSepar	boolean, reduce distance among karyotypes FALSE = equally sized karyotypes or TRUE = equally spaced karyotypes. Incompatible with addMissingOTUAfter
amoSepar	numeric, depends on karSepar=TRUE, if zero your karyotypes will have no distance among them, if overlap, increase this and karHeiSpace
addMissingOTUAfter	character, when you want to add space (ghost OTUs) after one or several OTUs, pass the names of OTUs preceding the desired space in a character vector i.e. c("species one", "species five")
addMissingOTUBefore	character, when you want to add space (ghost OTUs) before one or several OTUs, pass the names of OTUs after the desired space in a character vector i.e. c("species one", "species five")
missOTUspacings	numeric, when you use addMissingOTUAfter this numeric vector should have the same length and corresponds to the number of free spaces (ghost OTUs) to add after each OTU respectively

moveKarHor	character, OTUs' names of karyotypes that should be moved horizontally. See mkhValue
moveAllKarValueHor	numeric, similar to mkhValue, but affects all karyotypes.
moveAllKarValueY	numeric, similar to moveAllKarValueHor, but affects y axis.
karAnchorLeft	character, OTUs' add anchor to the left of this OTU names of karyotypes. For verticalPlot=FALSE
karAnchorRight	character, OTUs' add anchor to the right of this OTU names of karyotypes. For verticalPlot=FALSE
anchor	boolean, when TRUE, plots a parent progeny structure in karyotypes in moveKarHor. Or a horizontal anchor to the left/right of karAnchorLeft, karAnchorRight when verticalPlot=FALSE
anchorLineLty	numeric, type of line in anchor, corresponds to lty. Defaults to 1
anchorText	character, text to add to anchor structure near symbol. See anchor. Defaults to ""
anchorTextMParental	character, designed to fill with a character object the space left of a missing parental in the anchor structure.
anchorTextMoveX	numeric, for vertical plots with anchorText move text in X axis. Defaults to 0.5
anchorTextMoveY	numeric, for horizontal plots with anchorText move text in Y axis. Defaults to 1
anchorTextMoveParenX	numeric, for plots with anchorTextMParental move text in X axis. Defaults to 0
anchorTextMoveParenY	numeric, for plots with anchorTextMParental move text in Y axis. Defaults to 0
anchorVsizeF	numeric, factor to modify vertical size of anchor 0.5 (default). Size itself is equal to karHeiSpace
pchAnchor	numeric, symbol for anchor, see ?points and anchor
moveAnchorV	numeric, displace anchor vertical portion to right or left. See anchor
moveAnchorH	numeric, displace anchor horizontal portion to right or left. See anchor
mkhValue	numeric, value to move kar. hor. See moveKarHor
n,	numeric vertices number for round corners
notes,	data.frame, (to the right), with columns OTU and note for adding notes to each OTU, they appear to the right of chromosomes
leftNotes,	data.frame, (to the left), with columns OTU and note for adding notes to each OTU, they appear to the left of chromosomes
leftNotesUp,	data.frame, (to the left), similar to leftNotes, but intended for placement over chr.

notesTextSize	numeric, font size of notes, see notes
notesLeft	deprecated, use a data.frame for leftNotes
notesPosX	numeric, move right notes to the right or left (x axis)
notesPosY	numeric, move right notes down or up (y axis)
leftNotesPosX	numeric, move left notes to the right or left (x axis)
leftNotesPosY	numeric, move left notes (leftNotes) down or up (y axis)
leftNotesUpPosY	numeric, move up left notes (leftNotesUp) down or up (y axis)
leftNoteFont, leftNoteFontUp,	numeric 1 for normal, 2 for bold, 3 for italics, 4 for bold-italics. See leftNotes
noteFont,	numeric 1 for normal, 2 for bold, 3 for italics, 4 for bold-italics. See notes
parseTypes,	boolean, parse in notes the <i>Citrus</i> chr. types names. Creates subindex pos. for FL. Defaults to TRUE. Incompatible with parseStr2lang
parseStr2lang,	boolean, parse string in notes with function <code>str2lang(paste0("paste(", note, "))")</code> for ex: <code>"italic('C. sinensis'), ' Author' "</code> . See notes, leftNotes, leftNotesUp.
propWidth,	boolean, defaults to FALSE. Diminishes chr. width with increasing number of OTUs
MbThreshold,	numeric, if greater than this number (defaults to 10000), MbUnit will apply and specialyTitle will not.
threshold,	this is the max. value allowed for the main two significant digits, otherwise scale will shrink. For example, after 35 μm (Default), apparent size will be 3.5 and scale interval will change. See also ceilingFactor, you may have to use -1. Introduced in 1.13
MbUnit,	character, text of units of title when MbThreshold met and OTU not in specialOTUNames. See specialyTitle Defaults to "Mb", but anything can be used. Introduced in 1.13. See specialyTitle
yTitle	character, units for common title. Defaults to μm
specialyTitle,	character, title of ruler if OTU is in specialOTUNames. Will not apply if MbThreshold met. In that case use MbUnit
specialOTUNames	character vector, normally title of ruler is micrometer or Mb (big numbers). Use this param. to be able to put a different unit in ruler title. See "specialyTitle"
addOTUName	boolean, when TRUE adds OTU (species) name to karyotype
OTU textSize	numeric, font size of OTU name (species). Defaults to 1. When OTUasNote is TRUE, use notesTextSize instead
OTUfont	numeric, 1 for normal, 2 for bold, 3 for italics, 4 for bold-italics
OTUfamily	character, font family for OTU name.
OTUasNote	boolean, when TRUE adds OTU (species) name to the right, see notes
OTUasLeftNote	boolean, when TRUE adds OTU (species) name to the left-up, see leftNotesUp

orderChr	character, when "size", sorts chromosomes by total length from the largest to the smallest. "original": preserves d.f. order. "name": sorts alphabetically; "group": sorts by group name; "chrNameUp": sorts according to column chrNameUp. See chrNameUp
chrId	character, print name of chromosome, "original" uses the original name in OTU column of dfChrSize, "simple" (just 1 to ...) or "" (none).
classMbName	character, name of "chromosome" when in Mbp. Defaults to "Pm". See MbUnit
classcMName	character, name of "chromosome" when OTU in specialOTUNames. Defaults to "L.G."
classChrName	character, name of "chromosome" when in micrometers (apparently). Defaults to "Chr.". See specialOTUNames, classMbName, classcMName
classChrNameUp	character, name of "chromosome" for col. "chrNameUp". Defaults to "Type"
classGroupName	character, name of groups. Defaults to ""
chrNameUp	boolean, when TRUE adds secondary chromosome name from col. chrNameUp over chrs. Defaults to FALSE
chrIdPatternRem	character, regex pattern to remove from chr. names
indexIdTextSize	numeric, font size of chr. and kar. indices and chromosome name. Defaults to 1
distTextChr	numeric, distance from name of chromosome to chromosome, also affects vertical separation of indices. Defaults to 1
groupUp	boolean, when TRUE when groups present, they appear over the chr. name. Defaults to FALSE
groupName	boolean, when TRUE (default), shows group names. When FALSE only line
groupSepar	numeric, factor for affecting chr. spacing chrSpacing among groups. Defaults to 0.5
chromatids	boolean, when TRUE shows separated chromatids. Defaults to TRUE
arrowsBothChrt	boolean, when TRUE (default) (for chromatids=TRUE) shows upArrow, downArrow styles of marks in both chromatids when arrowsToSide=TRUE.
holocenNotAsChromatids	boolean, when TRUE and chromatids=TRUE does not plot holocen kar. with chromatids. Defaults to FALSE. A value of TRUE modifies excHoloFrArrToSide to TRUE always.
excHoloFrArrToSide	boolean, when arrowsToSide=TRUE, excludes holocen. from this behaviour, plotting a centered arrow only.
xModifier	numeric, for chromatids=TRUE, separation among chromatids
xModMonoHoloRate	numeric, factor to shrink xModifier for holocen. 5 means 5 times smaller (quotient).
chrWidth	numeric, relative chromosome width. Defaults to 0.5
chrSpacing	numeric, horizontal spacing among chromosomes, see also chrWidth. Defaults to 0.5

specialChrWidth	numeric, relative chromosome width. Defaults to 0.5 for OTUs in specialOTUNames
specialChrSpacing	numeric, horizontal spacing among chromosomes for OTUs in specialOTUNames, see also chrWidth. Defaults to 0.5
chrColor	character, main color for chromosomes. Defaults to "gray"
chrBorderColor	character, color for border of chromosomes, defaults to chrColor
centromereSize	numeric, optional, this establishes the apparent size of cen. in the plot in μm . Automatic when NA. Default: NA
cenColor	character, color for centromeres, if GISH use NULL or NA. Defaults to chrColor
fixCenBorder	boolean, when TRUE uses chrColor as centromere (and cen. mark) border color. See also cenColor, chrColor, colorBorderMark, borderOfWhiteMarks. No default value. When chrColor is "white" this turns into "black".
gishCenBorder	boolean, when TRUE, cen. mark border color is the same as mark color, ignoring colorBorderMark. No default.
hideCenLines	numeric, factor to multiply line width (lwd) used for covering cen. border, when chrColor is white or when gishCenBorder=TRUE
roundedCen	boolean, when FALSE, cen has triangular aspect. When TRUE, it has rounded aspect (Default).
squareness	numeric, shape of vertices of chromosomes and square marks, higher values more squared. Defaults to 4
lwd.chr	thickness of border of chr., some marks and ruler. Thick of cM marks when lwd.cM absent and other marks when lwd.marks absent. Defaults to 0.5
lwd.cM	thickness of cM marks. Defaults to lwd.chr
lwd.marks	thickness of most marks. Except cM marks and centr. related marks. See lwd.chr, lwd.cM. Defaults to lwd.chr
dfMarkPos	data.frame of marks (sites): columns: OTU (opt), chrName, markName (name of site), chrRegion (for monocen. and opt for whole arm (w) in holocen.), markDistCen (for monocen.), markPos (for holocen.), markSize; column chrRegion: use p for short arm, q for long arm, cen for centromeric mark and w for whole chr. mark; column markDistCen: use distance from centromere to mark, not necessary for cen. marks (cen), w, p, q (when whole arm). See also param. markDistType
dfCenMarks	data.frame, specific for centromeric marks. columns: chrName and markName. See also dfMarkPos for another option to pass cen. marks
defaultStyleMark	character, default style of mark, only used when style column of dfMarkColor data.frame is missing or in absence of this data.frame. Use "square" (default), "squareLeft", "dots", "cM", "cMLeft", "cenStyle", "upArrow", "downArrow".
markDistType	character, if "cen" = the distance you provided in data.frame (dfMarkPos) column markDistCen or markPos is to the center of the mark, if "beg" = the distance you provided is to the beginning of the mark (Default)
protruding	numeric, when style of mark is "cM", fraction of chrWidth to stretch marker. Defaults to 0.2. Introduced in 1.13

origin,	For non-monocentric chr. (for holocentrics only) Use "b" (default) if distance to mark in ("markPos" column in "dfMarkPos") data.frame measured from bottom of chromosome, use "t" for distance to mark from top of chr.
efZero,	numeric, numbers below this one will be considered as zero, for comparison purposes. Defaults to 1e-5
cMBeginCenter,	boolean, start position of cM and cMLeft marks. If TRUE, starts in the center (width) of chr. . Defaults to FALSE
arrowhead	numeric, proportion of head of arrow (mark styles: upArrow, downArrow). Defaults to 0.3
shrinkArrow	numeric, proportion, shrinks body of arrow. Defaults to 0.3333
arrowheadWidthShrink	numeric, proportion, shrinks head of arrow. Defaults to 0.1
arrowsToSide	boolean, when FALSE use a centered arrow, instead of an arrow next to chr. margins (TRUE, default). See arrowsBothChr
useOneDot	boolean, use one dot instead of two in style of marks dots. Defaults to FALSE. Not useful for chromatids=TRUE
dotsAsOval	boolean, use oval instead of two dots in style of marks dots. Defaults to FALSE. See useOneDot. Not useful for chromatids=TRUE or circularPlot=TRUE
dfMarkColor	data.frame, optional, specifying colors and style for marks (sites); columns: markName, markColor, style. style accepts: square, squareLeft, dots, cM, "cMLeft", "cenStyle", "upArrow", "downArrow". (if column style missing all (except 5S) are plotted as in param. defaultStyleMark).
mycolors	character vector, optional, i.e. c("blue", "red", "green") for specifying color of marks in order of appearance. if diverges with number of marks will be recycled if dfMarkColor present, mycolors will be ignored. To know the order of your marks use something like: unique(c(dfMarkPos\$markName, dfCenMarks\$markName))
borderOfWhiteMarks	boolean, if TRUE (Default) uses black border for white marks. See dfMarkColor. Does not apply to marks with style cenStyle
colorBorderMark	character, without default, pass a name of a color to use as border of marks. See borderOfWhiteMarks
lwd.mimicCen	thickness of lines of cenStyle marks; affects only lateral borders. Defaults to lwd.chr
defCenStyleCol	character, color of outer part of cenStyle marks. Defaults to white
pattern	REGEX pattern to remove from names of marks
legend	character, "" for no legend; "inline" prints labels near chromosomes; "aside" prints legend to the right of karyotypes (default). See markLabelSpacer
remSimiMarkLeg	boolean, when legend="aside", if you use pattern, you can have several marks with same name. When TRUE this remove this pseudoduplicates from legend. Be sure that this pseudoduplicates have the same color, otherwise you should use FALSE (default).

bannedMarkName	character, character string or vector with mark names to be removed from plot. Not the marks but the labels. Except when bannedMarkNameAside is used.
bannedMarkNameAside	boolean, when TRUE and legend="inline", shows marks in bannedMarkName as legend="aside".
forbiddenMark,	character, character string or vector with mark names to be removed from plot. Not the marks but the labels.
legendWidth	numeric, factor to increase width of squares and of legend. Defaults to 1.7
legendHeight	numeric, factor to increase height of squares and dots of legend. Automatic.
markLabelSize	numeric, only if legend != (not) "", size of the font of labels of marks (legend). Defaults to 1
markLabelSpacer	numeric, only if legend="aside", space from the rightmost chr. to legend. Defaults to 1
legendYcoord	numeric, modify Y position of legend when legend="aside"
markNewLine,	character, character to split mark Names into different lines. Applies to square marks. Defaults to NA
mylheight,	numeric, for markNewLine!=NA; is equivalent to lheight of par: "The line height multiplier. The height of a line of text (used to vertically space multi-line text) is found by multiplying the character height both by the current character expansion and by the line height multiplier." Defaults to 0.7.
chrSize	boolean, when TRUE adds total chr size under each chr. Defaults to FALSE
nsmall	numeric, rounding decimals for chrSize parameter. Defaults to 1
chrSizeMbp	boolean, when TRUE adds total Mbp chr. size to each chr. provided, there is a Mbp column in dfChrSize data.frame. Defaults to FALSE. If data in columns shortArmSize, or col. chrSize is in millions ("Mbp"). Use chrSize=TRUE not this one (not column Mbp, you don't need this).
markPer	character, name of mark to calculate % of mark in chr. and add it to plot. See perAsFraction
showMarkPos	boolean, adds position of marks under karyotype (fraction 0-1) when TRUE. Defaults to FALSE
bToRemove,	character, bands to remove from calc. of pos.
perAsFraction	boolean, when TRUE % is shown as fraction. Defaults to FALSE. See markPer
chrIndex	character, add arm ratio with "AR" and centromeric index with "CI", or "both" (Default), or "" for none
morpho	character, when "both" (default) prints the Guerra and Levan classif of cen. position, use also "Guerra" or "Levan" or "" for none. See also ?armRatioCI.
nameChrIndexPos	numeric, modify position of name of chr. indices
karIndex	logical, add karyotype indices A (intrachromosomal - centromere pos.) and A2 (interchromosomal asymmetry, variation among chromosome sizes)
karIndexPos	numeric, move karyotype index

<code>ruler</code>	boolean, display ruler to the left of karyotype, when FALSE no ruler
<code>useMinorTicks</code>	boolean, display minor ticks between labeled ticks in ruler. See <code>miniTickFactor</code> . Defaults to FALSE. (ticks without label)
<code>miniTickFactor</code>	numeric, number of minor ticks for each labeled tick. See <code>useMinorTicks</code> . Defaults to 10
<code>rulerPos</code>	numeric, absolute position of ruler, corresponds to <code>pos</code> argument of axis R plot
<code>ruler.tck</code>	numeric, tick size of ruler, corresponds to <code>tck</code> argument of axis R plot. Defaults to -0.02
<code>rulerNumberPos</code>	numeric, modify position of numbers of ruler. Defaults to 0.5
<code>rulerNumberSize</code>	numeric, size of number's font in ruler. Defaults to 1
<code>rulerInterval</code>	numeric, intervals in ruler. No default, automatic. Introduced in 1.13
<code>rulerIntervalcM</code>	numeric, intervals in ruler of OTU in <code>specialOTUNames</code> . No default. Introduced in 1.13
<code>rulerIntervalMb</code>	numeric, intervals in ruler of OTU with data in Mb (>MbThreshold) and absent from <code>specialOTUNames</code> . No default. Introduced in 1.13
<code>ceilingFactor</code>	numeric, affects number of decimals for ceiling. Affects max. value of ruler. Defaults to 0. When threshold is greater than 35 this may have to be negative. Introduced in 1.13
<code>xPosRulerTitle,</code>	numeric, modify position of ruler title. See <code>yTitle</code> , <code>specialyTitle</code> , <code>MbUnit</code> . Defaults to 2.6. A value of 2.6 means 2.6 times the value of <code>chrSpacing</code> to the left, from the first chr.
<code>yPosRulerTitle,</code>	numeric, affects vertical position of ruler title. Defaults to 0
<code>rulerTitleSize,</code>	numeric font size of units of ruler. See also <code>xPosRulerTitle</code>
<code>xlimLeftMod</code>	numeric, modifies <code>xlim</code> left argument of plot
<code>xlimRightMod</code>	numeric, <code>xlim</code> right side modification by adding space to the right of idiograms. Defaults to 2
<code>ylimBotMod</code>	numeric, modify <code>ylim</code> bottom argument of plot
<code>ylimTopMod</code>	numeric, modify <code>ylim</code> top argument of plot
<code>callPlot</code>	boolean, create new plot in your device. Defaults to TRUE
<code>asp,</code>	numeric, y x aspect of plot. Defaults to 1
<code>circularPlot</code>	boolean, if TRUE chromosomes/karyotypes are plotted in concentric circles. Defaults to FALSE
<code>verticalPlot</code>	boolean, when TRUE karyotypes are plotted vertically, otherwise, horizontally Defaults to TRUE
<code>karSpaceHor</code>	numeric, separation among horizontal karyotypes. When <code>verticalPlot=FALSE</code> . Defaults to 0

shrinkFactor	numeric, for circularPlot=TRUE percentage of usage of circle. Defaults to 0.9
separFactor	numeric, for circularPlot=TRUE modify separation of concentric karyotypes. Defaults to 1.5
labelSpacing	numeric, for circularPlot=TRUE. Spacing of mark labels. Defaults to 0.7
labelOutwards	boolean, inline labels projected outwards
chrLabelSpacing	numeric, for circularPlot=TRUE. Spacing of chr. labels. Defaults to 0.5
radius	numeric, for circularPlot=TRUE. Affects radius of karyotypes. Defaults to 0.5
rotation	numeric, anti-clockwise rotation, defaults to 0.5 which rotates chr. from top to -90 degrees. $(-0.5 * \pi)$
circleCenter	numeric, for circularPlot=TRUE. Coordinate X of center of circles. Affects legend="aside" position. Defaults to 1
circleCenterY	numeric, for circularPlot=TRUE. Coordinate Y of center of circles. Affects legend="aside" position. Defaults to 1
OTUlabelSpacing	numeric, for circularPlot=TRUE. Spacing for OTU names. Defaults to 0.3
OTUsrt	numeric, for circularPlot=TRUE. Angle to use for OTU names. Defaults to 0
OTUplacing	character, for circularPlot=TRUE. location of OTU name. Defaults to "first" plots name near first chr. "number" places number near 1st chr. and index and name to the right or center. "simple" place name to the right or center without numbering. See also OTUcentered
OTUlabelSpacerx	numeric, for circularPlot=TRUE and OTUplacing="number" or "simple". Modifies x names position
OTUlabelSpacery	numeric, for circularPlot=TRUE and OTUplacing="number" or "simple". Modifies y names position
OTUcentered	boolean, for circularPlot=TRUE and OTUplacing="number" or "simple". OTU name in center of circle when TRUE, otherwise, to the right.
OTUjustif	numeric, for circularPlot=TRUE and OTUplacing="number" or "simple". Justification of OTU name. 0 = left (Default); use 0.5 for centered. See ?text -> adj
OTUlegendHeight	numeric, for circularPlot=TRUE and OTUplacing="number" or "simple". Modifies y names separation
roundness	deprecated, use squareness
...	accepts other arguments for the plot, see, ?plot

Value

plot

See Also

[asymmetry](#)
[armRatioCI](#)
[chrbasicdatamono](#)
[chrbasicdataHolo](#)
[markposDFs](#)
[markdataholo](#)
[dfMarkColor](#)

Examples

```

data(dfOfChrSize)
plotIdiograms(dfOfChrSize, ylimBotMod = .75, rulerPos=-.5)
plotIdiograms(dfOfChrSize, circularPlot = TRUE, chrLabelSpacing = 1)
plotIdiograms(dfChrSizeHolo, rulerPos=-.5)

```

posCalc

FUNCTION posCalc

Description

calculates position of marks in fraction of (%) chromosome units (0-1)

Usage

```

posCalc(
  dfMarkPos,
  listOfdfChromSize,
  bToRemove = "",
  markDistType = "beg",
  origin = "b",
  result = "tibble"
)

```

Arguments

dfMarkPos	data.frame of marks' position
listOfdfChromSize	list data.frames of chr. sizes. Require col. chrSize for all. Use armRatioCI
bToRemove,	character, bands to remove from calc. of pos.
markDistType	markDistType character, if "cen" = the distance you provided in data.frame (dfMarkPos) column markDistCen or markPos is to the center of the mark, if "beg" = the distance you provided is to the beginning of the mark (Default)

origin, For non-monocentric chr. (for holocentrics only) Use "b" (default) if distance to mark in ("markPos" column in "dfMarkPos") data.frame measured from bottom of chromosome, use "t" for distance to mark from top of chr.

result character, use "tibble" to get results in tibble, other string results in a list

Value

list, tibble

Examples

```
# Monocentrics - Beginning with two data.frames with column OTU
require(idiogramFISH)

dfOfChrSize$OTU<-1
dfOfMarks2$OTU<-1

# check missing data

dfOfMarks2[which(is.na(dfOfMarks2$markSize) & dfOfMarks2$chrRegion %in% c("p","q") ),]
# markSize and markDistCen missing

# add markDistCen
dfOfMarks2$markDistCen <- ifelse( is.na(dfOfMarks2$markDistCen) &
dfOfMarks2$chrRegion %in% c("p","q"),
0,
dfOfMarks2$markDistCen)

# add markSize
XshortSize <- dfOfChrSize[which(dfOfChrSize$chrName=="X"),]$shortArmSize
dfOfMarks2[which(dfOfMarks2$chrName=="X" & dfOfMarks2$chrRegion=="p") ,]$markSize<-XshortSize

# add column chrSize if missing
dfOfChrSizeWithChrSize <- armRatioCI(dfOfChrSize)

# data.frame of chr. size to list
listOfdfChr <- idiogramFISH::dfToListColumn(dfOfChrSizeWithChrSize)

ti<-posCalc(dfOfMarks2,listOfdfChr)
as.list(ti[[1]][,1])
posCalc(dfOfMarks2,listOfdfChr, result="list")

# holocentrics example

dfChrSizeHolo$OTU<-2
dfMarkPosHolo$OTU<-2

# data.frame of chr. size to list
listOfdfChrHolo <- idiogramFISH::dfToListColumn(dfChrSizeHolo)

ti2<-posCalc(dfMarkPosHolo,listOfdfChrHolo)
ti2
```

```
posCalc(dfMarkPosHolo,listOfdfChrHolo, result="list")
as.list(ti2[[1]][,1] )
```

 robert

FUNCTION to produce a Robertsonian translocation

Description

This function reads a data.frame with chr. sizes [chrbasicdatamono](#) and another with marks' positions, [markposDFs](#) and gets as arguments two chr. names and two arms, respectively.

It returns a list with two data.frames. One with the chr. size of the resulting translocation and another with the marks' positions for the derivative chr.

Usage

```
robert(dfChrSize, dfMarkPos, chr1, chr2, arm1, arm2)
```

Arguments

dfChrSize	name of data.frame of chr. sizes
dfMarkPos	name of data.frame of chr marks' positions
chr1	name of chr.
chr2	name of chr.
arm1	arm of chr1 to be included
arm2	arm of chr2 to be included

Value

list

References

Robertson, W. R. B. (1916). Chromosome studies. I. Taxonomic relationships shown in the chromosomes of Tettigidae and Acrididae: V-shaped chromosomes and their significance in Acrididae, Locustidae, and Gryllidae: chromosomes and variation. *Journal of Morphology*, 27(2), 179-331.

Examples

```
data(humChr)
data(humMarkPos)
chrt13q14q<-robert(humChr,humMarkPos,13,14,"q","q")
```

runBoard	<i>FUNCTION runBoard</i>
----------	--------------------------

Description

runBoard: run shinyApp

Usage

runBoard()

Value

shiny

Index

- * **arm**
 - armRatioCI, 2
 - asymmetry, 3
 - citrusSize, 7
 - mapGGChr, 13
 - * **chromosome**
 - perMark, 18
 - plotIdiograms, 19
 - posCalc, 32
 - * **create**
 - makedfMarkColorMycolors, 13
 - * **data.frame**
 - armRatioCI, 2
 - asymmetry, 3
 - mapGGChr, 13
 - namesToColumns, 17
 - plotIdiograms, 19
 - * **datasets**
 - chrbasicdataHolo, 5
 - chrbasicdatamono, 6
 - dfMarkStyle, 10
 - markdataholo, 14
 - markposDFs, 15
 - * **duplicates**
 - make.uniqueIF, 12
 - * **fraction**
 - posCalc, 32
 - * **genBank**
 - genBankReadIF, 11
 - * **marks**
 - namesToColumns, 17
 - * **mark**
 - makedfMarkColorMycolors, 13
 - perMark, 18
 - posCalc, 32
 - * **percentage**
 - perMark, 18
 - * **position**
 - posCalc, 32
 - * **shiny**
 - runBoard, 35
 - * **size**
 - armRatioCI, 2
 - asymmetry, 3
 - citrusSize, 7
 - mapGGChr, 13
 - * **span**
 - perMark, 18
 - * **string**
 - make.uniqueIF, 12
 - * **translocation**
 - robert, 34
 - * **unique**
 - make.uniqueIF, 12
- allChrSizeSample (chrbasicdatamono), 6
- allMarksSample (markposDFs), 15
- armRatioCI, 2, 7, 32
- asymmetry, 3, 7, 32
- asymmetryA2, 5
- asymmetryA2 (asymmetry), 3
- bigdfChrSizeHolo (chrbasicdataHolo), 5
- bigdfMarkPosHolo (markdataholo), 14
- bigdfOfChrSize (chrbasicdatamono), 6
- bigdfOfChrSize3Mb (chrbasicdataHolo), 5
- bigdfOfMarks (markposDFs), 15
- bigdfOfMarks3Mb (markdataholo), 14
- chrbasicdataHolo, 4, 5, 15, 32
- chrbasicdatamono, 3, 4, 6, 17, 32, 34
- citrusMarkPos (citrusSize), 7
- citrusMarkPos, (citrusSize), 7
- citrusSize, 7
- dfAlloParentMarks (markposDFs), 15
- dfAlloParentMarksHolo (markdataholo), 14
- dfChrSizeHolo (chrbasicdataHolo), 5
- dfMarkColor, 17, 19, 32

dfMarkColor (dfMarkStyle), 10
dfMarkPosHolo (markdataholo), 14
dfMarkStyle, 10
dfOfChrSize (chrbasicdatamono), 6
dfOfMarks (markposDFs), 15
dfOfMarks2 (markposDFs), 15

genBankReadIF, 11

humChr (chrbasicdatamono), 6
humMarkColor (dfMarkStyle), 10
humMarkPos (markposDFs), 15

make.uniqueIF, 12
makedfMarkColorMyColors, 13
mapGGChr, 13
mapGGChrMark (mapGGChr), 13
markdataholo, 5, 11, 14, 17, 32
markOverCMA (citrusSize), 7
markposDFs, 7, 11, 15, 15, 19, 32, 34
mydfMaColor (dfMarkStyle), 10

namesToColumns, 17

parentalAndHybChrSize
 (chrbasicdatamono), 6
parentalAndHybHoloChrSize
 (chrbasicdataHolo), 5
perMark, 18
plotIdiograms, 5, 7, 11, 15, 17, 19
posCalc, 32

robert, 34
runBoard, 35

swapChrRegionDfSizeAndMarks
 (armRatioCI), 2

traspadf (chrbasicdatamono), 6
traspamarks (markposDFs), 15