

Package ‘pillar’

February 22, 2021

Title Coloured Formatting for Columns

Version 1.5.0

Description Provides ‘pillar’ and ‘colonade’ generics designed for formatting columns of data using the full range of colours provided by modern terminals.

License MIT + file LICENSE

URL <https://pillar.r-lib.org/>, <https://github.com/r-lib/pillar>

BugReports <https://github.com/r-lib/pillar/issues>

Imports cli, crayon (>= 1.3.4), ellipsis, fansi, lifecycle, rlang (>= 0.3.0), utf8 (>= 1.1.0), utils, vctrs (>= 0.2.0)

Suggests bit64, debugme, DiagrammeR, knitr, lubridate, nycflights13, rmarkdown, survival, testthat (>= 3.0.2), tibble, withr

VignetteBuilder knitr

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1.9001

Config/testthat/edition 3

Config/testthat/parallel true

Config/testthat/start-first format_multi_fuzz, format_multi_fuzz_2, format_multi, ctl_colonnade, ctl_colonnade_1, ctl_colonnade_2

NeedsCompilation no

Author Kirill Müller [aut, cre],
Hadley Wickham [aut],
RStudio [cph]

Maintainer Kirill Müller <krlmlr+r@mailbox.org>

Repository CRAN

Date/Publication 2021-02-22 16:40:02 UTC

R topics documented:

pillar-package	2
align	3
ctl_new_pillar	4
dim_desc	5
format_tbl	6
format_type_sum	7
get_extent	8
glimpse	8
new_ornament	9
new_pillar	10
new_pillar_component	11
new_pillar_shaft	12
new_pillar_title	13
new_pillar_type	14
pillar	14
pillar_shaft	15
style_num	17
tbl_format_body	18
tbl_format_footer	19
tbl_format_header	19
tbl_format_setup	20
tbl_sum	21

Index	22
--------------	-----------

pillar-package *pillar: Coloured Formatting for Columns*

Description

[Maturing] Provides `pillar` and `colonnade` generics designed for formatting columns of data using the full range of colours provided by modern terminals.

Details

See `pillar()` for formatting a single column, and `colonnade()` for formatting multiple columns passed as a data frame.

Package options

- `pillar.bold`: Use bold font, e.g. for column headers? This currently defaults to FALSE, because many terminal fonts have poor support for bold fonts.
- `pillar.subtle`: Use subtle style, e.g. for row numbers and data types? Default: TRUE.
- `pillar.subtle_num`: Use subtle style for insignificant digits? Default: FALSE, is also affected by the `pillar.subtle` option.

- `pillar.neg`: Highlight negative numbers? Default: TRUE.
- `pillar.sigfig`: The number of significant digits that will be printed and highlighted, default: 3. Set the `pillar.subtle` option to FALSE to turn off highlighting of significant digits.
- `pillar.min_title_chars`: The minimum number of characters for the column title, default: 15. Column titles may be truncated up to that width to save horizontal space. Set to Inf to turn off truncation of column titles.
- `pillar.min_chars`: The minimum number of characters wide to display character columns, default: 0. Character columns may be truncated up to that width to save horizontal space. Set to Inf to turn off truncation of character columns.

Author(s)

Maintainer: Kirill Müller <krlmlr+r@mailbox.org>

Authors:

- Hadley Wickham

Other contributors:

- RStudio [copyright holder]

See Also

Useful links:

- <https://pillar.r-lib.org/>
- <https://github.com/r-lib/pillar>
- Report bugs at <https://github.com/r-lib/pillar/issues>

Examples

```
pillar(1:3)
pillar(c(1, 2, 3))
pillar(factor(letters[1:3]), title = "letters")
colonade(iris[1:3, ])
```

align

Alignment helper

Description

Facilitates easy alignment of strings within a character vector. Designed to help implementers of formatters for custom data types.

Usage

```
align(x, width = NULL, align = c("left", "right"))
```

Arguments

<code>x</code>	A character vector
<code>width</code>	The width that each string is padded to. If <code>NULL</code> , the maximum display width of the character vector is used (see get_max_extent()).
<code>align</code>	How should strings be aligned? If <code>align = left</code> then padding appears on the right, and vice versa.

Examples

```
align(c("abc", "de"), align = "left")
align(c("abc", "de"), align = "right")
```

`ctl_new_pillar`

Customize your tibble subclass

Description

Gain full control over the appearance of the pillars of your tibble subclass in its body. These methods are intended for implementers of subclasses of the "`tbl`" class. Users will rarely need them.

Usage

```
ctl_new_pillar(controller, x, width, ..., title = NULL)

ctl_new_compound_pillar(controller, x, width, ..., title = NULL)
```

Arguments

<code>controller</code>	The object of class " <code>tbl</code> " currently printed.
<code>x</code>	A vector, can also be a data frame, array or matrix in <code>ctl_new_compound_pillar()</code>
<code>width</code>	The available width, can be a vector for multiple tiers
<code>...</code>	These dots are for future extensions and must be empty.
<code>title</code>	The title, derived from the name of the column in the data

Details

`ctl_new_pillar()` is called to construct pillars for regular (one-dimensional) vectors. The default implementation returns an object constructed with [pillar\(\)](#). Extend this method to tweak pillar components returned from the default implementation. Override this method to completely change the appearance of the pillars.

`ctl_new_compound_pillar()` is called for compound pillars: columns that are data frames, matrices or arrays. The default implementation returns a compound pillar with suitable formatting for the titles and types of the sub-pillar. Users will only rarely need to override this method if ever.

Implementations should return `NULL` if none of the data fits the available width.

Examples

```
lines <- function(char = "-") {  
  stopifnot(nchar(char) == 1)  
  structure(char, class = "lines")  
}  
  
format.lines <- function(x, width, ...) {  
  paste(rep(x, width), collapse = "")  
}  
  
ctl_new_pillar.line_tbl <- function(controller, x, width, ..., title = NULL) {  
  out <- NextMethod()  
  new_pillar(list(  
    title = out$title,  
    type = out$type,  
    lines = new_pillar_component(list(lines("=")), width = 1),  
    data = out$data  
  ))  
}  
  
vctrs::new_data_frame(  
  list(a = 1:3, b = letters[1:3]),  
  class = c("line_tbl", "tbl")  
)
```

dim_desc

Format dimensions

Description

Multi-dimensional objects are formatted as a x b x ..., for vectors the length is returned.

Usage

```
dim_desc(x)
```

Arguments

x	The object to format the dimensions for
---	---

Examples

```
dim_desc(1:10)  
dim_desc(Titanic)
```

format_tbl

Formatting of tbl objects

Description

These functions and methods are responsible for printing objects of the "tbl" class, which includes `tibbles` and `dbplyr` lazy tables. See `tibble::formatting` for user level documentation, and `vignette("customization")` for details.

While it is possible to implement a custom `format()` or `print()` method for your tibble-like objects, it should never be necessary if your class inherits from "tbl". In this case, the default methods offer many customization options at every level of detail. This means you only need to override or extend implementations for the parts that need change.

Usage

```
## S3 method for class 'tbl'
print(x, width = NULL, ..., n = NULL, n_extra = NULL)

## S3 method for class 'tbl'
format(x, width = NULL, ..., n = NULL, n_extra = NULL)
```

Arguments

<code>x</code>	Object to format or print.
<code>width</code>	Width of text output to generate. This defaults to <code>NULL</code> , which means use <code>getOption("tibble.width")</code> or (if also <code>NULL</code>) <code>getOption("width")</code> ; the latter displays only the columns that fit on one screen. You can also set <code>options(tibble.width = Inf)</code> to override this default and always print all columns.
<code>...</code>	Passed on to <code>tbl_format_setup()</code> .
<code>n</code>	Number of rows to show. If <code>NULL</code> , the default, will print all rows if less than option <code>tibble.print_max</code> . Otherwise, will print <code>tibble.print_min</code> rows.
<code>n_extra</code>	Number of extra columns to print abbreviated information for, if the width is too small for the entire tibble. If <code>NULL</code> , the default, the value of the <code>tibble.max_extra_cols</code> option is used.

See Also

- `tbl_format_setup()` for preparing an object for formatting

Examples

```
print(vctrs::new_data_frame(list(a = 1), class = "tbl"))
```

format_type_sum	<i>Format a type summary</i>
-----------------	------------------------------

Description

Called on values returned from `type_sum()` for defining the description in the capital. Implement this method for a helper class for custom formatting, and return an object of this helper class from your `type_sum()` implementation. See examples.

Usage

```
format_type_sum(x, width, ...)

## Default S3 method:
format_type_sum(x, width, ...)
```

Arguments

x	A return value from <code>type_sum()</code>
width	The desired total width. If the returned string still is wider, it will be trimmed. Can be NULL.
...	Arguments passed to methods.

Examples

```
format_type_sum(1, NULL)
pillar(1)

type_sum.accel <- function(x) {
  structure("kg m/s^2", width = 8, class = "type_sum_accel")
}
format_type_sum.type_sum_accel <- function(x, width, ...) {
  if (!is.null(width) && width < attr(x, "width")) {
    x <- substr(x, 1, width)
  }
  style_subtle(x)
}
accel <- structure(9.81, class = "accel")
pillar(accel)
```

get_extent	<i>Calculate display width</i>
------------	--------------------------------

Description

`get_extent()` calculates the display width for each string in a character vector.

`get_max_extent()` calculates the maximum display width of all strings in a character vector, zero for empty vectors.

Usage

```
get_extent(x)
get_max_extent(x)
```

Arguments

`x` A character vector.

Examples

```
get_extent(c("abc", "de"))
get_extent("\u904b\u6c23")
get_max_extent(c("abc", "de"))
```

glimpse	<i>Get a glimpse of your data</i>
---------	-----------------------------------

Description

[Maturing]

`glimpse()` is like a transposed version of `print()`: columns run down the page, and data runs across. This makes it possible to see every column in a data frame. It's a little like `str()` applied to a data frame but it tries to show you as much data as possible. (And it always shows the underlying data, even when applied to a remote data source.)

This generic will be moved to `pillar`, and reexported from there as soon as it becomes available.

Usage

```
glimpse(x, width = NULL, ...)
```

Arguments

x	An object to glimpse at.
width	Width of output: defaults to the setting of the option <code>tibble.width</code> (if finite) or the width of the console.
...	Unused, for extensibility.

Value

x original x is (invisibly) returned, allowing `glimpse()` to be used within a data pipe line.

S3 methods

`glimpse` is an S3 generic with a customised method for `tbls` and `data.frames`, and a default method that calls `str()`.

Examples

```
glimpse(mtcars)
```

```
glimpse(nycflights13::flights)
```

`new_ornament`

Helper to define the contents of a pillar

Description

This function is useful if your data renders differently depending on the available width. In this case, implement the `pillar_shaft()` method for your class to return a subclass of "pillar_shaft" and have the `format()` method for this subclass call `new_ornament()`. See the implementation of `pillar_shaft.numeric()` and `format.pillar_shaft_decimal()` for an example.

Usage

```
new_ornament(x, width = NULL, align = NULL)
```

Arguments

x	A character vector with formatting, see <code>crayon</code>
width	An optional width of the resulting pillar, computed from x if missing
align	Alignment, one of "left" or "right"

Examples

```
new_ornament(c("abc", "de"), align = "right")
```

new_pillar*Construct a custom pillar object*

Description

[Experimental]

Usage

```
new_pillar(components, ..., width = NULL, class = NULL)
```

Arguments

components	A named list of components constructed with pillar_component() .
...	These dots are for future extensions and must be empty.
width	Default width, optional.
class	Name of subclass.

Details

`new_pillar()` is the low-level constructor for pillar objects. It supports arbitrary components. See [pillar\(\)](#) for the high-level constructor with default components.

Arbitrary components are supported. If your tibble subclass needs more or different components in its pillars, override or extend [ctl_new_pillar\(\)](#) and perhaps [ctl_new_compound_pillar\(\)](#).

Examples

```
lines <- function(char = "-") {
  stopifnot(nchar(char) == 1)
  structure(char, class = "lines")
}

format.lines <- function(x, width, ...) {
  paste(rep(x, width), collapse = "")
}

new_pillar(list(
  title = pillar_component(new_ornament(c("abc", "de"), align = "right")),
  lines = new_pillar_component(list(lines("-"))), width = 1
))
```

new_pillar_component *Components of a pillar*

Description

`new_pillar_component()` constructs an object of class "pillar_component".

`pillar_component()` is a convenience helper that wraps the input in a list and extracts width and minimum width.

Usage

```
new_pillar_component(x, ..., width, min_width = NULL)  
pillar_component(x)
```

Arguments

`x` A bare list (for `new_pillar_component()`), or an object with width and minimum width attributes (for `pillar_component()`).

`...` These dots are for future extensions and must be empty.

`width, min_width`

TBD

Details

Objects of class "pillar" are internally a named lists of their components. The default components are title (may be missing), type, and data. Each component is a "pillar_component".

This class captures contents that can be fitted in a rectangle. Each component consists of one or multiple cells that are aligned horizontally (with one space in between) when printed. Each cell has a maximum (i.e., desired) width and may have a minimum width if the contents are compressible. The component object stores the width of the cells as an attribute.

Examples

```
# TBD
```

new_pillar_shaft	<i>Constructor for column data</i>
------------------	------------------------------------

Description

[Stable]

The `new_pillar_shaft()` constructor creates objects of the "pillar_shaft" class. This is a virtual or abstract class, you must specify the `class` argument. By convention, this should be a string that starts with "pillar_shaft_". See `vignette("extending", package = "tibble")` for usage examples.

This method accepts a vector of arbitrary length and is expected to return an S3 object with the following properties:

- It has an attribute "width"
- It can have an attribute "min_width", if missing, "width" is used
- It must implement a method `format(x, width, ...)` that can be called with any value between `min_width` and `width`
- This method must return an object that inherits from `character` and has attributes "align" (with supported values "left", "right", and "center") and "width"

The function `new_pillar_shaft()` returns such an object, and also correctly formats NA values. In many cases, the implementation of `pillar_shaft.your_class_name()` will format the data as a character vector (using color for emphasis) and simply call `new_pillar_shaft()`. See `pillar:::pillar_shaft.numeric` for a code that allows changing the display depending on the available width.

`new_pillar_shaft_simple()` provides an implementation of the `pillar_shaft` class suitable for output that has a fixed formatting, which will be truncated with a continuation character (ellipsis or ~) if it doesn't fit the available width. By default, the required width is computed from the natural width of the `formatted` argument.

Usage

```
new_pillar_shaft(
  x,
  ...,
  width = NULL,
  min_width = width,
  class = NULL,
  subclass = NULL
)
new_pillar_shaft_simple(
  formatted,
  ...,
  width = NULL,
```

```
  align = "left",
  min_width = NULL,
  na = NULL,
  na_indent = 0L
)
```

Arguments

x	An object
...	Additional attributes.
width	The maximum column width.
min_width	The minimum allowed column width, width if omitted.
class	The name of the subclass.
subclass	Deprecated, pass the class argument instead.
formatted	An object coercible to character .
align	Alignment of the column.
na	String to use as NA value, defaults to "NA" styled with style_na() with fallback if color is not available.
na_indent	Indentation of NA values.

Details

The formatted argument may also contain ANSI escapes to change color or other attributes of the text, see [crayon](#).

new_pillar_title *Prepare a column title for formatting*

Description

Call [format\(\)](#) on the result to render column titles.

Usage

```
new_pillar_title(x, ...)
```

Arguments

x	A character vector of column titles.
...	These dots are for future extensions and must be empty.

Examples

```
format(new_pillar_title(names(iris)))
```

`new_pillar_type` *Prepare a column type for formatting*

Description

Calls `type_sum()` to format the type. Call `format()` on the result to render column types.

Usage

```
new_pillar_type(x, ...)
```

Arguments

- `x` A vector for which the type is to be retrieved.
- `...` These dots are for future extensions and must be empty.

Examples

```
format(new_pillar_type(iris$Species))
```

`pillar` *Object for formatting a vector suitable for tabular display*

Description

[Stable]

`pillar()` creates an object that formats a vector. The output uses one row for a title (if given), one row for the type, and `vec_size(x)` rows for the data.

Usage

```
pillar(x, title = NULL, width = NULL, ...)
```

Arguments

- `x` A vector to format.
- `title` An optional title for the column. The title will be used "as is", no quoting will be applied.
- `width` Default width, optional.
- `...` Passed on to `pillar_shaft()`.

Details

A pillar consists of arbitrary components. The `pillar()` constructor uses `title`, `type`, and `data`.

- `title` via `new_pillar_title()`
- `type` via `new_pillar_type()`, which calls `type_sum()` internally
- `data` via `pillar_shaft()`

All components are formatted via `format()` when displaying the pillar. A `width` argument is passed to each `format()` call.

As of pillar 1.5.0, `pillar()` returns `NULL` if the width is insufficient to display the data.

Examples

```
x <- 123456789 * (10 ^ c(-1, -3, -5, NA, -8, -10))
pillar(x)
pillar(-x)
pillar(runif(10))
pillar(rcauchy(20))

# Special values are highlighted
pillar(c(runif(5), NA, NaN, Inf, -Inf))

# Very wide ranges will be displayed in scientific format
pillar(c(1e10, 1e-10), width = 20)
pillar(c(1e10, 1e-10))

x <- c(FALSE, NA, FALSE, FALSE, TRUE, FALSE, FALSE, TRUE, FALSE, TRUE)
pillar(x)

x <- c("This is string is rather long", NA, "?", "Short")
pillar(x)
pillar(x, width = 30)
pillar(x, width = 5)

date <- as.Date("2017-05-15")
pillar(date + c(1, NA, 3:5))
pillar(as.POSIXct(date) + c(30, NA, 600, 3600, 86400))
```

`pillar_shaft`

Column data

Description

[Stable]

Internal class for formatting the data for a column. `pillar_shaft()` is a coercion method that must be implemented for your data type to display it in a tibble.

This class comes with a default method for `print()` that calls `format()`. If `print()` is called without `width` argument, the natural width will be used when calling `format()`. Usually there's no need to implement this method for your subclass.

Your subclass must implement `format()`, the default implementation just raises an error. Your `format()` method can assume a valid value for the `width` argument.

Usage

```
pillar_shaft(x, ...)

## S3 method for class 'pillar_shaft'
print(x, width = NULL, ...)

## S3 method for class 'pillar_shaft'
format(x, width, ...)

## S3 method for class 'logical'
pillar_shaft(x, ...)

## S3 method for class 'numeric'
pillar_shaft(x, ..., sigfig = NULL)

## S3 method for class 'Date'
pillar_shaft(x, ...)

## S3 method for class 'POSIXt'
pillar_shaft(x, ...)

## S3 method for class 'character'
pillar_shaft(x, ..., min_width = NULL)

## S3 method for class 'pillar_vertical'
pillar_shaft(x, ..., min_width = NULL, na_indent = 0L)

## S3 method for class 'list'
pillar_shaft(x, ...)

## S3 method for class 'factor'
pillar_shaft(x, ...)

## S3 method for class 'AsIs'
pillar_shaft(x, ...)

## Default S3 method:
pillar_shaft(x, ...)
```

Arguments

x	A vector to format
---	--------------------

...	Arguments passed to methods.
width	Width for printing and formatting.
sigfig	Minimum number of significant figures to display, default: 3. Numbers larger than 1 will potentially show more significant figures than this.
min_width	Minimum number of characters to display, unless the string fits a shorter width.
na_indent	Indentation of NA values.

Details

The default method will currently format via `format()`, but you should not rely on this behavior.

Examples

```
pillar_shaft(1:3)
pillar_shaft(1.5:3.5)
pillar_shaft(NA)
pillar_shaft(c(1:3, NA))
```

`style_num`

Styling helpers

Description

Functions that allow implementers of formatters for custom data types to maintain a consistent style with the default data types.

Usage

```
style_num(x, negative, significant = rep_along(x, TRUE))

style_subtle(x)

style_subtle_num(x, negative)

style_bold(x)

style_na(x)

style_neg(x)
```

Arguments

x	The character vector to style.
negative, significant	Logical vector the same length as x that indicate if the values are negative and significant, respectively

Details

- `style_subtle()` is affected by the `pillar.subtle` option.
- `style_subtle_num()` is affected by the `pillar.subtle_num` option, which is FALSE by default.
- `style_bold()` is affected by the `pillar.bold` option.
- `style_neg()` is affected by the `pillar.neg` option.

See Also

[pillar-package](#) for a list of options

Examples

```
style_num(
  c("123", "456"),
  negative = c(TRUE, FALSE)
)
style_num(
  c("123", "456"),
  negative = c(TRUE, FALSE),
  significant = c(FALSE, FALSE)
)
style_subtle("text")
style_subtle_num(0.01 * 1:3, c(TRUE, FALSE, TRUE))
style_bold("Petal.Width")
style_na("NA")
style_neg("123")
```

tbl_format_body *Format the body of a tibble*

Description

For easier customization, the formatting of a tibble is split into three components: header, body, and footer. The `tbl_format_body()` method is responsible for formatting the body of a tibble.

Override this method if you need to change the appearance of all parts of the body. If you only need to change the appearance of a single data type, override [vctrs::vec_ptype_abbr\(\)](#) and [pillar_shaft\(\)](#) for this data type.

Usage

```
tbl_format_body(x, setup, ...)
```

Arguments

- | | |
|--------------------|---|
| <code>x</code> | A tibble-like object. |
| <code>setup</code> | A setup object returned from tbl_format_setup() . |
| <code>...</code> | These dots are for future extensions and must be empty. |

Value

A character vector.

tbl_format_footer *Format the footer of a tibble*

Description

For easier customization, the formatting of a tibble is split into three components: header, body, and footer. The `tbl_format_footer()` method is responsible for formatting the footer of a tibble.

Override or extend this method if you need to change the appearance of the footer. The default implementation adds information about rows and columns that are not shown in the body.

Usage

```
tbl_format_footer(x, setup, ...)
```

Arguments

- | | |
|-------|--|
| x | A tibble-like object. |
| setup | A setup object returned from <code>tbl_format_setup()</code> . |
| ... | These dots are for future extensions and must be empty. |

Value

A character vector.

tbl_format_header *Format the header of a tibble*

Description

For easier customization, the formatting of a tibble is split into three components: header, body, and footer. The `tbl_format_header()` method is responsible for formatting the header of a tibble.

Override this method if you need to change the appearance of the entire header. If you only need to change or extend the components shown in the header, override or extend `tbl_sum()` for your class which is called by the default method.

Usage

```
tbl_format_header(x, setup, ...)
```

Arguments

- `x` A tibble-like object.
- `setup` A setup object returned from `tbl_format_setup()`.
- `...` These dots are for future extensions and must be empty.

Value

A character vector.

`tbl_format_setup` *Set up formatting*

Description

`tbl_format_setup()` is called by `format.tbl()`. This method collects information that is common to the header, body, and footer parts of a tibble. Examples:

- the dimensions sometimes are reported both in the header and (implicitly) in the footer of a tibble;
- the columns shown in the body decide which columns are shown in the footer.

This information is computed once in `tbl_format_setup()`. The result is passed on to the `tbl_format_header()`, `tbl_format_body()`, and `tbl_format_footer()` methods. If you need to customize parts of the printed output independently, override these methods instead.

Usage

```
tbl_format_setup(x, width = NULL, ..., n = NULL, max_extra_cols = NULL)

## S3 method for class 'tbl'
tbl_format_setup(x, width, ..., n, max_extra_cols)
```

Arguments

- `x` An object.
- `width` Actual width for printing, a numeric greater than zero. This argument is mandatory for all implementations of this method.
- `...` Extra arguments to `print.tbl()` or `format.tbl()`.
- `n` Actual number of rows to print. No `options` should be considered by implementations of this method.
- `max_extra_cols` Number of columns to print abbreviated information for, if the width is too small for the entire tibble. No `options` should be considered by implementations of this method.

Details

Extend this method to prepare information that is used in several parts of the printed output of a tibble-like object, or to collect additional arguments passed via ... to [print.tbl\(\)](#) or [format.tbl\(\)](#).

We expect that `tbl_format_setup()` is extended only rarely, and overridden only in exceptional circumstances, if at all. If you override this method, you must also implement `tbl_format_header()`, `tbl_format_body()`, and `tbl_format_footer()` for your class.

Implementing a method allows to override printing and formatting of the entire object without overriding the `print()` and `format()` methods directly. This allows to keep the logic of the `width` and `n` arguments.

The default method for the "tbl" class collects information for standard printing for tibbles. See [new_tbl_format_setup\(\)](#) for details on the returned object.

Value

An object that will be passed as `setup` argument to `tbl_format_header()`, `tbl_format_body()`, and `tbl_format_footer()`.

tbl_sum

Provide a succinct summary of an object

Description

`tbl_sum()` gives a brief textual description of a table-like object, which should include the dimensions and the data source in the first element, and additional information in the other elements (such as grouping for `dplyr`). The default implementation forwards to [obj_sum\(\)](#).

Usage

```
tbl_sum(x)
```

Arguments

x	Object to summarise.
---	----------------------

Details

This generic will be moved to `pillar`, and reexported from there as soon as it becomes available.

Value

A named character vector, describing the dimensions in the first element and the data source in the name of the first element.

See Also

[type_sum\(\)](#)

Index

align, 3
character, 13
colonnade, 2
colonnade(), 2
crayon, 9, 13
ctl_new_compound_pillar
 (ctl_new_pillar), 4
ctl_new_compound_pillar(), 10
ctl_new_pillar, 4
ctl_new_pillar(), 10

dim_desc, 5

format(), 6, 9, 13–17, 21
format.pillar_shaft(pillar_shaft), 15
format.tbl(format_tbl), 6
format.tbl(), 20, 21
format_tbl, 6
format_type_sum, 7

get_extent, 8
get_max_extent(get_extent), 8
get_max_extent(), 4
glimpse, 8

new_ornament, 9
new_pillar, 10
new_pillar_component, 11
new_pillar_shaft, 12
new_pillar_shaft(), 12
new_pillar_shaft_simple
 (new_pillar_shaft), 12
new_pillar_title, 13
new_pillar_title(), 15
new_pillar_type, 14
new_pillar_type(), 15
new_tbl_format_setup(), 21

obj_sum(), 21
option, 20

pillar, 2, 14
pillar(), 2, 4, 10
pillar-package, 2, 18
pillar_component
 (new_pillar_component), 11
pillar_component(), 10
pillar_shaft, 15
pillar_shaft(), 9, 14, 15, 18
print(), 6, 16, 21
print.pillar_shaft(pillar_shaft), 15
print.tbl(format_tbl), 6
print.tbl(), 20, 21

str(), 8, 9
style_bold(style_num), 17
style_na(style_num), 17
style_na(), 13
style_neg(style_num), 17
style_num, 17
style_subtle(style_num), 17
style_subtle_num(style_num), 17

tbl_format_body, 18
tbl_format_body(), 20, 21
tbl_format_footer, 19
tbl_format_footer(), 20, 21
tbl_format_header, 19
tbl_format_header(), 20, 21
tbl_format_setup, 20
tbl_format_setup(), 6, 18–20
tbl_sum, 21
tbl_sum(), 19
tibble, 6
tibble.max_extra_cols, 6
tibble::formatting, 6
type_sum(), 7, 14, 15, 21

vctrs::vec_ptype_abbr(), 18