

Package ‘postGGIR’

March 1, 2021

Version 1.0.0

Title Data Processing after Running 'GGIR' for Accelerometer Data

Description

Generate all necessary R/Rmd/shell files for data processing after running 'GGIR' (v2.0) for accelerometer data. In part 1, all csv files in the GGIR output directory were read, transformed and then merged. In part 2, the GGIR output files were checked and summarized in one excel sheet. In part 3, the merged data was cleaned according to the number of valid hours on each night and the number of valid days for each subject. In part 4, the cleaned activity data was imputed by the average Euclidean norm minus one (ENMO) over all the valid days for each subject. Finally, a comprehensive report of data processing was created using Rmarkdown, and the report includes few exploratory plots and multiple commonly used features extracted from minute level actigraphy data.

Maintainer Wei Guo <wei.guo3@nih.gov>

License GPL-3

Imports refund, denseFLMM, dplyr, xlsx, survival, stats, tidyr, zoo, ineq, cosinor, abind, accelerometry, minpack.lm, kableExtra, GGIR

Depends R (>= 3.6.0)

Suggests knitr, rmarkdown

Encoding UTF-8

LazyData TRUE

ByteCompile true

Type Package

VignetteBuilder knitr

RoxygenNote 7.1.1

NeedsCompilation no

Author Wei Guo [aut, cre],
Vadim Zipunnikov [aut],
Kathleen Merikangas [aut]

Repository CRAN

Date/Publication 2021-03-01 09:00:02 UTC

R topics documented:

ActCosinor	2
afterggir	3
create.postGGIR	5
data.imputation	5
DataShrink	7
ExtCos2	9
ExtCos_long2	10
fragmentation2	10
fragmentation_long2	11
ggir.dataatransform	13
ggir.summary	14
IS_long2	16
IV	17
IV_long2	17
jive.predict2	18
pheno.plot	18
RA2	19
RA_long2	20
SVDmiss2	20
Time2	21
Time_long2	21
Tvol2	22
wear_flag	23
Index	24

ActCosinor	<i>Cosinor Model for Circadian Rhythmicity for Whole Dataset</i>
------------	--

Description

A parametric approach to study circadian rhythmicity assuming cosinor shape. Here we used the anti logistic transformed cosine curves, which provided 3 parameters.

Usage

```
ActCosinor(data, window = 1)
```

Arguments

data	data.frame of dimension n*1442 containing the 1440 minute activity data for all n subject days. The first two columns have to be ID and Day.
window	number 1440/window is the dimension of the data. Default is 1.

Value

A data.frame with following columns

ID	identifier of the person
mesor	mesor
amp	amplitude
acro	acrophase

afterggir	<i>Main Call for Data Processing after Runing GGIR for Accelerometer Data</i>
-----------	---

Description

This R script will generate all necessary R/Rmd/shell files for data processing after running GGIR for accelerometer data.

Usage

```
afterggir(  
  mode,  
  useIDs.FN = NULL,  
  currentdir,  
  studyname,  
  bindir = NULL,  
  outputdir,  
  epochIn = 5,  
  epochOut = 5,  
  flag.epochOut = 60,  
  log.multiplier = 9250,  
  use.cluster = TRUE,  
  QCdays.alpha = 7,  
  QChours.alpha = 16,  
  QCnights.feature.alpha = c(0, 0),  
  Rversion = "R",  
  filename2id = NULL,  
  PA.threshold = c(50, 100, 400),  
  desiredtz = "US/Eastern",  
  RemoveDaySleeper = FALSE,  
  trace = FALSE  
)
```

Arguments

mode	number Specify which of the five parts need to be run, e.g. mode = 0 makes that all R/Rmd/sh files are generated for other parts. When mode = 1, all csv files in the GGIR output directory were read, transformed and then merged. When mode = 2, the GGIR output files were checked and summarized in one excel sheet. When mode = 3, the merged data was cleaned according to the number of valid hours on each night and the number of valid days for each subject. When mode = 4, the cleaned data was imputed.
useIDs.FN	character Filename with or without directory for sample information in CSV format, which including "filename" and "duplicate" in the headlines at least. If duplicate="remove", the accelerometer files will not be used in the data analysis of part 5-7. Default is NULL, which makes all accelerometer files will be used in part 5-7.
currentdir	character Directory where the output needs to be stored. Note that this directory must exist.
studyname	character Specify the study name that used in the output file names
bindir	character Directory where the accelerometer files are stored or list
outputdir	character Directory where the GGIR output was stored.
epochIn	number Epoch size to which acceleration was averaged (seconds) in GGIR output. Default is 5 seconds.
epochOut	number Epoch size to which acceleration was averaged (seconds) in part1. Default is 5 seconds.
flag.epochOut	number Epoch size to which acceleration was averaged (seconds) in part 3. Default is 60 seconds.
log.multiplier	number The coefficient used in the log transformation of the ENMO data, i.e. $\log(\log.multiplier * ENMO + 1)$, which have been used in part 5-7. Default is 9250.
use.cluster	logical Specify if part1 will be done by parallel computing. Default is TRUE, and the CSV file in GGIR output will be merged for every 20 files first, and then combined for all.
QCdays.alpha	number Minimum required number of valid days in subject specific analysis as a quality control step in part2. Default is 7 days.
QChours.alpha	number Minimum required number of valid hours in day specific analysis as a quality control step in part2. Default is 16 hours.
QCnights.feature.alpha	number Minimum required number of valid nights in day specific mean and SD analysis as a quality control step in the JIVE analysis. Default is c(0,0), i.e. no additional data cleaning in this step.
Rversion	character R version, eg. "R/3.6.3". Default is "R".
filename2id	R function User defined function for converting filename to sample IDs. Default is NULL.
PA.threshold	number Threshold for light, moderate and vigorous physical activity. Default is c(50,100,400).

desiredtz	character desired timezone: see also http://en.wikipedia.org/wiki/Zone.tab . Used in <code>g.inspectfile()</code> . Default is "US/Eastern".
RemoveDaySleeper	logical Specify if the daysleeper nights are removed from the calculation of number of valid days for each subject. Default is FALSE.
trace	logical Specify if the intermediate results is printed when the function was executed. Default is FALSE.

Value

See postGGIR manual for details.

create.postGGIR	<i>Create a template shell script of postGGIR</i>
-----------------	---

Description

Create a template shell script of postGGIR, named as STUDYNAME_part0.maincall.R.

Usage

```
create.postGGIR()
```

Value

The function will create a template shell script of postGGIR in the current directory, names as STUDYNAME_part0.maincall.R

data.imputation	<i>Data imputation for the cleaned data with annotation</i>
-----------------	---

Description

Data imputation for the merged ENMO data with annotation. The missing values were imputed by the average ENMO over all the valid days for each subject.

Usage

```
data.imputation(workdir, csvInput)
```

Arguments

workdir	character Directory where the output needs to be stored. Note that this directory must exist.
csvInput	character File name with or without directory for sample information in CSV format. The ENMO data will be read through read.csv(csvInput,header=1) command, and the missing values were imputed by the average ENMO over all the valid days for each subject at each time point. In this package, csvInput = flag_All_studyname_ENMO.data.Xs.csv.

Value

Files were written to the specified sub-directory, named as impu.flag_All_studyname_ENMO.data.Xs.csv, which Xs is the epoch size to which acceleration was averaged (seconds) in GGIR output. This excel file includes the following columns,

filename	accelerometer file name
Date	date recored from the GGIR part2.summary file
id	IDs recored from the GGIR part2.summary file
calender_date	date in the format of yyyy-mm-dd
N.valid.hours	number of hours with valid data recored from the part2_daysummary.csv file in the GGIR output
N.hours	number of hours of measurement recored from the part2_daysummary.csv file in the GGIR output
weekday	day of the week-Day of the week
measurementday	day of measurement-Day number relative to start of the measurement
newID	new IDs defined as the user-defined function of filename2id(), e.g. substrings of the filename
Nmiss_c9_c31	number of NAs from the 9th to 31th column in the part2_daysummary.csv file in the GGIR output
missing	"M" indicates missing for an invalid day, and "C" indicates completeness for a valid day
Ndays	number of days of measurement
ith_day	rank of the measurementday, for example, the value is 1,2,3,4,-3,-2,-1 for measurementday = 1,...,7
Nmiss	number of missing (invalid) days
Nnonmiss	number of non-missing (valid) days
misspattern	indicators of missing/nonmissing for all measurement days at the subject level
RowNonWear	number of columnns in the non-wearing matrix
NonWearMin	number of minutes of non-wearing
daysleeper	If 0 then the person is a nightsleeper (sleep period did not overlap with noon) if value=1 then the person is a daysleeper (sleep period did overlap with noon).

remove16h7day	indicator of a key quality control output. If remove16h7day=1, the day need to be removed. If remove16h7day=0, the day need to be kept.
duplicate	If duplicate="remove", the accelerometer files will not be used in the data analysis of part5.
ImpuMiss.b	number of missing values on the ENMO data before imputation
ImpuMiss.a	number of missing values on the ENMO data after imputation
KEEP	The value is "keep"/"remove", e.g. KEEP="remove" if remove16h7day=1 or duplicate="remove" or ImpuMiss.a>0

DataShrink *Annotating the merged data for all accelerometer files in the GGIR output*

Description

Annotating the merged ENMO/ANGLEZ data by adding some descriptive variables such as number of valid days and missing pattern.

Usage

```
DataShrink(
  studyname,
  outputdir,
  workdir,
  QCdays.alpha = 7,
  QChours.alpha = 16,
  summaryFN = "../summary/part24dayssummary.info.csv",
  epochIn = 5,
  epochOut = 60,
  useIDs.FN = NULL,
  RemoveDaySleeper = FALSE,
  trace = FALSE,
  Step = 1
)
```

Arguments

studyname	character Specify the study name that used in the output file names
outputdir	character Directory where the GGIR output was stored.
workdir	character Directory where the output needs to be stored. Note that this directory must exist.
QCdays.alpha	number Minimum required number of valid days in subject specific analysis as a quality control step in part2. Default is 7 days.
QChours.alpha	number Minimum required number of valid hours in day specific analysis as a quality control step in part2. Default is 16 hours.

summaryFN	character Filename with or without directory for sample information in CSV format, which includes summary description of each accelerometer file. Some description will be extracted and merged into the ENMO/ANGLEZ data.
epochIn	number Epoch size to which acceleration was averaged (seconds) in GGIR output. Default is 5 seconds.
epochOut	number Epoch size to which acceleration was averaged (seconds) in part1. Default is 60 seconds.
useIDs.FN	character Filename with or without directory for sample information in CSV format, which includes "filename" and "duplicate" in the headlines at least. If duplicate="remove", the accelerometer files will not be used in the data analysis of part 5-7. Default is NULL, which makes all accelerometer files will be used in part 5-7.
RemoveDaySleeper	logical Specify if the daysleeper nights are removed from the calculation of number of valid days for each subject. Default is FALSE.
trace	logical Specify if the intermediate results is printed when the function was executed. Default is FALSE.
Step	number Specify which of the variable need to be cleaned. For example, Step = 1 for the "anglez" variable, and Step = 2 for the "enmo" variable.

Value

Files were written to the specified sub-directory, named as flag_ALL_studyname_ENMO.data.Xs.csv and flag_ALL_studyname_ANGLEZ.data.Xs.csv, which Xs is the epoch size to which acceleration was averaged (seconds) in GGIR output. This excel file includes the following columns,

filename	accelerometer file name
Date	date recored from the GGIR part2.summary file
id	IDs recored from the GGIR part2.summary file
calender_date	date in the format of yyyy-mm-dd
N.valid.hours	number of hours with valid data recored from the part2_daysummary.csv file in the GGIR output
N.hours	number of hours of measurement recored from the part2_daysummary.csv file in the GGIR output
weekday	day of the week-Day of the week
measurementday	day of measurement-Day number relative to start of the measurement
newID	new IDs defined as the user-defined function of filename2id(), e.g. substrings of the filename
Nmiss_c9_c31	number of NAs from the 9th to 31th column in the part2_daysummary.csv file in the GGIR output
missing	"M" indicates missing for an invalid day, and "C" indicates completeness for a valid day
Ndays	number of days of measurement

ith_day	rank of the measurementday, for example, the value is 1,2,3,4,-3,-2,-1 for measurementday = 1,...,7
Nmiss	number of missing (invalid) days
Nnonmiss	number of non-missing (valid) days
misspattern	indicators of missing/nonmissing for all measurement days at the subject level
RowNonWear	number of columns in the non-wearing matrix
NonWearMin	number of minutes of non-wearing
Nvalid.day	number of valid days with/without removing daysleeper nights; It is equal to Nnonmiss when RemoveDaySleeper=FALSE.
daysleeper	If 0 then the person is a nightsleeper (sleep period did not overlap with noon) if value=1 then the person is a daysleeper (sleep period did overlap with noon).
remove16h7day	indicator of a key quality control output. If remove16h7day=1, the day need to be removed. If remove16h7day=0, the day need to be kept.
duplicate	If duplicate="remove", the accelerometer files will not be used in the data analysis of part5-7.

ExtCos2

*Extended Cosinor Model for Circadian Rhythmicity***Description**

A parametric approach to study circadian rhythmicity assuming cosinor shape. Here we used the anti logistic transformed cosine curves, which provided 5 parameters.

Usage

```
ExtCos2(x, logtransform = TRUE)
```

Arguments

x	vector vector of dimension n*1440 which represents n days of 1440 minute activity data
logtransform	Conduct log transformation before. Default is TRUE.

Value

A list with elements

min	minimum
amp	amplitude
alpha	alpha parameter:determines whether the peaks of the curve are wider than the troughs
beta	beta parameter: determines whether the function rises and falls more steeply than the cosine curve
acro	acrophase
F_imp	pseudo-F statistics

ExtCos_long2	<i>Extended Cosinor Model for Circadian Rhythmicity for Whole Dataset</i>
--------------	---

Description

A parametric approach to study circadian rhythmicity assuming cosinor shape. Here we used the anti logistic transformed cosine curves, which provided 5 parameters. This function is a wrapper for ExtCos.

Usage

```
ExtCos_long2(count.data, logtransform = TRUE)
```

Arguments

count.data	data.frame of dimension n*1442 containing the 1440 minute activity data for all n subject days. The first two columns have to be ID and Day.
logtransform	Conduct log transformation before. Default is TRUE.

Value

A data.frame with following columns

ID	identifier of the person
min	minimum
amp	amplitude
alpha	alpha parameter
beta	beta parameter
acro	acrophase
F_imp	pseudo-F statistics

fragmentation2	<i>Fragmentation Metrics</i>
----------------	------------------------------

Description

Fragmentation methods to study the transition between two states, e.g. sedentary v.s. active.

Usage

```
fragmentation2(
  x,
  w,
  thresh,
  bout.length = 1,
  metrics = c("mean_bout", "TP", "Gini", "power", "hazard", "all")
)
```

Arguments

x	integer vector of activity data.
w	vector of wear flag data with same dimension as x.
thresh	threshold to binarize the data.
bout.length	minimum duration of defining an active bout; defaults to 1.
metrics	What is the fragmentation metrics to extract. Can be "mean_bout", "TP", "Gini", "power", "hazard", or all the above metrics "all".

Details

Metrics include mean_bout (mean bout duration), TP (between states transition probability), Gini (gini index), power (alpha parameter for power law distribution) hazard (average hazard function)

Value

A list with elements

mean_r	mean sedentary bout duration
mean_a	mean active bout duration
SATP	sedentary to active transition probability
ASTP	bactive to sedentary transition probability
Gini_r	Gini index for active bout
Gini_a	Gini index for sedentary bout
h_r	hazard function for sedentary bout
h_a	hazard function for active bout
alpha_r	power law parameter for sedentary bout
alpha_a	power law parameter for active bout

References

Di et al. Patterns of sedentary and active time accumulation are associated with mortality in US adults: The NHANES study.

fragmentation_long2 *Fragmentation Metrics for Whole Dataset*

Description

Fragmentation methods to study the transition between two states, e.g. sedentary v.s. active. This function is a whole dataset wrapper for fragmentation

Usage

```
fragmentation_long2(
  count.data,
  weartime,
  thresh,
  bout.length = 1,
  metrics = c("mean_bout", "TP", "Gini", "power", "hazard", "all"),
  by = c("day", "subject")
)
```

Arguments

count.data	data.frame of dimension n*1442 containing the 1440 minute activity data for all n subject days. The first two columns have to be ID and Day.
wear.time	data.frame with dimension of count.data. The first two columns have to be ID and Day.
thresh	threshold to binarize the data.
bout.length	minimum duration of defining an active bout; defaults to 1.
metrics	What is the fragmentation metrics to extract. Can be "mean_bout", "TP", "Gini", "power", "hazard", or all the above metrics "all".
by	Determine whether fragmentation is calculated by day or by subjects (i.e. aggregate bouts across days). by-subject is recommended to gain more power.

Details

Metrics include mean_bout (mean bout duration), TP (between states transition probability), Gini (gini index), power (alpha parameter for power law distribution) hazard (average hazard function)

Value

A dataframe with some of the following columns

ID	identifier of the person
Day	indicator of which day of activity it is, can be a numeric vector of sequence 1,2,... or a string of date
mean_r	mean sedentary bout duration
mean_a	mean active bout duration
SATP	sedentary to active transition probability
ASTP	bactive to sedentary transition probability
Gini_r	Gini index for active bout
Gini_a	Gini index for sedentary bout
h_r	hazard function for sedentary bout
h_a	hazard function for active bout
alpha_r	power law parameter for sedentary bout
alpha_a	power law parameter for active bout

ggir.datatransform	<i>Transform the data and merge all accelerometer files in the GGIR output</i>
--------------------	--

Description

An accelerometer file was transformed into wide data matrix, in which the rows represent available days and the columns including all timestamps for 24 hours. Further, the wide data was merged together.

Usage

```
ggir.datatransform(  
  outputdir,  
  subdir,  
  studyname,  
  numericID = FALSE,  
  sortByid = "newID",  
  f0 = 1,  
  f1 = 1e+06,  
  epochIn = 5,  
  epochOut = 600,  
  mergeVar = 1  
)
```

Arguments

outputdir	character Directory where the GGIR output was stored.
subdir	character Sub-directory where the summary output was stored under the current directory. Default is "data".
studyname	character Specify the study name that used in the output file names
numericID	logical Specify if the ID is numeric when checking ID errors in part2. Default is FALSE.
sortByid	character Specify the name of "ID" for each accelerometer file in the report of part5. The value could be "newID", "id" and "filename". Default is "filename".
f0	number File index to start with (default = 1). Index refers to the filenames sorted in increasing order.
f1	number File index to finish with. Note that file ends with the minimum of f1 and the number of files available. Default = 1000000.
epochIn	number Epoch size to which acceleration was averaged (seconds) in GGIR output. Default is 5 seconds.
epochOut	number Epoch size to which acceleration was averaged (seconds) in part1. Default is 600 seconds.

mergeVar number Specify which of the variable need to be processed and merged. For example, mergeVar = 1 makes that the M\$metalong variables were read from R data on the directory of /meta/basic under GGIR output directory, which includes "nonwearscore", "clippingscore", "lightmean", "lightpeak", "temperaturemean" and "EN". When mergeVar = 2, makes that the "enmo" and "anglez" variables were read from csv data on the directory of /meta/csv under GGIR output directory.

Value

mergeVar = 1 Six files were written to the specified sub-directory as follows,

nonwearscore_studyname_f0_f1_Xs.xlsx
 Data matrix of nonwearscore, where f0 and f1 are the file index to start and finish with and Xs is the epoch size to which acceleration was averaged (seconds) in GGIR output.

clippingscore_studyname_f0_f1_Xs.xlsx
 Data matrix of clippingscore

lightmean_studyname_f0_f1_Xs.xlsx
 Data matrix of lightmean

lightpeak_studyname_f0_f1_Xs.xlsx
 Data matrix of lightpeak

temperaturemean_studyname_f0_f1_Xs.xlsx
 Data matrix of temperaturemean

EN_studyname_f0_f1_Xs.xlsx
 Data matrix of EN

mergeVar = 2 Two files were written to the specified sub-directory as follows,

studyname_ENMO.dataf0_f1_Xs.xlsx
 Data matrix of ENMO, where f0 and f1 are the file index to start and finish with and Xs is the epoch size to which acceleration was averaged (seconds) in GGIR output.

studyname_ANGLEZ.dataf0_f1_Xs.xlsx
 Data matrix of ANGLEZ

ggir.summary

Description of all accelerometer files in the GGIR output

Description

Description of all accelerometer files in the GGIR output and this script was executed when mode=2 in the main call.

Usage

```
ggir.summary(
  bindir = NULL,
  outputdir,
  studyname,
  numericID = FALSE,
  sortByid = "filename",
  subdir = "summary",
  part5FN = "WW_L50M125V500_T5A5",
  QChours.alpha = 16,
  filename2id = NULL,
  desiredtz = "US/Eastern",
  trace = FALSE
)
```

Arguments

bindir	character Directory where the accelerometer files are stored or list for the purpose of extracting the bin file list. Default=NULL when it is not available and therefore the bin file list is extracted from the /meta/basic folder of the GGIR output.
outputdir	character Directory where the GGIR output was stored.
studyname	character Specify the study name that used in the output file names
numericID	logical Specify if the ID is numeric when checking ID errors in part2. Default is FALSE.
sortByid	character Specify the name of "ID" for each accelerometer file in the report of part2. The value could be "newID","id" and "filename". Default is "filename".
subdir	character Sub-directory where the summary output was stored under the current directory. Default is "summary".
part5FN	character Specify which output is used in the GGIR part5 results. Default is "WW_L50M125V500_T5A5", which means that part5_daysummary_WW_L50M125V500_T5A5.csv and part5_personsummary_WW_L50M125V500_T5A5.csv are used in the analysis.
QChours.alpha	number Minimum required number of valid hours in day specific analysis as a quality control step in part2. Default is 16 hours.
filename2id	R function User defined function for converting filename to sample IDs. Default is NULL.
desiredtz	character desired timezone: see also http://en.wikipedia.org/wiki/Zone.tab . Used in g.inspectfile(). Default is "US/Eastern".
trace	logical Specify if the intermediate results is printed when the function was executed. Default is FALSE.

Value

Four files were written to the specified sub-directory

studyname_ggir_output_summary.xlsx	This excel file includes 9 pages as follows,
page 1	List of files in the GGIR output
page 2	Summary of files
page 3	List of duplicate IDs
page 4	ID errors
page 5	Number of valid days
page 6	Table of number of valid/missing days
page 7	Missing patten
page 8	Frequency of the missing pattern
page 9	Description of all accelerometer files
page 10	Inspects accelerometer file for key information, including: monitor brand, sample frequency and file header
studyname_ggir_output_summary_plot.pdf	Some plots such as the number of valid days, which were included in the part2a_studyname_postGGIR.rep file as well.
part24dayssummary.info.csv	Intermediate results for description of each accelerometer file.
studyname_samples_remove_temp.csv	Create studyname_samples_remove.csv file by filling "remove" in the "duplicate" column in this template. If duplicate="remove", the accelerometer files will not be used in the data analysis of part 5-7.

 IS_long2

Interdaily Stability

Description

This function calculate interdaily stability, a nonparametric metric of circadian rhythmicity

Usage

```
IS_long2(count.data, level = "hour")
```

Arguments

count.data	data.frame of dimension p by 1440, representing the p days of activity data for one subject
level	character level="hour" or not

Value

IS

 IV *Intradaily Variability*

Description

This function calculate intradaily variability, a nonparametric metric representing fragmentation of circadian rhythmicity

Usage

IV(x)

Arguments

x vector of dimension 1440 which represents 1440 minute activity data. Or users can bin the data into different resolutions, e.g. 10 minute, 1 hour, etc.

Value

IV

 IV_long2 *Intradaily Variability*

Description

This function calculate intradaily variability, a nonparametric metric representing fragmentation of circadian rhythmicity

Usage

IV_long2(count.data, level = 600)

Arguments

count.data data.frame of dimension n * 1442 containing the 1440 minute activity data for all n subject days.

level character the number of seconds in each window. level= 600 seconds (10 minutes) by default.

Value

IV

jive.predict2	<i>Modified jive.predict function (package: r.jive)</i>
---------------	---

Description

Replace SVDmiss by SVDmiss2 in the function

Usage

```
jive.predict2(data.new, jive.output)
```

Arguments

data.new	data.new A list of two or more linked data matrices on which to estimate JIVE scores. These matrices must have the same column dimension N, which is assumed to be common.
jive.output	jive.output An object of class "jive", with row dimensions matching those for data.new.

Details

See `jive.predict(package:r.jive)` for details.

Value

See `r.jive::jive.predict` for details

pheno.plot	<i>View phenotype variables</i>
------------	---------------------------------

Description

This R script will generate plot for each variable and write description to a log file.

Usage

```
pheno.plot(  
  inputFN,  
  outFN = paste("plot_", inputFN, ".pdf", sep = ""),  
  csv = TRUE,  
  sep = " ",  
  start = 3,  
  read = TRUE,  
  logFN = NULL,  
  track = TRUE  
)
```

Arguments

inputFN	character	Input file name or input data
outFN	character	Output pdf file name for the plots
csv	logical	Specify if input file is a CSV file. Default is TRUE.
sep	character	Separator between columns. Default is space. If csv=TRUE, this will not be used.
start	number	The location of the first phenotype variable starts in the input file.
read	logical	Specify if inputFN is a file name or a data. Default is TRUE when inputFN is a file name.
logFN	character	File name of the log file. Default is NULL, while logFN=paste(inputFN, ".log", sep="") in the function.
track	logical	Specify if the intermediate results is printed when the function was executed. Default is TRUE.

Value

Files were written to the current directory. One is .pdf file for plots and the other is .log file for variable description.

RA2	<i>Relative Amplitude</i>
-----	---------------------------

Description

This function calculate relative amplitude, a nonparametric metric representing fragmentation of circadian rhythmicity

Usage

RA2(x)

Arguments

x	vector	vector of dimension 440 which represents 1440 minute activity data
---	--------	--

Value

RA

RA_long2	<i>Relative Amplitude for Whole Dataset</i>
----------	---

Description

Relative Amplitude is a nonparametric metric representing fragmentation of circadian rhythmicity. this function is a whole data wrapper for RA.

Usage

```
RA_long2(count.data)
```

Arguments

count.data	data.frame of dimension n * 1442 containing the 1440 minute activity data for all n subject days. The first two columns have to be ID and Day.
------------	--

Value

A data.frame with following columns

ID	identifier of the person
Day	indicator of which day of activity it is, can be a numeric vector of sequence 1,2,... or a string of date
RA	RA

#' @importFrom zoo rollapplyr

SVDmiss2	<i>Modified SVDmiss function (package SpatioTemporal)</i>
----------	---

Description

Modify ncomp = min(ncol(X),nrow(X),ncomp) for the matrix with nrow(X)<ncol(X)

Usage

```
SVDmiss2(X, niter = 200, ncomp = dim(X)[2], conv.reldiff = 0.001)
```

Arguments

X	X Data matrix, with missing values marked by 'NA'.
niter	niter Maximum number of iterations to run before exiting, 'Inf' will run until the 'conv.reldiff' criteria is met.
ncomp	ncomp Number of SVD components to use in the reconstruction (>0).
conv.reldiff	conv.reldiff Assume the iterative procedure has converged when the relative difference between two consecutive iterations is less than 'conv.reldiff'.

Details

See `SVDmiss(package:SpatioTemporal)` for details.

Value

See `SpatioTemporal::SVDmiss` for details

Time2	<i>Time of A Certain activity State</i>
-------	---

Description

Calculate the total time of being in certain state, e.g. sedentary, active, MVPA, etc.

Usage

```
Time2(x, w, thresh, smallerthan = TRUE, bout.length = 1)
```

Arguments

x	vector of activity data.
w	vector of wear flag data with same dimension as x.
thresh	threshold to binarize the data.
smallerthan	Find a state that is smaller than a threshold, or greater than or equal to.
bout.length	minimum duration of defining an active bout; defaults to 1.

Value

Time

Time_long2	<i>Timne Metrics for Whole Dataset</i>
------------	--

Description

This function is a whole dataset wrapper for Time

Usage

```
Time_long2(count.data, weartime, thresh, smallerthan = TRUE, bout.length = 1)
```

Arguments

<code>count.data</code>	<code>data.frame</code> of dimension $n*1442$ containing the 1440 minute activity data for all n subject days. The first two columns have to be ID and Day.
<code>wear.time</code>	<code>data.frame</code> with dimension of <code>count.data</code> . The first two columns have to be ID and Day.
<code>thresh</code>	threshold to binarize the data.
<code>smallerthan</code>	Find a state that is smaller than a threshold, or greater than or equal to.
<code>bout.length</code>	minimum duration of defining an active bout; defaults to 1.

Value

A dataframe with some of the following columns

ID	identifier of the person
Day	indicator of which day of activity it is, can be a numeric vector of sequence 1,2,... or a string of date
time	time of certain state

Tvol2

Total Volumen of Activity for Whole Dataset

Description

Calculate total volume of activity level, which includes TLAC (total log transformed activity counts), TAC (total activity counts).

Usage

```
Tvol2(count.data, wear.time, logtransform = FALSE, log.multiplier = 9250)
```

Arguments

<code>count.data</code>	<code>data.frame</code> of dimension $n*1442$ containing the 1440 minute activity data for all n subject days. The first two columns have to be ID and Day.
<code>wear.time</code>	<code>data.frame</code> with dimension of <code>count.data</code> . The first two columns have to be ID and Day.
<code>logtransform</code>	if TRUE, then calculate TLAC. Or calculate TAC.
<code>log.multiplier</code>	number The coefficient used in the log transformation of the ENMO data, i.e. $\log(\log.multiplier * ENMO + 1)$. Default is 9250.

Details

log transformation is defined as $\log(x+1)$.

Value

A dataframe with some of the following columns

ID	identifier of the person
Day	indicator of which day of activity it is, can be a numeric vector of sequence 1,2,... or a string of date
TAC	total activity count
TLAC	total log activity count

wear_flag	<i>Create Wear/Nonwear Flags</i>
-----------	----------------------------------

Description

Determine during which time period, subject should wear the device. It is preferable that user provide their own wear/non wear flag which should has the same dimension as the activity data. This function provide wear/non wear flag based on time of day.

Usage

```
wear_flag(count.data, start = "05:00", end = "23:00")
```

Arguments

count.data	data.frame of dimension n*1442 containing the 1440 minute activity data for all n subject days. The first two columns have to be ID and Day.
start	start time, a string in the format of 24hr, e.g. "05:00"; defaults to "05:00".
end	end time, a string in the format of 24hr, e.g. "23:00"; defaults to "23:00"

Details

Some of the features can be only calculated at certain time period. For example, fragmentation metrics are usually defined when subject is awake. The `wear_time` provide time periods on which those features should be extracted. This can be also used as indication of wake/sleep.

Value

A data.frame with same dimension and column name as the `count.data`, with 0/1 as the elements representing wear, nonwear respectively.

Index

ActCosinor, [2](#)
afterggir, [3](#)

create.postGGIR, [5](#)

data.imputation, [5](#)
DataShrink, [7](#)

ExtCos2, [9](#)
ExtCos_long2, [10](#)

fragmentation2, [10](#)
fragmentation_long2, [11](#)

ggir.datatransform, [13](#)
ggir.summary, [14](#)

IS_long2, [16](#)
IV, [17](#)
IV_long2, [17](#)

jive.predict2, [18](#)

pheno.plot, [18](#)

RA2, [19](#)
RA_long2, [20](#)

SVDmiss2, [20](#)

Time2, [21](#)
Time_long2, [21](#)
Tvol2, [22](#)

wear_flag, [23](#)